

1 ORDER OF OPERATIONS

Enumerate: What type of system is this? (`cat /etc/os-release` to see distribution/version). What users are on the system? What services are running? What ports are open? `ss -tulnp` lists listening tcp/udp ports with owning process. Run `linpeas.sh` early to see what a red teamer would find first (SUID/SGID binaries, weak perms, writable cron jobs, creds in files/history) and fix what it flags.

Firewall: Install UFW. `sudo ufw allow ssh`. Allow other required services: For Jenkins: `allow 8080/tcp`; For OpenVPN: `allow 1194/udp`; For web servers: `allow 443/tcp`.

User Management: List users: (look for users with shells/hashes). `sudo cat /etc/passwd` and `sudo cat /etc/shadow`. Expire unneeded. Change passwords.

Verify Packages: Debian: `sudo dpkg --verify`. RHEL: `sudo rpm -Va`.

Update Packages: Debian: `apt update && apt upgrade -y`. RHEL: `apt = yum (dnf on Fedora)`.

Secure service: Check configuration. Manage users (if applicable).

Install and Configure Auditd: Monitor and defend. Watch logs. Keep looking for badness.

Deny red team tooling: Strip interpreters/compilers/relay tools a scored service does not use (see below).

2 USERS

useradd [name]: Creates a user account.

- `-m`: Creates a home folder for the user.

passwd [user]: Change a user's password.

chpasswd: Batch update passwords (format: `user:pass`).

- *Direct usage:* Run `sudo chpasswd`, type list, press `Ctrl+D` to save changes.

- *File usage:* `sudo chpasswd < list.txt`

usermod [user]: Modify a user account.

- `-aG [group]`: Add user to a group (e.g., `sudo/wheel`).
- `--expiredate 1`: Completely disable the account.
- `--expiredate 2030-01-01`: Reactivate expired account.

su [user]: Switch user. `sudo su =` become root.

find / -name authorized_keys: Find allowed SSH keys.

who -a: Show logged in users, session PIDs, and remote IPs.

3 NETWORKING

ip a: List all network interfaces and their addresses.

netstat: Print network connections and routing tables.

- `-tulnp`: Show listening tcp/udp ports and processes.
- `-tupan`: Show listening and outbound connections.

ufw: Uncomplicated firewall.

- *Setup:* `sudo apt install ufw -y`, `sudo ufw allow ssh`, `sudo ufw enable`.
- *Allow port:* `sudo ufw allow port/protocol`.
- *Examples:* `sudo ufw allow 443/tcp`, `sudo ufw allow 53/udp`.

firewalld (RHEL/CentOS/Fedora):

- *Status:* `firewall-cmd --state`
- *Allow Service:* `firewall-cmd --permanent --add-service=http`
- *Allow Port:* `firewall-cmd --permanent --add-port=8080/tcp`
- *Apply:* `firewall-cmd --reload`
- *List Rules:* `firewall-cmd --list-all`

nmap [host(s)]: Network scanner.

Example: `nmap -A 10.0.10.0-255` (OS, Service, Scan).

nmap (Local Scan):

- `nmap -sV 10.0.10.0/24`: Scan local subnet for service versions.
- `nmap -A [host]`: OS detection, service version, script scanning.
- `nmap -p- [host]`: Scan all 65535 ports.

4 FILE PERMISSIONS

chown [user] [file]: Change the owner of a file.

chmod: Change file permissions.

- *Symbolic:* `u=User/Owner`, `g=Group`, `o=Other`, `a=All`, `r=read`, `w=write`, `x=execute`
- *Numeric:* `1=execute`, `2=write`, `4=read`.
- *Example:* `chmod 740 file` (Owner=7=rwx, Group=4=r, Other=0=—).
- *Example:* `chmod a+x file` (Give everyone execute).

5 IMPORTANT FILES

`/etc/passwd:` List of all users.

`/etc/shadow:` List of user password hashes.

`/etc/sudoers` & `/etc/sudoers.d:` Defines sudo permissions. `ALL ALL=(ALL) ALL` means all users can use sudo. Use `visudo` to edit.

`/etc/group:` Lists all groups and their members.

`/var/log/auth.log` & `/var/log/syslog:` Auth and system logs.

tail -f [file]: Watch log for new events in real-time.

6 AUDITD, AUREPORT, AUSEARCH

Setup: `sudo apt install auditd, curl -O [rules]`, `mv` to `/etc/audit/rules.d/`, `sudo service auditd restart`.

aureport -i: Reports info on audit logs.

- `-x --summary`: Show run counts for executables (Check for malware).
- `-au:` Authentication attempts. `-u:` User commands.
- `-h:` Connected hosts. `-f --summary`: Files opened.
- `-tm:` Terminals used. `-m:` User modifications.

ausearch -i: Search the audit logs.

- `-k [key]:` Search by event key (`rootcmd`, `susp_activity`).
- `-p [pid]:` Events related to a specific process ID.
- `-m [type]:` Message type (`LOGIN`, `EXECVE`, `ADD_USER`).

7 SYSTEMD & CRON

systemctl: Manage system services.

- `list-units --type=service`: List all services.
 - `enable/disable/restart [srv]`: Persistence/state.
 - `status [srv]`: Show if service is active or failed.
- `/etc/systemd/:` Look for weird unit files in `system/user` dirs; disable if bad.

Cron: Command scheduler. Remove unauthorized entries.

- *Root crontabs:* `/etc/crontab`, `/etc/cron.d/`.

- *User crontabs:* `/var/spool/cron/`.

8 DENY RED TEAM TOOLING

Most of red team's toolkit depends on what's already sitting on the box. Confirm nothing scored needs an item, then remove it and log the change.

- **Python:** Ansible's default connection plugin needs a Python interpreter on the managed node; most red team post-ex/staging scripts assume one too. `apt remove --purge python3` (or `chmod 000` the binary + `apt-mark hold python3`) breaks both.

- **Perl, Ruby, other unused interpreters:** same idea, lower prevalence.

- **Compilers (gcc, cc, make, build-essential):** rarely needed at runtime. Blocks on-box compilation of an exploit or implant.

- **netcat/ncat/socat, if unused:** the default pivot/reverse-shell relay. Check startup scripts and cron first.

- **SSH client (not server) on hosts that never SSH out:** removes a lateral-movement path, leaves inbound access alone.

- `find / -perm -4000 -o -perm -2000 2>/dev/null:` SUID/SGID binaries vs. a known-good list; an unexpected one is a ready-made LOLBin.

9 MALWARE: YARA & CLAMAV

Yara: Malware classification tool.

- *Setup:* `sudo apt install yara -y`, `git clone [rules]`.
- *Usage:* `yara [rules] [target] [-r] -w`.
- *Ex:* `yara rules/malware_index.yar / -r` (Full scan).

ClamAV: `apt install clamav`.

- `freshclam:` Update signature database.
- `clamscan:` Run a scan (may fail on low memory).

10 PROCESSES & THREAT HUNTING

ps -aux: List all running processes.

top: Live resource usage.

kill [**pid**]: Kill a process.

killall [**name**]: Kill all by name (e.g. `killall perl`).

Everything in Linux is a file (`/proc/[pid]/`):

- **cwd**: Current working dir of process.
- **cmdline**: Arguments used to run the program.
- **exe**: The executable (even if deleted from disk).
- **environ**: Environment variables (look for **USER**).

11 AWS NACLs & SECURITY GROUPS

AWS NACLs: Enable GuardDuty + CloudTrail.
Check S3 perms and IAM roles. Check EC2 IAM roles.
Setup SGs for RDS/Lambda.

AWS Security Groups: Stateful. Only allow ssh and required services in. Only allow https and dns out. Disallow all outbound after updates.

12 SSHD & PAM

Config: `/etc/ssh/sshd.config` (Check `.d/*.conf` overrides).

- **AllowUsers** `user1 user2`: Limit login access.
- **PermitRootLogin** `no`: Disable root SSH.
- **PermitEmptyPasswords** `no`: Require passwords for all logins.

PAM: Config `/etc/pam.conf`, `/etc/pam.d`.

- Check configs for ssh, su. `dpkg -V` catches changes.
- Look for “**sufficient**”: Verify if module called is legitimate.
- *Complexity*: `minlen=8, dcredit=-1, enforce_for_root.`