

Outline:

This report is aimed at building a binary classification algorithm by using Logistic regression and KNN. The dataset was from Fashion-MNIST, where containing 60,000 examples in training set and 10,000 examples in test set. Each example is a 28 x 28 single channel grayscale images, associated with label from one of ten classes.

It is required to extract only 2 labels for this binary classification task. 'Sandal' and 'Sneaker', where 'Sandal' is set to be positive class ($Y=1$).

Deliverables:


D1: Summarising the dataset:

- Answer:

	Total
The number of instances in Training:	11988
The number of instances in Test :	2000
The total number of instances :	13988


D2: Provide a bar plot showing the number of instances for each class.

- Answer: As figure 1 shows, we have a perfectly balanced training set.




D3: Plot the first six images from each class with the corresponding example id and label listed.

- Answer : Figure 2.




D4: Fitting my own implementation of logistic regression with neg log loss / binary cross entropy as cost function. Experience with different learning rate (η) in gradient descent.

- Answer: As shown in Figure 3, different learning rate affect the gradient descent distinctively. With a high $\eta = 0.01$, the cost is jumping around and not able to achieve global minimum, where the low $\eta = 0.00001$ showing a very slow reduction, and may need more than 10,000 iterations. The $\eta=0.0001$ is acceptable, showing a very fast convergence but if the iteration is more than 2,000, it will start to bouncing. With $\eta=0.0001$ to be the most stable learning rate in 10,000 iterations.



D5. Set $\eta = 0.00001$, providing side by side plot, showing the cost (y-axis) for each iteration (x-axis) for the training and validation set. The right plot showing the fraction of misclassification (y-axis) for each iteration (x-axis).

- Answer : Figure 4,




D6. Interpretation of Figure 4.

- Answer: As shown in figure 4, both the costs of training and validation are showing decreases along with the increases of the iterations. However clearly the cost on the validation set start to be constantly higher than the training cost, from around 1000 iteration mark. Meaning the model perform better on the training set but not as good as on the validation set. The model may have overfitting issue with high variance. If we increase the bias, the model may generalize better.

D7. Incorporate a L2 regularisation in the model.

- Answer : Figure 5. Provide side by side plots showing the value of cost function for each C value, and the fraction of misclassifications for each C value.

*Here we define: $C_range = np.logspace(-10, 5, 30)$



- Discussion:
In order to be comparable with the C hyperparameters from Sklearn packages for all the following deliverables. Here C is defined as "Inverse of regularization strength". [Sklearn](#)
As we can see from the plot above, the small C has imposed a very strong regularization on the model, where reduced all the weights to nearly 0 (not equal to 0 like lasso regression). Therefore leading to the high loss, and the 50% misclassification rate as the model is predicting every instance to $Y=0$, sneakers.
- Extra discussion (not required in deliverables)

In the usual L2 norm regression mathematic equation, the α , or sometimes λ , is a constant that multiply the regularization term, the higher the value, the stronger the regularization.

○ Cost function with L2 norm = cost + $\alpha \sum_{i=1}^n \theta_i^2$

But the C defined in SKLearn documentation. The hyperparameter has been added onto the log loss cost function. Hence the inverse effect.

As an optimization problem, binary class logistic regression with regularization term $r(w)$ minimizes the following cost function:

(1)

$$\min_w C \sum_{i=1}^n s_i (-y_i \log(\hat{p}(X_i)) - (1 - y_i) \log(1 - \hat{p}(X_i))) + r(w),$$

where s_i corresponds to the weights assigned by the user to a specific training sample (the vector s is formed by element-wise multiplication of the class weights and sample weights).


We currently provide four choices for the regularization term $r(w)$ via the `penalty` argument:

penalty	$r(w)$
None	0
ℓ_1	$\ w\ _1$
ℓ_2	$\frac{1}{2} \ w\ _2^2 = \frac{1}{2} w^T w$
ElasticNet	$\frac{1-\rho}{2} w^T w + \rho \ w\ _1$

○


Therefore it is a bit unclear where the task requirement stated as : "Your task is to select an optimal value for the regularisation hyperparameter C (the hyperparameter α in the textbook) ".

I have further provided a following figure 5 (a), where showing the effect of α for my logistic regression.




As we can see the large alpha leads to heavy penalization, same effects with the small C as above.

The following figure 5 (b), is by using SKLearn logistic regression, where showing the effect of C on training and validation set.



D8. Incorporate a L2 regularisation with Cross Validation, by using `sklearn.linear_model.LogisticRegressionCV`

- Answer: Figure 6.



D9: Conclusion:

- Answer: Comparing between Figure 6 (with cross-validation) and Figure 5 and 5(b) (without cross-validation), The optimal C value shifted to a larger value, I would choose the C value after the cross validation as indicated above in the figure 6. The cost and misclassification rate are slightly improved. The average of all 10 folds of cross-validations on each C, would yield a better result. For the fixed validation set, the C may only be optimal for that particular training set - validation split, may not be optimised for generalization.

D10: Using SGDClassifier together with GridSearchCV to find the optimal regularisation parameter and learning rate.

- According to grid search:
*again here, SGDClassifier using α not C as hyperparameters, so conversion has been conducted and recorded in the Jupyternote book clearly.


The optimal value of α (from SGDClassifier with GridSearchCV):	18.453589348268654
Conversion into hyperparameter C:	4.520353656360249e-06 (same with annotated in fig.6 when using logisticRegCV)
The value of cost function in the training set for this optimal value:	0.09656777383905067
The value of cost function in the test set for this optimal value:	0.10285665156767708
The fraction of misclassifications in the training set:	0.034932221063607924
The fraction of misclassifications in the validation set:	0.03544620517097581

D11: Give a short interpretation of above result comparing with obtained in task D8.

- Answer: Comparing with D8 using the logisticRegressionCV, the grid search combining with SGDClassifier has returned an exact same optimal C value, in a form of α before conversion, as well as an optimal learning rate.
- Both the cost and misclassification fraction on validation set have improved slightly in Gridsearch CV. The grid search has yield the best performance on the validation set in all the previous attempts.

D12: Train the model with optimal C, plot precision vs recall.

- Answer



- Comment:
 - As we can see, when threshold is 0, the model predicts all the instances as Sandals (Class 1). Therefore, the recall is 1, It has predicted all the true Sandals as Sandales, where precision is 50%, as our relatively balanced dataset, all the Sneakers got predicted incorrectly. Similarly, when threshold is approaching to 1, the model predict has no false positive prediction, hence precision is 1, but false negative would be very high.
 - The red line indicates a 0.5 standard threshold, the figure shows if we choose 0.5, we could have higher precision than recall, meaning more false negative, less false positive, If model return the predicted class as 1 Sandales, less likely it is incorrect. But if model predict class as 0 Sneakers, more likely it should be Sandales instead.

- I would choose a threshold between 0.4 and 0.5 to reach a balance of predicting both class correctly, no bias to Sandals or Sneakers.


D13: Find and report the optimal threshold, comment comparing with reflection in D12.

- Answer:
Optimal threshold : 0.42779265
Fscore: 0.9608985

Comparing with D12, this optimal threshold falling between 0.4 and 0.5, which agrees my previous choice, however in the real life scenario, the optimal threshold may be determined case by case, on the different task objectives and the main goal to achieve. (e.g. Spam email classification vs Cancer detection)

D14: Analysing the performance closer, provide model performance on the test set for LR1, LR2, LR3, LR4.

- Answer: Figure 8.



D15. Conclusion:¶

- Answer: From above table and figure 8 Confusion matrix, we can see the LR1 model without penalisation generalize the worst on the testing set. Both LR2, and LR3 are quite similar with L2 norm penalisation implemented, in order to improved the model and distinctively reduced FP and FN.
- The LR4 has more balanced result. based on the best F1 score to pick the optimal threshold.

D16. Consider LR4 and show 5 images from FP and FN on the test set.

- Answer. Figure 9(a) and 9(b).

First 6 False Positive images on the test set, classified as Sandals but should be Sneakers




Figure 9 (a)

First 6 False Negative images on the test set, classified as Sneakers but should be Sandals



Figure 9 (b)

D17. Comment:

- Answer: The first 6 False Positive images show quite uniformed pixels, where model may not able to distinguish the class. The pixels have very low contract, however the Adidas sneakers maybe falsely classified as sandal straps.
- The second 6 False Negative images shows quite clustered pixels, where may more looks like sneakers rather than sandals. Even with human eyes it is a bit hard to tell a definite answer.

D18. Plot the LR4 estimated weights:

- Answer. Figure 10.





Figure 10

D19. Comment:

- Answer: The model LR4 has stronger weights around the front of the shoes, if the shoes with enclosed front it may be a good indication to be sneakers, rather than sandals where it is more likely to be open at front.

D20. K-NN, plot showing the fraction of misclassification for each K.

- Answer: Figure 11.



D21. Comment:

- Answer: with the increase of the K, the model misclassification rate increase accordingly. It is interesting to see the model perform better on the K being a odd number, compared to even number K. It is usually not recommended the choose K = 1 due to the high likelihood being overfitting, but based on this training and validation set, K=1 perform the best on the validation set. Comparing with the logistic regression in section 4.2, KNN perform also quite well with the mis classification rate being around 0.05. similar to the logistic regression.