




Qualcomm Technologies, Inc.



DragonBoard™ 410c based on Qualcomm® Snapdragon™ 410E processor

Android Display Overview

September 2016

© 2015-2016 Qualcomm Technologies, Inc. All rights reserved.

MSM and Qualcomm Snapdragon are products of Qualcomm Technologies, Inc. Other Qualcomm products referenced herein are products of Qualcomm Technologies, Inc. or its other subsidiaries.

DragonBoard, MSM, Qualcomm and Snapdragon are trademarks of Qualcomm Incorporated, registered in the United States and other countries. Other product and brand names may be trademarks or registered trademarks of their respective owners.

This technical data may be subject to U.S. and international export, re-export, or transfer ("export") laws. Diversion contrary to U.S. and international law is strictly prohibited.

Use of this document is subject to the license set forth in Exhibit 1.

Questions or comments: <https://www.96boards.org/DragonBoard410c/forum>

Qualcomm Technologies, Inc.
5775 Morehouse Drive
San Diego, CA 92121
U.S.A.

LM80-P0436-10 Rev D

Revision history

Revision	Date	Description
D	September 2016	Update to 'E' part.
C	June 12, 2015	Miscellaneous updates
B	May 22, 2015	Updated Revision history and © date for Rev B.
A	May 6, 2015	Initial release

Contents

1 Introduction	5
1.1 Purpose	5
1.2 Scope.....	5
1.3 Display hardware in APQ8016E Android	5
1.4 Display driver in APQ8016E Android	6
1.5 Acronyms, abbreviations, and terms.....	6
1.6 Additional information	7
2 System Architecture	8
2.1 MDSS 1.0 multimedia display subsystem overview	8
3 Feature Overview	12
3.1 Supported interfaces.....	12
4 Display and Video Processing Features	15
5 APQ8016E Display Features	16
6 Software Architecture	17
6.1 Android display subsystem	17
6.2 Composition	17
6.3 MDSS driver software block diagram.....	18
7 Source Code Layout	20
7.1 Software directory structure (userspace)	20
7.2 Software directory structure (driver).....	20
8 Software Interface Structure (Userspace and Driver)	21
8.1 Support for standard IOCTLs ofAndroid.....	21
8.2 Qualcomm added IOCTLs	21
EXHIBIT 1.....	22

Figures

Figure 2-1 Display peripheral	9
Figure 2-2 MIPI DSI	10
Figure 2-3 DSI interface	11
Figure 3-1 Display over WiFi.....	14
Figure 6-1 3D core overlay engine 2D core	17
Figure 6-2 MDSS driver architecture.....	19

Tables

Table 1-1 Acronyms, abbreviations, and terms6

Table 3-1 Source Surface Processor Pipes (SSPP)12

Table 3-2 Layer mixer, BG color, and hardware cursor.....13

Table 3-3 Destination Surface Processor Pipes (DSPP).....13

Table 3-4 Rotator and WB13

Table 3-5 Wireless display14

Table 4-1 Scaling15

Table 5-1 Performance16

Table 5-2 Image processing.....16

1 Introduction

1.1 Purpose

This document will familiarize you with the Qualcomm® Snapdragon™ 410E (APQ8016E) Linux Android™ display, including:

- Distinction between display-related hardware and software components.
- Display capabilities and performance benefits of the Multimedia Display Sub-System (MDSS).
- Control flow and data flow.
- Basic information on source code layout, build, and debugging.

1.2 Scope

This document provides an introduction to the Android display driver on the Qualcomm Technologies, Inc. APQ ASICs. This document is applicable to:

- Chipset – Snapdragon 410E (APQ8016E) processor
- Platform – Linux/Android

1.3 Display hardware in APQ8016E Android

- Provides hardware-accelerated image processing using MDSS architecture.
 - Up to four parallel processing pipes, two RGB pipes, one YUV pipe, and one DMA pipe.
 - Supports various image processing for each video and graphics surface.
- Kicks off image data to display interface.
 - MIPI DSI (in default use case Bridge chip ADV7533BCBZ converts DSI to HDMI).
 - Multiple mixers allows simultaneous update to primary and WFD.
- Enhances the image quality on the screen.
 - Post processing and color correction.
 - Panel calibration.

1.4 Display driver in APQ8016E Android

- Provides the optimized interface to access the hardware.
 - SurfaceFlinger, Hardware Composer (HWC), and overlay
 - Framebuffer driver
 - MIPI DSI interface

1.5 Acronyms, abbreviations, and terms

Table 1-1 provides definitions for the acronyms, abbreviations, and terms used in this document.

Table 1-1 Acronyms, abbreviations, and terms

Term	Definition
ABGR	Alpha Blue Green Red
API	Application Programming Interface
APQ	Application Processor Qualcomm
ARGB	Alpha Red Green Blue
BG	Blue Green
BGR	Blue Green Red
BGRA	Blue Green Red Alpha
CABL	Content Adaptive Backlight
CAF	C++ Actor Framework
DMA	Direct Memory Access
DSI	Display Serial Interface
DSP	Destination Surface Processor
DSPP	Destination Surface Processor Pipes
HAL	Hardware Abstraction Layer
HDMI	High Definition Multimedia Interface
HWC	Hardware Composer
IOCTL	Input/Output Control
LM	Layer Mixer
LUT	Look-Up Table
MDP	Mobile Development Platforms
MDSS	Multimedia Display Sub-System
MIPI	Mobile Industry Processor Interface
MSM	Mobile Station Modem
PCMN	Phase control M/N
RGB	Red Green Blue
RGBA	Red Green Blue Alpha
SMP	Simple Management Protocol
SSPP	Source Surface Processor Pipes

Term	Definition
SVI	Sunlight Visibility Improvement
WB	Wide Band
WFD	Wi-Fi Display

1.6 Additional information

For additional information, go to <http://www.96boards.org/db410c-getting-started/>.

2 System Architecture

2.1 MDSS 1.0 multimedia display subsystem overview

- Source Surface Processor (ViG, RGB, DMA - SSPP)
 - Format conversion and quality improvement for source surfaces (video, graphics, etc.)
- Layer Mixer (LM)
 - Blend and mix source surface together
- Destination Surface Processor (DSPP)
 - Conversion, correction, and adjustment based on panel characteristics
- Write-Back/Rotation (WB)
 - Write back to memory
 - Perform rotation if required
- Display interface
 - Timing generator and interface connecting the display peripheral




Figure 2-1 Display peripheral




Figure 2-2 MIPI DSI




Figure 2-3 DSI interface

- The DSI controller is implemented to support the MIPI Alliance Standard for Display Serial Interface (DSI).
- The DSI controller includes one high-speed clock lane and one or more data lanes. Each lane is carried on two wires and uses low-voltage differential signaling.
- There are two modes of operations for DSI-compliant peripherals: Command mode and Video mode

3 Feature Overview

3.1 Supported interfaces

APQ8016E supports up to two concurrent displays:

- DSI up to 1200 x 800 @ 60 fps (in default use case Bridge chip ADV7533BCBZ converts DSI to HDMI)
- Wi-Fi display 1280 x 720 @ 30 fps

Table 3-1 Source Surface Processor Pipes (SSPP)

Feature	ViG	RGB	DMA
Number of pipes	1	2	1
	<ul style="list-style-type: none"> ■ 2s4-bit RGB (888) ■ 16-bit RGB (565) ■ 16-bit x/ARGB (4444,1555) ■ 32-bit x/ARGB (8888) (with ARGB/RGBA/ABGR/BGRA and RGB/BGR permutation) ■ YCbCr422 interleaved (YCrYCb, YCbYCr, CbYCrY, and CrYCbY) ■ AYCrCb444 interleaved ■ YCbCr420 pseudo planar (NV12 and NV21) ■ YCbCr422 pseudo planar (H1V2 and H2V1) ■ NV12/NV21 + alpha ■ YCbCr422 pseudo planar + alpha ■ YCbCr420 planar ■ YCbCr422 planar 	<ul style="list-style-type: none"> ■ 24-bit RGB (888) ■ 16-bit RGB (565) ■ 16-bit x/ARGB (4444 and 1555) ■ 32-bit x/ARGB (8888) (with ARGB/RGBA/ABGR/BGR A, and RGB/BGR permutation) 	<ul style="list-style-type: none"> ■ 24-bit RGB (888) ■ 16-bit RGB (565) ■ 16-bit x/ARGB (4444,1555) ■ 32-bit x/ARGB (8888) (with ARGB/RGBA/ABGR/BGR A, and RGB/BGR permutation) ■ YCbCr422 interleaved (YCrYCb, YCbYCr, CbYCrY, and CrYCbY) ■ AYCrCb444 interleaved ■ YCbCr420 pseudo planar (NV12 and NV21) ■ YCbCr422 pseudo planar (H1V2 and H2V1) ■ NV12/NV21 + alpha ■ YCbCr422 pseudo planar + alpha ■ YCbCr420 planar ■ YCbCr422 planar
CSC	Yes	No	No
Content adaptive contrast enhancement	256-bin histogram 256-entry LUT	No	No
Flip	Vertical and horizontal flip		

Table 3-2 Layer mixer, BG color, and hardware cursor

Feature	DragonBoard 410C support
Number of layer mixers	2
Maximum number of surfaces blended	4 + BG color + hardware cursor
Total number of pipes for blending	4 (1ViG + 2 RGB + 1 DMA)
Alpha blending	Constant alpha, per pixel alpha, pre-multiplied alpha, modulation alpha. Reverse alpha for all the above.
Alpha blending for BG color	Yes
BG color generation	Yes (no data fetch for BG color)
Transparency color key	Source color key, destination color key, simultaneous source and destination color key, and color key range
Arbitrary blending order	Yes
Blending in linear space	Yes
Blending color depth	12-bits/component
Hardware cursor size	64 x 64

Table 3-3 Destination Surface Processor Pipes (DSPP)

Feature	DragonBoard 410C support
Sunlight Visibility Improvement (SVI)	Global tone mapping
Content Adaptive Backlight (CABL) scaling	256-bin histogram and 256-entry LUT
Panel color correction	3 x 11 polynomial
Bit-depth for color correction	12-bits/component
Gamma correction	3-channel LUT
Picture adjustment	Smooth curve, soft clip, memory, and 6-zone color adjustment
Dither	4 x 4 ordered dithering performed without panel depth reduction

Table 3-4 Rotator and WB

Feature	DragonBoard 410C support
Rotator	
Input format support	Same as ViG
Rotation modes	90, 180, 270°
WB	
Number of WBs	2 – WB0 and WB2
WB performance	WB0 – 1280 x 800 @ 60 fps and WB2 – 1280 x 720 @ 30 fps

Feature	DragonBoard 410C support
WB format	<ul style="list-style-type: none"> 24-bit RGB (888) 16-bit RGB (565) 16-bit x/ARGB (4444 and 1555) 32-bit x/ARGB (8888) – With ARGB/RGBA/ABGR/BGRA and RGB/BGR permutation YCbCr420 pseudo planar (NV12 and NV21) YCbCr422 pseudo planar (H1V2 and H2V1) NV12 + alpha YCbCr422 pseudo planar + alpha YCbCr420 planar YCbCr422 planar

Table 3-5 Wireless display

Feature	DragonBoard 410C support
Number of WBs used	1 (WB2 with display processing)
WFD	WB2 – 720p at 30 fps
WFD possible formats	<ul style="list-style-type: none"> 24-bit RGB (888) 16-bit RGB (565) 32-bit x/ARGB or BGRx/A(8888) YCbCr420 pseudo planar (NV12)
Composition	WB for the final composition surface and WB2 with hardware cursor

**Figure 3-1 Display over WiFi**

4 Display and Video Processing Features

Table 4-1 Scaling

Feature		ViG pipe	RGB pipe
Scaling	Scaling ratio	1/64-20x (decimation for <1/4)	No
	Upscaling filter	<ul style="list-style-type: none">▪ 4-tap CAF (32 phases)▪ 2-tap bilinear (32 phases)▪ Nearest neighbor (32 phases)	No
	Downscaling filter	PCMN (8 phases)	No
Content Adaptive Filter (CAF) – Adjust filter coefficients based on content Phase control M/N (PCMN) – Phase control M/N. Fractional averaging filter for downscaling.			

5 APQ8016E Display Features

Table 5-1 Performance

Features	APQ8016E
Panel resolution	1200 x 800 @ 60 fps
Number of displays	2
External resolution	WFD – 1280 x 720 @ 30 fps
Maximum concurrency	1200 x 800 @ 60 primary + 1280 x 720 @ 30 WFD

Table 5-2 Image processing

Item	APQ8016E
Scaling	1/64 to 20x (Only VG pipe)
Composition layers	4 (1 ViG + 2 RGB + 1 DMA) + BG color + hardware cursor
SMP blocks	8 blocks of 8 KB
MDP clock	320 MHz

6 Software Architecture

6.1 Android display subsystem

- Android frameworks – Surface texture and SurfaceFlinger
- HALs – Overlay, graphics allocation, and hardware composer
- Primary panel interfaces – MIPI DSI
- External display – WFD
- MDP core – MDP drivers, overlay pipe management, clocks/power/performance
- Post processing and color management – CABL, color conversion, etc.

6.2 Composition




Figure 6-1 3D core overlay engine 2D core

6.3 MDSS driver software block diagram

- mdss_fb → Top-level IOCTL/native framebuffer interface
- mdss_mdp.c → MDP resources (clocks/irq/bus-bw/power)
- mdss_mdp_overlay → Overlay/DMA top-level API
- mdss_mdp_ctl → Controls the hardware abstraction to club the (LM + DSPP + Ping-pong + interface)
- mdss_mdp_pipe → SRC pipe related handling
- mdss_mdp_intf_cmd/mdss_mdp_intf_video/mdss_mdp_intf_writeback → MDP panel interface related handling
- mdss_mdp_pp → Postprocessing related implementation
- mdss_mdp_rotator → Rotator APIs (overlay_set/overlay_play interface)
- mdss_mdp_pp.c → Postprocessing related material




Figure 6-2 MDSS driver architecture

7 Source Code Layout

7.1 Software directory structure (userspace)

- SurfaceTexture – frameworks\native\libs\gui
- SurfaceFlinger – frameworks\native\services\surfaceflinger
- Overlay HAL – hardware\qcom\display\liboverlay
- Graphics alloc – hardware\qcom\display\libgralloc
- Hardware composer – hardware\qcom\display\libhwcomposer

7.2 Software directory structure (driver)

- MDSS driver – kernel\drivers\video\msm\mdss
 - Source surface process
 - mdss_mdp_overlay.c
 - mdss_mdp_pipe.c
- Layer Mixer
 - mdss_mdp_ctl.c
- Destination Surface Processor (DSP)
 - mdss_mdp_intf_cmd.c
 - mdss_mdp_intf_video.c
 - mdss_mdp_intf_writeback.c
 - mdss_mdp_rotator
- Display peripheral interface
 - mdss_dsi.c
 - mdss_dsi_host.c

8 Software Interface Structure (Userspace and Driver)

8.1 Support for standard IOCTLs of Android

- FBIOGET_VSCREENINFO – Gets variable information of framebuffer device
- FBIOPUT_VSCREENINFO – Put variable information of framebuffer device
- FBIOBLANK – Turns on/off framebuffer device (display on/off)
- FBIOPAN_DISPLAY – Updates display/framebuffer device with new image

8.2 Qualcomm added IOCTLs

- MSMFB_OVERLAY_GET – Gets overlay pipe/rotator information
- MSMFB_OVERLAY_SET – Sets parameters/allocating overlay pipe/rotator
- MSMFB_OVERLAY_UNSET – Closes pipe/rotator
- MSMFB_OVERLAY_PLAY_ENABLE – Controls overlay update
- MSMFB_OVERLAY_PLAY – Queues buffer to pipe
- MSMFB_OVERLAY_PLAY_WAIT – Waits for vsync
- MSMFB_CURSOR – Hardware cursor support
- MSMFB_SET_LUT – Gamma look up table setup for CABL
- MSMFB_HISTOGRAM – Reading histogram
- MSMFB_HISTOGRAM_START – Starting Histogram
- MSMFB_HISTOGRAM_STOP – Stopping Histogram

EXHIBIT 1

PLEASE READ THIS LICENSE AGREEMENT ("AGREEMENT") CAREFULLY. THIS AGREEMENT IS A BINDING LEGAL AGREEMENT ENTERED INTO BY AND BETWEEN YOU (OR IF YOU ARE ENTERING INTO THIS AGREEMENT ON BEHALF OF AN ENTITY, THEN THE ENTITY THAT YOU REPRESENT) AND QUALCOMM TECHNOLOGIES, INC. ("QTI" "WE" "OUR" OR "US"). THIS IS THE AGREEMENT THAT APPLIES TO YOUR USE OF THE DESIGNATED AND/OR ATTACHED DOCUMENTATION AND ANY UPDATES OR IMPROVEMENTS THEREOF (COLLECTIVELY, "MATERIALS"). BY USING OR COMPLETING THE INSTALLATION OF THE MATERIALS, YOU ARE ACCEPTING THIS AGREEMENT AND YOU AGREE TO BE BOUND BY ITS TERMS AND CONDITIONS. IF YOU DO NOT AGREE TO THESE TERMS, QTI IS UNWILLING TO AND DOES NOT LICENSE THE MATERIALS TO YOU. IF YOU DO NOT AGREE TO THESE TERMS YOU MUST DISCONTINUE AND YOU MAY NOT USE THE MATERIALS OR RETAIN ANY COPIES OF THE MATERIALS. ANY USE OR POSSESSION OF THE MATERIALS BY YOU IS SUBJECT TO THE TERMS AND CONDITIONS SET FORTH IN THIS AGREEMENT.

1.1 **License.** Subject to the terms and conditions of this Agreement, including, without limitation, the restrictions, conditions, limitations and exclusions set forth in this Agreement, Qualcomm Technologies, Inc. ("QTI") hereby grants to you a nonexclusive, limited license under QTI's copyrights to use the attached Materials; and to reproduce and redistribute a reasonable number of copies of the Materials. You may not use Qualcomm Technologies or its affiliates or subsidiaries name, logo or trademarks; and copyright, trademark, patent and any other notices that appear on the Materials may not be removed or obscured. QTI shall be free to use suggestions, feedback or other information received from You, without obligation of any kind to You. QTI may immediately terminate this Agreement upon your breach. Upon termination of this Agreement, Sections 1.2-4 shall survive.

1.2 **Indemnification.** You agree to indemnify and hold harmless QTI and its officers, directors, employees and successors and assigns against any and all third party claims, demands, causes of action, losses, liabilities, damages, costs and expenses, incurred by QTI (including but not limited to costs of defense, investigation and reasonable attorney's fees) arising out of, resulting from or related to: (i) any breach of this Agreement by You; and (ii) your acts, omissions, products and services. If requested by QTI, You agree to defend QTI in connection with any third party claims, demands, or causes of action resulting from, arising out of or in connection with any of the foregoing.

1.3 **Ownership.** QTI (or its licensors) shall retain title and all ownership rights in and to the Materials and all copies thereof, and nothing herein shall be deemed to grant any right to You under any of QTI's or its affiliates' patents. You shall not subject the Materials to any third party license terms (e.g., open source license terms). You shall not use the Materials for the purpose of identifying or providing evidence to support any potential patent infringement claim against QTI, its affiliates, or any of QTI's or QTI's affiliates' suppliers and/or direct or indirect customers. QTI hereby reserves all rights not expressly granted herein.

1.4 **WARRANTY DISCLAIMER.** YOU EXPRESSLY ACKNOWLEDGE AND AGREE THAT THE USE OF THE MATERIALS IS AT YOUR SOLE RISK. THE MATERIALS AND TECHNICAL SUPPORT, IF ANY, ARE PROVIDED "AS IS" AND WITHOUT WARRANTY OF ANY KIND, WHETHER EXPRESS OR IMPLIED. QTI ITS LICENSORS AND AFFILIATES MAKE NO WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THE MATERIALS OR ANY OTHER INFORMATION OR DOCUMENTATION PROVIDED UNDER THIS AGREEMENT, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR AGAINST INFRINGEMENT, OR ANY EXPRESS OR IMPLIED WARRANTY ARISING OUT OF TRADE USAGE OR OUT OF A COURSE OF DEALING OR COURSE OF PERFORMANCE. NOTHING CONTAINED IN THIS AGREEMENT SHALL BE CONSTRUED AS (I) A WARRANTY OR REPRESENTATION BY QTI, ITS LICENSORS OR AFFILIATES AS TO THE VALIDITY OR SCOPE OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT OR (II) A WARRANTY OR REPRESENTATION BY QTI THAT ANY MANUFACTURE OR USE WILL BE FREE FROM INFRINGEMENT OF PATENTS, COPYRIGHTS OR OTHER INTELLECTUAL PROPERTY RIGHTS OF OTHERS, AND IT SHALL BE THE SOLE RESPONSIBILITY OF YOU TO MAKE SUCH DETERMINATION AS IS NECESSARY WITH RESPECT TO THE ACQUISITION OF LICENSES UNDER PATENTS AND OTHER INTELLECTUAL PROPERTY OF THIRD PARTIES.

1.5 **LIMITATION OF LIABILITY.** IN NO EVENT SHALL QTI, QTI'S AFFILIATES OR ITS LICENSORS BE LIABLE TO YOU FOR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES, INCLUDING BUT NOT LIMITED TO ANY LOST PROFITS, LOST SAVINGS, OR OTHER INCIDENTAL DAMAGES, ARISING OUT OF THE USE OR INABILITY TO USE, OR THE DELIVERY OR FAILURE TO DELIVER, ANY OF THE MATERIALS, OR ANY BREACH OF ANY OBLIGATION UNDER THIS AGREEMENT, EVEN IF QTI HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. THE FOREGOING LIMITATION OF LIABILITY SHALL REMAIN IN FULL FORCE AND EFFECT REGARDLESS OF WHETHER YOUR REMEDIES HEREUNDER ARE DETERMINED TO HAVE FAILED OF THEIR ESSENTIAL PURPOSE. THE ENTIRE LIABILITY OF QTI, QTI'S AFFILIATES AND ITS LICENSORS, AND THE SOLE AND EXCLUSIVE REMEDY OF YOU, FOR ANY CLAIM OR CAUSE OF ACTION ARISING HEREUNDER (WHETHER IN CONTRACT, TORT, OR OTHERWISE) SHALL NOT EXCEED US\$10.

2. **COMPLIANCE WITH LAWS; APPLICABLE LAW.** You agree to comply with all applicable local, international and national laws and regulations and with U.S. Export Administration Regulations, as they apply to the subject matter of this Agreement. This Agreement is governed by the laws of the State of California, excluding California's choice of law rules.

3. **CONTRACTING PARTIES.** If the Materials are downloaded on any computer owned by a corporation or other legal entity, then this Agreement is formed by and between QTI and such entity. The individual accepting the terms of this Agreement represents and warrants to QTI that they have the authority to bind such entity to the terms and conditions of this Agreement.

4. **MISCELLANEOUS PROVISIONS.** This Agreement, together with all exhibits attached hereto, which are incorporated herein by this reference, constitutes the entire agreement between QTI and You and supersedes all prior negotiations, representations and agreements between the parties with respect to the subject matter hereof. No addition or modification of this Agreement shall be effective unless made in writing and signed by the respective representatives of QTI and You. The restrictions, limitations, exclusions and conditions set forth in this Agreement shall apply even if QTI or any of its affiliates becomes aware of or fails to act in a manner to address any violation or failure to comply therewith. You hereby acknowledge and agree that the restrictions, limitations, conditions and exclusions imposed in this Agreement on the rights granted in this Agreement are not a derogation of the benefits of such rights. You further acknowledges that, in the absence of such restrictions, limitations, conditions and exclusions, QTI would not have entered into this Agreement with You. Each party shall be responsible for and shall bear its own expenses in connection with this Agreement. If any of the provisions of this Agreement are determined to be invalid, illegal, or otherwise unenforceable, the remaining provisions shall remain in full force and effect. This Agreement is entered into solely in the English language, and if for any reason any other language version is prepared by any party, it shall be solely for convenience and the English version shall govern and control all aspects. If You are located in the province of Quebec, Canada, the following applies: The Parties hereby confirm they have requested this Agreement and all related documents be prepared in English.