

🌐 conciliacao-fretes ▾

⊗ **Payment method removed**

Your credit card was removed from your workspace, which temporarily prevents adding a new card and creating paid services.

🌐 WEB SERVICE

conciliacao-fretes

Docker

Free

[Upgrade your instance →](#)

Connect ▾

Manual Deploy

Service ID: `srv-d9udbam1egvs73e8ffa0` 

 cofresgoldsafe / conciliacao-fretes 🔖 main

<https://conciliacao-fretes.onrender.com> 

Settings

General

Name

A unique name for your Web Service.

conciliacao-fretes

 Edit

Region

Your services in the same [region](#) can communicate over a [private network](#).

Virginia (US East)

Instance Type

Free

0.1 CPU 512 MB

Update

ⓘ Please [enter your payment information](#) to select an instance type with higher limits.

ⓘ See [remaining free usage](#), or learn about [free service limits](#).

Build

Source

The build source for your Web Service

 cofresgoldsafe / conciliacao-fretes

 Edit

Branch

The Git branch to build and deploy.

 main

 Edit

Root Directory Optional

If set, Render runs commands from this directory instead of the repository root. Additionally, code changes outside of this directory do not trigger an auto-deploy. Most commonly used with a [monorepo](#).

 Edit

Registry Credential

If your service pulls private Docker images from a registry, specify a credential that can access those images. Manage your credentials in [Settings](#).

No credential



 Edit

Dockerfile Path

The path to your service's Dockerfile, relative to the repo root. Defaults to `./Dockerfile`.

`./Dockerfile`

 Edit

Docker Build Context Directory

The path to your service's [Docker build context](#), relative to the repo root. Defaults to the root.

`$ .`

 Edit

Git Credentials

User providing the credentials to pull the repository.

contato@goldsafe.com.br (you)

Use My Credentials

Build Filters

Include or ignore specific paths in your repo when determining whether to trigger an auto-deploy. Paths are relative to your repo's root directory. [Learn more](#).

 Edit

Included Paths

Changes that match these paths will trigger a new build.

+ Add Included Path

Ignored Paths

Changes that match these paths will not trigger a new build.

+ Add Ignored Path

Deploy

Docker Command

Optionally override your Dockerfile's `CMD` and `ENTRYPOINT` instructions with a different command to start your service.

 Edit

Pre-Deploy Command Optional

Render runs this command before the start command. Useful for database migrations and static asset uploads.



 Edit

Auto-Deploy

By default, Render automatically deploys your service whenever you update its code or configuration. Disable to handle deploys manually. [Learn more.](#)

On Commit 

 Edit

Deploy Hook

Your private URL to trigger a deploy for this server. Remember to keep this a secret.

.....  

 Regenerate hook

 Loading...

PR Previews

Pull Request Previews

Spin up temporary instances to test pull requests opened against the main branch of `cofresgoldsafe/conciliacao-fretes`. Choose **Automatic** to preview all PRs, or **Manual** for only PRs with `[render preview]` in their title. [Pull Request Previews](#) create a new instance for just this service. Use [Preview Environments](#) to clone a group of services for every PR.

Off



 Edit

Networking

Edge Caching

Serve static content at the edge to improve performance and reduce service load.

[Learn more.](#)

Cacheable File Types

Specify which file types Render is allowed to cache for your service. You can fine-tune this behavior with `Cache-Control` headers.

None



 Edit

 PAID

Edge Caching is only available for paid instances.

[Upgrade](#)

Notifications

Service Notifications

Set notifications to receive for your service. This setting will override your workspace's default settings.

Use workspace default (Only failure notifications)



 Edit

Preview Environment Notifications

Configure notifications for [preview environments](#) and [service previews](#).

Use account default (Disabled)



 Edit

Health Checks

Health Check Path

Provide an HTTP endpoint path that Render messages periodically to monitor your service.

[Learn More.](#)

 Edit

Maintenance Mode

Maintenance Mode

Temporarily disable public access to your service. While enabled, Render serves a static maintenance page for all incoming requests. [Learn more.](#)



Maintenance Mode Disabled

Custom Maintenance Page Optional

If provided, Render uses the specified URL for your maintenance page instead of serving the [default page](#).

 PAID

Maintenance mode is only available for paid instances.

[Upgrade](#)

[Delete Web Service](#)

 [Suspend Web Service](#)

