USQL Formal Grammar Specification

This document defines the complete formal grammar for USQL, UQA's SQL dialect. Only syntax that is actually implemented in the compiler (`uqa/sql/compiler.py`) is listed here. The notation follows ISO 14977 EBNF with the extensions noted below.

USQL Formal Grammar Specification
- Notation
- 1. Top-Level Statement
- 2. Data Definition Language (DDL)
  - 2.1 CREATE TABLE
  - 2.2 CREATE TABLE AS
  - 2.3 ALTER TABLE
  - 2.4 DROP TABLE
  - 2.5 TRUNCATE
  - 2.6 CREATE / DROP VIEW
  - 2.7 Indexes
  - 2.8 Sequences
  - 2.9 Foreign Data Wrappers
- 3. Data Manipulation Language (DML)
  - 3.1 INSERT
  - 3.2 UPDATE
  - 3.3 DELETE
- 4. Queries (SELECT)
  - 4.1 SELECT
  - 4.2 FROM Clause
  - 4.3 WHERE Clause
  - 4.4 GROUP BY
  - 4.5 ORDER BY
  - 4.6 LIMIT / OFFSET
  - 4.7 Set Operations
- 5. Common Table Expressions (WITH)
- 6. Window Functions
  - Ranking Functions
  - Value Functions
- 7. Aggregate Functions
  - Supported Aggregate Functions
- 8. Expressions
  - 8.1 Literals
  - 8.2 Column References
  - 8.3 Operators
  - 8.4 CASE Expression
  - 8.5 Type Cast
  - 8.6 Function Call
  - 8.7 Subquery Expression
  - 8.8 Parameter Reference
- 9. Data Types
- 10. Scalar Functions
  - 10.1 String Functions
  - 10.2 Regular Expression Functions
  - 10.3 Math Functions
  - 10.4 Trigonometric Functions
  - 10.5 Date/Time Functions

10.6 Conditional Functions
10.7 Type Inspection
10.8 Sequence Functions
10.9 UUID Functions
11. JSON/JSONB Functions
11.1 Construction
11.2 Access
11.3 Inspection
11.4 Containment Operators
11.5 Modification
11.6 Set-Returning JSON Functions
12. Array Functions
13. Cross-Paradigm Search Functions
13.1 Full-Text Search
13.2 Vector Similarity Search
13.3 Graph Traversal
13.4 Hierarchical Filters
14. Probabilistic Fusion
15. Table-Returning Functions (FROM Clause)
16. Cypher / Graph Integration
17. Transactions
18. Prepared Statements
19. Utility Statements
19.1 EXPLAIN
19.2 ANALYZE
20. Information Schema
21. Hierarchical Functions (SELECT List)
Appendix A: Operator Precedence (highest to lowest)
Appendix B: Reserved Words

Notation

```
KEYWORD          Uppercase words are SQL keywords (case-insensitive)
name             Lowercase italic words are non-terminal symbols
'literal'        Single-quoted strings are literal tokens
|                Alternation
[ ... ]          Optional
{ ... }          Repetition (zero or more)
( ... )          Grouping
```

---

1. Top-Level Statement

```
statement
    = select_stmt
    | insert_stmt
    | update_stmt
    | delete_stmt
    | create_table_stmt
    | create_table_as_stmt
```

```
    | drop_table_stmt
    | alter_table_stmt
    | rename_stmt
    | truncate_stmt
    | create_view_stmt
    | drop_view_stmt
    | create_index_stmt
    | drop_index_stmt
    | create_sequence_stmt
    | alter_sequence_stmt
    | drop_sequence_stmt
    | create_foreign_server_stmt
    | create_foreign_table_stmt
    | drop_foreign_server_stmt
    | drop_foreign_table_stmt
    | explain_stmt
    | analyze_stmt
    | transaction_stmt
    | prepare_stmt
    | execute_stmt
    | deallocate_stmt
    ;
```

---

2. Data Definition Language (DDL)

2.1 CREATE TABLE

```
create_table_stmt
    = CREATE [ TEMPORARY | TEMP ] TABLE [ IF NOT EXISTS ] table_name
      '(' column_def { ',' column_def } { ',' table_constraint } ')'
    ;

column_def
    = column_name data_type { column_constraint }
    ;

column_constraint
    = PRIMARY KEY
    | NOT NULL
    | NULL
    | UNIQUE
    | DEFAULT expression
    | CHECK '(' expression ')'
    | REFERENCES table_name '(' column_name ')'
    ;

table_constraint
    = PRIMARY KEY '(' column_name { ',' column_name } ')'
    | UNIQUE '(' column_name { ',' column_name } ')'
    | CHECK '(' expression ')'
    | FOREIGN KEY '(' column_name ')' REFERENCES table_name '(' column_name ')'
    ;
```

2.2 CREATE TABLE AS

```
create_table_as_stmt
    = CREATE [ TEMPORARY | TEMP ] TABLE table_name AS select_stmt
    ;
```

2.3 ALTER TABLE

```
alter_table_stmt
    = ALTER TABLE table_name alter_action
    ;

alter_action
    = ADD [ COLUMN ] column_name data_type { column_constraint }
    | DROP [ COLUMN ] [ IF EXISTS ] column_name
    | RENAME [ COLUMN ] column_name TO column_name
    | RENAME TO table_name
    | ALTER [ COLUMN ] column_name SET DEFAULT expression
    | ALTER [ COLUMN ] column_name DROP DEFAULT
    | ALTER [ COLUMN ] column_name SET NOT NULL
    | ALTER [ COLUMN ] column_name DROP NOT NULL
    ;
```

2.4 DROP TABLE

```
drop_table_stmt
    = DROP TABLE [ IF EXISTS ] table_name { ',' table_name }
    ;
```

2.5 TRUNCATE

```
truncate_stmt
    = TRUNCATE [ TABLE ] table_name [ RESTART IDENTITY ]
    ;
```

2.6 CREATE / DROP VIEW

```
create_view_stmt
    = CREATE VIEW view_name AS select_stmt
    ;

drop_view_stmt
    = DROP VIEW [ IF EXISTS ] view_name
    ;
```

2.7 Indexes

```
create_index_stmt
```

```
    = CREATE [ UNIQUE ] INDEX [ index_name ] ON table_name
      [ USING index_method ]
      '(' index_column { ',' index_column } ')'
      [ WITH '(' index_parameter { ',' index_parameter } ')' ]
    ;

index_method
    = 'btree' | 'hnsw'
    ;

index_column
    = column_name [ ASC | DESC ]
    ;

index_parameter
    = parameter_name '=' numeric_literal
    ;

drop_index_stmt
    = DROP INDEX [ IF EXISTS ] index_name
    ;
```

When `index_method` is `hnsw`, the column must be of type `VECTOR(n)`. Supported `index_parameter` names: `ef_construction` (default 200), `m` (default 16).

2.8 Sequences

```
create_sequence_stmt
    = CREATE SEQUENCE sequence_name
      [ START [ WITH ] integer ]
      [ INCREMENT [ BY ] integer ]
      [ MINVALUE integer ]
      [ MAXVALUE integer ]
      [ CYCLE | NO CYCLE ]
    ;

alter_sequence_stmt
    = ALTER SEQUENCE sequence_name
      [ RESTART [ WITH integer ] ]
      [ INCREMENT [ BY ] integer ]
      [ START [ WITH ] integer ]
    ;

drop_sequence_stmt
    = DROP SEQUENCE [ IF EXISTS ] sequence_name
    ;
```

2.9 Foreign Data Wrappers

```
create_foreign_server_stmt
    = CREATE FOREIGN SERVER server_name
      TYPE string_literal
      [ VERSION string_literal ]
```

```
      OPTIONS '(' option_pair { ',' option_pair } ')'
    ;

create_foreign_table_stmt
    = CREATE FOREIGN TABLE table_name
      '(' column_def { ',' column_def } ')'
      SERVER server_name
      [ OPTIONS '(' option_pair { ',' option_pair } ')' ]
    ;

option_pair
    = option_name string_literal
    ;

drop_foreign_server_stmt
    = DROP FOREIGN SERVER [ IF EXISTS ] server_name
    ;

drop_foreign_table_stmt
    = DROP FOREIGN TABLE [ IF EXISTS ] table_name
    ;
```

3. Data Manipulation Language (DML)

3.1 INSERT

```
insert_stmt
    = INSERT INTO table_name [ '(' column_name { ',' column_name } ')' ]
      insert_source
      [ on_conflict_clause ]
      [ returning_clause ]
    ;

insert_source
    = VALUES row_value { ',' row_value }
    | select_stmt
    ;

row_value
    = '(' expression { ',' expression } ')'
    ;

on_conflict_clause
    = ON CONFLICT '(' column_name { ',' column_name } ')'
      DO NOTHING
    | ON CONFLICT '(' column_name { ',' column_name } ')'
      DO UPDATE SET assignment { ',' assignment }
      [ WHERE expression ]
    ;

assignment
    = column_name '=' expression
    ;
```

```

returning_clause
    = RETURNING select_list
    ;
```

The `EXCLUDED` pseudo-table references the row proposed for insertion inside `ON CONFLICT DO UPDATE SET` expressions.

3.2 UPDATE

```
update_stmt
    = UPDATE table_name [ [ AS ] alias ]
      SET assignment { ',' assignment }
      [ FROM from_item { ',' from_item } ]
      [ WHERE expression ]
      [ returning_clause ]
    ;
```

3.3 DELETE

```
delete_stmt
    = DELETE FROM table_name [ [ AS ] alias ]
      [ USING from_item { ',' from_item } ]
      [ WHERE expression ]
      [ returning_clause ]
    ;
```

---

4. Queries (SELECT)

4.1 SELECT

```
select_stmt
    = [ with_clause ] select_body
      { set_operation select_body }
      [ order_by_clause ]
      [ limit_clause ]
    ;

select_body
    = SELECT [ DISTINCT [ ON '(' expression { ',' expression } ')' ] ]
      select_list
      [ FROM from_item { ',' from_item } ]
      [ WHERE expression ]
      [ GROUP BY group_by_item { ',' group_by_item } ]
      [ HAVING expression ]
      [ WINDOW window_def { ',' window_def } ]
    ;

select_list
    = '*'
    | select_item { ',' select_item }
```

```
    ;

select_item
    = expression [ [ AS ] alias ]
    ;
```

4.2 FROM Clause

```
from_item
    = table_reference
    | joined_table
    | subquery_reference
    | lateral_reference
    | function_reference
    ;

table_reference
    = table_name [ [ AS ] alias ]
    ;

joined_table
    = from_item join_type JOIN from_item ON expression
    | from_item join_type JOIN from_item USING '(' column_name { ',' column_name } ')'
    | from_item CROSS JOIN from_item
    ;

join_type
    = [ INNER ]
    | LEFT [ OUTER ]
    | RIGHT [ OUTER ]
    | FULL [ OUTER ]
    ;

subquery_reference
    = '(' select_stmt ')' [ AS ] alias
    ;

lateral_reference
    = LATERAL '(' select_stmt ')' [ AS ] alias
    | from_item ',' LATERAL '(' select_stmt ')' [ AS ] alias
    ;

function_reference
    = function_call [ AS alias [ '(' column_def_list ')' ] ]
    ;
```

Multiple comma-separated items in `FROM` produce implicit cross joins.

4.3 WHERE Clause

```
where_expression
    = comparison_expr
```

```
    | boolean_expr
    | null_test
    | between_expr
    | in_expr
    | like_expr
    | exists_expr
    | sublink_expr
    | search_function
    | fusion_function
    ;

comparison_expr
    = expression comp_op expression
    ;

comp_op
    = '=' | '!=' | '<>' | '<' | '>' | '<=' | '>='
    ;

boolean_expr
    = expression AND expression
    | expression OR expression
    | NOT expression
    ;

null_test
    = expression IS NULL
    | expression IS NOT NULL
    ;

between_expr
    = expression [ NOT ] BETWEEN expression AND expression
    ;

in_expr
    = expression [ NOT ] IN '(' expression { ',' expression } ')'
    | expression [ NOT ] IN '(' select_stmt ')'
    ;

like_expr
    = expression [ NOT ] LIKE string_literal [ ESCAPE string_literal ]
    | expression [ NOT ] ILIKE string_literal [ ESCAPE string_literal ]
    ;

exists_expr
    = EXISTS '(' select_stmt ')'
    | NOT EXISTS '(' select_stmt ')'
    ;

sublink_expr
    = expression comp_op '(' select_stmt ')'
    ;
```

4.4 GROUP BY

```
group_by_item
    = column_name
    | column_alias
    | integer_literal                       (* ordinal reference *)
    | expression                            (* computed expression *)
    ;
```

4.5 ORDER BY

```
order_by_clause
    = ORDER BY sort_item { ',' sort_item }
    ;

sort_item
    = expression [ ASC | DESC ] [ NULLS FIRST | NULLS LAST ]
    ;
```

`expression` may be a column name, column alias, ordinal (integer), or arbitrary expression.

4.6 LIMIT / OFFSET

```
limit_clause
    = LIMIT expression [ OFFSET expression ]
    | OFFSET expression
    | FETCH FIRST expression ROWS ONLY
    | FETCH NEXT expression ROWS ONLY
    ;
```

4.7 Set Operations

```
set_operation
    = UNION [ ALL ]
    | INTERSECT [ ALL ]
    | EXCEPT [ ALL ]
    ;
```

---

5. Common Table Expressions (WITH)

```
with_clause
    = WITH [ RECURSIVE ] cte_def { ',' cte_def }
    ;

cte_def
    = cte_name [ '(' column_name { ',' column_name } ')' ] AS '(' select_stmt ')'
    ;
```

Recursive CTEs require `UNION ALL` between the base case and the recursive case. Termination occurs at fixpoint (when the recursive step produces no new rows). Maximum recursion depth defaults to 1000.

---

6. Window Functions

```
window_function
    = function_name '(' [ expression { ',' expression } ] ')' OVER window_spec
    | function_name '(' [ expression { ',' expression } ] ')' OVER window_name
    ;

window_spec
    = '(' [ PARTITION BY expression { ',' expression } ]
          [ ORDER BY sort_item { ',' sort_item } ]
          [ frame_clause ]
      ')'
    ;

frame_clause
    = ROWS BETWEEN frame_bound AND frame_bound
    | RANGE BETWEEN frame_bound AND frame_bound
    ;

frame_bound
    = UNBOUNDED PRECEDING
    | UNBOUNDED FOLLOWING
    | CURRENT ROW
    | integer_literal PRECEDING
    | integer_literal FOLLOWING
    ;

window_def
    = window_name AS window_spec
    ;
```

Ranking Functions

```
ROW_NUMBER() OVER (...)
RANK() OVER (...)
DENSE_RANK() OVER (...)
NTILE( integer ) OVER (...)
PERCENT_RANK() OVER (...)
CUME_DIST() OVER (...)
```

Value Functions

```
LAG( expression [, offset [, default ]] ) OVER (...)
LEAD( expression [, offset [, default ]] ) OVER (...)
FIRST_VALUE( expression ) OVER (...)
LAST_VALUE( expression ) OVER (...)
NTH_VALUE( expression , integer ) OVER (...)
```

Any aggregate function can also be used as a window function with an `OVER (...)` clause.

---

7. Aggregate Functions

```
aggregate_call
    = aggregate_name '(' [ DISTINCT ] expression { ',' expression } ')'
      [ agg_order_by ]
      [ filter_clause ]
    | aggregate_name '(' '*' ')' [ filter_clause ]
    ;

agg_order_by
    = ORDER BY sort_item { ',' sort_item }
    ;

filter_clause
    = FILTER '(' WHERE expression ')'
    ;
```

Supported Aggregate Functions

Category	Functions
Basic	`COUNT`, `SUM`, `AVG`, `MIN`, `MAX`
Collection	`STRING_AGG`, `ARRAY_AGG`, `BOOL_AND`, `BOOL_OR`
JSON	`JSON_OBJECT_AGG`, `JSONB_OBJECT_AGG`
Statistical	`STDDEV`, `STDDEV_POP`, `STDDEV_SAMP`, `VARIANCE`, `VAR_POP`, `VAR_SAMP`
Correlation	`CORR`, `COVAR_POP`, `COVAR_SAMP`
Regression	`REGR_SLOPE`, `REGR_INTERCEPT`, `REGR_R2`, `REGR_COUNT`, `REGR_AVGX`, `REGR_AVGY`, `REGR_SXX`, `REGR_SYY`, `REGR_SXY`

`COUNT(*)` counts all rows. `COUNT(DISTINCT col)` counts distinct non-NULL values.

`STRING_AGG` and `ARRAY_AGG` accept an optional `ORDER BY` inside the aggregate call.

---

8. Expressions

8.1 Literals

```
literal
    = integer_literal
    | float_literal
    | string_literal
    | boolean_literal
    | null_literal
    | array_literal
    ;

integer_literal = digit { digit } ;
float_literal   = digit { digit } '.' digit { digit } ;
string_literal  = "'" { character } "'" ;
boolean_literal = TRUE | FALSE ;
null_literal    = NULL ;
array_literal   = ARRAY '[' expression { ',' expression } ']' ;
```

8.2 Column References

```
column_ref
    = column_name
    | table_name '.' column_name
    | '*'
    | table_name '.' '*'
    ;
```

8.3 Operators

```
expression
    = unary_expression
    | expression arithmetic_op expression
    | expression comp_op expression
    | expression string_op expression
    | expression boolean_op expression
    | expression json_op expression
    | expression IS [ NOT ] NULL
    | expression [ NOT ] BETWEEN expression AND expression
    | expression [ NOT ] IN '(' expression_list ')'
    | expression [ NOT ] IN '(' select_stmt ')'
    | expression [ NOT ] LIKE expression [ ESCAPE expression ]
    | expression [ NOT ] ILIKE expression [ ESCAPE expression ]
    | '(' expression ')'
    | '(' select_stmt ')'
    ;

unary_expression
    = [ '+' | '-' ] primary_expression
    | NOT expression
    ;

arithmetic_op = '+' | '-' | '*' | '/' | '%' ;
string_op     = '||' ;
boolean_op    = AND | OR ;

```

```
json_op
    = '->'                  (* field access, returns JSON *)
    | '->>'                 (* field access, returns TEXT *)
    | '#>'                  (* path access, returns JSON *)
    | '#>>'                 (* path access, returns TEXT *)
    | '@>'                  (* contains *)
    | '<@'                  (* contained by *)
    | '?'                   (* has key *)
    | '?|'                  (* has any key *)
    | '?&'                  (* has all keys *)
    ;
```

8.4 CASE Expression

```
case_expression
    = CASE { WHEN expression THEN expression } [ ELSE expression ] END
    | CASE expression { WHEN expression THEN expression } [ ELSE expression ] END
    ;
```

8.5 Type Cast

```
type_cast
    = CAST '(' expression AS data_type ')'
    | expression '::' data_type
    ;
```

8.6 Function Call

```
function_call
    = function_name '(' [ expression { ',' expression } ] ')'
    | function_name '(' '*' ')'
    ;
```

8.7 Subquery Expression

```
subquery_expression
    = '(' select_stmt ')'                          (* scalar subquery *)
    | expression [ NOT ] IN '(' select_stmt ')'
    | EXISTS '(' select_stmt ')'
    ;
```

8.8 Parameter Reference

```
param_ref = '$' integer_literal ;
```

Used in `PREPARE` statements and `engine.sql()` parameter binding.

---

9. Data Types

```
data_type
    = numeric_type
    | text_type
    | boolean_type
    | datetime_type
    | json_type
    | binary_type
    | special_type
    | array_type
    ;

numeric_type
    = INTEGER | INT | INT2 | INT4 | INT8
    | BIGINT | SMALLINT
    | SERIAL | BIGSERIAL
    | REAL | FLOAT | FLOAT4 | FLOAT8 | DOUBLE PRECISION
    | NUMERIC [ '(' precision ',' scale ')' ]
    | DECIMAL [ '(' precision ',' scale ')' ]
    ;

text_type
    = TEXT
    | VARCHAR [ '(' length ')' ]
    | CHARACTER VARYING [ '(' length ')' ]
    | CHAR [ '(' length ')' ]
    | CHARACTER [ '(' length ')' ]
    | NAME
    ;

boolean_type = BOOLEAN | BOOL ;

datetime_type
    = DATE
    | TIMESTAMP [ WITHOUT TIME ZONE ]
    | TIMESTAMPTZ
    | TIMESTAMP WITH TIME ZONE
    | INTERVAL
    ;

json_type = JSON | JSONB ;

binary_type = BYTEA ;

special_type
    = UUID
    | VECTOR '(' integer_literal ')'
    ;

array_type = data_type '[]' ;
```

`VECTOR(n)` defines an n-dimensional vector column. Vectors are stored in the document store as JSON arrays. For approximate nearest neighbor search, create an HNSW index with `CREATE INDEX ... USING hnsw (column)`. Without an index, `knn_match()` uses brute-force exact cosine similarity.

---

10. Scalar Functions

10.1 String Functions

```
UPPER( text ) -> text
LOWER( text ) -> text
INITCAP( text ) -> text
LENGTH( text ) -> integer
CHAR_LENGTH( text ) -> integer
CHARACTER_LENGTH( text ) -> integer
OCTET_LENGTH( text ) -> integer
SUBSTRING( text, start [, length] ) -> text
SUBSTR( text, start [, length] ) -> text
POSITION( substring IN text ) -> integer
STRPOS( text, substring ) -> integer
TRIM( text ) -> text
BTRIM( text [, characters] ) -> text
LTRIM( text [, characters] ) -> text
RTRIM( text [, characters] ) -> text
LPAD( text, length [, fill] ) -> text
RPAD( text, length [, fill] ) -> text
REPEAT( text, count ) -> text
REVERSE( text ) -> text
REPLACE( text, from, to ) -> text
CONCAT( value, ... ) -> text
CONCAT_WS( separator, value, ... ) -> text
SPLIT_PART( text, delimiter, index ) -> text
LEFT( text, count ) -> text
RIGHT( text, count ) -> text
TRANSLATE( text, from_chars, to_chars ) -> text
ASCII( text ) -> integer
CHR( code ) -> text
STARTS_WITH( text, prefix ) -> boolean
OVERLAY( text, replacement, start [, length] ) -> text
FORMAT( format_string, ... ) -> text
ENCODE( data, format ) -> text
DECODE( text, format ) -> bytea
MD5( text ) -> text
text || text -> text
```

10.2 Regular Expression Functions

```
REGEXP_MATCH( text, pattern [, flags] ) -> text[]
REGEXP_MATCHES( text, pattern [, flags] ) -> SETOF text[]
REGEXP_REPLACE( text, pattern, replacement [, flags] ) -> text
REGEXP_SPLIT_TO_ARRAY( text, pattern [, flags] ) -> text[]
```

Flags: `g` (global), `i` (case-insensitive), `s` (dotall).

10.3 Math Functions

```
ABS( numeric ) -> numeric
SIGN( numeric ) -> integer
ROUND( numeric [, digits] ) -> numeric
TRUNC( numeric [, digits] ) -> numeric
CEIL( numeric ) -> integer
CEILING( numeric ) -> integer
FLOOR( numeric ) -> integer
POWER( base, exponent ) -> numeric
POW( base, exponent ) -> numeric
SQRT( numeric ) -> numeric
CBRT( numeric ) -> numeric
EXP( numeric ) -> numeric
LN( numeric ) -> numeric
LOG( numeric ) -> numeric
LOG10( numeric ) -> numeric
LOG( base, value ) -> numeric
DIV( dividend, divisor ) -> integer
MOD( dividend, divisor ) -> numeric
GCD( a, b ) -> integer
LCM( a, b ) -> integer
PI() -> numeric
RANDOM() -> numeric
WIDTH_BUCKET( value, low, high, buckets ) -> integer
MIN_SCALE( numeric ) -> integer
TRIM_SCALE( numeric ) -> numeric
```

10.4 Trigonometric Functions

```
SIN( radians ) -> numeric
COS( radians ) -> numeric
TAN( radians ) -> numeric
ASIN( value ) -> numeric
ACOS( value ) -> numeric
ATAN( value ) -> numeric
ATAN2( y, x ) -> numeric
DEGREES( radians ) -> numeric
RADIANS( degrees ) -> numeric
```

10.5 Date/Time Functions

```
NOW() -> timestamp
CURRENT_TIMESTAMP -> timestamp
CURRENT_DATE -> date
CURRENT_TIME -> time
CLOCK_TIMESTAMP() -> timestamp
TIMEOFDAY() -> text
EXTRACT( field FROM timestamp ) -> numeric
DATE_PART( field, timestamp ) -> numeric
```

```
DATE_TRUNC( precision, timestamp ) -> timestamp
TO_CHAR( timestamp, format ) -> text
TO_DATE( text, format ) -> date
TO_TIMESTAMP( text, format ) -> timestamp
TO_NUMBER( text ) -> numeric
MAKE_DATE( year, month, day ) -> date
MAKE_TIMESTAMP( year, month, day, hour, minute, second ) -> timestamp
MAKE_INTERVAL( [years, months, weeks, days, hours, minutes, seconds] ) -> interval
AGE( timestamp [, timestamp] ) -> interval
OVERLAPS( start1, end1, start2, end2 ) -> boolean
ISFINITE( value ) -> boolean
```

`EXTRACT` / `DATE_PART` fields: `year`, `month`, `day`, `hour`, `minute`, `second`, `epoch`, `dow`, `doy`, `quarter`, `week`.

`DATE_TRUNC` precision values: `year`, `month`, `day`, `hour`, `minute`, `second`.

10.6 Conditional Functions

```
COALESCE( value, value, ... ) -> value
NULLIF( value1, value2 ) -> value
GREATEST( value, value, ... ) -> value
LEAST( value, value, ... ) -> value
```

10.7 Type Inspection

```
TYPEOF( value ) -> text
CAST( value AS type ) -> value
value :: type -> value
```

10.8 Sequence Functions

```
NEXTVAL( sequence_name ) -> integer
CURRVAL( sequence_name ) -> integer
SETVAL( sequence_name, value ) -> integer
```

10.9 UUID Functions

```
GEN_RANDOM_UUID() -> uuid
```

---

11. JSON/JSONB Functions

11.1 Construction

```
JSON_BUILD_OBJECT( key, value, ... ) -> json
JSONB_BUILD_OBJECT( key, value, ... ) -> jsonb
JSON_BUILD_ARRAY( value, ... ) -> json
JSONB_BUILD_ARRAY( value, ... ) -> jsonb
TO_JSON( value ) -> json
TO_JSONB( value ) -> jsonb
ROW_TO_JSON( record ) -> json
```

11.2 Access

```
json -> key -> json
json ->> key -> text
json -> index -> json
json ->> index -> text
json #> '{key1,key2}' -> json
json #>> '{key1,key2}' -> text
JSON_EXTRACT_PATH( json, key1, key2, ... ) -> json
JSON_EXTRACT_PATH_TEXT( json, key1, key2, ... ) -> text
JSONB_EXTRACT_PATH( jsonb, key1, key2, ... ) -> jsonb
JSONB_EXTRACT_PATH_TEXT( jsonb, key1, key2, ... ) -> text
```

11.3 Inspection

```
JSON_TYPEOF( json ) -> text
JSONB_TYPEOF( jsonb ) -> text
JSON_ARRAY_LENGTH( json ) -> integer
JSONB_ARRAY_LENGTH( jsonb ) -> integer
```

`JSON_TYPEOF` returns: `object`, `array`, `string`, `number`, `boolean`, `null`.

11.4 Containment Operators

```
jsonb @> jsonb -> boolean
jsonb <@ jsonb -> boolean
jsonb ? text -> boolean
jsonb ?| text[] -> boolean
jsonb ?& text[] -> boolean
```

11.5 Modification

```
JSONB_SET( target, path, new_value [, create_if_missing] ) -> jsonb
JSONB_INSERT( target, path, new_value ) -> jsonb
JSONB_STRIP_NULLS( jsonb ) -> jsonb
JSON_STRIP_NULLS( json ) -> json
```

11.6 Set-Returning JSON Functions

```
JSON_EACH( json ) -> SETOF (key text, value json)
JSONB_EACH( jsonb ) -> SETOF (key text, value jsonb)
JSON_EACH_TEXT( json ) -> SETOF (key text, value text)
JSONB_EACH_TEXT( jsonb ) -> SETOF (key text, value text)
JSON_ARRAY_ELEMENTS( json ) -> SETOF json
JSONB_ARRAY_ELEMENTS( jsonb ) -> SETOF jsonb
JSON_ARRAY_ELEMENTS_TEXT( json ) -> SETOF text
JSONB_ARRAY_ELEMENTS_TEXT( jsonb ) -> SETOF text
JSON_OBJECT_KEYS( json ) -> SETOF text
JSONB_OBJECT_KEYS( jsonb ) -> SETOF text
```

---

12. Array Functions

```
ARRAY_LENGTH( array, dimension ) -> integer
ARRAY_UPPER( array, dimension ) -> integer
ARRAY_LOWER( array, dimension ) -> integer
ARRAY_CAT( array, array ) -> array
ARRAY_APPEND( array, element ) -> array
ARRAY_REMOVE( array, element ) -> array
CARDINALITY( array ) -> integer
```

---

13. Cross-Paradigm Search Functions

These functions appear in WHERE clauses and produce relevance scores accessible via the `_score` pseudo-column.

13.1 Full-Text Search

```
text_match_call     = TEXT_MATCH '(' column_name ',' string_literal ')' ;
bayesian_match_call = BAYESIAN_MATCH '(' column_name ',' string_literal ')' ;
```

`TEXT_MATCH` scores with BM25. `BAYESIAN_MATCH` applies Bayesian calibration to produce $P(\text{relevant}) \in [0, 1]$.

13.2 Vector Similarity Search

```
knn_match_call
    = KNN_MATCH '(' column_name ',' vector_arg ',' integer_literal ')'
    ;

vector_exclude_call
    = VECTOR_EXCLUDE '(' column_name ',' vector_arg ',' vector_arg ','
                         integer_literal ',' numeric_literal ')'
    ;

vector_arg
    = array_literal
    | param_ref
    ;
```

`KNN_MATCH` returns the top-k nearest neighbors by cosine similarity. Uses the HNSW index if one exists on the column, otherwise falls back to brute-force exact scan.

13.3 Graph Traversal

```
traverse_match_call
    = TRAVERSE_MATCH '(' integer_literal ',' string_literal ',' integer_literal ')'
    ;
```

13.4 Hierarchical Filters

```
path_filter_call
    = PATH_FILTER '(' string_literal ',' expression ')'
    | PATH_FILTER '(' string_literal ',' string_literal ',' expression ')'
    ;
```

---

14. Probabilistic Fusion

Fusion meta-functions combine multiple search signals in the WHERE clause. Each signal argument must be a search function call.

```
fusion_call
    = FUSE_LOG_ODDS '(' signal { ',' signal } [ ',' numeric_literal ] ')'
    | FUSE_PROB_AND '(' signal { ',' signal } ')'
    | FUSE_PROB_OR '(' signal { ',' signal } ')'
    | FUSE_PROB_NOT '(' signal ')'
    ;

signal
    = text_match_call
    | bayesian_match_call
    | knn_match_call
    | traverse_match_call
    ;
```

Inside a fusion context, `TEXT_MATCH` is automatically promoted to Bayesian BM25 calibration so all signals produce probabilities in $(0, 1)$.

---

15. Table-Returning Functions (FROM Clause)

```
generate_series_call
    = GENERATE_SERIES '(' start ',' stop [ ',' step ] ')'
    ;

regexp_split_to_table_call
    = REGEXP_SPLIT_TO_TABLE '(' text ',' pattern [ ',' flags ] ')'
    ;

```

```
traverse_call
    = TRAVERSE '(' start_id ',' label ',' max_hops [ ',' table_name ] ')'
    ;

rpq_call
    = RPQ '(' path_expression ',' start_id ')'
    ;
```

`GENERATE_SERIES` produces integer or timestamp series.

---

16. Cypher / Graph Integration

```
cypher_call
    = CYPHER '(' cypher_query_string [ ',' graph_name ] ')'
    ;

create_graph_call
    = CREATE_GRAPH '(' graph_name ')'
    ;

drop_graph_call
    = DROP_GRAPH '(' graph_name ')'
    ;
```

These are used in the FROM clause:

```
SELECT * FROM cypher('MATCH (n) RETURN n.name') AS (name agtype);
SELECT * FROM cypher('MATCH (n) RETURN n', 'my_graph') AS (n agtype);
SELECT * FROM create_graph('social');
SELECT * FROM drop_graph('social');
```

See the USQL Language Reference for the full openCypher clause and pattern syntax.

---

17. Transactions

```
transaction_stmt
    = BEGIN [ TRANSACTION ]
    | COMMIT [ TRANSACTION ]
    | ROLLBACK [ TRANSACTION ]
    | SAVEPOINT savepoint_name
    | RELEASE SAVEPOINT savepoint_name
    | ROLLBACK TO SAVEPOINT savepoint_name
    ;
```

---

18. Prepared Statements

```
prepare_stmt
    = PREPARE statement_name [ '(' data_type { ',' data_type } ')' ] AS statement
    ;

execute_stmt
    = EXECUTE statement_name [ '(' expression { ',' expression } ')' ]
    ;

deallocate_stmt
    = DEALLOCATE statement_name
    | DEALLOCATE ALL
    ;
```

---

19. Utility Statements

19.1 EXPLAIN

```
explain_stmt
    = EXPLAIN select_stmt
    | EXPLAIN ANALYZE select_stmt
    | EXPLAIN '(' option { ',' option } ')' select_stmt
    ;

option
    = ANALYZE boolean_literal
    | VERBOSE boolean_literal
    ;
```

19.2 ANALYZE

```
analyze_stmt
    = ANALYZE [ table_name ]
    ;
```

Collects per-column statistics: distinct count, NULL count, min/max values, equi-depth histograms, most common values and frequencies. Used by the query optimizer for cardinality estimation.

---

20. Information Schema

```
information_schema_query
    = SELECT ... FROM information_schema '.' view_name [ WHERE ... ]
    ;
```

Supported views:

View	Columns
`information_schema.tables`	`table_catalog`, `table_schema`, `table_name`, `table_type`, `is_insertable_into`, `is_typed`, `commit_action`
`information_schema.columns`	`table_catalog`, `table_schema`, `table_name`, `column_name`, `ordinal_position`, `column_default`, `is_nullable`, `data_type`, `character_maximum_length`, `numeric_precision`, `numeric_scale`

---

21. Hierarchical Functions (SELECT List)

```
path_value_call = PATH_VALUE '(' path_string ')' ;
path_agg_call   = PATH_AGG '(' path_string ',' agg_name ')' ;
```

`PATH_VALUE` navigates a dot-delimited path in a nested document and returns the value found. `PATH_AGG` collects array element values at the path and applies an aggregation (`sum`, `count`, `avg`, `min`, `max`).

Appendix A: Operator Precedence (highest to lowest)

Precedence	Operator	Associativity
1	`::`	left
2	`->`, `->>`, `#>`, `#>>`	left
3	unary `-`, unary `+`	right
4	`*`, `/`, `%`	left
5	`+`, `-`	left
6	`||`	left
7	`@>`, `<@`, `?`, `?|`, `?&`	left
8	`=`, `!=`, `<>`, `<`, `>`, `<=`, `>=`	left
9	`IS`, `IS NOT`, `IN`, `LIKE`, `ILIKE`, `BETWEEN`	left
10	`NOT`	right
11	`AND`	left
12	`OR`	left

Appendix B: Reserved Words

The following words are treated as reserved keywords and cannot be used as unquoted identifiers:

```
ALL, ALTER, ANALYZE, AND, ANY, ARRAY, AS, ASC, BEGIN, BETWEEN, BIGINT,
BIGSERIAL, BOOLEAN, BY, CASCADE, CASE, CAST, CHECK, COLUMN, COMMIT,
CONFLICT, CREATE, CROSS, CURRENT, DATE, DEALLOCATE, DECIMAL, DEFAULT,
DELETE, DESC, DISTINCT, DO, DROP, ELSE, END, EXCEPT, EXCLUDED, EXECUTE,
EXISTS, EXPLAIN, FALSE, FETCH, FILTER, FIRST, FLOAT, FOLLOWING, FOR,
FOREIGN, FROM, FULL, GROUP, HAVING, IF, ILIKE, IN, INDEX, INNER,
INSERT, INTEGER, INTERSECT, INTERVAL, INTO, IS, JOIN, JSON, JSONB, KEY,
LAST, LATERAL, LEFT, LIKE, LIMIT, NOT, NULL, NULLS, NUMERIC, OFFSET,
ON, ONLY, OR, ORDER, OUTER, OVER, PARTITION, PRECEDING, PREPARE,
PRIMARY, RANGE, REAL, RECURSIVE, REFERENCES, RELEASE, RENAME, RESTART,
RETURNING, RIGHT, ROLLBACK, ROWS, SAVEPOINT, SELECT, SEQUENCE, SERIAL,
SERVER, SET, SMALLINT, TABLE, TEMP, TEMPORARY, TEXT, THEN, TIMESTAMP,
TIMESTAMPTZ, TO, TRANSACTION, TRUE, TRUNCATE, UNBOUNDED, UNION, UNIQUE,
UPDATE, USING, UUID, VACUUM, VALUES, VARCHAR, VECTOR, VIEW, WHEN,
WHERE, WINDOW, WITH
```

Identifiers that collide with reserved words must be double-quoted: `"select"`, `"table"`.