

Core - Task # 60249

Epic # 58282 (Accepted): Workspaces Workpackage #2

Story # 58284 (New): Bug fixes & Behaviour

Status:	Resolved	Priority:	Must have
Author:	Oliver Hader	Category:	Workspaces
Created:	2014-07-10	Assigned To:	Oliver Hader
Updated:	2014-08-13	Due date:	
TYPO3 Version:	6.2		
PHP Version:	5.3		
Complexity:			
Sprint Focus:			
Subject:	Publishing delete placeholder affects different workspaces as well		
Description			
Scenario:			
<ul style="list-style-type: none">- having two workspaces (1 and 2)- having a live record with uid 10- having a delete placeholder for uid 10 in workspace 1- having a delete placeholder for uid 10 in workspace 2			
Action:			
<ul style="list-style-type: none">- publish the delete placholder for uid 10 in workspace 1			
Experience:			
<ul style="list-style-type: none">- published delete placeholder for uid 10 in workspace 2 (which was not the active workspace)			

Associated revisions

Revision bbbd8146 - 2014-08-13 16:30 - Oliver Hader

[BUGFIX] Publishing delete placeholder affects other workspaces

On publishing a delete placeholder all other versions shall be deleted as well, since the original record will be deleted after that action. However, this is only valid for the live workspace and using the legacy version behavior there.

DataHandler::deleteVersionsForRecord() calls BackendUtility::selectVersionsOfRecord(), but without the additional, but required, \$workspace argument. Thus, all other versions in other workspaces are deleted as well. The SQL query to determine versions needs to be limited to either the live workspace (for legacy versions) and the current workspace.

Resolves: #60249

Releases: master, 6.2

Change-Id: If90511dc4ac2bc3dde6e58570e6bf10e4ac949db

Reviewed-on: <http://review.typo3.org/31589>

Reviewed-by: Oliver Hader <oliver.hader@typo3.org>

Tested-by: Oliver Hader <oliver.hader@typo3.org>

Revision 6f945001 - 2014-08-13 16:31 - Oliver Hader

[BUGFIX] Publishing delete placeholder affects other workspaces

On publishing a delete placeholder all other versions shall be deleted as well, since the original record will be deleted after that action. However, this is only valid for the live workspace and using the legacy version behavior there.

DataHandler::deleteVersionsForRecord() calls BackendUtility::selectVersionsOfRecord(), but without the additional, but required, \$workspace argument. Thus, all other versions in other workspaces are deleted as well. The SQL query to determine versions needs to be limited to either the live workspace (for legacy versions) and the current workspace.

Resolves: #60249

Releases: master, 6.2

Change-Id: If90511dc4ac2bc3dde6e58570e6bf10e4ac949db

Reviewed-on: <http://review.typo3.org/32139>

Reviewed-by: Oliver Hader <oliver.hader@typo3.org>

Tested-by: Oliver Hader <oliver.hader@typo3.org>

History

#1 - 2014-07-11 11:22 - Gerrit Code Review

- Status changed from New to Under Review

Patch set 1 for branch **master** of project **Packages/TYPO3.CMS** has been pushed to the review server.

It is available at <https://review.typo3.org/31589>

#2 - 2014-08-13 16:30 - Gerrit Code Review

Patch set 2 for branch **master** of project **Packages/TYPO3.CMS** has been pushed to the review server.

It is available at <http://review.typo3.org/31589>

#3 - 2014-08-13 16:31 - Gerrit Code Review

Patch set 1 for branch **TYPO3_6-2** of project **Packages/TYPO3.CMS** has been pushed to the review server.

It is available at <http://review.typo3.org/32139>

#4 - 2014-08-13 17:00 - Oliver Hader

- Status changed from Under Review to Resolved

- % Done changed from 0 to 100

Applied in changeset commit:bbbd814622970061d47868f574aad72f974540e2.