

Core - Bug # 15617

Status:	Resolved	Priority:	Should have
Author:	old_hkdennis2k	Category:	
Created:	2006-02-13	Assigned To:	Christian Kuhn
Updated:	2009-03-20	Due date:	
TYPO3 Version:	3.8.1		
PHP Version:	5		
Complexity:			
Is Regression:			
Sprint Focus:			
Subject:	template->docType is not compatible with IE		
Description			
<p>If you set</p> <pre>\$SOBE->doc->docType='xhtml_trans';</pre> <p>IE may ignore Content-Type setting and using XML parser open the page.</p> <p>I am using UTF-8 in typo3.</p> <p>When php print unicode BOM and some empty lines at the beginning.</p> <p>I think these clause by include() / include_once()</p> <p>--- begin ---</p> <pre>C:\Perl\bin>get axS -H "User-Agent: Mozilla/4.0 (compatible; MSIE 6.0; Windows NT 5.1; SV1)" http://127.0.0.1/typo3/ more LWP::UserAgent::new: () LWP::UserAgent::request: () LWP::UserAgent::send_request: GET http://127.0.0.1/typo3/ LWP::UserAgent::_need_proxy: Not proxied LWP::Protocol::http::request: () Parsing of undecoded UTF-8 will give garbage when decoding entities at C:/Perl/site/lib/LWP/Protocol.pm line 114. LWP::Protocol::collect: read 243 bytes LWP::UserAgent::request: Simple response: OK GET http://127.0.0.1/typo3/ -> 200 OK &#8745;&#9559;&#9488;</pre> <pre><!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd"> ?xml-stylesheet href="#internalStyle" type="text/css"?> <html>.....TYPO3 print content following --- end ---</pre> <p>IE will ignore Content-Type and always using XML mode to read the content.</p> <p>(and it is not a valid xml because <html> don't have a default namespace)</p> <p>Software version</p> <pre>typo3 3.8.1 IE 6.0.2900.2180 apache 2.0.55 PHP 5.0.5 (cli) (built: Sep 5 2005 15:54:44) with eAccelerator v0.9.3-rc2</pre>			

Solution

add @ob_clean(); at the beginng of template-startPage()

typo3/template.php

```
function startPage($title) {  
  
    @ob_clean(); // FIX IE bug~!!!  
  
    +  
        // Get META tag containing the currently selected charset for backend output. The function sets $this->charSet.  
        $charSet = $this->initCharset();  
        $generator = $this->generator();
```

(issue imported from #M2549)

Related issues:

related to Core - Bug # 19038: template->startPage returns invalid XHTML

Resolved

2008-06-30

History

#1 - 2009-03-20 00:48 - Christian Kuhn

Resolved with unable to reproduce: I do not get any empty lines in current trunk (r5210) preceding the DOCTYPE tag.

The xmlns issue is reported with #20216.