TYPO3.Flow - Bug # 40410

Status:Needs FeedbackPriority:Should haveAuthor:Kobbe van DaatselaarCategory:CacheCreated:2012-08-30Assigned To:Karsten DambekalnsUpdated:2012-10-25Due date:

PHP Version: 5.3 Has patch: No

Complexity:

Affected Flow version: FLOW3 1.1.0

Subject: Exception when using Apc, Memcached of Redis cache backend for reflection status and object configuration

Description

When I configure to FLOW3 to use an other backend than the (Simple)FileBackend it throws an exception during compiletime:

14 TYPO3\FLOW3\Error\ErrorHandler::handleError(4096, "Argument 1 passed to

TYPO3\FLOW3\Object\ObjectManager::setObjects() must be an array, boolean given, called in

/Packages/Framework/TYPO3.FLOW3/Classes/Core/Booting/Scripts.php on line 292 and defined",

"/Packages/Framework/TYPO3.FLOW3/Classes/Object/ObjectManager.php", 92, array)

13 TYPO3\FLOW3\Object\ObjectManager::setObjects(boolean)

12 TYPO3\FLOW3\Core\Booting\Scripts::initializeObjectManager(TYPO3\FLOW3\Core\Bootstrap)

11 call_user_func(array, TYPO3\FLOW3\Core\Bootstrap)

10 TYPO3\FLOW3\Core\Booting\Step::__invoke(TYPO3\FLOW3\Core\Bootstrap)

9 TYPO3\FLOW3\Core\Booting\Sequence::invokeStep(TYPO3\FLOW3\Core\Booting\Step, TYPO3\FLOW3\Core\Bootstrap)

8 TYPO3\FLOW3\Core\Booting\Sequence::invokeStep(TYPO3\FLOW3\Core\Booting\Step, TYPO3\FLOW3\Core\Booting\Step, TYPO3\FLOW3\Co

7 TYPO3\FLOW3\Core\Booting\Sequence::invokeStep(TYPO3\FLOW3\Core\Booting\Step, TYPO3\FLOW3\Core\Bootstrap)

6 TYPO3\FLOW3\Core\Booting\Sequence::invokeStep(TYPO3\FLOW3\Core\Booting\Step, TYPO3\FLOW3\Core\Bootstrap)

5 TYPO3\FLOW3\Core\Booting\Sequence::invokeStep(TYPO3\FLOW3\Core\Booting\Step, TYPO3\FLOW3\Core\Bootstrap)

4 TYPO3\FLOW3\Core\Booting\Sequence::invoke(TYPO3\FLOW3\Core\Bootstrap)

3 TYPO3\FLOW3\Http\RequestHandler::boot()

2 TYPO3\FLOW3\Http\RequestHandler::handleRequest()

1 TYPO3\FLOW3\Core\Bootstrap::run()

This happens when I configure the Object_Configuration or Reflection_Status in Caches.yaml

FLOW3_Object_Configuration:

backend: TYPO3\FLOW3\Cache\Backend\ApcBackend

FLOW3 Reflection Status:

backend: TYPO3\FLOW3\Cache\Backend\ApcBackend

or

FLOW3_Object_Configuration:

backend: TYPO3\FLOW3\Cache\Backend\MemcachedBackend

backendOptions:

servers: - 127.0.0.1

FLOW3 Reflection Status:

backend: TYPO3\FLOW3\Cache\Backend\MemcachedBackend

2015-08-03 1/5

backendOptions: servers: - 127.0.0.1

or

FLOW3_Object_Configuration:

backend: TYPO3\FLOW3\Cache\Backend\RedisBackend

backendOptions: database: 3

compressionLevel: 0 FLOW3_Reflection_Status:

backend: TYPO3\FLOW3\Cache\Backend\RedisBackend

backendOptions: database: 4

compressionLevel: 0

History

#1 - 2012-09-12 11:21 - Karsten Dambekalns

- Status changed from New to Needs Feedback
- Assigned To set to Karsten Dambekalns

When using Redis it works for me, no exceptions whatsoever. APC and memcache fail with a variety of errors. Can you give more details on your errors?

#2 - 2012-09-26 13:00 - Kobbe van Daatselaar

APC (all done in production context)

REFLECTION STATUS

 ${\sf FLOW3_Reflection_Status:}$

backend: TYPO3\FLOW3\Cache\Backend\ApcBackend

I get the following error when compiling:

./flow3 flow3:core:compile

PHP Fatal error: Call to undefined method TYPO3\FLOW3\Cache\Backend\ApcBackend::initializeObject() in /www/hexia/Packages/Framework/TYPO3.FLOW3/Classes/Reflection/ReflectionService.php on line 189

PHP Stack trace:

PHP 1. {main}() /www/hexia/flow3:0

PHP 2. require() /www/hexia/flow3:28

2015-08-03 2/5

PHP 3. TYPO3\FLOW3\Core\Bootstrap->run() /www/hexia/Packages/Framework/TYPO3.FLOW3/Scripts/flow3.php:42

PHP 4. TYPO3\FLOW3\Cli\CommandRequestHandler->handleRequest()

/www/hexia/Packages/Framework/TYPO3.FLOW3/Classes/Core/Bootstrap.php:112

PHP 5. TYPO3\FLOW3\Cli\CommandRequestHandler->boot()

/www/hexia/Packages/Framework/TYPO3.FLOW3/Classes/Cli/CommandRequestHandler.php:91

PHP 6. TYPO3\FLOW3\Core\Booting\Sequence->invoke()

/www/hexia/Packages/Framework/TYPO3.FLOW3/Classes/Cli/CommandRequestHandler.php:147

PHP 7. TYPO3\FLOW3\Core\Booting\Sequence->invokeStep()

/www/hexia/Packages/Framework/TYPO3.FLOW3/Classes/Core/Booting/Sequence.php:73

PHP 8. TYPO3\FLOW3\Core\Booting\Sequence->invokeStep()

/www/hexia/Packages/Framework/TYPO3.FLOW3/Classes/Core/Booting/Sequence.php:93

PHP 9. TYPO3\FLOW3\Core\Booting\Sequence->invokeStep()

/www/hexia/Packages/Framework/TYPO3.FLOW3/Classes/Core/Booting/Sequence.php:93

PHP 10. TYPO3\FLOW3\Core\Booting\Sequence->invokeStep()

/www/hexia/Packages/Framework/TYPO3.FLOW3/Classes/Core/Booting/Sequence.php:93

PHP 11. TYPO3\FLOW3\Core\Booting\Sequence->invokeStep()

/www/hexia/Packages/Framework/TYPO3.FLOW3/Classes/Core/Booting/Sequence.php:93

PHP 12. TYPO3\FLOW3\Core\Booting\Step->__invoke()

/www/hexia/Packages/Framework/TYPO3.FLOW3/Classes/Core/Booting/Sequence.php:89

PHP 13. call_user_func() /www/hexia/Packages/Framework/TYPO3.FLOW3/Classes/Core/Booting/Step.php:49

PHP 14. TYPO3\FLOW3\Core\Booting\Scripts::initializeReflectionService()

/www/hexia/Packages/Framework/TYPO3.FLOW3/Classes/Core/Booting/Step.php:49

PHP 15. TYPO3\FLOW3\Reflection\ReflectionService->setStatusCache()

/www/hexia/Packages/Framework/TYPO3.FLOW3/Classes/Core/Booting/Scripts.php:316

OBJECT CONFIGURATION

FLOW3_Object_Configuration:

backend: TYPO3\FLOW3\Cache\Backend\ApcBackend

I get no error when running ./flow3 flow3:core:compile

But when I open a URL in my browser I get:

FLOW3: The compile run failed. Please check the error output or system log for more information.

There is no error in the logs:

12-09-26 10:55:22 2681	NOTICE	FLOW3	Unlocked site.
12-09-26 10:55:22 2685	NOTICE	FLOW3	Locking site. Lock file: /www/hexia/Data/Temporary/Production/FLOW3.lock
12-09-26 10:55:22 2685	INFO	FLOW3	Aspect classes have been modified, flushing the whole proxy classes cache.
12-09-26 10:55:22 2685	INFO	FLOW3	Domain model changes have been detected, triggering Doctrine 2 proxy rebuilding.
12-09-26 10:55:22 2685	INFO	FLOW3	File Monitor "FLOW3_ClassFiles" detected 1771 changed files and 13 changed
directories.			
12-09-26 10:55:22 2685	INFO	FLOW3	The security policies have changed, flushing the policy cache.
12-09-26 10:55:22 2685	INFO	FLOW3	A Routes.yaml file has been changed, flushing the routing cache.
12-09-26 10:55:22 2685	INFO	FLOW3	The configuration has changed, triggering an AOP proxy class rebuild.
12-09-26 10:55:22 2685	INFO	FLOW3	File Monitor "FLOW3_ConfigurationFiles" detected 63 changed files and 7 changed
directories.			
12-09-26 10:55:22 2685	INFO	FLOW3	The localization files have changed, thus flushing the I18n XML model cache.

2015-08-03 3/5

12-09-26 10:55:22 2685	INFO FLOW3	File Monitor "FLOW3_TranslationFiles" detected 7 changed files and 2 changed
directories.		
12-09-26 10:55:36 2685	INFO FLOW3	Reflected 947 emerged classes.
12-09-26 10:55:39 2685	INFO FLOW3	Aspects have been modified, therefore rebuilding all target classes.
12-09-26 10:55:45 2685	NOTICE FLOW3	Unlocked site.

#3 - 2012-09-26 13:15 - Kobbe van Daatselaar

MEMCACHED (all done in production context)

OBJECT CONFIGURATION

FLOW3_Object_Configuration:

backend: TYPO3\FLOW3\Cache\Backend\MemcachedBackend

backendOptions:

servers:

- 127.0.0.1

I get no error when running ./flow3 flow3:core:compile

But when I open a URL in my browser I get:

FLOW3: The compile run failed. Please check the error output or system log for more information.

There is no error in the logs:

12-09-26 11:14:37 2857	NOTICE	FLOW3	Unlocked site.
12-09-26 11:14:42 2863	NOTICE	FLOW3	Locking site. Lock file: /www/hexia/Data/Temporary/Production/FLOW3.lock
12-09-26 11:14:43 2863	INFO	FLOW3	Aspect classes have been modified, flushing the whole proxy classes cache.
12-09-26 11:14:43 2863	INFO	FLOW3	Domain model changes have been detected, triggering Doctrine 2 proxy rebuilding.
12-09-26 11:14:43 2863	INFO	FLOW3	File Monitor "FLOW3_ClassFiles" detected 1771 changed files and 13 changed
directories.			
12-09-26 11:14:43 2863	INFO	FLOW3	The security policies have changed, flushing the policy cache.
12-09-26 11:14:43 2863	INFO	FLOW3	A Routes.yaml file has been changed, flushing the routing cache.
12-09-26 11:14:43 2863	INFO	FLOW3	The configuration has changed, triggering an AOP proxy class rebuild.
12-09-26 11:14:43 2863	INFO	FLOW3	File Monitor "FLOW3_ConfigurationFiles" detected 63 changed files and 7 changed
directories.			
12-09-26 11:14:43 2863	INFO	FLOW3	The localization files have changed, thus flushing the I18n XML model cache.
12-09-26 11:14:43 2863	INFO	FLOW3	File Monitor "FLOW3_TranslationFiles" detected 7 changed files and 2 changed
directories.			
12-09-26 11:14:56 2863	INFO	FLOW3	Reflected 947 emerged classes.
12-09-26 11:14:59 2863	INFO	FLOW3	Aspects have been modified, therefore rebuilding all target classes.
12-09-26 11:15:07 2863	NOTICE	FLOW3	Unlocked site.

#4 - 2012-09-26 13:21 - Kobbe van Daatselaar

In general it would be nice if the caching segment of the documentation was updated with different backend setups (what can be cached and what

2015-08-03 4/5

frontend / backend can be used).

Apparently not all combinations can be used. For example: reflection data can only be cached on disk (which is slow) but it contains the largest amount of data.

#5 - 2012-10-25 15:56 - Thomas Plessis

Kobbe van Daatselaar wrote:

In general it would be nice if the caching segment of the documentation was updated with different backend setups (what can be cached and what frontend / backend can be used).

Agreed with that too! :) I'm a bit confused with all those system cache.

2015-08-03 5/5