

ICC

1 Info

Procedure used here is based Muraki et al. (2022)

- Muraki, E. J., Abdalla, S., Brysbaert, M., & Pexman, P. M. (2022). Concreteness ratings for 62,000 English multiword expressions. Behavior Research Methods. <https://doi.org/10.3758/s13428-022-01912-6>

2 Imports

```
knitr::opts_chunk$set(echo = TRUE)
library(tidyverse)
library(moments)
library(tm) #Function to remove strings
library(reshape2) #for data manipulation
library(nlme) #for ICC
library(multilevel) #for ICC
library(arsenal) #for dataframe comparisons
library(jtools) #for theme_apa function for plots
library(apaTables) #for APA format tables
library(fuzzyjoin)
```

3 GSD (sentences, gold standard)

3.1 Load data

```
dir0 <- "../data/u1001_gold_standard_nlp_bert/"
if0 <- "long.csv"

ratings_icc <- read_csv(file = file.path(dir0, if0))
spec(ratings_icc)
ratings_icc
```

```
indexing long.csv [=====] 18.31GB/s, eta: 0s
```

```
Rows: 9000 Columns: 3
  Column specification
Delimiter: ","
chr (1): PID
dbl (2): SENT, EVAL
```

Use ``spec()`` to retrieve the full column specification for this data.
Specify the column types or set ``show_col_types = FALSE`` to quiet this message.

```
cols(
  PID = col_character(),
  SENT = col_double(),
  EVAL = col_double()
)
# A tibble: 9,000 × 3
  PID          SENT EVAL
  <chr>      <dbl> <dbl>
1 6282ac6bddcf580b46bdef2d      1    -2
2 5b737a81f80f680001b60f85      1    -2
3 5997e57d6b939900012da0e2      1     0
4 5ba8ba00d9c1080001fa4193      1     0
5 6110ce792276c9f74115dbd2      1     0
6 56220229ed6e5a0005c7fac1      1     1
7 5e346dedaf532102529ce9da      1    -1
8 5edbaae1b9f9f68349ce80f3      1    -2
9 63f779120de2ae5b2620ce9b      1     0
10 63ed42100168a762350b416f      1     1
# 8,990 more rows
# Use `print(n = ...)` to see more rows
```

3.2 ICC

```
#Calculate ICC based on function from psychometric package but customized optimizer (see Brysbaert)
#Run multilevel model with optimizer set to optim
attach(ratings_icc)
mod <- lme(EVAL ~ 1, random = ~1 | SENT, na.action = na.omit, control = lmeControl(opt = "optim"))
detach(ratings_icc)
#Extract intercept variance
t0 <- as.numeric(VarCorr(mod)[1,1])
#Extract residual variance
sig2 <- as.numeric(VarCorr(mod)[2,1])
#Calculate ICC based on intercept and residual variance
icc1 <- t0/(t0 + sig2)
#Calculate mean ICC across all group ICCs
# icc2 <- mean(GmeanRel(mod)$MeanRel)
icc2 <- mean(gmeanrel(mod)$MeanRel)
paste(icc1)
paste(icc2)
```

[1] "0.720399837021778"

[1] "0.987221876053856"

References

Muraki, E. J., Abdalla, S., Brysbaert, M., & Pexman, P. M. (2022). Concreteness ratings for 62,000 English multiword expressions. *Behavior Research Methods*. <https://doi.org/10.3758/s13428-022-01912-6> (cit. on p. 1)