

CS450

Structure of Higher Level Languages

Lecture 1: Course info, arithmetic in Racket, evaluation

Tiago Cogumbreiro

About the course

- **Instructor:** Tiago (蒂亚戈) Cogumbreiro (he/him)

How to reach me

- **Office hours** in person (have priority), or remotely via Zoom
- **Announcements** in #cs450-news-2 (Discord)
- **Q&A** in #cs450-2 (Discord)



How we are doing remote teaching

- **Open door policy, via Discord.**
 - Message me at any time, any day with your questions.
 - Channel questions answered first, direct-messages answered second.
 - I reply as soon as possible, during office hours in the latest.
- **Homework assignments** we use a grading server (Gradescope)

Course webpage

cogumbreiro.github.io/teaching/cs450/f26-2/

Syllabus

cogumbreiro.github.io/teaching/cs450/f26-2/syllabus.pdf

A	A-	B+	B	B-	C+	C	C-	D+	D	D-	F
100..95	94..90	89..85	84..80	79..75	74..70	69..65	59..55	54..50	49..45	44..40	39..0

- Course divided into 9 modules
- 1 homework assignment per module
- Final grade: 95% homework + 5% participation
- *Homework grade*: average of **9 assignments** (possibly weighted)
- **You must pass 7** out of 9 assignments. If you fail 3 or more assignments (<40 points), then you fail the course.

Course requirements

Course requirements

Checklist

- Install Racket ≥ 8.2 : racket-lang.org
- Sign in on GitLab (invitation by email)
- Sign in on Discord, say "Hi" in [#cs450-lounge-2](#) (invitation link in the GitLab page)
- Sign in on Gradescope, upload the template `hw1.rkt` (invitation by email)

Heads up

- Please, **register using your UMB email address**, otherwise you won't be able to submit your first homework.
- The deadline of homework assignment n is last class of module n plus 1 week



Why learn the Structure of Higher Level Languages?

Structure of Higher Level Languages

I postponed this discussion, because I felt that you are now better suited to understand and relate to the points being made.

- Why learn the fundamental concepts in all programming languages?
- Why learn different languages?
- Why focus on functional programming?
- Why use Racket?

Disclaimer

- Most of these claims are opinions
- These will be mostly informal claims
- We are **not** trying to find the best language (or programming model)



Overview

- Languages are just tools, learn which language is amenable to what context
- The best programming language does not exist (theoretically most languages are equivalent)
- Different languages have different characteristics that favor different domains: for instance, functional languages being used in Programming Language research, C/Fortran in scientific/high-performance computing
- A programming language is a computing interface: it is crucial to understand its meaning
- The importance of first-class functions and avoiding mutation

Semantics and idioms

Why should we care about language semantics?

- **A language is a *computing user interface*.**
We are learning reusable, cross-cutting patterns.
- **The semantics must be *unambiguous and precise*.**
It is not a matter of personal opinion how a conditional expression works. Language features must be described unambiguously to users.
- **The semantics defines a software contract.**
Is the bug in the client's bug, or is it in our code?
- **Language idioms (patterns) are transferrable knowledge.**
Understanding idioms (patterns) teaches you something that can be applied across languages and technologies.

How are all languages similar?

How are all languages the same?

- **Theoretical:** Any input-output behavior implementable in language X is implementable in language Y (Church-Turing thesis), and *equivalent to the λ -calculus without numbers*
- **Practical:** Reoccurring fundamentals: variables, abstraction, recursive definitions

How are languages different?

Disclaimer

Languages are not slow/fast

- A language **implementation** is fast/slow, not the language itself
- Certain languages computational models are more amenable to implement efficiently
- Languages are user interfaces of computational models

How different languages behave in different contexts?

Why is C faster than all other languages?

Is it because C is "close to the metal?" That is, is C fast because its semantics matches the processor's semantics?

Why is C faster than all other languages?

Is it because C is "close to the metal?" That is, is C fast because its semantics matches the processor's semantics? **No!**

- Which processor? How could it match the semantics of all processors?
- Which compiler? The key of C's success lays in having good compilers.
- C compilers are fast because C is **old and its interface remains stable!**
- Popular C compilers are **really** good at optimizing the target language.
- There is a set of good practices to write optimizer-ready C code

Take away

The facts above make C quite successful in High Performance Computing (large scale scientific codes).

Source: *C Is Not a Low-level Language: Your computer is not a fast PDP-11.* David Chisnall. ACM Queue vol. 16, no. 2, 2018



Why is Python slow multithreading?

- CPython (the main implementation of Python) is conditioned by the GIL (the Global Interpreter Lock) which effectively serializes parallel execution
- To parallelize code we must run multiple processes, where shared memory is especially slow, which, in turn, slows down compute-bound programs

Take away

■ Avoid running compute-bound parallel codes in Python. Maybe choose C?

Source: [Global Interpreter Lock. Python Wiki. Last edit in 2017, accessed in 2019.](#)

Constraint language programming

We solve the equation `SEND+MORE=MONEY` where each letter represents a digit in Prolog using a constraint language programming module:

```
sendmore(Digits) :-                               % Source: https://en.wikipedia.org/wiki/Constraint_programming
    Digits = [S,E,N,D,M,O,R,E],                  % Create variables
    Digits ins 0..9,                               % Associate domains to variables
    S #\= 0,                                         % Constraint: S must be different from 0
    M #\= 0,
    all_different(Digits),                          % all the elements must take different values
    1000*S + 100*E + 10*N + D                      % Other constraints
    + 1000*M + 100*O + 10*R + E
    #= 10000*M + 1000*O + 100*N + 10*E + Y,
    label(Digits).                                 % Start the search
```

Take away

Some problems are more amenable to certain programming languages.



How are languages different?

1. **The implementation matters:** A language implementation may be conditioned (faster/slower) in certain contexts
2. **The model matters:** Certain problems are simpler/more efficient to write in specific languages
3. **The domain matters:** A technology your business needs may only be available in some language (say TensorFlow in Python)

Why learn different languages?

■ Learn at least one new language every year.

Source: *The Pragmatic Programmer*. Andrew Hunt and David Thomas. 1999.

Why should you care

- Deeper understanding of the differences and the similarities between languages
- Learn different approaches to the same problems
- More job opportunities
- Better technology choices (some technologies are only available in specific languages)

Why functional programming?

What is functional programming?

- Mutation is discouraged
- Higher-order functions serve as a generalization device

Why should we care?

- These features help designing correct, elegant, and efficient software
- Functional programming languages are heavily favored by PL researchers, which means they serve as **a test bed for PL design**. Functional programming is close(r) to math formalism, thus implementation is usually simpler in functional programming languages.
- **Functional programming is trendy!** C++/Java/C#/Python/JavaScript are all incorporating functional programming idioms.



Why should we discourage mutation?

- Simpler to reason about: no surprises passing a data-structure to functions/objects
- Concurrency-ready: read-only means no race conditions (and no locks), which leads to simpler, faster code

Who is using it?

- `immutable.js` for JavaScript by Facebook
- `vavr`, `PCollections`, the Scala runtime, and the Closure runtime for Java
- `immer` for C++
- immutable collections for .NET

Why should we use higher-order functions?

- Simpler interface than objects (which method? which order?)
- Can be combined effectively (frameworks on combining functions)

A researcher's Petri Dish

Most programming languages features started out in functional programming languages.

- Garbage collection (LISP, 1959)
- Generics (Hindley-Milner-Damas type system 1969/1978, implemented in ML in ~1977)
- Higher-order functions (lambda expressions in C++, C#, Java, Python) introduced in LISP (1959) and in ISWIM (1966)
- Type inference, e.g., auto in C++, var in C# (Hindley-Milner-Damas)
- Algebraic-data types and pattern matching (1970s in Hope)
- Recursion

A new wave of languages

■ Many new interesting programming languages

- Swift: next-generation programming language for Apple systems
- Rust: functional programming meets system programming
- F#: an ML derivate for the .NET ecosystem
- Elixir: highly-available distributed system
- Clojure: a LISP-influenced language for the JVM and the web

How are we using functional programming ?

- **OCaml**: web development (Facebook/Meta), distributed systems (Docker), finance (Tezos, Jane Street, Bloomberg, Aesthetic Integration), hardware virtualization (Citrix)
- **Haskell**: verification (Facebook), distributed systems (Google), compilers (Intel), distributed systems (Microsoft)
- **Erlang**: communication (WhatsApp), ads (AddRoll), web backend (Bet365), finance (Goldman Sachs)
- **Elixir**: spam prevention (Pinterest), micro services (Lonely Planet)
- **F#**: data analysis (Kaggle), trading (Credit Suisse), gaming backend (GameSys)
- **Racket** game scripting (Naughty Dog), image processing (YouPatch)
- **Scala** middleware (Twitter), database (Netflix), microservices (Tumblr), web (The Guardian)

Honorable mentions

- ReasonML, Elm, PureScript, ClojureScript



Course overview

This course is **NOT**...

- **on algorithms**

For a nice free book read [Algorithms](#) by Jeff Erickson.

- **an introduction on programming and computing**

For a nice free book read [How to design programs](#) by Matthias Felleisen, Robert Bruce Findler, Matthew Flatt, Shriram Krishnamurthi

- **on programming with Racket**

For a nice free book read [The Racket Guide](#) by Matthew Flatt, Robert Bruce Findler, and PLT

This course is...

- **on designing programming language features**

We will focus mainly on functional and object-oriented programming.

- **on semi-formal specification**

We will drive our course with precise mathematical notations and tests.

- **on programming patterns**

We will characterize patterns and study abstractions of these patterns.

- **on purely functional programming**

We will approach programming without using assignment (mutation).

Today we will learn

- a formalism to describe a programming language (Racket)
- the semantics of a programming language

How we will learn it

■ We introduce one language feature at a time

1. **Syntax:** We formalize each language feature (What)
2. **Example:** We illustrate a feature with an example
3. **Semantics:** We introduce how each language feature works (How)

Semantics

- *Abstract Syntax*: how we write something. Example, which characters/string we use write a keyword, or a number.
- *Semantics*: what that something does/means (evaluation here means as the program runs)

In this class, we focus on the **semantics** of programming languages. We define the semantics of some programming language features.

1. We shall *not* print to output!

Instead, we will use *assertions*.

2. We shall *not* mutate variables!

Instead, we will use *persistent data structures*.

3. We shall *not* use loops!

Instead, we will use *recursion*.

Your first program

Program

In Racket, **everything evaluates down to or is a value**. A Racket program consists of a preamble followed by zero or more expressions:

```
program = #lang racket expression*
```

1. Racket has no end-of-sentence delimiters (contrary to, say, C-like languages which use semi-colons)
2. Racket evaluates each expression from top-to-bottom, left-to-right

■ For space-constraint reasons, code listings might omit the preamble.

Language specification

- **Grayed out text** represents the concrete syntax
- *Italic text* represents a meta-variable

Expressions

Expressions can be values, among other things

```
expression = value | ...
```

Values

- **Numbers**
- Void
- Booleans
- Lists
- ...

Numbers

Numbers

All numbers are complex numbers. Some of them are real numbers, and all of the real numbers that can be represented are also rational numbers, except for `+inf.0` (positive infinity), `+inf.f` (single-precision variant), `-inf.0` (negative infinity), `-inf.f` (single-precision variant), `+nan.0` (not-a-number), and `+nan.f` (single-precision variant). Among the rational numbers, some are integers, because `round` applied to the number produces the same number.

Source: [Racket Manual, Section 4.2](#)

Hello, Numbers!

Your first Racket program

```
#lang racket
10      ; A positive number
+10     ; The plus sign is optional
-10     ; A negative number
0+1i    ; A complex number
1/3     ; A rational number
0.33    ; A floating-point number
```

```
$ racket nums.rkt
10
10
-10
0+1i
1/3
0.33
```

Note: a semi-colon (;) initiates a comment section, which is ignored in Racket. A semi-colon is **not** a end-of-line marker, like in C-like languages.

Expressions are separated by white-space

These two programs are equal:

```
#lang racket
10
+10
-10
0+1i
1/3
0.33
```

```
#lang racket
10 +10 -10      0+1i 1/3 0.33
```

Caveats: `-1` is different than `- 1` (notice the white space in between both characters). The former is the negative one, the latter is the expression `-` and the value `1`. Similarly, `1/3` is a single rational number, whereas `1 / 3` are three expressions.

Function calls

Function call

Delimited by parenthesis and its constituents are separated by white-space characters. The first expression must evaluate to a function, the remaining expressions are the arguments. Each expression is evaluated to a value from left-to-right before applying the function.

```
expression = value | variable | function-call | ...  
function-call = ( expression-func expression-arg* )
```

For instance, function call `(expt 2 3)`, for exponentiation, returns `2` raised to the power of `3`. Function `sin` computes the sine function of its sole argument.

```
#lang racket  
(expt 2 3)  
(sin (expt 2 3))
```

```
$ racket nums-func.rkt  
8  
0.9893582466233818
```

Note: Function calls can be compounded, as the parameters of a function are arguments too.

No infix notation in Racket

There is **NO INFIX NOTATION** for arithmetic operations (unlike most languages).

The usual arithmetic operations are all just variables: addition `+`, subtraction `-`, multiplication `*`, division `/`.

Example:

```
( * 3.14159 ( * 10 10))  
| | |      | | | → Number  
| | |      | | | → Number  
| | |      | | → Variable  
| | |      | → Function call  
| | | → Number  
| | → Variable  
| → Function call
```

Note: In Racket parenthesis represent function application. Contrasted with most C-like languages where parenthesis in expressions are optional and only there to help the reader.

