

EVENT time: 18.705740, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: aaaaaaaaaaaaaaaaaa
- Sending Message: aaaaaaaaaaaaaaaaaa ack# = 0 seq# = 0
- Started timer

EVENT time: 24.170835, type: 2, fromlayer3 entity: 1

- B side received packet: aaaaaaaaaaaaaaaaaa ack# = 0 seq# = 0
- B side received valid packet.
- Sending pkt to upper layer.
- B side sending ACK for packet with highest in-order sequence number
- B side sent ACK: ACK ack# = 0 seq# = 0
- TOLAYER3: packet being corrupted

EVENT time: 29.402449, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 0 seq# = 999999
- A side received corrupt packet :(

EVENT time: 35.124840, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: bbbbbbbbbbbbbbbbbbbb
- Sending Message: bbbbbbbbbbbbbbbbbbbb ack# = 1 seq# = 1
- TOLAYER3: packet being lost.

EVENT time: 37.680447, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: cccccccccccccccccc
- Sending Message: cccccccccccccccccc ack# = 2 seq# = 2
- TOLAYER3: packet being corrupted

EVENT time: 38.705742, type: 0, timerinterrupt entity: 0

- TIMEOUT - timer restarted,
- all packets in window resent
- Sending Message: aaaaaaaaaaaaaaaaaa ack# = 0 seq# = 0
- TOLAYER3: packet being lost.
- Sending Message: bbbbbbbbbbbbbbbbbbbb ack# = 1 seq# = 1
- Sending Message: cccccccccccccccccc ack# = 2 seq# = 2

EVENT time: 42.147713, type: 2, fromlayer3 entity: 1

- B side received packet: Zccccccccccccccccc ack# = 2 seq# = 2
- B side received corrupted packet.
- B side sending ACK for packet with highest in-order sequence number
- B side sent ACK: ACK ack# = 0 seq# = 0
- TOLAYER3: packet being corrupted

EVENT time: 46.394402, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: dddddddddddddddddd
- Sending Message: dddddddddddddddddd ack# = 3 seq# = 3

TOLAYER3: packet being lost.

EVENT time: 51.166374, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ZCK ack# = 0 seq# = 0
- A side received corrupt packet :(

EVENT time: 51.576138, type: 2, fromlayer3 entity: 1

- B side received packet: bbbbbbbbbbbbbbbbbbb ack# = 1 seq# = 1
- B side received valid packet.  
Sending pkt to upper layer.
- B side sending ACK for packet with highest  
in-order sequence number
- B side sent ACK: ACK ack# = 1 seq# = 1  
TOLAYER3: packet being corrupted

EVENT time: 53.202408, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: eeeeeeeeeeeeeeeeeee
- Sending Message: eeeeeeeeeeeeeeeeeee ack# = 4 seq# = 4

EVENT time: 57.152939, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ZCK ack# = 1 seq# = 1
- A side received corrupt packet :(

EVENT time: 58.705742, type: 0, timerinterrupt entity: 0

- TIMEOUT - timer restarted,  
all packets in window resent
  - Sending Message: aaaaaaaaaaaaaaaaaaa ack# = 0 seq# = 0  
TOLAYER3: packet being lost.
  - Sending Message: bbbbbbbbbbbbbbbbbbb ack# = 1 seq# = 1  
TOLAYER3: packet being corrupted
  - Sending Message: ccccccccccccccccccc ack# = 2 seq# = 2
  - Sending Message: dddddddddddddddddd ack# = 3 seq# = 3  
TOLAYER3: packet being lost.
  - Sending Message: eeeeeeeeeeeeeeeeeee ack# = 4 seq# = 4

EVENT time: 59.039051, type: 2, fromlayer3 entity: 1

- B side received packet: ccccccccccccccccccc ack# = 2 seq# = 2
- B side received valid packet.  
Sending pkt to upper layer.
- B side sending ACK for packet with highest  
in-order sequence number
- B side sent ACK: ACK ack# = 2 seq# = 2  
TOLAYER3: packet being corrupted

EVENT time: 63.197636, type: 2, fromlayer3 entity: 1

- B side received packet: eeeeeeeeeeeeeeeeeee ack# = 4 seq# = 4
- B side received a packet with a greater  
sequence number than expected. Expected

3, got 4.

Discarding packet...

- B side sending ACK for packet with highest  
in-order sequence number

- B side sent ACK: ACK ack# = 2 seq# = 2  
TOLAYER3: packet being corrupted

EVENT time: 64.617668, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ZCK ack# = 2 seq# = 2  
- A side received corrupt packet :(

EVENT time: 69.035599, type: 2, fromlayer3 entity: 1

- B side received packet: Zbbbbbbbbbbbbbbbbbb ack# = 1 seq# = 1  
- B side received corrupted packet.  
- B side sending ACK for packet with highest  
in-order sequence number  
- B side sent ACK: ACK ack# = 2 seq# = 2

EVENT time: 70.867599, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ZCK ack# = 2 seq# = 2  
- A side received corrupt packet :(

EVENT time: 70.910789, type: 2, fromlayer3 entity: 1

- B side received packet: ccccccccccccccccccc ack# = 2 seq# = 2  
- B side received a packet with a lower  
sequence number than expected. Expected  
3, got 2.  
Discarding packet...  
- B side sending ACK for packet with highest  
in-order sequence number  
- B side sent ACK: ACK ack# = 2 seq# = 2

EVENT time: 72.217178, type: 2, fromlayer3 entity: 1

- B side received packet: eeeeeeeeeeeeeeeeeee ack# = 4 seq# = 4  
- B side received a packet with a greater  
sequence number than expected. Expected  
3, got 4.  
Discarding packet...  
- B side sending ACK for packet with highest  
in-order sequence number  
- B side sent ACK: ACK ack# = 2 seq# = 2

EVENT time: 72.839478, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: ffffffffffffffffffffff  
- Sending Message: ffffffffffffffffffffff ack# = 5 seq# = 5

EVENT time: 73.456062, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: gggggggggggggggggggggg

- Sending Message: gggggggggggggggggggggg ack# = 6 seq# = 6  
TOLAYER3: packet being lost.

EVENT time: 75.686882, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 2 seq# = 2

- A side received valid packet.

\*\* 3 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

- Updating sending window...

- Updated ACKS, restarted timer to reflect the oldest packet in the sending window.

- A side making sure all packets in sending window have been sent to B side...

- Message in window, already sent: ddddddddddddddddddd ack# = 3 seq# = 3

- Message in window, already sent: eeeeeeeeeeeeeeeeeee ack# = 4 seq# = 4

- Message in window, already sent: ffffffffffffffffffff ack# = 5 seq# = 5

- Message in window, already sent: gggggggggggggggggggggg ack# = 6 seq# = 6

EVENT time: 76.283989, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: hhhhhhhhhhhhhhhhhhhh

- Sending Message: hhhhhhhhhhhhhhhhhhhh ack# = 7 seq# = 7  
TOLAYER3: packet being lost.

EVENT time: 78.458145, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: iiiiiiiiiiiiiiiiii

- Sending Message: iiiiiiiiiiiiiiiiii ack# = 8 seq# = 8  
TOLAYER3: packet being lost.

EVENT time: 82.230896, type: 2, fromlayer3 entity: 1

- B side received packet: ffffffffffffffffffff ack# = 5 seq# = 5

- B side received a packet with a greater sequence number than expected. Expected 3, got 5.

Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 2 seq# = 2  
TOLAYER3: packet being lost.

EVENT time: 82.674294, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: jjjjjjjjjjjjjjjjjjj

- Sending Message: jjjjjjjjjjjjjjjjjjj ack# = 9 seq# = 9  
TOLAYER3: packet being lost.

EVENT time: 85.082962, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 2 seq# = 2

- A side received valid packet.

\*\* 3 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

```
EVENT time: 94.315727,  type: 2, fromlayer3  entity: 0
- A side received from Lower Layer:      ACK                ack# = 2    seq# = 2
- A side received valid packet.
** 3 MESSAGES HAVE BEEN SENT SUCCESSFULLY **

EVENT time: 95.686882,  type: 0, timerinterrupt  entity: 0
- TIMEOUT - timer restarted,
  all packets in window resent
  - Sending Message:      ddddddddddddddddddd  ack# = 3    seq# = 3
  - Sending Message:      eeeeeeeeeeeeeeeeeee  ack# = 4    seq# = 4
  - Sending Message:      ffffffffffffffffffff  ack# = 5    seq# = 5
    TOLAYER3: packet being lost.
  - Sending Message:      ggggggggggggggggggg  ack# = 6    seq# = 6
  - Sending Message:      hhhhhhhhhhhhhhhhhhh  ack# = 7    seq# = 7
    TOLAYER3: packet being corrupted
  - Sending Message:      iiiiiiiiiiiiiiiiii  ack# = 8    seq# = 8
    TOLAYER3: packet being lost.
  - Sending Message:      jjjjjjjjjjjjjjjjjj  ack# = 9    seq# = 9

EVENT time: 97.658607,  type: 1, fromlayer5  entity: 0
- A side received message from upper layer:  kkkkkkkkkkkkkkkkkkk
- Sending Message:      kkkkkkkkkkkkkkkkkkk  ack# = 10   seq# = 10

EVENT time: 98.703918,  type: 2, fromlayer3  entity: 1
- B side received packet:      ddddddddddddddd  ack# = 3    seq# = 3
- B side received valid packet.
  Sending pkt to upper layer.
- B side sending ACK for packet with highest
  in-order sequence number
- B side sent ACK:      ACK                ack# = 3    seq# = 3

EVENT time: 103.457977,  type: 2, fromlayer3  entity: 1
- B side received packet:      eeeeeeeeeeeeeeeee  ack# = 4    seq# = 4
- B side received valid packet.
  Sending pkt to upper layer.
- B side sending ACK for packet with highest
  in-order sequence number
- B side sent ACK:      ACK                ack# = 4    seq# = 4

EVENT time: 108.551895,  type: 2, fromlayer3  entity: 0
- A side received from Lower Layer:      ACK                ack# = 3    seq# = 3
- A side received valid packet.
** 4 MESSAGES HAVE BEEN SENT SUCCESSFULLY **
- Updating sending window...
- Updated ACKS, restarted timer to reflect
  the oldest packet in the sending window.
- A side making sure all packets in sending
  window have been sent to B side...
```

- Message in window, already sent:	eeeeeeeeeeeeeeeeeeee	ack# = 4	seq# = 4
- Message in window, already sent:	ffffffffffffffffffff	ack# = 5	seq# = 5
- Message in window, already sent:	gggggggggggggggggg	ack# = 6	seq# = 6
- Message in window, already sent:	hhhhhhhhhhhhhhhhhh	ack# = 7	seq# = 7
- Message in window, already sent:	iiiiiiiiiiiiiiiiiii	ack# = 8	seq# = 8
- Message in window, already sent:	jjjjjjjjjjjjjjjjjj	ack# = 9	seq# = 9
- Message in window, already sent:	kkkkkkkkkkkkkkkkkk	ack# = 10	seq# = 10

EVENT time: 109.442078, type: 2, fromlayer3 entity: 1

- B side received packet: gggggggggggggggggggg ack# = 6 seq# = 6
- B side received a packet with a greater sequence number than expected. Expected 5, got 6.
- Discarding packet...
- B side sending ACK for packet with highest in-order sequence number
- B side sent ACK: ACK ack# = 4 seq# = 4

EVENT time: 111.297134, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 4 seq# = 4
- A side received valid packet.
- \*\* 5 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*
- Updating sending window...
- Updated ACKS, restarted timer to reflect the oldest packet in the sending window.
- A side making sure all packets in sending window have been sent to B side...
 

- Message in window, already sent:	ffffffffffffffffffff	ack# = 5	seq# = 5
- Message in window, already sent:	gggggggggggggggggg	ack# = 6	seq# = 6
- Message in window, already sent:	hhhhhhhhhhhhhhhhhh	ack# = 7	seq# = 7
- Message in window, already sent:	iiiiiiiiiiiiiiiiiii	ack# = 8	seq# = 8
- Message in window, already sent:	jjjjjjjjjjjjjjjjjj	ack# = 9	seq# = 9
- Message in window, already sent:	kkkkkkkkkkkkkkkkkk	ack# = 10	seq# = 10

EVENT time: 113.437668, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: 111111111111111111
- Sending Message: 111111111111111111 ack# = 11 seq# = 11
- TOLAYER3: packet being lost.

EVENT time: 117.304016, type: 2, fromlayer3 entity: 1

- B side received packet: hhhhhhhhhhhhhhhhhhh ack# = 7 seq# = 999999
- B side received corrupted packet.
- B side sending ACK for packet with highest in-order sequence number
- B side sent ACK: ACK ack# = 4 seq# = 4

EVENT time: 119.658302, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: mmmmmmmmmmmmmmmmmmm



- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 4 seq# = 4

TOLAYER3: packet being corrupted

EVENT time: 134.724152, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: nnnnnnnnnnnnnnnnnnnnn

- Packet 13 buffered in sending buffer.

EVENT time: 135.236816, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 999999 seq# = 4

- A side received corrupt packet :(

EVENT time: 139.988739, type: 2, fromlayer3 entity: 1

- B side received packet: Zfffffffffffffffffffff ack# = 5 seq# = 5

- B side received corrupted packet.

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 4 seq# = 4

EVENT time: 141.196960, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: oooooooooooooooooooooo

- Packet 14 buffered in sending buffer.

EVENT time: 148.249649, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: ppppppppppppppppppppp

- Packet 15 buffered in sending buffer.

EVENT time: 148.811859, type: 2, fromlayer3 entity: 1

- B side received packet: Zggggggggggggggggggggg ack# = 6 seq# = 6

- B side received corrupted packet.

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 4 seq# = 4

EVENT time: 149.111435, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 4 seq# = 4

- A side received valid packet.

\*\* 5 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 150.395721, type: 2, fromlayer3 entity: 1

- B side received packet: Zhhhhhhhhhhhhhhhhhhh ack# = 7 seq# = 7

- B side received corrupted packet.

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 4 seq# = 4

EVENT time: 151.297134, type: 0, timerinterrupt entity: 0



- TIMEOUT - timer restarted,  
all packets in window resent

- Sending Message:	fffffffffffffffffffff	ack# = 5	seq# = 5
- Sending Message:	gggggggggggggggggggg	ack# = 6	seq# = 6
TOLAYER3: packet being corrupted			
- Sending Message:	hhhhhhhhhhhhhhhhhhhh	ack# = 7	seq# = 7
- Sending Message:	iiiiiiiiiiiiiiiiiiii	ack# = 8	seq# = 8
- Sending Message:	jjjjjjjjjjjjjjjjjjjj	ack# = 9	seq# = 9
- Sending Message:	kkkkkkkkkkkkkkkkkkkk	ack# = 10	seq# = 10
- Sending Message:	llllllllllllllllllll	ack# = 11	seq# = 11
- Sending Message:	mmmmmmmmmmmmmmmmmmmm	ack# = 12	seq# = 12

TOLAYER3: packet being corrupted

EVENT time: 155.642853, type: 2, fromlayer3 entity: 1

- B side received packet: iiiiiiiiiiiiiiiiiiiiii ack# = 8 seq# = 8

- B side received a packet with a greater sequence number than expected. Expected 5, got 8.

Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 4 seq# = 4

EVENT time: 156.713440, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 4 seq# = 4

- A side received valid packet.

\*\* 5 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 163.684784, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: qqqqqqqqqqqqqqqqqqq

- Packet 16 buffered in sending buffer.

EVENT time: 164.586594, type: 2, fromlayer3 entity: 1

- B side received packet: Zjjjjjjjjjjjjjjjjjjjj ack# = 9 seq# = 9

- B side received corrupted packet.

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 4 seq# = 4

TOLAYER3: packet being lost.

EVENT time: 165.844330, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 4 seq# = 4

- A side received valid packet.

\*\* 5 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 170.383362, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: rrrrrrrrrrrrrrrrrrrr

- Packet 17 buffered in sending buffer.

EVENT time: 171.297134, type: 0, timerinterrupt entity: 0

- TIMEOUT - timer restarted,  
all packets in window resent
  - Sending Message: ffffffffffffffffffffffff ack# = 5 seq# = 5
  - Sending Message: gggggggggggggggggggggg ack# = 6 seq# = 6
  - Sending Message: hhhhhhhhhhhhhhhhhhhh ack# = 7 seq# = 7
  - Sending Message: iiiiiiiiiiiiiiiiii ack# = 8 seq# = 8
  - Sending Message: jjjjjjjjjjjjjjjjjjjj ack# = 9 seq# = 9
  - TOLAYER3: packet being lost.
  - Sending Message: kkkkkkkkkkkkkkkkkkkk ack# = 10 seq# = 10
  - TOLAYER3: packet being corrupted
  - Sending Message: llllllllllllllllllll ack# = 11 seq# = 11
  - Sending Message: mmmmmmmmmmmmmmmmmm ack# = 12 seq# = 12

EVENT time: 172.349716, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 4 seq# = 4
- A side received valid packet.

\*\* 5 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 173.909042, type: 2, fromlayer3 entity: 1

- B side received packet: Zkkkkkkkkkkkkkkkkkkk ack# = 10 seq# = 10
- B side received corrupted packet.
- B side sending ACK for packet with highest in-order sequence number
- B side sent ACK: ACK ack# = 4 seq# = 4
- TOLAYER3: packet being corrupted

EVENT time: 175.808777, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: ssssssssssssssssssss
- Packet 18 buffered in sending buffer.

EVENT time: 176.322769, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ZCK ack# = 4 seq# = 4
- A side received corrupt packet :(

EVENT time: 176.905426, type: 2, fromlayer3 entity: 1

- B side received packet: llllllllllllllllllll ack# = 11 seq# = 11
- B side received a packet with a greater sequence number than expected. Expected 5, got 11.
- Discarding packet...
- B side sending ACK for packet with highest in-order sequence number
- B side sent ACK: ACK ack# = 4 seq# = 4
- TOLAYER3: packet being corrupted

EVENT time: 179.009201, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ZCK ack# = 4 seq# = 4

- A side received corrupt packet :(

EVENT time: 181.283447, type: 2, fromlayer3 entity: 1

- B side received packet: ffffffffffffffffffff ack# = 5 seq# = 5

- B side received valid packet.

Sending pkt to upper layer.

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 5 seq# = 5

TOLAYER3: packet being lost.

EVENT time: 184.605209, type: 2, fromlayer3 entity: 1

- B side received packet: Zggggggggggggggggggg ack# = 6 seq# = 6

- B side received corrupted packet.

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 5 seq# = 5

EVENT time: 186.142715, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 5 seq# = 5

- A side received valid packet.

\*\* 6 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

- Updating sending window...

- Updated ACKS, restarted timer to reflect the oldest packet in the sending window.

- A side making sure all packets in sending window have been sent to B side...

- Message in window, already sent:	gggggggggggggggggggg	ack# = 6	seq# = 6
- Message in window, already sent:	hhhhhhhhhhhhhhhhhh	ack# = 7	seq# = 7
- Message in window, already sent:	iiiiiiiiiiiiiiiiiii	ack# = 8	seq# = 8
- Message in window, already sent:	jjjjjjjjjjjjjjjjjj	ack# = 9	seq# = 9
- Message in window, already sent:	kkkkkkkkkkkkkkkkkk	ack# = 10	seq# = 10
- Message in window, already sent:	llllllllllllllllll	ack# = 11	seq# = 11
- Message in window, already sent:	mmmmmmmmmmmmmmmmmm	ack# = 12	seq# = 12
- Sending NEW buffered message:	nnnnnnnnnnnnnnnnnn	ack# = 13	seq# = 13

TOLAYER3: packet being lost.

EVENT time: 186.201691, type: 2, fromlayer3 entity: 1

- B side received packet: hhhhhhhhhhhhhhhhhh ack# = 7 seq# = 7

- B side received a packet with a greater sequence number than expected. Expected 6, got 7.

Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 5 seq# = 5

TOLAYER3: packet being corrupted

EVENT time: 189.919907, type: 2, fromlayer3 entity: 1

- B side received packet: iiiiiaaaack# = 8 seq# = 8
- B side received a packet with a greater sequence number than expected. Expected 6, got 8.  
Discarding packet...
- B side sending ACK for packet with highest in-order sequence number
- B side sent ACK: ACK ack# = 5 seq# = 5  
TOLAYER3: packet being lost.

EVENT time: 191.882996, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 999999 seq# = 5
- A side received corrupt packet :(

EVENT time: 193.972565, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: ttttttttttttttttttttt
- Packet 19 buffered in sending buffer.

EVENT time: 194.791580, type: 2, fromlayer3 entity: 1

- B side received packet: jjjjjjjjjjjjjjjjjjjj ack# = 9 seq# = 9
- B side received a packet with a greater sequence number than expected. Expected 6, got 9.  
Discarding packet...
- B side sending ACK for packet with highest in-order sequence number
- B side sent ACK: ACK ack# = 5 seq# = 5  
TOLAYER3: packet being lost.

EVENT time: 201.330811, type: 2, fromlayer3 entity: 1

- B side received packet: kkkkkkkkkkkkkkkkkkkk ack# = 10 seq# = 10
- B side received a packet with a greater sequence number than expected. Expected 6, got 10.  
Discarding packet...
- B side sending ACK for packet with highest in-order sequence number
- B side sent ACK: ACK ack# = 5 seq# = 5  
TOLAYER3: packet being lost.

EVENT time: 205.438553, type: 2, fromlayer3 entity: 1

- B side received packet: llllllllllllllllllll ack# = 11 seq# = 11
- B side received a packet with a greater sequence number than expected. Expected 6, got 11.  
Discarding packet...



EVENT time: 219.297546, type: 2, fromlayer3 entity: 1

```
- B side received packet:          hhhhhhhhhhhhhhhhhhhh      ack# = 7      seq# = 7
- B side received valid packet.
  Sending pkt to upper layer.
- B side sending ACK for packet with highest
  in-order sequence number
- B side sent ACK:                ACK                        ack# = 7      seq# = 7
```

EVENT time: 220.438263, type: 2, fromlayer3 entity: 0

```
- A side received from Lower Layer:      ACK          ack# = 5      seq# = 5
- A side received valid packet.
** 6 MESSAGES HAVE BEEN SENT SUCCESSFULLY **
```

EVENT time: 224.057510, type: 1, fromlayer5 entity: 0

[illegible]

EVENT time: 225.030594, type: 2, fromlayer3 entity: 1

```
- B side received packet:          iiiiiiiiiiiiiiiiiiii      ack# = 8      seq# = 8
- B side received valid packet.
  Sending pkt to upper layer.
- B side sending ACK for packet with highest
  in-order sequence number
- B side sent ACK:                ACK                ack# = 8      seq# = 8
```

EVENT time: 226.062958, type: 1, fromlayer5 entity: 0

```
- A side received message from upper layer:      wwwwww.....
- Packet 22 buffered in sending buffer.
```

EVENT time: 226.142715, type: 0, timerinterrupt entity: 0

```
- TIMEOUT - timer restarted,
  all packets in window resent
    - Sending Message:          gggggggggggggggggggg      ack# = 6      seq# = 6
      TOLAYER3: packet being lost.
    - Sending Message:          hhhhhhhhhhhhhhhhhhhh      ack# = 7      seq# = 7
    - Sending Message:          iiiiiiiiiiiiiiiiii      ack# = 8      seq# = 8
    - Sending Message:          jjjjjjjjjjjjjjjjjj      ack# = 9      seq# = 9
    - Sending Message:          kkkkkkkkkkkkkkkkkkk      ack# = 10     seq# = 10
    - Sending Message:          llllllllllllllllllll      ack# = 11     seq# = 11
      TOLAYER3: packet being lost.
    - Sending Message:          mmmmmmmmmmmmmmmmmmm      ack# = 12     seq# = 12
    - Sending Message:          nnnnnnnnnnnnnnnnnnnn      ack# = 13     seq# = 13
```

EVENT time: 228.570892, type: 2, fromlayer3 entity: 0

```
- A side received from Lower Layer:      ACK          ack# = 5      seq# = 5
- A side received valid packet.
** 6 MESSAGES HAVE BEEN SENT SUCCESSFULLY **
```

EVENT time: 228.901932, type: 2, fromlayer3 entity: 1

- ```
- B side received packet:                Zkkkkkkkkkkkkkkkkkkkk      ack# = 10    seq# = 10
- B side received corrupted packet.
- B side sending ACK for packet with highest
  in-order sequence number
- B side sent ACK:                        ACK                ack# = 8      seq# = 8
  TOLAYER3: packet being corrupted
```

EVENT time: 233.026901, type: 2, fromlayer3 entity: 1

- ```
- B side received packet:          11111111111111111111      ack# = 11      seq# = 11
- B side received a packet with a greater
  sequence number than expected. Expected
  9, got 11.
  Discarding packet...
- B side sending ACK for packet with highest
  in-order sequence number
- B side sent ACK:                  ACK                      ack# = 8      seq# = 8
```

EVENT time: 236.722610, type: 2, fromlayer3 entity: 0

- ```
- A side received from Lower Layer:          ACK              ack# = 6      seq# = 6
- A side received valid packet.
** 7 MESSAGES HAVE BEEN SENT SUCCESSFULLY **
- Updating sending window...
- Updated ACKS, restarted timer to reflect
  the oldest packet in the sending window.
- A side making sure all packets in sending
  window have been sent to B side...
    - Message in window, already sent:         hhhhhhhhhhhhhhhhhhhh      ack# = 7      seq# = 7
    - Message in window, already sent:         iiiiiiiiiiiiiiiiii      ack# = 8      seq# = 8
    - Message in window, already sent:         jjjjjjjjjjjjjjjjjjjj      ack# = 9      seq# = 9
    - Message in window, already sent:         kkkkkkkkkkkkkkkkkkkk      ack# = 10     seq# = 10
    - Message in window, already sent:         llllllllllllllllllll      ack# = 11     seq# = 11
    - Message in window, already sent:         mmmmmmmmmmmmmmmmmmmm      ack# = 12     seq# = 12
    - Message in window, already sent:         nnnnnnnnnnnnnnnnnnnn      ack# = 13     seq# = 13
    - Sending NEW buffered message:             oooooooooooooooooooooo      ack# = 14     seq# = 14
```

EVENT time: 241.037369, type: 2, fromlayer3 entity: 0

- ```
- A side received from Lower Layer:      ACK      ack# = 7      seq# = 7
- A side received valid packet.
** 8 MESSAGES HAVE BEEN SENT SUCCESSFULLY **
- Updating sending window...
- Updated ACKS, restarted timer to reflect
  the oldest packet in the sending window.
- A side making sure all packets in sending
  window have been sent to B side...
    - Message in window, already sent:      iiiiiiiiiiiiiiiiiiii      ack# = 8      seq# = 8
    - Message in window, already sent:      jjjjjjjjjjjjjjjjjjjj      ack# = 9      seq# = 9
```







TOLAYER3: packet being lost.

EVENT time: 266.623718, type: 0, timerinterrupt entity: 0

```
- TIMEOUT - timer restarted,
  all packets in window resent
    - Sending Message:          jjjjjjjjjjjjjjjjjjjj      ack# = 9      seq# = 9
      TOLAYER3: packet being corrupted
    - Sending Message:          kkkkkkkkkkkkkkkkkkkk      ack# = 10     seq# = 10
      TOLAYER3: packet being lost.
    - Sending Message:          llllllllllllllllllll      ack# = 11     seq# = 11
    - Sending Message:          mmmmmmmmmmmmmmmmmmmmm      ack# = 12     seq# = 12
    - Sending Message:          nnnnnnnnnnnnnnnnnnnnn      ack# = 13     seq# = 13
    - Sending Message:          oooooooooooooooooooooo      ack# = 14     seq# = 14
      TOLAYER3: packet being lost.
    - Sending Message:          ppppppppppppppppppppp      ack# = 15     seq# = 15
    - Sending Message:          qqqqqqqqqqqqqqqqqqqq      ack# = 16     seq# = 16
```

EVENT time: 266.763336, type: 2, fromlayer3 entity: 1

```
- B side received packet:      llllllllllllllllllll      ack# = 11     seq# = 11
- B side received a packet with a greater
  sequence number than expected. Expected
  9, got 11.
  Discarding packet...
- B side sending ACK for packet with highest
  in-order sequence number
- B side sent ACK:              ACK                      ack# = 8      seq# = 8
```

EVENT time: 269.046051, type: 2, fromlayer3 entity: 0

```
- A side received from Lower Layer:      ACK              ack# = 8      seq# = 8
- A side received valid packet.
** 9 MESSAGES HAVE BEEN SENT SUCCESSFULLY **
```

EVENT time: 269.708801, type: 1, fromlayer5 entity: 0

```
- A side received message from upper layer:      ccccccccccccccccccc
- Packet 28 buffered in sending buffer.
```

EVENT time: 272.397247, type: 1, fromlayer5 entity: 0

```
- A side received message from upper layer:      ddddddddddddddddddd
- Packet 29 buffered in sending buffer.
```

EVENT time: 273.382233, type: 2, fromlayer3 entity: 1

```
- B side received packet:      mmmmmmmmmmmmmmmmmmm      ack# = 12     seq# = 12
- B side received a packet with a greater
  sequence number than expected. Expected
  9, got 12.
  Discarding packet...
- B side sending ACK for packet with highest
  in-order sequence number
```

```
- B side sent ACK:          ACK          ack# = 8      seq# = 8
```

EVENT time: 275.997803, type: 2, fromlayer3 entity: 0

```
- A side received from Lower Layer:      ACK      ack# = 8      seq# = 8
```

- A side received valid packet.

**\*\* 9 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\***

EVENT time: 280.302887, type: 2, fromlayer3 entity: 0

```
- A side received from Lower Layer:      ACK      ack# = 8      seq# = 8
```

- A side received valid packet.

**\*\* 9 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\***

EVENT time: 280.538635, type: 2, fromlayer3 entity: 1

```
- B side received packet:      nnnnnnnnnnnnnnnnnnnnnnnn      ack# = 13      seq# = 13
```

- B side received a packet with a greater sequence number than expected. Expected 9, got 13.

Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

```
- B side sent ACK:      ACK      ack# = 8      seq# = 8
```

TOLAYER3: packet being corrupted

EVENT time: 282.580597, type: 2, fromlayer3 entity: 1

```
- B side received packet:      hhhhhhhhhhhhhhhhhhhhhh      ack# = 7      seq# = 7
```

- B side received a packet with a lower sequence number than expected. Expected 9, got 7.

Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

```
- B side sent ACK:          ACK          ack# = 8      seq# = 8
```

```
EVENT time: 286.623718, type: 0, timerinterrupt entity: 0
```

- TIMEOUT - timer restarted,

all packets in window resent

```
- Sending Message:      jjjjjjjjjjjjjjjjjjjjjj      ack# = 9      seq# = 9
```

```
- Sending Message:      kkkkkkkkkkkkkkkkkkkkkkk      ack# = 10      seq# = 10
```

```
- Sending Message:      11111111111111111111      ack# = 11      seq# = 11
```

TOLAYER3: packet being corrupted

```
- Sending Message:      mmmmmmmmmmmmmmmmmmmmmmmmm    ack# = 12   seq# = 12
```

TOLAYER3: packet being lost.

```
- Sending Message:      nnnnnnnnnnnnnnnnnnnnnnnn    ack# = 13    seq# = 13
```

```
- Sending Message:      00000000000000000000      ack# = 14      seq# = 14
```

```
- Sending Message:      ppppppppppppppppppppppppp    ack# = 15    seq# = 15
```

```
- Sending Message:      qqqqqqqqqqqqqqqqqqqqqqqq      ack# = 16      seq# = 16
```

TOLAYER3: packet being lost.

EVENT time: 287.430176, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 8 seq# = 8
- A side received valid packet.

\*\* 9 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 289.418091, type: 2, fromlayer3 entity: 1

- B side received packet: iiiiiiiiiiiiiiiiii ack# = 8 seq# = 8
- B side received a packet with a lower sequence number than expected. Expected 9, got 8.
- Discarding packet...
- B side sending ACK for packet with highest in-order sequence number
- B side sent ACK: ACK ack# = 8 seq# = 8
- TOLAYER3: packet being corrupted

EVENT time: 290.616821, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: eeeeeeeeeeeeeeeeeee
- Packet 30 buffered in sending buffer.

EVENT time: 292.874481, type: 2, fromlayer3 entity: 1

- B side received packet: jjjjjjjjjjjjjjjjjjj ack# = 9 seq# = 9
- B side received valid packet.
- Sending pkt to upper layer.
- B side sending ACK for packet with highest in-order sequence number
- B side sent ACK: ACK ack# = 9 seq# = 9
- TOLAYER3: packet being corrupted

EVENT time: 295.734436, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: fffffffffffffffffffff
- Packet 31 buffered in sending buffer.

EVENT time: 295.774292, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ZCK ack# = 8 seq# = 8
- A side received corrupt packet :(

EVENT time: 301.245117, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 8 seq# = 8
- A side received valid packet.

\*\* 9 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 302.487274, type: 2, fromlayer3 entity: 1

- B side received packet: kkkkkkkkkkkkkkkkkkk ack# = 10 seq# = 10
- B side received valid packet.
- Sending pkt to upper layer.
- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 10 seq# = 10

EVENT time: 306.203918, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ZCK ack# = 8 seq# = 8  
- A side received corrupt packet :(

EVENT time: 306.623718, type: 0, timerinterrupt entity: 0

- TIMEOUT - timer restarted,  
all packets in window resent

- Sending Message:	jjjjjjjjjjjjjjjjjjj	ack# = 9	seq# = 9
- Sending Message:	kkkkkkkkkkkkkkkkkkk	ack# = 10	seq# = 10
- Sending Message:	lllllllllllllllllll	ack# = 11	seq# = 11
TOLAYER3: packet being lost.			
- Sending Message:	mmmmmmmmmmmmmmmmmm	ack# = 12	seq# = 12
TOLAYER3: packet being corrupted			
- Sending Message:	nnnnnnnnnnnnnnnnnnn	ack# = 13	seq# = 13
TOLAYER3: packet being corrupted			
- Sending Message:	oooooooooooooooooooo	ack# = 14	seq# = 14
- Sending Message:	ppppppppppppppppppp	ack# = 15	seq# = 15
- Sending Message:	qqqqqqqqqqqqqqqqqq	ack# = 16	seq# = 16

EVENT time: 307.660828, type: 2, fromlayer3 entity: 1

- B side received packet: mmmmmmmmmmmmmmmmmmm ack# = 12 seq# = 12  
- B side received a packet with a greater  
sequence number than expected. Expected  
11, got 12.  
Discarding packet...  
- B side sending ACK for packet with highest  
in-order sequence number  
- B side sent ACK: ACK ack# = 10 seq# = 10

EVENT time: 308.025513, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: gggggggggggggggggggg  
- Packet 32 buffered in sending buffer.

EVENT time: 310.967010, type: 2, fromlayer3 entity: 1

- B side received packet: nnnnnnnnnnnnnnnnnnnn ack# = 13 seq# = 13  
- B side received a packet with a greater  
sequence number than expected. Expected  
11, got 13.  
Discarding packet...  
- B side sending ACK for packet with highest  
in-order sequence number  
- B side sent ACK: ACK ack# = 10 seq# = 10

EVENT time: 314.943695, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 9 seq# = 999999  
- A side received corrupt packet :(

EVENT time: 320.107056, type: 2, fromlayer3 entity: 1

```
- B side received packet:                00000000000000000000    ack# = 14    seq# = 14
- B side received a packet with a greater
  sequence number than expected. Expected
  11, got 14.
  Discarding packet...
- B side sending ACK for packet with highest
  in-order sequence number
- B side sent ACK:                        ACK                    ack# = 10    seq# = 10
```

EVENT time: 321.153900, type: 2, fromlayer3 entity: 1

```
- B side received packet:                pppppppppppppppppppppp      ack# = 15      seq# = 15
- B side received a packet with a greater
  sequence number than expected. Expected
  11, got 15.
  Discarding packet...
- B side sending ACK for packet with highest
  in-order sequence number
- B side sent ACK:                        ACK                        ack# = 10      seq# = 10
  TOLAYER3: packet being corrupted
```

EVENT time: 323.192474, type: 2, fromlayer3 entity: 1

```
- B side received packet:                Zjjjjjjjjjjjjjjjjjjj      ack# = 9      seq# = 9
- B side received corrupted packet.
- B side sending ACK for packet with highest
  in-order sequence number
- B side sent ACK:                        ACK                ack# = 10      seq# = 10
  TOLAYER3: packet being lost.
```

EVENT time: 324.792267, type: 2, fromlayer3 entity: 0

```
- A side received from Lower Layer:      ACK          ack# = 10    seq# = 10
- A side received valid packet.
```

**\*\* 11 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\***

- Updating sending window...
- Updated ACKS, restarted timer to reflect the oldest packet in the sending window.
- A side making sure all packets in sending window have been sent to B side...

```
- Message in window, already sent:      11111111111111111111      ack# = 11      seq# = 11
- Message in window, already sent:      mmmmmmmmmmmmmmmmmmmmm      ack# = 12      seq# = 12
- Message in window, already sent:      nnnnnnnnnnnnnnnnnnnnn      ack# = 13      seq# = 13
- Message in window, already sent:      oooooooooooooooooooooo      ack# = 14      seq# = 14
- Message in window, already sent:      ppppppppppppppppppppp      ack# = 15      seq# = 15
- Message in window, already sent:      qqqqqqqqqqqqqqqqqqqq      ack# = 16      seq# = 16
- Sending NEW buffered message:          rrrrrrrrrrrrrrrrrrrrr      ack# = 17      seq# = 17
  TOLAYER3: packet being lost.
- Sending NEW buffered message:          sssssssssssssssssssss      ack# = 18      seq# = 18
```

TOLAYER3: packet being corrupted

EVENT time: 326.165863, type: 1, fromlayer5 entity: 0

```
- A side received message from upper layer:      hhhhhhhhhhhhhhhhhhhhhhhhhhh
```

- Packet 33 buffered in sending buffer.

EVENT time: 330.796448, type: 2, fromlayer3 entity: 1

```
- B side received packet:      11111111111111111111      ack# = 11      seq# = 11
```

- B side received valid packet.

Sending pkt to upper layer.

- B side sending ACK for packet with highest in-order sequence number

```
- B side sent ACK:          ACK          ack# = 11    seq# = 11
```

EVENT time: 331.902588, type: 2, fromlayer3 entity: 1

```
- B side received packet:      mmmmmmmmmmmmmmmmmmmmmmmmmmmmmmm    ack# = 12    seq# = 12
```

- B side received valid packet.

Sending pkt to upper layer.

- B side sending ACK for packet with highest in-order sequence number

```
- B side sent ACK:          ACK          ack# = 12  seq# = 12
```

EVENT time: 333.037750, type: 2, fromlayer3 entity: 0

```
- A side received from Lower Layer:      ACK          ack# = 10    seq# = 10
```

- A side received valid packet.

**\*\* 11 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\***

EVENT time: 335.188293, type: 2, fromlayer3 entity: 1

```
- B side received packet:      nnnnnnnnnnnnnnnnnnnnnnnn    ack# = 13    seq# = 13
```

- B side received valid packet.

Sending pkt to upper layer.

- B side sending ACK for packet with highest in-order sequence number

```
- B side sent ACK:          ACK          ack# = 13    seq# = 13
```

TOLAYER3: packet being lost.

```
EVENT time: 337.638184, type: 2, fromlayer3 entity: 0
```

```
- A side received from Lower Layer:      ACK          ack# = 10    seq# = 10
```

- A side received valid packet.

\*\* 11 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 338.034851, type: 2, fromlayer3 entity: 1

```
- B side received packet:      pppppppppppppppppppppppp      ack# = 15      seq# = 15
```

- B side received a packet with a greater sequence number than expected. Expected 14, got 15.

Discarding packet...

- B side sending ACK for packet with highest





```
EVENT time: 348.194092,  type: 1, fromlayer5  entity: 0
- A side received message from upper layer:      jjjjjjjjjjjjjjjjjjjj
- Packet 35 buffered in sending buffer.
```

```
EVENT time: 348.394226,  type: 2, fromlayer3  entity: 0
- A side received from Lower Layer:      ACK          ack# = 999999      seq# = 10
- A side received corrupt packet :(
```

```
EVENT time: 349.306641,  type: 1, fromlayer5  entity: 0
- A side received message from upper layer:      kkkkkkkkkkkkkkkkkkkk
- Packet 36 buffered in sending buffer.
```

```
EVENT time: 349.812653,  type: 2, fromlayer3  entity: 0
- A side received from Lower Layer:          ACK          ack# = 11    seq# = 11
- A side received valid packet.
```

\*\* 12 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

```
- Updating sending window...
- Updated ACKS, restarted timer to reflect
the oldest packet in the sending window.
- A side making sure all packets in sending
window have been sent to B side...
    - Message in window, already sent:      mmmmmmmmmmmmmmmmmmmmmmmmmmmmmmm   ack# = 12   seq# = 12
    - Message in window, already sent:      nnnnnnnnnnnnnnnnnnnnnnnnnnnnnnn   ack# = 13   seq# = 13
    - Message in window, already sent:      oooooooooooooooooooooooo          ack# = 14   seq# = 14
    - Message in window, already sent:      ppppppppppppppppppppppppp        ack# = 15   seq# = 15
    - Message in window, already sent:      qqqqqqqqqqqqqqqqqqqqqqqq         ack# = 16   seq# = 16
    - Message in window, already sent:      rrrrrrrrrrrrrrrrrrrrrrrr         ack# = 17   seq# = 17
    - Message in window, already sent:      ssssssssssssssssssssssss         ack# = 18   seq# = 18
    - Sending NEW buffered message:          tttttttttttttttttttt             ack# = 19   seq# = 19
```

TOLAYER3: packet being corrupted

```
EVENT time: 350.157288,  type: 2, fromlayer3  entity: 1
- B side received packet:                kkkkkkkkkkkkkkkkkkkk      ack# = 10    seq# = 10
- B side received a packet with a lower
  sequence number than expected. Expected
  14, got 10.
  Discarding packet...
- B side sending ACK for packet with highest
  in-order sequence number
- B side sent ACK:                        ACK                        ack# = 13    seq# = 13
```

```
EVENT time: 353.041290,  type: 2, fromlayer3  entity: 0
- A side received from Lower Layer:          ACK          ack# = 12    seq# = 12
- A side received valid packet.
** 13 MESSAGES HAVE BEEN SENT SUCCESSFULLY **
- Updating sending window...
- Updated ACKS, restarted timer to reflect
```

the oldest packet in the sending window.

- A side making sure all packets in sending window have been sent to B side...

- Message in window, already sent:	nnnnnnnnnnnnnnnnnnnn	ack# = 13	seq# = 13
- Message in window, already sent:	oooooooooooooooooooo	ack# = 14	seq# = 14
- Message in window, already sent:	pppppppppppppppppppp	ack# = 15	seq# = 15
- Message in window, already sent:	qqqqqqqqqqqqqqqqqqq	ack# = 16	seq# = 16
- Message in window, already sent:	rrrrrrrrrrrrrrrrrrrr	ack# = 17	seq# = 17
- Message in window, already sent:	ssssssssssssssssssss	ack# = 18	seq# = 18
- Message in window, already sent:	tttttttttttttttttttt	ack# = 19	seq# = 19
- Sending NEW buffered message:	uuuuuuuuuuuuuuuuuuuu	ack# = 20	seq# = 20

EVENT time: 354.545380, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: 111111111111111111
- Packet 37 buffered in sending buffer.

EVENT time: 355.623932, type: 2, fromlayer3 entity: 1

- B side received packet: Z111111111111111111 ack# = 11 seq# = 11
- B side received corrupted packet.
- B side sending ACK for packet with highest in-order sequence number
- B side sent ACK: ACK ack# = 13 seq# = 13
- TOLAYER3: packet being lost.

EVENT time: 360.106476, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: mmmmmmmmmmmmmmmmmmm
- Packet 38 buffered in sending buffer.

EVENT time: 361.889709, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 13 seq# = 13
- A side received valid packet.

\*\* 14 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

- Updating sending window...
- Updated ACKS, restarted timer to reflect the oldest packet in the sending window.
- A side making sure all packets in sending window have been sent to B side...

- Message in window, already sent:	oooooooooooooooooooo	ack# = 14	seq# = 14
- Message in window, already sent:	pppppppppppppppppppp	ack# = 15	seq# = 15
- Message in window, already sent:	qqqqqqqqqqqqqqqqqqq	ack# = 16	seq# = 16
- Message in window, already sent:	rrrrrrrrrrrrrrrrrrrr	ack# = 17	seq# = 17
- Message in window, already sent:	ssssssssssssssssssss	ack# = 18	seq# = 18
- Message in window, already sent:	tttttttttttttttttttt	ack# = 19	seq# = 19
- Message in window, already sent:	uuuuuuuuuuuuuuuuuuuu	ack# = 20	seq# = 20
- Sending NEW buffered message:	vvvvvvvvvvvvvvvvvvvv	ack# = 21	seq# = 21

EVENT time: 361.970581, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: nnnnnnnnnnnnnnnnnnn

- Packet 39 buffered in sending buffer.

EVENT time: 364.766754, type: 2, fromlayer3 entity: 1

- ```
- B side received packet:                nnnnnnnnnnnnnnnnnnnnnn      ack# = 13    seq# = 13
- B side received a packet with a lower
  sequence number than expected. Expected
  14, got 13.
  Discarding packet...
- B side sending ACK for packet with highest
  in-order sequence number
- B side sent ACK:                        ACK                      ack# = 13    seq# = 13
```

EVENT time: 368.461945, type: 1, fromlayer5 entity: 0

- ```
- A side received message from upper layer:      00000000000000000000
- Packet 40 buffered in sending buffer.
```

EVENT time: 368.983612, type: 2, fromlayer3 entity: 0

- ```
- A side received from Lower Layer:      ACK          ack# = 999999      seq# = 13
- A side received corrupt packet :(
```

EVENT time: 371.321045, type: 2, fromlayer3 entity: 1

- ```
- B side received packet:          00000000000000000000    ack# = 14    seq# = 14
- B side received valid packet.
  Sending pkt to upper layer.
- B side sending ACK for packet with highest
  in-order sequence number
- B side sent ACK:                ACK                      ack# = 14    seq# = 14
```

EVENT time: 372.587799, type: 2, fromlayer3 entity: 0

- ```
- A side received from Lower Layer:      ACK          ack# = 13   seq# = 13
- A side received valid packet.
** 14 MESSAGES HAVE BEEN SENT SUCCESSFULLY **
```

EVENT time: 379.763428, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: ppppppppppppppppppppp
- Packet 41 buffered in sending buffer.

EVENT time: 379.853912, type: 2, fromlayer3 entity: 1

- ```
- B side received packet:                ppppppppppppppppppppppp      ack# = 15    seq# = 15
- B side received valid packet.
  Sending pkt to upper layer.
- B side sending ACK for packet with highest
  in-order sequence number
- B side sent ACK:                        ACK                          ack# = 15    seq# = 15
  TOLAYER3: packet being lost.
```

```
EVENT time: 380.950745,  type: 2,  fromlayer3  entity: 0
```

- ```
- A side received from Lower Layer:      ACK      ack# = 13  seq# = 13
```

- A side received valid packet.  
\*\* 14 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 381.889709, type: 0, timerinterrupt entity: 0

- TIMEOUT - timer restarted,  
all packets in window resent

|                                  |                      |           |           |
|----------------------------------|----------------------|-----------|-----------|
| - Sending Message:               | oooooooooooooooooooo | ack# = 14 | seq# = 14 |
| - Sending Message:               | pppppppppppppppppppp | ack# = 15 | seq# = 15 |
| - Sending Message:               | qqqqqqqqqqqqqqqqqq   | ack# = 16 | seq# = 16 |
| - Sending Message:               | rrrrrrrrrrrrrrrrrrrr | ack# = 17 | seq# = 17 |
| TOLAYER3: packet being lost.     |                      |           |           |
| - Sending Message:               | ssssssssssssssssssss | ack# = 18 | seq# = 18 |
| - Sending Message:               | tttttttttttttttttttt | ack# = 19 | seq# = 19 |
| - Sending Message:               | uuuuuuuuuuuuuuuuuuuu | ack# = 20 | seq# = 20 |
| TOLAYER3: packet being corrupted |                      |           |           |
| - Sending Message:               | vvvvvvvvvvvvvvvvvvvv | ack# = 21 | seq# = 21 |
| TOLAYER3: packet being lost.     |                      |           |           |

EVENT time: 382.379333, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: qqqqqqqqqqqqqqqqqqq

- Packet 42 buffered in sending buffer.

EVENT time: 382.883423, type: 2, fromlayer3 entity: 1

- B side received packet: jjjjjjjjjjjjjjjjjjjj ack# = 9 seq# = 9

- B side received a packet with a lower sequence number than expected. Expected 16, got 9.  
Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 15 seq# = 15

TOLAYER3: packet being corrupted

EVENT time: 383.390289, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 13 seq# = 13

- A side received valid packet.

\*\* 14 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 390.379578, type: 2, fromlayer3 entity: 1

- B side received packet: kkkkkkkkkkkkkkkkkkkk ack# = 10 seq# = 10

- B side received a packet with a lower sequence number than expected. Expected 16, got 10.  
Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 15 seq# = 15



window have been sent to B side...

|                                    |                        |           |           |
|------------------------------------|------------------------|-----------|-----------|
| - Message in window, already sent: | qqqqqqqqqqqqqqqqqqqq   | ack# = 16 | seq# = 16 |
| - Message in window, already sent: | rrrrrrrrrrrrrrrrrrrr   | ack# = 17 | seq# = 17 |
| - Message in window, already sent: | ssssssssssssssssssss   | ack# = 18 | seq# = 18 |
| - Message in window, already sent: | tttttttttttttttttttt   | ack# = 19 | seq# = 19 |
| - Message in window, already sent: | uuuuuuuuuuuuuuuuuuuu   | ack# = 20 | seq# = 20 |
| - Message in window, already sent: | vvvvvvvvvvvvvvvvvvvv   | ack# = 21 | seq# = 21 |
| - Message in window, already sent: | wwwwwwwwwwwwwwwwwwww   | ack# = 22 | seq# = 22 |
| - Sending NEW buffered message:    | xxxxxxxxxxxxxxxxxxxxxx | ack# = 23 | seq# = 23 |

EVENT time: 408.179504, type: 2, fromlayer3 entity: 1

- B side received packet: 00000000000000000000 ack# = 14 seq# = 14

- B side received a packet with a lower sequence number than expected. Expected 16, got 14.

Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 15 seq# = 15

EVENT time: 409.684082, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 15 seq# = 15

- A side received valid packet.

\*\* 16 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 411.501801, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: sssssssssssssssssss

- Packet 44 buffered in sending buffer.

EVENT time: 412.601624, type: 2, fromlayer3 entity: 1

- B side received packet: pppppppppppppppppppp ack# = 15 seq# = 15

- B side received a packet with a lower sequence number than expected. Expected 16, got 15.

Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 15 seq# = 15

EVENT time: 414.110596, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 15 seq# = 15

- A side received valid packet.

\*\* 16 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 419.326660, type: 2, fromlayer3 entity: 1

- B side received packet: qqqqqqqqqqqqqqqqqqqq ack# = 16 seq# = 16

- B side received valid packet.

Sending pkt to upper layer.

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 16 seq# = 16

EVENT time: 419.575531, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 15 seq# = 15

- A side received valid packet.

\*\* 16 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 420.767181, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: tttttttttttttttttttt

- Packet 45 buffered in sending buffer.

EVENT time: 423.621887, type: 0, timerinterrupt entity: 0

- TIMEOUT - timer restarted,  
all packets in window resent

|                                  |                        |           |           |
|----------------------------------|------------------------|-----------|-----------|
| - Sending Message:               | qqqqqqqqqqqqqqqqqqqq   | ack# = 16 | seq# = 16 |
| - Sending Message:               | rrrrrrrrrrrrrrrrrrrr   | ack# = 17 | seq# = 17 |
| - Sending Message:               | ssssssssssssssssssss   | ack# = 18 | seq# = 18 |
| - Sending Message:               | tttttttttttttttttttt   | ack# = 19 | seq# = 19 |
| TOLAYER3: packet being corrupted |                        |           |           |
| - Sending Message:               | uuuuuuuuuuuuuuuuuuuu   | ack# = 20 | seq# = 20 |
| - Sending Message:               | vvvvvvvvvvvvvvvvvvvv   | ack# = 21 | seq# = 21 |
| - Sending Message:               | wwwwwwwwwwwwwwwwwwww   | ack# = 22 | seq# = 22 |
| - Sending Message:               | xxxxxxxxxxxxxxxxxxxxxx | ack# = 23 | seq# = 23 |

EVENT time: 425.354095, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 15 seq# = 15

- A side received valid packet.

\*\* 16 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 426.932861, type: 2, fromlayer3 entity: 1

- B side received packet: Zssssssssssssssssssss ack# = 18 seq# = 18

- B side received corrupted packet.

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 16 seq# = 16

EVENT time: 428.671967, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: uuuuuuuuuuuuuuuuuuuu

- Packet 46 buffered in sending buffer.

EVENT time: 430.918976, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 16 seq# = 16

- A side received valid packet.

\*\* 17 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

- Updating sending window...

- Updated ACKS, restarted timer to reflect

- A side making sure all packets in sending window have been sent to B side...

EVENT time: 432.421204, type: 2, fromlayer3 entity: 0

- A side received valid packet.

EVENT time: 434.021973, type: 2, fromlayer3 entity: 1

- B side received corrupted packet.

EVENT time: 438.685089, type: 2, fromlayer3 entity: 0

- A side received valid packet.

EVENT time: 439.332092, type: 2, fromlayer3 entity: 1

- B side received corrupted packet.

EVENT time: 443.399719, type: 2, fromlayer3 entity: 1

- B side received a packet with a lower sequence number than expected. Expected 17, got 14.

EVENT time: 447.736298, type: 1, fromlayer5 entity: 0

```
- A side received message from upper layer:      vvvvvvvvvvvvvvvvvvvvvvvvvvvvv
```



- Packet 47 buffered in sending buffer.

EVENT time: 447.913910, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 16 seq# = 16  
- A side received valid packet.  
\*\* 17 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 448.389648, type: 2, fromlayer3 entity: 1

- B side received packet: pppppppppppppppppppp ack# = 15 seq# = 15  
- B side received a packet with a lower sequence number than expected. Expected 17, got 15.  
Discarding packet...  
- B side sending ACK for packet with highest in-order sequence number  
- B side sent ACK: ACK ack# = 16 seq# = 16

EVENT time: 450.918976, type: 0, timerinterrupt entity: 0

- TIMEOUT - timer restarted,  
all packets in window resent  
- Sending Message: rrrrrrrrrrrrrrrrrrrrrr ack# = 17 seq# = 17  
- Sending Message: ssssssssssssssssssssss ack# = 18 seq# = 18  
TOLAYER3: packet being lost.  
- Sending Message: tttttttttttttttttttttt ack# = 19 seq# = 19  
TOLAYER3: packet being lost.  
- Sending Message: uuuuuuuuuuuuuuuuuuuuuu ack# = 20 seq# = 20  
TOLAYER3: packet being corrupted  
- Sending Message: vvvvvvvvvvvvvvvvvvvvvv ack# = 21 seq# = 21  
- Sending Message: wwwwwwwwwwwwwwwwwwwwww ack# = 22 seq# = 22  
- Sending Message: xxxxxxxxxxxxxxxxxxxxxxxx ack# = 23 seq# = 23  
- Sending Message: yyyyyyyyyyyyyyyyyyyyyyyy ack# = 24 seq# = 24

EVENT time: 452.354980, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 16 seq# = 16  
- A side received valid packet.  
\*\* 17 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 455.916321, type: 2, fromlayer3 entity: 1

- B side received packet: qqqqqqqqqqqqqqqqqqqq ack# = 16 seq# = 16  
- B side received a packet with a lower sequence number than expected. Expected 17, got 16.  
Discarding packet...  
- B side sending ACK for packet with highest in-order sequence number  
- B side sent ACK: ACK ack# = 16 seq# = 16

EVENT time: 460.482574, type: 1, fromlayer5 entity: 0

- A side received message from upper layer:        www  
- Packet 48 buffered in sending buffer.

EVENT time: 462.099121,    type: 2, fromlayer3    entity: 0  
- A side received from Lower Layer:        ACK                    ack# = 16    seq# = 16  
- A side received valid packet.  
\*\* 17 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 462.399445,    type: 2, fromlayer3    entity: 1  
- B side received packet:                    sssssssssssssssssssss        ack# = 18    seq# = 18  
- B side received a packet with a greater  
  sequence number than expected. Expected  
  17, got 18.  
  Discarding packet...  
- B side sending ACK for packet with highest  
  in-order sequence number  
- B side sent ACK:                    ACK                    ack# = 16    seq# = 16

EVENT time: 463.386658,    type: 1, fromlayer5    entity: 0  
- A side received message from upper layer:        xxxxxxxxxxxxxxxxxxxxxxx  
- Packet 49 buffered in sending buffer.

EVENT time: 464.853729,    type: 2, fromlayer3    entity: 1  
- B side received packet:                    Zttttttttttttttttttt        ack# = 19    seq# = 19  
- B side received corrupted packet.  
- B side sending ACK for packet with highest  
  in-order sequence number  
- B side sent ACK:                    ACK                    ack# = 16    seq# = 16

EVENT time: 465.257294,    type: 2, fromlayer3    entity: 0  
- A side received from Lower Layer:        ACK                    ack# = 16    seq# = 16  
- A side received valid packet.  
\*\* 17 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 465.523834,    type: 1, fromlayer5    entity: 0  
- A side received message from upper layer:        yyyyyyyyyyyyyyyyyyyyyyy  
- Packet 50 buffered in sending buffer.

EVENT time: 470.918976,    type: 0, timerinterrupt    entity: 0  
- TIMEOUT - timer restarted,  
  all packets in window resent  
  - Sending Message:                    rrrrrrrrrrrrrrrrrrrr        ack# = 17    seq# = 17  
    TOLAYER3: packet being lost.  
  - Sending Message:                    sssssssssssssssssssss        ack# = 18    seq# = 18  
  - Sending Message:                    tttttttttttttttttttt        ack# = 19    seq# = 19  
  - Sending Message:                    uuuuuuuuuuuuuuuuuuuu        ack# = 20    seq# = 20  
    TOLAYER3: packet being corrupted  
  - Sending Message:                    vvvvvvvvvvvvvvvvvvvv        ack# = 21    seq# = 21

TOLAYER3: packet being corrupted

|                                  |                        |           |           |
|----------------------------------|------------------------|-----------|-----------|
| - Sending Message:               | wwwwwwwwwwwwwwwwwwww   | ack# = 22 | seq# = 22 |
| TOLAYER3: packet being corrupted |                        |           |           |
| - Sending Message:               | xxxxxxxxxxxxxxxxxxxxxx | ack# = 23 | seq# = 23 |
| - Sending Message:               | yyyyyyyyyyyyyyyyyyyy   | ack# = 24 | seq# = 24 |

EVENT time: 473.793976, type: 2, fromlayer3 entity: 1

- B side received packet: uuuuuuuuuuuuuuuuuuuu ack# = 20 seq# = 20

- B side received a packet with a greater sequence number than expected. Expected 17, got 20.  
Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 16 seq# = 16

EVENT time: 474.913727, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 16 seq# = 16

- A side received valid packet.

\*\* 17 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 477.450897, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 16 seq# = 16

- A side received valid packet.

\*\* 17 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 478.363037, type: 2, fromlayer3 entity: 1

- B side received packet: vvvvvvvvvvvvvvvvvvvv ack# = 21 seq# = 21

- B side received a packet with a greater sequence number than expected. Expected 17, got 21.  
Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 16 seq# = 16

EVENT time: 480.118408, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: zzzzzzzzzzzzzzzzzzzz

- Packet 51 buffered in sending buffer.

EVENT time: 483.144379, type: 2, fromlayer3 entity: 1

- B side received packet: oooooooooooooooooooooo ack# = 14 seq# = 14

- B side received a packet with a lower sequence number than expected. Expected 17, got 14.  
Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 16 seq# = 16

EVENT time: 487.266724, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 16 seq# = 16

- A side received valid packet.

\*\* 17 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 490.128174, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: aaaaaaaaaaaaaaaaaaaaaa

- Packet 52 buffered in sending buffer.

EVENT time: 490.283142, type: 2, fromlayer3 entity: 1

- B side received packet: pppppppppppppppppppppp ack# = 15 seq# = 15

- B side received a packet with a lower sequence number than expected. Expected 17, got 15.

Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 16 seq# = 16

TOLAYER3: packet being lost.

EVENT time: 490.918976, type: 0, timerinterrupt entity: 0

- TIMEOUT - timer restarted, all packets in window resent

- Sending Message: rrrrrrrrrrrrrrrrrrrrrr ack# = 17 seq# = 17

- Sending Message: ssssssssssssssssssssss ack# = 18 seq# = 18

TOLAYER3: packet being corrupted

- Sending Message: tttttttttttttttttttttt ack# = 19 seq# = 19

- Sending Message: uuuuuuuuuuuuuuuuuuuuuu ack# = 20 seq# = 20

- Sending Message: vvvvvvvvvvvvvvvvvvvvvv ack# = 21 seq# = 21

TOLAYER3: packet being corrupted

- Sending Message: wwwwwwwwwwwwwwwwwwwwww ack# = 22 seq# = 22

- Sending Message: xxxxxxxxxxxxxxxxxxxxxxxx ack# = 23 seq# = 23

- Sending Message: yyyyyyyyyyyyyyyyyyyyyyyy ack# = 24 seq# = 24

EVENT time: 494.029510, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 16 seq# = 16

- A side received valid packet.

\*\* 17 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 495.501587, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: bbbbbbbbbbbbbbbbbbbbbb

- Packet 53 buffered in sending buffer.

EVENT time: 496.193756, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 16 seq# = 16

- A side received valid packet.

**\*\* 17 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\***

EVENT time: 498.695740, type: 2, fromlayer3 entity: 1

```
- B side received packet:      qqqqqqqqqqqqqqqqqqqqqqqq      ack# = 16      seq# = 16
```

- B side received a packet with a lower sequence number than expected. Expected 17, got 16.

Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

```
- B side sent ACK:          ACK          ack# = 16    seq# = 16
```

EVENT time: 506.711700, type: 2, fromlayer3 entity: 0

```
- A side received from Lower Layer:      ACK      ack# = 16      seq# = 16
```

- A side received valid packet.

**\*\* 17 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\***

EVENT time: 507.348480, type: 2, fromlayer3 entity: 1

```
- B side received packet:      sssssssssssssssssssssss      ack# = 18      seq# = 18
```

- B side received a packet with a greater sequence number than expected. Expected 17, got 18.

Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

```
- B side sent ACK:          ACK          ack# = 16    seq# = 16
```

EVENT time: 508.817200, type: 2, fromlayer3 entity: 0

```
- A side received from Lower Layer:      ACK      ack# = 16      seq# = 16
```

- A side received valid packet.

**\*\* 17 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\***

EVENT time: 509.332733, type: 2, fromlayer3 entity: 1

```
- B side received packet:      ttttttttttttttttttttttt      ack# = 19      seq# = 19
```

- B side received a packet with a greater sequence number than expected. Expected 17, got 19.

Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

```
- B side sent ACK:          ACK          ack# = 16    seq# = 16
```

TOLAYER3: packet being lost.

```
EVENT time: 510.918976, type: 0, timerinterrupt entity: 0
```

- TIMEOUT - timer restarted, all packets in window resent

```
- Sending Message:      rrrrrrrrrrrrrrrrrrrrrrrr    ack# = 17   seq# = 17
```

```
- Sending Message:      sssssssssssssssssssssss      ack# = 18      seq# = 18
```

TOLAYER3: packet being corrupted

|                              |                        |           |           |
|------------------------------|------------------------|-----------|-----------|
| - Sending Message:           | tttttttttttttttttttt   | ack# = 19 | seq# = 19 |
| - Sending Message:           | uuuuuuuuuuuuuuuuuuuu   | ack# = 20 | seq# = 20 |
| - Sending Message:           | vvvvvvvvvvvvvvvvvvvv   | ack# = 21 | seq# = 21 |
| - Sending Message:           | wwwwwwwwwwwwwwwwwwww   | ack# = 22 | seq# = 22 |
| TOLAYER3: packet being lost. |                        |           |           |
| - Sending Message:           | xxxxxxxxxxxxxxxxxxxxxx | ack# = 23 | seq# = 23 |
| - Sending Message:           | yyyyyyyyyyyyyyyyyyyyyy | ack# = 24 | seq# = 24 |

EVENT time: 512.155823, type: 2, fromlayer3 entity: 1

|                                                                       |                      |               |           |
|-----------------------------------------------------------------------|----------------------|---------------|-----------|
| - B side received packet:                                             | uuuuuuuuuuuuuuuuuuuu | ack# = 999999 | seq# = 20 |
| - B side received corrupted packet.                                   |                      |               |           |
| - B side sending ACK for packet with highest in-order sequence number |                      |               |           |
| - B side sent ACK:                                                    | ACK                  | ack# = 16     | seq# = 16 |
| TOLAYER3: packet being corrupted                                      |                      |               |           |

EVENT time: 514.096375, type: 2, fromlayer3 entity: 1

|                                                                                               |                      |           |           |
|-----------------------------------------------------------------------------------------------|----------------------|-----------|-----------|
| - B side received packet:                                                                     | wwwwwwwwwwwwwwwwwwww | ack# = 22 | seq# = 22 |
| - B side received a packet with a greater sequence number than expected. Expected 17, got 22. |                      |           |           |
| Discarding packet...                                                                          |                      |           |           |
| - B side sending ACK for packet with highest in-order sequence number                         |                      |           |           |
| - B side sent ACK:                                                                            | ACK                  | ack# = 16 | seq# = 16 |

EVENT time: 515.035706, type: 1, fromlayer5 entity: 0

|                                             |                      |
|---------------------------------------------|----------------------|
| - A side received message from upper layer: | cccccccccccccccccccc |
| - Packet 54 buffered in sending buffer.     |                      |

EVENT time: 516.722473, type: 1, fromlayer5 entity: 0

|                                             |                      |
|---------------------------------------------|----------------------|
| - A side received message from upper layer: | dddddddddddddddddddd |
| - Packet 55 buffered in sending buffer.     |                      |

EVENT time: 516.810608, type: 2, fromlayer3 entity: 0

|                                     |     |           |           |
|-------------------------------------|-----|-----------|-----------|
| - A side received from Lower Layer: | ZCK | ack# = 16 | seq# = 16 |
| - A side received corrupt packet :( |     |           |           |

EVENT time: 518.617310, type: 2, fromlayer3 entity: 0

|                                     |     |           |           |
|-------------------------------------|-----|-----------|-----------|
| - A side received from Lower Layer: | ACK | ack# = 16 | seq# = 16 |
| - A side received valid packet.     |     |           |           |

\*\* 17 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 519.945923, type: 2, fromlayer3 entity: 1

|                                                                                   |                        |           |           |
|-----------------------------------------------------------------------------------|------------------------|-----------|-----------|
| - B side received packet:                                                         | xxxxxxxxxxxxxxxxxxxxxx | ack# = 23 | seq# = 23 |
| - B side received a packet with a greater sequence number than expected. Expected |                        |           |           |

17, got 23.  
Discarding packet...

- B side sending ACK for packet with highest in-order sequence number
- B side sent ACK: ACK ack# = 16 seq# = 16

EVENT time: 524.406982, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 16 seq# = 16
- A side received valid packet.

\*\* 17 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 525.757690, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: eeeeeeeeeeeeeeeeeeee
- Packet 56 buffered in sending buffer.

EVENT time: 526.194458, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: ffffffffffffffffffffff
- Packet 57 buffered in sending buffer.

EVENT time: 529.231140, type: 2, fromlayer3 entity: 1

- B side received packet: qqqqqqqqqqqqqqqqqqqq ack# = 16 seq# = 16
- B side received a packet with a lower sequence number than expected. Expected 17, got 16.  
Discarding packet...
- B side sending ACK for packet with highest in-order sequence number
- B side sent ACK: ACK ack# = 16 seq# = 16

EVENT time: 530.918945, type: 0, timerinterrupt entity: 0

- TIMEOUT - timer restarted,  
all packets in window resent
- Sending Message: rrrrrrrrrrrrrrrrrrrrrr ack# = 17 seq# = 17  
TOLAYER3: packet being lost.
- Sending Message: ssssssssssssssssssssss ack# = 18 seq# = 18
- Sending Message: tttttttttttttttttttttt ack# = 19 seq# = 19
- Sending Message: uuuuuuuuuuuuuuuuuuuuuu ack# = 20 seq# = 20
- Sending Message: vvvvvvvvvvvvvvvvvvvvvv ack# = 21 seq# = 21
- Sending Message: wwwwwwwwwwwwwwwwwwwwww ack# = 22 seq# = 22  
TOLAYER3: packet being corrupted
- Sending Message: xxxxxxxxxxxxxxxxxxxxxxxx ack# = 23 seq# = 23
- Sending Message: yyyyyyyyyyyyyyyyyyyyyyyy ack# = 24 seq# = 24

EVENT time: 535.792419, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: gggggggggggggggggggggg
- Packet 58 buffered in sending buffer.

EVENT time: 536.076477, type: 2, fromlayer3 entity: 1





|                    |                                |           |           |
|--------------------|--------------------------------|-----------|-----------|
| - Sending Message: | rrrrrrrrrrrrrrrrrrrrrrrrrrrrrr | ack# = 17 | seq# = 17 |
| - Sending Message: | ssssssssssssssssssssssssssss   | ack# = 18 | seq# = 18 |
| - Sending Message: | tttttttttttttttttttttttttttt   | ack# = 19 | seq# = 19 |
| - Sending Message: | uuuuuuuuuuuuuuuuuuuuuuuuuuuu   | ack# = 20 | seq# = 20 |
| - Sending Message: | vvvvvvvvvvvvvvvvvvvvvvvvvvvv   | ack# = 21 | seq# = 21 |
| - Sending Message: | wwwwwwwwwwwwwwwwwwwwwwwwwwww   | ack# = 22 | seq# = 22 |
| - Sending Message: | xxxxxxxxxxxxxxxxxxxxxxxxxxxxxx | ack# = 23 | seq# = 23 |
| - Sending Message: | yyyyyyyyyyyyyyyyyyyyyyyyyyyyyy | ack# = 24 | seq# = 24 |

EVENT time: 551.383118, type: 2, fromlayer3 entity: 1

- B side received packet: uuuuuuuuuuuuuuuuuuuuuuuuuuuuuu ack# = 20 seq# = 20
- B side received a packet with a greater sequence number than expected. Expected 19, got 20.  
Discarding packet...
- B side sending ACK for packet with highest in-order sequence number
- B side sent ACK: ACK ack# = 18 seq# = 18

EVENT time: 556.519409, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 18 seq# = 18
- A side received valid packet.

\*\* 19 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

- Updating sending window...
- Updated ACKS, restarted timer to reflect the oldest packet in the sending window.
- A side making sure all packets in sending window have been sent to B side...
 

|                                    |                                |           |           |
|------------------------------------|--------------------------------|-----------|-----------|
| - Message in window, already sent: | tttttttttttttttttttttttttttt   | ack# = 19 | seq# = 19 |
| - Message in window, already sent: | uuuuuuuuuuuuuuuuuuuuuuuuuuuu   | ack# = 20 | seq# = 20 |
| - Message in window, already sent: | vvvvvvvvvvvvvvvvvvvvvvvvvvvv   | ack# = 21 | seq# = 21 |
| - Message in window, already sent: | wwwwwwwwwwwwwwwwwwwwwwwwwwww   | ack# = 22 | seq# = 22 |
| - Message in window, already sent: | xxxxxxxxxxxxxxxxxxxxxxxxxxxxxx | ack# = 23 | seq# = 23 |
| - Message in window, already sent: | yyyyyyyyyyyyyyyyyyyyyyyyyyyyyy | ack# = 24 | seq# = 24 |
| - Sending NEW buffered message:    | zzzzzzzzzzzzzzzzzzzzzzzzzzzz   | ack# = 25 | seq# = 25 |

 TOLAYER3: packet being corrupted
- Sending NEW buffered message: aaaaaaaaaaaaaaaaaaaaaaa ack# = 26 seq# = 26

EVENT time: 556.762695, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: kkkkkkkkkkkkkkkkkkkkkkkkkkkkk
- Packet 62 buffered in sending buffer.

EVENT time: 557.538208, type: 2, fromlayer3 entity: 1

- B side received packet: vvvvvvvvvvvvvvvvvvvvvvvvvvvvvv ack# = 21 seq# = 21
- B side received a packet with a greater sequence number than expected. Expected 19, got 21.  
Discarding packet...



- A side received from Lower Layer: ACK ack# = 18 seq# = 18  
- A side received valid packet.  
\*\* 19 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 576.519409, type: 0, timerinterrupt entity: 0

- TIMEOUT - timer restarted,  
all packets in window resent

|                    |                        |           |           |
|--------------------|------------------------|-----------|-----------|
| - Sending Message: | tttttttttttttttttttt   | ack# = 19 | seq# = 19 |
| - Sending Message: | uuuuuuuuuuuuuuuuuuuu   | ack# = 20 | seq# = 20 |
| - Sending Message: | vvvvvvvvvvvvvvvvvvvv   | ack# = 21 | seq# = 21 |
| - Sending Message: | wwwwwwwwwwwwwwwwwwww   | ack# = 22 | seq# = 22 |
| - Sending Message: | xxxxxxxxxxxxxxxxxxxxxx | ack# = 23 | seq# = 23 |
| - Sending Message: | yyyyyyyyyyyyyyyyyyyy   | ack# = 24 | seq# = 24 |
| - Sending Message: | zzzzzzzzzzzzzzzzzzzz   | ack# = 25 | seq# = 25 |
| - Sending Message: | aaaaaaaaaaaaaaaaaaaaa  | ack# = 26 | seq# = 26 |

EVENT time: 580.374939, type: 2, fromlayer3 entity: 1

- B side received packet: yyyyyyyyyyyyyyyyyyyy ack# = 24 seq# = 24  
- B side received a packet with a greater  
sequence number than expected. Expected  
19, got 24.  
Discarding packet...  
- B side sending ACK for packet with highest  
in-order sequence number  
- B side sent ACK: ACK ack# = 18 seq# = 18  
TOLAYER3: packet being lost.

EVENT time: 581.636230, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: nnnnnnnnnnnnnnnnnnnn  
- Packet 65 buffered in sending buffer.

EVENT time: 586.891174, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: oooooooooooooooooooooo  
- Packet 66 buffered in sending buffer.

EVENT time: 588.541931, type: 2, fromlayer3 entity: 1

- B side received packet: rrrrrrrrrrrrrrrrrrrr ack# = 17 seq# = 17  
- B side received a packet with a lower  
sequence number than expected. Expected  
19, got 17.  
Discarding packet...  
- B side sending ACK for packet with highest  
in-order sequence number  
- B side sent ACK: ACK ack# = 18 seq# = 18

EVENT time: 590.022583, type: 2, fromlayer3 entity: 1

- B side received packet: uuuuuuuuuuuuuuuuuuuu ack# = 20 seq# = 999999  
- B side received corrupted packet.

- ```
- B side sending ACK for packet with highest
  in-order sequence number
- B side sent ACK:                                ACK                ack# = 18    seq# = 18
  TOLAYER3: packet being corrupted
```

EVENT time: 596.059448, type: 2, fromlayer3 entity: 0

- ```
- A side received from Lower Layer:      ACK          ack# = 18   seq# = 18
- A side received valid packet.
** 19 MESSAGES HAVE BEEN SENT SUCCESSFULLY **
```

```
EVENT time: 596.519409, type: 0, timerinterrupt entity: 0
```

- ```
- TIMEOUT - timer restarted,
  all packets in window resent
    - Sending Message:          tttttttttttttttttttt      ack# = 19    seq# = 19
      TOLAYER3: packet being lost.
    - Sending Message:          uuuuuuuuuuuuuuuuuuuuu      ack# = 20    seq# = 20
      TOLAYER3: packet being lost.
    - Sending Message:          vvvvvvvvvvvvvvvvvvvvv      ack# = 21    seq# = 21
      TOLAYER3: packet being lost.
    - Sending Message:          wwwwwwwwwwwwwwwwwwwww      ack# = 22    seq# = 22
    - Sending Message:          xxxxxxxxxxxxxxxxxxxxxxxx      ack# = 23    seq# = 23
    - Sending Message:          yyyyyyyyyyyyyyyyyyyyyyyy      ack# = 24    seq# = 24
    - Sending Message:          zzzzzzzzzzzzzzzzzzzzz      ack# = 25    seq# = 25
      TOLAYER3: packet being lost.
    - Sending Message:          aaaaaaaaaaaaaaaaaaaaaa      ack# = 26    seq# = 26
      TOLAYER3: packet being lost.
```

EVENT time: 596.519470, type: 2, fromlayer3 entity: 1

- ```
- B side received packet: vvvvvvvvvvvvvvvvvvvvvv      ack# = 21      seq# = 21
- B side received a packet with a greater
  sequence number than expected. Expected
  19, got 21.
  Discarding packet...
- B side sending ACK for packet with highest
  in-order sequence number
- B side sent ACK:          ACK          ack# = 18      seq# = 18
  TOLAYER3: packet being lost.
```

EVENT time: 598.445984, type: 2, fromlayer3 entity: 1

- ```
- B side received packet:                ack# = 22    seq# = 22
- B side received a packet with a greater
  sequence number than expected. Expected
  19, got 22.
  Discarding packet...
- B side sending ACK for packet with highest
  in-order sequence number
- B side sent ACK:                ACK                ack# = 18    seq# = 18
```

EVENT time: 599.757324, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: ppppppppppppppppppppp
- Packet 67 buffered in sending buffer.

EVENT time: 601.882629, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ZCK ack# = 18 seq# = 18
- A side received corrupt packet :(

EVENT time: 603.342651, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 18 seq# = 18
- A side received valid packet.

\*\* 19 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 608.359253, type: 2, fromlayer3 entity: 1

- B side received packet: xxxxxxxxxxxxxxxxxxxxxx ack# = 23 seq# = 23
- B side received a packet with a greater sequence number than expected. Expected 19, got 23.
- Discarding packet...
- B side sending ACK for packet with highest in-order sequence number
- B side sent ACK: ACK ack# = 18 seq# = 18
- TOLAYER3: packet being corrupted

EVENT time: 610.601074, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ZCK ack# = 18 seq# = 18
- A side received corrupt packet :(

EVENT time: 612.935608, type: 2, fromlayer3 entity: 1

- B side received packet: yyyyyyyyyyyyyyyyyyyyyy ack# = 24 seq# = 24
- B side received a packet with a greater sequence number than expected. Expected 19, got 24.
- Discarding packet...
- B side sending ACK for packet with highest in-order sequence number
- B side sent ACK: ACK ack# = 18 seq# = 18

EVENT time: 616.519409, type: 0, timerinterrupt entity: 0

- TIMEOUT - timer restarted,
- all packets in window resent
- Sending Message: tttttttttttttttttttt ack# = 19 seq# = 19
- Sending Message: uuuuuuuuuuuuuuuuuuuu ack# = 20 seq# = 20
- Sending Message: vvvvvvvvvvvvvvvvvvvv ack# = 21 seq# = 21
- Sending Message: wwwwwwwwwwwwwwwwwwww ack# = 22 seq# = 22
- Sending Message: xxxxxxxxxxxxxxxxxxxxxx ack# = 23 seq# = 23
- TOLAYER3: packet being lost.
- Sending Message: yyyyyyyyyyyyyyyyyyyyyy ack# = 24 seq# = 24



- Message in window, already sent:	uuuuuuuuuuuuuuuuuuuu	ack# = 20	seq# = 20
- Message in window, already sent:	vvvvvvvvvvvvvvvvvvvv	ack# = 21	seq# = 21
- Message in window, already sent:	wwwwwwwwwwwwwwwwwww	ack# = 22	seq# = 22
- Message in window, already sent:	xxxxxxxxxxxxxxxxxxxxxx	ack# = 23	seq# = 23
- Message in window, already sent:	yyyyyyyyyyyyyyyyyyyy	ack# = 24	seq# = 24
- Message in window, already sent:	zzzzzzzzzzzzzzzzzzz	ack# = 25	seq# = 25
- Message in window, already sent:	aaaaaaaaaaaaaaaaaaaaa	ack# = 26	seq# = 26
- Sending NEW buffered message:	bbbbbbbbbbbbbbbbbbbbb	ack# = 27	seq# = 27

```
B side received packet:                uuuuuuuuuuuuuuuuuuuuu      ack# = 20    seq# = 999999
B side received corrupted packet.
B side sending ACK for packet with highest
in-order sequence number
B side sent ACK:                        ACK              ack# = 19    seq# = 19
TOLAYER3: packet being lost.
```

```
A side received message from upper layer:      sssssssssssssssssssss
Packet 70 buffered in sending buffer.
```

```

B side received packet:          Zvvvvvvvvvvvvvvvvvv          ack# = 21    seq# = 21
B side received corrupted packet.
B side sending ACK for packet with highest
in-order sequence number
B side sent ACK:                ACK                ack# = 19    seq# = 19

```

```
B side received packet:          Zwwwwwwwwwwwwwwwwwwwwww      ack# = 22    seq# = 22  
B side received corrupted packet.  
B side sending ACK for packet with highest  
in-order sequence number  
B side sent ACK:                ACK                      ack# = 19    seq# = 19
```

```

B side received packet:                xxxxxxxxxxxxxxxxxxxx      ack# = 23      seq# = 23
B side received a packet with a greater
sequence number than expected. Expected
20, got 23.
Discarding packet...
B side sending ACK for packet with highest
in-order sequence number
B side sent ACK:                        ACK                        ack# = 19      seq# = 19
TOLAYER3: packet being lost.

```

```
VENT time: 649.130005, type: 2, fromlayer3 entity: 0
```

- A side received from Lower Layer: ACK ack# = 19 seq# = 19  
- A side received valid packet.  
\*\* 20 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 651.665771, type: 1, fromlayer5 entity: 0  
- A side received message from upper layer: tttttttttttttttttttt  
- Packet 71 buffered in sending buffer.

EVENT time: 653.164490, type: 2, fromlayer3 entity: 1  
- B side received packet: yyyyyyyyyyyyyyyyyyyy ack# = 24 seq# = 24  
- B side received a packet with a greater sequence number than expected. Expected 20, got 24.  
Discarding packet...  
- B side sending ACK for packet with highest in-order sequence number  
- B side sent ACK: ACK ack# = 19 seq# = 19  
TOLAYER3: packet being lost.

EVENT time: 655.608582, type: 0, timerinterrupt entity: 0  
- TIMEOUT - timer restarted, all packets in window resent  
- Sending Message: uuuuuuuuuuuuuuuuuuuu ack# = 20 seq# = 20  
TOLAYER3: packet being lost.  
- Sending Message: vvvvvvvvvvvvvvvvvvvv ack# = 21 seq# = 21  
- Sending Message: wwwwwwwwwwwwwwwwwwww ack# = 22 seq# = 22  
- Sending Message: xxxxxxxxxxxxxxxxxxxxxx ack# = 23 seq# = 23  
- Sending Message: yyyyyyyyyyyyyyyyyyyy ack# = 24 seq# = 24  
- Sending Message: zzzzzzzzzzzzzzzzzzzz ack# = 25 seq# = 25  
TOLAYER3: packet being corrupted  
- Sending Message: aaaaaaaaaaaaaaaaaaaaaa ack# = 26 seq# = 26  
- Sending Message: bbbbbbbbbbbbbbbbbbbbbb ack# = 27 seq# = 27  
TOLAYER3: packet being corrupted

EVENT time: 655.872192, type: 2, fromlayer3 entity: 0  
- A side received from Lower Layer: ACK ack# = 19 seq# = 19  
- A side received valid packet.  
\*\* 20 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 659.140808, type: 2, fromlayer3 entity: 1  
- B side received packet: rrrrrrrrrrrrrrrrrrrr ack# = 17 seq# = 17  
- B side received a packet with a lower sequence number than expected. Expected 20, got 17.  
Discarding packet...  
- B side sending ACK for packet with highest in-order sequence number  
- B side sent ACK: ACK ack# = 19 seq# = 19



EVENT time: 660.642700, type: 1, fromlayer5 entity: 0

```
- A side received message from upper layer:      uuuuuuuuuuuuuuuuuuuuuuuuuuuuuuu
```

- Packet 72 buffered in sending buffer.

EVENT time: 663.167969, type: 2, fromlayer3 entity: 1

```
- B side received packet:      Zssssssssssssssssssssss      ack# = 18      seq# = 18
```

- B side received corrupted packet.

- B side sending ACK for packet with highest in-order sequence number

```
- B side sent ACK:      ACK      ack# = 19    seq# = 19
```

EVENT time: 664.782715, type: 2, fromlayer3 entity: 0

```
- A side received from Lower Layer:      ACK      ack# = 19      seq# = 19
```

- A side received valid packet.

**\*\* 20 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\***

EVENT time: 671.323975, type: 2, fromlayer3 entity: 1

```
- B side received packet:      ttttttttttttttttttttttt      ack# = 19      seq# = 19
```

- B side received a packet with a lower sequence number than expected. Expected 20, got 19.

Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

```
- B side sent ACK:      ACK      ack# = 19  seq# = 19
```

TOLAYER3: packet being corrupted

```
EVENT time: 673.908813, type: 2, fromlayer3 entity: 0
```

```
- A side received from Lower Layer:      ACK      ack# = 19      seq# = 19
```

- A side received valid packet.

**\*\* 20 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\***

EVENT time: 675.608582, type: 0, timerinterrupt entity: 0

- TIMEOUT - timer restarted,

all packets in window resent

[illegible]

```
- Sending Message:          vvvvvvvvvvvvvvvvvvvvvvvv      ack# = 21    seq# = 21
```

TOLAYER3: packet being corrupted

```
- Sending Message:      wwwwwwwwwwwwwwwwwwwwwwww      ack# = 22      seq# = 22
```

```
- Sending Message:                xxxxxxxxxxxxxxxxxxxxxx    ack# = 23    seq# = 23
```

```
- Sending Message:                yyyyyyyyyyyyyyyyyyyyyyy          ack# = 24    seq# = 24
```

TOLAYER3: packet being corrupted

```
- Sending Message: zzzzzzzzzzzzzzzzzzzzzzzz    ack# = 25    seq# = 25
```

```
- Sending Message:                aaaaaaaaaaaaaaaaaaaaaa    ack# = 26    seq# = 26
```

TOLAYER3: packet being lost.

```
- Sending Message:      bbbbbbbbbbbbbbbbbbbb      ack# = 27      seq# = 27
```

EVENT time: 675.908691, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: vvvvvvvvvvvvvvvvvvvvv
- Packet 73 buffered in sending buffer.

EVENT time: 678.893616, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ZCK ack# = 19 seq# = 19
- A side received corrupt packet :(

EVENT time: 679.576660, type: 2, fromlayer3 entity: 1

- B side received packet: uuuuuuuuuuuuuuuuuuuuuu ack# = 20 seq# = 20
- B side received valid packet.  
Sending pkt to upper layer.
- B side sending ACK for packet with highest in-order sequence number
- B side sent ACK: ACK ack# = 20 seq# = 20  
TOLAYER3: packet being corrupted

EVENT time: 681.084229, type: 2, fromlayer3 entity: 1

- B side received packet: Zvvvvvvvvvvvvvvvvvvvvv ack# = 21 seq# = 21
- B side received corrupted packet.
- B side sending ACK for packet with highest in-order sequence number
- B side sent ACK: ACK ack# = 20 seq# = 20

EVENT time: 682.955566, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: wwwwwwwwwwwwwwwwwwwww
- Packet 74 buffered in sending buffer.

EVENT time: 687.260498, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ZCK ack# = 20 seq# = 20
- A side received corrupt packet :(

EVENT time: 687.862915, type: 2, fromlayer3 entity: 1

- B side received packet: wwwwwwwwwwwwwwwwwwwwwv ack# = 22 seq# = 22
- B side received a packet with a greater sequence number than expected. Expected 21, got 22.  
Discarding packet...
- B side sending ACK for packet with highest in-order sequence number
- B side sent ACK: ACK ack# = 20 seq# = 20

EVENT time: 690.231323, type: 2, fromlayer3 entity: 1

- B side received packet: xxxxxxxxxxxxxxxxxxxxxx ack# = 23 seq# = 23
- B side received a packet with a greater sequence number than expected. Expected 21, got 23.  
Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 20 seq# = 20

EVENT time: 691.390442, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 20 seq# = 20

- A side received valid packet.

\*\* 21 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

- Updating sending window...

- Updated ACKS, restarted timer to reflect the oldest packet in the sending window.

- A side making sure all packets in sending window have been sent to B side...

- Message in window, already sent: vvvvvvvvvvvvvvvvvvvvvv ack# = 21 seq# = 21
- Message in window, already sent: wwwwwwwwwwwwwwwwwwwww ack# = 22 seq# = 22
- Message in window, already sent: xxxxxxxxxxxxxxxxxxxxxxxx ack# = 23 seq# = 23
- Message in window, already sent: yyyyyyyyyyyyyyyyyyyyyyyy ack# = 24 seq# = 24
- Message in window, already sent: zzzzzzzzzzzzzzzzzzzzzz ack# = 25 seq# = 25
- Message in window, already sent: aaaaaaaaaaaaaaaaaaaaaa ack# = 26 seq# = 26
- Message in window, already sent: bbbbbbbbbbbbbbbbbbbbbb ack# = 27 seq# = 27
- Sending NEW buffered message: cccccccccccccccccccccc ack# = 28 seq# = 28

EVENT time: 694.757019, type: 2, fromlayer3 entity: 1

- B side received packet: yyyyyyyyyyyyyyyyyyyy ack# = 24 seq# = 24

- B side received a packet with a greater sequence number than expected. Expected 21, got 24.

Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 20 seq# = 20

EVENT time: 696.968872, type: 2, fromlayer3 entity: 1

- B side received packet: rrrrrrrrrrrrrrrrrrrrrr ack# = 17 seq# = 17

- B side received a packet with a lower sequence number than expected. Expected 21, got 17.

Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 20 seq# = 20

EVENT time: 700.885559, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: xxxxxxxxxxxxxxxxxxxxxxxx

- Packet 75 buffered in sending buffer.

EVENT time: 701.197815, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 20 seq# = 20



- A side received valid packet.  
\*\* 21 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 718.543274, type: 1, fromlayer5 entity: 0  
- A side received message from upper layer: yyyyyyyyyyyyyyyyyyy  
- Packet 76 buffered in sending buffer.

EVENT time: 719.325439, type: 1, fromlayer5 entity: 0  
- A side received message from upper layer: zzzzzzzzzzzzzzzzzzzz  
- Packet 77 buffered in sending buffer.

EVENT time: 721.401489, type: 2, fromlayer3 entity: 1  
- B side received packet: uuuuuuuuuuuuuuuuuuuu ack# = 20 seq# = 20  
- B side received a packet with a lower  
sequence number than expected. Expected  
21, got 20.  
Discarding packet...  
- B side sending ACK for packet with highest  
in-order sequence number  
- B side sent ACK: ACK ack# = 20 seq# = 20  
TOLAYER3: packet being corrupted

EVENT time: 723.563660, type: 2, fromlayer3 entity: 0  
- A side received from Lower Layer: ACK ack# = 20 seq# = 20  
- A side received valid packet.  
\*\* 21 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 724.580017, type: 2, fromlayer3 entity: 0  
- A side received from Lower Layer: ACK ack# = 20 seq# = 20  
- A side received valid packet.  
\*\* 21 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 730.381348, type: 2, fromlayer3 entity: 1  
- B side received packet: vvvvvvvvvvvvvvvvvvvv ack# = 21 seq# = 21  
- B side received valid packet.  
Sending pkt to upper layer.  
- B side sending ACK for packet with highest  
in-order sequence number  
- B side sent ACK: ACK ack# = 21 seq# = 21

EVENT time: 731.390442, type: 0, timerinterrupt entity: 0  
- TIMEOUT - timer restarted,  
all packets in window resent  
- Sending Message: vvvvvvvvvvvvvvvvvvvv ack# = 21 seq# = 21  
- Sending Message: wwwwwwwwwwwwwwwwwwwww ack# = 22 seq# = 22  
TOLAYER3: packet being lost.  
- Sending Message: xxxxxxxxxxxxxxxxxxxxxx ack# = 23 seq# = 23  
TOLAYER3: packet being corrupted

- Sending Message:	yyyyyyyyyyyyyyyyyyyy	ack# = 24	seq# = 24
- Sending Message:	zzzzzzzzzzzzzzzzzzzz	ack# = 25	seq# = 25
- Sending Message:	aaaaaaaaaaaaaaaaaaaaa	ack# = 26	seq# = 26
TOLAYER3: packet being lost.			
- Sending Message:	bbbbbbbbbbbbbbbbbbbb	ack# = 27	seq# = 27
- Sending Message:	cccccccccccccccccccc	ack# = 28	seq# = 28

EVENT time: 732.282654, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 20 seq# = 999999  
 - A side received corrupt packet :(

EVENT time: 735.263245, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: aaaaaaaaaaaaaaaaaa  
 - Packet 78 buffered in sending buffer.

EVENT time: 735.820557, type: 2, fromlayer3 entity: 1

- B side received packet: xxxxxxxxxxxxxxxxxxxx ack# = 23 seq# = 23  
 - B side received a packet with a greater sequence number than expected. Expected 22, got 23.  
 Discarding packet...  
 - B side sending ACK for packet with highest in-order sequence number  
 - B side sent ACK: ACK ack# = 21 seq# = 21

EVENT time: 737.492859, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 21 seq# = 21  
 - A side received valid packet.

\*\* 22 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

- Updating sending window...  
 - Updated ACKS, restarted timer to reflect the oldest packet in the sending window.  
 - A side making sure all packets in sending window have been sent to B side...  

- Message in window, already sent:	wwwwwwwwwwwwwwwwwwww	ack# = 22	seq# = 22
- Message in window, already sent:	xxxxxxxxxxxxxxxxxxxxxx	ack# = 23	seq# = 23
- Message in window, already sent:	yyyyyyyyyyyyyyyyyyyy	ack# = 24	seq# = 24
- Message in window, already sent:	zzzzzzzzzzzzzzzzzzzz	ack# = 25	seq# = 25
- Message in window, already sent:	aaaaaaaaaaaaaaaaaaaaa	ack# = 26	seq# = 26
- Message in window, already sent:	bbbbbbbbbbbbbbbbbbbb	ack# = 27	seq# = 27
- Message in window, already sent:	cccccccccccccccccccc	ack# = 28	seq# = 28
- Sending NEW buffered message:	dddddddddddddddddd	ack# = 29	seq# = 29

 TOLAYER3: packet being lost.

EVENT time: 744.785461, type: 2, fromlayer3 entity: 1

- B side received packet: yyyyyyyyyyyyyyyyyy ack# = 24 seq# = 24  
 - B side received a packet with a greater sequence number than expected. Expected

22, got 24.

Discarding packet...

- B side sending ACK for packet with highest in-order sequence number

- B side sent ACK: ACK ack# = 21 seq# = 21

EVENT time: 744.826416, type: 2, fromlayer3 entity: 0

- A side received from Lower Layer: ACK ack# = 21 seq# = 21

- A side received valid packet.

\*\* 22 MESSAGES HAVE BEEN SENT SUCCESSFULLY \*\*

EVENT time: 746.562134, type: 1, fromlayer5 entity: 0

- A side received message from upper layer: bbbbbbbbbbbbbbbbbbbb

- Packet 79 buffered in sending buffer.

EVENT time: 748.833496, type: 2, fromlayer3 entity: 1