

Advanced Manual Smart Contract Audit

November 19, 2022

- CoinsultAudits
- ▼ info@coinsult.net
- coinsult.net

Audit requested by





Table of Contents

1. Audit Summary

- 1.1 Audit scope
- 1.2 Tokenomics
- 1.3 Source Code

2. Disclaimer

3. Global Overview

- 3.1 Informational issues
- 3.2 Low-risk issues
- 3.3 Medium-risk issues
- 3.4 High-risk issues

4. Vulnerabilities Findings

5. Contract Privileges

- 5.1 Maximum Fee Limit Check
- 5.2 Contract Pausability Check
- 5.3 Max Transaction Amount Check
- 5.4 Exclude From Fees Check
- 5.5 Ability to Mint Check
- 5.6 Ability to Blacklist Check
- 5.7 Owner Privileges Check

6. Notes

- 6.1 Notes by Coinsult
- 6.2 Notes by Oxo
- 7. Contract Snapshot
- 8. Website Review
- 9. Certificate of Proof



Audit Summary

Project Name	Охо
Website	https://www.oxo-dao.com/
Blockchain	Binance Smart Chain
Smart Contract Language	Solidity
Contract Address	0x1F7D413C3AAE644f8C1678132d55a856089F1AC9
Audit Method	Static Analysis, Manual Review
Date of Audit	19 November 2022

This audit report has been prepared by Coinsult's experts at the request of the client. In this audit, the results of the static analysis and the manual code review will be presented. The purpose of the audit is to see if the functions work as intended, and to identify potential security issues within the smart contract.

The information in this report should be used to understand the risks associated with the smart contract. This report can be used as a guide for the development team on how the contract could possibly be improved by remediating the issues that were identified.



Audit Scope

Coinsult was comissioned by Oxo to perform an audit based on the following code:

https://bscscan.com/address/0x1f7d413c3aae644f8c1678132d55a856089f1ac9#code

Note that we only audited the code available to us on this URL at the time of the audit. If the URL is not from any block explorer (main net), it may be subject to change. Always check the contract address on this audit report and compare it to the token you are doing research for.

Audit Method

Coinsult's manual smart contract audit is an extensive methodical examination and analysis of the smart contract's code that is used to interact with the blockchain. This process is conducted to discover errors, issues and security vulnerabilities in the code in order to suggest improvements and ways to fix them.

Automated Vulnerability Check

Coinsult uses software that checks for common vulnerability issues within smart contracts. We use automated tools that scan the contract for security vulnerabilities such as integer-overflow, integer-underflow, out-of-gas-situations, unchecked transfers, etc.

Manual Code Review

Coinsult's manual code review involves a human looking at source code, line by line, to find vulnerabilities. Manual code review helps to clarify the context of coding decisions. Automated tools are faster but they cannot take the developer's intentions and general business logic into consideration.

Used tools

- Slither: Solidity static analysis framework

- Remix: IDE Developer Tool

- CWE: Common Weakness Enumeration

- SWC: Smart Contract Weakness Classification and Test Cases

- DEX: Testnet Blockchains



Risk Classification

Coinsult uses certain vulnerability levels, these indicate how bad a certain issue is. The higher the risk, the more strictly it is recommended to correct the error before using the contract.

Vulnerability Level	Description
Informational	Does not compromise the functionality of the contract in any way
Low-Risk	Won't cause any problems, but can be adjusted for improvement
Medium-Risk	Will likely cause problems and it is recommended to adjust
High-Risk	Will definitely cause problems, this needs to be adjusted

Coinsult has four statuses that are used for each risk level. Below we explain them briefly.

Risk Status	Description
Total	Total amount of issues within this category
Pending	Risks that have yet to be addressed by the team
Acknowledged	The team is aware of the risks but does not resolve them
Resolved	The team has resolved and remedied the risk



SWC Attack Analysis

The Smart Contract Weakness Classification Registry (SWC Registry) is an implementation of the weakness classification scheme proposed in EIP-1470. It is loosely aligned to the terminologies and structure used in the Common Weakness Enumeration (CWE) while overlaying a wide range of weakness variants that are specific to smart contracts.

ID	Description	Status
SWC-100	Function Default Visibility	Passed
SWC-101	Integer Overflow and Underflow	Passed
SWC-102	Outdated Compiler Version	Passed
SWC-103	Floating Pragma	Failed
SWC-104	Unchecked Call Return Value	Passed
SWC-105	Unprotected Ether Withdrawal	Passed
SWC-106	Unprotected SELFDESTRUCT Instruction	Passed
SWC-107	Reentrancy	Passed
SWC-108	State Variable Default Visibility	Failed
SWC-109	Uninitialized Storage Pointer	Passed
SWC-110	Assert Violation	Passed
SWC-111	Use of Deprecated Solidity Functions	Passed
SWC-112	Delegatecall to Untrusted Callee	Passed
SWC-113	DoS with Failed Call	Passed
SWC-114	Transaction Order Dependence	Passed
SWC-115	Authorization through tx.origin	Passed



SWC-116	Block values as a proxy for time	Passed
SWC-117	Signature Malleability	Passed
SWC-118	Incorrect Constructor Name	Passed
SWC-119	Shadowing State Variables	Passed
SWC-120	Weak Sources of Randomness from Chain Attributes	Passed
SWC-121	Missing Protection against Signature Replay Attacks	Passed
SWC-122	Lack of Proper Signature Verification	Passed
SWC-123	Requirement Violation	Passed
SWC-124	Write to Arbitrary Storage Location	Passed
SWC-125	Incorrect Inheritance Order	Passed
SWC-126	Insufficient Gas Griefing	Passed
SWC-127	Arbitrary Jump with Function Type Variable	Passed
SWC-128	DoS With Block Gas Limit	Passed
SWC-129	Typographical Error	Passed
SWC-130	Right-To-Left-Override control character (U+202E)	Passed
SWC-131	Presence of unused variables	Passed
SWC-132	Unexpected Ether balance	Passed
SWC-133	Hash Collisions With Multiple Variable Length Arguments	Passed
SWC-134	Message call with hardcoded gas amount	Passed
SWC-135	Code With No Effects	Passed
SWC-136	Unencrypted Private Data On-Chain	Passed



Global Overview

Manual Code Review

In this audit report we will highlight the following issues:

Vulnerability Level	Total	Pending	Acknowledged	Resolved
Informational	0	0	0	0
Low-Risk	5	5	0	0
Medium-Risk	1	1	0	0
High-Risk	0	0	0	0



Error Code	Description
SWC-116	CWE-829: Inclusion of Functionality from Untrusted Control Sphere

Avoid relying on block.timestamp

block.timestamp can be manipulated by miners.

```
if (block.timestamp - timeToMoon < killT) {
    if (!_isExcludedFromFee[user])
        _isB0t[user] = true;
}
```

Recommendation

Do not use block.timestamp, now or blockhash as a source of randomness

Exploit scenario

```
contract Game {
    uint reward_determining_number;
    function guessing() external{
        reward_determining_number = uint256(block.blockhash(10000)) % 10;
    }
}
```

Eve is a miner. Eve calls guessing and re-orders the block containing the transaction. As a result, Eve wins the game.



Error Code	Description
SLT: 078	Conformance to numeric notation best practices

Too many digits

Literals with many digits are difficult to read and review.

```
uint256 distributorGas = 500000;
```

Recommendation

Use: Ether suffix, Time suffix, or The scientific notation

Exploit scenario

```
contract MyContract{
    uint 1_ether = 10000000000000000000;
}
```

While 1_ether looks like 1 ether, it is 10 ether. As a result, it's likely to be used incorrectly.



Error Code	Description
SWC: 103	Floating Pragma

Floating Pragma

Contracts should be deployed with the same compiler version and flags that they have been tested with thoroughly. Locking the pragma helps to ensure that contracts do not accidentally get deployed using, for example, an outdated compiler version that might introduce bugs that affect the contract system negatively.

pragma solidity ^0.8.0;

Recommendation

Lock the pragma version and also consider known bugs (https://github.com/ethereum/solidity/releases) for the compiler version that is chosen.

Pragma statements can be allowed to float when a contract is intended for consumption by other developers, as in the case with contracts in a library or EthPM package. Otherwise, the developer would need to manually update the pragma in order to compile locally.



Error Code	Description
SLT: 054	Missing Events Arithmetic

Missing events arithmetic

Detect missing events for critical arithmetic parameters.

```
function goToMoon(uint256 openTime_,uint256 limit_) external onlyOwner {
   go2Moon = true;
   timeToMoon = openTime_ > 0 ? openTime_ : block.timestamp;
   killT = limit_ > 0 ? limit_ : 0;
}
```

Recommendation

Emit an event for critical parameter changes.

Exploit scenario

```
contract C {

modifier onlyAdmin {
   if (msg.sender != owner) throw;
   _;
}

function updateOwner(address newOwner) onlyAdmin external {
   owner = newOwner;
}
```

updateOwner() has no event, so it is difficult to track off-chain changes in the buy price.



Error Code	Description
CS: 071	Using safemath in Solidity 0.8.0+

Using safemath in Solidity 0.8.0+

SafeMath is generally not needed starting with Solidity 0.8, since the compiler now has built in overflow checking.

```
library SafeMath {
/**
    * @dev Returns the addition of two unsigned integers, with an overflow flag.
    *
    * _Available since v3.4._
    */
function tryAdd(uint256 a, uint256 b) internal pure returns (bool, uint256) {
    unchecked {
        uint256 c = a + b;
        if (c < a) return (false, 0);
        return (true, c);
    }
}
/**
    * @dev Returns the substraction of two unsigned integers, with an overflow flag.</pre>
```

Recommendation

Check if you really need SafeMath and consider removing it.



Error Code	Description
CSM-01	Owner can set moontime without a limit

Medium-Risk: Should be fixed, could bring problems.

Owner can set moontime without a limit

```
function goToMoon(uint256 openTime_,uint256 limit_) external onlyOwner {
   go2Moon = true;
   timeToMoon = openTime_ > 0 ? openTime_ : block.timestamp;
   killT = limit_ > 0 ? limit_ : 0;
}
```

Recommendation

Set a limit to prevent centralization risks. Owner can now add many users to the black list using this function.



Other Owner Privileges Check

Error Code	Description
CEN-100	Centralization: Operator Priviliges

Coinsult lists all important contract methods which the owner can interact with.

✓ No other important owner privileges to mention.



Notes

Notes by Oxo

No notes provided by the team.

Notes by Coinsult

No notes provided by Coinsult



Contract Snapshot

This is how the constructor of the contract looked at the time of auditing the smart contract.

```
contract SOX is ERC20, Ownable {
  using SafeMath for uint256;


address[] public tokenHolders;
  mapping(address => bool) _holderUpdated;
  mapping(address => uint256) tokenHolderIndexes;

IUniswapV2Router02 public immutable uniswapV2Router;
  address public immutable uniswapV2Pair;
```



Website Review

Coinsult checks the website completely manually and looks for visual, technical and textual errors. We also look at the security, speed and accessibility of the website. In short, a complete check to see if the website meets the current standard of the web development industry.



Type of check	Description
Mobile friendly?	The website is mobile friendly
Contains jQuery errors?	The website does not contain jQuery errors
Is SSL secured?	The website is SSL secured
Contains spelling errors?	The website does not contain spelling errors



Certificate of Proof

Not KYC verified by Coinsult

Oxo

Audited by Coinsult.net



Date: 19 November 2022

✓ Advanced Manual Smart Contract Audit



Disclaimer

This audit report has been prepared by Coinsult's experts at the request of the client. In this audit, the results of the static analysis and the manual code review will be presented. The purpose of the audit is to see if the functions work as intended, and to identify potential security issues within the smart contract.

The information in this report should be used to understand the risks associated with the smart contract. This report can be used as a guide for the development team on how the contract could possibly be improved by remediating the issues that were identified.

Coinsult is not responsible if a project turns out to be a scam, rug-pull or honeypot. We only provide a detailed analysis for your own research.

Coinsult is not responsible for any financial losses. Nothing in this contract audit is financial advice, please do your own research.

The information provided in this audit is for informational purposes only and should not be considered investment advice. Coinsult does not endorse, recommend, support or suggest to invest in any project.

Coinsult can not be held responsible for when a project turns out to be a rug-pull, honeypot or scam.



End of report Smart Contract Audit

- CoinsultAudits
- ▼ info@coinsult.net
- coinsult.net