

Advanced Manual Smart Contract Audit

September 11, 2022

Audit requested by





Table of Contents

1. Audit Summary

- 1.1 Audit scope
- 1.2 Tokenomics
- 1.3 Source Code

2. Disclaimer

3. Global Overview

- 3.1 Informational issues
- 3.2 Low-risk issues
- 3.3 Medium-risk issues
- 3.4 High-risk issues

4. Vulnerabilities Findings

5. Contract Privileges

- 5.1 Maximum Fee Limit Check
- 5.2 Contract Pausability Check
- 5.3 Max Transaction Amount Check
- 5.4 Exclude From Fees Check
- 5.5 Ability to Mint Check
- 5.6 Ability to Blacklist Check
- 5.7 Owner Privileges Check

6. Notes

- 6.1 Notes by Coinsult
- 6.2 Notes by TrendoID
- 7. Contract Snapshot
- 8. Website Review
- 9. Certificate of Proof



Audit Summary

Audit Scope

Project Name	TrendoID
Website	https://trendo.id
Blockchain	Binance Smart Chain
Smart Contract Language	Solidity
Contract Address	0x9063073A088149956f292c14535E089aFE77BdB3
Audit Method	Static Analysis, Manual Review
Date of Audit	11 September 2022

This audit report has been prepared by Coinsult's experts at the request of the client. In this audit, the results of the static analysis and the manual code review will be presented. The purpose of the audit is to see if the functions work as intended, and to identify potential security issues within the smart contract.

The information in this report should be used to understand the risks associated with the smart contract. This report can be used as a guide for the development team on how the contract could possibly be improved by remediating the issues that were identified.



Tokenomics

Rank	Address	Quantity (Token)	Percentage
1	0xa8152d9db9ecc6e8b8a92fdc83cd402dca1af3c8	589,986,360,000	58.9986%
2	Pinksale: PinkLock V2	410,000,000,000	41.0000%
3	Null Address: 0x000dEaD	13,640,000	0.0014%

Source Code

Coinsult was comissioned by TrendoID to perform an audit based on the following code:

https://bscscan.com/address/0x9063073A088149956f292c14535E089aFE77BdB3#code



Disclaimer

This audit report has been prepared by Coinsult's experts at the request of the client. In this audit, the results of the static analysis and the manual code review will be presented. The purpose of the audit is to see if the functions work as intended, and to identify potential security issues within the smart contract.

The information in this report should be used to understand the risks associated with the smart contract. This report can be used as a guide for the development team on how the contract could possibly be improved by remediating the issues that were identified.

Coinsult is not responsible if a project turns out to be a scam, rug-pull or honeypot. We only provide a detailed analysis for your own research.

Coinsult is not responsible for any financial losses. Nothing in this contract audit is financial advice, please do your own research.

The information provided in this audit is for informational purposes only and should not be considered investment advice. Coinsult does not endorse, recommend, support or suggest to invest in any project.

Coinsult can not be held responsible for when a project turns out to be a rug-pull, honeypot or scam.



Global Overview

Manual Code Review

In this audit report we will highlight the following issues:

Vulnerability Level	Total	Pending	Acknowledged	Resolved
Informational	0	0	0	0
Low-Risk	6	6	0	0
Medium-Risk	0	0	0	0
High-Risk	0	0	0	0

Privilege Overview

Coinsult checked the following privileges:

Contract Privilege	Description
Owner can mint?	Owner cannot mint new tokens
Owner can blacklist?	Owner cannot blacklist addresses
Owner can set fees > 25%?	Owner can set the sell fee to 25% or higher
Owner can exclude from fees?	Owner can exclude from fees
Owner can pause trading?	Owner cannot pause the contract
Owner can set Max TX amount?	Owner can set max transaction amount

More owner priviliges are listed later in the report.



Contract contains Reentrancy vulnerabilities

Additional information: This combination increases risk of malicious intent. While it may be justified by some complex mechanics (e.g. rebase, reflections, buyback).

More information: Slither

```
function _transfer(address sender, address recipient, uint256 amount) private returns (bool) {
    require(sender != address(0), "ERC20: transfer from the zero address");
    require(recipient != address(0), "ERC20: transfer to the zero address");

if(inSwapAndLiquify)
{
    return _basicTransfer(sender, recipient, amount);
}
    else
{
    if(!isTxLimitExempt[sender] && !isTxLimitExempt[recipient]) {
        require(amount = minimumTokensBeforeSwap;

    if (overMinimumTokenBalance && !inSwapAndLiquify && !isMarketPair[sender] &;
    {
        if(swapAndLiquifyByLimitOnly)
            contractTokenBalance = minimumTokensBeforeSwap;
        swapAndLiquify(contractTokenBalance);
    }
    balances[sender] = balances[sender1.sub(amount. "Insufficient Balance");
```

Recommendation

Apply the check-effects-interactions pattern.

Exploit scenario

```
function withdrawBalance(){
    // send userBalance[msg.sender] Ether to msg.sender
    // if mgs.sender is a contract, it will call its fallback function
    if( ! (msg.sender.call.value(userBalance[msg.sender])() ) ){
        throw;
    }
    userBalance[msg.sender] = 0;
}
```

Bob uses the re-entrancy bug to call withdrawBalance two times, and withdraw more than its initial deposit to the contract.



Too many digits

Literals with many digits are difficult to read and review.

```
uint256 public _maxTxAmount = 10000000000000 * 10**_decimals;
```

Recommendation

Use: Ether suffix, Time suffix, or The scientific notation

Exploit scenario

```
contract MyContract{
    uint 1_ether = 100000000000000000000;
}
```

While 1_ether looks like 1 ether, it is 10 ether. As a result, it's likely to be used incorrectly.



No zero address validation for some functions

Detect missing zero address validation.

```
function setMarketingWalletAddress(address newAddress) external onlyOwner() {
    marketingWalletAddress = payable(newAddress);
}
```

Recommendation

Check that the new address is not zero.

Exploit scenario

```
contract C {

modifier onlyAdmin {
   if (msg.sender != owner) throw;
   _;
}

function updateOwner(address newOwner) onlyAdmin external {
   owner = newOwner;
}
```

Bob calls updateOwner without specifying the newOwner, soBob loses ownership of the contract.



Functions that send Ether to arbitrary destinations

Unprotected call to a function sending Ether to an arbitrary address.

```
function addLiquidity(uint256 tokenAmount, uint256 ethAmount) private {
    // approve token transfer to cover all possible scenarios
    _approve(address(this), address(uniswapV2Router), tokenAmount);

    // add the liquidity
    uniswapV2Router.addLiquidityETH{value: ethAmount}(
        address(this),
        tokenAmount,
        0, // slippage is unavoidable
        0, // slippage is unavoidable
        owner(),
        block.timestamp
    );
}
```

Recommendation

Ensure that an arbitrary user cannot withdraw unauthorized funds.

Exploit scenario

```
contract ArbitrarySend{
   address destination;
   function setDestination(){
       destination = msg.sender;
   }

   function withdraw() public{
       destination.transfer(this.balance);
   }
}
```

Bob calls setDestination and withdraw. As a result he withdraws the contract's balance.



Missing events arithmetic

Detect missing events for critical arithmetic parameters.

```
function setBuyTaxes(uint256 newLiquidityTax, uint256 newMarketingTax, uint256 newTeamTax) external only
    _buyLiquidityFee = newLiquidityTax;
    _buyMarketingFee = newMarketingTax;
    _buyTeamFee = newTeamTax;

_totalTaxIfBuying = _buyLiquidityFee.add(_buyMarketingFee).add(_buyTeamFee);
}
```

Recommendation

Emit an event for critical parameter changes.

Exploit scenario

```
contract C {

modifier onlyAdmin {
   if (msg.sender != owner) throw;
   _;
}

function updateOwner(address newOwner) onlyAdmin external {
   owner = newOwner;
}
```

updateOwner() has no event, so it is difficult to track off-chain changes in the buy price.



Redundant Statements

Detect the usage of redundant statements that have no effect.

```
function _msgData() internal view virtual returns (bytes memory) {
   this; // silence state mutability warning without generating bytecode - see https://github.com/ether
   return msg.data;
}
```

Recommendation

Remove redundant statements if they congest code but offer no value.

Exploit scenario

```
contract RedundantStatementsContract {
    constructor() public {
        uint; // Elementary Type Name
        bool; // Elementary Type Name
        RedundantStatementsContract; // Identifier
    }
    function test() public returns (uint) {
        uint; // Elementary Type Name
        assert; // Identifier
        test; // Identifier
        return 777;
    }
}
```

Each commented line references types/identifiers, but performs no action with them, so no code will be generated for such statements and they can be removed.



Contract Privileges

Maximum Fee Limit Check

Coinsult tests if the owner of the smart contract can set the transfer, buy or sell fee to 25% or more. It is bad practice to set the fees to 25% or more, because owners can prevent healthy trading or even stop trading when the fees are set too high.

Type of fee	Description
Transfer fee	Owner can set the transfer fee to 25% or higher
Buy fee	Owner can set the buy fee to 25% or higher
Sell fee	Owner can set the sell fee to 25% or higher

Note: this is a boolean check to 25%, we will not change this value in the report.



Contract Pausability Check

Coinsult tests if the owner of the smart contract has the ability to pause the contract. If this is the case, users can no longer interact with the smart contract; users can no longer trade the token.

Privilege Check	Description
Can owner pause the contract?	Owner cannot pause the contract



Max Transaction Amount Check

Coinsult tests if the owner of the smart contract can set the maximum amount of a transaction. If the transaction exceeds this limit, the transaction will revert. Owners could prevent normal transactions to take place if they abuse this function.

Privilege Check	Description
Can owner set max tx amount?	Owner can set max transaction amount



Exclude From Fees Check

Coinsult tests if the owner of the smart contract can exclude addresses from paying tax fees. If the owner of the smart contract can exclude from fees, they could set high tax fees and exclude themselves from fees and benefit from 0% trading fees. However, some smart contracts require this function to exclude routers, dex, cex or other contracts / wallets from fees.

Privilege Check	Description
Can owner exclude from fees?	Owner can exclude from fees



Ability To Mint Check

Coinsult tests if the owner of the smart contract can mint new tokens. If the contract contains a mint function, we refer to the token's total supply as non-fixed, allowing the token owner to "mint" more tokens whenever they want.

A mint function in the smart contract allows minting tokens at a later stage. A method to disable minting can also be added to stop the minting process irreversibly.

Minting tokens is done by sending a transaction that creates new tokens inside of the token smart contract. With the help of the smart contract function, an unlimited number of tokens can be created without spending additional energy or money.

Privilege Check	Description
Can owner mint?	Owner cannot mint new tokens



Ability To Blacklist Check

Coinsult tests if the owner of the smart contract can blacklist accounts from interacting with the smart contract. Blacklisting methods allow the contract owner to enter wallet addresses which are not allowed to interact with the smart contract.

This method can be abused by token owners to prevent certain / all holders from trading the token. However, blacklists might be good for tokens that want to rule out certain addresses from interacting with a smart contract.

Privilege Check	Description
Can owner blacklist?	Owner cannot blacklist addresses



Other Owner Privileges Check

Coinsult lists all important contract methods which the owner can interact with.

- ⚠ Owner can exclude addresses from max transaction limit
- ⚠ Owner can exclude addresses from max wallet balance limit
- ⚠ Owner can set wallet balance limit
- Owner has transferred ownership to deadwallet



Notes

Notes by TrendoID

No notes provided by the team.

Notes by Coinsult

✓ No notes provided by Coinsult




Contract Snapshot

This is how the constructor of the contract looked at the time of auditing the smart contract.



Website Review

Coinsult checks the website completely manually and looks for visual, technical and textual errors. We also look at the security, speed and accessibility of the website. In short, a complete check to see if the website meets the current standard of the web development industry.



Type of check	Description
Mobile friendly?	The website is mobile friendly
Contains jQuery errors?	The website does not contain jQuery errors
Is SSL secured?	The website is SSL secured
Contains spelling errors?	The website does not contain spelling errors



Certificate of Proof

Not KYC verified by Coinsult



✓ Advanced Manual Smart Contract Audit



Smart Contract Audit