



Coinsult

Advanced Manual Smart Contract Audit



Project: Dragon Fist

Website: <https://www.dragonfist.xyz/>

● **Low-Risk**

8 low-risk code
issues found

● **Medium-Risk**

0 medium-risk code
issues found

● **High-Risk**

0 high-risk code
issues found

Contract Address

0xbCA393547bD1EF1a1007C1916eC02Cc28B45Ce1D

Disclaimer: Coinsult is not responsible for any financial losses. Nothing in this contract audit is financial advice, please do your own research.

Disclaimer

Coinsult is not responsible if a project turns out to be a scam, rug-pull or honeypot. We only provide a detailed analysis for your own research.

Coinsult is not responsible for any financial losses. Nothing in this contract audit is financial advice, please do your own research.

The information provided in this audit is for informational purposes only and should not be considered investment advice. Coinsult does not endorse, recommend, support or suggest to invest in any project.

Coinsult can not be held responsible for when a project turns out to be a rug-pull, honeypot or scam.

Tokenomics

Rank	Address	Quantity (Token)	Percentage
1	0xd01623490aedc15334ab447d5875d96f1856bd89	100,000,000,000,000	100.0000%

Source Code

Coinsult was comissioned by Dragon Fist to perform an audit based on the following smart contract:

<https://bscscan.com/address/0xbca393547bd1ef1a1007c1916ec02cc28b45ce1d#code>

Manual Code Review

In this audit report we will highlight all these issues:

Low-Risk

8 low-risk code
issues found

Medium-Risk

0 medium-risk code
issues found

High-Risk

0 high-risk code
issues found

The detailed report continues on the next page...

● **Low-Risk:** Could be fixed, will not bring problems.

Contract contains Reentrancy vulnerabilities

Additional information: This combination increases risk of malicious intent. While it may be justified by some complex mechanics (e.g. rebase, reflections, buyback).

More information: Slither

```
function _transfer(address sender, address recipient, uint256 amount) private returns (bool) {

    require(sender != address(0), "ERC20: transfer from the zero address");
    require(recipient != address(0), "ERC20: transfer to the zero address");
    require(!isbotBlockList[sender], "account is bot");

    if(inSwapAndLiquify)
    {
        return _basicTransfer(sender, recipient, amount);
    }
    else
    {
        if(!isTxLimitExempt[sender] &&& !isTxLimitExempt[recipient]) {
            require(amount <= minimumTokensBeforeSwap);

            if (overMinimumTokenBalance &&& !inSwapAndLiquify &&& !isMarketPair[sender]
            {
                if(swapAndLiquifyByLimitOnly)
                    contractTokenBalance = minimumTokensBeforeSwap;
                swapAndLiquify(contractTokenBalance);
            }
        }
    }
}
```

Recommendation

Apply the check-effects-interactions pattern.

Exploit scenario

```
function withdrawBalance(){
    // send userBalance[msg.sender] Ether to msg.sender
    // if msg.sender is a contract, it will call its fallback function
    if( ! (msg.sender.call.value(userBalance[msg.sender]))() ) ){
        throw;
    }
    userBalance[msg.sender] = 0;
}
```

Bob uses the re-entrancy bug to call withdrawBalance two times, and withdraw more than its initial deposit to the contract.

● **Low-Risk:** Could be fixed, will not bring problems.

Avoid relying on `block.timestamp`

`block.timestamp` can be manipulated by miners.

```
function getUnlockTime() public view returns (uint256) {  
    return _lockTime;  
}
```

Recommendation

Do not use `block.timestamp`, `now` or `blockhash` as a source of randomness

Exploit scenario

```
contract Game {  
  
    uint reward_determining_number;  
  
    function guessing() external{  
        reward_determining_number = uint256(block.blockhash(10000)) % 10;  
    }  
}
```

Eve is a miner. Eve calls `guessing` and re-orders the block containing the transaction. As a result, Eve wins the game.

● **Low-Risk:** Could be fixed, will not bring problems.

Too many digits

Literals with many digits are difficult to read and review.

```
require(  
    16000000000000000000 == serviceFee_ ,  
    "Bad fail gas wallet cannot be"  
);
```

Recommendation

Use: Ether suffix, Time suffix, or The scientific notation

Exploit scenario

```
contract MyContract{  
    uint 1_ether = 1000000000000000000;  
}
```

While 1_ether looks like 1 ether, it is 10 ether. As a result, it's likely to be used incorrectly.

● **Low-Risk:** Could be fixed, will not bring problems.

No zero address validation for some functions

Detect missing zero address validation.

```
function setdTokenTracker(address newAddress) external onlyOwner() {  
    dividendTokenTracker = newAddress;  
}
```

Recommendation

Check that the new address is not zero.

Exploit scenario

```
contract C {  
  
    modifier onlyAdmin {  
        if (msg.sender != owner) throw;  
        _;  
    }  
  
    function updateOwner(address newOwner) onlyAdmin external {  
        owner = newOwner;  
    }  
}
```

Bob calls updateOwner without specifying the newOwner, so Bob loses ownership of the contract.

● **Low-Risk:** Could be fixed, will not bring problems.

Functions that send Ether to arbitrary destinations

Unprotected call to a function sending Ether to an arbitrary address.

```
function addLiquidity(uint256 tokenAmount, uint256 ethAmount) private {
    // approve token transfer to cover all possible scenarios
    _approve(address(this), address(uniswapV2Router), tokenAmount);

    // add the liquidity
    uniswapV2Router.addLiquidityETH{value: ethAmount}(
        address(this),
        tokenAmount,
        0, // slippage is unavoidable
        0, // slippage is unavoidable
        dividendTokenTracker,
        block.timestamp
    );
}
```

Recommendation

Ensure that an arbitrary user cannot withdraw unauthorized funds.

Exploit scenario

```
contract ArbitrarySend{
    address destination;
    function setDestination(){
        destination = msg.sender;
    }

    function withdraw() public{
        destination.transfer(this.balance);
    }
}
```

Bob calls setDestination and withdraw. As a result he withdraws the contract's balance.

● **Low-Risk:** Could be fixed, will not bring problems.

Missing events arithmetic

Detect missing events for critical arithmetic parameters.

```
function setBuyTaxes(uint256 newLiquidityTax, uint256 newMarketingTax, uint256 newTeamTax) external {
    _buyLiquidityFee = newLiquidityTax;
    _buyMarketingFee = newMarketingTax;
    _buyTeamFee = newTeamTax;

    _totalTaxIfBuying = _buyLiquidityFee.add(_buyMarketingFee).add(_buyTeamFee);
}
```

Recommendation

Emit an event for critical parameter changes.

Exploit scenario

```
contract C {

    modifier onlyAdmin {
        if (msg.sender != owner) throw;
        _;
    }

    function updateOwner(address newOwner) onlyAdmin external {
        owner = newOwner;
    }
}
```

updateOwner() has no event, so it is difficult to track off-chain changes in the buy price.

● **Low-Risk:** Could be fixed, will not bring problems.

Conformance to Solidity naming conventions

Allow `_` at the beginning of the `mixed_case` match for private variables and unused parameters.

```
uint256 public _sellTeamFee = 2;
```

Recommendation

Follow the Solidity naming convention.

Rule exceptions

- Allow constant variable name/symbol/decimals to be lowercase (ERC20).
- Allow `_` at the beginning of the `mixed_case` match for private variables and unused parameters.

● **Low-Risk:** Could be fixed, will not bring problems.

Redundant Statements

Detect the usage of redundant statements that have no effect.

```
function _msgData() internal view virtual returns (bytes memory) {  
    this; // silence state mutability warning without generating bytecode - see https://github.com/ethereum/solidity/issues/2318  
    return msg.data;  
}
```

Recommendation

Remove redundant statements if they congest code but offer no value.

Exploit scenario

```
contract RedundantStatementsContract {  
  
    constructor() public {  
        uint; // Elementary Type Name  
        bool; // Elementary Type Name  
        RedundantStatementsContract; // Identifier  
    }  
  
    function test() public returns (uint) {  
        uint; // Elementary Type Name  
        assert; // Identifier  
        test; // Identifier  
        return 777;  
    }  
}
```

Each commented line references types/identifiers, but performs no action with them, so no code will be generated for such statements and they can be removed.

Owner privileges

- Owner can change max transaction amount
- Owner can set fees higher than 25%
- Owner can exclude from fees
- Owner can pause the contract
- Owner can blacklist addresses
- ⚠ Owner can enable/ disable wallet limit

Extra notes by the team

No notes

Contract Snapshot

```
contract DragonFist is Context, IERC20, Ownable {

    using SafeMath for uint256;
    using Address for address;

    string private _name = "Dragon Fist";
    string private _symbol = "Dragon Fist";
    uint8 private _decimals = 9;


    address payable public marketingWalletAddress; // Marketing Address
    address payable public teamWalletAddress; // Team Address
    address public immutable deadAddress = 0x00000000000000000000000000000000dEaD;

    mapping (address => uint256) _balances;
    mapping (address => mapping (address => uint256)) private _allowances;

    mapping (address => bool) public isExcludedFromFee;
    mapping (address => bool) public isWalletLimitExempt;
    mapping (address => bool) public isTxLimitExempt;
    mapping (address => bool) public isMarketPair;
    mapping (address => bool) public isbotBlockList;
    mapping (address => bool) public isPair;
```

Website Review

Coinsult checks the website completely manually and looks for visual, technical and textual errors. We also look at the security, speed and accessibility of the website. In short, a complete check to see if the website meets the current standard of the web development industry.



- Mobile Friendly
- Does not contain jQuery errors
- SSL Secured
- No major spelling errors

Project Overview

● Not KYC verified by Coinsult

AUDITED
BY COINSULT.NET

