

# Open Addressing: Linear Probing

$$h' : U \rightarrow \{0, 1, \dots, m - 1\}$$

0	
5	
10	
14	

- Hash Function is  $h(x, i) = (h'(x) + i) \bmod m$  where  $h'(x)$  is original hash function.
- **Insert:** Attempts insertion at  $h'(x)$ , then  $h'(x) + 1$ ,  $h'(x) + 2$ , etc,. (wrapping around to 0 after reaching end of table) until empty slot is found and  $x$  inserted there.
- In our case  $h'(x) = x \bmod 15$
- Need to insert 19, 6, 18, 34, 25, 4 in that order

# Open Addressing: Linear Probing

$$h' : U \rightarrow \{0, 1, \dots, m - 1\}$$

0	
	19
5	
10	
14	

- Hash Function is  $h(x, i) = (h'(x) + i) \bmod m$  where  $h'(x)$  is original hash function.
- **Insert:** Attempts insertion at  $h'(x)$ , then  $h'(x) + 1$ ,  $h'(x) + 2$ , etc,. (wrapping around to 0 after reaching end of table) until empty slot is found and  $x$  inserted there.
- In our case  $h'(x) = x \bmod 15$
- Need to insert 19, 6, 18, 34, 25, 4 in that order

# Open Addressing: Linear Probing

$$h' : U \rightarrow \{0, 1, \dots, m - 1\}$$

0	
	19
5	
	6
10	
14	

- Hash Function is  $h(x, i) = (h'(x) + i) \bmod m$  where  $h'(x)$  is original hash function.
- **Insert:** Attempts insertion at  $h'(x)$ , then  $h'(x) + 1$ ,  $h'(x) + 2$ , etc,. (wrapping around to 0 after reaching end of table) until empty slot is found and  $x$  inserted there.
- In our case  $h'(x) = x \bmod 15$
- Need to insert 19, 6, 18, 34, 25, 4 in that order

# Open Addressing: Linear Probing

$$h' : U \rightarrow \{0, 1, \dots, m - 1\}$$

0	
	18
	19
5	
	6
10	
14	

- Hash Function is  $h(x, i) = (h'(x) + i) \bmod m$  where  $h'(x)$  is original hash function.
- **Insert:** Attempts insertion at  $h'(x)$ , then  $h'(x) + 1$ ,  $h'(x) + 2$ , etc,. (wrapping around to 0 after reaching end of table) until empty slot is found and  $x$  inserted there.
- In our case  $h'(x) = x \bmod 15$
- Need to insert 19, 6, 18, 34, 25, 4 in that order

# Open Addressing: Linear Probing

$$h' : U \rightarrow \{0, 1, \dots, m - 1\}$$

0	
	18
	19
5	34
	6
10	
14	

- Hash Function is  $h(x, i) = (h'(x) + i) \bmod m$  where  $h'(x)$  is original hash function.
- **Insert:** Attempts insertion at  $h'(x)$ , then  $h'(x) + 1$ ,  $h'(x) + 2$ , etc,. (wrapping around to 0 after reaching end of table) until empty slot is found and  $x$  inserted there.
- In our case  $h'(x) = x \bmod 15$
- Need to insert 19, 6, 18, 34, 25, 4 in that order

# Open Addressing: Linear Probing

$$h' : U \rightarrow \{0, 1, \dots, m - 1\}$$

0	
	18
	19
5	34
	6
10	25
14	

- Hash Function is  $h(x, i) = (h'(x) + i) \bmod m$  where  $h'(x)$  is original hash function.
- **Insert:** Attempts insertion at  $h'(x)$ , then  $h'(x) + 1$ ,  $h'(x) + 2$ , etc,. (wrapping around to 0 after reaching end of table) until empty slot is found and  $x$  inserted there.
- In our case  $h'(x) = x \bmod 15$
- Need to insert 19, 6, 18, 34, 25, 4 in that order

# Open Addressing: Linear Probing

$$h' : U \rightarrow \{0, 1, \dots, m-1\}$$

0	
	18
	19
5	34
	6
	4
10	25
14	

- Hash Function is  $h(x, i) = (h'(x) + i) \bmod m$  where  $h'(x)$  is original hash function.
- **Insert:** Attempts insertion at  $h'(x)$ , then  $h'(x) + 1$ ,  $h'(x) + 2$ , etc., (wrapping around to 0 after reaching end of table) until empty slot is found and  $x$  inserted there.
- In our case  $h'(x) = x \bmod 15$
- Need to insert 19, 6, 18, 34, 25, 4 in that order