

GrantGuru Normal Forms Disussion

Abdullahi Abdullahi, Mathieu Poulin, James Tedder, Colby Wirth

October 13, 2025

Highest Normal Form Achieved

The GrantGuru database design satisfies **Boyce-Codd Normal Form (BCNF)** but does not achieve Fourth Normal Form (4NF). Our design eliminates partial dependencies, transitive dependencies, and ensures all determinants are superkeys. However, multi-valued dependencies in the research fields' attributes prevent 4NF compliance.

How the Database Achieves BCNF

First Normal Form (1NF): Atomicity

The database achieves 1NF through atomic attributes and unique identification. The **User entity** properly decomposes the composite **Name** attribute into **f_name**, **l_name**, and **m_name**. All attributes (**user_id**, **email**, **hashed_password**, **institution**) contain single, indivisible values. The **Grant entity** maintains atomicity with single-valued attributes like **grant_id**, **grant_title**, **award_max_amnt**, and **provider**. The **Documents entity** stores atomic values for **document_id**, **document_name**, and **document_type**. Each entity has a primary key ensuring unique record identification.

Second Normal Form (2NF): No Partial Dependencies

The design satisfies 2NF by using single-attribute primary keys, preventing partial dependencies. In the **Application entity**, **application_id** serves as the primary key, and the non-key attribute **status** depends on the complete key. Since there are no composite primary keys, partial dependencies cannot exist. In the **Documents entity**, attributes like **document_type** depend entirely on **document_id**, not on any portion of a composite key.

Third Normal Form (3NF): No Transitive Dependencies

The database achieves 3NF by ensuring direct dependencies without transitive relationships. In the **Grant entity**, all attributes depend directly on **grant_id**: **grant_id** → **provider**, **grant_id** → **eligibility**, **grant_id** → **award_max_amnt**. Importantly, **award_max_amnt** and **award_min_amnt** are independent attributes both determined by **grant_id**, not by each other, avoiding transitive dependency. In the **User entity**, **institution** depends directly on **user_id**, not transitively through **email**. The **Application entity** demonstrates 3NF as **status** depends solely on **application_id** without intermediate non-key attributes.

Achieving BCNF: All Determinants Are Superkeys

BCNF requires that every determinant must be a superkey. The GrantGuru database satisfies this:

User Entity: Primary Key: **user_id**; Candidate Key: **email**. Both determinants are superkeys.

Grant Entity: Primary Key: **grant_id**. The only determinant is the primary key.

Application Entity: Primary Key: **application_id**; Potential Candidate Key: (**user_id**, **grant_id**). Both are candidate keys.

Documents and Internal Deadlines: Single primary keys (**document_id**, **deadline_id**) serve as sole determinants.

There are no functional dependencies where a non-superkey determines other attributes—every functional dependency has a superkey on the left side.

Why the Database Does Not Achieve 4NF

Fourth Normal Form eliminates multi-valued dependencies (MVDs). An MVD $\alpha\beta$ means that values of β associated with a given α are independent of other attributes. However, the GrantGuru database contains a MVD violation:

Multi-Valued Dependency in User Entity

The `research_fields` attribute creates: `user_id research_fields`

A faculty member has multiple independent research interests (e.g., 'Machine Learning,' 'Computer Vision,' 'NLP'). These are independent of `email` and `institution`. If stored as multiple rows, `email` and `institution` are redundantly repeated for each research field, violating 4NF.

Justification for Not Achieving 4NF

Implementation Simplicity: Avoiding separate research field tables accelerates initial deployment while preserving future normalization options.

Path to 4NF

To achieve 4NF, decomposition would be required:

```
User(user_id, email, hashed_password, f_name, l_name, m_name, institution)
UserResearchField(user_id, research_field)s
```

This would eliminate redundancy and satisfy 4NF by removing the multi-valued dependencies.