

Colby Crutcher

Lab 4

Secure Coding

Part 1

1.

```
(gdb) disass
Dump of assembler code for function main:
0x000055555555129 <+0>:      endbr64
0x00005555555512d <+4>:      push    %rbp
0x00005555555512e <+5>:      mov     %rsp,%rbp
=> 0x000055555555131 <+8>:      movl    $0x19,-0x4(%rbp)
0x000055555555138 <+15>:     movl    $0x1e,-0x8(%rbp)
0x00005555555513f <+22>:     movq    $0x2d,-0x10(%rbp)
0x000055555555147 <+30>:     mov     -0x4(%rbp),%edx
0x00005555555514a <+33>:     mov     -0x8(%rbp),%eax
0x00005555555514d <+36>:     add     %edx,%eax
0x00005555555514f <+38>:     cltq
0x000055555555151 <+40>:     sub     -0x10(%rbp),%rax
0x000055555555155 <+44>:     mov     %rax,-0x10(%rbp)
0x000055555555159 <+48>:     mov     $0x0,%eax
0x00005555555515e <+53>:     pop     %rbp
0x00005555555515f <+54>:     ret
End of assembler dump.
```

- `movl $0x19,-0x4(%rbp)` Store 32-bit value `0x19 = 25` → local int a.
- `movl $0x1e,-0x8(%rbp)` Store 32-bit value `0x1e = 30` → local int b.
- `movq $0x2d,-0x10(%rbp)` Store 64-bit value `0x2d = 45` → local 64-bit variable (long/long long) at `-0x10`.
- `mov -0x4(%rbp),%eax/%edx` = copies the values of aoffsets -4, and -8 into registers
- `add %edx, %eax` = `a + b` because it adds the values in `%edx` which is a, to the b value, which is `%eax`. It stores the result in `%eax` as well.
- `sub -0x10(%rbp),%rax` = the subtraction of the value c. it subtracts the value c located at offset memory `-0x10`, from the sum currently in the register.
- `mov %rax, -0x10(%rbp)` = This converts to `c = (a + b) - c`. It moves the final result from the register back into the memory location for variable c, updating its value.

Code in C:

```
int main(){
    int a = 25;        // 0x19
    int b = 30;        // 0x1e
    long c = 45;       // 0x2d (stored as 8 bytes)

    c = (long)(a + b) - c; // = 55 - 45 = 10

    return 0;
}
```

2.

```
(gdb) disass
Dump of assembler code for function main:
0x000055555555129 <+0>:    endbr64
0x00005555555512d <+4>:    push    %rbp
0x00005555555512e <+5>:    mov     %rsp,%rbp
=> 0x000055555555131 <+8>:    movl    $0x19,-0x4(%rbp)
0x000055555555138 <+15>:   movl    $0x1e,-0x8(%rbp)
0x00005555555513f <+22>:   mov     -0x4(%rbp),%eax
0x000055555555142 <+25>:   cmp     -0x8(%rbp),%eax
0x000055555555145 <+28>:   jle     0x55555555150 <main+39>
0x000055555555147 <+30>:   movl    $0x1,-0xc(%rbp)
0x00005555555514e <+37>:   jmp     0x55555555157 <main+46>
0x000055555555150 <+39>:   movl    $0x0,-0xc(%rbp)
0x000055555555157 <+46>:   mov     $0x0,%eax
0x00005555555515c <+51>:   pop     %rbp
0x00005555555515d <+52>:   ret
```

End of assembler dump.

- `movl 0x4(%rbp) → int x`, stores a 32-bit value `0x19 = 25` into local stack slot `-0x4 → local int x = 25`;
- `movl 0x8(%rbp) → int y`, stores 32-bit value `0x1e = 30` into local stack slot `-0x8 → local int y = 30`;
- `mov -0x4(%rbp),%eax` → loads the 32-bit value at `-0x4(%rbp)` (`x`) into `%eax` → `%eax = x`; (Now the compare will use `%eax` vs `y`.)
- `cmp -0x8(%rbp),%eax` → Compares `%eax` (`x`) with the value at `-0x8(%rbp)` (`y`). Internally it does `%eax - y` to set CPU flags (ZF/SF/OF), without storing the subtraction result. This is a conditional statement
- `jle 0x55555555150 <main+39>` → Jump if Less-or-Equal (signed) based on the flags from `cmp`. If `x ≤ y`, jump to `<main+39>` (the “if” branch).
- `movl $0x1,-0xc(%rbp)` → runs only if the jump was not taken (meaning `x > y`). Store 1 into local stack slot `-0xc → flag/result = 1`; (the “else” case)
- `jmp 0x55555555157 <main+46>` → Unconditional jump to skip over the “if” assignment, so the result is not overwritten.

- `movl $0x0,-0xc(%rbp)` → This runs only if `jle` was taken (meaning `x <= y`). Store 0 into local stack slot `-0xc` → `z = 0`; (the “if” case)
- `0xc(%rbp)` → `int z`
- `mov $0x0,%eax` → sets return value register to 0 → return 0;

Code in C:

```
int main(void) {
    int x = 25;    // Corresponds to: movl $0x19, -0x4(%rbp)
    int y = 30;    // Corresponds to: movl $0x1e, -0x8(%rbp)
    int z; // Corresponds to storage at -0xc(%rbp)

    if (x <= y) {    // movl $0x0, -0xc(%rbp)
        z = 0;
    } else { //movl $0x1, -0xc(%rbp)
        z = 1;
    }

    return 0; //mov $0x0, %eax
}
```

3.

3.

```
(gdb) disass
Dump of assembler code for function main:
0x000055555555129 <+0>:    endbr64
0x00005555555512d <+4>:    push    %rbp
0x00005555555512e <+5>:    mov     %rsp,%rbp
=> 0x000055555555131 <+8>:    movq    $0xa,-0x40(%rbp)
0x000055555555139 <+16>:   movq    $0x14,-0x38(%rbp)
0x000055555555141 <+24>:   movq    $0x1e,-0x30(%rbp)
0x000055555555149 <+32>:   movq    $0x28,-0x28(%rbp)
0x000055555555151 <+40>:   movq    $0x32,-0x20(%rbp)
0x000055555555159 <+48>:   movq    $0x0,-0x10(%rbp)
0x000055555555161 <+56>:   jmp     0x55555555175 <main+76>
0x000055555555163 <+58>:   mov     -0x10(%rbp),%rax
0x000055555555167 <+62>:   mov     -0x40(%rbp,%rax,8),%rax
0x00005555555516c <+67>:   add     %rax,-0x8(%rbp)
0x000055555555170 <+71>:   addq    $0x1,-0x10(%rbp)
0x000055555555175 <+76>:   cmpq    $0x4,-0x10(%rbp)
0x00005555555517a <+81>:   jle     0x55555555163 <main+58>
0x00005555555517c <+83>:   mov     $0x0,%eax
0x000055555555181 <+88>:   pop     %rbp
0x000055555555182 <+89>:   ret
End of assembler dump.
```

- `movq $0xa,-0x40(%rbp)` → Stores 64-bit value `0x0a = 10` into stack slot `-0x40`. This corresponds to the first element of a local long array → `arr[0]`

= 10;

- `movq $0x14,-0x38(%rbp)` → Stores 64-bit value `0x14 = 20` into stack slot `-0x38`. This corresponds to `→ arr[1] = 20;`
- `movq $0x1e,-0x30(%rbp)` → Stores 64-bit value `0x1e = 30` into stack slot `-0x30`. This corresponds to `→ arr[2] = 30;`
- `movq $0x28,-0x28(%rbp)` → Stores 64-bit value `0x28 = 40` into stack slot `-0x28`. This corresponds to `→ arr[3] = 40;`
- `movq $0x32,-0x20(%rbp)` → Stores 64-bit value `0x32 = 50` into stack slot `-0x20`. This corresponds to `→ arr[4] = 50;`
- `movq $0x0,-0x10(%rbp)` → Stores 64-bit value `0` into stack slot `-0x10`. This initializes the loop counter `→ long i = 0;`
- `jmp 0x55555555175 <main+76>` → Unconditional jump to the loop condition check before executing the loop body. This is how a while or for loop is implemented in assembly.
- `mov -0x10(%rbp),%rax` → Loads the current value of `i` into `%rax` → `%rax = i;`
- `mov -0x40(%rbp,%rax,8),%rax` → Loads the value of `arr[i]` into `%rax`. Explanation: `-0x40(%rbp)` is the base address of the array, `%rax` is the index, and `*8` accounts for 8-byte (long) elements.
- `add %rax,-0x8(%rbp)` → Adds the value of `arr[i]` to the variable stored at `-0x8(%rbp)`. This corresponds to `→ sum += arr[i];`
- `addq $0x1,-0x10(%rbp)` → Increments the loop counter stored at `-0x10(%rbp)` → `i++;`
- `cmpq $0x4,-0x10(%rbp)` → compares the loop counter `i` to 4 by computing `i - 4` and setting CPU flags. This prepares for a conditional loop check.
- `jle 0x55555555163 <main+58>` → Jump if Less-or-Equal (signed). If `i <= 4`, control jumps back to the loop body, continuing the loop.
- `mov $0x0,%eax` → Sets the return value register to 0 → `return 0;`

Code in C:

```
int main(void) {
    long arr[5] = {10, 20, 30, 40, 50};
    long i = 0;
    long sum = 0;           // this corresponds to -0x8(%rbp)

    while (i <= 4) {
        sum += arr[i];
        i++;
    }
}
```

```

    }
    return 0;
}

```

4.

```

(gdb) disass
Dump of assembler code for function main:
0x000055555555144 <+0>:    endbr64
0x000055555555148 <+4>:    push    %rbp
0x000055555555149 <+5>:    mov     %rsp,%rbp
=> 0x00005555555514c <+8>:    sub     $0x10,%rsp
0x000055555555150 <+12>:   movl    $0x5,-0x4(%rbp)
0x000055555555157 <+19>:   movl    $0x6,-0x8(%rbp)
0x00005555555515e <+26>:   mov     -0x8(%rbp),%edx
0x000055555555161 <+29>:   mov     -0x4(%rbp),%eax
0x000055555555164 <+32>:   mov     %edx,%esi
0x000055555555166 <+34>:   mov     %eax,%edi
0x000055555555168 <+36>:   call    0x55555555129 <fun>
0x00005555555516d <+41>:   mov     %eax,-0x4(%rbp)
0x000055555555170 <+44>:   mov     $0x0,%eax
0x000055555555175 <+49>:   leave
0x000055555555176 <+50>:   ret
End of assembler dump.
(gdb) disass fun
Dump of assembler code for function fun:
0x000055555555129 <+0>:    endbr64
0x00005555555512d <+4>:    push    %rbp
0x00005555555512e <+5>:    mov     %rsp,%rbp
0x000055555555131 <+8>:    mov     %edi,-0x4(%rbp)
0x000055555555134 <+11>:   mov     %esi,-0x8(%rbp)
0x000055555555137 <+14>:   mov     -0x4(%rbp),%edx
0x00005555555513a <+17>:   mov     -0x8(%rbp),%eax
0x00005555555513d <+20>:   add     %edx,%eax
0x00005555555513f <+22>:   sub     $0x1,%eax
0x000055555555142 <+25>:   pop     %rbp
0x000055555555143 <+26>:   ret
End of assembler dump.

```

main:

- `movl $0x5,-0x4(%rbp)` → stores 32-bit value `0x5 = 5` into local int → `int a = 5`;
- `movl $0x6,-0x8(%rbp)` → stores 32-bit value `0x6 = 6` into local int → `int b = 6`;
- `mov -0x8(%rbp),%edx` → loads `b` into `%edx` → `%edx = b`;

- `mov -0x4(%rbp),%eax` → loads `a` into `%eax` → `%eax = a`;
- `mov %edx,%esi` → copies `%edx` (`b`) into `%esi` (2nd integer argument register) → sets up `arg2` → 2nd arg = `b`;
- `mov %eax,%edi` → copies `%eax` (`a`) into `%edi` (1st integer argument register) → sets up `arg1` → 1st arg = `a`;
- `call 0x55555555129` → calls `fun(a, b)` and gets the return value in `%eax`.
- `mov %eax,-0x4(%rbp)` → stores return value back into local `a` → `a = fun(a, b)`;
- `mov $0x0,%eax` → sets return value to 0 → return 0;

fun:

- `mov %edi,-0x4(%rbp)` → stores the 1st argument into local int → `x = arg1`;
- `mov %esi,-0x8(%rbp)` → stores the 2nd argument into local int → `y = arg2`;
- `mov -0x4(%rbp),%edx` → loads `x` into `%edx` → `%edx = x`;
- `mov -0x8(%rbp),%eax` → loads `y` into `%eax` → `%eax = y`;
- `add %edx,%eax` → adds `x` into `%eax` → `%eax = y + x`; (so now `%eax = x + y`)
- `sub $0x1,%eax` → subtracts 1 from `%eax` → `%eax = (x + y) - 1`;
- `ret` (implied end) → returns with `%eax` holding the result → return `(x + y) - 1`;

Code in C:

```
int fun(int x, int y) {
    // fun returns the sum of the two args minus 1
    return (x + y) - 1;
}

int main(void) {
    int a = 5;
    int b = 6;

    // call fun(a, b) and store result back into a
    a = fun(a, b);

    return 0;
}
```

5.

(gdb) disass

Dump of assembler code for function **main**:

```
0x000055555555195 <+0>:    endbr64
0x000055555555199 <+4>:    push    %rbp
0x00005555555519a <+5>:    mov     %rsp,%rbp
=> 0x00005555555519d <+8>:    mov     $0xa,%edx
0x0000555555551a2 <+13>:   mov     $0x14,%esi
0x0000555555551a7 <+18>:   mov     $0x1e,%edi
0x0000555555551ac <+23>:   call    0x5555555514b <fun1>
0x0000555555551b1 <+28>:   mov     $0x0,%eax
0x0000555555551b6 <+33>:   pop     %rbp
0x0000555555551b7 <+34>:   ret
```

End of assembler dump.

(gdb) disass fun1

Dump of assembler code for function **fun1**:

```
0x00005555555514b <+0>:    endbr64
0x00005555555514f <+4>:    push    %rbp
0x000055555555150 <+5>:    mov     %rsp,%rbp
0x000055555555153 <+8>:    sub     $0x28,%rsp
0x000055555555157 <+12>:   mov     %rdi,-0x18(%rbp)
0x00005555555515b <+16>:   mov     %rsi,-0x20(%rbp)
0x00005555555515f <+20>:   mov     %rdx,-0x28(%rbp)
0x000055555555163 <+24>:   mov     -0x18(%rbp),%rax
0x000055555555167 <+28>:   imul    -0x20(%rbp),%rax
0x00005555555516c <+33>:   mov     -0x28(%rbp),%rdx
0x000055555555170 <+37>:   imul    %rdx,%rax
0x000055555555174 <+41>:   mov     %rax,-0x8(%rbp)
0x000055555555178 <+45>:   mov     -0x8(%rbp),%rdx
0x00005555555517c <+49>:   mov     -0x18(%rbp),%rax
0x000055555555180 <+53>:   mov     %rdx,%rsi
0x000055555555183 <+56>:   mov     %rax,%rdi
0x000055555555186 <+59>:   call    0x55555555129 <fun2>
0x00005555555518b <+64>:   mov     %rax,-0x8(%rbp)
0x00005555555518f <+68>:   mov     -0x8(%rbp),%rax
0x000055555555193 <+72>:   leave
0x000055555555194 <+73>:   ret
```

End of assembler dump.

```
(gdb) disass fun2
Dump of assembler code for function fun2:
0x000055555555129 <+0>:      endbr64
0x00005555555512d <+4>:      push    %rbp
0x00005555555512e <+5>:      mov     %rsp,%rbp
0x000055555555131 <+8>:      mov     %rdi,-0x18(%rbp)
0x000055555555135 <+12>:     mov     %rsi,-0x20(%rbp)
0x000055555555139 <+16>:     mov     -0x18(%rbp),%rax
0x00005555555513d <+20>:     sub     -0x20(%rbp),%rax
0x000055555555141 <+24>:     mov     %rax,-0x8(%rbp)
0x000055555555145 <+28>:     mov     -0x8(%rbp),%rax
0x000055555555149 <+32>:     pop     %rbp
0x00005555555514a <+33>:     ret
End of assembler dump.
```

main:

- `mov $0xa,%edx` → loads the constant 0x0a (= 10) into %edx, which is used as the 3rd integer argument register → sets up `arg3 = 10`.
- `mov $0x14,%esi` → loads the constant 0x14 (= 20) into %esi, which is the 2nd integer argument register → sets up `arg2 = 20`.
- `mov $0x1e,%edi` → loads the constant 0x1e (= 30) into %edi, which is the 1st integer argument register → sets up `arg1 = 30`.
- `call 0x5555555514b` → calls the function `fun1(arg1, arg2, arg3)` using the calling convention registers → this corresponds to `fun1(30, 20, 10)`;
- `mov $0x0,%eax` → sets the return value register to 0 → return 0;

```
int main(void) {
    fun1(30, 20, 10);
    return 0;
}
```

fun1:

- `mov %rdi,-0x18(%rbp)` → saves 1st argument → `x = arg1`;
- `mov %rsi,-0x20(%rbp)` → saves 2nd argument → `y = arg2`;
- `mov %rdx,-0x28(%rbp)` → saves 3rd argument → `z = arg3`;
- `mov -0x18(%rbp),%rax` → loads x into %rax → `%rax = x`;
- `imul -0x20(%rbp),%rax` → multiplies %rax by y → `%rax = x * y`;
- `mov -0x28(%rbp),%rdx` → loads z into %rdx → `%rdx = z`;
- `imul %rdx,%rax` → multiplies %rax by %rdx → `%rax = (x * y) * z`; (so `%rax = xyz`)

- `mov %rax,-0x8(%rbp)` → stores the product into a local variable → `prod = xyz`;
- Call `fun2(x, prod)`
- `mov -0x8(%rbp),%rdx` → loads `prod` into `%rdx` → `%rdx = prod`;
- `mov -0x18(%rbp),%rax` → loads `x` into `%rax` → `%rax = x`;
- `mov %rdx,%rsi` → sets up 2nd argument register for the call → `%rsi = prod`;
- `mov %rax,%rdi` → sets up 1st argument register for the call → `%rdi = x`;
- `call 0x55555555129` → calls `fun2(x, prod)` which returns `x - prod` in `%rax`.
- `mov %rax,-0x8(%rbp)` → stores return value from `fun2` → `result = fun2(x, prod)`;
- `mov -0x8(%rbp),%rax` → loads result into `%rax` for return → return result;

```
int fun1(int x, int y, int z) {
    // Multiply all three arguments
    int prod = x * y * z;

    // Call fun2 with x and the product
    // Returns x - (x * y * z)
    return fun2(x, prod);
}
```

fun2:

- `mov %rdi,-0x18(%rbp)` → saves 1st argument (in `%rdi`) into a local variable → `a = arg1`;
- `mov %rsi,-0x20(%rbp)` → saves 2nd argument (in `%rsi`) into a local variable → `b = arg2`;
- `mov -0x18(%rbp),%rax` → loads `a` into `%rax` → `%rax = a`;
- `sub -0x20(%rbp),%rax` → subtracts `b` from `%rax` → `%rax = a - b`; (this is the actual math)
- `mov %rax,-0x8(%rbp)` → stores the result (`a - b`) into a local variable → `result = a - b`;
- `mov -0x8(%rbp),%rax` → loads result back into `%rax` so it can be returned → return result;

```
int fun2(int a, int b) {
    // fun2 subtracts the second argument from the first
    return a - b;
}
```

Part 2

6.

```
#include <stdio.h>
int main() {
    char city[10];
    printf("Enter city: ");
    scanf("%s", city);
    printf("City: %s\n", city);
    return 0;
}
```

- Vulnerability: `scanf("%s", city);` has no length limit, so any input longer than 9 characters (+ null terminator) will overflow `char city[10]` and can corrupt stack data (the stack canary will likely detect this).
- Some good test cases for this I used was Spokane, Seattle. Anything after more than 9 characters will cause a break so for a fail test I did 'notarealcitythisshouldfail' to get over the character limit.




Figure 1: Successful Test




Figure 2: Failed test

My Fix:

```
#include <stdio.h>

int main() {
    char city[10];

    printf("Enter city: ");
```

```

    // Limit input to 9 chars + '\0'
    scanf("%9s", city);

    printf("City: %s\n", city);
    return 0;
}

```

- This works because %9s tells scanf to read at most 9 characters, leaving room for the '\0' terminator, preventing buffer overflow.

7.

```

#include <stdio.h>
int main()
{
    char buf[8];
    int i = 0;
    char c;
    while ((c = getchar()) != '\n') {
        buf[i++] = c;
    }
    buf[i] = '\0';
    printf("%s\n", buf);
    return 0;
}

```

- Vulnerability: buf is only 8 bytes, but the loop keeps writing buf[i++] = c; until newline with no bounds check, so long lines overflow buf. Also, buf[i] = '\0' can write out of bounds if i >= 8.
- For a safe input I just put the string 'hello', and it worked fine. To create an overflow, I did 'ABCDEFGHijkl', which is 12 characters causing an 'abort'




Figure 3: Working

My fix:

```

#include <stdio.h>

int main() {

```




Figure 4: Overflow

```
char buf[8];
int i = 0;
int c;

while ((c = getchar()) != '\n' && c != EOF) {
    if (i < (int)sizeof(buf) - 1) {
        buf[i++] = (char)c;
    }
    // else: ignore extra chars until newline
}

buf[i] = '\0';
printf("%s\n", buf);
return 0;
}
```

- This works because the code only writes if $i < \text{sizeof}(\text{buf}) - 1$, leaving space for `'\0'`. Extra characters are safely ignored until newline, so no overwrite happens. If you want it to accept more characters, just change the size of `buf`.




Figure 5: Working output(changed the buff size)

8.

```
#include <stdio.h>
int main()
{
    char buf[10];
    int i;
```

```

for (i = 0; i <= 10; i++)
    buf[i] = 'A';

printf("Done\n");
return 0;
}

```

- Vulnerability: char buf[10] arr is 10, but the loop runs for (i = 0; i <= 10; i++), which writes 11 bytes: buf[0] through buf[10]. buf[10] is out of bounds.




Figure 6: Output

My fix:

```

#include <stdio.h>

int main() {
    char buf[10];
    int i;

    for (i = 0; i < 10; i++)
        buf[i] = 'A';

    printf("Done\n");
    return 0;
}

```

- This works because $i < 10$ ensures the last write is buf[9], which is the final valid element.



Figure 7: Fixed code output

9.

```

int fun (double *to, double *from, int pos, int n)
{

```

```

int k;
for (k=0; k<n; k++)
{
to[pos] = from[k];
pos++;
}
return pos;
}

```

- Vulnerability: to[pos] = from[k] writes starting at pos for n elements without checking that pos and pos+n-1 are within the bounds of array to. If pos is near the end (or negative), it writes out of bounds
- For my main function, I included an overflow test case, and a call that stays in bounds.

```

#include <stdio.h>

```

```

int fun(double *to, double *from, int pos, int n)
{
    int k;
    for (k = 0; k < n; k++) {
        to[pos] = from[k];
        pos++;
    }
    return pos;
}

int main(void) {
    double to[5]    = {0, 0, 0, 0, 0};
    double from[5]  = {1.1, 2.2, 3.3, 4.4, 5.5};

    // Safe test case
    fun(to, from, 1, 3); // writes to[1..3]
    printf("Safe:  %.1f %.1f %.1f %.1f %.1f\n", to[0], to[1], to[2], to[3], to[4]);

    // Overflow test case (writes past to[4])
    fun(to, from, 4, 3); // tries to write to[4], to[5], to[6] (overflow)
    printf("After overflow attempt: %.1f %.1f %.1f %.1f %.1f\n",
        to[0], to[1], to[2], to[3], to[4]);

    return 0;
}

```

```
colby@Colby-PC:/mnt/c/Users/wcrut/OneDrive/Documents/GitHub/SecureCoding/Labs/Lab4$ ./q9
Safe:  0.0 1.1 2.2 3.3 0.0
After overflow attempt: 0.0 1.1 2.2 3.3 1.1
```

Figure 8: Output with main function

My fix:

```
#include <stdio.h>

int fun(double *to, int to_len, double *from, int pos, int n)
{
    int k;

    // Clamp pos to valid range
    if (pos < 0) pos = 0;
    if (pos > to_len) pos = to_len;

    // Clamp n so we never write past to[to_len-1]
    if (n < 0) n = 0;
    if (pos + n > to_len) {
        n = to_len - pos;
    }

    for (k = 0; k < n; k++) {
        to[pos] = from[k];
        pos++;
    }
    return pos;
}

int main(void) {
    double to[5] = {0, 0, 0, 0, 0};
    double from[5] = {1.1, 2.2, 3.3, 4.4, 5.5};

    fun(to, 5, from, 1, 3);
    printf("Safe:  %.1f %.1f %.1f %.1f %.1f\n", to[0], to[1], to[2], to[3], to[4]);

    // Same overflow attempt now becomes safe (copy is clamped)
    fun(to, 5, from, 4, 3);
    printf("After clamped copy: %.1f %.1f %.1f %.1f %.1f\n",
        to[0], to[1], to[2], to[3], to[4]);

    return 0;
}
```

}

- This works because instead of rejecting user input, it makes the function safe by clamping pos and n so the copy stays inside to[]

```
colby@Colby-PC:/mnt/c/Users/wcrut/OneDrive/Documents/GitHub/SecureCoding/Labs/Lab4$ ./q9
Safe:  0.0 1.1 2.2 3.3 0.0
After clamped copy: 0.0 1.1 2.2 3.3 1.1
colby@Colby-PC:/mnt/c/Users/wcrut/OneDrive/Documents/GitHub/SecureCoding/Labs/Lab4$
```

Figure 9: Revised code output