Linus timeline planner

U1 UNIT **planWalk.spec.js**

folds the points a group only walks through into the stop it walks on from

```
    expect(stops.map((s) => s.name || s.number)).toEqual(['Gate', 'Hall', 3])
    expect(stops[0].rows.map((r) => r.t_s)).toEqual([0, 120, 240])
    expect(stops[0].via.map((r) => r.t_s)).toEqual([120, 240])
    expect(stops[0].endsAt).toBe(rows[3].planned_at)
```

C1 COMPONENT **PlanProblems.spec.js**

separates errors from warnings, and keeps a dismissed warning out of the way until it is asked for

```
    expect(wrapper.get('[data-testid="problems-errors"]').text()).toBe('2 errors')
    expect(wrapper.get('[data-testid="problems-warnings"]').text()).toBe('1 warning')
    expect(wrapper.findAll('[data-testid="plan-problem"]')).toHaveLength(2)
    expect(wrapper.findAll('[data-testid="plan-warning"]')).toHaveLength(1)
```

C2 COMPONENT **PlanProblems.spec.js**

gives the fixes to a planner, and only points a reader at where the problem is

```
    expect(reader.find('[data-testid="fix-suggest"]').exists()).toBe(false)
    expect(reader.find('[data-testid="problems-lock"]').exists()).toBe(false) // the lock is a warning to the editor
    await reader.get('[data-testid="problem-show"]').trigger('click')
    expect(reader.emitted('show')[0][0]).toMatchObject({ id: 'e1' })
```

E1 E2E **planning.spec.js**

a group with no position is placed with

```
  await expect(place).toHaveCount(2) // Alpha and Bravo: nobody is on the map yet
  await place.first().click()
  await expect(page.getByTestId('board-hint')).toContainText('Tap the map where')
  await expect(page.locator('.pv-map')).toHaveClass(/leaflet-container/)
```

E2 E2E **touch.spec.js**

a finger a little off a frame dot still opens that frame

```
  await expect(page.locator('.pv-frame')).toHaveCount(3)
  const dot = page.locator('.pv-frame').nth(2)
  await expect(page.getByTestId('insp-tab-frame')).toBeVisible()
  await dot.evaluate((el) => el.scrollIntoView({ block: 'center' }))
```

vitest run

```
src/utils/__tests__/planWalk.spec.js (3 tests) 8ms
src/components/__tests__/PlanProblems.spec.js (2 tests) 93ms
Test Files 2 passed (2)
Tests 5 passed (5)
```

playwright test

```
ok planning.spec.js a group with no position is placed with "Place
on map" and one tap (5.6s)
ok touch.spec.js a finger a little off a frame dot still opens that
frame (4.3s)
```

Komin live operations dashboard

U1 UNIT **permissions.spec.js**

gives the whole event to the root and the planners, and everyone else their own group

```
      expect(can('wholeEvent', row.role), at('wholeEvent')).toBe(row.whole)
      expect(canView('map', row.role), at('map')).toBe(row.map)
      expect(canView('people', row.role), at('people')).toBe(row.people)
      expect(canEdit('timeline', row.role), at('edit the plan')).toBe(row.plan)
```

C1 COMPONENT **EventOverview.spec.js**

reads out the status and the counts it was given, and shows the invite code to staff only

```
    expect(planner.get('[data-testid="overview-status"]').text()).toBe('Live now')
    expect(planner.text()).toContain('4 in 2 groups')
    expect(planner.get('[data-testid="join-code-display"]').text()).toBe('ABC123')
    const scheduled = mountOverview({
```

C2 COMPONENT **EventOverview.spec.js**

will not save an end that is before the start, and saves nothing until something has changed

```
    expect(save().attributes('disabled')).toBeDefined()
    await wrapper.get('[data-testid="overview-name"]').setValue('Night Walk 2026')
    expect(save().attributes('disabled')).toBeUndefined()
    const startsAt = '2026-11-05T19:00'
```

E1 E2E **komin.spec.js**

the dashboard counts the event, and a member is shown neither the count nor the invite code

```
  await expect(planner.getByTestId('overview')).toBeVisible({ timeout: 30_000 })
  await expect(planner.getByTestId('overview')).toContainText('6 in 2 groups')
  await expect(planner.getByTestId('join-code-display')).toHaveText(ev.joinCode)
  await shot(planner, 'ops-01-planner-dashboard')
```

E2 E2E **komin.spec.js**

the live map keeps working when the OneMap tiles do not load

```
  await expect(page.getByTestId('live-map')).toBeVisible({ timeout: 30_000 })
  await expect(page.locator('.leaflet-container')).toBeVisible()
  await expect(page.locator('.leaflet-control-zoom')).toBeVisible()
  const size = await page.locator('.leaflet-container').evaluate((el) => [el.clientWidth, el.clientHeight])
```

vitest run

```
src/utils/__tests__/permissions.spec.js (1 test) 3ms
src/components/__tests__/EventOverview.spec.js (2 tests) 125ms
Test Files 2 passed (2)
Tests 3 passed (3)
```

playwright test

```
ok komin.spec.js the dashboard counts the event, and a member is
shown neither the count nor the invite code (11.4s)
ok komin.spec.js the live map keeps working when the OneMap tiles
do not load (7.4s)
```

Ern Qi attendance

U1 UNIT **useAttendance.spec.js**

accepts exactly what the IC screen shows, and refuses anything else without guessing

```
    expect(parseAttendanceQr('PLANOVA-ATT|9f2c-rollcall|a1b2c3')).toEqual({ rollcallId: '9f2c-rollcall', token: 'a1b2c3' })
    expect(parseAttendanceQr('PLANOVA-ATT|0|0')).toEqual({ rollcallId: '0', token: '0' })
    expect(parseAttendanceQr('https://example.com/menu')).toBe(null)
    expect(parseAttendanceQr('PLANOVA-ATT|only-two-parts')).toBe(null)
```

C1 COMPONENT **AttendancePanel.spec.js**

by hand: counts who is present, who is not marked yet, and sends the one mark that was asked for

```
    expect(wrapper.find('[data-testid="attendance-mode"]').exists()).toBe(true)
    expect(wrapper.find('[data-testid="attendance-mode-qr"]').exists()).toBe(true)
    expect(wrapper.get('[data-testid="attendance-count"]').text()).toContain('1 of 2 present')
    expect(wrapper.find('[data-testid="att-present-qa_member"]').exists()).toBe(true)
```

C2 COMPONENT **AttendancePanel.spec.js**

by QR: shows the code that changes every 5 seconds, and only a planner may still tick somebody by hand

```
    expect(ic.find('[data-testid="attendance-qr-box"]').exists()).toBe(true)
    await ic.setProps({ qr })
    await flushPromises()
    expect(ic.find('[data-testid="attendance-qr"]').exists()).toBe(true)
```

E1 E2E **sos-attendance.spec.js**

the IC takes a roll call by hand; the member sees they are marked present

```
  await expect(ic.getByTestId('attendance-run')).toBeVisible({ timeout: 20_000 })
  await ic.getByTestId('attendance-title').fill('Morning muster')
  await ic.getByTestId('attendance-start').click()
  await expect(ic.getByTestId('att-mark-qa_member')).toBeVisible({ timeout: 20_000 })
```

E2 E2E **sos-attendance.spec.js**

in QR mode the member checks in with the code on the IC

```
  await expect(ic.getByTestId('attendance-qr')).toBeVisible({ timeout: 20_000 })
  await shot(ic, 'att-04-ic-qr', { fullPage: true })
  const member = pages.member
  await member.goto(`/events/${ev.eventId}/attendance`)
```

vitest run

```
src/composables/__tests__/useAttendance.spec.js (1 test) 5ms
src/components/__tests__/AttendancePanel.spec.js (2 tests) 110ms
Test Files 2 passed (2)
Tests 3 passed (3)
```

playwright test

```
ok sos-attendance.spec.js the IC takes a roll call by hand; the
member sees they are marked present (9.0s)
ok sos-attendance.spec.js in QR mode the member checks in with the
code on the IC's screen, and an old code is refused (23.8s)
```

Rui Heng event setup and invite

U1 UNIT **eventWizard.spec.js**

names the missing detail at step 1 and the reason at step 3, and nothing on a step that is fine

```
    expect(wizard.validate(1)).toEqual({
      name: 'Give the event a name',
      startsAt: 'Pick a start date and time',
      endsAt: 'Pick an end date and time',
```

C1 COMPONENT **InvitePanel.spec.js**

shows one code in every place it is offered: the panel, the link and both shares

```
    expect(wrapper.get('[data-testid="join-code-display"]').text()).toBe('ABC123')
    const link = 'https://gpstesting.vercel.app/join/ABC123'
    expect(wrapper.get('[data-testid="invite-link"]').text()).toBe(link)
    const whatsapp = wrapper.get('[data-testid="share-whatsapp"]').attributes('href')
```

C2 COMPONENT **InvitePanel.spec.js**

copies the code, and still explains itself when the browser refuses the clipboard

```
    expect(writeText).toHaveBeenCalledWith('ABC123')
    expect(toast).toHaveBeenCalledWith('Event code copied.', 'success', 2500)
    await wrapper.find('.ov2-link button').trigger('click')
    await flushPromises()
```

E1 E2E **wizard.spec.js**

root makes an event with people and a group, then deletes it

```
  await expect(page.getByTestId('wiz-errors')).toBeVisible() // no name, no times
  await shot(page, 'wiz-01-errors')
  const name = 'QA-Wizard ' + Date.now().toString(36)
  await page.getByTestId('wiz-name').fill(name)
```

E2 E2E **event-flow.spec.js**

someone outside joins with the code and lands in the event as a member

```
  await expect(page).toHaveURL(new RegExp(`/events/${ev.eventId}`))
  await shot(page, 'flow-13-outsider-joined')
```

vitest run

```
src/stores/__tests__/eventWizard.spec.js (1 test) 15ms
src/components/__tests__/InvitePanel.spec.js (2 tests) 73ms
Test Files 2 passed (2)
Tests 3 passed (3)
```

playwright test

```
ok wizard.spec.js root makes an event with people and a group, then
deletes it (12.4s)
ok event-flow.spec.js someone outside joins with the code and lands
in the event as a member (3.2s)
```

Kenneth groups and users

U1 UNIT **people.spec.js**

draws initials, escapes a name before it becomes markup, and says how long ago a reading was

```
    expect(initials('Komin Chow')).toBe('KC')
    expect(initials('  hazel  tan ')).toBe('HT') // spaces are not a third word
    expect(initials('Bob')).toBe('BO')
    expect(initials('')).toBe('?') // the fallback is a placeholder, not an exception
…
```

C1 COMPONENT **PeoplePanel.spec.js**

offers a role change only on the rows this role may change, and only the roles somebody actually has

```
…
    expect(root.find('[data-testid="person-role-select-qa_member"]').exists()).toBe(true)
    expect(root.find('[data-testid="person-role-select-qa_admin"]').exists()).toBe(true)
    expect(root.find('[data-testid="person-role-select-qa_root"]').exists()).toBe(false)
    expect(root.find('[data-testid="person-ic-qa_ic1"]').exists()).toBe(true)
…
```

C2 COMPONENT **MembersPanel.spec.js**

opens on my own group and only that one, with no controls for a member who may not change it

```
…
    expect(ic.find('[data-testid="group-view-Gate Crew"]').exists()).toBe(true)
    expect(ic.find('[data-testid="group-view-Stage"]').exists()).toBe(false)
    expect(ic.find('[data-testid="group-card-Stage"]').exists()).toBe(false)
    expect(ic.find('[data-testid="group-back"]').exists()).toBe(false)
…
```

E1 E2E **kenneth.spec.js**

a planner moves a person from one group to another, and the database agrees

```
…
  await expect(select).toBeVisible({ timeout: 30_000 })
  await select.selectOption({ label: 'Bravo' })
  await page.getByTestId('confirm-ok').click()
  await shot(page, 'people-01-moved')
…
```

E2 E2E **kenneth.spec.js**

the People page is still usable on a phone, with no sideways scroll

```
…
  await expect(page.getByTestId('people-list')).toBeVisible({ timeout: 30_000 })
  const row = page.getByTestId('person-qa_member')
  await expect(row).toBeVisible()
  const overflow = await page.evaluate(
…
```

vitest run

```
src/utils/__tests__/people.spec.js (1 test) 2ms
src/components/__tests__/MembersPanel.spec.js (1 test) 64ms
src/components/__tests__/PeoplePanel.spec.js (1 test) 93ms
Test Files 3 passed (3)
Tests 3 passed (3)
```

playwright test

```
ok kenneth.spec.js a planner moves a person from one group to
another, and the database agrees (5.0s)
ok kenneth.spec.js the People page is still usable on a phone, with
no sideways scroll (4.1s)
```

Hazel venue areas on the map

U1 UNIT **areaShape.spec.js**

calls a plain square legal, refuses a bow tie, and does not mistake a shared corner for a crossing

```
    expect(pathCrossing(SQUARE)).toBe(null)
    expect(closingCrosses(SQUARE)).toBe(false)
    expect(ringCrossing(SQUARE)).toBe(null)
    expect(edgesCross([0, 0], [1, 1], [1, 1], [2, 0])).toBe(false)
…
```

C1 COMPONENT **AreaListGroups.spec.js**

groups the areas by type in the order of the type dropdown, and says nothing about a type with none

```
…
    expect(groupKeys(wrapper)).toEqual(['zone', 'stage', 'entrance'])
    expect(wrapper.get('[data-testid="area-group-zone"]').text()).toBe('Zone (1)')
    expect(wrapper.find('[data-testid="area-group-no_go"]').exists()).toBe(false)
    expect(wrapper.find('[data-testid="area-group-obstacle"]').exists()).toBe(false)
…
```

C2 COMPONENT **AreaListGroups.spec.js**

keeps a type this build does not know in Other, and changes the name and the code only when they are valid

```
…
    expect(groupKeys(wrapper)).toEqual(['other'])
    expect(wrapper.get('[data-testid="area-group-other"]').text()).toBe('Other (1)')
    expect(wrapper.find('[data-testid="area-row-Helipad"]').exists()).toBe(true)
    expect(wrapper.text()).toContain('GATE_A') // the code a plan and the radio refer to
…
```

E1 E2E **hazel.spec.js**

an area drawn as No-Go is still No-Go after a reload, and is listed under it

```
…
  await expect(draw).toBeVisible({ timeout: 30_000 })
  await draw.click()
  const map = page.locator('.bench-map')
  const box = await map.boundingBox()
…
```

E2 E2E **planning.spec.js**

a locked area lets presses through, and the lock is stored on the shape

```
…
  await expect(draw).toBeVisible({ timeout: 20_000 })
  await draw.click()
  const map = page.locator('.bench-map')
  const box = await map.boundingBox()
…
```

vitest run

```
src/utils/__tests__/areaShape.spec.js (1 test) 3ms
src/components/__tests__/AreaListGroups.spec.js (2 tests) 109ms
Test Files 2 passed (2)
Tests 3 passed (3)
```

playwright test

```
ok hazel.spec.js an area drawn as No-Go is still No-Go after a
reload, and is listed under it (9.8s)
ok planning.spec.js a locked area lets presses through, and the
lock is stored on the shape (16.3s)
```