




This document is the property of Amphenol Corporation and is delivered on the express condition that it is not to be disclosed, reproduced or used, in whole or in part, for manufacture or sale by anyone other than Amphenol Corporation without its prior consent, & that no right is granted to disclose or to use any information in this document.

Customer drawing



Recommended PCB layout
Tolerance: $\pm 0.05\text{mm}$

Dimensions

Positions	A	B	C	E
9	30.81	24.99	16.92	11.08
15	39.20	33.30	25.25	19.39
25	53.05	47.04	38.96	33.24
37	69.40	63.50	55.42	49.86




REVISIONS

SYM	ECN	DESCRIPTION	DATE	APPROVED
1	HK--	First Release Drawing	01/20/17	IP

D-SUB TECHNICAL DATA

SHELL: SPCC, 100u" min Tin over 50u" min Nickel over 50u" min Copper
BODY: PBT, UL 94V-0 Color: Black.
CONTACTS: Copper alloy
Gold flash over 50u" Nickel on mating area
100u" Tin over 50u" Nickel on solder area
BOARDLOCK: Copper alloy, Tin plated
SCREWLOCK: Copper alloy, Nickel plated
RIVET: Copper alloy, Nickel plated
ELECTRICAL: Current Rating: 3A
Voltage Rating: 250 VAC (RMS) Max.
Contact Resistance: 20 mohms Max.
Insulation Resistance: 1000 Mohms Min
Withstanding voltage: 1000V Rms
MARKING : Amphenol...(Series No.)
Commercial reference
Manufacturing date

PRODUCT CODE



UNLESS OTHERWISE SPECIFIED TOLERANCES		APPROVAL		DATE
U.S.	METRIC	DRAWN	Simon Chen	01/20/17
.X +/-	0.50	CHECKED	Tony Tang	01/20/17
.XX +/-	0.30	CHECKED		
.XXX +/-	0.20			
FRACTIONS +/-				
ANGLES +/-	5°			
FOR MATERIALS AND FINISHES SEE NOTES		DRAWING FILE :		
REMOVE SHARP EDGES		ANGLE OF PROJECTION		
DIMENSIONS				
U.S.	INCHES			
METRIC	MM			

Amphenol

TITLE
D-sub connector,SD Series

SIZE	DRAWING NO.	REV.
A4	L717SDXXXPA4CH3F	1
SCALE	NONE	SHEET 1 OF 1