

Troubleshooting Heart Rate Monitor (HRM) Pairing

Pairing a heart rate monitor (HRM) allows users to record accurate BPM data during workouts and races. If an HRM fails to connect or disconnects during a session, follow the steps below to verify setup and isolate the issue.

1. Confirm the HRM is powered on, worn with direct skin contact, and using a fresh battery.
2. If the strap uses conductive pads, have the user lightly moisten the sensors for better contact.
3. Ask the user to confirm Bluetooth or ANT+ is enabled on their device.
4. Instruct the user to open the device pairing screen in the fitness application.
5. Have the user select **Heart Rate** from the available pairing options.
 - a. If multiple HRMs appear, ensure the user selects the correct model.
6. Once paired, confirm the status indicator is displaying live BPM data.

If no BPM data appears:

1. Have the user unpair the HRM and pair it again.
2. Ask the user to restart the application and retry pairing.
3. Verify no other fitness apps are currently connected to the HRM.

If the issue continues:

1. Have the user test the device in the manufacturer's app.
2. If the HRM fails in multiple apps, advise the user to contact the manufacturer.
3. If the HRM works elsewhere but not in the primary application, escalate for technical review.

Calibrating a Smart Trainer in a Multi-Platform Fitness Application

Calibrating a smart trainer ensures accurate power readings and consistent resistance during workouts. Most calibration issues stem from incomplete warmups, outdated software, unstable connections, or sensors not recognized by the application. Follow the steps below to assist users experiencing calibration problems.

1. Confirm the smart trainer is powered on and connected to the fitness application via Bluetooth or ANT+.
2. Verify the trainer's firmware is up to date.
3. Confirm the application and any companion app are updated to the latest version.
4. Instruct the user to complete a warmup:
 - a. Pedal for 5–10 minutes to bring the trainer to operating temperature.
 - b. Maintain steady cadence and moderate resistance.
5. Ask the user to check nearby devices and disconnect any paired to the trainer.
6. Have the user open the application's pairing or connections screen.
7. Confirm the trainer appears as both the power source and controllable device.
8. Select the trainer and choose the calibration or spindown option.
9. Instruct the user to follow the on-screen prompts:
 - a. Accelerate to the target speed shown in the application.
 - b. Stop pedaling when prompted and let the flywheel coast to a stop.
 - c. Wait for the success confirmation.

If calibration fails:

- Repeat the warmup and calibration steps.

- Verify no other apps are connected to the trainer via Bluetooth.
- Confirm the trainer is on a stable surface with no wheel slippage.

If calibration continues to fail:

- Escalate for technical review.