

Supervised Classification

Boosting

AdaBoosting

- **Weight Assignment:** $w_{i,0} = \frac{1}{n}$

$$\sum_{i=1}^N w^{(i)}$$

$$\text{Error Rate: } r_j = \frac{\sum_{i=1}^N w^{(i)} \mathbb{1}_{y_j \neq y^{(i)}}}{\sum_{i=1}^N w^{(i)}}$$

$$\text{Predictor Weight: } \alpha_j = \eta \ln \left(\frac{1-r_j}{r_j} \right)$$

Hard SVM

- $y(x) = w^T \phi(x) + b = 0$
- **Margin:** $\frac{1}{\|w\|}$
- **Objective:** $\min_{w,b} \frac{1}{2} \|w\|^2$
- **Discriminant Function:** $f(x) = w^T \phi(x) + b$
- **Support Vectors:** $y_i(w^T \phi(x_i) + b) = 1$
- **Polynomial Kernel:** $K(x, y) = (1 + \langle x, y \rangle)^d$
- **Gaussian RBF Kernel:** $K(x, y) = \exp \left(-\frac{\|x-y\|^2}{2\sigma^2} \right)$

Soft SVM

- **Objective:** $\min_{w,b,\xi} \frac{1}{2} \|w\|^2 + C \sum_{i=1}^N \xi_i$
- **Constraints:** $y_i(w^T \phi(x_i) + b) \geq 1 - \xi_i$
- **Slack Variables:** $\xi_i \geq 0$
- **Lagrangian:** $\mathcal{L}(w, b, \xi, \alpha, \beta) = \frac{1}{2} \|w\|^2 + C \sum_{i=1}^N \xi_i - \sum_{i=1}^N \alpha_i (y_i(w^T \phi(x_i) + b) - 1 + \xi_i) - \sum_{i=1}^N \beta_i \xi_i$

- **KKT Conditions:** $\alpha_i \geq 0, \beta_i \geq 0, \alpha_i(y_i(w^T \phi(x_i) + b) - 1 + \xi_i) = 0, \beta_i \xi_i = 0$

- **Dual Problem:** $\max_{\alpha} \sum_{i=1}^N \alpha_i - \frac{1}{2} \sum_{i=1}^N \sum_{j=1}^N \alpha_i \alpha_j y_i y_j K(x_i, x_j)$

- **Predictor:** $f(x) = \sum_{i=1}^N \alpha_i y_i K(x, x_i) + b$

Dimensionality Reduction

Curse of Dimensionality

- **Volume:** $V_d(r) = r^d$
- **Ratio:** $ratio = \frac{V_{crust}}{V_{S_1}} = \frac{V_{S_1} - V_{crust}}{V_{S_1}}$
- **Vol Eqn:** $V = \frac{r^D \cdot \pi^{D/2}}{\rho^{(D/2+1)}}$
- **ratio** $= 1 - (1 - \frac{\epsilon}{r})^D$

Feature Selection

- **Embedded:** L1: $\|w\|_1 = \sum_{j=0}^M |w_j|$
- **Wrappers:** Recursive Feature Elimination using Greedy Search
- **Feature Extraction:** PCA, LDA

PCA:

- **Mean:** $\mu = \frac{1}{N} \sum_{i=1}^N x_i$
- **Covariance:** $\Sigma = \frac{1}{N} \sum_{i=1}^N (x_i - \mu)(x_i - \mu)^T$
- **Eigendecomposition:** $\Sigma = W \Lambda W^T$
- **Sorting:** $\lambda_1 \geq \lambda_2 \geq \dots \geq \lambda_M$
- **Projection:** $z = W^T x$
- **Reconstruction:** $x = Wz + \mu$

MDS:

- **Distance Matrix:** $D = \{d_{ij}\}$
- **Gram Matrix:** $G = -\frac{1}{2} HDH$
- **Eigendecomposition:** $G = V \Lambda V^T$
- **Projection:** $Z = V \Lambda^{1/2}$
- **Reconstruction:** $D = \{d_{ij}\}$

0.1 ISOMAP

- **Shortest Path:** $d_{ij} = \min_{p_{ij}} \sum_{k=1}^{L_{ij}-1} \|x_{p_{ij}(k)} - x_{p_{ij}(k+1)}\|$
- **Time Complexity:** $O(N^3)$

LLE

- Finding a set of weights $W \in \mathbb{R}^{D \times d}$ that minimizes the reconstruction error
- $x_i = \sum_{j=1}^K w_{ij} x_{i(j)}$

t-SNE

- **Objective:** $KL(P||Q) = \sum_i \sum_j p_{ij} \log \frac{p_{ij}}{q_{ij}}$
- **Perplexity:** $\text{Perp}(P_i) = 2^{H(P_i)}$
- **Symmetric SNE:** $p_{ij} = \frac{p_{ij} + p_{ji}}{2N}$
- **Gradient:** $\frac{\partial C}{\partial y_i} = 4 \sum_j (p_{ij} - q_{ij})(y_i - y_j)(1 + \|y_i - y_j\|^2)^{-1}$
- **Time Complexity:** $O(N^2)$

Clustering

K-Means

1. Centroid Assignment: $u^{(i)} = \arg \min_j \|x^{(i)} - \mu_j\|^2$
2. Requires **Scaling the Data**
3. Convergence if Assignments do not change

Cluster Validity Metrics

Internal Criteria

1. **Silhouette Coefficient:** $s = \frac{\frac{1}{N} \sum_{i=1}^N \frac{b_i - a_i}{\max(a_i, b_i)}}$

External Criteria

1. **Rand Index:**
 - (a) a is the number of pairs of elements in X that are in the same subset in C and in the same subset in D .
 - (b) b is the number of pairs of elements in X that are in different subset in C and in different subset in D .
 - (c) c is the number of pairs of elements in X that are in the same subset in C and in different subset in D .
 - (d) d is the number of pairs of elements in X that are in different subset in C and in the same subset in D .

$$2. \text{Rand Score} = \frac{a+b}{a+b+c+d}$$

DBSCAN

- **Core Point:** $N_{\epsilon}(x) \geq \text{minPts}$
- **Border Point:** $N_{\epsilon}(x) < \text{minPts}$, but x is in the ϵ -neighborhood of a core point
- **Noise Point:** Neither core nor border
- **Time Complexity:** $O(N \log N)$

Heirarchical Clustering

Agglomerative

- **Single Linkage:** $d(C_i, C_j) = \min_{x \in C_i, y \in C_j} \|x - y\|$
- **Complete Linkage:** $d(C_i, C_j) = \max_{x \in C_i, y \in C_j} \|x - y\|$
- **Average Linkage:** $d(C_i, C_j) = \frac{1}{|C_i||C_j|} \sum_{x \in C_i} \sum_{y \in C_j} \|x - y\|$

Distance Metrics

1. **Euclidean:** $\|x - y\|_2 = \sqrt{\sum_{i=1}^D (x_i - y_i)^2}$
2. **City-Block:** $\|x - y\|_1 = \sum_{i=1}^D |x_i - y_i|$
3. **Mahalanobis:** $\|x - y\|_M = \sqrt{(x - y)^T M (x - y)}$ where M is the covariance matrix
4. **Cosine:** $\cos(x, y) = \frac{x^T y}{\|x\|_2 \|y\|_2}$

Neural Networks

Activation Functions

1. **Heaviside:** $H(x) = \begin{cases} 0 & x < 0 \\ 1 & x \geq 0 \end{cases}$
2. **Linear:** $f(x) = x$
3. **Sigmoid:** $f(x) = \frac{1}{1+e^{-x}}$
4. **Tanh:** $f(x) = \frac{\exp(x) - \exp(-x)}{\exp(x) + \exp(-x)}$
5. **ReLU:** $f(x) = \max(0, x)$
6. **Leaky ReLU:** $f(x) = \max(\alpha \cdot x, x)$
7. **Softmax:** $f(x)_i = \frac{\exp(x_i)}{\sum_{j=1}^K \exp(x_j)}$
8. **Exponential Linear Unit:** $f(x) = \begin{cases} x & x \geq 0 \\ \alpha(\exp(x) - 1) & x < 0 \end{cases}$
9. **Softplus:** $f(x) = \log(1 + \exp(x))$

Backpropagation

1. **Forward Pass:** $z^{(l)} = W^{(l)} a^{(l-1)} + b^{(l)}, a^{(l)} = f^{(l)}(z^{(l)})$
2. **Backward Pass:** $\frac{\delta^{(L)}}{\nabla_a J} \odot f^{(L)'}(z^{(L)}), \delta^{(l)} = (W^{(l+1)})^T \delta^{(l+1)} \odot f^{(l)'}(z^{(l)})$
3. **Weight Update:** $\nabla_{W^{(l)}} J = \delta^{(l)} (a^{(l-1)})^T, \nabla_{b^{(l)}} J = \delta^{(l)}$