## $\begin{array}{c} {\rm Amik~St\text{-}Cyr} \\ {\bf On~Optimized~Schwarz~Preconditioning~for~High\text{-}Order} \\ {\bf Spectral~Element~Methods} \end{array}$

National Center for Atmospheric Research
1850 Table Mesa Drive
Boulder
CO 80305.
amik@ucar.edu
Martin. J. Gander
Stephen J. Thomas

## Abstract

Optimized Schwarz preconditioning is applied to a spectral element method for the modified Helmholtz equation and pseudo-Laplacian arising in incompressible flow solvers. The preconditioning is performed on an element-by-element basis. The method enables one to use non-overlapping elements, yielding an effective algorithm in terms of communication between elements and implementation. Two approaches are tested. The first consists of constructing a  $P_1$  finite element problem on each overlapping element. In the second, the preconditioner is applied directly on a non-overlapping spectral element. Numerical results demonstrate an improvement in the iteration count over the classical Schwarz algorithm.

Introduction The classical Schwarz algorithm uses Dirichlet transmission conditions between subdomains. By introducing a more general Robin boundary condition, it is possible to optimize the convergence characteristics of the original algorithm (Charton et al. 1991; Chevalier et al. 1998; Gander et al 2002; Gander 2003). In this work, a study of the model equations  $u - \Delta u = f$  and pseudo-Laplacian arising in incompressible flow solvers is performed. As suggested by the work of Fischer et al. (2000), the preconditioning is either implemented via a  $P_1$  finite element formulation of the original problem build on the spectral element grid, or directly by solving a smaller spectral element problem without overlap on each spectral element. Although traditional Schwarz preconditioning combined with a coarse grid solver is quite efficient, the need for even more powerful preconditioning techniques stems from atmospheric modeling. Recently (see Thomas and Loft 2002; St-Cyr and Thomas 2004), a semi-implicit SEM was combined with OIFS time stepping, enabling time steps on the order of 20 times the advective CFL condition (Xiu and Karniadakis 2001). This directly reflects as a significant increase in the number of conjugate gradient iterations required to perform the semi-implicit step.

- P. CHARTON, F. NATAF AND F. ROGIER (1991), Méthode de décomposition de domaines pour l'équation d'advection-diffusion, C. R. Acad. Sci., Vol. 313, No. 9, pp. 623-626.
- P. CHEVALIER AND F. NATAF (1998), Symmetrized method with optimized second-order conditions for the Helmholtz equation, In Domain decomposition methods, 10 (Boulder, CO, 1997), pp. 400-407, Amer. Math. Soc., Providence, RI.
- P.F. FISCHER, N.I. MILLER AND H.M. TUFO (2000), An overlapping Schwarz method for spectral element simulation of three-dimensional incompressible flows,

- in Parallel Solution of Partial Differential Equations, P. Bjorstad and M. Luskin, eds., Springer-Verlag, pp.159-180.
- M. J. Gander, *Optimized Schwarz Methods (2003)*, Research Report, No. 2003-01, Dept. of Mathematics and Statistics, McGill University, 33 pages, submitted.
- M.J. GANDER, F. MAGOULES AND F. NATAF (2002), *Optimized Schwarz Methods without Overlap for the Helmholtz Equation*, SIAM Journal on Scientific Computing, Vol. 24, No 1, pp. 38-60.
- J.W. LOTTES AND P.F. FISCHER (2003), Hybrid Multigrid/Schwarz Algorithms for the Spectral Element Method, submitted.
- A. St-Cyr and S.J. Thomas (2004), Non-linear operator integration factor splitting for the shallow water equations, In preparation for J. Sci. Comp.
- S. J. Thomas, J. M. Dennis, H. M. Tufo, and P. F. Fischer (2003), A Schwarz Preconditioner for the Cubed-Sphere, SIAM J. Sci. Comp., Vol. 25, No. 2, pp. 442-453.
- S.J. Thomas and R.D. Loft (2002), Semi-implicit spectral element atmospheric model. Journal of Scientific Computing, vol 17, 339-350.
- D. XIU AND G.E. KARNIADAKIS (2001), A semi-Lagrangian high-order method for Navier-Stokes equations, J.C.P., No. 172, pp. 658-684.