
Marco, M. Donatelli
Regularization by multigrid-type algorithms

Universit dell'Insubria
Dip Fisica e Matematica
Via Valleggio
11
22100 Como (CO) - Italy
`marco.donatelli@uninsubria.it`
Stefano, S. Serra-Capizzano

We consider the de-blurring problem of noisy and blurred images in the case of space invariant point spread functions. The use of appropriate boundary conditions leads to linear systems with structured coefficient matrices related to space invariant operators like Toeplitz, circulants, trigonometric matrix algebras etc. We combine an algebraic multigrid (which is designed ad hoc for structured matrices) with the low-pass projectors typical of the classical geometrical multigrid employed in a PDEs context. Thus, using an appropriate smoother, we obtain an iterative regularizing method (see [2, 1]) based on: projection in a subspace where it is easier to distinguish between the signal and the noise and then application of an iterative regularizing method in the projected subspace. Therefore any iterative regularizing method like conjugate gradient (CG), conjugate gradient for normal equation (CGNE), Landweber etc., can be used as smoother in our multigrid algorithm. The projector is chosen in order to maintain the same algebraic structure at each recursion level and having a low-pass filter property, which is very useful in order to reduce the noise effects. In this way, we obtain a better restored image with a flatter restoration error curve and also in less time than the auxiliary method used as smoother.

Like any multigrid algorithm, the resulting technique is parameterized in order to have more degrees of freedom: a simple choice of the parameters allows to devise a powerful regularizing method whose main features are the following:

1. it is used with early stopping like any regularizing iterative method and its cost per iteration is about 1/3 of the cost of the method used as smoother (CG, Landweber, CGNE);
2. it can be adapted to work with all the boundary conditions used in literature (Dirichlet, periodic, Neumann or anti-reflective);
3. the minimal relative restoration error with respect to the true image is significantly lower with regard to the method used as smoother and the associated curve of the relative restoration errors with respect to the itera-

tions is “flatter” (therefore the quality of the reconstruction is not critically dependent on the stopping iteration);

4. when it is applied to the system $A\mathbf{f} = \mathbf{g}$ the minimal relative error is comparable with regard to all the best known techniques for the normal equations $A^T A\mathbf{f} = A^T \mathbf{g}$, but in this case the convergence is much faster;

As direct consequence of point 3, the choice of the exact iteration where to stop is less critical than in other regularizing iterative methods while, as a consequence of point 4, we can choose multigrid procedures which are extremely more efficient than classical techniques without losing accuracy in the restored image. Several numerical experiments show the effectiveness of our proposal. A Theoretical analysis of multigrid methods is usually a difficult task and a first largely used approach considers a two grid method. In the same way, to proving the regularizing properties of our multigrid methods, we provide some estimations on the filter factor of the two level strategy.

Finally, it can be easily (by using a simple projection at every step) combined with nonnegativity constraints. Moreover we propose a possible generalization where the multigrid regularization is applied as a one-step method: now the only parameter to choose is the number of recursive calls.

Bibliography

- [1] M. DONATELLI. *Image Deconvolution and Multigrid Methods*, PhD Thesis in Applied and Computational Mathematics, Univ. of Milano, December 2005.
- [2] M. DONATELLI AND S. SERRA CAPIZZANO, *On the regularizing power of multigrid-type algorithms*, SIAM J. Sci. Comput., in press.