

# EXTENSIONS OF CERTAIN GRAPH-BASED ALGORITHMS FOR PRECONDITIONING

DAVID FRITZSCHE\*, ANDREAS FROMMER<sup>†</sup>, AND DANIEL B. SZYLD\*

**Abstract.** The original TPABLO algorithms are a collection of algorithms which compute a symmetric permutation of a linear system such that the permuted system has a relatively full block diagonal with relatively large nonzero entries. This block diagonal can then be used as a preconditioner. We propose and analyze three extensions of this approach: we incorporate a nonsymmetric permutation to obtain a large diagonal, we use a more general parametrization for TPABLO, and we use a block Gauss-Seidel preconditioner which can be implemented to have the same execution time as the corresponding block Jacobi preconditioner. Since our approach allows for efficient use of level 3 BLAS operations, it outperforms direct solvers and rivals standard ILU preconditioners on many test problems on a single processor system, while having good potential for efficient parallelization.

**Key words.** block partitioning, PABLO, TPABLO, preconditioning, cache aware algorithms, block Gauss-Seidel, ILU decomposition

---

\*Department of Mathematics, Temple University, Philadelphia, PA 19122-6094, {david.fritzsche,szyld}@math.temple.edu. This paper was supported in part by the National Science Foundation under grant DMS-0207525 and by the U.S. Department of Energy under grant DE-FG02-05ER25672.

<sup>†</sup>Faculty of Mathematics and Science, Bergische Universität Wuppertal, D-42097 Wuppertal, Germany, frommer@math.uni-wuppertal.de