

---

Georg Stadler  
**Experience with parallel AMG for large-scale adaptive  
mantle convection**

Institute for Computational Engineering and Sciences (ICES)  
The University of Texas at Austin  
1 University Station  
C0200  
Austin  
TX 78712

`georgst@ices.utexas.edu`

Carsten Burstedde

*Institute for Computational Engineering and Sciences (ICES) The University  
of Texas at Austin, Austin, TX*

Omar Ghattas

*Institute for Computational Engineering and Sciences (ICES) and Depts. of  
Geological Sciences and Mechanical Engineering The University of Texas at  
Austin, Austin, TX*

Michael Gurnis

*Seismological Laboratory, California Institute of Technology, Pasadena, CA*

Eh Tan

*Computational Infrastructure for Geodynamics, California Institute of  
Technology, Pasadena, CA*

Tiankai Tu

*Institute for Computational Engineering and Sciences (ICES) The University  
of Texas at Austin, Austin, TX*

Lucas W. Wilcox

*Institute for Computational Engineering and Sciences (ICES) The University  
of Texas at Austin, Austin, TX*

Zhong, Shijie

*Department of Physics, University of Colorado, Boulder, CO*

Mantle convection is the principal control on the thermal and geological evolution of the Earth. Its modeling involves solution of the mass, momentum, and energy equations for a viscous, creeping, incompressible non-Newtonian fluid at high Rayleigh and Peclet numbers. We are developing the parallel adaptive mantle convection code **Rhea**, which builds on our **A**daptive **L**arge-scale **P**arallel **S**imulations (ALPS) framework.

The numerical simulation of mantle convection requires the solution of a stationary, highly variable-viscosity Stokes system at each time step. The Stokes equation is discretized using trilinear finite elements for both velocity and pressure, and polynomial pressure projection is used to stabilize this equal-order ap-

proximation. For the solution of the discrete Stokes saddle point system we use the preconditioned minimal residual (MINRES) method. The preconditioner is based on an approximate Schur complement for the pressure component and involves a solve with a positive definite operator for the velocity field. This block solve is approximated with one V-cycle of algebraic multigrid. Results obtained with the parallel AMG libraries *BoomerAMG* from *hypre* and with *ML* from *Trilinos* will be shown. We discuss the parallel scalability of the solver on up to 16K cores, as well as its dependence on viscosity variations and boundary conditions.