

gmd
a General Material Model Driver

Tim Fuller

September 24, 2013

Chapter 1

Introduction to gmd

gmd is a **General Material model Driver** designed for rapid development and testing of material models. **gmd** can be thought to drive a single material point of a finite element simulation through very specific user designed paths. This permits exercising material models in ways not possible in finite element calculations, designing verification and validation tests of the material response, among others. **gmd** is a small tool at the developers disposal to aid in the design and implementation of material models in larger finite element host codes. **gmd** is the successor the **payette** material model [?] which was itself based in part on Tom Pucick's **MMD** [?] and Rebecca Brannon's **MED** [?] drivers.

The core of the **gmd** code base is written in Python and leverages Python's object oriented programming (OOP) design. OOP techniques are used throughout **gmd** to setup and manage simulation data. Computationally heavy portions of the code, and the material models themselves are written in Fortran for its speed and ubiquity in scientific computing. Calling Fortran procedures from Python is made possible by the **f2py** module, standard in Numpy, that compiles and creates Python shared object libraries from Fortran sources.

Output files from **gmd** simulations are in the **EXODUSII** [?] database format, developed at Sandia National Labs for storing finite element simulation data. Since **gmd** is designed to be used by material model developers, it is expected that the typical user will want access to *all* all available output from a material model, thus all simulation data is written to the output database. **EXODUSII** database files can be post processed via the **gmdviz** utility, in addition to other visualization packages such as **PARAVIEW** [?].

gmd is free software released under the MIT License.

1.1 Why a Single Element Driver?

Due to their complexity, it is often overkill to use a finite element code for constitutive model development. In addition, features such as artificial viscosity can mask the actual material response from constitutive model development. Single element drivers allow the constitutive model developer to concentrate on model development and not the finite element response. Other advantages of the `gmd` (or, more generally, of any stand-alone constitutive model driver) are

- `gmd` is a very small, special purpose, code. Thus, maintaining and adding new features to `gmd` is very easy.
- Simulations are not affected by irrelevant artifacts such as artificial viscosity or uncertainty in the handling of boundary conditions.
- It is straightforward to produce supplemental output for deep analysis of the results that would otherwise constitute an unnecessary overhead in a finite element code.
- Specific material benchmarks may be developed and automatically run quickly any time the model is changed.
- Specific features of a material model may be exercised easily by the model developer by prescribing strains, strain rates, stresses, stress rates, and deformation gradients as functions of time.

1.2 Why Python?

Python is an interpreted, high level object oriented language. It allows for writing programs rapidly and, because it is an interpreted language, does not require a compiling step. While this might make programs written in python slower than those written in a compiled language, modern packages and computers make the speed up difference between python and a compiled language for single element problems almost insignificant.

For numeric computations, the NumPy and SciPy modules allow programs written in Python to leverage a large set of numerical routines provided by LAPACK, BLASPACK, EIGPACK, etc. Python's APIs also allow for calling subroutines written in C or Fortran (in addition to a number of other

languages), a prerequisite for model development as most legacy material models are written in Fortran. In fact, most modern material models are still written in Fortran to this day.

Python's object oriented nature allows for rapid installation of new material models.

1.3 Obtaining gmd

`gmd` is an open source project licensed under the MIT license. A copy of may be obtained from <https://github.com/tjfulle/gmd>

Chapter 2

gmd Quick Start Guide

This guide provides an outline for building and running **gmd**.
Build gmd See Chapter 3.

- Download **gmd** and setup environment
- `$ cd $GMDROOT/toolset && ./setup.py`
- `$ buildmtls`

Prepare Input Inputs are xml specification files. See Chapter 7.

- Set up the desired simulation path.
- Add material model.
- Add desired extraction requests.

Run

- `$ gmd [options] runid [,runid_1, ..., runid_n]`
runid is prefix of “.xml” file.
- Complete list of options given by
`$ gmd -h`

Postprocess

- `$ gmdviz runid [,runid_1, ..., runid_n]`
- **PARAVIEW** also reads exodus files.

Chapter 3

Building gmd

`gmd`'s code base is largely written in Python and requires no additional compiling. However, the **EXODUSII** third party library and material models written in fortran must be built.

3.1 System and Software Requirements

`gmd` has been built and tested extensively on several versions of linux and the Apple Mac OSX operating systems. It is unknown whether or not `gmd` will run on Windows.

`gmd` requires the following software installed for your platform:

- Python 2.7
- NumPy 1.6
- SciPy 0.10
- A fortran compiler

The required software may be obtained in several ways, though all development has been made using Enthought Canopy (<http://http://www.enthought.com>).

A note on the fortran compiler. It is recommended to use the same fortran compiler to build the `gmd` components that was used to build SciPy.

3.2 Installation

Ensure that all `gmd` prerequisites are installed and working properly before proceeding.

3.2.1 Set Environment and Path

`GMDROOT` Optional, name of installation directory

`PATH` `$GMDROOT/toolset:$PATH`

`GMDMTLS` “.” separated list of paths to directories containing user defined material models. See Section 10.2.

`GMDTESTS` “.” separated list of paths to directories containing user defined regression tests. See Section ??.

3.2.2 Set Up

Set up and build the TPLs.

```
$ cd $GMDROOT/toolset
```

```
$ python setup.py
```

In addition to building the TPLs, `setup.py` generates the following executable scripts

`buildmtls` Build material models

`gmd` Run `gmd` simulations

`gmddump` Read a `gmd` output and dumps requested variables to ascii columnar files

`gmdviz` 2D plots of `gmd` output

`runtests` Run the regression tests

Each script is a wrapper to another `gmd` Python file. In the wrapper, relevant environment variables are set (e.g., `$PYTHONPATH`) and the correct Python executable (the one used to set up) is used to interpret the `gmd` source file. The full set of options for each script is obtained by

```
$ scriptname -h
```

where `scriptname` is the name of the script.

The TPLs will build the first time `gmd` is setup. Thereafter after, only the executable scripts are rewritten. Execute

```
$ python setup.py -h
```

for options to rebuild the TPLs.

3.2.3 Build

Build the material libraries

```
$ buildmtls
```

3.2.4 Test the Installation

To test `gmd` after installation, execute

```
$ runtests [-j N]
```

which will run the `gmd` regression tests.

3.2.5 Troubleshooting

If you experience problems when building/installing/testing `gmd`, you can ask help from the `gmd` developers. Please include the following information in your message:

- Platform information OS, its distribution name and version information etc.

```
$ python -c 'import os,sys;print os.name,sys.platform'
$ uname -a
```

- Information about C,C++,Fortran compilers/linkers as reported by the compilers when requesting their version information, e.g., the output of


```
$ gcc -v  
$ gfortran --version
```

- Python version

```
$ python -c 'import sys;print sys.version'
```

- NumPy version

```
$ python -c 'import numpy;print numpy.__version__'
```

- SciPy version

```
$ python -c 'import scipy;print scipy.__version__'
```

- Feel free to add any other relevant information.

Chapter 4

gmd Solution Method

`gmd` exercises a material model directly by “driving” it through user specified paths using a specified driver. Currently installed drivers are the `solid` and `eos` drivers. The details of the solution method depend on the driver and are described in the sections to follow.

In solid mechanics inevitably run in to the momentum equation. In equation is stress, need a constitutive model for stress.

4.1 Supported Drivers

4.1.1 Solid

The `solid` driver is designed to exercises material models designed to predict an increment in the material state given the current state and an increment in strain.

$$\boldsymbol{\sigma} = f[\boldsymbol{\sigma}, \boldsymbol{\eta}^k, \dot{\boldsymbol{\epsilon}}] \quad (4.1)$$

where $\boldsymbol{\sigma}$ is the stress state, $\boldsymbol{\eta}^k$ are a set of path dependent internal state variables, and $\dot{\boldsymbol{\epsilon}}$ is the strain rate. The definitions of $\boldsymbol{\sigma}$ and $\dot{\boldsymbol{\epsilon}}$ are left intentionally vague, except that the pair is work conjugate. Further explanation of $\boldsymbol{\sigma}$ and $\dot{\boldsymbol{\epsilon}}$ are deferred until a later section. Users drive the material through specified deformation paths. The path can also be a specified stress, in which case we solve for $\dot{\boldsymbol{\epsilon}}$ to be

$$\dot{\boldsymbol{\epsilon}} = \dot{\boldsymbol{\epsilon}}_0 + f^{-1}[\boldsymbol{\sigma}, \boldsymbol{\eta}^k, \dot{\boldsymbol{\epsilon}}](\boldsymbol{\sigma} - \boldsymbol{\sigma}_0) \quad (4.2)$$

Mixed modes are also allowed. Paths can be prescribed by specifying the components of strain and their rates, components of deformation gradient,

displacements of boundary of unit cube, components of stress and their rates.
Mixed modes involving strains and stresses allowed.

4.1.2 Electrical

Electric field can be prescribed for testing piezoelectric models.

Chapter 5

Running

```
$ gmd runid[.xml]
```

The following files will be produced

```
$ ls runid.*  
runid.exo      runid.log      runid.xml
```

`runid.exo` is the `EXODUSII` output database, `runid.log` the log file, and `runid.xml` the input file.

Chapter 6

User Input: GMDSpec

User input is via xml control files. In general, tags use CamelCase and attributes lower case. Attributes are described in this document as

`attr="type[default]{choices}"`

where `default` is the default value (if any) and `{choices}` are valid choices (if any). Any attribute not having a default value is required. Types are `str`, `int`, `real`, `list`. Lists are given as space separated lists (e.g., "1 2 3"). In the following, elements shown in red are required input.

6.1 GMDSpec

All input files must have as their root element `<GMDSpec>`.

`<GMDSpec>`

Recognized subelements of `<GMDSpec>` are

- `<Physics>`
- `<Permutation>`
- `<Optimization>`

The following elements are read from any scope in the input file

- `<Include>`

- `<Function>`

The `<Physics>`, `<Permutation>`, `<Optimization>` and input blocks are described separately in their own chapters.

6.2 Preprocessing

Preprocessing allows specifying variables in the input inside of comment tags for use in other parts of the input. Syntax mirrors that of `aprepro`. Preprocessor also evaluates (nearly) any Python expression.

The `random()` expression generates a random number. The `random_seed` variable sets the random state seed. Note, expressions are evaluated in order, therefore, if setting the `random_seed` it should occur early.

The following input stub demonstrates specifying the `<Material>` parameter `K` and `G`, and `<Path>` parameter `estar` as variables

```
<GMDSpec>
  <!-- {random_seed = 7}
    {G = 54e9 * random()}
    {K = 23e9}
    {estar = -.05}
  -->
  <Physics>
    <Material model="elastic">
      <K> {K} </K>
      <G> {G} </G>
    </Material>
    <Path type="prdef" estar="{estar}">
      ...
    </Path>
  </Physics>
</GMDSpec>
```

6.3 Include

Path to file to be included as if its contents were inplace in the input file

```
<Include href="str"/>
```

The following stub input demonstrates how to include a file in place

```
<Include href="/path/to/some/file.ext"/>
```

6.4 Function

Define functions to be used elsewhere in input. `id=0` and `id=1` are reserved for the constant 0 and 1 functions, respectively. `href` is the path to a file containing the function definition (useful when the function is a large piecewise linear table). `cols` specifies the columns in which data is located in a piecewise linear table.

```
<Function id="int"
      type="str{analytic_expression, piecewise_linear}"
      var="str[x]" href="str[]" cols="list[1 2]">
```

The following input stub demonstrates how to define an analytic expression and piecewise linear table as functions

```
<Function id="2" type="analytic_expression" var="t">
  sin(t)
</Function>
<Function id="3" type="piecewise_linear">
  1 2
  2 3
  3 5
</Function>

<!-- Read a piecewise linear table from an external file using
      columns 1 and 3
-->
<Function id="4" type="piecewise_linear" href="./file.dat"
      cols="1 3"/>
```

```
$ cat file.dat
# Column1 Column2 Column3
```

1 1 4
2 3 7
.
.
.
100 4.2 1.43

Chapter 7

User Input: Physics

Define the physics of the simulation. If specified, `termination_time` defines the termination time for the simulation. If not specified, termination time is taken as final time in `<Path>`.

```
<Physics driver="str[solid]{solid, eos}"
        termination_time="real[]" ">
```

Recognized subelements of `<Physics>` are

- `<Path>`
- `<Material>`
- `<Extract>`

7.1 Path

Define deformation paths through which the material will be exercised.

```
<Path type="str{prdef, surface}"
      format="str[default]{default, table, fcnspec}"
      cols="list[1, ..., n]" cfmt="str"
      tfmt="str[time]{time, dt}"
      nfac="int[1]" kappa="real[0]" rstar="real[1]"
      tstar="real[1]" estar="real[1]" sstar="real[1]"
      amplitude="real[1]" ratfac="real[1]" href="str">
```

7.1.1 Path Attributes

type

The type of path specified. Valid types are **prdef** and **surface**.

The **prdef** type defines a prescribed deformation. The *j*th leg of **<Path>** is sent to the driver in form **[tf, n, cfmt, Cij]**, where **tf**, **n**, **cfmt**, and **Cij** are the termination time, number of steps, control format, and control values. Methods of inputting legs depends on the attributes of **<Path>** and will be shown in examples to follow.

The **surface** input is similar to the **prdef** specification, but leg termination time is not specified. Control parameters also differ, as shown in Table 7.2.

Format

The format by which the legs of the deformation path are specified. Valid formats are **default**, **table**, and **fcnspec**. In the following subsections, the different formats are described.

Format: default The **default** format offers the most control. In this format, the termination time, number of steps, control format, and components of deformation are specified for each leg as in the following stub input

```
<Path type="default">
  <!-- tterm nsteps cfmt c1 c2 c3 ... -->
  0  0 222222 0 0 0 0 0 0
  1 10 222222 1 0 0 0 0 0
</Path>
```

See Section 7.1.1 for a full description of the control format **cfmt** and its relationship with the **c1**, **c2**, **c3**,

Format: table The **table** format allows reading in deformation paths from a columnar table of data. Control format is uniform for all legs. Specify control format as **cfmt** attribute of **<Path>**. Specify which columns to read data with the **cols** attribute. The first column is assumed to be the time specifier. See Section 7.1.1 for a description of the **cols** attribute. The **tfmt** attribute specifies if the time column represents the actual time (**tfmt="time"**) or time step (**tfmt="dt"**). The number of steps for each leg

can be set by `nfac`. The `href` attribute specifies an external file to read the table.

The following input stubs demonstrate reading a table from the input file and from an external file.

```
<!-- Read entries from table. -->
<Path type="prdef" format="table" cols="1:4" cfmt="222"
      tfmt="time">
  0 0 0 0
  1 1 0 0
  ...
  n 2 0 0
</Path>
```

```
<!-- Read table from external file -->
<Path type="prdef" format="table" cols="1 3:8" cfmt="222222"
      tfmt="time" href="exmpls.tbl"/>
```

Format: fcnspec The `fcnspec` format allows defining a deformation path by a function. A deformation path defined by `fcnspec` must have only 1 leg defining the termination time and the function specifier defining the values of the components of deformation. The function specifier is of the form

```
function_id[:scale]
```

where `function_id` is the ID of the function as specified in its `<Function>` element. The optional scale is multiplied by the function.

The following input stub demonstrates uniaxial strain deformation, using a user defined function to specify the 11 component of strain through time.

```
<Path type="prdef" format="fcnspec" cfmt="222" nfac="200">
  <!-- termination time, fcn spec -->
  {2 * pi} 2:1.e-1 0 0
</Path>
```

Control Format

The control format `cfmt` is concatenated integer list specifying in its i^{th} component the i^{th} component of deformation, i.e., `cfmt[i]` instructs the driver

as to the type of deformation represented by `Cij[i]`. Types of deformation represented by `cfmt` are shown in Table 7.1.

For example, the following `cfmt` instructs the driver that the components of `Cij` represent [stress, strain, stress rate, strain rate, strain, strain], respectively:

```
cfmt="423122"
```

Mixed modes are allowed only for components of strain rate, strain, stress rate, and stress. Electric field components can be included with any deformation type.

The components `Cij` take the following order

Vectors: [X, Y, Z]

Symmetric tensors: [XX, YY, ZZ, XY, YZ, XZ]

Tensors: [XX, XY, XZ, YX, YY, YZ, ZX, ZY, ZZ]

If `len(Cij) ≠ 6` (or 9 for deformation gradient), the missing components are assumed to be zero strain.

<code>cfmt</code>	Deformation type
1	Strain rate
2	Strain
3	Stress rate
4	Stress
5	Deformation gradient
6	Electric field

Table 7.1: Supported deformation types and `cfmt` code for `solid prdef` paths

<code>cfmt</code>	Variable type
1	Density
2	Temperature

Table 7.2: Supported surface variable types and `cfmt` code for `eos surface` paths

Time Format

The `tfmt=["time"]` `{"time", "dt"}` flag specifies the time format. If `tfmt="time"` (default) the first value of each leg is interpreted as the termination time for the leg. For `tfmt="dt"` the first value of each leg is interpreted as a time increment.

kappa

The attribute `kappa` is only used/defined for the purposes of strain or strain rate control. It refers to the coefficient used in the Seth-Hill generalized strain definition

$$\boldsymbol{\varepsilon} = \frac{1}{\kappa} (\boldsymbol{U}^\kappa - \boldsymbol{\delta}) \quad (7.1)$$

where κ is the keyword `kappa`, $\boldsymbol{\varepsilon}$ is the strain tensor, \boldsymbol{U} is the right Cauchy stretch tensor, and $\boldsymbol{\delta}$ is the second order identity tensor. Common values of κ and the associated common names for each (there is some ambiguity in the names) are:

κ	Name(s)
-2	Green
-1	True, Cauchy
0	Logarithmic, Hencky, True
1	Engineering, Swainger
2	Lagrange, Almansi

The Column Specifier

The columns to read from a table or the `fncspec` leg are specified by the `cols` attribute. `cols` are specified as a space separated list of columns. Number is 1 based. Ranges can be specified using Python slice syntax.

The following input stubs demonstrate two equivalent ways to read columns 1, 3, 4, 5, 8, 9, and 13 from a table.

```
cols="1 3 4 5 8 9 13"
```

```
cols="1 3:5 8:9 13"
```

Step Multiplier

`nfac` is a multiplier on the number of steps for each leg.

Amplitude

`amplitude` is a factor multiplied to all components of deformation.

The “star” Multipliers

`[rtes(ef)]star` are multipliers on the components of density, time (temperature for `type="surface"`), strain, stress, and electric field, respectively. The `[rtes(ef)]star` are first multiplied by `amplitude`.

Rate Factor

`ratfac` is a divisor to the termination time of each leg, thereby effectively increasing the rate of deformation.

7.1.2 More Examples

The following examples will help clarify the `<Path>` input syntax

```
<!-- uniaxial strain, all six components of strain
prescribed -->
<Path type="prdef" kappa="0" tstar="1" estar="-.5"
      amplitude="1" ratfac="1">
  <!-- termination time, number of steps, cfmt, Cij -->
  0   0 222222 0 0 0 0 0 0
  1 100 222222 1 0 0 0 0 0
  2 100 222222 2 0 0 0 0 0
  3 100 222222 1 0 0 0 0 0
  4 100 222222 0 0 0 0 0 0
</Path>
```

```

<!-- uniaxial strain, stress controlled -->
<Path type="prdef" nfac="100">
  0 0 444 0 0 0
  1 1 444 -7490645504 -3739707392 -3739707392
  2 1 444 -14981291008 -7479414784 -7479414784
  3 1 444 -7490645504 -3739707392 -3739707392
  4 1 444 0 0 0
</Path>

```

```

<!-- uniaxial stress, mixed mode -->
<Path type="prdef" nfac="100">
  0 0 222 0 0 0
  1 1 244 {epsmax} 0 0
  4 1 244 0 0 0
</Path>

```

Example of type="surface"

The following examples demonstrate the type="surface"

```

<Path type="surface">
  <!-- nsteps, control, Cij -->
  <!-- control goes as 1 -> density
                                2 -> temperature -->
    0 12 1 100
    100 12 5 300
</Path>

```

```

<Path type="surface" format="table" cfmt="12" nfac="100">
  <!-- Cij -->
  1 100
  5 300
</Path>

```

7.2 Material

Define the material model.

```
<Material model="str">
```

Subelements of **<Material>** are

- **<Matlabel>**
- **<ParameterArray>**
- **<InitialState>**
- **<Key>***

***<Key>** is a valid material parameter name.

7.2.1 Attributes of Material

Model

The name of the material model.

7.2.2 Matlabel

Insert model parameters from a database file.

```
<Matlabel href="str[F_MTL_PARAM_DB]" material="str"/>
```

href

The path to the database file. Defaults to
\$GMDROOT/materials/material_properties.db if no file is given.

material

Name of material as given in the database file.

The following input stub demonstrates the use of **<Matlabel>**

```
<Material model="elastic">  
  <Matlabel href="./materials.xml" material="aluminum"/>  
</Material>
```


7.2.3 ParameterArray

Specify the parameter array for the material as whitespace separated list of floats. The list of values must be the same length as the parameter array for the material or an error will occur.

```
<ParameterArray>
  VAL1 VAL2 ... VALN
</ParameterArray>
```

7.2.4 InitialState

Specify the initial state of the material as a whitespace separated list of floats. Six stress values must be followed by material variables (if any). The length of the material variables must be the same as the length of the **xtra** variable array for the material or an error will occur. Note, implementation is material model specific.

```
<InitialState>
  STRESS_XX STRESS_YY ... STRESS_XZ XTRA1 XTRA2 ... XTRAN
</InitialState>
```

7.2.5 Specify Individual Parameters

Specify individual parameters as xml text nodes

```
<Key> float </Key>
```

The following stub inputs demonstrate the **<Material>** input

```
<Material model="elastic">
  <G> 54E+09 </G>
  <K> 124E+09 </K>
</Material>
```

7.3 Extract

Extract variables and paths from **ExodusII** output and (optionally) write to different formats.

```
<Extract format="str[ascii]{ascii, mathematica, ndarray}"
        step="int[1]" ffmt="str[.18f]">
```

Recognized subelements of `<Extract>` are

- `<Path>*`
- `<Variables>`

* eos driver only

7.3.1 Attributes of Extract

format

The format to write the output. `ascii` format writes out columnar data as an ascii text file, `mathematica` writes an ascii text file that can be read by Mathematica, and `ndarray` writes the data to a file in the numpy `.npz` binary format.

step

Extract every `stepth` timestep.

ffmt

The string format used write out variables.

7.3.2 Variables

Variables to extract from the `ExodusII` output database. Variables are specified children of the `<Variables>` element. All components of vector and tensor variables will be extracted if only the basename is specified. Time is always extracted as the first entry of the output file. Extracted variables are in `runid.out` or `runid.math` depending if the format is `ascii` or `mathematica`.

```
<Variables>
  VAR_1, ..., VAR_N
</Variables>
```

The following example demonstrates how to extract all components of stress and strain

```
<Extract format="ascii">
  <variables>
    STRESS STRAIN
  </variables>
</Extract>
```

Extract only the XX, YY, and ZZ components of stress

```
<Extract format="ascii">
  <variables>
    STRESS_XX STRESS_YY STRESS_ZZ
  </variables>
</Extract>
```

Extract all variables

```
<Extract format="ascii">
  <variables>
    ALL
  </variables>
</Extract>
```

Path

Extract a specified path from the equation of state surface through the specified density range starting at the initial temperature.

```
<Path type="str{isotherm, hugoniot}" increments="int[100]"
      density_range="list" initial_temperature="real">
```

The following input stub demonstrates extracting Hugoniot and Isotherm paths

```
<Extract>
  <Path type="isotherm" increments="200"
        density_range="1 3" initial_temperature="225"/>
  <Path type="hugoniot" increments="100"
        density_range="1 3" initial_temperature="100"/>
</Extract>
```

Chapter 8

User Input: Permutation

Permutate model input parameters, running jobs with different realization of parameters. Good for investigating model sensitivities.

```
<Permutation method="str[zip]{zip,combine,shotgun}"  
              seed="real[date]"  
              correlation="list[none]{plot,table,none}">
```

Recognized subelements of <Permutation> are

- <Permutate>
- <ResponseFunction>

8.0.3 Attributes of Permutation

method

The **method** attribute describes which method to use to determine parameter combinations to run.

The **zip** method runs one job for each set of parameters (and, thus, the number of realizations for each parameter must be identical), the **combine** method runs every combination of parameters.

correlation

Create correlation table and plots of relating permuted parameters and value of response function. **correlation** is only meaningful if a <ResponseFunction> is specified.

seed

The seed for the random number generator. **date** is today's date in seconds.

8.0.4 Permutate

Specify the parameters to permutate.

```
<Permutate var="str"
          values="func{range,list,weibull,uniform,
                    normal,percentage}"
```

var

var is the name of the variable and should occur elsewhere in the input file in preprocessing braces.

values

values are the specific values. The **range**, **list**, **weibull**, **uniform**, **normal**, **percentage** are all specified as functions with the following form

```
values="func(start,stop,N)"
```

The following input stub demonstrates how to permutate the **K** and **G** parameters

```
<Permutation method="zip" seed="12">
  <Permutate var="K" values="weibull(125.e9, 14, 3)"/>
  <Permutate var="G" values="percentage(45.e9, 10, 3)"/>
</Permutation>
```

In the **<Material>** element, the **K** and **G** parameters are specified as

```
<Material model="elastic">
  <K> {K} </K>
  <G> {G} </G>
</Material>
```

8.0.5 ResponseFunction

The `<ResponseFunction>` returns the response from permutation or optimization jobs.

```
<ResponseFunction href="str" function="gmdfcn"  
                  descriptor="str[]" />
```

One of `href` or `function` must be specified.

`href`

`href` is the path to an executable file script containing the response function. The script is called from the command line as

```
% ./scriptname runid.exo
```

An example of a response function specifying `href` is

```
<ResponseFunction href="./scriptname" descriptor="PRES"/>
```

`function`

`function` is the name of a builtin `gmd` response function. Built in response functions are

- `gmd.max` maximum value of a simulation variable output
- `gmd.min` minimum value of a simulation variable output
- `gmd.mean` mean value of a simulation variable output
- `gmd.ave` average value of a simulation variable output
- `gmd.absmax` maximum absolute value of a simulation variable output
- `gmd.absmin` minimum absolute value of a simulation variable output

Built in response functions operate only on variables in the simulation output file.

An example of a response function specifying `function` is

```
<ResponseFunction href="gmd.max(PRESSURE)" descriptor="PRES"/>
```

descriptor

descriptor is the name given to the response function in the output.

Chapter 9

User Input: Optimization

Optimize specified parameters against user specified objective function.

```
<Optimization method="str[simplex]{simplex, powell, cobyla}"  
               maxiter="int[25]" tolerance="real[1e-6]">
```

Recognized subelements of <Optimization> are

- <Optimize>
- <AuxiliaryFile>
- <ResponseFunction>

9.0.6 Attributes of Optimization

method

method specifies the optimization method. All optimization routines utilize the `scipy.optimize` module.

maxiter

maxiter is the maximum number of iterations.

tolerance

tolerance is the optimization tolerance.

9.0.7 Optimize

Specify the variable to be optimized.

```
<Optimize var="str" initial_value="real" bounds="list[]" />
```

var

var is the name of the variable and should occur elsewhere in the input file in preprocessing braces.

initial_value

initial_value is the initial value of **var**

bounds

bounds specifies lower and upper bounds on **var**. Only the **cobyla** method accepts bounds.

9.0.8 AuxiliaryFile

Path to any auxiliary file needed by the optimization objective function.

```
<AuxiliaryFile href="str"/>
```

9.0.9 ResponseFunction

Same as for **<Permutation>**, except that auxiliary files are also passed to the function. The value returned from the response function is interpreted as the error to be minimized.

If the **<ResponseFunction>** is given by **href**, it is called as

```
% ./scriptname runid.exo [AuxFile1[AuxFile2[...]]]
```

9.0.10 Example

Optimize the K and G parameters

```

<Optimization method="simplex" maxiter="25" tolerance="1e-4">
  <ResponseFunction href="opt-sig-v-time"
    descriptor="SIG_V_TIME"/>
  <AuxiliaryFile href="opt-baseline.dat"/>
  <Optimize var="opt_k" initial_value="129.e9"/>
  <Optimize var="opt_g" initial_value="54.e9"/>
</Optimization>

```

In the **<Material>** element, the K and G parameters are specified as

```

<Material model="elastic">
  <K> {opt_k} </K>
  <G> {opt_g} </G>
</Material>

```

Chapter 10

gmd User Material Interface

`gmd` can be made to find, build, and execute user materials outside of `$GMDROOT`. User materials can be written in Python or Fortran and `gmd` interacts with them through the application programming interface (API). In general, the following pattern is followed for exercising a material model with `gmd`:

1. create a material model interface (MMI)
2. build and link the material model to `gmd`
3. exercise the model

10.1 Material Model Interface

`gmd` interacts with materials through a material interface file. The material interface file defines the material class which must be a subclass of `$GMDROOT/materials._material.Material`. In this section, methods of the `Material` class are described.

10.1.1 Material Class Instantiation

The base class `Material` in `$GMDROOT/materials._material` creates new `gmd` materials and provides the interface with which `gmd` interacts. Each class must define its name (`Material.name`) and an ordered list of material parameter names (`Material.param_names`) as they appear in the input file. The class should not define an `__init__` method and if it does, should call the `__init__` of the base class.

Material: Interface

```
mtl = Material()
```

The following is an example of a `Material` declaration for the Elastic material model

```
from materials._material import Material
class Elastic(Material)
    name = 'elastic'
    param_names = ['K', 'G']
```

10.1.2 Setup the Material

The method `setup` sets up the material model by checking and setting the material parameter array, requesting allocation of storage of material variables, and computing and storing the `bulk_modulus` and `shear_modulus` of the material.

Material.setup: Interface

```
mtl.setup(params)
```

ndarray params

Material parameters parsed from the input file

The following is an example of a `setup` method

```
def setup(self, params):
    if elastic is None:
        raise Error1("elastic model not imported")
    elastic.elastic_check(params, log_error, log_message)
    K, G, = params
    self.set_param_vals(params)
    self.bulk_modulus = K
    self.shear_modulus = G
```

10.1.3 Store Parameter Array with `gmd`

The method `set_param_vals` stores the checked parameter values with `gmd`. It must be called by each instance of the material model.

Material.set_param_vals: Interface

```
mtl.set_param_vals(params)
```

ndarray params

Checked material parameters

The following is an example of how `set_param_vals` is used within a materials setup method.

```
params = self._check_params(params)
self.set_param_val(params)
```

10.1.4 Adjust the Initial State

The method `adjust_initial_state` adjusts the initial state after the material is setup. Method provided by base class should be adequate for most materials. A material should only override the base method if absolutely necessary.

Material.adjust_initial_state: Interface

```
mtl.adjust_initial_state(xtra)
```

ndarray xtra

Material variables

10.1.5 Update the Material State

The material state is updated to the end of the step via the `update_state` method. Each material model must provide its own `update_state` method.

Material.update_state: Interface

```
stress, xtra = mtl.update_state(dt, d, sig, xtra, *args)
```

real dt

timestep size

ndarray d

rate of deformation

ndarray sig

stress at beginning of step

`ndarray xtra`
extra state variables at beginning of step
`tuple args`
(`defgrad`, `efield`, `time`, `rho`, `tmpr`) extra positional arguments.
`dict kwargs`
extra keyword args (not used)
`ndarray stress`
stress at end of step
`ndarray xtra`
extra state variables at end of step
The following code segment is used by the driver to update the material state

```
args = (f, ef, t, None, None)
sig, xtra = mtl.update_state(dt, d, sig, xtra, *args)
```

10.1.6 Example

A complete example

```

import numpy as np
from materials._material import Material
from core.io import Error1, log_error, log_message
try:
    import lib.elastic as elastic
except ImportError:
    elastic = None

class Elastic(Material):
    name = "elastic"
    param_names = ["K", "G"]
    def __init__(self):
        super(Elastic, self).__init__()

    def setup(self, params):
        if elastic is None:
            raise Error1("elastic model not imported")
        elastic.elastic_check(params, log_error, log_message)
        K, G, = params
        self.set_param_vals(params)
        self.bulk_modulus = K
        self.shear_modulus = G

    def update_state(self, dt, d, stress, xtra, *args):
        elastic.elastic_update_state(dt, self._param_vals,
                                     d, stress,
                                     log_error, log_message)

        return stress, xtra

    def jacobian(self, dt, d, stress, xtra, v):
        return self.constant_jacobian(v)

```

10.2 Building and Linking Materials to gmd

`buildmtls` builds the `gmd` materials by searching the subdirectories of `$GMDROOT/materials/library` and the directories specified by the `$GMDMTLS`

environment variables and building materials it finds. It does so by searching for a single file `makemf.py` in each directory. `makemf.py` is responsible for building the materials and communicating back to `buildmtls`.

10.2.1 Building User Materials

User materials are built by the `makemf` function of the `makemf.py` scripts

makemf.makemf: Interface

```
    blt, fld, skip = makemf(destd, fc, fio, materials=None, *args)
str dest
    path to directory to copy built shared object libraries (if any)
str fc
    path to fortran compiler
str fio
    path to the fortran IO routines
list materials
    list of materials to build. if empty, build all
tuple args
    not used
tuple blt
    (name, interface, mclass, parameters). name is the name of the
    material, interface the file path to the interface file, mclass the ma-
    terial model class name in interface, parameters an order list of
    parameter names
list fld
    list of names of materials that failed to build
list skip
    list of names of materials that were skipped
```

10.2.2 Building Materials with f2py

Material models written in Fortran should be built in to Python shared object libraries with `f2py`. The function `utils.gmdf2py.f2yp` provides an interface to `f2py`.

utils.gmdf2py.f2py: Interface

```
stat = f2py(name, source_files, signature, fc, incd=None)
```

str name
material model name. will be used to set name of shared object library.

list source_files
list of absolute values of Fortran source files

str signature
path to signature file

str fc
path to Fortran compiler

str ind
(optional) path to include directories

int stat
returns 0 if successful, 1 otherwise

Below is an example of using `gmdf2py.f2py`

```
from utils.gmdf2py import f2py
def makemf(destd, fc, fio, materials=None, *args)
    ...
    stat = f2py(name, source_files, signature, fc, incd)
    if stat != 0:
        return [], [name], []

    shutil.move(name + ".so", os.path.join(destd, name + ".so"))
    return (name, filepath, mclass, parameters), [], []
```

Chapter 11

Regression Testing