

SANYO	No.1775A	LA7851
		CRT Display Synchronization Deflection Circuit

The LA7851 is a sync-deflection circuit IC dedicated to CRT display use. It can be connected to the LA7832,7833 (for vertical output use) to form a sync-deflection circuit that meets every requirement for CRT display use.

So far, ICs for color TV use have been applied to the sync-deflection circuit for CRT display use and general-purpose ICs such as one-shot multivibrator, inverter and a lot of transistors have been used to form the peripherals such as sync input interface, horizontal phase shifter. The LA7851 contains these peripherals on chip, has a wide vertical pull-in range of 20Hz, and adopts a stable circuit for horizontal oscillation from 15kHz to 100kHz aiming at improving the characteristics required for CRT display use.

Features

- The vertical pull-in range 20Hz permits non-adjusting at vertical sync 50Hz/60Hz.
- The horizontal oscillation frequency can be adjusted stably from 15kHz to 100kHz.
- The horizontal display can be shifted right/left.
- The horizontal/vertical sync input can be used intact regardless of the difference in pulse polarity and pulse width.
- The AFC feedback sawtooth wave can be obtained by simply applying a flyback pulse to the IC as a trigger pulse.
- Any duty of the horizontal pulse can be set.
- Good linearity because DC bias at vertical output stage is subjected to sampling control within retrace time.

On-chip Functions

[Horizontal Block]

- AFC
- Horizontal OSC
- X-ray protector
- Horizontal phase shift
- AFC sawtooth wave generator
- Horizontal pulse duty setting


[Vertical Block]

- Vertical OSC
- Vertical sawtooth wave generator
- Sampling type DC voltage control

Package Dimensions

(unit:mm)

3021B



LA7851

Maximum Ratings at Ta = 25°C

Maximum Supply Voltage	$V_{10}, V_{20} \max$	14	V
Allowable Power Dissipation	$P_d \max$ Ta ≤ 65°C	780	mW
Operating Temperature	Topr	-20 to +85	°C
Storage Temperature	Tstg	-55 to +125	°C

Operating Conditions at Ta = 25°C



Recommended Supply Voltage	V_{10}, V_{20}	12.0	V
Operating Voltage Range	$V_{10}, V_{20} \text{ op}$	9 to 13.5	V
Recommended Vertical Pulse Input Peak Value	V_{PULSE}	5.0	Vp-p
Operating Vertical Pulse Input Peak Value Range	V_{PULSE}	2.0 to 6.0	Vp-p
Recommended Horizontal Pulse Input Peak Value	H_{PULSE}	5.0	Vp-p
Operating Horizontal Pulse Input Peak Value Range	H_{PULSE}	2.0 to 6.0	Vp-p

Operating Characteristics at Ta = 25°C, $V_{11}, V_{22} = 12\text{V}$


		min	typ	max	unit
VCC10 Current Dissipation	I_{10}	12		30	mA
VCC20 Current Dissipation	I_{20}	5		12	mA
Vertical Frequency Pull-in Range	V_{PIN} Vertical sync 60Hz	21.0		23.0	Hz
Vertical Free-running Frequency	f_v f_v center 55Hz	50		60	Hz
Increased/Reduced Voltage	Δf_{vv} $V_{22} = 12 \pm 1\text{V}, 55\text{Hz at } 12\text{V}$	-0.1		0.1	Hz
Characteristic of Vertical Frequency					
Midpoint Control Threshold Level		3.8		4.4	V
Vertical OSC Start Voltage	$f_{v, \text{st}}$			4.0	V
Temperature Characteristic of Vertical Frequency	Ta = -10 to +60°C	-0.028		0.028	Hz/°C
Vertical Driver Amplification Factor	G_v	12		18	dB
Horizontal AFC DC Loop Gain	I_{AFC}	±0.85		±1.6	mA
Horizontal Free-running Frequency	f_H f_H center 15.734kHz	-750		750	Hz
Horizontal OSC Start Voltage	$f_{H, \text{st}}$			4.0	V
Increased/Reduced Voltage	$\Delta f_{H, v}$ $V_{11} = 12 \pm 1\text{V}, 15.734\text{kHz at } 12\text{V}$	-50		50	Hz
Characteristic of Horizontal Frequency					
Horizontal OSC Warm-up Drift	Δf_H 5s. to 30min. after application of power	-50		50	Hz
Temperature Characteristic of Horizontal Frequency	Ta = -10 to +60°C	-2.9		2.9	Hz/°C
Horizontal Output Drive Current	I_{12}	6.0		12.0	mA
Increased/Reduced Voltage	$V_{10} = 12 \pm 1\text{V}$	-0.5		0.5	%/V
Characteristic of Phase Shifter Delay Time					
Temperature Characteristic of Phase Shifter Delay Time	Ta = -10 to +60°C	-0.1		0.1	%/°C
Increased/Reduced Voltage	$V_{10} = 12 \pm 1\text{V}$	-1.0		1.0	%/V
Characteristic of Phase Shifter Delay Time					
Temperature Characteristic of Phase Shifter Pulse Width	Ta = -10 to +60°C	-0.13		0.13	%/°C
AFC Phase Comparison Center Time	15.734kHz after F.B.P. input	9.9		11.5	μs
Increased/Reduced Voltage	$V_{10} = 12 \pm 1\text{V}$	-1.5		1.5	%/V
Characteristic of AFC Phase Comparison Center Time					
Temperature Characteristic of AFC Phase Comparison Center Time	Ta = -10 to +60°C	-0.2		0.2	%/°C
Comparison Waveform Generating Input Operation Voltage	V_4	0.6		0.9	V
Pin 13 Voltage at Hold-down Operation Start	V_{13}	0.5		0.8	V

LA7851

Equivalent Circuit Block Diagram



Sample Application Circuit: 14" Color Monitor/ $f_V=60\text{Hz}$, $f_H=15.734\text{kHz}$

Unit (resistance: Ω , capacitance:F)

- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
 - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of **June , 1996** . Specifications and information herein are subject to change without notice.

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.