

Exact Descent of Ternary Relations along Incidence Bisimulation Quotients

Jun Kawasaki
root@junkawasaki.com

July 2026

Abstract

We study when an independently supplied, possibly multi-valued ternary relation on an incidence structure survives behavioral identification. Exact descent to the incidence-bisimulation quotient is equivalent to coordinatewise representative independence; the descended relation is unique, and the quotient has both a kernel-pair coequalizer universal property and an abstract congruence-reflection formulation. For a finite carrier of size n , failure is witnessed by one of three coordinate-tagged four-variable certificates, giving a $3n^4$ search rather than a six-variable search. Support-minimal certificates carry an action of the resonance-bisimulation automorphism group. For a seven-cell simplex selector we prove, without relying on exhaustive cardinality computation, that there are exactly 32 minimal obstruction orbits, partitioned into five structural families of sizes 8, 4, 4, 12, 4. Positive examples include dimension-graded simplicial families and a small structural reaction-network model; a natural-number coproduct supplies an explicit failure. The theorem package, categorical constructions, structural classification, and executable cross-checks are machine checked in Lean 4.

1 Introduction

Quotienting a structured object is routine only after every relevant operation and relation has been shown independent of representatives. This familiar principle becomes nontrivial when the equivalence is generated behaviorally by one part of a structure while another relation is supplied independently. Our case has two layers: signed boundary data determines an incidence bisimulation, whereas a ternary relation $\text{Res}(x, y, z)$ records a potentially multi-valued “resonance” mode. Boundary-indistinguishable cells need not be interchangeable in all three resonance coordinates.

The central question is therefore precise:

When is there a ternary relation on the incidence-bisimulation quotient whose truth on quotient classes is exactly the original truth on every choice of representatives?

The answer is the expected congruence condition, but its incidence-specific consequences are useful. It yields a categorical quotient theorem, explicit positive and negative models, and a finite theory of compatibility obstructions. The latter decomposes a global six-representative failure into three local four-variable failures and supports classification modulo the automorphisms that preserve both incidence bisimulation and resonance.

Our contributions are:

1. an exact-descent iff theorem, uniqueness, universal factorization, kernel-pair coequalizer, reflection, and adjunction;
2. a finite $3n^4$ obstruction criterion and support-minimal orbit theory;

3. a structural, card-independent classification of the 32 minimal obstruction orbits in a seven-cell simplex selector;
4. generic graded and simplicial positive families, explicit negative and non-faithful positive examples, and a structural reaction-network instance;
5. a Lean-to-paper index linking every stated result to checked declarations and their hypotheses.

We do not claim novelty for congruence quotients, coequalizers, coalgebraic bisimulation, relational quotients, free algebras, or symmetry reduction in isolation. These are established tools [13, 14, 15, 6, 7]. The contribution is the incidence-derived equivalence, its interaction with an independent ternary relation, and the resulting checked obstruction package.

2 Incidence, bisimulation, and exact descent

The Lean development uses a rich **Incidence** structure containing a carrier, typed signed boundary entries with positive multiplicity, a unit and gluing operation, structural laws, and ternary resonance. Only the following reduct is needed for the main quotient theorem.

Definition 2.1 (Paper-facing reduct). An *incidence-resonance system* consists of a set I , an equivalence relation $\sim_b$ obtained from the boundary behavior of an incidence structure, and a ternary relation $\text{Res} \subseteq I^3$. Write $q : I \rightarrow I/\sim_b$ for the quotient map.

The full boundary definition matters for the examples and for how $\sim_b$ is generated, but the descent argument depends only on the resulting equivalence.

Definition 2.2 (Exact descent). The relation Res *descends exactly* if there is a relation $\overline{\text{Res}} \subseteq (I/\sim_b)^3$ such that, for all $x, y, z \in I$,

$$\overline{\text{Res}}(qx, qy, qz) \iff \text{Res}(x, y, z).$$

Definition 2.3 (Resonance congruence). The equivalence $\sim_b$ is a *resonance congruence* if

$$x_1 \sim_b x_2, \quad y_1 \sim_b y_2, \quad z_1 \sim_b z_2 \implies (\text{Res}(x_1, y_1, z_1) \leftrightarrow \text{Res}(x_2, y_2, z_2)).$$

There is always an existential-image relation on quotient classes,

$$\text{Res}_q(X, Y, Z) :\iff \exists x \in X \exists y \in Y \exists z \in Z, \text{Res}(x, y, z).$$

Without congruence it is a saturation rather than an exact representation.

Theorem 2.4 (Exact descent criterion). Res *descends exactly along q if and only if $\sim_b$ is a resonance congruence. When these conditions hold, $\text{Res}_q(qx, qy, qz)$ is equivalent to $\text{Res}(x, y, z)$.*

Proof. If $\overline{\text{Res}}$ is exact, replace representatives in each coordinate and use equality of quotient classes. Conversely, congruence makes the displayed truth value independent of representatives; equivalently, the existential image Res_q reflects as well as preserves Res . $\square$

Proposition 2.5 (Uniqueness). *Any relation on $(I/\sim_b)^3$ exact on representatives equals Res_q .*

Proof. Every quotient class has a representative. Induction on the three quotient arguments reduces equality to exactness on (qx, qy, qz) . $\square$

The criterion also admits a coalgebra-facing decomposition. Say that resonance has *mode transport* when replacing bisimilar left and right inputs can transport every output to some bisimilar resonant output, in both directions. Say that it is *output saturated* when replacing an output by a bisimilar one preserves and reflects resonance.

Theorem 2.6 (Transport and saturation). *Exact descent is equivalent to mode transport along bisimilar inputs together with output saturation under bisimilarity.*

The forward implication uses full three-coordinate congruence. Conversely, transport supplies a suitable output representative after changing the two inputs, and output saturation first aligns that representative and then changes the requested output coordinate.

3 Universal and categorical formulations

Let a ternary resonance system be a set with a ternary relation, and let a morphism preserve that relation. These systems and morphisms form a category **TRS**. A map $f : I \rightarrow A$ is bisimulation invariant when $x \sim_b y$ implies $f(x) = f(y)$.

Theorem 3.1 (Universal factorization). *Every bisimulation-invariant resonance morphism $f : I \rightarrow A$ factors uniquely as $I \xrightarrow{q} I/\sim_b \xrightarrow{\bar{f}} A$. If theorem 2.4 holds, $\bar{f}$ is a resonance morphism from $(I/\sim_b, \text{Res}_q)$.*

Proof. Define $\bar{f}([x]) = f(x)$. Invariance gives well-definedness, quotient surjectivity gives uniqueness, and the existential definition of Res_q reduces relation preservation to that of f . $\square$

Form the kernel-pair carrier $K = \{(x, y) \in I^2 \mid x \sim_b y\}$, equipped componentwise with resonance, and let $p_1, p_2 : K \rightrightarrows I$ be the projections.

Theorem 3.2 (Kernel-pair coequalizer). *Under resonance congruence, the quotient projection is a coequalizer of p_1, p_2 in **TRS**. The Lean category-theory interface packages the quotient cocone as a *Cofork* carrying an *IsColimit*; the induced hom-set equivalence is natural under postcomposition.*

The same theorem is not specific to incidence after the congruence has been identified. Let **CTRS** be ternary systems bundled with a setoid that is a relation congruence. Quotienting defines $Q : \mathbf{CTRS} \rightarrow \mathbf{TRS}$, while equipping a system with equality defines $E : \mathbf{TRS} \rightarrow \mathbf{CTRS}$.

Theorem 3.3 (Congruence reflection). *There is an adjunction $Q \dashv E$. Its objectwise unit is the quotient projection and its hom-set equivalence is the factorization of theorem 3.1. Every resonance-congruent incidence-bisimulation quotient is an instance of this reflection.*

These categorical results state the universal status of the quotient; they are not presented as a new general theorem about congruences.

4 Finite compatibility obstructions

Negating resonance congruence yields six representatives. It is more useful to change one coordinate at a time.

Definition 4.1 (Local obstruction). A local obstruction consists of a tag $c \in \{L, R, O\}$, a bisimilar but distinct pair $a \sim_b a'$, and two fixed entries u, v , such that replacing a by a' in coordinate c changes the truth of Res . For example, a left obstruction satisfies

$$\text{Res}(a, u, v) \not\leftrightarrow \text{Res}(a', u, v).$$

The right and output cases are analogous.

Theorem 4.2 (Coordinatewise classification). *Resonance congruence is equivalent to invariance separately in the left, right, and output coordinates. Hence exact descent fails if and only if a local obstruction exists.*

Proof. Global congruence immediately implies each one-coordinate condition. For the converse, move from (x_1, y_1, z_1) to (x_2, y_2, z_2) through the three intermediate triples, changing one coordinate at a time. $\square$

Corollary 4.3 (Finite search). *For a finite carrier of size n with decidable equivalence and resonance, exact descent is equivalent to emptiness of an executable obstruction table with three tagged searches over four carrier entries. The raw search space has size $3n^4$.*

Swapping a and a' is a fixed-point-free involution on local obstructions, so every swap orbit has two elements. More structure is obtained from automorphisms preserving both $\sim_b$ and Res.

Definition 4.4 (Support-minimal obstruction). The support of a local obstruction is the set of carrier elements appearing in its representative pair and fixed entries. An obstruction is support-minimal when no obstruction has strictly smaller support cardinality.

Theorem 4.5 (Minimal orbit criterion). *Every failed finite exact descent has a support-minimal local obstruction. Resonance-bisimulation automorphisms preserve obstruction status, support size, and minimality. Exact descent is equivalent to absence of an orbit containing a support-minimal obstruction. For finite decidable systems, these orbits form an executable table.*

For graph-functional resonance, $\text{Res}(x, y, z)$ is the graph of a selector $s(x, y) = z$. Two generic mechanisms generate obstructions: selector disagreement on bisimilar inputs, and a selected output class containing more than one element. Thus exact descent forces selector invariance and singleton selected output classes under the hypotheses formalized in the development.

5 The seven-cell simplex classification

The principal finite example has cells

$$V = \{v_0, v_1, v_2\}, \quad E = \{e_{01}, e_{02}, e_{12}\}, \quad F = \{f_{012}\}.$$

Boundary behavior identifies exactly cells of the same shape: the three vertices form one class, the three edges a second, and the face a singleton. An ordinary simplex selector supplies graph-functional resonance and fails exact descent.

Theorem 5.1 (Sharp support). *Every local obstruction has support size at least two. The simplex selector has support-minimal obstructions of size two, and every support-minimal simplex obstruction has support exactly two. Its representative pair has vertex or edge shape, never face shape, and both fixed entries belong to that pair.*

The automorphism group of the simplex resonance/bisimulation structure has 12 elements. Pair transitivity normalizes each ordered distinct edge pair to (e_{01}, e_{02}) and gives the corresponding vertex normalizations. Four fixed-slot patterns encode the two fixed entries drawn from a representative pair. Combining coordinate, shape, distinguished- v_0 position, and slot equality yields eight structural parameter summands.

Theorem 5.2 (Structural orbit classification). *The support-minimal simplex obstruction orbits are in explicit bijection with a 32-element structural parameter type. They split into five coordinate-and-shape families with orbit counts*

$$8, \quad 4, \quad 4, \quad 12, \quad 4, \quad 8 + 4 + 4 + 12 + 4 = 32.$$

The parameter map is injective by an orbit-constant normal-form signature and surjective by explicit automorphism normalization. Consequently the count 32 does not depend on native enumeration.

Proof architecture. Each parameter constructs an obstruction whose fixed slots lie in its distinct representative pair; a general two-support lemma proves minimality. The normal-form signature separates parameter values, proving injectivity on orbits. Conversely, theorem 5.1 restricts an arbitrary minimal obstruction to a vertex or edge pair and four slot patterns. Pair transitivity and coordinate-specific normalization carry it to a canonical parameter, proving surjectivity. The displayed cardinal arithmetic then gives 32. $\square$

Lean also evaluates the complete finite tables, independently obtaining 12 automorphisms and 32 minimal orbits. This computation is a cross-check, not the proof of theorem 5.2.

6 Positive and negative models

6.1 Explicit failure and success

A coproduct of two natural-number incidence systems is an explicit negative model: boundary behavior identifies representatives that its resonance distinguishes, so no exact quotient relation exists.

The saturated simplex relation, by contrast, is closed across the three shape classes. Its seven cells collapse non-faithfully to vertex, edge, and face, and resonance descends exactly. A non-saturated geometric variant declares an output mode when its shape equals either input shape:

$$\overline{\text{Res}}(\ell, r, o) \iff (o = \ell) \vee (o = r).$$

Vertex–face interaction therefore has two output modes and is genuinely multi-valued.

6.2 Graded representation theorem

Theorem 6.1 (Class-mode representation). *Let $g : I \rightarrow G$ be a surjective classifier whose kernel is incidence bisimulation. Suppose the class-mode selector always chooses one of the two input classes and is compatible with g . Then resonance descends exactly and the quotient relation is represented by*

$$\overline{\text{Res}}(gx, gy, gz) \iff (gz = gx) \vee (gz = gy).$$

Grade-preserving maps induce resonance morphisms and respect identity and composition.

A bounded graded-boundary profile gives sufficient boundary hypotheses for $g(x) = g(y)$ iff $x \sim_b y$: positive-dimensional boundaries lower grade by one, are nonempty, and equal-grade cells have matching boundary profiles. This reconstructs the triangle grading and applies to an infinite node/edge path.

Corollary 6.2 (Simplicial families). *Every downward-closed decidable family of nonempty finite vertex sets, with a chosen unit cell, carries the codimension-one incidence used in the Lean development. Two cells are bisimilar exactly when their dimensions agree, and the represented dimensions give an exact class-mode quotient as in theorem 6.1.*

6.3 Structural reaction network

Signed reactant/product boundaries encode the reversible pair $A \rightleftharpoons B$. A separate ternary relation records molecular modes exposed by interacting reaction modes.

Proposition 6.3 (Reaction-network instance). *The model’s bisimulation classes are exactly “molecule” and “reaction”. Resonance descends exactly to these two classes, while the source model is non-faithful and genuinely multi-valued.*

This is a structural Petri-net-style toy, not a kinetic semantics: it contains no rates, concentrations, firing semantics, mass-action dynamics, thermodynamics, or empirical claim. Established compositional reaction-network semantics are substantially richer [1, 2].

7 Presentations, logic, and boundary encoding

The formal development contains three supporting extensions.

First, unit-normal binary trees form a free empty-boundary incidence. Adding irreflexive generator-boundary lists and ternary relation generators gives a presented free incidence. Every compatible generator interpretation extends uniquely to a morphism preserving unit, glue, boundary membership, and resonance. Term equations generate the least glue congruence; the quotient is an incidence exactly when boundary data is representative independent and no endpoint collapses to its source, and resonance descends exactly when the generated equation relation is a resonance congruence. These three iff conditions form one quotient-admissibility certificate. This is an objectwise universal property; we do not claim a proved adjunction between categories of presentations and incidence algebras.

Second, a propositional observation language generated by one ternary atom, truth, falsity, conjunction, disjunction, and implication satisfies:

Theorem 7.1 (Logical necessity). *Exact descent is equivalent to invariance of every formula under pointwise bisimilar valuations. If descent fails, the atomic resonance formula already separates two such valuations.*

The translation into the repository’s conservative `IncProof.Formula` syntax commutes with its forgetful retraction and preserves semantics for agreeing physical interpretations. No quotient rule for the `IncProof.Derives` judgment is claimed.

Third, every boundary occurrence yields a three-sorted incidence hypergraph

$$\text{IncidencePoint} \longrightarrow \text{Vertex}, \quad \text{IncidencePoint} \longrightarrow \text{Edge},$$

where endpoint cells are vertices and boundary-source cells are edges. Structured incidence morphisms induce commuting maps and preserve identity and composition. This encoding is deliberately forgetful: roles, signs, multiplicities, glue, guards, types, and resonance are not recoverable. It is not an equivalence or faithful representation of the full theory. Categorical incidence hypergraphs already form an established theory [9].

8 Related work and claim boundary

Congruence quotients and free algebras are standard universal algebra [6]. Coalgebra supplies behavioral equivalence, bisimulation, minimization, and quotient reasoning [13, 14, 15, 8]. Bisimulation invariance and expressive modal languages are also established [3, 4]; Marić studies bisimulation quotients directly in inquisitive modal logic [11]. Quotients and strong homomorphisms of relational systems precede the present work [12, 7], and many-sorted quotient algebra has been mechanized in Mizar [10]. Isabelle’s bounded-natural-functor development includes bisimulation and quotient-coalgebra infrastructure [5].

Accordingly, the exact-descent criterion is an instance of standard relational compatibility once the incidence equivalence is fixed. Our novelty claim is limited to the combined incidence/resonance theorem package and its particular finite obstruction invariant. We make no priority or formalization-first claim. A scoped public and mechanized prior-art audit accompanies the source; subscription-database citation traversal and external specialist review remain requirements before asserting a stronger journal-level novelty position.

9 Mechanization and reproducibility

All results are checked with Lean 4 and mathlib v4.23.0. The main source is `IncidenceTheory/IncidenceResearch.lean`. The repository maintains:

- a completion-claim matrix mapping scoped claims to declarations;
- a 29-row Lean-to-paper theorem index whose boundaries are checked in CI;
- an axiom audit allowing only `propext`, `Classical.choice`, and `Quot.sound` in the capstone dependency closure;
- executable finite counts as independent checks of the structural proof.

The verification entry point is `./verify.sh`. Source and reproducibility metadata are available at <https://github.com/com-junkawasaki/inc>.

10 Conclusion

An incidence quotient preserves an independent ternary relation exactly when incidence bisimulation is a congruence for that relation. Beyond this standard quotient mechanism, coordinate decomposition turns failure into a finite $3n^4$ obstruction problem, and automorphism normalization exposes a concrete structural classification: 32 minimal orbits for the seven-cell simplex selector. The categorical, finite, logical, simplicial, and reaction-network instances are checked in one Lean development, with broad foundational and applied claims kept outside scope.

A Checked theorem groups

The machine-readable theorem index contains 29 groups. For readability they are summarized here; the repository’s TSV theorem index is authoritative for exact Lean declarations and hypotheses.

1–4	core structures; exact descent; uniqueness; universal factorization
5–6	natural-number obstruction; saturated-simplex positive model
7–11	finite, coordinate, swap-orbit, functional, and support-minimal classifications
12–14	transport/saturation criterion; kernel-pair and standard categorical coequalizers
15–16	geometric simplex and generic class-mode representation
17–21	free, presented, equational, logical, and reference-syntax results
22–24	congruence reflection, graded functoriality, and quotient adjunction
25–27	infinite path, bounded grading, and standard simplicial families
28–29	forgetful incidence-hypergraph encoding and reversible reaction model

References

- [1] J. C. Baez and B. S. Pollard. A compositional framework for reaction networks. *Rev. Math. Phys.* 29(9), 2017. doi:10.1142/S0129055X17500283.
- [2] J. C. Baez, F. Genovese, J. Master, and M. Shulman. Categories of nets. arXiv:2101.04238, 2021.
- [3] Z. Bakhtiari and H. H. Hansen. Bisimulation for weakly expressive coalgebraic modal logics. *CALCO 2017, LIPIcs* 72, 4:1–4:16.
- [4] Z. Bakhtiari, H. H. Hansen, and A. Kurz. On the logic of behavioural equivalence, 2019.
- [5] J. C. Blanchette, A. Popescu, and D. Traytel. Operations on bounded natural functors. *Archive of Formal Proofs*, 2017.
- [6] S. Burris and H. P. Sankappanavar. *A Course in Universal Algebra*. Springer, 1981.

- [7] I. Chajda and H. Länger. Quotients and homomorphisms of relational systems. *Acta Univ. Palacki. Olomuc., Fac. Rerum Nat., Math.* 49(2):37–47, 2010.
- [8] U. Dorsch, S. Milius, L. Schröder, and T. Wißmann. Efficient coalgebraic partition refinement. *CONCUR 2017*, LIPIcs 85, 32:1–32:16.
- [9] J. Grilliette and L. J. Rusnak. Incidence hypergraphs: box products and the Laplacian. arXiv:1805.07670, 2018.
- [10] M. Korolkiewicz. Many sorted quotient algebra. *Formalized Mathematics* 5(1):79–84, 1996.
- [11] S. Marić. Bisimulation quotient in inquisitive modal logic. *Logics* 3(3):11, 2025. doi:10.3390/logics3030011.
- [12] M. Novotný. Homomorphisms and strong homomorphisms of relational structures. *Archivum Mathematicum* 33(1–2):57–64, 1997.
- [13] J. J. M. M. Rutten. Universal coalgebra: a theory of systems. *Theor. Comput. Sci.* 249(1):3–80, 2000.
- [14] S. Staton. Relating coalgebraic notions of bisimulation. *Logical Methods in Computer Science* 7(1), 2011.
- [15] T. Wißmann. *Coalgebraic Semantics and Minimization in Sets and Beyond*. PhD thesis, Friedrich-Alexander-Universität Erlangen–Nürnberg, 2020.