

Exact Descent of Ternary Relations along Incidence Bisimulation Quotients

Jun Kawasaki
root@junkawasaki.com

July 2026

Abstract

We study when an independently supplied, possibly multi-valued ternary relation on an incidence structure survives behavioral identification. Exact descent to the incidence-bisimulation quotient is equivalent to coordinatewise representative independence; the descended relation is unique, and the quotient has both a kernel-pair coequalizer universal property and an abstract congruence-reflection formulation. For a finite carrier of size n , failure is witnessed by one of three coordinate-tagged four-variable certificates, giving a $3n^4$ search rather than a six-variable search. Support-minimal certificates carry an action of the resonance-bisimulation automorphism group. For a seven-cell simplex selector we prove, without relying on exhaustive cardinality computation, that there are exactly 32 minimal obstruction orbits, partitioned into five structural families of sizes 8, 4, 4, 12, 4. Positive examples include dimension-graded simplicial families and a small structural reaction-network model; a natural-number coproduct supplies an explicit failure. The theorem package, categorical constructions, structural classification, and executable cross-checks are machine checked in Lean 4.

1 Introduction

Quotienting a structured object is routine only after every relevant operation and relation has been shown independent of representatives. This familiar principle becomes nontrivial when the equivalence is generated behaviorally by one part of a structure while another relation is supplied independently. Our case has two layers: signed boundary data determines an incidence bisimulation, whereas a ternary relation $\text{Res}(x, y, z)$ records a potentially multi-valued “resonance” mode. Boundary-indistinguishable cells need not be interchangeable in all three resonance coordinates.

The central question is therefore precise:

When is there a ternary relation on the incidence-bisimulation quotient whose truth on quotient classes is exactly the original truth on every choice of representatives?

The answer is the expected congruence condition, but its incidence-specific consequences are useful. It yields a categorical quotient theorem, explicit positive and negative models, and a finite theory of compatibility obstructions. The latter decomposes a global six-representative failure into three local four-variable failures and supports classification modulo the automorphisms that preserve both incidence bisimulation and resonance.

Our contributions are:

1. an exact-descent iff theorem, uniqueness, universal factorization, kernel-pair coequalizer, reflection, and adjunction;
2. a finite $3n^4$ obstruction criterion and support-minimal orbit theory;

3. a structural, card-independent classification of the 32 minimal obstruction orbits in a seven-cell simplex selector;
4. generic graded and simplicial positive families, explicit negative and non-faithful positive examples, and a structural reaction-network instance;
5. a Lean-to-paper index linking every stated result to checked declarations and their hypotheses.

We do not claim novelty for congruence quotients, coequalizers, coalgebraic bisimulation, relational quotients, free algebras, or symmetry reduction in isolation. These are established tools [13, 14, 15, 6, 7]. The contribution is the incidence-derived equivalence, its interaction with an independent ternary relation, and the resulting checked obstruction package.

2 Incidence, bisimulation, and exact descent

The Lean development uses a rich **Incidence** structure containing a carrier, typed signed boundary entries with positive multiplicity, a unit and gluing operation, structural laws, and ternary resonance. Only the following reduct is needed for the main quotient theorem.

Definition 2.1 (Paper-facing reduct). An *incidence-resonance system* consists of a set I , an equivalence relation $\sim_b$ obtained from the boundary behavior of an incidence structure, and a ternary relation $\text{Res} \subseteq I^3$. Write $q : I \rightarrow I/\sim_b$ for the quotient map.

The full boundary definition matters for the examples and for how $\sim_b$ is generated, but the descent argument depends only on the resulting equivalence.

Definition 2.2 (Exact descent). The relation Res *descends exactly* if there is a relation $\overline{\text{Res}} \subseteq (I/\sim_b)^3$ such that, for all $x, y, z \in I$,

$$\overline{\text{Res}}(qx, qy, qz) \iff \text{Res}(x, y, z).$$

Definition 2.3 (Resonance congruence). The equivalence $\sim_b$ is a *resonance congruence* if

$$x_1 \sim_b x_2, \quad y_1 \sim_b y_2, \quad z_1 \sim_b z_2 \implies (\text{Res}(x_1, y_1, z_1) \leftrightarrow \text{Res}(x_2, y_2, z_2)).$$

There is always an existential-image relation on quotient classes,

$$\text{Res}_q(X, Y, Z) :\iff \exists x \in X \exists y \in Y \exists z \in Z, \text{Res}(x, y, z).$$

Without congruence it is a saturation rather than an exact representation.

Theorem 2.4 (Exact descent criterion). Res *descends exactly along q if and only if $\sim_b$ is a resonance congruence. When these conditions hold, $\text{Res}_q(qx, qy, qz)$ is equivalent to $\text{Res}(x, y, z)$.*

Proof. If $\overline{\text{Res}}$ is exact, replace representatives in each coordinate and use equality of quotient classes. Conversely, congruence makes the displayed truth value independent of representatives; equivalently, the existential image Res_q reflects as well as preserves Res . $\square$

Proposition 2.5 (Uniqueness). *Any relation on $(I/\sim_b)^3$ exact on representatives equals Res_q .*

Proof. Every quotient class has a representative. Induction on the three quotient arguments reduces equality to exactness on (qx, qy, qz) . $\square$

The criterion also admits a coalgebra-facing decomposition. Say that resonance has *mode transport* when replacing bisimilar left and right inputs can transport every output to some bisimilar resonant output, in both directions. Say that it is *output saturated* when replacing an output by a bisimilar one preserves and reflects resonance.

Theorem 2.6 (Transport and saturation). *Exact descent is equivalent to mode transport along bisimilar inputs together with output saturation under bisimilarity.*

The forward implication uses full three-coordinate congruence. Conversely, transport supplies a suitable output representative after changing the two inputs, and output saturation first aligns that representative and then changes the requested output coordinate.

3 Universal and categorical formulations

Let a ternary resonance system be a set with a ternary relation, and let a morphism preserve that relation. These systems and morphisms form a category **TRS**. A map $f : I \rightarrow A$ is bisimulation invariant when $x \sim_b y$ implies $f(x) = f(y)$.

Theorem 3.1 (Universal factorization). *Every bisimulation-invariant resonance morphism $f : I \rightarrow A$ factors uniquely as $I \xrightarrow{q} I/\sim_b \xrightarrow{\bar{f}} A$. If theorem 2.4 holds, $\bar{f}$ is a resonance morphism from $(I/\sim_b, \text{Res}_q)$.*

Proof. Define $\bar{f}([x]) = f(x)$. Invariance gives well-definedness, quotient surjectivity gives uniqueness, and the existential definition of Res_q reduces relation preservation to that of f . $\square$

Form the kernel-pair carrier $K = \{(x, y) \in I^2 \mid x \sim_b y\}$, equipped componentwise with resonance, and let $p_1, p_2 : K \rightrightarrows I$ be the projections.

Theorem 3.2 (Kernel-pair coequalizer). *Under resonance congruence, the quotient projection is a coequalizer of p_1, p_2 in **TRS**. The Lean category-theory interface packages the quotient cocone as a *Cofork* carrying an *IsColimit*; the induced hom-set equivalence is natural under postcomposition.*

The same theorem is not specific to incidence after the congruence has been identified. Let **CTRS** be ternary systems bundled with a setoid that is a relation congruence. Quotienting defines $Q : \mathbf{CTRS} \rightarrow \mathbf{TRS}$, while equipping a system with equality defines $E : \mathbf{TRS} \rightarrow \mathbf{CTRS}$.

Theorem 3.3 (Congruence reflection). *There is an adjunction $Q \dashv E$. Its objectwise unit is the quotient projection and its hom-set equivalence is the factorization of theorem 3.1. Every resonance-congruent incidence-bisimulation quotient is an instance of this reflection.*

These categorical results state the universal status of the quotient; they are not presented as a new general theorem about congruences.

4 Finite compatibility obstructions

Negating resonance congruence yields six representatives. It is more useful to change one coordinate at a time.

Definition 4.1 (Local obstruction). A local obstruction consists of a tag $c \in \{L, R, O\}$, a bisimilar but distinct pair $a \sim_b a'$, and two fixed entries u, v , such that replacing a by a' in coordinate c changes the truth of Res . For example, a left obstruction satisfies

$$\text{Res}(a, u, v) \not\leftrightarrow \text{Res}(a', u, v).$$

The right and output cases are analogous.

Theorem 4.2 (Coordinatewise classification). *Resonance congruence is equivalent to invariance separately in the left, right, and output coordinates. Hence exact descent fails if and only if a local obstruction exists.*

Proof. Global congruence immediately implies each one-coordinate condition. For the converse, move from (x_1, y_1, z_1) to (x_2, y_2, z_2) through the three intermediate triples, changing one coordinate at a time. $\square$

Corollary 4.3 (Finite search). *For a finite carrier of size n with decidable equivalence and resonance, exact descent is equivalent to emptiness of an executable obstruction table with three tagged searches over four carrier entries. The raw search space has size $3n^4$.*

Swapping a and a' is a fixed-point-free involution on local obstructions, so every swap orbit has two elements. More structure is obtained from automorphisms preserving both $\sim_b$ and Res.

Definition 4.4 (Support-minimal obstruction). The support of a local obstruction is the set of carrier elements appearing in its representative pair and fixed entries. An obstruction is support-minimal when no obstruction has strictly smaller support cardinality.

Theorem 4.5 (Minimal orbit criterion). *Every failed finite exact descent has a support-minimal local obstruction. Resonance-bisimulation automorphisms preserve obstruction status, support size, and minimality. Exact descent is equivalent to absence of an orbit containing a support-minimal obstruction. For finite decidable systems, these orbits form an executable table.*

For graph-functional resonance, $\text{Res}(x, y, z)$ is the graph of a selector $s(x, y) = z$. Two generic mechanisms generate obstructions: selector disagreement on bisimilar inputs, and a selected output class containing more than one element. Thus exact descent forces selector invariance and singleton selected output classes under the hypotheses formalized in the development.

5 The seven-cell simplex classification

The principal finite example has cells

$$V = \{v_0, v_1, v_2\}, \quad E = \{e_{01}, e_{02}, e_{12}\}, \quad F = \{f_{012}\}.$$

Boundary behavior identifies exactly cells of the same shape: the three vertices form one class, the three edges a second, and the face a singleton. An ordinary simplex selector supplies graph-functional resonance and fails exact descent.

Theorem 5.1 (Sharp support). *Every local obstruction has support size at least two. The simplex selector has support-minimal obstructions of size two, and every support-minimal simplex obstruction has support exactly two. Its representative pair has vertex or edge shape, never face shape, and both fixed entries belong to that pair.*

The automorphism group of the simplex resonance/bisimulation structure has 12 elements. Pair transitivity normalizes each ordered distinct edge pair to (e_{01}, e_{02}) and gives the corresponding vertex normalizations. Four fixed-slot patterns encode the two fixed entries drawn from a representative pair. Combining coordinate, shape, distinguished- v_0 position, and slot equality yields eight structural parameter summands.

Theorem 5.2 (Structural orbit classification). *The support-minimal simplex obstruction orbits are in explicit bijection with a 32-element structural parameter type. They split into five coordinate-and-shape families with orbit counts*

$$8, \quad 4, \quad 4, \quad 12, \quad 4, \quad 8 + 4 + 4 + 12 + 4 = 32.$$

The parameter map is injective by an orbit-constant normal-form signature and surjective by explicit automorphism normalization. Consequently the count 32 does not depend on native enumeration.

Proof architecture. Each parameter constructs an obstruction whose fixed slots lie in its distinct representative pair; a general two-support lemma proves minimality. The normal-form signature separates parameter values, proving injectivity on orbits. Conversely, theorem 5.1 restricts an arbitrary minimal obstruction to a vertex or edge pair and four slot patterns. Pair transitivity and coordinate-specific normalization carry it to a canonical parameter, proving surjectivity. The displayed cardinal arithmetic then gives 32. $\square$

Lean also evaluates the complete finite tables, independently obtaining 12 automorphisms and 32 minimal orbits. This computation is a cross-check, not the proof of theorem 5.2.

6 Positive and negative models

6.1 Explicit failure and success

A coproduct of two natural-number incidence systems is an explicit negative model: boundary behavior identifies representatives that its resonance distinguishes, so no exact quotient relation exists.

For a sum carrying the exact representative-control certificate, the canonical classifier instead factors uniquely through the bisimulation quotient. Restricting its codomain to reachable observations produces an isomorphism of ternary resonance systems. On the category whose morphisms preserve both sum resonance and bisimulation, quotient and reachable-image assignments are functors and these comparison isomorphisms form a natural isomorphism. This is a conditional controlled-sum theorem, not unconditional closure of arbitrary incidence coproducts under quotient descent.

The saturated simplex relation, by contrast, is closed across the three shape classes. Its seven cells collapse non-faithfully to vertex, edge, and face, and resonance descends exactly. A non-saturated geometric variant declares an output mode when its shape equals either input shape:

$$\overline{\text{Res}}(\ell, r, o) \iff (o = \ell) \vee (o = r).$$

Vertex–face interaction therefore has two output modes and is genuinely multi-valued.

6.2 Graded representation theorem

Theorem 6.1 (Class-mode representation). *Let $g : I \rightarrow G$ be a surjective classifier whose kernel is incidence bisimulation. Suppose the class-mode selector always chooses one of the two input classes and is compatible with g . Then resonance descends exactly and the quotient relation is represented by*

$$\overline{\text{Res}}(gx, gy, gz) \iff (gz = gx) \vee (gz = gy).$$

Grade-preserving maps induce resonance morphisms and respect identity and composition.

A bounded graded-boundary profile gives sufficient boundary hypotheses for $g(x) = g(y)$ iff $x \sim_b y$: positive-dimensional boundaries lower grade by one, are nonempty, and equal-grade cells have matching boundary profiles. This reconstructs the triangle grading and applies to an infinite node/edge path.

Corollary 6.2 (Simplicial families). *Every downward-closed decidable family of nonempty finite vertex sets, with a chosen unit cell, carries the codimension-one incidence used in the Lean development. Two cells are bisimilar exactly when their dimensions agree, and the represented dimensions give an exact class-mode quotient as in theorem 6.1.*

6.3 Structural reaction network

Signed reactant/product boundaries encode the reversible pair $A \rightleftharpoons B$. A separate ternary relation records molecular modes exposed by interacting reaction modes.

Proposition 6.3 (Reaction-network instance). *The model’s bisimulation classes are exactly “molecule” and “reaction”. Resonance descends exactly to these two classes, while the source model is non-faithful and genuinely multi-valued.*

This is a structural Petri-net-style toy, not a kinetic semantics: it contains no rates, concentrations, firing semantics, mass-action dynamics, thermodynamics, or empirical claim. Established compositional reaction-network semantics are substantially richer [1, 2].

7 Presentations, logic, and boundary encoding

The formal development contains three supporting extensions.

First, unit-normal binary trees form a free empty-boundary incidence. Adding irreflexive generator-boundary lists and ternary relation generators gives a presented free incidence. Every compatible generator interpretation extends uniquely to a morphism preserving unit, glue, boundary membership, and resonance. Term equations generate the least glue congruence; the quotient is an incidence exactly when boundary data is representative independent and no endpoint collapses to its source, and resonance descends exactly when the generated equation relation is a resonance congruence. These three iff conditions form one quotient-admissibility certificate. This is an objectwise universal property; we do not claim a proved adjunction between categories of presentations and incidence algebras.

Second, a propositional observation language generated by one ternary atom, truth, falsity, conjunction, disjunction, and implication satisfies:

Theorem 7.1 (Logical necessity). *Exact descent is equivalent to invariance of every formula under pointwise bisimilar valuations. If descent fails, the atomic resonance formula already separates two such valuations.*

The translation into the repository’s conservative `IncProof.Formula` syntax commutes with its forgetful retraction and preserves semantics for agreeing physical interpretations. No quotient rule for the `IncProof.Derives` judgment is claimed.

Third, every boundary occurrence yields a three-sorted incidence hypergraph

$$\text{IncidencePoint} \longrightarrow \text{Vertex}, \quad \text{IncidencePoint} \longrightarrow \text{Edge},$$

where endpoint cells are vertices and boundary-source cells are edges. Structured incidence morphisms induce commuting maps and preserve identity and composition. This encoding is deliberately forgetful: roles, signs, multiplicities, glue, guards, types, and resonance are not recoverable. It is not an equivalence or faithful representation of the full theory. Categorical incidence hypergraphs already form an established theory [9].

8 Related work and claim boundary

Congruence quotients and free algebras are standard universal algebra [6]. Coalgebra supplies behavioral equivalence, bisimulation, minimization, and quotient reasoning [13, 14, 15, 8]. Bisimulation invariance and expressive modal languages are also established [3, 4]; Marić studies bisimulation quotients directly in inquisitive modal logic [11]. Quotients and strong homomorphisms of relational systems precede the present work [12, 7], and many-sorted quotient algebra has been mechanized in Mizar [10]. Isabelle’s bounded-natural-functor development includes bisimulation and quotient-coalgebra infrastructure [5].

Accordingly, the exact-descent criterion is an instance of standard relational compatibility once the incidence equivalence is fixed. Our novelty claim is limited to the combined incidence/resonance theorem package and its particular finite obstruction invariant. We make no priority or formalization-first claim. A scoped public and mechanized prior-art audit accompanies the source; subscription-database citation traversal and external specialist review remain requirements before asserting a stronger journal-level novelty position.

8.1 Canonical congruence saturation

The obstruction criterion also yields a canonical positive completion, rather than merely rejecting noncongruent relations. Let a ternary relation be specified directly on the bisimulation quotient and pull it back along the three quotient projections. If it contains every output selected by the glue operation, this pullback is a valid resonance on the unchanged incidence data. Its bisimulation relation is unchanged and exact descent holds automatically; the descended relation is exactly the relation originally specified on the quotient.

Taking the specified relation to be the existential quotient image of the original resonance defines the *canonical bisimulation-congruence saturation*. It contains the original resonance and is contained in every three-coordinate bisimulation-congruent relation that contains the original. It fixes precisely the already congruent resonances and applying it twice has the same effect as applying it once. Thus it is an extensive, least, and idempotent completion at the resonance level. It deliberately leaves the carrier, boundary, type, and glue unchanged; it is not a construction of a full incidence object on the quotient carrier.

Resonance-saturation reflection. Fix the carrier, boundary, type, and glue data, and order all admissible resonance extensions pointwise. The canonical saturation is monotone, extensive, and idempotent, hence defines a closure operator on this poset. Its closed elements are exactly the extensions for which bisimulation is a ternary congruence. Saturation and the inclusion of closed extensions form a Galois insertion, so this is a reflector between the associated thin categories and the closure is its idempotent monad. This first statement is fiberwise over one fixed incidence skeleton.

Global saturation adjunction. Fix only the boundary-role type and allow carriers and cell types to vary. Morphisms preserve the unit, selected glue, boundary occurrences, resonance, and bisimulation. These data form a category, and saturation acts functorially on its carrier-changing morphisms. The extensive inclusion is a natural unit and the square of the saturation functor is naturally isomorphic to saturation itself. Quotient-congruent objects form a structured subcategory, and saturation into it is left adjoint to inclusion. Equivalently, every morphism into a congruent target factors uniquely through the saturation unit. A checked non-surjective map from a one-point to a two-point trivial incidence witnesses that this category genuinely permits carrier changes. The present category fixes the role type and requires only forward boundary preservation; role-changing or boundary-reflecting morphisms are not claimed in this weaker category.

Role-changing exact-boundary adjunction. A stronger category allows carrier, role, and cell-type maps simultaneously. Its morphisms preserve the algebraic and behavioral data above and require an if-and-only-if law for membership of every mapped boundary occurrence. The saturation functor, natural unit, idempotence isomorphism, congruent subcategory, adjunction, and unique factorization all lift to this category. A non-surjective map from a one-point incidence with role type `GraphRole` to a two-point incidence with role type `Unit` witnesses both carrier and role change. Boundary exactness concerns mapped occurrences; essential surjectivity onto all target boundary occurrences is not required in this intermediate category.

Globally boundary-surjective adjunction. The strongest morphism class considered here additionally requires every boundary occurrence at every target cell to have a source cell and source occurrence mapping to it. Identity and composition preserve this global coverage law. Since saturation changes only resonance, its functor, natural unit, idempotence isomorphism, congruent subcategory, adjunction, and unique factorization all restrict to these maps. The role-changing one-point to two-point example remains carrier-nonsurjective but covers all target boundary data. Thus the theorem asserts essential surjectivity of boundary occurrences, not surjectivity onto target cells having empty boundary.

Carrier-and-boundary-surjective adjunction. Finally, imposing surjectivity on the carrier map as well gives the strongest morphism category formalized here. It is closed under identity and composition, and saturation again has its natural unit, idempotence isomorphism, congruent-object adjunction, and unique factorization. A checked map from a two-point incidence with role type **GraphRole** onto a one-point incidence with role type **Unit** is surjective but noninjective, showing that this category is not restricted to isomorphisms.

Internal-logic conservativity. Saturation is monotone at the level of resonance atoms. Consequently the positive language generated by truth, falsity, atoms, conjunction, and disjunction is preserved from every incidence into its saturation. The full language also contains implication and is not monotone in this sense. Full preservation and reflection for every formula holds exactly when the source resonance is already a bisimulation congruence; equivalently, every source formula is bisimulation invariant. Every formula is invariant after saturation. The ordinary simplex is a strict witness: its **v1/face/face** observation atom is false before saturation and true afterwards. These theorems transfer through the mechanized resonance-to-**IncProof** translation whenever the encoded atomic truth predicates agree with the source and saturated resonance relations.

Dependent-calculus conservativity. The normalized dependent completion for the raw $\Pi/\Sigma/\text{Id}$ calculus bundles structural renaming and substitution preservation with resonance symmetry, units, type compatibility, relational associativity, and quotient congruence. Its congruence field makes the resonance relation a fixed point of saturation. Hence the completion transfers to saturation while all formation and typing renaming/substitution outputs remain definitionally unchanged. When paired with the public completed-typing interpreter, every semantic interpretation and its substitution-coherence theorem are unchanged as well. The natural-number completion is a concrete instance. This is a conservativity theorem for an existing normalized completion; saturation alone does not synthesize associativity for an arbitrary resonance.

Associative saturation completion. There is also a genuinely generative dependent result. Saturation preserves resonance symmetry, units, and type compatibility unconditionally. If source modes transport along bisimilar input representatives, source relational associativity transports to saturation: the transport law aligns the two representatives of each intermediate mode before applying associativity. Consequently structural preservation, resonance laws, associativity, and mode transport suffice to construct a normalized dependent completion; saturation supplies the missing quotient congruence. The two-point trivial incidence is a strict example. Its bisimulation is total, its functional resonance is associative and transports modes, but it is not output-saturated. Saturation adds the **true/true/false** mode and remains associative. No preservation of associativity is claimed without the mode-transport hypothesis.

Exact quotient-associativity criterion. For an arbitrary source relation, associativity can be stated directly for its existential relation on bisimulation classes, without assuming exact

descent. Saturated resonance is associative if and only if this quotient relation is associative. One direction descends a saturated intermediate mode to its class; the other chooses a representative of the quotient intermediate mode. Thus mode transport is a sufficient source-level proof principle, not a necessary condition. Structural preservation, source resonance laws, and the exact quotient-associativity condition directly generate a normalized saturated dependent completion.

Associativity obstruction certificates. Failure of quotient associativity has a carrier-level certificate. A directional candidate records four values such that one parenthesization has a two-step saturated resonance chain while the opposite parenthesization has no intermediate mode. Such certificates are absent exactly when saturated resonance is associative, equivalently when the existential quotient relation is associative. On a finite carrier all candidates form a finite table and table emptiness is the exact criterion. The two-point strict-saturation model has an empty table. This first table uses classical decidability; no native enumeration or automorphism-minimized classification is claimed.

Executable associativity decision. Given exact Boolean checkers for source bisimulation and resonance, nested finite searches compute saturated modes and the two possible two-step chains. A Boolean directional checker is proved correct for obstruction certificates, and filtering all candidates produces an executable finite table. Its emptiness is equivalent to quotient associativity. For the two-point strict-saturation model, table emptiness is evaluated by `native_decide`. Automorphism-orbit and support-minimal compression remain optional optimizations, not correctness prerequisites.

Ternary interaction representation. Every small ternary relational system admits a canonical Incidence representation after freely adjoining a unit. The original carrier is the nonunit sector, and resonance on three original elements holds exactly when the source ternary relation holds. Relation-preserving maps extend functorially, and the resulting functor is faithful. Restriction back to the nonunit sector recovers the source system up to a checked isomorphism. This is a representation theorem for ternary interaction systems, not yet for arbitrary categories or dependent type theories; boundary and cell-type data are intentionally trivial in this first construction.

Small-category composition representation. For every small category, take endpoint-tagged arrows as a carrier and declare a ternary mode precisely when the first two arrows are composable and the third is their composite. This relation recognizes ordinary composition exactly, is single-valued, and satisfies relational associativity. Every functor induces a resonance-preserving map, compatibly with identity and functor composition. Applying the preceding free-unit construction gives an Incidence representation and recovers the composition system from its nonunit sector. The later recovery and scoped-fullness results strengthen this to typed categorical data and an exact morphism image. Higher categories are not covered.

Internal category recovery. The same representation also recovers the typed categorical data. Objects embed injectively as identity arrows, and the original object type is equivalent to that image. For each object pair (X, Y) , the hom type $\mathcal{C}(X, Y)$ is equivalent to the fiber of represented arrows with source X and target Y . Under these fiber equivalences, Incidence resonance holds exactly when the recovered output equals categorical composition. The bundled certificate therefore recovers objects, hom types, and composition for every small category. It uses the known identity embedding and endpoint projections; the following layers supply an intrinsic identity predicate and scoped fullness. Univalence and higher coherence are not claimed.

Intrinsic identity and object recovery. The external choice of the identity-arrow image can also be removed. Define an arrow to be intrinsically unital when its endpoints agree and it acts as a left and right unit for every endpoint-compatible arrow under the ternary composition relation. This relational predicate holds exactly for the identity arrow on its source. Hence the original object type is equivalent to the subtype of intrinsically unital arrows, and the preceding hom-fiber and composition recovery gives an intrinsic recovery certificate. Endpoint projections remain part of the predicate; the following result supplies scoped fullness. Univalence and higher coherence are not asserted.

Scoped fullness and exact functor image. The morphism-level comparison can also be made exact. A functorial category-composition homomorphism carries object and hom actions satisfying the identity and composition laws, and its resonance map is the induced map on endpoint-tagged arrows. Every such homomorphism is induced by a unique functor. Conversely, an arbitrary ternary-resonance homomorphism belongs to the functor image exactly when it admits this structure. Thus the representation is faithful and full on precisely characterized admissible morphisms. We do not claim unrestricted fullness for bare relation maps, which need not preserve endpoints or identities.

Pure relational category recovery. Endpoint projections can be removed from the recovery specification. Call an arrow a pure identity when every defined left or right composite with it is unchanged. This predicate uses only the ternary composition relation and is proved equivalent to being a categorical identity. The source identity of an arrow is then the unique pure identity whose left composite is that arrow, and the target identity is characterized dually. The original object type is equivalent to the pure-identity subtype; each hom type is equivalent to the fiber defined by these two relational endpoint predicates; and composition is recovered exactly on those fibers. This is the representation and recovery direction; the following result supplies an abstract recognition interface. It is not a univalence result.

Relational category recognition. There is also a converse construction for abstract ternary systems. Assume functionality, self-composition of pure identities, unique relational source and target identities, existence of composition exactly when the middle identity matches, stability of outer endpoints, and relational associativity. Pure identities then form the objects of a category; arrows with fixed relational endpoints form its hom types; and the unique resonant output defines composition. The category laws follow from the identity, functionality, and associativity axioms. Every small-category composition system satisfies this interface, every carrier element appears as a typed reconstructed hom, and resonance on typed homs holds exactly for reconstructed composition. We do not claim independence or minimality of these axioms, univalence, or higher coherence.

Relational category system round trip. The reconstruction is exact at the ternary-system level. Map each original carrier element to the endpoint-tagged arrow whose objects are its uniquely selected source and target identities and whose hom is the element itself; decode by taking the underlying hom value. These maps are mutually inverse, including their dependent endpoint fields. Moreover, original resonance holds exactly when the three encoded arrows satisfy reconstructed categorical composition. They therefore define an isomorphism from the original ternary system to the composition system of its reconstructed category. The proof uses classical choice for the unique endpoints and composite. It does not establish an equivalence of categories of all models and morphisms, axiom minimality, univalence, or higher coherence.

Functorial relational category reconstruction. The reconstruction also extends to morphisms. Bundle recognized ternary systems with the preceding axioms and take as morphisms

the carrier maps that preserve resonance and pure identities. These objects and morphisms form a category. Each morphism preserves relational source and target identities and therefore induces a functor between the reconstructed categories. This assignment preserves identity and composition exactly. Moreover, encoding an element before applying the induced arrow map agrees with first applying the system morphism and then encoding; decoding satisfies the dual equality. Thus the round trip is natural at the morphism level. The following result packages this assignment as one functor; a categorical equivalence is not asserted here.

Cat-valued reconstruction functor. The reconstructed category objects and reconstructed functors assemble into a single universe-explicit functor from recognized ternary systems to `mathlib`'s category `Cat`. Its object action is definitionally the category of pure identities and relational endpoint fibers, and its morphism action is the preceding reconstructed functor. The identity and composition laws are those already checked, while the capstone retains encoding naturality. We do not. The following result constructs the inverse-direction functor; natural isomorphisms of the resulting composites and a categorical equivalence are not part of this theorem.

Category recognition inverse-direction functor. Conversely, every `mathlib` `Cat` object is sent to its endpoint-tagged ternary composition system equipped with the recognition axioms, and every functor is sent to its map on tagged arrows. Functors preserve resonance and pure identities, and the induced recognized morphisms preserve identity and composition exactly. Hence these assignments form one functor from `Cat` to recognized ternary systems. Together with the preceding reconstruction functor, both directions are now packaged. The following result supplies the recognized-system-side natural isomorphism; the `Cat`-side one remains to obtain a categorical equivalence.

Recognized-system round-trip natural isomorphism. Exact relation transport shows that encoding and decoding preserve pure identities, not merely resonance. They therefore define inverse morphisms in the category of recognized systems at every object. The morphism naturality proved above assembles these component isomorphisms into a natural isomorphism from the identity functor to reconstruction followed by recognition. This is one of the two natural isomorphisms required for a categorical equivalence; the `Cat`-side round trip is supplied objectwise by the following theorem.

Category round-trip equivalence. For every small category, send an object to its pure identity arrow in the reconstructed category and send a morphism to the corresponding relational endpoint fiber. This canonical functor is faithful because tagged arrows retain their hom value. It is full because every morphism between canonical identity objects has the required original endpoints, and it is essentially surjective because every pure identity is the identity of its recovered source object. Consequently every category is equivalent to the category recovered from its ternary composition system. This is an objectwise equivalence of categories; a `Cat`-valued natural isomorphism and a single global equivalence of the two model categories are not claimed. The following theorem supplies the functor naturality of these objectwise equivalences.

Category round-trip functor naturality. For every original functor, first applying the canonical round-trip embedding and then its reconstructed functor agrees exactly with first applying the original functor and then embedding. The two paths are equal as functors, with separate checked object and dependent-hom equations. This is the naturality appropriate to the objectwise equivalences above. We retain the distinction between equivalence of categories and isomorphism in the ordinary 1-category `Cat`: a natural isomorphism in that 1-category would require strict category isomorphisms as its components.

Relational-category comparison capstone. The exact comparison level is bundled in one typed certificate: it contains both directional functors, the recognized-system natural isomorphism, the Cat-side objectwise equivalences, their canonical full, faithful, essentially surjective functors, and the exact naturality squares. This package is deliberately not labelled a 1-categorical equivalence of model categories, because isomorphism in ordinary **Cat** is stricter than equivalence of categories. A native bicategorical pseudonatural-equivalence package is a separate future strengthening.

Dependent judgment interaction representation. Fix a context of the raw dependent $\Pi/\Sigma/\text{Id}$ calculus. Tagged raw types and terms form a ternary system in which a diagonal type interaction exists exactly when the type is well formed, and a term/type interaction exists exactly when the corresponding typing judgment is inhabited. Every derivation-preserving context renaming induces a resonance homomorphism; these maps preserve identities and composition exactly. The free-unit Incidence encoding preserves both judgment relations and recovers the original ternary system after the adjoined unit is removed. This is a representation theorem for the checked raw calculus, not a completeness theorem for an internal dependent language over arbitrary **ResonanceSpec** models.

General resonance laws. A carrier-independent propositional axiom schema expresses resonance symmetry, both unit laws, and the exclusion of every type-incompatible resonance atom. An arbitrary valuation satisfies the entire schema exactly when it is a symmetric, unital, type-compatible ternary relation over the fixed incidence signature. In particular, the physical resonance valuation satisfies the schema exactly when the Incidence admits a **ResonanceSpec**. Proofs from the possibly infinite schema remain finitary: each natural-deduction derivation uses a finite context of schema instances. Such derivations are sound in every law model. This removes finite enumeration from general axiomatization and soundness; strong Kripke completeness for the infinite schema is not asserted.

General resonance-law Kripke semantics. A lawful Kripke model requires its valuation to satisfy symmetry, both unit laws, and type compatibility at every world. Each law-schema instance is forced at every such world, including all future worlds quantified by implication and negation. Consequently every finitary derivation from the full schema is Kripke-sound without enumerating the carrier. Strong completeness is proved equivalent to one explicit remaining obligation: every nonderivable formula must fail at some world of a lawful Kripke model. Thus the unchecked part is isolated as an infinite-schema canonical-countermodel construction; the manuscript does not assert that this final obligation is discharged.

Countable-schema completeness. For a resonance-atom language equipped with a countable coding, the remaining countermodel obligation is discharged. Schema-relative derivations admit finite support and form a deductively closed theory. A relative avoidance chain then constructs a prime theory containing every law instance while excluding a chosen nonderivable formula. The upper cone above this theory is a lawful canonical Kripke model: restricting to the cone preserves the truth lemma, and every world satisfies symmetry, both units, and type compatibility. Thus a formula is forced in every lawful Kripke model exactly when it is derivable from finitely many instances of the full, potentially infinite schema. This covers finite and countably infinite carriers; no enumeration-free completeness claim is made for uncountable atom languages.

Enumeration-free completeness. The countability condition can be removed by a separate Zorn argument. Consider the sets of formulas that extend an arbitrary deductively closed theory and whose finite subcontexts do not derive a chosen forbidden formula. A nonempty

inclusion chain is bounded by its union because every natural-deduction proof uses only a finite context. A maximal extension therefore exists; maximality forces deductive closure and disjunction primeness. This yields relative prime extensions and implication-failure future worlds without a formula schedule, and hence an enumeration-free canonical truth lemma. Applied to the resonance law schema, the construction provides a lawful countermodel for every nonderivable formula and proves strong Kripke completeness for arbitrary same-universe carriers. The proof is classical and uses choice; no predicative or choice-free completeness theorem is claimed.

Dependent judgment proof-theoretic semantics. The raw dependent $\Pi/\Sigma/\text{Id}$ calculus admits an explicit inference-rule model interface: formation and typing are arbitrary predicates closed under every raw constructor. Mutual induction proves soundness in every such model. The syntactic model interprets validity as nonempty derivability; it is exact, least among inference-rule models, and stable under well-typed renaming and substitution. This is a proof-theoretic term-model completeness theorem, not extensional set-valued or CwF semantics, conversion, normalization, or higher identity coherence.

Dependent contextual-category comprehension. Well-formed raw contexts are objects and extensional well-typed substitutions are morphisms. Their derivation witnesses are retained propositionally but erased from morphism equality, yielding strict identity and associativity. Raw types reindex contravariantly with exact identity and composition laws; context extension has a display projection and generic variable. A base substitution and term of the reindexed display type pair uniquely into the extension, establishing the comprehension universal property. These results provide the contextual-category comprehension core beneath the existing set-valued family semantics. A fully bundled CwF with well-formed type and term presheaves is not claimed.

Dependent type-and-term presheaves. Well-formed raw types now form an explicit contravariant reindexing family over the context category, with strict identity and composition laws. The total family of typed terms has the same laws, and its projection to the type family is natural. The precise remaining CwF obstruction is also formalized: Nat-indexed substitutions into the empty context retain unconstrained irrelevant components, so its identity and constant-unit endomorphisms are distinct. Consequently the present empty context is not terminal. A finite-context extensional quotient or normalization of irrelevant substitution components is required before claiming a full CwF.

Dependent scoped syntax. Mutual depth predicates bound every de Bruijn variable in raw types and terms. Every lookup position lies below context length, and formation and typing derivations imply the corresponding scopedness judgments. Hence substitutions that agree on the finitely many variables of a context act identically on all well-formed types and well-typed terms.

Finite-support context quotient. Quotienting substitutions by this finite agreement is compatible with composition in both arguments and produces a strict corrected context category. In that quotient every map into the empty context is equal, so the empty context is terminal and the preceding obstruction is discharged. Descending the type/term presheaves and comprehension to this quotient remains the boundary before a full CwF package.

Finite-support type and typed-term presheaves. Well-formed types and total typed terms descend to substitution classes without choosing representatives: scoped substitution congruence proves both reindexing operations well defined. Their identity and contravariant composition laws hold strictly, and the typed-term projection to types is natural.

Finite-support comprehension universality. Context extension, display projection, and the generic variable also descend. A substitution and term of the reindexed type pair into the extension; both component equations hold, and the pairing is unique. Thus terminal context, type and term reindexing, and comprehension universality coexist in the same corrected category. A conventional dependent term-fiber bundle remains packaging work before exposing a standard bundled-CwF interface.

Bundled finite syntactic category with families. Terms are finally exposed as dependent fibers of the total typed-term space over each well-formed type. These fibers reindex along quotient substitutions; identity and composition are expressed by heterogeneous equality across the propositionally equal fibers. The generic variable inhabits the exact pullback of the display type, and fiber-level pairing satisfies projection, genericity, and uniqueness. A single certificate therefore combines terminal context, type and dependent-term substitution, and split comprehension. This closes the syntactic CwF construction; comparison with the existing set-valued semantics remains a separate morphism theorem.

Completed-fragment CwF semantic comparison. Every fully coherent completed typing judgment embeds conservatively into the finite syntactic CwF: its raw context, type, and term are unchanged. The same certificate supplies the existing set-valued semantic context, type, and term, and the interpretation commutes with semantic identity substitution through the certified fiber equivalence. Semantic completion is stated as an explicit gate on raw CwF terms. We do not claim a morphism on the whole raw CwF; arbitrary-substitution and comprehension naturality and completion of every raw judgment remain separate obligations.

Completed-fragment substitution naturality. A semantic realization of a raw substitution packages source and target context interpretations, the semantic substitution, and interpretations of all replacement variables. It induces the corresponding finite-support syntactic substitution, and reindexing the embedded term is exactly raw substitution. The general mutual dispatcher proves arbitrary-substitution naturality: interpretation of the substituted term agrees with semantic substitution of the original interpretation. Global realization coverage and comprehension naturality remain explicit gates before a whole-CwF morphism can be claimed.

Completed-fragment comprehension naturality. Each completed display type selects corresponding finite-syntactic and set-valued context extensions. Given a semantically realized substitution, the same completed term determines comprehension pairings on both sides. Projection and generic-variable equations hold, and the semantic generic component equals the fiber-transported interpretation of the syntactically substituted term. Hence comprehension is preserved on the completed realized fragment. Global judgment completion and semantic-substitution coverage remain the exact gates before these comparisons assemble into a whole-CwF morphism.

Whole-CwF morphism readiness boundary. Coherent telescope synthesis canonically realizes identity substitution for every completed judgment, including all semantic lookup replacements. The local judgment, arbitrary-substitution, and comprehension comparison laws are then bundled with an exact totality boundary: a whole-CwF morphism requires precisely completion of every finite-CwF term and semantic realization of every raw substitution into a completed judgment. Neither global coverage statement is claimed here.

Completed display-projection semantics. Every completed display type canonically realizes the nonidentity raw successor-variable projection. Its semantic map is exactly the set-valued Sigma projection, every replacement is the corresponding semantic lookup weakened along that

projection, and the induced finite-support morphism is exactly the syntactic CwF display projection. Nonidentity coverage therefore includes the fundamental comprehension projection; arbitrary substitutions and global judgment completion remain open.

Semantic-substitution composition and finite functoriality. Well-typed raw substitutions compose by term substitution. Their semantic assignment maps compose as functions, while replacement interpretations compose by reindexing the later replacements along the earlier map. A realization into a fixed interpreted target context is packaged independently of any selected target term, so every completed realization is closed under precomposition by such a realization into its source. The induced finite-support morphism is exactly categorical composition in the syntactic context category. This is a closure theorem rather than a construction of realizations for all raw substitutions; arbitrary substitution coverage and global judgment completion remain open.

Completed-term semantic pairing realization. A realized base substitution and completed target term canonically determine a raw comprehension pairing into the extended context. Its semantic assignment map is the set-valued Sigma pairing, its newest replacement is the interpreted substituted term, and all older replacements are inherited from the base realization. The induced finite-support morphism is exactly the syntactic CwF pairing. This covers pairings generated by completed target terms; an arbitrary source-side head component need not be such a reindexing, so global substitution coverage is not claimed.

General source-side semantic pairing realization. The target-term restriction is removed by accepting the exact local semantic data for an arbitrary well-typed source head: a coherent target formation, its substitution fiber equivalence, and a source semantic term. Transporting that term across the equivalence extends any target-independent realized base substitution to the context extension. The semantic projection and generic equations hold, and the induced finite-support morphism is exactly the quotient-CwF pairing. Hence pairing shape is no longer an obstruction; global coverage is reduced to supplying the explicit formation and typing semantic data uniformly.

Canonical raw-substitution pairing decomposition. Every substitution into an extended target has a canonical tail and a newest component typed in the display family reindexed along that tail. Re-pairing recovers its term components exactly, its proof-erased extensional substitution exactly, and its finite-support class exactly as the CwF comprehension pairing. Raw substitutions retain proof-relevant typing derivations, so equality of the proof-relevant structures before erasure is not asserted. Together with the general semantic pairing theorem, this reduces global semantic-substitution coverage recursively to uniform formation and typing semantic data for each head component.

Recursive semantic-substitution realization induction. Semantic realization transports across changes of proof-relevant typing witnesses when the substitution term function is unchanged. Every substitution into the empty target has a canonical realization, while the extension step takes a realized canonical tail and the general formation/typing semantics of the actual source head and realizes the original substitution. This gives an exact recursive induction principle for global coverage. Uniform synthesis of the per-head semantic data remains the outstanding premise. The current basic realization record packages maps and replacement terms; a future strengthened interface should additionally internalize their lookup-by-lookup coherence, which the concrete constructors establish through their individual equations.

Intrinsic lookup-coherent semantic substitutions. The strengthened realization interface retains a target semantic tree and, for every target lookup, a fiber equivalence between the selected replacement family and the target lookup family reindexed by the semantic assignment map. It also requires equality between the transported replacement term and the reindexed target variable. Identity substitutions and completed display projections inhabit this interface with exact target-tree preservation. Strengthened pairing and composition closure remain before the recursive coverage induction can be promoted wholesale to this intrinsic interface.

Lookup-coherent closure. The *Lookup-coherent pairing and composition closure* theorem shows that target-independent realizations compose generically. Intrinsic lookup coherence is preserved under composition by reindexing each later fiber equivalence along the earlier semantic map and using transport naturality for the term equation. General source-side pairing is coherent at the newest lookup by its formation equivalence and at every older lookup by inherited base coherence. The semantic maps remain exactly function composition and Sigma pairing. Uniform synthesis of formation and typing semantics for every head is now the remaining coverage premise for substitutions.

Strengthened coherent whole-CwF readiness boundary. Fixing a completion model anchors every target to its canonically synthesized semantic context and tree. The strengthened global substitution gate requires intrinsic lookup coherence rather than only an assignment map and replacement terms. Forgetting coherence recovers the previous completed-substitution and whole-CwF readiness gates, while strengthened readiness is equivalent exactly to judgment completion conjoined with canonical coherent substitution coverage. Neither global gate is claimed; uniform judgment completion and per-head semantic synthesis remain the totality obligations.

Recursive lookup-coherent substitution induction. Transport across proof-relevant substitution witnesses with the same term function preserves both the semantic assignment map and the exact target tree. Empty targets have canonical coherent realizations, and a coherent canonical tail plus general semantic data for the actual source head realizes the original substitution with every lookup equation intact. The recursive coverage mechanism therefore lands directly in the strengthened interface; uniform formation and typing semantic synthesis for every head is its sole remaining substitution premise.

9 Mechanization and reproducibility

All results are checked with Lean 4 and mathlib v4.23.0. The main source is `IncidenceTheory/IncidenceResearch.lean`. The repository maintains:

- a completion-claim matrix mapping scoped claims to declarations;
- a 106-row Lean-to-paper theorem index whose boundaries are checked in CI;
- an axiom audit allowing only `propext`, `Classical.choice`, and `Quot.sound` in the capstone dependency closure;
- executable finite counts as independent checks of the structural proof.

The verification entry point is `./verify.sh`. Source and reproducibility metadata are available at <https://github.com/com-junkawasaki/inc>.

10 Conclusion

An incidence quotient preserves an independent ternary relation exactly when incidence bisimulation is a congruence for that relation. Beyond this standard quotient mechanism, coordinate decomposition turns failure into a finite $3n^4$ obstruction problem, and automorphism normalization exposes a concrete structural classification: 32 minimal orbits for the seven-cell simplex selector. The categorical, finite, logical, simplicial, and reaction-network instances are checked in one Lean development, with broad foundational and applied claims kept outside scope.

A Checked theorem groups

The machine-readable theorem index contains 106 groups. For readability they are summarized here; the repository’s TSV theorem index is authoritative for exact Lean declarations and hypotheses.

1–4	core structures; exact descent; uniqueness; universal factorization
5–6	natural-number obstruction; saturated-simplex positive model
7–11	finite, coordinate, swap-orbit, functional, and support-minimal classifications
12–14	transport/saturation criterion; kernel-pair and standard categorical coequalizers
15–16	geometric simplex and generic class-mode representation
17–21	free, presented, equational, logical, and reference-syntax results
22–24	congruence reflection, graded functoriality, and quotient adjunction
25–27	infinite path, bounded grading, and standard simplicial families
28–29	forgetful incidence-hypergraph encoding and reversible reaction model
30	controlled-sum quotient/image natural isomorphism
31	canonical bisimulation-congruence saturation and closure laws
32	resonance-saturation closure operator and reflection
33	global carrier-changing saturation adjunction and factorization
34	role-changing exact-boundary saturation adjunction
35	globally boundary-surjective saturation adjunction

36	carrier-and-boundary-surjective saturation adjunction
37	saturation internal-logic and translated- IncProof conservativity
38	dependent $\Pi/\Sigma/\text{Id}$ saturation conservativity
39	associative saturation and generated dependent completion
40	exact quotient-associativity criterion and completion
41	saturation-associativity obstruction certificates
42	executable associativity-obstruction decision
43	faithful and recoverable representation of ternary interaction systems
44	exact, associative representation of small-category composition
45	recovery of objects, hom fibers, and composition
46	intrinsic relational characterization of identities and objects
47	scoped fullness and exact characterization of the functor image
48	endpoint-free relational recovery of objects, homs, and composition
49	relational recognition and reconstruction of categories
50	exact ternary-system round trip through reconstructed categories
51	functorial reconstruction and morphism-level round-trip naturality
52	packaged functor from recognized ternary systems to Cat
53	inverse-direction functor from Cat to recognized systems
54	recognized-system round-trip natural isomorphism
55	full, faithful, essentially-surjective category round-trip equivalence
56	naturality of the canonical category round-trip functors
57	bundled relational-category comparison data and scope boundary
58	exact, functorial, recoverable representation of dependent judgments
59	general resonance-law axiomatization, model characterization, and soundness
60	lawful Kripke semantics, schema soundness, and the exact completeness gate
61	finite-support Lindenbaum construction and countable-schema strong completeness
62	Zorn prime extension and enumeration-free resonance-law completeness
63	dependent judgment proof-theoretic soundness and term-model completeness
64	dependent contextual category, reindexing, and comprehension universality
65	dependent type/term presheaves and the exact terminal-context residual
66	scoped dependent syntax and finite-support substitution congruence
67	finite-support context quotient and terminal empty context
68	finite-support type and typed-term presheaves
69	finite-support comprehension equations and universality
70	bundled finite syntactic category with families

71	completed-fragment CwF semantic comparison
72	completed-fragment substitution naturality
73	completed-fragment comprehension naturality
74	whole-CwF morphism readiness boundary
75	completed display-projection semantics
76	semantic-substitution composition and finite functoriality
77	completed-term semantic pairing realization
78	general source-side semantic pairing realization
79	canonical raw-substitution pairing decomposition
80	recursive semantic-substitution realization induction
81	intrinsic lookup-coherent semantic substitutions
82	lookup-coherent pairing and composition closure
83	strengthened coherent whole-CwF readiness boundary
84	recursive lookup-coherent substitution induction
85	readiness-aligned context semantic synthesis
86	exact source-head semantic coverage boundary
87	two-sided coherent semantic substitutions
88	source-head readiness and type-alignment discharge
89	global two-sided substitution realization
90	formation target-invariance boundary
91	mutual target-invariance induction motives
92	Pi/Sigma constructor target equations
93	dependent formation target packages
94	recursive Pi/Sigma target invariance
95	Identity target package and normalization boundary
96	canonical-provenance-scoped rebase
97	dispatcher-parametric target invariance
98	scoped canonical base/unit/Pi/Sigma target invariance
99	scoped typing target-invariance base and variable boundary
100	scoped Identity endpoint alignment
101	scoped Identity package equality and conditional closure
102	global scoped formation target invariance
103	scoped typing recursive normalization and Lambda boundary
104	scoped Lambda target-package invariance and conditional closure
105	scoped Refl target-package invariance and conditional closure
106	scoped Apply target package and instantiation boundary

References

- [1] J. C. Baez and B. S. Pollard. A compositional framework for reaction networks. *Rev. Math. Phys.* 29(9), 2017. doi:10.1142/S0129055X17500283.
- [2] J. C. Baez, F. Genovese, J. Master, and M. Shulman. Categories of nets. arXiv:2101.04238, 2021.
- [3] Z. Bakhtiari and H. H. Hansen. Bisimulation for weakly expressive coalgebraic modal logics. *CALCO 2017*, LIPIcs 72, 4:1–4:16.
- [4] Z. Bakhtiari, H. H. Hansen, and A. Kurz. On the logic of behavioural equivalence, 2019.
- [5] J. C. Blanchette, A. Popescu, and D. Traytel. Operations on bounded natural functors. *Archive of Formal Proofs*, 2017.
- [6] S. Burris and H. P. Sankappanavar. *A Course in Universal Algebra*. Springer, 1981.
- [7] I. Chajda and H. Länger. Quotients and homomorphisms of relational systems. *Acta Univ. Palacki. Olomuc., Fac. Rerum Nat., Math.* 49(2):37–47, 2010.
- [8] U. Dorsch, S. Milius, L. Schröder, and T. Wißmann. Efficient coalgebraic partition refinement. *CONCUR 2017*, LIPIcs 85, 32:1–32:16.
- [9] J. Grilliette and L. J. Rusnak. Incidence hypergraphs: box products and the Laplacian. arXiv:1805.07670, 2018.
- [10] M. Korolkiewicz. Many sorted quotient algebra. *Formalized Mathematics* 5(1):79–84, 1996.

- [11] S. Marić. Bisimulation quotient in inquisitive modal logic. *Logics* 3(3):11, 2025. doi:10.3390/logics3030011.
- [12] M. Novotný. Homomorphisms and strong homomorphisms of relational structures. *Archivum Mathematicum* 33(1–2):57–64, 1997.
- [13] J. J. M. M. Rutten. Universal coalgebra: a theory of systems. *Theor. Comput. Sci.* 249(1):3–80, 2000.
- [14] S. Staton. Relating coalgebraic notions of bisimulation. *Logical Methods in Computer Science* 7(1), 2011.
- [15] T. Wißmann. *Coalgebraic Semantics and Minimization in Sets and Beyond*. PhD thesis, Friedrich-Alexander-Universität Erlangen–Nürnberg, 2020.