

## SE507 $\mu$ Hacking Password Hashes with Rainbow Tables

### Quizz 3: Rainbow table

This assessment evaluates the following competencies:

- CS007 – Understand why it is important to store passwords carefully
- CS901 – Understand how passwords database can be attacked
- CS502 – Understand how rainbow table can be used to find a password given the hashed passwords database

Three affirmations are given for each assessed competency. For each of them, you have to decide whether it is true or false. To get a star for the competency, you must have the correct answer for the three affirmations.

CS007	True	False
If an attacker knows your identifier and managed to find your password (in clear), he/she can be authenticated on any website/platform where you use this (identifier, password) pair.	<input type="checkbox"/>	<input type="checkbox"/>
A longer password with a very diverse charset (character, digit, special character, etc.) is better than a short one with only digits (such as a PIN code).	<input type="checkbox"/>	<input type="checkbox"/>
Encrypting a passwords database file may slow down the account creation and login processes, but increases the security of the system in case of a theft of the passwords database.	<input type="checkbox"/>	<input type="checkbox"/>

CS901	True	False
Reversing a password that has been hashed with a salt is not impossible, but very time consuming.	<input type="checkbox"/>	<input type="checkbox"/>
Given one hashed password, I can find the corresponding clear passwords, for sure, just by enumerating all the possible passwords.	<input type="checkbox"/>	<input type="checkbox"/>
Given one hashed password, I may find the corresponding clear passwords just by enumerating all the possible passwords, but I am not sure to find it.	<input type="checkbox"/>	<input type="checkbox"/>

CS502	True	False
A rainbow table is a collection of hash chains, that is alternating sequences of clear passwords and their corresponding hashes.	<input type="checkbox"/>	<input type="checkbox"/>
A rainbow table can be used to store many (password, hash) pairs efficiently regarding memory consumption.	<input type="checkbox"/>	<input type="checkbox"/>
Given a rainbow table with 1000 chains and 1000 reduction functions, in the worst case it will take about 1000000 operations to try all the represented (password, hash) pairs.	<input type="checkbox"/>	<input type="checkbox"/>