

How to Remember and Revisit Many Genetic Design Variants Automatically



Nicholas Roehner, Douglas Densmore CIDAR Lab of Boston University

COMBINE 2016 | Sept. 19 - 23 | Newcastle Upon Tyne



Splice: Synthetic Biology Board Game








How to Encode Many Possible Designs for a 4-Gene Cluster?








How to Track Which Designs are Ruled Out as Data is Gathered?








GenBank is Not the Answer






684,544 Files Memory >6 GB




Knox Provides a Solution






Genetic Design Space Memory <200 KB



684,544 GenBank Files Memory >6 GB



What is a Genetic Design Space?




A genetic design space is a graph that encodes design rules for composing sets of genetic parts.




Each Edge is Labeled with a Set of Parts



























































































Design Spaces Can Be Combined via Graph Operations in Knox








Design Spaces Can Be Combined via Graph Operations in Knox








Design Spaces Can Be Combined via Graph Operations in Knox




















Design Space for Majority Circuit





Every Design Space in Knox has a Version History






Design Spaces

Version Histories



Every Design Space in Knox has a Version History






Design Spaces

Version Histories



Every Design Space in Knox has a Version History






Design Spaces


Version Histories



Changes to a Design Space Can Be Saved to its Version History











Changes to a Design Space Can Be Saved to its Version History










Combining Design Spaces in Knox Also Merges Version Histories











Version History for Majority Circuit





Branching a Design Space in Knox Creates Two Parallel Versions









Further Refinements Can Be Saved to Separate Branches










Further Refinements Can Be Saved to Separate Branches








Branches Can Be Recombined Using Any Operator in Knox









Previous Commits Can Be Revisited with the Revert Operator



c8 is a copy of c5m11








Knox Provides a Web-Accessible Platform to Store and Track Changes to Design Spaces







Finch vs. Eugene





Finch

- Variable design length
- More machine-comparable,
 -mergable




- Fixed design length
- More human-readable, -writable



Eugene for Two Genes






Device toggle(Promoter, CDS, Promoter, CDS);



MIT-Broad Foundry

Constrained Eugene for Two Genes



Device toggle(Promoter, CDS, Promoter, CDS);

```
Rule toggleRules (ON toggle:
ALL_FORWARD AND
tetR BEFORE pTet AND
lacI BEFORE pLac
);
```





```
Device toggle(Promoter, CDS, Promoter, CDS);

Rule toggleRules (ON toggle:
    ALL_FORWARD AND
    tetR BEFORE pTet AND
    lacI BEFORE pLac
).
```





```
Device toggle(Promoter, CDS, Promoter, CDS);

Rule toggleRules(ON toggle:
    ALL_FORWARD AND
    tetR BEFORE pTet AND
    lacI BEFORE pLac
);
```





```
Device toggle(Promoter, CDS, Promoter, CDS);

Rule toggleRules(ON toggle:
    ALL_FORWARD AND
    tetR BEFORE pTet AND
    lacI BEFORE pLac
);
```





Device toggle(Promoter, CDS, Promoter, CDS);

Rule toggleRules(ON toggle:

ALL_FORWARD AND

tetR BEFORE pTet AND
lacI BEFORE pLac
);





Device toggle(Promoter, CDS, Promoter, CDS);

Rule toggleRules(ON toggle:


ALL_FORWARD AND

tetR BEFORE pTet AND
lacI BEFORE pLac
);





Device toggle(Promoter, CDS, Promoter, CDS);







Finch Code for Two Gene Design Space

```
pTet THEN NOT tetR THEN {
        { pLac THEN NOT lacI, tetR } OR
        { NOT pLac THEN NOT tetR }
} OR {
    NOT pTet,pLac THEN cds THEN {
        { pTet THEN NOT tetR } OR
        {NOT pTet,pLac THEN cds } OR
        { pLac THEN NOT lacl }
} OR {
    pLac THEN NOT lacI THEN {
        { pTet THEN NOT lacl, tetR } OR
        { NOT pTet THEN NOT lac! }
```



Scaling for Eugene Compilation



2^R where R is number of independent precedence rules

ABC AB BC AB



Acknowledgments



BOSTON



Densmore



Prof. Douglas Prof. Swapnil Bhatia

And the CIDAR Lab





D. Benjamin Gordon



Prof. Christopher Voigt

And the Broad Institute

This research was funded by the DARPA Living foundries award HR0011-15-C-0084.





Thank You - Knox GUI in Action



