

1. 运行结果: [ PASS ] ping command

对应代码 (tests/unit/ping.tcl) :

```
1 test "ping command" {
2     set reply [redis ping]
3     assert_equal $reply "PONG"
4
5     set reply [redis ping "hello"]
6     assert_equal $reply "hello"
7 }
```

2. 运行结果: [ PASS ] set and get with string values

对应代码 (tests/unit/string.tcl) :

```
1 test "set and get with string values" {
2     redis set foo "bar"
3     assert_equal [redis get foo] "bar"
4
5     redis set empty ""
6     assert_equal [redis get empty] ""
7 }
```

3. 运行结果: [ PASS ] incr and decr numeric values

对应代码 (tests/unit/string.tcl) :

```
1 test "incr and decr numeric values" {
2     redis set counter 10
3     assert_equal [redis incr counter] 11
4     assert_equal [redis decr counter] 10
5     assert_equal [redis incrby counter 5] 15
6 }
```

4. 运行结果: [ PASS ] expire key with 1 second

对应代码 (tests/unit/expire.tcl) :

```
1 test "expire key with 1 second" {
2     redis set temp "value"
3     redis expire temp 1
4     assert_equal [redis exists temp] 1
5     after 1100
6     assert_equal [redis exists temp] 0
7 }
```

5. 运行结果: [ PASS ] lpush and lrange on list

对应代码 (tests/unit/list.tcl) :

```

1 test "lpush and lrange on list" {
2     redis del mylist
3     redis lpush mylist "a"
4     redis lpush mylist "b"
5     assert_equal [redis lrange mylist 0 -1] {b a}
6 }

```

6. 运行结果: [ PASS ] hset and hget on hash

对应代码 (tests/unit/hash.tcl) :

```

1 test "hset and hget on hash" {
2     redis hset user:1 name "alice"
3     redis hset user:1 age "30"
4     assert_equal [redis hget user:1 name] "alice"
5     assert_equal [redis hgetall user:1] {name alice age 30}
6 }

```

7. 运行结果: [ PASS ] sadd and smembers on set

对应代码 (tests/unit/set.tcl) :

```

1 test "sadd and smembers on set" {
2     redis sadd fruits "apple"
3     redis sadd fruits "banana"
4     set members [redis smembers fruits]
5     assert_equal [lsort $members] {apple banana}
6 }

```

8. 运行结果: [ PASS ] zadd and zrange on sorted set

对应代码 (tests/unit/sorted\_set.tcl) :

```

1 test "zadd and zrange on sorted set" {
2     redis zadd scores 100 "alice"
3     redis zadd scores 90 "bob"
4     assert_equal [redis zrange scores 0 -1 withscores] {bob 90 alice 100}
5 }

```

9. 运行结果: [ PASS ] basic transaction with MULTI/EXEC

对应代码 (tests/unit/transactions.tcl) :

```

1 test "basic transaction with MULTI/EXEC" {
2     redis multi
3     redis set a 1
4     redis set b 2
5     set replies [redis exec]
6     assert_equal $replies {OK OK}
7     assert_equal [redis get a] "1"
8     assert_equal [redis get b] "2"
9 }

```

10. 运行结果: [ PASS ] publish and subscribe to channel

对应代码 (tests/unit/pubsub.tcl) :

```
1 test "publish and subscribe to channel" {
2     set subscriber [redis_client]
3     $subscriber subscribe testchan
4     after 100 ;# wait for subscription to take effect
5
6     set count [redis publish testchan "hello"]
7     assert_equal $count 1
8
9     set msg [$subscriber read]
10    assert_equal $msg [list message testchan "hello"]
11
12    $subscriber close
13 }
```