CHAPTER 1

VISUAL PERCEPTION AND IMAGE REPRESENTATION

Slides courtesy of Prof. Soo-Jin Lee, Paichai Univ.

Visual Perception

- The Human Visual System (HVS)
  - Vision is our most powerful sense
  - Enables us to gather information and learn through observation
  - Allows to interact with the environment without any physical contact
  - HVS consists of two primary components
    - The eye (receiving sensor)
    - The brain (processor)
      Both are connected by the optic nerve



Visual Perception

How are images converted into information by the viewer?

- Understanding visual perception helps designing image processing algorithms.
- Image data represents physical quantities, e.g. chromaticity and luminance.
- Chromaticity: color quality of light defined by its wavelength.
- Luminance: amount of light

125 million rods
7 million cones



Cross section of working eyeball

Visual Perception

- Rods
  - Intensity only
  - Essentially night vision and peripheral vision only



- Cones
  - Concentrated in the center of the retina in an area called the fovea.
  - Detect color and fine detail
  - Three types perceive different portions of the visible light spectrum



Newton's Prism Experiment - 1666





Color: visible range of the electromagnetic spectrum



Absorption of light in the cones of the human retina



Visual Perception

- Three variables for color image perception:
  - Hue
  - Saturation
  - Lightness



Visual Perception

- Hue



Visual Perception

- Saturation



Visual Perception

- Lightness



Visual Perception

- Contrast
  The range from the darkest regions of the image to the light regions.

$$contrast = \frac{I_{\max} - I_{\min}}{I_{\max} + I_{\min}}$$

I_{max} , I_{min} : maximum, minimum intensities of a region or image



Visual Perception

- Simultaneous Contrast

A phenomenon of the human visual system that causes perceived brightness to be dependent not only on the brightness levels, but also on brightness levels of the adjacent areas



Circle = 127, background =0 | Circle = 127, background =64 | Circle = 127, background =150 | Circle = 127, background =180

All the inner circles have the same intensity, but they appear progressively darker as the background becomes lighter.

Visual Perception

- The Mach Band Effect

  The response of our visual system to an abrupt change in luminance tends to emphasize the edge.



Image Formation

- Light source (λ: wavelength of the source)
  - $E(x,y,z,\lambda)$: incident light on a point (x,y,z)
- Each point of the scene has a reflectivity function
  - $r(x,y,z,\lambda)$: reflectivity function
- Light reflects from a point and the reflected light is captured by an imaging device
  - $C(x,y,z,\lambda)=E(x,y,z,\lambda)*r(x,y,z,\lambda)$: reflected light





a
b c d e

FIGURE 2.15 An example of the digital image acquisition process. (a) Energy ("illumination") source. (b) An element of a scene. (c) Imaging system. (d) Projection of the scene onto the image plane. (e) Digitized image.

a b
c d

FIGURE 2.16
Generating a digital image. (a) Continuous image. (b) A scan line from *A* to *B* in the continuous image, used to illustrate the concepts of sampling and quantization. (c) Sampling and quantization. (d) Digital scan line.





a b

FIGURE 2.17 (a) Continuos image projected onto a sensor array. (b) Result of image sampling and quantization.

a
b c

FIGURE 2.18
(a) Image plotted as a surface.
(b) Image displayed as a visual intensity array.
(c) Image shown as a 2-D numerical array (0, .5, and 1 represent black, gray, and white, respectively).



Spatial and Gray-Level Resolution

- Spatial resolution
  - A measure of the smallest discernible detail in an image
  - Stated with *line pairs per unit distance, dots (pixels) per unit distance, dots per inch (dpi)*
- Intensity resolution
  - The smallest discernible change in intensity level
  - Stated with *8 bits, 12 bits, 16 bits, etc.*



FIGURE 2.19 A 1024 × 1024, 8-bit image subsampled down to size 32 × 32 pixels. The number of allowable gray levels was kept at 256.

a b c
d e f

FIGURE 2.20 (a) 1024×1024, 8-bit image. (b) 512×512 image resampled into 1024×1024 pixels by row and column duplication. (c) through (f) 256×256, 128×128, 64×64, and 32×32 images resampled into 1024×1024 pixels.

Image Formation

- Visible light is a form of ElectroMagnetic (EM) radiation, with λ at 350nm to 750nm.



Two Types of Light Source

- Primary Light
  - Emits the EM wave (sun, light bulb, etc.)
  - Folllows the additive law
  - Primary colors: Red/Green/Blue



- Secondary Light
  - Reflects an incident light (dye, object, etc.)
  - Follows the subtractive law
  - Primary colors: Cyan/Magenta/Yellow



Image Representation





Grayscale Images

- The intensity value of each pixel is 0 ~ 255.
- Matrix representation of 2-D image:

The Lena Picture

$$F = \begin{bmatrix} 142 & 139 & \cdots & 192 & 213 \\ 146 & 137 & \cdots & 187 & 205 \\ \vdots & \vdots & \ddots & \vdots & \vdots \\ 94 & 93 & \cdots & 84 & 89 \\ 87 & 89 & \cdots & 79 & 82 \end{bmatrix}$$

Binary vs. Grayscale Images

- Binary images use only 2 levels (0 or 1)
- Grayscale images use 256 (=2^8) gray levels (0 to 255)



Binary Image

Grayscale Image

Color Images

- Generating RGB Images

a
b

(a) Generating the RGB image of the cross-sectional color plane (127, G, B).
(b) The three hidden surface planes in the color cube of Fig. 6.8.



Color Images

a b
c d

(a) RGB image.
(b) Red component image.
(c) Green component.
(d) Blue component.

Color Representation

- Different image processing systems use different color models for different reasons.

- Human perception of color is a function of the response of three types of cones.

- Color systems are based on three numbers (tristimulus values).

- Color Models
  - RGB: CRT monitors and most computer graphics systems
  - CMY: color picture publishing industry
  - HSI: systems requiring manipulations of Hue/Saturation/Intensity separately
  - YC_bC_r: systems needed to separate the luminance from the color information

Color Representation

- RGB Model





- RGB to Grayscale Conversion
  - NTSC standard: 0.299R + 0.587G + 0.114B
  - Simple average: 0.333R + 0.333G + 0.333B



Color Representation

- CMY Model
  - Consists of cyan, magenta, and yellow.
  - Cyan, magenta, and yellow are the complements of red, green, and blue, respectively.
  - To go from RGB to CMY, subtract the complement from white:
    - C=1.0-R (R=1.0-C) (in a 24-bit color system, C=255-R)
    - M=1.0-G (G=1.0-M)
    - Y=1.0-B (B=1.0-Y)
- CMYK Model
  - Black (K) is added in the printing process : CMYK=CMY+K
  - Pure black provides greater contrast.
  - CMY to CMYK conversion:
    - K=min(C,M,Y)
    - C=C-K
    - M=M-K
    - Y=Y-K



Color Representation



FIGURE 6.36 Color balancing corrections for CMYK color images.

Color Representation

- HSI Mode
- (Hue), (Saturation), (Intensity)



Color Representation

- HSI Model (continued)
  - To produce a color, simply adjust the hue. (angle H)
  - To make it deeper or shallower, adjust the saturation. (radius S)
  - To make it darker or lighter, adjust the intensity. (vertical axis I)



Color Representation

- RGB vs. HSI



RGB 24-bit color cube.



a b c

HSI components of the image in Fig. 6.8. (a) Hue, (b) saturation, and (c) intensity images.

Color Representation

- RGB vs. HSI



a b
c d

(a) RGB image and the components of its corresponding HSI image: (b) hue, (c) saturation, and (d) intensity.

Color Representation

- RGB vs. HSI



a b
c d

(a)–(c) Modified HSI component images. (d) Resulting RGB image. (See Fig. 6.16 for the original HSI images.)

Color Representation



a b c

HSI components of the RGB color image in Fig. 6.38(a). (a) Hue. (b) Saturation. (c) Intensity.

Color Representation

- YC_bC_r Mode
  - Another color space that separates the luminance from the color information.
  - The luminance is encoded in Y and the blueness and redness encoded in C_bC_r.

  - Conversion from RGB to YCbCr:

$$Y = 0.29900R + 0.58700G + 0.11400B$$
$$Cb = -0.16874R - 0.33126G + 0.50000B$$
$$Cr = 0.50000R - 0.41869G - 0.08131B$$

  - Conversion from YCbCr to RGB:

$$R = 1.00000Y + 1.40200Cr$$
$$G = 1.00000Y - 0.34414Cb - 0.71414Cr$$
$$B = 1.00000Y + 1.77200Cb$$

Color Representation

A full-color image and its various color-space components.