



POLITECNICO
MILANO 1863

AIRLAB
ARTIFICIAL INTELLIGENCE AND ROBOTICS LAB

Fuzzy Rules Introduction

Andrea Bonarini
andrea.bonarini@polimi.it

*Artificial Intelligence and Robotics Lab
Dipartimento di Elettronica, Informazione e Bioingegneria
Politecnico di Milano*

What is an inference rule?

We can consider an inference rule as a model, a way to define a mapping from input to output.

Rules are used to represent inferential relationships among pieces of knowledge.

We consider *forward chaining rules*, having the shape

IF <antecedent> THEN <consequent>

where:

- <antecedent> is a set of <clause>s related by logical operators AND, OR, NOT
- <consequent> is a set of <clause>s related by the logical operators AND, OR, NOT
- <clause>, in general, is either a <proposition>, i.e., a sequence of symbols, or a <pattern>, i.e., a sequence of symbols and variables

What are rules for?

Inference rules are used to implement Knowledge-Based Systems, among which Expert Systems are mostly known as successful AI applications, e.g. for diagnosis, forecast, design, control, classification, planning, etc.

An Expert System is designed upon the experience of somebody to replicate, or improve her/his performance in solving a problem.

Knowledge Acquisition is a complex process bringing to the definition of rule-based systems, implemented and running on computers.

How can rules be used in a computer?

Pattern matching: identify the rules whose antecedents match the known facts (fact base). These can be considered for activation, given the corresponding assignment to variables.

Selection of the rule(s) to be activated: among the rules identified with pattern matching (candidate rules), select the rules that should be activated, i.e., whose consequents have to be asserted as new knowledge in the fact base.

Activation of the selected rules: assert the consequents of the selected rules in the fact base.

With this, rules and information (i.e., knowledge) a system can **generate** new information.

Inference rules example (from Wikipedia)

Suppose that the *rule base* contains the following four rules:

1. **If** X croaks and X eats flies - **Then** X is a frog
2. **If** X chirps and X sings - **Then** X is a canary
3. **If** X is a frog - **Then** X is green
4. **If** X is a canary - **Then** X is yellow

Suppose to observe the following facts (*fact base*):

- a. Fritz croaks
- b. Fritz eats flies

From rule 1 and facts a and b we can add to the fact base the fact

Given the new fact base, we can use rule 3 to deduce the fact

c. Fritz is a frog.

d. Fritz is green.

What is a fuzzy rule?

A fuzzy rule is a rule whose clauses have the shape

$$(V \text{ is } L)$$

where V is a linguistic variable and L is a label, a value for V associated to a fuzzy set. This is a linguistic clause.

Often, clauses in the antecedent are only related by the AND operator which is not explicitly written.

The antecedent is usually matched against facts that are represented as values of the base variables corresponding to the linguistic variables.

The consequent may be one of two types ...

Linguistic rules

Linguistic rules (Mamdani): the consequent is a conjunction of linguistic clauses

IF (A is LA_i) AND (B is LB_k) AND... THEN (U is LU_m) AND ...

E.g.:

IF (Distance is Far) AND (BallDirection is Front)
THEN (Speed is High) AND (Direction is Ahead)

This can be considered as a mapping between
the interpretation of an input configuration
and
a symbolic description of the desired output

Model rules

Model rules (Sugeno, or Takagi-Sugeno-Kosko TSK): bind a model (linear, non linear, NN, ...) to the linguistic interpretation of its applicability conditions

IF (A is LAn) AND (B is LBk) AND... THEN U is $f(A, B)$


E.g.:

IF (Temperature is High) AND (Pressure is High)
THEN Heating = $2000 - 3T - 7P$

This can be considered as a mapping between
the interpretation of an input configuration (the applicability condition of a model)
and
a model to be applied to the input real values to obtain the output


How to use fuzzy rules (Mamdani): input and output

Two input variables: A and B, frame of cognition with equally distributed fuzzy sets (fuzzy partition), from Negative large (NL) to Positive Large (PL).



One output variable: U, frame of cognition with equally distributed fuzzy sets (fuzzy partition), from Negative large (NL) to Positive Large (PL).

The fuzzy sets are all singletons, because this makes the computation faster, does not affect the possibility to obtain values in the full range of the output variable, and other reasons defined later.



How to use fuzzy rules (Mamdani): the rules for the example

Usually, we have rules for all the combinations of the possible input values. Here there only 3 rules of the rule base are reported.

The designer can also associate weights to rules, to define the relative relevance of their contribution to the final result.

R1: if A is PL and B is PS Then X is PM
weight 1


R2: if A is PM and B is PS Then X is PS
weight 0.5

R3: if A is PL and B is PM Then X is PM
weight 1


How to use fuzzy rules (Mamdani): the steps

- Input matching
- Combination of matching degrees
- Combination with rule weight, if present
- Aggregation of output from different rules
- Eventual defuzzification of output

Input matching



Input



R1: IF (A is PL) (B is PS) THEN (X is PM)
0.2 0.6

R2: IF (A is PM) (B is PS) THEN (X is PS)
0.8 0.6

R3: IF (A is PM) (B is PM) THEN (X is PM)
0.8 0.4

Combination of matching degrees in the antecedent

R1: IF (A is PL) (B is PS) THEN (X is PM)

$$\begin{array}{cc} 0.2 & 0.6 \\ \underbrace{\hspace{1.5cm}} & \\ 0.2 & \end{array}$$

R2: IF (A is PM) (B is PS) THEN (X is PS)

$$\begin{array}{cc} 0.8 & 0.6 \\ \underbrace{\hspace{1.5cm}} & \\ 0.6 & \end{array}$$

R3: IF (A is PM) (B is PM) THEN (X is PM)

$$\begin{array}{cc} 0.8 & 0.4 \\ \underbrace{\hspace{1.5cm}} & \\ 0.4 & \end{array}$$

We use the **min** operator

The matching degree of the antecedent is a measure of how much the rule fits the current situation


Combination with the rule weight

R1: IF (A is PL) (B is PS) THEN (X is PM)



We use the **min** operator

R2: IF (A is PM) (B is PS) THEN (X is PS)




R3: IF (A is PM) (B is PM) THEN (X is PM)




The resulting value is a measure of how much the rule is “good” given the situation and “per se”

Output aggregation

We use the operator **max** to aggregate weights given to the same output value




The final weights give the level of cut of the output fuzzy sets



(Eventual) defuzzification

The output is given by the fuzzy set composed by the two fuzzy sets identified by the rules, cut at the level provided by the computed weights.

If we would like to have a number, as needed by many applications, we have to defuzzify the result.



$$(10 \cdot 0.5 + 20 \cdot 0.4) / (0.5 + 0.4) = \mathbf{14.44}$$

We use the operator
“weighted media” on the
weights of the output
values to obtain a
numerical value

Defuzzification

Also for the defuzzification we have many possible operators

Centroid

Bisector



Average of maxima

Lowest maximum

Highest maximum

Center of the highest area


...



Another possible output: linguistic approximation

X is PM with weight 0.4

X is PS with weight 0.5



$$(10 \cdot 0.5 + 20 \cdot 0.4) / (0.5 + 0.4) = \mathbf{14.44}$$

In this case, we would like to have the name of a fuzzy set as an output, e.g. because it corresponds to a decision to take.

The fuzzy set closer to the output is selected.


How to use fuzzy rules (Sugeno)

Let's consider the following fuzzy rules. Inputs are like in the Mamdani example

R1: if A is PL and B is PS Then X is $A+2B$

R2: if A is PM and B is PS Then X is $A + 3$

R3: if A is PL and B is PM Then X is $A+B$



The first steps are like
in the other example

Output aggregation

R1: if (A is PL) (B is PS) Then (X is A+2B)

0.2

R2: if (A is PM) (B is PS) Then (X is A+3)

0.5

R3: if (A is PL) (B is PM) Then (X is A+B)

0.4

The output is a weighted combination of the models defined in the output of the rules matching the inputs, by using the computed weights

$$X \text{ is } (0.2*(A+2B)+0.5*(A+3)+0.4*(A+B))/(0.2+0.5+0.4)$$

Since A=22 and B=140 then X=125.18

Some exercises

Define the rules to control the light in your room according to the external light coming from a window

Define the rules to decide what to do when you see a large, bad-looking dog on your way

What to remember from these slides?

- Definition of fuzzy rule
- Computation of output from inputs through fuzzy rules
- Defuzzification
- Role of operators