

System headers

```
#include <iostream>           //For cin & cout
#include <vector>              //For vector
#include <list>                //For list
#include <memory>              //For shared_ptr
#include <thread>              //For thread
#include <mutex>               //For mutex and unique_lock
#include <condition_variable> //For condition_variable
#include <functional>          //For bind/function

using namespace std; //Standard classes are in namespace std
```

Memory allocation

```
void allocTest() {
    int *intOnTheHeap=new int;
    delete intOnTheHeap;

    int *intArrayOnTheHeap=new int[10];
    delete[] intArrayOnTheHeap;
}
```

Classes

//Class definition, ususally in a .h header file

```
class TestClass
{
public:
    TestClass();
    TestClass(const TestClass& other);
    TestClass& operator= (const TestClass& other);
    ~TestClass();

    void set(int i) {
        //Short member functions can be declared inside class as a convenience
        this->i=i; //Note that this is a pointer
    }

    int get() const;
private:
    int i;
}; //Note the ; at the end
```

//Class implementation, usually in the corresponding .cpp source file

```
TestClass::TestClass() : i(0) {
    cout<<"Constructor called"<<endl;
}

TestClass::TestClass(const TestClass& other) {
    //Copy constructor, the default implementation would have done the same thing
    i=other.i;
}

TestClass& TestClass::operator= (const TestClass& other) {
    //Operator=, the default implementation would have done the same thing
    i=other.i;
    return *this; //By convention operator= always return a reference to this
}

TestClass::~~TestClass() {
    cout<<"Destructor called"<<endl;
}

int TestClass::get() const { //Note that const is part of the function signature
    return i;
}
```

Templates

```
//Template function, need to go in header file, as the compiler needs to see the entire
//function body to specialize the template
template<typename T>
T duplicate(T param) {
    return param*2;
}

//Calling template function
void testTemplate() {
    cout<<duplicate(2)<<endl;    //T=int
    cout<<duplicate(2.5)<<endl; //T=double
}

//Template class, goes in .h header file
template<typename T>
class TemplateClass
{
public:
    void set(const T& data);
    T get() const {
        //Short member functions can be declared inside class as a convenience
        return data;
    }
private:
    T data;
};

//Non inline template member functions, still need to go in header file
template<typename T>
void TemplateClass<T>::set(const T& data) {
    this->data=data;
}

//Calling template class
void testTemplate2() {
    TemplateClass<string> ts;
    TemplateClass<int> ti;
    ts.set("hello");
    ti.set(2);
}
```

STL

```
void testVector() {
    vector<int> vi1;           //Empty vector
    vector<int> vi2={1,2,3};  //Pre-initialized vector

    vi2.push_back(4);         //Adding elements (to the end)

    cout<<vi2[2]<<endl;        //Random access (without baound checking)
    cout<<vi2.at(10)<<endl;    //Random access (bound checked), throws exception

    vector<int>::iterator it; //Iterating with iterator
    //Note the != in the end condition, NEVER use < with iterators
    for(it=vi2.begin();it!=vi2.end();++it) {
        int number=*it; //Dereference iterator to get the element
        cout<<number<<endl;
    }

    //Iterating with random access
    for(int i=0;i<vi2.size();i++) cout<<vi2[i]<<endl;

    cout<<vi2.front()<<endl; //Quick access to first element
    cout<<vi2.back()<<endl;  //Quick access to last element

    vi2.pop_back(); //Erasing elements (from the end), element is NOT returned
}
```

```

void testList()
{
    list<int> li1;           //Empty list
    list<int> li2={1,3,4}; //Pre-initialized list

    li2.push_back(5); //Adding elements (to the end)
    li2.push_front(0); //Adding elements (at the beginning)

    list<int>::iterator it=li2.begin(); //it points to 0
    it++;                               //it points to 1
    it++;                               //it points to 3
    li2.insert(it,2); //insert element before current iterator position

    //List has NO random access, only iterators
    //Note the != in the end condition, NEVER use < with iterators
    for(it=li2.begin();it!=li2.end();++it) {
        int number=*it; //Dereference iterator to get the element
        cout<<number<<endl;
    }

    cout<<li2.front()<<endl; //Quick access to first element
    cout<<li2.back()<<endl;  //Quick access to last element

    li2.pop_front(); //Erasing elements (from the beginning), element is NOT returned
    li2.pop_back();  //Erasing elements (from the end), element is NOT returned
}

```

Smart pointers

```

void testSharedPtr() {
    //Works, but long to write
    shared_ptr<string> ptr1=make_shared<string>("hello world");

    //using C++11 auto keyword
    auto ptr2=make_shared<string>("hello world");
}

```

Threads

```

void threadFunc(int i) {
    cout<<"Inside a new thread "<<i<<endl;
}

void createThread() {
    thread t(threadFunc,10);
    t.join();
}

```

Mutex

```

mutex myMutex;

void criticalSection() {
    //Here the mutex is not locked
    {
        unique_lock<mutex> lock(myMutex);
        //Here the mutex is locked
    }
    //Here the mutex is not locked
}

```

Condition variable

```

condition_variable myCv;

void testConditionVariableWait() {
    unique_lock<mutex> lock(myMutex);
    myCv.wait(lock);
}

```

```

void testConditionVariableNotify() {
    unique_lock<mutex> lock(myMutex);
    myCv.notify_one(); //Wakes only one of the waiting threads (if any)
    myCv.notify_all(); //Wakes all the waiting threads (if any)
}

```

Bind/function

```

void printNumber(int i, int j, int k) {
    cout<<"i="<<i<<" j="<<j<<" k="<<k<<endl;
}

```

```

void testBind() {
    //Binding all parameters of original function leaves a function without arguments
    function<void ()> fn1=bind(&printNumber,1,2,3);
    fn1(); //prints i=1 j=2 k=3

    //Binding all parameters of original function but the last, which is taken
    //from the first parameter of the resulting function
    function<void (int)> fn2=bind(&printNumber,1,2,placeholders::_1);
    fn2(4); //prints i=1 j=2 k=4

    //Binding:
    //1 to first parameter of original function,
    //the first and second parameter of the resulting function, swapped, to the
    //other two parameters of the original function
    //ignoring the third parameter of the resulting function
    function<void (int,int,int)>
    fn3=bind(&printNumber,1,placeholders::_2,placeholders::_1);
    fn3(2,3,4); //prints i=1 j=3 k=2
}

```

Processes

```

#include <sys/types.h>           //For pid_t
#include <unistd.h>              //For fork, exec*, pipe
#include <signal.h>              //For kill
#include <sys/wait.h>            //For wait, waitpid
#include <sys/stat.h>            //For mkfifo
#include <sys/mman.h>            //For shm_open, mmap
#include <semaphore.h>           //For sem_* functions

pid_t fork(void);
pid_t wait(int *status);
pid_t waitpid(pid_t pid, int *status, int options);
int execl(const char *path, const char *arg, ...);
int execvp(const char *file, const char *arg, ...);
int execle(const char *path, const char *arg, ..., char * const envp[]);
int execv(const char *path, char *const argv[]);
int execvp(const char *file, char *const argv[]);
int kill(pid_t pid, int sig);
struct sigaction {
    void (*sa_handler)(int);
    //[...]
};
int sigaction(int signum, const struct sigaction *act, struct sigaction *oldact);
int pipe(int pipefd[2]);
int mkfifo(const char *pathname, mode_t mode);
int shm_open(const char *name, int oflag, mode_t mode);
int shm_unlink(const char *name);
void *mmap(void *addr, size_t length, int prot, int flags, int fd, off_t offset);
int munmap(void *addr, size_t length);
sem_t *sem_open(const char *name, int oflag, mode_t mode, unsigned int value);
int sem_wait(sem_t *sem);
int sem_post(sem_t *sem);
int sem_close(sem_t *sem);
int sem_unlink(const char *name);

```