

The Engineering Guide to Machine Learning & Artificial Intelligence

Daniël Heres
Version 0.1

May 27, 2019

Contents

1	Introduction	3
2	Data Collection	4
2.1	Labeling	4
2.2	Labeling Platforms	4
2.3	Labeling by Customers	5
2.4	Bootstrapping	5
3	Learning and modeling	6
3.1	Train, validate, test	6
3.2	Cross-validation	6
3.3	Raw Feature Models	6
3.4	Image Models	6
3.5	Text Models	6
3.6	Sequence Models	6
3.7	Search & Ranking	6
3.8	Clustering	6
3.9	Anomaly Detection	6
4	Feature Engineering	7
4.1	Normalization	7
4.2	Cyclical Features	7
4.3	Categorical Embeddings	8
4.4	Thermometer Encoding	8
4.5	Positional Encoding	9
5	Version Control for Data, Models and Experiments	10
6	Data Augmentation	11
7	Feature Databases	12
8	Metrics	13
8.1	Mean Opinion Score	13

9	Optimization	14
9.1	Stochastic Gradient Descent	14
9.1.1	Stochastic Gradient Descent with momentum	14
9.1.2	Adam	14
9.2	Evolutionary Algorithms	14
9.3	Bayesian Optimization	14
10	Hyperparameter Optimization	15
10.1	Neural Architecture Search	15
11	Complexity and Maintainability in Machine Learning	16
11.1	Feature Selection	16
11.2	Ablation Studies	16
11.3	Expressiveness	16
11.4	Don't Repeat Yourself	16
11.5	Feature Store	16
11.6	Data Recency	17
11.7	Numerical Libraries and Frameworks	17
11.8	TensorFlow	17
11.9	PyTorch	17
11.10	MxNet	17
11.11	Scikit-learn	17
11.12	NumPy	17
11.13	Keras	17
11.14	XGBoost	17
11.15	LightGBM	17
11.16	FastAI	17
12	Machine Learning on Big Data	18
12.1	Multi machine Learning	18
12.2	Distributed Machine Learning	18
12.3	Data Formats	18
13	Productionizing Models	19
13.1	Model Formats	19
13.2	Serving Models	19
14	Hardware for Machine Learning	20
14.1	GPU	20
14.2	TPU	20
14.3	CPU	20
14.4	Mobile Devices	20
14.5	Future Hardware	20
15	Automated Machine Learning	21
16	Reinforcement Learning	22

Chapter 1

Introduction

What are the factors that makes Machine Learning projects successful? What should you focus on and what can be solved by tools? How do we bring models into production? Which skills do I need to develop to become productive? How do we tune models? How can we maintain models over time and understand the real time impact? How can we maintain and improve a model over time?

Machine Learning, being a relatively new field in industry, has many of these questions still open. Where more older profession in technology, such as Software Engineering, has developed lots of tools, patterns and ideas around it, in Machine Learning things are much more evolving and open. Also, as the field moves very fast, tools and ideas can become quickly outdated.

In this document I give an introduction into how to apply Machine Learning in practical settings. It is by no means complete or finished, and will need to be updated to stay actual.

In this guide we focus on the engineering side of machine learning, answering questions like these. I distill patterns that can be applied to the development cycle and the design and use of popular machine learning tools.

Chapter 2

Data Collection

2.1 Labeling

Currently, the collection of labeled data is an important part of the machine learning practice.

Today's algorithms often need both data of a certain quality (e.g. should be very similar to the) and a certain quantity (the best algorithms need ≥ 1 million samples).

Even though in Machine Learning research approaches such as Transfer Learning and Self-supervised Learning reduce the need for labeled data, the need for large labeled data sets for accurate models is still big.

There are a couple of approaches towards collecting labeled data.

- **Automated.** This can be the case whenever there is existing historical data available, e.g. the number of page views at a certain day or the number of times a certain hashtag is used on Twitter. Although humans are part of the process, we don't need to manually collect the labels.
- **Semi-automated.** A human will provide feedback to a system's automatic suggestions. This example can then be used to improve the model's predictive performance and/or for measuring the performance. Sometimes labels can be collected without explicitly labeling
- **Manual:** Humans will completely label every example without the help of a computer.

2.2 Labeling Platforms

To collect labeled data, there are platforms and ecosystems. One of the biggest platform is Amazon Mechanical Turk <https://mturk.com>. This platform

2.3 Labeling by Customers

A common strategy used by companies is to use an existing product to collect labels from customers, instead of paying per label.

This way, we can vastly expand our labeled data, and improve our existing labeled data by finding consensus in labeling with minimal cost.

2.4 Bootstrapping

Chapter 3

Learning and modeling

Currently, the most successful and accurate models are using Supervised Learning. This means that a model is learned, from scratch, on a set of labeled data.

In this chapter we give some examples of commonly used models and how they work.

3.1 Train, validate, test

3.2 Cross-validation

3.3 Raw Feature Models

3.4 Image Models

3.5 Text Models

3.6 Sequence Models

3.7 Search & Ranking

3.8 Clustering

3.9 Anomaly Detection

Chapter 4

Feature Engineering

Although we are moving more and more towards the fully automatic learning. Especially with numerical data (such as financial, sales-numbers, etc) feature engineering is an crucial part of models.

4.1 Normalization

Normalization is an important part of making features. Lots of algorithms such as neural networks work better when features are normalized.

For neural networks, the most important property of features is that the range of different features should be similar.

One basic way for normalization is to transform the features to have unit zero mean:

$$z = (x - \mu) / \sigma \tag{4.1}$$

Depending on the distribution of data, we need different ways of transformation. E.g. for a variable that is more exponential in nature, using a logarithm to transform it back. to a more linear distribution helps to make it a more useful feature to learning algorithms.

Similarly, if the data you have is quadratical, then taking the square root of the variable helps algorithms.

4.2 Cyclical Features

Cyclical features are very common in data involving time: we have often access to a timestamp or a day variable. Often there is a periodic pattern in this data. We want to use the fact that two times are similar when they are close to each other. E.g. 11:59 PM is very close to 00:00 AM. However, naively using the minutes since 00:00 AM as feature will have those features maximally apart!

One good way of using the time as a feature is to project them on a circle using sine and cosine.

If we have a (Unix) timestamp variable with the number of seconds, projecting it to a circle for minutes in an hour, hours in a day, and days in a week is easy:

$$\begin{aligned}
 min_{sin} &= \sin\left(\frac{t \cdot 2\pi}{3600}\right) \\
 min_{cos} &= \cos\left(\frac{t \cdot 2\pi}{3600}\right) \\
 hour_{sin} &= \sin\left(\frac{t \cdot 2\pi}{24 \cdot 3600}\right) \\
 hour_{cos} &= \cos\left(\frac{t \cdot 2\pi}{24 \cdot 3600}\right) \\
 day_{sin} &= \sin\left(\frac{t \cdot 2\pi}{24 \cdot 3600 \cdot 7}\right) \\
 day_{cos} &= \cos\left(\frac{t \cdot 2\pi}{24 \cdot 3600 \cdot 7}\right)
 \end{aligned} \tag{4.2}$$

We can do the same for yearly patterns, but the usefulness will depend on how many years of data you have.

4.3 Categorical Embeddings

If you have categorical variables. One basic way is to use One Hot Encoding.

Some examples of categories are

- Shoe color
-

4.4 Thermometer Encoding

When we have a feature bounded between two numbers we can. However, for example in neural networks, the way we use this feature will be linear. The idea of thermometer encoding is to transform one feature into n features, where each feature will be active at a certain threshold where each feature holds roughly the same amount of data points.

For example, when we have a variable from 0 to 10 and we want to transform it to a thermometer using stepsize of 1, the thresholds are at the values 0, 1, 2, 3, 4, 5, 6, 7, 8, 9.

Between the buckets, we like to interpolate the val

A value 8.5 can be visualized as this "thermometer":

An implementation in NumPy:



Figure 4.1: Thermometer 8.5/10

```
import numpy as np

def thermometer(x, start, end, step_size=1):
    rs = np.arange(start, end, step_size)
    therm = (x > rs).astype(float)
    m = np.fmod(x, step_size)
    therm[:, ((x - start) // step_size).astype(int)] = m
    return therm
```

This function gives the desired result:

```
>>> thermometer(np.array([[8.5]]), 0, 10)
array([[1. , 1. , 1. , 1. , 1. , 1. , 1. , 1. , 0.5, 0. ]])
```

4.5 Positional Encoding

Chapter 5

Version Control for Data, Models and Experiments

Chapter 6

Data Augmentation

Chapter 7

Feature Databases

Chapter 8

Metrics

8.1 Mean Opinion Score

Chapter 9

Optimization

9.1 Stochastic Gradient Descent

9.1.1 Stochastic Gradient Descent with momentum

9.1.2 Adam

9.2 Evolutionary Algorithms

9.3 Bayesian Optimization

Chapter 10

Hyperparameter Optimization

Usually, models contain lots of parameters that are chosen before training a model. Some examples are the number of layers in a neural network and the number of convolutional filters, the features that are used in the model or the learning rate that is used for the optimization algorithm.

We usually do hyperparameter on a metric which we directly want to optimize, such as top-1 accuracy. This is in contrast with gradient-based optimization where we often use a surrogate metric such as cross-entropy loss.

10.1 Neural Architecture Search

Chapter 11

Complexity and Maintainability in Machine Learning

11.1 Feature Selection

11.2 Ablation Studies

Many machine learning models contain a lot of complexity that seem to make them successful.

The question is whether all this complexity is needed, or can we do with less?

One of the ways to answer this is to perform an ablation study:

11.3 Expressiveness

11.4 Don't Repeat Yourself

11.5 Feature Store

In a larger organisation, multiple data science teams often use the same datasets for learning predictive models. Without any tooling or discussion, they will start to perform feature engineering and . This has a couple of downsides:

- Teams can not quickly experiment and try to learn a model based on features, they have to start to build features first.
- Every team performs the same steps in feature engineering, with large differences in quality of the features

11.6 Data Recency

11.7 Numerical Libraries and Frameworks

To define and train Machine Learning models efficiently, we need libraries and frameworks.

11.8 TensorFlow

11.9 PyTorch

11.10 MxNet

11.11 Scikit-learn

11.12 NumPy

11.13 Keras

11.14 XGBoost

11.15 LightGBM

11.16 FastAI

Chapter 12

Machine Learning on Big Data

12.1 Multi machine Learning

12.2 Distributed Machine Learning

12.3 Data Formats

Chapter 13

Productionizing Models

13.1 Model Formats

After learning a ML model such as a neural network or a random forest, we have to store the *weights* of the model and the *structure* of the model.

- ONNX
- TensorFlow SavedModel
- TensorFlow Lite
- Keras File. A binary file format from Keras that can be used to save / share. It uses the HDF5 format to save the model weights and
- Pickle. This is the built-in object serialization functionality of Python. It is meant to temporarily write an (Python) object to disk, to load it again later within the same environment.

13.2 Serving Models

- TensorFlow Serving
- MXNet Model Server

Chapter 14

Hardware for Machine Learning

14.1 GPU

14.2 TPU

14.3 CPU

14.4 Mobile Devices

14.5 Future Hardware

Chapter 15

Automated Machine Learning

Chapter 16

Reinforcement Learning