

# Functional Package for Transport Layer Security (TLS)



Version: 2.0-draft  
2022-08-24

**National Information Assurance Partnership**

# Revision History

---

Version	Date	Comment
1.0	2018-12-17	First publication
1.1	2019-03-01	Clarifications regarding override for invalid certificates, renegotiation_info extension, DTLS versions, and named Diffie-Hellman groups in DTLS contexts
2.0	2022-08-24	Added audit events, added TLS 1.3 support, deprecated TLS 1.0 and 1.1, updated algorithms/ciphersuites in accordance with CNSA suite RFC and to consider PSK, restructured SFRs for clarity

# Contents

---

- 1 Introduction
  - 1.1 Overview
  - 1.2 Terms
    - 1.2.1 Common Criteria Terms
    - 1.2.2 Technical Terms
  - 1.3 Compliant Targets of Evaluation
- 2 Conformance Claims
- 3 Security Functional Requirements
  - 3.1 Auditable Events for Mandatory SFRs
  - 3.2 Cryptographic Support (FCS)
- Appendix A - Optional Requirements
  - A.1 Strictly Optional Requirements
  - A.2 Objective Requirements
  - A.3 Implementation-dependent Requirements
- Appendix B - Selection-based Requirements
  - B.1 Auditable Events for Selection-based Requirements
  - B.2 Cryptographic Support (FCS)
- Appendix C - Acronyms
- Appendix D - Bibliography

# 1 Introduction

## 1.1 Overview

Transport Layer Security (TLS) and the closely-related Datagram TLS (DTLS) are cryptographic protocols designed to provide communications security over IP networks. Several versions of the protocol are in widespread use in software that provides functionality such as web browsing, email, instant messaging, and voice-over-IP (VoIP). Major websites use TLS to protect communications to and from their servers. TLS is also used to protect communications between hosts and network infrastructure devices for administration. The underlying platform, such as an operating system, often provides the actual TLS implementation. The primary goal of the TLS protocol is to provide confidentiality and integrity of data transmitted between two communicating endpoints, as well as authentication of at least the server endpoint.

TLS supports many different methods for exchanging keys, encrypting data, and authenticating message integrity. These methods are dynamically negotiated between the client and server when the TLS connection is established. As a result, evaluating the implementation of both endpoints is typically necessary to provide assurance for the operating environment.

This "Functional Package for Transport Layer Security" (short name "TLS-PKG") defines functional requirements for the implementation of the TLS and DTLS protocols. The requirements are intended to improve the security of products by enabling their evaluation.

## 1.2 Terms

The following sections list Common Criteria and technology terms used in this document.

### 1.2.1 Common Criteria Terms

Assurance	Grounds for confidence that a TOE meets the SFRs <a href="#">[CC]</a> .
Base Protection Profile (Base-PP)	Protection Profile used as a basis to build a PP-Configuration.
Collaborative Protection Profile (cPP)	A Protection Profile developed by international technical communities and approved by multiple schemes.
Common Criteria (CC)	Common Criteria for Information Technology Security Evaluation (International Standard ISO/IEC 15408).
Common Criteria Testing Laboratory	Within the context of the Common Criteria Evaluation and Validation Scheme (CCEVS), an IT security evaluation facility accredited by the National Voluntary Laboratory Accreditation Program (NVLAP) and approved by the NIAP Validation Body to conduct Common Criteria-based evaluations.
Common Evaluation Methodology (CEM)	Common Evaluation Methodology for Information Technology Security Evaluation.
Distributed TOE	A TOE composed of multiple components operating as a logical whole.
Extended Package (EP)	A deprecated document form for collecting SFRs that implement a particular protocol, technology, or functionality. See Functional Packages.
Functional Package (FP)	A document that collects SFRs for a particular protocol, technology, or functionality.
Operational Environment (OE)	Hardware and software that are outside the TOE boundary that support the TOE functionality and security policy.
Protection Profile (PP)	An implementation-independent set of security requirements for a category of products.
Protection Profile Configuration (PP-Configuration)	A comprehensive set of security requirements for a product type that consists of at least one Base-PP and at least one PP-Module.

Protection Profile Module (PP-Module)	An implementation-independent statement of security needs for a TOE type complementary to one or more Base-PPs.
Security Assurance Requirement (SAR)	A requirement to assure the security of the TOE.
Security Functional Requirement (SFR)	A requirement for security enforcement by the TOE.
Security Target (ST)	A set of implementation-dependent security requirements for a specific product.
Target of Evaluation (TOE)	The product under evaluation.
TOE Security Functionality (TSF)	The security functionality of the product under evaluation.
TOE Summary Specification (TSS)	A description of how a TOE satisfies the SFRs in an ST.

### 1.2.2 Technical Terms

Certificate Authority (CA)	Issuer of digital certificates.
Datagram Transport Layer Security (DTLS)	Cryptographic network protocol, based on TLS, which provides communications security for datagram protocols.
Transport Layer Security (TLS)	Cryptographic network protocol for providing communications security over a TCP/IP network.

## 1.3 Compliant Targets of Evaluation

The Target of Evaluation (TOE) in this Package is a product which acts as a (D)TLS client, a (D)TLS server, or both. This Package describes the security functionality of TLS and DTLS in terms of [\[CC\]](#).

The contents of this Package must be appropriately combined with a PP or PP-Module. When this Package is instantiated by a PP or PP-Module, the Package must include selection-based requirements in accordance with the selections or assignments indicated in the PP or PP-Module. These may be expanded by the the ST author.

The PP or PP-Module which instantiates this Package must typically include the following components in order to satisfy dependencies of this Package. It is the responsibility of the PP or PP-Module author who instantiates this Package to ensure that dependence on these components is satisfied:

Component	Explanation
<a href="#">FCS_CKM.1</a>	To support TLS ciphersuites that use RSA, DHE or ECDHE for key exchange, the PP or PP-Module must include <a href="#">FCS_CKM.1</a> and specify the corresponding key generation algorithm.
<a href="#">FCS_CKM.2</a>	To support TLS ciphersuites that use RSA, DHE or ECDHE for key exchange, the PP or PP-Module must include <a href="#">FCS_CKM.2</a> and specify the corresponding algorithm.
<a href="#">FCS_COP.1</a>	To support TLS ciphersuites that use AES for encryption and decryption, the PP or PP-Module must include <a href="#">FCS_COP.1</a> (iterating as needed) and specify AES with corresponding key sizes and modes. To support TLS ciphersuites that use SHA for hashing, the PP or PP-Module must include <a href="#">FCS_COP.1</a> (iterating as needed) and specify SHA with corresponding digest sizes.
<a href="#">FCS_RBG_EXT.1</a>	To support random bit generation needed for the TLS handshake, the PP or PP-Module must include <a href="#">FCS_RBG_EXT.1</a> .
<a href="#">FIA_X509_EXT.1</a>	To support validation of certificates needed during TLS connection setup, the PP or PP-Module must include <a href="#">FIA_X509_EXT.1</a> .
<a href="#">FIA_X509_EXT.2</a>	To support the use of X509 certificates for authentication in TLS connection setup, the PP

or PP-Module must include [FIA\\_X509\\_EXT.2](#).

An ST must identify the applicable version of the PP or PP-Module and this Package in its conformance claims.

# 2 Conformance Claims

## Conformance Statement

An ST must claim exact conformance to this Package, as defined in the CC and CEM addenda for Exact Conformance, Selection-based SFRs, and Optional SFRs (dated May 2017).

## CC Conformance Claims

This Package is conformant to Parts 2 (extended) and 3 (conformant) of Common Criteria Version 3.1, Revision 5.

## PP Claim

This Package does not claim conformance to any Protection Profile.

## Package Claim

This Package does not claim conformance to any packages.

## Conformance Statement

This Package serves to provide Protection Profiles with additional SFRs and associated Evaluation Activities specific to TLS clients and servers.

This Package conforms to Common Criteria [\[CC\]](#) for Information Technology Security Evaluation, Version 3.1, Revision 5. It is CC Part 2 extended conformant.

In accordance with CC Part 1, dependencies are not included when they are addressed by other SFRs. The evaluation activities provide adequate proof that any dependencies are also satisfied.

# 3 Security Functional Requirements

This chapter describes the security requirements which have to be fulfilled by the product under evaluation. Those requirements comprise functional components from Part 2 of [CC]. The following conventions are used for the completion of operations:

- **Refinement** operation (denoted by **bold text** or ~~striketrough text~~): Is used to add details to a requirement (including replacing an assignment with a more restrictive selection) or to remove part of the requirement that is made irrelevant through the completion of another operation, and thus further restricts a requirement.
- **Selection** (denoted by *italicized text*): Is used to select one or more options provided by the [CC] in stating a requirement.
- **Assignment** operation (denoted by *italicized text*): Is used to assign a specific value to an unspecified parameter, such as the length of a password. Showing the value in square brackets indicates assignment.
- **Iteration** operation: Is indicated by appending the SFR name with a slash and unique identifier suggesting the purpose of the operation, e.g. "/EXAMPLE1."

## 3.1 Auditable Events for Mandatory SFRs

The auditable events specified in this Functional Package are included in a Security Target if the incorporating PP or PP-Module supports audit event reporting through FAU\_GEN.1 and all other criteria in the incorporating PP or PP-Module are met.

Table 1: Auditable Events for Mandatory Requirements

Requirement	Auditable Events	Additional Audit Record Contents
<a href="#">FCS_TLS_EXT.1</a>	No events specified	N/A

## 3.2 Cryptographic Support (FCS)

### FCS\_TLS\_EXT.1 TLS Protocol

FCS\_TLS\_EXT.1.1

The TSF shall implement [**selection:**

- *TLS as a client*
- *TLS as a server*
- *DTLS as a client*
- *DTLS as a server*

].

**Application Note:** If *TLS as a client* is selected, then the ST must include the requirements from [FCS\\_TLSC\\_EXT.1](#).  
If *TLS as a server* is selected, then the ST must include the requirements from [FCS\\_TLSS\\_EXT.1](#).

If *DTLS as a client* is selected, then the ST must include the requirements from [FCS\\_DTLSC\\_EXT.1](#).  
If *DTLS as a server* is selected, then the ST must include the requirements from [FCS\\_DTLSS\\_EXT.1](#).

### Evaluation Activities ▼

[FCS\\_TLS\\_EXT.1](#)

#### TSS

The evaluator shall examine the TSS to verify that the TLS and DTLS claims are consistent with those selected in the SFR.

#### Guidance

The evaluator shall ensure that the selections indicated in the ST are consistent with selections in the dependent components.

#### Tests

There are no test activities for this SFR; the following information is provided as an overview of the expected functionality and test environment for all subsequent SFRs.



**Figure 1: TLS Hello**

The chart above provides an overview of the TLS hello messages, the content and protections, and the establishment of cryptographic keys in support of the protections.

- Blue text indicates a message or content unique to TLS 1.2.
- Green text indicates uniqueness to TLS 1.3.
- Black text indicates features common to both TLS 1.2 and TLS 1.3.
- Bold text indicates mandatory features.
- Italics emphasizes optional features.
- A shaded text box indicates that the message is encrypted for TLS 1.2 (blue), TLS 1.3 (green) or both TLS 1.2 and TLS 1.3 (grey).
- An outlined text box indicates that the content in the message is signed, and/or provides authentication of the handshake to that point.

#### **Test Environment:**

Tests for TLS 1.2 and TLS 1.3 include examination of the handshake messages and behavior of the TSF when presented with unexpected or invalid messages. For TLS 1.2 and below, previous versions of this Functional Package only required visibility of network traffic and the ability to modify a valid handshake message sent to the TSF.





**Figure 2: Test environment for TLS 1.2 using network traffic visibility and control tools**

TLS 1.3 introduces the encryption of handshake messages subsequent to the server hello exchange which prevents visibility and control using midpoint capabilities. To achieve equivalent validation of TLS 1.3 requires the ability to modify the traffic underlying the encryption applied after the server hello message. This can be achieved by introducing additional control of the messages sent, and visibility of messages received by the test TLS client, when validating TLS server functionality or test server, when validating TLS client functionality.



**Figure 3: Test environment for TLS 1.3 using custom endpoint capabilities for visibility and control**

Typically, a compliant TLS 1.3 library modified to provide visibility and control of the handshake messages prior to encryption suffices for all tests. Such modification will require the test client and/or server to be validated.

Since validations of products supporting only TLS 1.2 are still expected under this Package, the test environment for TLS 1.2-only validations may include network sniffers and man-in-the-middle products that do not require such modifications to a compliant TLS 1.2 library. For consistency, a compliant TLS client (or TLS server) together with the network sniffers and man-in-the-middle capabilities will also be referred to as a test TLS client (or test TLS server, respectively) in the following evaluation activities.



**Figure 4: Combined test environment for TLS 1.2 and TLS 1.3 using both network tools and custom endpoint capabilities**



# Appendix A - Optional Requirements

As indicated in the introduction to this Package, the baseline requirements (those that must be performed by the TOE) are contained in the body of this Package. This appendix contains three other types of optional requirements that may be included in the ST, but are not required in order to conform to this Package. However, applied modules, packages and/or use cases may refine specific requirements as mandatory.

The first type ([A.1 Strictly Optional Requirements](#)) are strictly optional requirements that are independent of the TOE implementing any function. If the TOE fulfills any of these requirements or supports a certain functionality, the vendor is encouraged to include the SFRs in the ST, but are not required in order to conform to this Package.

The second type ([A.2 Objective Requirements](#)) are objective requirements that describe security functionality not yet widely available in commercial technology. The requirements are not currently mandated in the body of this Package, but will be included in the baseline requirements in future versions of this Package. Adoption by vendors is encouraged and expected as soon as possible.

The third type ([A.3 Implementation-dependent Requirements](#)) are dependent on the TOE implementing a particular function. If the TOE fulfills any of these requirements, the vendor must either add the related SFR or disable the functionality for the evaluated configuration.

## A.1 Strictly Optional Requirements

---

This Package does not define any Strictly Optional requirements.

## A.2 Objective Requirements

---

This Package does not define any Objective requirements.

## A.3 Implementation-dependent Requirements

---

This Package does not define any Implementation-dependent requirements.

# Appendix B - Selection-based Requirements

As indicated in the introduction to this Package, the baseline requirements (those that must be performed by the TOE or its underlying platform) are contained in the body of this Package. There are additional requirements based on selections in the body of the Package: if certain selections are made, then additional requirements below must be included.

## B.1 Auditable Events for Selection-based Requirements

The auditable events in the table below are included in a Security Target if both the associated requirement is included and the incorporating PP or PP-Module supports audit event reporting through FAU\_GEN.1 and any other criteria in the incorporating PP or PP-Module are met.

**Table 2: Auditable Events for Selection-based Requirements**

Requirement	Auditable Events	Additional Audit Record Contents
FCS_TLSC_EXT.1	<b>[selection:</b> <i>Failure to establish a TLS session, None</i> <b>]</b>	Reason for failure.
	<b>[selection:</b> <i>Failure to verify presented identifier, None</i> <b>]</b>	Presented identifier and reference identifier.
	<b>[selection:</b> <i>Establishment/termination of a TLS session, None</i> <b>]</b>	Non-TOE endpoint of connection.
FCS_TLSC_EXT.2	No events specified	N/A
FCS_TLSC_EXT.3	No events specified	N/A
FCS_TLSC_EXT.4	No events specified	N/A
FCS_TLSC_EXT.5	No events specified	N/A
FCS_TLSC_EXT.6	No events specified	N/A
FCS_TLSS_EXT.1	<b>[selection:</b> <i>Failure to establish a TLS session, None</i> <b>]</b>	Reason for failure
FCS_TLSS_EXT.3	No events specified	N/A
FCS_TLSS_EXT.4	No events specified	N/A
FCS_TLSS_EXT.5	No events specified	N/A
FCS_TLSS_EXT.6	No events specified	N/A
FCS_DTLSC_EXT.1	<b>[selection:</b> <i>Failure of the certificate validity check, None</i> <b>]</b>	Issuer Name and Subject Name of certificate.
FCS_DTLSC_EXT.2	No events specified	N/A
FCS_DTLSS_EXT.1	<b>[selection:</b> <i>Failure of the certificate validity check, None</i> <b>]</b>	Issuer Name and Subject Name of certificate
FCS_DTLSS_EXT.2	No events specified	N/A

## B.2 Cryptographic Support (FCS)

### FCS\_TLSC\_EXT.1 TLS Client Protocol

***The inclusion of this selection-based component depends upon selection in FCS\_TLS\_EXT.1.1.***

#### FCS\_TLSC\_EXT.1.1

The TSF shall implement TLS 1.2 (RFC 5246) and **[selection:** *TLS 1.3 (RFC 8446), no other TLS version***]** as a client that supports additional functionality for session renegotiation protection and **[selection:**

- *mutual authentication*

- *supplemental downgrade protection*
- *session resumption*
- *no optional functionality*

] and shall abort attempts by a server to negotiate all other TLS or SSL versions.

**Application Note:** Session renegotiation protection is required for both TLS 1.2 and TLS 1.3, and the ST must include the requirements from [FCS\\_TLSC\\_EXT.4](#). Within [FCS\\_TLSC\\_EXT.4](#), options for implementation of secure session renegotiation for TLS 1.2, or rejecting renegotiation requests are claimed.

The ST author will claim TLS 1.3 functionality if supported, and optional functionality as appropriate for the claimed versions.

If "mutual authentication" is selected, then the ST must additionally include the requirements from [FCS\\_TLSC\\_EXT.2](#). If the TOE implements mutual authentication, this selection must be made.

If "supplemental downgrade protection" is selected, then the ST must additionally include the requirements from [FCS\\_TLSC\\_EXT.3](#). This is claimed if TLS 1.3 is supported, or if the product supports TLS 1.1 or below downgrade protection using the mechanism described in RFC 8446.

If "session resumption" is selected, then the ST must additionally include the requirements from [FCS\\_TLSC\\_EXT.5](#).

#### FCS\_TLSC\_EXT.1.2

The TSF shall be able to support the following TLS 1.2 ciphersuites: [**selection:**

- *TLS\_ECDHE\_ECDSA\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5289, RFC 8422*
- *TLS\_ECDHE\_RSA\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5289, RFC 8422*
- *TLS\_RSA\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5288*
- *TLS\_DHE\_RSA\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5288*
- *TLS\_ECDHE\_ECDSA\_WITH\_AES\_256\_CBC\_SHA384 as defined in RFC 5289*
- *TLS\_ECDHE\_RSA\_WITH\_AES\_256\_CBC\_SHA384 as defined in RFC 5289*
- *TLS\_RSA\_WITH\_AES\_256\_CBC\_SHA256 as defined in RFC 5246*
- *TLS\_DHE\_RSA\_WITH\_AES\_256\_CBC\_SHA256 as defined in RFC 5246*
- *TLS\_ECDHE\_ECDSA\_WITH\_AES\_128\_GCM\_SHA256 as defined in RFC 5289*
- *TLS\_ECDHE\_RSA\_WITH\_AES\_128\_GCM\_SHA256 as defined in RFC 5289*
- *TLS\_ECDHE\_RSA\_WITH\_AES\_128\_CBC\_SHA256 as defined in RFC 5289*
- *TLS\_RSA\_WITH\_AES\_128\_CBC\_SHA256 as defined in RFC 5246*
- *TLS\_DHE\_RSA\_WITH\_AES\_128\_CBC\_SHA256 as defined in RFC 5246*
- *TLS\_RSA\_WITH\_AES\_128\_CBC\_SHA as defined in RFC 5246*
- *PP-specific ciphersuites using pre-shared secrets including [**selection:***
  - *TLS\_ECDHE\_PSK\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 8442*
  - *TLS\_DHE\_PSK\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5487*
  - *TLS\_RSA\_PSK\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5487*
  - *TLS\_ECDHE\_PSK\_WITH\_AES\_128\_GCM\_SHA256 as defined in RFC 8442*
  - *TLS\_DHE\_PSK\_WITH\_AES\_128\_GCM\_SHA256 as defined in RFC 5487*
  - *TLS\_RSA\_PSK\_WITH\_AES\_128\_GCM\_SHA256 as defined in RFC 5487*

]

- *the following TLS 1.3 ciphersuites: [**selection:***

- *TLS\_AES\_256\_GCM\_SHA384 as defined in RFC 8446*
- *TLS\_AES\_128\_GCM\_SHA256 as defined in RFC 8446*
- *[**assignment:** other TLS 1.3 ciphersuites]]*

]

] offering the supported ciphersuites in a client hello message in preference order: [**assignment:** *list of supported ciphersuites*].

**Application Note:** The ST author should select the ciphersuites that are supported, and must select at least one ciphersuite for each TLS version supported. The ciphersuites to be tested in the evaluated configuration are limited by this requirement. However, this requirement does not restrict the TOE's ability to propose additional non-deprecated ciphersuites beyond the ones listed in this requirement in its Client Hello message as indicated in the ST. That is, the TOE may propose any ciphersuite not excluded by this element, but the evaluation will only test ciphersuites from the above list. It is necessary to limit the ciphersuites that can be used in an evaluated configuration administratively

on the server in the test environment.

TLS 1.3 ciphersuites are claimed if support for TLS 1.3 is claimed in [FCS\\_TLSC\\_EXT.1.1](#). The assignment of preference order provides an ordered list of all supported ciphersuites with the most preferred ciphersuites listed first. Ciphersuites listed in [RFC 9151, "CNFS Suite TLS Profile"] are preferred over all other ciphersuites, GCM ciphersuites are preferred over CBC ciphersuites, ECDHE preferred over RSA and DHE, and SHA256 or SHA384 over SHA1.

Ciphersuites for TLS 1.2 are of the form TLS\_{key exchange algorithm}\_WITH\_{encryption algorithm}\_{message digest algorithm}, and are listed in the TLS parameters section of the internet assignments at [iana.org](http://iana.org).

#### FCS\_TLSC\_EXT.1.3

The TSF shall not offer the following ciphersuites indicating the following:

- the null encryption component
- support for anonymous servers
- use of deprecated or export-grade cryptography including DES, 3DES, RC2, RC4, or IDEA for encryption
- use of MD

and shall abort sessions where a server attempts to negotiate ciphersuites not enumerated in the client hello message.

#### FCS\_TLSC\_EXT.1.4

The TSF shall be able to support the following TLS client hello message extensions:

- signature\_algorithms extension (RFC 8446) indicating support for **[selection:**
  - *ecdsa-secp384r1\_sha384 (RFC 8446)*
  - *rsa\_psk1\_sha384 (RFC 8446)***], and [selection:**
  - *rsa\_pss\_pss\_sha384 (RFC 8603)*
  - *rsa\_pss\_rsae\_sha384 (RFC 8603)*
  - **[assignment:** *other non-deprecated signature algorithms]*
  - *no other signature algorithms***]**
- extended\_master\_secret extension (RFC 7627) enforcing server support
- the following other extensions: **[selection:**
  - signature\_algorithms\_cert extension (RFC 8446) indicating support for **[selection:**
    - *ecdsa-secp384r1\_sha384 (RFC 8446)*
    - *rsk\_psk1\_sha384 (RFC 8446)***], and [selection:**
    - *rsa\_pss\_pss\_sha384 (RFC 8603)*
    - *rsa\_pss\_rsae\_sha384 (RFC 8603)*
    - *rsa\_pkcs1\_sha256 (RFC 8446)*
    - *rsa\_pss\_rsae\_sha256 (RFC 8446)*
    - **[assignment:** *other non-deprecated signature algorithms]*
    - *no other signature algorithms***]**
  - supported\_versions extension (RFC 8446) indicating support for TLS 1.3
  - supported\_groups extension (RFC 7919, RFC 8446) indicating support for **[selection:**
    - *secp256r1*
    - *secp384r1*
    - *secp521r1*
    - *ffdhe2048(256)*
    - *ffdhe3072(257)*
    - *ffdhe4096(258)*
    - *ffdhe6144(259)*
    - *ffdhe8192(260)***]**
  - key\_share extension (RFC 8446)
  - post\_handshake\_auth (RFC 8446), pre\_shared\_key (RFC 8446), and psk\_key\_exchange\_mode (RFC 8446) indicating DHE or ECDHE mode
  - no other extensions**]** and shall not send the following extensions:
  - early\_data
  - psk\_key\_exchange\_mode indicating PSK only mode.

**Application Note:** If TLS 1.3 is claimed in [FCS\\_TLSC\\_EXT.1.1](#), supported\_versions, supported\_groups, and key\_share extensions are claimed in accordance with RFC 8446. If TLS 1.3 is not claimed, supported\_versions and key\_share extensions are not claimed. Other extensions may be supported; certain extensions may need to be claimed based on other SFR claims made.

If ECDHE ciphersuites are claimed in [FCS\\_TLSC\\_EXT.1.2](#), the supported\_groups extension is claimed here with appropriate secp groups claimed. If DHE ciphersuites are claimed in [FCS\\_TLSC\\_EXT.1.2](#), it is preferred that the appropriate ffdhe groups be claimed here. In a subsequent version of this FP, support for ffdhe groups will be required whenever DHE ciphersuites are claimed.

When 'other non-deprecated signature algorithms' is claimed, the assignment will describe the standard signature and hash algorithms supported. MD5 and SHA-1 hashes are deprecated and are not included in the signature\_algorithms or signature\_algorithms\_cert extensions.

#### FCS\_TLSC\_EXT.1.5

The TSF shall be able to **[selection:**

- *verify that a presented identifier of name type: **[selection:***
  - *DNS name type according to RFC 6125*
  - *URN name type according to RFC 6125*
  - *SRV name type according to RFC 6125*
  - *Common Name conversion to DNS name according to RFC 6125*
  - *Directory name type according to RFC 5280*
  - *IPAddress name type according to RFC 5280*
  - *rfc822Name type according to RFC 5280*
  - ***[assignment:** other name type]*
- *interface with a client application requesting the TLS channel to verify that a presented identifier*

] matches a reference identifier of the requested TLS server and shall abort the session if no match is found.

**Application Note:** The rules for verification identity are described in Section 6 of RFC 6125 and Section 7 of RFC 5280. The reference identifier is established by the user (e.g., entering a URL into a web browser or clicking a link), by configuration (e.g., configuring the name of a mail server or authentication server), or by an application (e.g., a parameter of an API) depending on the product service. The client establishes all acceptable reference identifiers and interfaces with the TLS implementation to provide acceptable reference identifiers, or to accept the presented identifiers as validated in the server's certificate. If the product performs matching of the reference identifiers to the identifiers provided in the server's certificate, the first option is claimed and all supported name types are claimed; if the product presents the certificate, or the presented identifiers from the certificate to the application, the second option is claimed.

In most cases where TLS servers are represented by DNS-type names, the preferred method for verification is the Subject Alternative Name using DNS names, URI names, or Service Names. Verification using a conversion of the Common Name relative distinguished name from a DNS name type in the subject field is allowed for the purposes of backward compatibility.

Finally, the client should avoid constructing reference identifiers using wildcards. However, if the presented identifiers include wildcards, the client must follow the best practices regarding matching; these best practices are captured in the evaluation activity. Support for other name types is rare, but may be claimed for specific applications.

[JF] App note talks about wildcards best practices being captured in the evaluation activity but nothing in the activity actually covers this.

#### FCS\_TLSC\_EXT.1.6

The TSF shall not establish a trusted channel if the server certificate is invalid **[selection:** *with no exceptions, except when override is authorized in the case where valid revocation information is not available* ].

**Application Note:** A certificate used in a manner that does not support revocation checking should not advertise revocation information locations. Common methods to address this include revoking the issuing CA, resetting certificate pinning mechanisms, or removing entries from trust stores. Thus, a certificate that does not advertise revocation status information is considered to



be not revoked and does not need to be processed via override mechanisms. Override mechanisms are for use with certificates with published revocation status information that is not accessible, whether temporarily or because the information cannot be accessed during the state of the TOE (e.g., for verifying signatures on boot code). The circumstances should be described by the ST author, who should indicate the override mechanism and conditions that apply to the override, including system state, user/admin actions, etc.

This SFR is claimed if "TLS as a client" is selected in [FCS\\_TLS\\_EXT.1.1](#).

## Evaluation Activities ▼

### [FCS\\_TLSC\\_EXT.1](#)

#### **TSS**

*The evaluator shall check the description of the implementation of this protocol in the TSS to ensure the supported TLS versions, features, ciphersuites, and extensions are specified in accordance with RFC 5246 (TLS 1.2) and RFC 8446 (TLS 1.3 and updates to TLS 1.2) and as refined in [FCS\\_TLSC\\_EXT.1](#) as appropriate.*

*The evaluator shall verify that ciphersuites indicated in [FCS\\_TLSC\\_EXT.1.2](#) are included in the description, and that none of the following ciphersuites are supported: ciphersuites indicating 'NULL,' 'RC2,' 'RC4,' 'DES,' 'IDEA,' or 'TDES' in the encryption algorithm component, indicating 'anon,' or indicating MD5 or SHA in the message digest algorithm component.*

*The evaluator shall verify that the TLS implementation description includes the extensions as required in [FCS\\_TLSC\\_EXT.1.4](#).*

*The evaluator shall verify that the ST describes applications that use the TLS functions and how they establish reference identifiers.*

*The evaluator shall verify that the ST includes a description of the name types parsed and matching methods supported for associating the server certificate to application defined reference identifiers.*

#### **Guidance**

*The evaluator shall check the operational guidance to ensure that it contains instructions on configuring the product so that TLS conforms to the description in the TSS and that it includes any instructions on configuring the version, ciphersuites, or optional extensions that are supported.*

*The evaluator shall verify that all configurable features for matching identifiers in certificates presented in the TLS handshake to application specific reference identifiers are described.*

#### **Tests**

*The evaluator shall perform the following tests:*

- **Test 1.1:** (supported configurations) *For each supported version, and for each supported ciphersuite associated with the version:*

*The evaluator shall establish a TLS connection between the TOE and a test TLS server that is configured to negotiate the tested version and ciphersuite in accordance with the RFC for the version.*

*The evaluator shall observe that the TSF presents a client hello with the highest version of TLS 1.2 or the legacy version (value '03 03') and shall observe that the supported version extension is not included for TLS 1.2, and, if TLS 1.3 is supported, is present and contains the value '03 04' for TLS 1.3.*

*The evaluator shall observe that the client hello indicates the supported ciphersuites in the order indicated, and that it includes only the extensions supported, with appropriate values, for that version in accordance with the requirement.*

*The evaluator shall observe that the TOE successfully completes the TLS handshake.*

**Note:** *TOEs supporting TLS 1.3, but allowing a server to negotiate TLS 1.2, should include all ciphersuites and all extensions as required for either version. If such a TOE is configurable to support only TLS 1.2, only TLS 1.3, or both TLS 1.2 and TLS 1.3, Test 1 should be performed in each configuration - with advertised ciphersuites appropriate for the configuration.*

*The connection in Test 1 may be established as part of the establishment of a higher-level protocol, e.g., as part of an EAP session.*

*It is sufficient to observe the successful negotiation of a ciphersuite to satisfy the intent of the test; it is not necessary to examine the characteristics of the encrypted traffic in an attempt to discern the ciphersuite being used (for example, that the cryptographic algorithm is 128-bit AES and not 256-bit AES).*

- **Test 1.2:** (obsolete versions) *The evaluator shall perform the following tests:*
  - **Test 2.2.1:** *For each of SSL version 3, TLS version 1.0, and TLS version 1.1, the*



evaluator shall initiate a TLS connection from the TOE to a test TLS server that is configured to negotiate the obsolete version and observe that the TSF terminates the connection.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., protocol version, insufficient security) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

- **Test 2.2.2:** The evaluator shall attempt to establish a connection with a test TLS server that is configured to send a server hello message indicating the selected version (referred to as the legacy version for TLS 1.3) with a value corresponding to an undefined TLS (legacy) version (e.g., '03 04') and observe that the TSF terminates the connection.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., protocol version) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

Test 2.2 is intended to test the TSF response to non-standard versions, including early proposals for 'beta TLS 1.3' versions. RFC 8446 requires the legacy version to have the value '03 03' and specifies TLS 1.3 in the supported versions extension with the value '03 04'. While not a preferred approach, if continued support for a beta TLS 1.3 version is desired and the TSF cannot be configured to reject such versions, another value (e.g., '03 05') can be used in Test 2.2. Implementations of non-standard versions are not tested.

- **Test 2.3:** (ciphersuites) The evaluator shall perform the following tests on handling unexpected ciphersuites using a test TLS server sending handshake messages compliant with the negotiated version except as indicated in the test:

- **Test 3.3.1:** (ciphersuite not offered) For each supported version, the evaluator shall attempt to establish a connection with a test TLS server configured to negotiate the supported version and a ciphersuite not included in the client hello and observe that the TOE rejects the connection.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., handshake failure) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

This test intended to test the TSF's generic ability to recognize non-offered ciphersuites. If the ciphersuites in the client hello are configurable, the evaluator shall configure the TSF to offer a ciphersuite outside those that are supported and use that ciphersuite in the test. If the TSF ciphersuite list is not configurable, it is acceptable to use a named ciphersuite from the IANA TLS protocols associated with the tested version. Additional special cases of this test for special ciphersuites are performed separately.

- **Test 3.3.2:** (version confusion) For each supported version, the evaluator shall attempt to establish a connection with a test TLS server that is configured to negotiate the supported version and a ciphersuite that is not associated with that version and observe that the TOE rejects the connection.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., handshake failure) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

It is intended that Test 3.2 use TLS 1.3 ciphersuites for a server negotiating TLS 1.2. If TLS 1.3 is supported, the test server negotiating TLS 1.3 should select a TLS 1.2 ciphersuite supported by the TOE for TLS 1.2 and matching the client's supported groups and signature algorithm indicated by extensions in the TLS 1.3 client hello. If the TOE is configurable to allow both TLS 1.2 and TLS 1.3 servers, the test server should use ciphersuites offered by the TSF in its client hello message.

- **Test 3.3.3:** (null ciphersuite) For each supported version, the evaluator shall attempt to establish a connection with a test TLS server configured to negotiate the null ciphersuite (TLS\_NULL\_WITH\_NULL\_NULL) and observe that the TOE rejects the connection.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., handshake failure, insufficient security) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

- **Test 3.3.4:** (anon ciphersuite) The evaluator shall attempt to establish a TLS 1.2 connection with a test TLS server configured to negotiate a ciphersuite using the anonymous server authentication method and observe that the TOE rejects the connection.

It is preferred that the TSF sends a fatal error alert message (e.g., handshake failure, insufficient security) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

See IANA TLS parameters for available ciphersuites to be selected by the test TLS

server. The test ciphersuite should use supported cryptographic algorithms for as many of the other components as possible. For example, if the TSF only supports the ciphersuite TLS\_ECDHE\_ECDSA\_WITH\_AES\_256\_GCM\_SHA384, the test server could select TLS\_DH\_ANON\_WITH\_AES\_256\_GCM\_SHA\_384.

- **Test 3.3.5:** (deprecated encryption algorithm) For each deprecated encryption algorithm (NULL, RC2, RC4, DES, IDEA, and TDES), the evaluator shall attempt to establish a TLS 1.2 connection with a test TLS server configured to negotiate a ciphersuite using the deprecated encryption algorithm and observe that the TOE rejects the connection.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., handshake failure, insufficient security) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

See IANA TLS parameters for available ciphersuites to be tested. The test ciphersuite should use supported cryptographic algorithms for as many of the other components as possible. For example, if the TSF only supports TLS\_ECDHE\_ECDSA\_WITH\_AES\_256\_GCM\_SHA384, the test server could select TLS\_ECDHE\_PSK\_WITH\_NULL\_SHA\_384, TLS\_RSA\_EXPORT\_WITH\_RC2\_CBC\_40\_MD5, TLS\_ECDHE\_RSA\_WITH\_RC4\_128\_SHA, TLS\_DHE\_DSS\_WITH\_DES\_CBC\_SHA, TLS\_RSA\_WITH\_IDEA\_CBC\_SHA, and TLS\_ECDHE\_RSA\_WITH\_3DES\_EDE\_CBC\_SHA.

- **Test 3.4:** (extensions) For each supported version indicated in the following tests, the evaluator shall establish a connection from the TOE with a test server negotiating the tested version and providing server handshake messages as indicated when performing the following tests for validating proper extension handling:

- **Test 4.4.1:** (signature\_algorithms) [conditional] If the TSF supports certificate-based server authentication, the evaluator shall perform the following tests:
  - **Test 5.4.1.1:** For each supported version, the evaluator shall initiate a TLS session with a TLS test server and observe that the TSF's client hello includes the signature\_algorithms extension with values in conformance with the ST.
  - **Test 5.4.1.2:** (TLS 1.2 only) [conditional] If the TSF supports an ECDHE or DHE ciphersuite, the evaluator shall ensure the test TLS server sends a compliant server hello message selecting TLS 1.2 and one of the supported ECDHE or DHE ciphersuites, a compliant server certificate message, and a key exchange message signed using a signature algorithm and hash combination not included in the client's hello message (e.g., RSA with SHA-1). The evaluator shall observe that the TSF terminates the handshake.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., handshake failure, illegal parameter, decryption error) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

- **Test 5.4.1.3:** [conditional] If TLS 1.3 is supported, the evaluator shall configure the test TLS server to respond to the TOE with a compliant server hello message selecting TLS 1.3 and a server certificate message, but then also sends a certificate verification message that uses a signature algorithm method not included in the signature\_algorithms extension. The evaluator shall observe that the TSF terminates the TLS handshake.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., handshake failure, illegal parameter, bad certificate, decryption error) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

- **Test 5.4.1.4:** [conditional] For all supported versions for which signature\_algorithms\_cert is not supported, the evaluator shall ensure the test TLS server sends a compliant server hello message for the tested version and a server certificate message containing a valid certificate that represents the test TLS server, but which is signed using a signature and hash combination not included in the TSF's signature\_algorithms extension (e.g., a certificate signed using RSA and SHA-1). The evaluator shall observe that the TSF terminates the TLS session.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., unsupported certificate, bad certificate, decryption error, handshake failure) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

Certificate-based server authentication is required unless the TSF only supports TLS with shared PSK. For TLS 1.2, this is the case if only TLS\_ECDHE\_PSK\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 8442, TLS\_DHE\_PSK\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5487, TLS\_ECDHE\_PSK\_WITH\_AES\_128\_GCM\_SHA256 as defined in RFC 8442, or TLS\_DHE\_PSK\_WITH\_AES\_128\_GCM\_SHA256 as defined in RFC 5487, are supported. For TLS 1.3, this is the case if only PSK handshakes are supported.

- **Test 5.4.2:** (*signature\_algorithms\_cert*) [conditional] If *signature\_algorithms\_cert* is supported, then for each version that uses the *signature\_algorithms\_cert* extension, the evaluator shall ensure that the test TLS server sends a compliant server hello message selecting the tested version and indicating certificate-based server authentication.

The evaluator shall ensure that the test TLS server forwards a certificate message containing a valid certificate that represents the test TLS server, but which is signed by a valid Certification Authority using a signature and hash combination not included in the TSF's *signature\_algorithms\_cert* extension (e.g., a certificate signed using RSA and SHA-1). The evaluator shall confirm the TSF terminates the session.

**Note:** Support for certificate based authentication is assumed if the *signature\_algorithms\_cert* is supported. For TLS 1.2, a non-PSK ciphersuite, or one of *TLS\_RSA\_PSK\_WITH\_AES\_256\_GCM\_SHA384* or *TLS\_RSA\_PSK\_WITH\_AES\_128\_GCM\_SHA256* as defined in RFC 5487 is used to indicate certificate-based server authentication. For TLS 1.3, the test server completes a full handshake, even if a PSK is offered to indicate certificate-based server authentication. If the TSF only supports shared PSK authentication, Test 4.2 is not performed.

For TLS 1.3, the server certificate message is encrypted. The evaluator will configure the test TLS server with the indicated certificate and ensure that the certificate is indeed sent by observing the buffer of messages to be encrypted, or by inspecting one or both sets of logs from the TSF and test TLS server.

It is preferred that the TSF sends a fatal error alert message (e.g., unsupported certificate, bad certificate, decryption error, handshake failure) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

- **Test 5.4.3:** (*extended\_master\_secret*) (TLS 1.2 only) The evaluator shall initiate a TLS 1.2 session with a test TLS server configured to compute a master secret according to RFC 5246, section 8.

The evaluator shall observe that the TSF's client hello includes the extended master secret extension in accordance with RFC 7627, and ensures that the test TLS server does not include the extended master secret extension in its server hello. The evaluator shall observe that the TSF terminates the session.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., handshake failure) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

- **Test 5.4.4:** (*supported\_groups*) (TLS 1.2 only – for TLS 1.3, testing is combined with testing of the keyshare extension)
  - **Test 6.4.4.1:** For each supported group, the evaluator shall initiate a TLS session with a compliant test TLS 1.2 server supporting RFC 7919. The evaluator shall ensure that the test TLS server is configured to select TLS 1.2 and a ciphersuite using the supported group. The evaluator shall observe that the TSF's client hello lists the supported groups as indicated in the ST, and that the TSF successfully establishes the TLS session.
  - **Test 6.4.4.2:** [conditional on TLS 1.2 support for ECDHE ciphersuites] The evaluator shall initiate a TLS session with a test TLS server that is configured to use an explicit version of a named EC group supported by the client. The evaluator shall ensure that the test TLS server key exchange message includes the explicit formulation of the group in its key exchange message as indicated in RFC 4492 section 5.4. The evaluator shall confirm that the TSF terminates the session.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., illegal parameter) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

- **Test 6.5:** (TLS 1.3 extensions) [conditional] If the TSF supports TLS 1.3, the evaluator shall perform the following tests. For each test, the evaluator shall observe that the TSF's client hello includes the supported versions extension with the value '03 04' indicating TLS 1.3:

- **Test 7.5.1:** (*supported\_versions*) The evaluator shall initiate TLS 1.3 sessions in turn from the TOE to a test TLS server configured as indicated in the sub-tests below:

- **Test 8.5.1.1:** The evaluator shall configure the test TLS server to include the supported versions extension in the server hello containing the value '03 03.' The evaluator shall observe that the TSF terminates the TLS session.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., illegal parameter, handshake failure, protocol version) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

- **Test 8.5.1.2:** The evaluator shall configure the test TLS server to include the

supported versions extension in the server hello containing the value '03 04' and complete a compliant TLS 1.3 handshake. The evaluator shall observe that the TSF completes the TLS 1.3 handshake successfully.

- **Test 8.5.1.3:** [conditional] If the TSF is configurable to support both TLS 1.2 and TLS 1.3, the evaluator shall follow operational guidance to configure this behavior. The evaluator shall ensure that the test TLS server sends a TLS 1.2 compliant server handshake and observe that the server random does not incidentally include any downgrade messaging. The evaluator shall observe that the TSF completes the TLS 1.2 handshake successfully.

**Note:** Enhanced downgrade protection defined in RFC 8446 is optional, and if supported, is tested separately. The evaluator may configure the test server's random, or may repeat the test until the server's random does not match a downgrade indicator.

- **Test 8.5.2:** (supported groups, key shares) The evaluator shall initiate TLS 1.3 sessions in turn with a test TLS server configured as indicated in the following sub-tests:

- **Test 9.5.2.1:** For each supported group, the evaluator shall configure the compliant test TLS 1.3 server to select a ciphersuite using the group. The evaluator shall observe that the TSF sends an element of the group in its client hello key shares extension (after a hello retry message from the test server, if the key share for the group is not included in the initial client hello). The evaluator shall ensure the test TLS server sends an element of the group in its server hello and observes that the TSF completes the TLS handshake successfully.
- **Test 9.5.2.2:** For each supported group, the evaluator shall modify the server hello sent by the test TLS server to include an invalid key share value claiming to be an element the group indicated in the supported groups extension. The evaluator shall observe that the TSF terminates the TLS session.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., illegal parameter) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

For DHE ciphersuites, a zero value, or a value greater or equal to the modulus is not a valid element. For ECDHE groups, an invalid point contains x and y coordinates of the correct size, but represents a point not on the curve. The evaluator can construct such an invalid point by modifying a byte in the y coordinate of a valid point and verify that the coordinates do not satisfy the curve equation.

- **Test 9.5.3:** (PSK support) [conditional] If the TOE supports pre-shared keys, the evaluator shall follow the operational guidance to use pre-shared keys, shall establish a pre-shared key between the TSF and the test TLS server, and initiate TLS 1.3 sessions in turn between the TSF and the test TLS server configured as indicated in the following sub-tests:

- **Test 10.5.3.1:** The evaluator shall configure the TSF to use the pre-shared key and ensure that the test TLS server functions as a compliant TLS 1.3 server. The evaluator shall observe that the TSF's client hello includes the `pre_shared_key` extension with the valid PSK indicator shared with the test server. The evaluator shall also observe that the TSF's client hello also includes the `psk_key_exchange_mode` and the `post_handshake_auth` extensions and that the `psk_key_exchange_mode` indicates one or more of DHE or ECDHE modes but does not include the PSK-only mode. The evaluator shall observe that the TSF completes the TLS 1.3 handshake successfully in accordance with RFC 8446, to include the TSF sending appropriate key shares for one or more of the supported groups.

Once the handshake is successful, the evaluator shall cause the test TLS server to send a certificate request and observe that the TSF provides a certificate message and certificate verify message.

**Note:** It may be necessary to complete a standard handshake and send a new-ticket message from the test TLS server to establish a pre-shared key, or it might be possible to configure the pre-shared key manually via out-of-band mechanisms. This can be performed in conjunction with other testing that is not tested as part of this SFR. It is not required at this time to support emerging standards on establishing PSK, but as such standards are finalized, this FP may be updated to require such support.

TLS messages after the handshake are encrypted so it may not be possible to observe the certificate and certificate verify messages sent by the TSF directly. The evaluator may need to configure the test TLS server to use an application that requires post-handshake client authentication and terminates the session or otherwise has an observable effect if the certificate is not provided.

- **Test 10.5.3.2:** The evaluator shall attempt to configure the TSF to send early



data. If there is no indication from the TSF that this is blocked, the evaluator shall repeat test 5.3.1 with the TSF so configured and observe that the TSF does not send application data prior to receiving the server hello.

**Note:** Early data will be encrypted under the PSK and received by the test TLS server prior to it sending a server hello message.

- **Test 10.6:** (corrupt finished message) For each supported version, the evaluator shall initiate a TLS session from the TOE to a test TLS server that sends a compliant set of server handshake messages, except for sending a modified finished message (modify a byte of the finished message that would have been sent by a compliant server). The evaluator shall observe that the TSF terminates the session and does not complete the handshake by observing that the TSF does not send application data provided to the TLS channel.
- **Test 10.7:** (missing finished message) For each supported version, the evaluator shall initiate a session from the TOE to a test TLS server providing a compliant handshake, except for sending a random TLS message (the five byte header indicates a correct TLS message for the negotiated version, but not indicating a finished message) as the final message. The evaluator shall observe that the TSF terminates the session and does not send application data.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., decryption error) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

For TLS 1.2, the modified message is sent after the `change_cipher_spec` message. For TLS 1.3, the modified message is sent as the last message of the server's second flight of messages.

- **Test 10.8:** (unexpected/corrupt signatures within handshake) The evaluator shall perform the following tests, according to the versions supported.
  - **Test 11.8.1:** (TLS 1.2 only) [conditional] If the ST indicates support for ECDSA or DSA ciphersuites, the evaluator shall initiate a TLS session with a compliant test TLS server and modify the signature in the server key exchange. The evaluator shall observe that the TSF terminates the session with a fatal alert message (e.g., decrypt error, handshake error).
  - **Test 11.8.2:** [conditional] If the ST indicates support for TLS 1.3, the evaluator shall initiate a TLS session between the TOE and a test TLS server that is configured to send a compliant server hello message, encrypted extension message, and certificate message, but will send a certificate verify message with an invalid signature (e.g., by modifying a byte from a valid signature). The evaluator shall confirm that the TSF terminates the session with a fatal error alert message (e.g., bad certificate, decrypt error, handshake error).
  - **Test 11.8.3:** (TLS 1.2 only) [conditional] If the ST indicates support for both RSA and ECDSA methods in the signature\_algorithm (or, if supported, the signature\_algorithms\_cert) extension, and if the ST indicates one or more TLS 1.2 ciphersuites indicating each of the RSA and ECDSA methods in its signature components, the evaluator shall choose two ciphersuites: one indicating an RSA signature (cipher 1) and one indicating an ECDSA signature (cipher 2). The evaluator shall then establish two certificates that are trusted by the TOE: one representing the test TLS 1.2 server using an RSA signature (cert 1) and one representing the test TLS 1.2 server using an ECDSA signature (cert 2). The evaluator shall initiate a TLS session between the TOE and the test TLS 1.2 server that is configured to select cipher 1 and to send cert 2. The evaluator shall verify that the TSF terminates this TLS session. The evaluator shall then initiate a TLS session between the TOE and the test 1.2 server that is configured to select cipher 2 and to send cert 1. The evaluator shall verify that the TSF also terminates this TLS session.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., bad certificate, decryption error, handshake failure) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

- **Test 11.9:** [conditional] If the TSF supports certificate-based server authentication, then for each supported version, the evaluator will initiate a TLS session from the TOE to the compliant test TLS server configured to negotiate the tested version, and to authenticate using a certificate trusted by the TSF as specified in the following:
  - **Test 12.9.1:** (certificate extended key usage purpose) The evaluator shall send a server certificate that contains the Server Authentication purpose in the extendedKeyUsage extension and verify that a connection is established. The evaluator shall repeat this test using a different certificate that is otherwise valid and trusted but lacks the Server Authentication purpose in the extendedKeyUsage extension and observe the TSF terminates the session.

**Note:** This test may be performed as part of certificate validation testing ([FIA\\_X509\\_EXT.1](#)).

It is preferred that the TSF sends a fatal error alert message (e.g., bad certificate, decryption error, handshake failure) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

Ideally, the two certificates should be similar in regards to structure, the types of identifiers used, and the chain of trust.

- **Test 12.9.2:** (certificate identifiers) For each supported method of matching presented identifiers, and for each name type for which the TSF parses the presented identifiers from the server certificate for the method, the evaluator shall establish a valid certificate trusted by the TSF to represent the test server using only the tested name type. The evaluator shall perform the following sub-tests:
  - **Test 13.9.2.1:** The evaluator shall prepare the TSF as necessary to use the matching method and establish reference identifiers for the test server for the tested name type. The evaluator shall ensure the test TLS server sends a certificate with a matching name of the tested name type and observe that the TSF completes the connection.
  - **Test 13.9.2.2:** The evaluator shall prepare the TSF as necessary to use the matching method and establish reference identifiers that do not match the name representing the test server. The evaluator shall ensure the test TLS server sends a certificate with a name of the type tested, and observe the TSF terminates the session.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., bad certificate, unknown certificate) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

- **Test 13.9.3:** (mixed identifiers)[conditional] If the TSF supports a name matching method where the TSF performs matching of both CN-encoded name types and SAN names of the same type, then for each such method, and for each such name type, the evaluator shall establish a valid certificate trusted by the TSF to represent the test server using one name for the CN-encoded name type and a different name for the SAN name type. The evaluator shall perform the following tests:
  - **Test 14.9.3.1:** The evaluator shall follow the operational guidance to configure the TSF to use the name matching method and establish reference identifiers matching only the SAN. The evaluator shall ensure that the test server sends the certificate with the matching SAN and non-matching CN-encoded name, and observe that the TSF completes the connection.

**Note:** Configuration of the TSF may depend on the application using TLS.

- **Test 14.9.3.2:** The evaluator shall follow the operational guidance to configure the TSF to use the name matching method and establish reference identifiers matching only the CN-encoded name. The evaluator shall ensure that the test server sends the certificate with the matching SAN name and non-matching CN-encoded name, and observe that the TSF terminates the session.

It is preferred that the TSF sends a fatal error alert message (e.g., bad certificate, unknown certificate) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

- **Test 14.9.4:** (empty certificate) The evaluator shall configure the test TLS server to supply an empty certificate message and verify that the TSF terminates the session.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., bad certificate, unknown certificate) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

- **Test 14.9.5:** (invalid certificate) [conditional] If validity exceptions are supported, then for each exception for certificate validity supported, the evaluator shall configure the TSF to allow the exception and ensure the test TLS server sends a certificate that is valid and trusted, except for the allowed exception. The evaluator shall observe that the TSF completes the session.

Without modifying the TSF configuration, the evaluator shall initiate a new session with the test TLS server that includes an additional validation error, and observe that the TSF terminates the session.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., decode error, bad certificate) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

The intent of this test is to verify the scope of the exception processing. If verifying certificate status information is claimed as an exception, then this test will verify that a TLS session succeeds when all supported methods for obtaining certificate status information is blocked from the TSF, to include removing any status information that might be cached by the TSF. If the exception is limited to specific certificates (e.g., only leaf certificates are exempt, or only certain leaf certificates are exempt) the additional validation error could be unavailable revocation information for a non-

exempt certificate (e.g., revocation status information from an intermediate CA is blocked for the issuing CA of an exempt leaf certificate, or revocation information from the issuing CA is blocked for a non-exempt leaf certificate). If the only option for the exception is for all revocation information for all certificates, another validation error from FIA\_X509\_EXT.1 (e.g., certificate expiration, extended key usage, etc.) may be used.

## FCS\_TLSC\_EXT.2 TLS Client Support for Mutual Authentication

**The inclusion of this selection-based component depends upon selection in [FCS\\_TLSC\\_EXT.1.1](#).**

### FCS\_TLSC\_EXT.2.1

The TSF shall support mutual authentication using X.509v3 certificates during the handshake and [**selection:** *in support of post-handshake authentication requests, at no other time* ], in accordance with [**selection:** *RFC 5246, section 7.4.4, RFC 8446, section 4.3.2* ].

**Application Note:** Clients that support TLS 1.3 and post-handshake authentication claim 'in support of post-handshake authentication requests' in the first selection. The 'at no other time' selection is claimed for clients only supporting TLS 1.2 or for TLS 1.3 clients that do not support post-handshake authentication.

The certificate request sent by the server specifies the signature algorithms and certification authorities supported by the server. If the client does not possess a matching certificate, it sends an empty certificate message. The structure of the certificate request message is changed in TLS 1.3 to use the signature\_algorithm, signature\_algorithms\_cert, and certificate\_authorities extensions, and RFC 8446 allows for TLS 1.2 implementations to use the new message structure. The "RFC 8446, section 4.3.2" option is claimed in the second selection if TLS 1.3 is supported or if the RFC 8446 method is supported for TLS 1.2 servers. The "RFC 5246, section 7.4.4" option is claimed if the RFC 5246 method is supported for interoperability with TLS 1.2 servers that do not adopt the RFC 8446 method. When mutual authentication is supported, at least one of these methods must be claimed, per the selection.

This SFR is claimed if "mutual authentication" is selected in [FCS\\_TLSC\\_EXT.1.1](#).

## Evaluation Activities ▼

### [FCS\\_TLSC\\_EXT.2](#)

#### **TSS**

The evaluator shall ensure that the TSS description required per FIA\_X509\_EXT.2.1 includes the use of client-side certificates for TLS mutual authentication. The evaluator shall also ensure that the TSS describes any factors beyond configuration that are necessary in order for the client to engage in mutual authentication using X.509v3 certificates.

#### **Guidance**

The evaluator shall ensure that the operational guidance includes any instructions necessary to configure the TOE to perform mutual authentication. The evaluator also shall verify that the operational guidance required per FIA\_X509\_EXT.2.1 includes instructions for configuring the client-side certificates for TLS mutual authentication.

#### **Tests**

For each supported TLS version, the evaluator shall perform the following tests:

- **Test 15.1:** The evaluator shall establish a TLS connection from the TSF to a test TLS server that negotiates the tested version and which is not configured for mutual authentication (i.e., does not send a Server's Certificate Request (type 13) message). The evaluator observes negotiation of a TLS channel and confirms that the TOE did not send a Client's Certificate message (type 11) during handshake.
- **Test 15.2:** The evaluator shall establish a connection to a test TLS server with a shared trusted root that is configured for mutual authentication (i.e., it sends a Server's Certificate Request (type 13) message). The evaluator observes negotiation of a TLS channel and confirms that the TOE responds with a non-empty Client's Certificate message (type 11) and Certificate Verify (type 15) message.
- **Test 15.3:** [conditional] If the TSF supports post-handshake authentication, the evaluator shall establish a pre-shared key between the TSF and a test TLS 1.3 server. The evaluator shall initiate a TLS session using the pre-shared key and confirm the TSF and test TLS 1.3

server successfully complete the TLS handshake and both support post-handshake authentication. After the session is successfully established, the evaluator shall initiate a certificate request message from the test TLS 1.3 server. The evaluator shall observe that the TSF receives that authentication request and shall take necessary actions, in accordance with the operational guidance, to complete the authentication request. The evaluator shall confirm that the test TLS 1.3 server receives certificate and certificate verification messages from the TSF over the channel that authenticates the client.

**Note:** TLS 1.3 certificate requests from the test server and client certificate and certificate verify messages are encrypted. The evaluator confirms that the TSF sends the appropriate messages by examining the messages received at the test TLS 1.3 server and by inspecting any relevant server logs. The evaluator may also take advantage of the calling application to demonstrate that the TOE receives data configured at the test TLS server.

## FCS\_TLSC\_EXT.3 TLS Client Downgrade Protection

**The inclusion of this selection-based component depends upon selection in [FCS\\_TLSC\\_EXT.1.1](#).**

### FCS\_TLSC\_EXT.3.1

The TSF shall not establish a TLS channel if the server hello message includes [selection: TLS 1.2 downgrade indicator, TLS 1.1 or below downgrade indicator ] in the server random field.

**Application Note:** The ST author claims the "TLS 1.2 downgrade indicator" when [FCS\\_TLSC\\_EXT.1](#) indicates support for both TLS 1.3 and supplemental downgrade protection. This option is not claimed if TLS 1.3 is not supported. The "TLS 1.1 or below downgrade indicator" option may be claimed regardless of support for TLS 1.3, but should only be claimed if the TSF is capable of detecting the indicator. As indicated in [FCS\\_TLSC\\_EXT.1.1](#), this FP requires the client to terminate TLS 1.1 or below sessions. It is acceptable for the TSF to always terminate TLS 1.1 sessions based on the server hello negotiated version field and ignore any downgrade indicator. However, a product that is capable of detecting the TLS 1.1 or below downgrade indicator may take different actions depending on whether the TLS 1.1 or below downgrade indicator is set.

This SFR is claimed if "supplemental downgrade protection" is selected in [FCS\\_TLSS\\_EXT.1.1](#).

## Evaluation Activities ▼

### [FCS\\_TLSC\\_EXT.3](#)

#### TSS

The evaluator shall review the TSS and confirm that the description of the TLS client protocol includes the downgrade protection mechanism in accordance with RFC 8446 and identifies any configurable features of the TSF needed to meet the requirements. If the ST claims that the TLS 1.1 and below indicator is processed, the evaluator shall confirm that the TSS indicates which configurations allow processing of the downgrade indicator and the specific response of the TSF when it receives the downgrade indicator as opposed to simply terminating the session for the unsupported version.

#### Guidance

The evaluator shall review the operational guidance and confirm that any instructions to configure the TSF to meet the requirements are included.

#### Tests

The evaluator shall perform the following tests to confirm the response to downgrade indicators from a test TLS 1.3 server:

- **Test 16.1:** [conditional] If the TSF supports TLS 1.3, the evaluator shall initiate a TLS 1.3 session with a test TLS 1.3 server configured to send a compliant TLS 1.2 server hello (not including any TLS 1.3 extensions) but including the TLS 1.2 downgrade indicator '44 4F 57 4E 47 52 44 01' in the last eight bytes of the server random field. The evaluator shall confirm that the TSF terminates the session.

**Note:** It is preferred that the TSF send a fatal error alert message (e.g., illegal parameter), but it is acceptable that the TSF terminate the session without sending an error alert.

- **Test 16.2:** [conditional] If the TSF supports the TLS 1.1 or below downgrade indicator and if the ST indicates a configuration where the indicator is processed, the evaluator shall follow operational guidance instructions to configure the TSF so it parses a TLS 1.1 handshake to detect and process the TLS downgrade indicator. The evaluator shall initiate



a TLS session between the TOE and a test TLS server that is configured to send a TLS 1.1 server hello message with the downgrade indicator '44 4F 57 4E 47 52 44 00' in the last eight bytes of the server random field, but which is otherwise compliant with RFC 4346. The evaluator shall observe that the TSF terminates the session as described in the ST.

**Note:** It is preferred that the TSF send a fatal error alert message (illegal parameter or unsupported version), but it is acceptable that the TSF terminate the session without sending an error alert.

Use of the TLS 1.1 and below indicator as a redundant mechanism where there is no configuration that actually processes the value does not require additional testing, since this would be addressed by Test 2.1 for [FCS\\_TLSC\\_EXT.1.1](#). This test is only required if the TSF responds differently (e.g., a different error alert) when the downgrade indicator is present than when TLS 1.1 or below is negotiated and the downgrade indicator is not present.

## FCS\_TLSC\_EXT.4 TLS Client Support for Renegotiation

**The inclusion of this selection-based component depends upon selection in [FCS\\_TLS\\_EXT.1.1](#).**

### FCS\_TLSC\_EXT.4.1

The TSF shall support secure renegotiation through use of [**selection:** the "renegotiation\_info" TLS extension, the TLS\_EMPTY\_RENEGOTIATION\_INFO\_SCSV signaling ciphersuite signaling value ] in accordance with RFC 5746, and shall terminate the session if an unexpected server hello is received and [**selection:** hello request message is received, in no other case ].

**Application Note:** A client allowing TLS 1.2 connections may present either the "renegotiation\_info" extension or the signaling ciphersuite value TLS\_EMPTY\_RENEGOTIATION\_INFO\_SCSV in the initial client hello message to indicate support for secure renegotiation. The ST author claims the methods supported. The TLS\_EMPTY\_RENEGOTIATION\_INFO\_SCSV is the preferred mechanism for TLS 1.2 protection against insecure renegotiation when the client does not renegotiate. The ST author will claim the 'hello request message is received' option in the second selection to indicate support for this mechanism.

RFC 5746 allows the client to accept connections with servers that do not support the extension; this FP refines RFC 5746 and requires the client to terminate sessions with such servers. Thus, unexpected server hello messages include an initial server hello negotiating TLS 1.2 that does not contain a renegotiation\_info extension, an initial server hello negotiating TLS 1.2 that has a renegotiation\_info that is non-empty, a subsequent server hello negotiating TLS 1.2 that does not contain a renegotiation\_info extension, and a subsequent server hello negotiating TLS 1.2 that has a renegotiation\_info extension with an incorrect renegotiated\_connection value.

TLS 1.3 provides protection against insecure renegotiation by not allowing renegotiation. If TLS 1.3 is claimed in [FCS\\_TLSC\\_EXT.1.1](#), the client receives a server hello that attempts to negotiate TLS 1.3, and the server hello also contains a renegotiation\_info extension; the client will terminate the connection.

This SFR is claimed if "TLS as a client" is selected in [FCS\\_TLS\\_EXT.1.1](#).

## Evaluation Activities ▼

### [FCS\\_TLSC\\_EXT.4](#)

#### **TSS**

The evaluator shall examine the ST to ensure that TLS renegotiation protections are described in accordance with the requirements. The evaluator shall ensure that any configurable features of the renegotiation protections are identified.

#### **Guidance**

The evaluator shall examine the operational guidance to confirm that instructions for any configurable features of the renegotiation protection mechanisms are included.

#### **Tests**

The evaluator shall perform the following tests as indicated. One or both of Tests 1 or 2 is required, depending on whether the TSF is configurable to reject renegotiation or supports secure renegotiation methods defined for TLS 1.2. If TLS 1.3 is supported, Test 2 is required.

- **Test 17.1:** [conditional] If the TSF supports a configuration to accept renegotiation requests for TLS 1.2, the evaluator shall follow any operational guidance to configure the TSF. The evaluator shall perform the following tests:
  - **Test 18.1.1:** The evaluator shall initiate a TLS connection with a test server configured to negotiate a compliant TLS 1.2 handshake. The evaluator shall inspect the messages received by the test TLS 1.2 server. The evaluator shall observe that either the "renegotiation\_info" field or the SCSV ciphersuite is included in the ClientHello message during the initial handshake.
  - **Test 18.1.2:** For each of the following sub-tests, the evaluator shall initiate a new TLS connection with a test TLS 1.2 server configured to send a renegotiation\_info extension as specified, but otherwise complete a compliant TLS 1.2 session:
    - **Test 19.1.2.1:** The evaluator shall configure the test TLS 1.2 server to send a renegotiation\_info extension whose value indicates a non-zero length. The evaluator shall confirm that the TSF terminates the connection.  
*Note:* It is preferred that the TSF sends a fatal error alert message (e.g., illegal parameter) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).
    - **Test 19.1.2.2:** The evaluator shall configure the test TLS 1.2 server to send a compliant renegotiation\_info extension and observe the TSF successfully completes the TLS 1.2 connection.
    - **Test 19.1.2.3:** The evaluator shall initiate a session renegotiation after completing a successful handshake with a test TLS 1.2 server that completes a successful TLS 1.2 handshake (as in Test 1.1) and then sends a hello reset request from the test TLS server with a "renegotiation\_info" extension that has an unexpected "client\_verify\_data" or "server\_verify\_data" value (modify a byte from a compliant response). The evaluator shall verify that the TSF terminates the connection.  
*Note:* It is preferred that the TSF sends a fatal error alert message (e.g., illegal parameter, handshake error) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).
- **Test 19.2:** [conditional] if the TSF supports a configuration that prevents renegotiation, the evaluator shall perform the following tests:
  - **Test 20.2.1:** (TLS 1.2) [conditional] If the TLS supports a configuration to reject TLS 1.2 renegotiation, the evaluator shall follow the operational guidance as necessary to prevent renegotiation. The evaluator shall initiate a TLS session between the so-configured TSF and a test TLS 1.2 server that is configured to perform a compliant handshake, followed by a hello reset request. The evaluator shall confirm that the TSF completes the initial handshake successfully but terminates the TLS session after receiving the hello reset request.  
*Note:* It is preferred that the TSF sends a fatal error alert message (e.g., unexpected message) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).
  - **Test 20.2.2:** [conditional] If the TSF supports TLS 1.3, the evaluator shall initiate a TLS session between the TSF and a test TLS 1.3 server that completes a compliant TLS 1.3 handshake, followed by a hello reset message. The evaluator shall observe that the TSF completes the initial TLS 1.3 handshake successfully, but terminates the session on receiving the hello reset message.  
*It is preferred that the TSF sends a fatal error alert message (e.g., unexpected message) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).*

## FCS\_TLSC\_EXT.5 TLS Client Support for Session Resumption

**The inclusion of this selection-based component depends upon selection in FCS\_TLSC\_EXT.1.1.**

### FCS\_TLSC\_EXT.5.1

The TSF shall support session resumption as a client via the use of [selection: session ID in accordance with RFC 5246, tickets in accordance with RFC 5077, PSK and tickets in accordance with RFC 8446 ].

**Application Note:** The ST author indicates which session resumption mechanisms are supported. One or both of the first two options, "session ID in accordance with RFC 5246" and "tickets in accordance with RFC 5077" are claimed for TLS 1.2 resumption. If resumption of TLS 1.3 sessions is supported, "PSK and tickets in accordance with RFC 8446" is selected, and the selection-

based SFR [FCS\\_TLSC\\_EXT.6](#) must also be claimed.

While it is possible to perform session resumption using PSK ciphersuites in TLS 1.2, this is uncommon. Validation of key exchange and session negotiation rules for PSK ciphersuites is independent of the source of the pre-shared key and is covered in [FCS\\_TLSC\\_EXT.1](#).

This SFR is claimed if "session resumption" is selected in [FCS\\_TLSC\\_EXT.1.1](#).

## Evaluation Activities ▼

### [FCS\\_TLSC\\_EXT.5](#)

#### **TSS**

*The evaluator shall examine the ST and confirm that the TLS client protocol description includes a description of the supported resumption mechanisms.*

#### **Guidance**

*The evaluator shall ensure the operational guidance describes instructions for any configurable features of the resumption mechanism.*

#### **Tests**

*The evaluator shall perform the following tests:*

- **Test 21.1:** For each supported TLS version and for each supported resumption mechanism that is supported for that version, the evaluator shall establish a new TLS session between the TSF and a compliant test TLS server that is configured to negotiate the indicated version and perform resumption using the indicated mechanism. The evaluator shall confirm that the TSF completes the initial TLS handshake and shall cause the TSF to close the session normally. The evaluator shall then cause the TSF to resume the session with the test TLS server using the indicated method and observe that the TSF successfully establishes the session.

**Note:** For each method, successful establishment refers to proper use of the mechanism, to include compliant extensions and behavior, as indicated in the referenced RFC.

- **Test 21.2:** (TLS 1.3 session id echo) [conditional] If the TSF supports TLS 1.3, the evaluator shall initiate a new TLS 1.3 session with a test TLS server. The evaluator shall cause the test TLS server to send a TLS 1.3 server hello message (or a hello retry request if the TSF doesn't include the key share extension) that contains a different value in the legacy\_session\_id field, and observe that the TSF terminates the session.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., illegal parameter) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

## FCS\_TLSC\_EXT.6 TLS Client TLS 1.3 Resumption Refinements

***The inclusion of this selection-based component depends upon selection in [FCS\\_TLSC\\_EXT.5.1](#).***

### FCS\_TLSC\_EXT.6.1

The TSF shall send a psk\_key\_exchange\_mode extension with the value psk\_dhe when TLS 1.3 session resumption is offered.

### FCS\_TLSC\_EXT.6.2

The TSF shall not send early data in TLS 1.3 sessions.

**Application Note:** This SFR is claimed when session resumption is supported for TLS 1.3. RFC 8446 allows pre-shared keys to be used directly and also allows early data to be protected using only the pre-shared key. This SFR refines the RFC to use PSK only with a supplemental DHE or ECDHE key exchange to ensure perfect forward secrecy for all sessions.

This SFR is claimed if "PSK and tickets in accordance with RFC 8446" is selected in [FCS\\_TLSC\\_EXT.5.1](#).

## Evaluation Activities ▼

### [FCS\\_TLSC\\_EXT.6](#)

#### **TSS**

*The evaluator shall examine the TSS to verify that the TLS client protocol description indicates*

that the PSK exchange requires DHE mode and prohibits sending early data. The evaluator shall examine the TSS to verify it lists all applications that can be secured by TLS 1.3 using pre-shared keys and describes how each TLS 1.3 client application ensures data for the application is not sent using early data.

### **Guidance**

The evaluator shall examine the operational guidance to verify that instructions for any configurable features that are required to meet the requirement are included. The evaluator shall ensure the operational guidance includes any instructions required to configure applications so the TLS 1.3 client implementation does not send early data.

### **Tests**

[conditional] For each application that is able to be secured via TLS 1.3 using PSK, the evaluator shall follow operational guidance to configure the application not to send early data. The evaluator shall cause the application to initiate a resumed TLS 1.3 session between the TSF and a compliant test TLS 1.3 server as in Test 1 of [FCS\\_TLSC\\_EXT.5](#). The evaluator shall observe that the TSF client hello for TLS 1.3 includes the `psk_mode` extension with the value `PSK_DHE` and sends a key share value for a supported group. The evaluator shall confirm that early data is not received by the test TLS server.

**Note:** If no applications supported by the TOE provide data to TLS 1.3 that can be sent using PSK, this test is omitted.

## **FCS\_TLSS\_EXT.1 TLS Server Protocol**

**The inclusion of this selection-based component depends upon selection in [FCS\\_TLS\\_EXT.1.1](#).**

### **FCS\_TLSS\_EXT.1.1**

The TSF shall implement TLS 1.2 (RFC 5246) and [**selection:** *TLS 1.3 (RFC 8446), no other TLS version* ] as a server that supports additional functionality for session renegotiation protection and [**selection:**

- *mutual authentication*
- *supplemental downgrade protection*
- *session resumption*
- *no optional functionality*

] and shall reject connection attempts from clients supporting only TLS 1.1, TLS 1.0, or SSL versions.

**Application Note:** These requirements will be revisited as new TLS versions are standardized by the IETF.

If "mutual authentication" is selected, then the ST must additionally include the requirements from [FCS\\_TLSS\\_EXT.2](#). If the TOE implements mutual authentication, this selection must be made.

If "session renegotiation protection" is selected, then the ST must additionally include the requirements from [FCS\\_TLSS\\_EXT.4](#). If the TOE implements session renegotiation, or if TLS 1.3 is supported, this selection must be made.

If "supplemental downgrade protection" is selected, then the ST must additionally include the requirements from [FCS\\_TLSS\\_EXT.3](#). If the TOE provides downgrade protection as indicated in RFC 8446, in particular, if TLS 1.3 is supported, this selection must be made.

If "session resumption" is selected, then the ST must additionally include the requirements from [FCS\\_TLSS\\_EXT.5](#).

### **FCS\_TLSS\_EXT.1.2**

The TSF shall be able to support the following TLS 1.2 ciphersuites: [**selection:**

- *TLS\_ECDHE\_ECDSA\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5289, RFC 8422*
- *TLS\_ECDHE\_RSA\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5289, RFC 8422*
- *TLS\_RSA\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5288*
- *TLS\_DHE\_RSA\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5288*
- *TLS\_ECDHE\_ECDSA\_WITH\_AES\_256\_CBC\_SHA384 as defined in RFC 5289*
- *TLS\_ECDHE\_RSA\_WITH\_AES\_256\_CBC\_SHA384 as defined in RFC 5289*
- *TLS\_RSA\_WITH\_AES\_256\_CBC\_SHA256 as defined in RFC 5246*
- *TLS\_DHE\_RSA\_WITH\_AES\_256\_CBC\_SHA256 as defined in RFC 5246*
- *TLS\_ECDHE\_ECDSA\_WITH\_AES\_128\_GCM\_SHA256 as defined in RFC 5289*

- *TLS\_ECDHE\_RSA\_WITH\_AES\_128\_GCM\_SHA256* as defined in RFC 5289
- *TLS\_ECDHE\_ECDSA\_WITH\_AES\_128\_CBC\_SHA256* as defined in RFC 5289
- *TLS\_ECDHE\_RSA\_WITH\_AES\_128\_CBC\_SHA256* as defined in RFC 5289
- *TLS\_RSA\_WITH\_AES\_128\_CBC\_SHA256* as defined in RFC 5246
- *TLS\_DHE\_RSA\_WITH\_AES\_128\_CBC\_SHA256* as defined in RFC 5246
- *TLS\_RSA\_WITH\_AES\_128\_CBC\_SHA* as defined in RFC 5246
- PP-specific ciphersuites using pre-shared secrets including **[selection:**
  - *TLS\_ECDHE\_PSK\_WITH\_AES\_256\_GCM\_SHA384* as defined in RFC 8442
  - *TLS\_DHE\_PSK\_WITH\_AES\_256\_GCM\_SHA384* as defined in RFC 5487
  - *TLS\_RSA\_PSK\_WITH\_AES\_256\_GCM\_SHA384* as defined in RFC 5487
  - *TLS\_ECDHE\_PSK\_WITH\_AES\_128\_GCM\_SHA256* as defined in RFC 8442
  - *TLS\_DHE\_PSK\_WITH\_AES\_128\_GCM\_SHA256* as defined in RFC 5487
  - *TLS\_RSA\_PSK\_WITH\_AES\_128\_GCM\_SHA256* as defined in RFC 5487
- ]
- the following TLS 1.3 ciphersuites: **[selection:**
  - *TLS\_AES\_256\_GCM\_SHA384* as defined in RFC 8446
  - *TLS\_AES\_128\_GCM\_SHA256* as defined in RFC 8446
  - **[assignment:** other TLS 1.3 ciphersuites]
- ]

] using a preference order based on **[selection:** RFC 9151 priority, client hello ordering, **[assignment:** additional priority] ]

**Application Note:** The ST author should select the ciphersuites that are supported and must select at least one ciphersuite for each TLS version supported. It is necessary to limit the ciphersuites that can be used in an evaluated configuration administratively on the server in the test environment. If administrative steps need to be taken so that the ciphersuites negotiated by the implementation are limited to those in this requirement, then the appropriate instructions need to be contained in the guidance.

The final selection indicates the TOE's preference for negotiating a ciphersuite. RFC 9151 indicates the required ciphersuites for NSS systems and 'RFC 9151 priority' is claimed if those ciphersuites are selected whenever offered by the client. In general, it is preferred that GCM ciphersuites are selected over CBC ciphersuites, ECDHE is selected over RSA and DHE, and SHA256 or SHA384 is selected over SHA1.

The 'client hello ordering' option is claimed if client priority is considered; if both are claimed, the ST author should indicate which is primary and which is secondary, and whether the priority scheme is configurable. If other priority schemes or if tertiary priority is used, the ST author will claim the third option and describe the scheme in the ST.

Support for *TLS\_RSA\_WITH\_AES\_128\_CBC\_SHA* is not required despite being mandated by RFC 5246.

#### FCS\_TLSS\_EXT.1.3

The TSF shall not establish a connection with a client that does not indicate support for at least one of the supported ciphersuites.

#### FCS\_TLSS\_EXT.1.4

The TSF shall be able to process the following TLS client hello message extensions:

- signature\_algorithms extension (RFC 8446) indicating support for **[selection:**
  - *ecdsa-secp384r1\_sha384* (RFC 8446)
  - *rsa\_psk1\_sha384* (RFC 8446)
- ], and **[selection:**
  - *rsa\_pss\_pss\_sha384* (RFC 8603)
  - *rsa\_pss\_rsae\_sha384* (RFC 8603)
  - **[assignment:** other non-deprecated signature algorithms]
  - no other signature algorithms
- ]
- extended\_master\_secret extension (RFC 7627) enforcing client support
- the following other extensions: **[selection:**
  - signature\_algorithms\_cert extension (RFC 8446) indicating support for **[selection:**
    - *ecdsa-secp384r1\_sha384* (RFC 8446)
    - *rsk\_psk1\_sha384* (RFC 8446)



], and **[selection:**

- *rsa\_pss\_pss\_sha384 (RFC 8603)*
- *rsa\_pss\_rsae\_sha384 (RFC 8603)*
- *rsa\_pkcs1\_sha256 (RFC 8446)*
- *rsa\_pss\_rsae\_sha256 (RFC 8446)*
- **[assignment:** *other non-deprecated signature algorithms*
- *no other signature algorithms*

]

- *supported\_versions extension (RFC 8446) indicating support for TLS 1.3*
- *supported\_groups extension (RFC 7919, RFC 8446) indicating support for [selection:*
  - *secp256r1*
  - *secp384r1*
  - *secp521r1*
  - *ffdhe2048(256)*
  - *ffdhe3072(257)*
  - *ffdhe4096(258)*
  - *ffdhe6144(259)*
  - *ffdhe8192(260)*

]

- *key\_share extension (RFC 8446)*
- *no other extensions*

].

**Application Note:** If support for TLS 1.3 is claimed in [FCS\\_TLSS\\_EXT.1.1](#), the selections for supported\_versions, supported\_groups, and key\_share are claimed. Even if support for TLS 1.3 is not claimed, if ECDHE ciphersuites are claimed in [FCS\\_TLSS\\_EXT.1.4](#), the entry for supported\_groups is claimed. Support for additional extensions is acceptable. For signature\_algorithms and signature\_algorithms\_certs (if supported), at least one of the signature schemes presented in the first sub-selection is claimed.

#### FCS\_TLSS\_EXT.1.5

The TSF shall perform key establishment for TLS using **[selection:**

- *RSA with size [selection: 2048 bits, 3072 bits, 4096 bits ] and no other sizes*
- *Diffie-Hellman parameters with size [selection: 2048 bits, 3072 bits, 4096 bits, 6144 bits, 8192 bits ] and no other sizes*
- *Diffie-Hellman groups [selection: ffdhe2048, ffdhe3072, ffdhe4096, ffdhe6144, ffdhe8192 ] and no other groups, consistent with the client's supported groups extension and [selection: key share, no other ] extension*
- *ECDHE parameters using elliptic curves [selection: secp256r1, secp384r1, secp521r1 ] and no other curves, consistent with the client's supported groups extension and [selection: key share, no other ] extension and using non-compressed formatting for points*

].

**Application Note:** TLS 1.2 and TLS 1.3 perform key exchange using different mechanisms. In TLS 1.2, the requirements apply to the key exchange messages received by the server and optionally (for DHE or ECDHE ciphersuites) sent by the server. In TLS 1.3, the requirements apply to the values of the key share extension contained in the client and server hello messages. The options depend on the supported ciphersuites. For each session, the key exchange method is consistent with the selected ciphersuite (TLS 1.2), the supported groups extension (TLS 1.3 and conditionally, TLS 1.2), or the key share extension (TLS 1.3).

If the ST lists an RSA ciphersuite in [FCS\\_TLSS\\_EXT.1.1](#), the ST must include the RSA selection in the requirement.

If the ST lists a DHE ciphersuite in [FCS\\_TLSS\\_EXT.1.2](#), the ST must include the Diffie-Hellman selection for parameters of a certain size, the Diffie-Hellman groups selection in support of TLS 1.2 exchanges, or both. The selection for "Diffie-Hellman parameters" refers to the method defined by RFC 5246, section 7.4.3 where the server provides Diffie-Hellman parameters to the client. The "Diffie-Hellman groups" selection indicates key exchange negotiation in accordance with RFC 7919 using the supported groups extension. RFC 7919 identifies particular Diffie-Hellman groups, which are listed in the following selection. This option is the preferred mechanism for TLS 1.2, and must be claimed if TLS 1.3 DHE ciphersuites are supported.

If the ST lists an ECDHE ciphersuite in [FCS\\_TLSS\\_EXT.1.2](#), the ST must include the selection for ECDHE using elliptic curves in the requirement, consistent with the support indicated for the supported groups extension in [FCS\\_TLSS\\_EXT.1.4](#).

When TLS 1.3 is negotiated (if supported), the supported group negotiated (a supported DHE or ECDHE group) agrees with one of the client's supported groups and the supplied key share element, and the product's key share element is a member of the selected group. If the TLS 1.3 client does not initially provide a key share element for a group supported by both the product and the client, the TOE is expected to send a hello retry request message indicating the selected group; the requirement for matching the group indicated in the client's hello message applies to the client's hello message received in response to the hello retry request message.

This SFR is claimed if "TLS as a server" is selected in [FCS\\_TLS\\_EXT.1.1](#).

## Evaluation Activities ▼

### [FCS\\_TLSS\\_EXT.1](#)

#### **TSS**

*The evaluator shall check the description of the implementation of this protocol in the TSS to ensure the supported TLS versions, features, ciphersuites, and extensions, are specified in accordance with RFC 5246 (TLS 1.2) and RFC 8446 (TLS 1.3 and updates to TLS 1.2) as appropriate. The evaluator shall check the description to see if beta TLS 1.3 versions are supported.*

*The evaluator shall verify that ciphersuites indicated in [FCS\\_TLSS\\_EXT.1.2](#) are included in the description, and that none of the following ciphersuites are supported: ciphersuites indicating 'NULL,' 'RC2,' 'RC4,' 'DES,' 'IDEA,' or 'TDES' in the encryption algorithm component, indicating 'anon,' or indicating MD5 or SHA in the message digest algorithm component.*

*The evaluator shall verify that the TLS implementation description includes the extensions as required in [FCS\\_TLSS\\_EXT.1.4](#).*

*The evaluator shall confirm that the TLS description includes the number and types of certificates that can be installed to represent the TOE.*

#### **Guidance**

*The evaluator shall check the operational guidance to ensure that it contains instructions on configuring the product so that the TSF conforms to the requirements. If the ST indicates that beta versions of TLS 1.3 are supported for backward compatibility, the evaluator shall ensure that the operational guidance provides instructions for disabling these versions.*

*The evaluator shall review the operational guidance to ensure instructions on installing certificates representing the TOE are provided.*

#### **Tests**

*The evaluator shall perform the following tests:*

- **Test 22.1:** (supported TLS 1.2 configurations) *The evaluator shall perform the following tests:*
  - **Test 23.1.1:** *For each supported TLS 1.2 ciphersuite, the evaluator shall send a compliant TLS 1.2 client hello with the highest version or legacy version of 1.2 (value '03 03'), a single entry in the ciphersuites field consisting of the specific ciphersuite, and no supported version extension or key share extension. The evaluator shall observe the TSF's server hello indicates TLS 1.2 in the highest version or legacy version field, does not include a supported version or key share extension, and indicates the specific ciphersuite in the ciphersuite field. If the ciphersuite requires certificate-based authentication, the evaluator shall observe that the TSF sends a valid certificate representing the TOE and successfully completes the TLS handshake.*

**Note:** The ciphersuites TLS\_ECDHE\_PSK\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 8442, TLS\_DHE\_PSK\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5487, TLS\_ECDHE\_PSK\_WITH\_AES\_128\_GCM\_SHA256 as defined in RFC 8442, and TLS\_DHE\_PSK\_WITH\_AES\_128\_GCM\_SHA256 as defined in RFC 5487, if supported, do not require certificate-based authentication of the server.
  - **Test 23.1.2:** (TLS 1.2 support for TLS 1.3 clients) [conditional] *If the TSF is configurable to support only TLS 1.2 (or if TLS 1.3 is not supported), and if the TSF supports DHE or ECDHE ciphersuites, the evaluator shall follow any operational guidance instructions necessary to configure the TSF to only support TLS 1.2. For each supported TLS 1.2 ciphersuite with DHE or ECDHE indicated as the key exchange method, the evaluator shall send a client hello with the highest version or legacy version of 1.2 (value '03 03'), a list of ciphersuites consisting of one or more TLS 1.3 ciphersuites followed by the specific TLS 1.2 ciphersuite and no other TLS 1.2 ciphersuites in the ciphersuites field, and including a TLS 1.3 supported group and key*

share extension with consistent values. The evaluator shall observe that the TSF's server hello indicates TLS 1.2 in the highest version or legacy version field, does not include a supported version or key share extension, and indicates the specific TLS 1.2 ciphersuite in the ciphersuite field. The evaluator shall observe that the TSF completes the TLS 1.2 handshake successfully.

**Note:** Supported ciphersuites using RSA key exchange should not be included in this test. The supported groups extension sent by the test TLS client should be consistent with the TLS 1.2 ciphersuite (e.g., it should be an EC group if the ciphersuite is ECDHE).

- **Test 23.1.3:** (TLS 1.3 support) [conditional] If the TSF supports TLS 1.3, then for each supported TLS 1.3 ciphersuite and key exchange group, the evaluator shall send a compliant TLS 1.3 client hello indicating a list of one or more TLS 1.2 ciphersuites followed by the specific TLS 1.3 ciphersuite and no other ciphersuites in the ciphersuites field, a supported version extension indicating TLS 1.3 (value '03 04') only, a supported groups extension indicating the selected group, and a key share extension containing a value representing an element of the specific group. The evaluator shall observe the TSF's server hello contains the supported versions extension indicating TLS 1.3, the specific ciphersuite in the selected ciphersuite field, and a key share extension containing an element of the specific supported group. The evaluator shall observe that the TSF completes the TLS 1.3 handshake successfully.

**Note:** The connections in Test 1 may be established as part of the establishment of a higher-level protocol, e.g., as part of an EAP session.

It is sufficient to observe the successful negotiation of a ciphersuite to satisfy the intent of the test; it is not necessary to examine the characteristics of the encrypted traffic in an attempt to discern the ciphersuite being used (for example, that the cryptographic algorithm is 128-bit AES and not 256-bit AES).

It is not necessary to pair every supported ciphersuite with every supported group. It is sufficient to use a set of ciphersuite and supported group pairs such that each ciphersuite and each supported group are included in this set.

TLS 1.3 includes the supported\_groups extension in the encrypted\_extensions message. This message may be observed at the test client after it is decrypted to help verify the key\_share is actually a member of the supported group requested.

- **Test 23.2:** (obsolete versions) The evaluator shall perform the following tests:
  - **Test 24.2.1:** For each of SSL version 2, SSL version 3, TLS version 1.0, and TLS version 1.1, the evaluator shall send a client hello to the TSF indicating the selected version as the highest version. The evaluator shall observe the TSF terminates the connection.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., protocol version, insufficient security) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

- **Test 24.2.2:** The evaluator shall follow the operational guidance to configure the TSF to ensure any supported beta TLS 1.3 versions are disabled, as necessary. The evaluator shall send the TSF a client hello message indicating the supported version (referred to as the legacy version for TLS 1.3) with the value '03 04' and observe that the TSF responds with a server hello indicating the highest version supported.

**Note:** Test 2.2 is intended to test the TSF response to non-standard versions, including beta versions of TLS 1.3. If the TSF supports such beta versions, the evaluator shall follow the operational guidance instructions to disable them prior to conducting Test 2.2.

Some TLS 1.3 implementations ignore the legacy version field and only check for the supported\_versions extension to determine TLS 1.3 support by a client. It is preferred that the legacy version field should still be set to a standard version ('03 03') in the server hello, but it is acceptable that presence of the supported\_versions indicating TLS 1.3 (value '03 04') overrides the legacy\_version indication to determine highest supported version.

- **Test 24.3:** (ciphersuites) The evaluator shall perform the following tests on handling unexpected ciphersuites using a test TLS client sending handshake messages compliant with the negotiated version except as indicated in the test:

- **Test 25.3.1:** (ciphersuite not supported) For each supported version, the evaluator shall follow the operational guidance, if available, to configure the TSF to disable a supported ciphersuite. The evaluator shall send a compliant client hello to the TSF indicating support for the specific version and a ciphersuites field containing this single disabled ciphersuite. The evaluator shall observe that the TOE rejects the connection.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., handshake failure) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).



If the TSF's ciphersuites are not configurable, it is acceptable to use a named ciphersuite from the IANA TLS protocols associated with the tested version. Additional special cases of this test for special ciphersuites are performed separately.

- **Test 25.3.2:** (version confusion) For each supported version, the evaluator shall send a client hello that is compliant for the specific version that includes a list of ciphersuites consisting of a single ciphersuite not associated with that version. The evaluator shall observe that the TOE rejects the connection.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., handshake failure) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

It is preferred that Test 3.2 use TLS 1.3 ciphersuites for a server negotiating TLS 1.2. If TLS 1.3 is supported, Test 3.2 also includes a server negotiating TLS 1.3 with a TLS 1.2 ciphersuite – in this case, the negotiated ciphersuite should be chosen to be one supported by the TOE if negotiating TLS 1.2. If the TOE is configurable to allow both TLS 1.2 and TLS 1.3 clients (or does so by default), this configuration is used for both the TLS 1.2 and TLS 1.3 iteration of this test; otherwise the TOE is configured to support the negotiated version in each iteration.

- **Test 25.3.3:** (null ciphersuite) For each supported version, the evaluator shall send a client hello indicating support for the version and include a ciphersuite list consisting of only the null ciphersuite (TLS\_NULL\_WITH\_NULL\_NULL, with the value '00 00') and observe that the TOE rejects the connection.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., handshake failure, insufficient security) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

- **Test 25.3.4:** (anon ciphersuite) The evaluator shall send the TSF a TLS 1.2 handshake that is compliant, except that the ciphersuites field includes a ciphersuite list consisting only of ciphersuites using the anonymous server authentication method and observe that the TOE rejects the connection.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., handshake failure, insufficient security) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

See IANA TLS parameters for available ciphersuites to be included in the client hello. The test ciphersuites list should include ciphersuites using supported cryptographic algorithms in as many of the other components as possible. For example, if the TSF supports the ciphersuite TLS\_ECDHE\_ECDSA\_WITH\_AES\_256\_GCM\_SHA384, the evaluator should include TLS\_DH\_ANON\_WITH\_AES\_256\_GCM\_SHA\_384.

- **Test 25.3.5:** (deprecated encryption algorithm) The evaluator shall send the TSF a TLS 1.2 client hello that is compliant, except that the ciphersuites field is a list consisting only of ciphersuites indicating a deprecated encryption algorithm, including at least one each of NULL, RC2, RC4, DES, IDEA, and TDES. The evaluator shall observe that the TOE rejects the connection.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., handshake failure, insufficient security) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

See IANA TLS parameters for available ciphersuites to be included. The test ciphersuite should use supported cryptographic algorithms for as many of the other components as possible. For example, if the TSF supports TLS\_ECDHE\_ECDSA\_WITH\_AES\_256\_GCM\_SHA384, the test could include TLS\_ECDHE\_PSK\_WITH\_NULL\_SHA\_384, TLS\_RSA\_EXPORT\_WITH\_RC2\_CBC\_40\_MD5, TLS\_ECDHE\_RSA\_WITH\_RC4\_128\_SHA, TLS\_DHE\_DSS\_WITH\_DES\_CBC\_SHA, TLS\_RSA\_WITH\_IDEA\_CBC\_SHA, and TLS\_ECDHE\_RSA\_WITH\_3DES\_EDE\_CBC\_SHA.

- **Test 25.4:** (extensions)

- **Test 26.4.1:** (signature algorithms) [conditional] If the TSF supports certificate-based authentication, then for each supported signature algorithm indicated in the ST, the evaluator shall perform the following sub-tests with certificates that represent the TOE. For each sub-test, the evaluator shall establish a to-be-signed certificate representing the TOE using a public-private key pair suitable for the specific signature algorithm value, and request that the certificate from a certification authority that uses the same signature algorithm, in accordance with FIA\_X509\_EXT.3.

*the reference to FIA\_X509\_EXT.3 implies that any PP or module that uses this package must have the ability to generate its own CSRs (either as part of the TOE or its underlying platform), unsure if this is intended or if it will be permissible to load a cert issued by a CA.*

If the TSF also supports the signature\_algorithms\_cert extension, then for each value of the signature\_algorithms\_cert extension, the evaluator shall repeat the sub-tests using a to-be-signed certificate using a key pair consistent with the signature

algorithm, with a certificate obtained from a certification authority that signs certificates using the specific value of the signature\_algorithm\_cert extension.

**Note:** The TSF supports certificate-based server authentication if the TLS 1.2 supported ciphersuites include ciphersuites other than TLS\_ECDHE\_PSK\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 8442, TLS\_DHE\_PSK\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5487, TLS\_ECDHE\_PSK\_WITH\_AES\_128\_GCM\_SHA256 as defined in RFC 8442, and TLS\_DHE\_PSK\_WITH\_AES\_128\_GCM\_SHA256 as defined in RFC 5487. If these are the only supported ciphersuites, this test is omitted. For TLS 1.3, certificate-based server authentication, the client hello should not include the PSK extension.

The evaluator shall follow operational guidance instructions to provision the TSF with one or more of these certificates as indicated in the following sub-tests:

- **Test 27.4.1.1:** (TLS 1.2) For each supported value of the signature\_algorithm extension, the evaluator shall provision a certificate with a key pair compatible with the specific signature\_algorithm value and send the TSF a TLS 1.2 client hello that indicates all supported ciphersuites and has a signature\_algorithm extension consisting of a single value matching the specific signature\_algorithm.

If the TSF supports signature\_algorithms\_cert extension, the client hello also contains the value consistent with the provisioned certificate.

The evaluator shall observe that the TSF negotiates TLS 1.2 with a TLS 1.2 ciphersuite that is compatible with the signature algorithm, and that it sends a certificate message containing the provisioned certificate with a key pair that is consistent with the specific signature\_algorithm value (and signed using the signature\_algorithms\_cert extension value, if supported).

**Note:** For TLS 1.2, the ciphersuite describes the signature algorithm as RSA or ECDSA and is compatible with the certificate used if the signature algorithm component of the ciphersuite is of the same type as the signature value of the signature\_algorithm extension.

- **Test 27.4.1.2:** [conditional] If the TSF supports TLS 1.3, then for each supported value of the signature\_algorithm, the evaluator shall provision a certificate with a key pair that is compatible with the specific signature\_algorithm value, send a TLS 1.3 client hello that indicates a supported ciphersuite and has a signature\_algorithm extension consisting of a single value matching the specific signature\_algorithm.

If the TSF supports the signature\_algorithms\_cert extension, the client hello also contains a signature\_algorithms\_cert extension with a value consistent with the provisioned certificate.

The evaluator shall observe that the TSF sends a certificate message containing the provisioned certificate consistent with the specific signature\_algorithm value (and signed using the signature\_algorithms\_cert extension value) and a certificate verify message using the signature\_algorithm extension value.

**Note:** For TLS 1.3, the certificate message and certificate verify is encrypted. The evaluator confirms the values of these messages as received at the test TLS client, using logs, or using a test TLS client designed to expose the certificates after they are decrypted.

It is not necessary to manually verify the signature used in the key exchange message (TLS 1.2) or certificate verify message (TLS 1.3).

- **Test 27.4.1.3:** [conditional] If the ST indicates that the TSF supports provisioning of multiple certificates, the evaluator shall repeat Test 4.1.1 with both the provisioned certificate indicated for Test 4.1.1 (and 4.1.2 if TLS 1.3 is supported) and a certificate that does not match the signature\_algorithm value. The evaluator shall observe that the certificate message (for TLS 1.2) does not include the certificate that does not match the signature\_algorithm value (and signature\_algorithms\_cert value if supported) in the client hello.

[JF] Per SME, this test has issues with TLS 1.3 and will need updates

- **Test 27.4.1.4:** (TLS 1.2) The evaluator shall provision a certificate as in Test 4.1.1 but shall send a client hello that only offers ciphersuites whose signature component does not match the value of the signature\_algorithm extension. The evaluator shall observe that the TSF terminates the handshake.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., handshake failure, illegal parameter) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

- **Test 27.4.2:** (extended master secret): The evaluator shall initiate a TLS 1.2 session with the TSF from a test TLS client for which the client hello does not include the extended master secret extension and observe that the TSF terminates the session.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., handshake error) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

- **Test 27.5:** (key exchange) The evaluator shall perform the following tests to confirm compliant key exchange:
  - **Test 28.5.1:** (TLS 1.2 RSA key exchange) [conditional] If any of the supported TLS 1.2 ciphersuites in the ST includes RSA for the key exchange method, the evaluator shall perform the following sub-tests:
    - **Test 29.5.1.1:** For each supported RSA key size, the evaluator shall provision the TSF with a valid certificate that has an RSA public key of that size. The evaluator shall initiate a valid TLS 1.2 handshake from a compliant test TLS 1.2 client and observe that the server certificate message matches the provisioned certificate.
    - **Test 29.5.1.2:** For each supported RSA key size, the evaluator shall send the TSF a compliant TLS 1.2 client hello, but in place of the client's key exchange message, the evaluator shall send the TSF a (non-compliant) Key Exchange message that is properly formatted but uses an invalid EncryptedPreMasterSecret field in the TLS handshake (e.g., modify a byte of a properly computed value). The evaluator shall attempt to complete the handshake using compliant client change cipher spec and finished messages and verify that the TSF terminates the handshake in a manner that is indistinguishable from a finished message error and does not send application data.

**Note:** Mitigations for oracle attacks described in RFC 5246 Appendix D require the TSF to exhibit the same behavior for key exchange failures as it does for finished message failures. It is preferred that the TSF send a fatal decrypt failure error alert at the end of the handshake in both this case and for a finished message error, but it is acceptable that the TSF terminate the session with another error alert, or without sending an error alert in either case. If the failure error alert is not for a decryption failure, the evaluator shall note that the TSF's response agrees with the response observed in the TLS 1.2 iteration of Test 5.2.

- **Test 29.5.2:** For each supported version, the evaluator shall initiate a compliant handshake up through the (implied for TLS 1.3) change cipher spec message. The evaluator shall then send a (non-compliant) client finished handshake message with an invalid 'verify data' value and verify that the server terminates the session and does not send any application data.

**Note:** TLS 1.2 handshakes include explicit change cipher spec messages, but TLS 1.3 omits the change cipher spec message. If TLS 1.3 is supported, the modified finished message is sent as the final message from the client after receiving the server's second flight of handshake messages {encrypted extensions, (new ticket), (certificate, certificate verify), (certificate request)}.

It is preferred that the TSF send a fatal decryption failure error alert, but it is acceptable that the TSF terminate the session using another error alert or without sending an error alert.

The finished message is encrypted. The invalid 'verify data' can be constructed by modifying a byte of a compliant finished message payload.

- **Test 29.5.3:** (TLS 1.2 DHE or ECDHE key exchange) [conditional] If the ST indicates support for DHE or ECDHE ciphersuites for TLS 1.2, then the evaluator shall perform the following sub-tests:
  - **Test 30.5.3.1:** [conditional] If the TSF supports DHE ciphersuites and supports DHE parameters that are not specified in the supported groups extension, then for each supported DHE parameter set, the evaluator shall follow the operational guidance to configure the TSF to use the DHE parameters in its key exchange. The evaluator shall then initiate a TLS 1.2 handshake from a test client with a client hello indicating a single DHE ciphersuite. The evaluator shall observe that the TSF key exchange message indicates the configured parameters and ensure that the client key exchange is a valid point for the parameter set. The evaluator shall confirm that the TSF successfully completes the session.

The evaluator shall close the session and resend the client hello. After the TSF responds with a valid key exchange message, the evaluator shall send an empty client key exchange message and observe that the TSF terminates the session.
  - Note:** It is preferred that the TSF sends a fatal error alert message (e.g., decryption failure, illegal parameter, handshake error) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).
  - **Test 30.5.3.2:** [conditional] If the TSF supports DHE ciphersuites and supports DHE groups in the supported groups extension, then for each supported DHE group, the evaluator shall send the TSF a compliant TLS 1.2 client hello indicating a single ciphersuite that is compatible with the group and indicating the group in the supported groups extension. The evaluator shall observe that the TSF



negotiates TLS 1.2 using the indicated ciphersuite and that the server key exchange message indicates the specific group. The evaluator shall send the TOE a client key exchange with a valid point in the group and observe that the TSF successfully completes the session.

The evaluator shall close the session and resend the client hello. After the TSF responds with a valid key exchange message, the evaluator shall send the TSF a client key exchange with the public key value '0.' The evaluator shall observe that the TSF terminates the session.

The evaluator shall send a new client hello including the same ciphersuite but indicating a group not supported by the TSF in the supported groups extension. The evaluator shall observe that the TSF terminates the session.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., decryption failure, illegal parameter, handshake error) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

- **Test 30.5.3.3:** [conditional] If the TSF supports ECDHE ciphersuites (and therefore supports ECDHE groups in the supported groups extension), the evaluator shall send a client hello message indicating a single supported ECDHE ciphersuite and including the supported ECDHE group in the supported groups extension. The evaluator shall observe that the TSF sends a key exchange message with a valid point of the specified group. The evaluator shall send the TSF a client key exchange message to the TSF consisting of a valid element in the supported group and observe that the TSF successfully completes the session.

The evaluator shall close the session and resend the client hello. After the TSF sends the valid key exchange message, the evaluator shall send a client key exchange message consisting of an invalid element of the supported group and observe that the TSF terminates the handshake.

The evaluator shall send a third client hello to the TSF indicating the supported ECDHE ciphersuite and including an ECDHE group that is not supported. The evaluator shall observe that the TSF terminates the session.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., decryption failure, illegal parameter, handshake error, insufficient security) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

An invalid ECDSA point consists of properly formatted x and y components, but for which the equation of the curve is not satisfied. To obtain an invalid point, the evaluator can modify a byte of the y coordinate value of a valid point and confirm that the point is not on the curve.

The IANA TLS parameters website lists registered ECDHE groups for use in selecting a non-supported group. If the TSF supports all registered ECDHE groups, it is acceptable to send the client hello without a supported groups extension. The TSF should reject such a client hello, but it is acceptable for the TSF to default to a supported group. In this case, the TSF passes the test.

- **Test 30.5.4:** (TLS 1.3 key exchange) [conditional] If the TSF supports TLS 1.3, then for each supported group the evaluator shall perform the following sub-tests:
  - **Test 31.5.4.1:** The evaluator shall send the TSF a compliant TLS 1.3 client hello indicating a single key share value from the supported group and shall observe that the server hello includes valid elements of the supported group.
  - **Test 31.5.4.2:** The evaluator shall send the TSF a TLS 1.3 client hello indicating a supported groups value supported by the TSF but containing a key share extension indicating an element claiming to be in the supported group that does not represent a valid element of the group. The evaluator shall observe that the TSF terminates the session.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., illegal parameter, handshake failure, decryption failure) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

For DHE groups, the invalid element may be of the wrong length; for ECDHE groups, the invalid element has coordinates (x and y) that do not satisfy the equation of the elliptic curve. To obtain an invalid ECDHE point, the evaluator can modify a byte of the y coordinate value of a valid point and confirm that the point is not on the curve.

- **Test 31.5.5:** For each supported version, the evaluator shall initiate a TLS handshake from a test TLS client with compliant handshake messages negotiating the version and supported parameters to include the change cipher spec message (implied for TLS 1.3), but which omits the finished message and instead sends an application message containing random data. The evaluator shall observe that the TSF terminates the

connection.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., decryption failure) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

Application data is indicated by the TLSCipherText ContentType field having value 23 (application data). The legacy record version '03 03' and length fields should match a valid TLSCipherText message of the same size.

### FCS\_TLSS\_EXT.3 TLS Server Downgrade Protection

**The inclusion of this selection-based component depends upon selection in [FCS\\_TLSS\\_EXT.1.1](#).**

#### FCS\_TLSS\_EXT.3.1

The TSF shall set the server hello extension to a random value concatenated with the TLS 1.2 downgrade indicator when negotiating TLS 1.2 as indicated in RFC 8446 section 4.1.3.

**Application Note:** This SFR is claimed if the TSF supports TLS 1.3. RFC 8446 requires both the TLS 1.2 downgrade indicator as well as an indicator for TLS 1.1 and below. This FP requires the server to reject attempts to establish TLS 1.1 and below, making this mechanism redundant. However, products may still implement both indicators to be compliant with the RFC.

This SFR is claimed if "supplemental downgrade protection" is selected in [FCS\\_TLSS\\_EXT.1.1](#).

### Evaluation Activities ▼

#### [FCS\\_TLSS\\_EXT.3](#)

##### **TSS**

The evaluator shall examine the ST and confirm that the TLS description includes details on the session downgrade protections that are supported.

##### **Guidance**

The evaluator shall examine the operational guidance to confirm that instructions are included to configure the TSF to support only TLS 1.3 and to provide the associated downgrade indications.

##### **Tests**

The evaluator shall follow the operational guidance as necessary to configure the TSF to negotiate only TLS 1.3 and to provide the associated downgrade indications. The evaluator shall send a TLS client hello to the TOE that indicates support for only TLS 1.2. The evaluator shall observe that the TSF sends a server hello with the last eight bytes of the server random value equal to 44 4F 57 4E 47 52 44 01.

### FCS\_TLSS\_EXT.4 TLS Server Support for Renegotiation

**The inclusion of this selection-based component depends upon selection in [FCS\\_TLS\\_EXT.1.1](#).**

#### FCS\_TLSS\_EXT.4.1

The TSF shall support secure renegotiation through the use of [**selection:** the "renegotiation\_info" TLS extension, not allowing session renegotiation ] in accordance with RFC 5746.

#### FCS\_TLSS\_EXT.4.2

The TSF shall, when negotiating a TLS 1.2 session, [**selection:** include the renegotiation\_info extension in ServerHello messages when a client hello with the renegotiation\_info extension is received and shall terminate a session if neither of the renegotiation\_info or TLS\_EMPTY\_RENEGOTIATION\_INFO\_SCSV signaling ciphersuites are indicated in the client hello, not allow renegotiation ].

#### FCS\_TLSS\_EXT.4.3

The TSF shall terminate the session if an unexpected client hello is received during an active TLS session.

**Application Note:** RFC 5746 defines an extension to TLS 1.2 that binds renegotiation handshakes to the cryptography in the original handshake. As a refinement of the RFC, servers that support renegotiation and negotiating TLS 1.2 will terminate a session if neither of the methods described in RFC 5746 are offered by the client. RFC 5746 indicates that a server negotiating TLS 1.2 is required to terminate the session if the conditions for secure renegotiation are not met. Alternatively, a TLS server may negotiate TLS 1.2 without any RFC 5746 client renegotiation indicators if it always terminates an existing session when a new client hello is received, similar to the implementation of TLS 1.3.

TLS 1.3 does not allow renegotiation. Termination, as indicated in [FCS\\_TLSS\\_EXT.4.3](#), covers TLS 1.3 sessions as well as TLS 1.2 sessions where the client hello received does not comply with RFC 5746, or when configured to reject renegotiation (if the product is configurable).

This SFR is claimed if "TLS as a server" is selected in [FCS\\_TLS\\_EXT.1.1](#).

## Evaluation Activities ▼

### [FCS\\_TLSS\\_EXT.4](#)

#### **TSS**

*The evaluator shall examine the ST to confirm that the TLS description includes details on session renegotiation protection methods supported, to include when renegotiation is prohibited.*

#### **Guidance**

*The evaluator shall examine the operational guidance to confirm that any instructions that are needed to meet the requirements are included. If support for TLS 1.2 is configurable to use RFC 5746 methods or to deny renegotiation, the evaluator shall ensure that the operational guidance includes instructions for configuring the TSF in this manner.*

#### **Tests**

*The evaluator shall perform the following tests, as indicated for each version supported, using a test TLS client able to construct the indicated messages and expose messages received from the TSF:*

- **Test 32.1:** (RFC 5746 compliant TLS 1.2 initial handshake) [conditional] *If the TSF supports renegotiation, the evaluator shall follow the operational guidance as necessary to configure the TSF to enforce RFC 5746 methods. The evaluator shall initiate a TLS 1.2 session from a test TLS client for each of the following sub-tests:*
  - **Test 33.1.1:** *The evaluator shall send an initial client hello without the renegotiation\_info extension and without including the signaling ciphersuite value, TLS\_EMPTY\_RENEGOTIATION\_INFO\_SCSV. The evaluator shall observe that the TSF terminates the session.*

**Note:** *It is preferred that the TSF sends a fatal error alert message (e.g., handshake failure) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).*
  - **Test 33.1.2:** *The evaluator shall send an initial client hello with the renegotiation\_info extension indicating a renegotiated\_connection length greater than zero. The evaluator shall observe that the TSF terminates the session.*

**Note:** *It is preferred that the TSF sends a fatal error alert message (e.g., handshake failure) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).*
- **Test 33.2:** (renegotiation attempt) *For each of the following sub-tests, the evaluator shall establish a compliant TLS channel with an initial handshake that uses the indicated secure renegotiation method for the version indicated. Without closing the session, the evaluator shall send a second client hello within the channel specific to the version as indicated:*
  - **Test 34.2.1:** [conditional] *If the TSF allows renegotiation, the evaluator shall configure the TSF to support RFC 5746 methods, send an initial handshake with a valid renegotiation extension, send a new TLS 1.2 client hello on the TLS 1.2 channel containing the renegotiation\_info extension indicating valid client\_verify\_data, and observe the TSF successfully completes the handshake.*
  - **Test 34.2.2:** [conditional] *If the TSF allows renegotiation, the evaluator shall send an initial client hello containing a valid renegotiation extension, send a new TLS 1.2 client hello on the TLS 1.2 channel with the signaling ciphersuite value, TLS\_EMPTY\_RENEGOTIATION\_INFO\_SCSV, and observe that the TSF terminates the session.*

**Note:** *It is preferred that the TSF sends a fatal error alert message (e.g., handshake failure) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).*
  - **Test 34.2.3:** [conditional] *If the TSF allows renegotiation, for each TLS 1.2*

renegotiation method claimed in accordance with RFC 5746, the evaluator shall send an initial client hello indicating the method, send a new TLS 1.2 client hello on the TLS 1.2 channel without a renegotiation\_info extension, and observe that the TSF terminates the session.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., unexpected message) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

- **Test 34.2.4:** [conditional]: If the TSF allows renegotiation, for each TLS 1.2 renegotiation method claimed in accordance with RFC 5746, the evaluator shall send an initial client hello indicating the method, send a new TLS 1.2 client hello on the TLS 1.2 channel with a renegotiation\_info extension indicating an invalid client\_verify\_data value (modify a byte of a valid value), and observe that the TSF terminates the session.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., unexpected message) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

- **Test 34.2.5:** [conditional] If the TSF supports TLS 1.3, or if the TSF rejects renegotiation for TLS 1.2, then for each such version, the evaluator shall follow the operational guidance as necessary to configure the TSF to negotiate the version and reject renegotiation. The evaluator shall initiate a valid initial session for the specified version, send a valid client hello on the non-renegotiable TLS channel, and observe that the TSF terminates the session.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., unexpected message) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

## FCS\_TLSS\_EXT.5 TLS Server Support for Session Resumption

**The inclusion of this selection-based component depends upon selection in [FCS\\_TLSS\\_EXT.1.1](#).**

### FCS\_TLSS\_EXT.5.1

The TSF shall support session resumption as a server via the use of [**selection:** session ID in accordance with RFC 5246, tickets in accordance with RFC 5077, PSK and tickets in accordance with RFC 8446 ].

**Application Note:** The ST author indicates which session resumption mechanisms are supported. One or both of the first two options, "session ID in accordance with RFC 5246" and "tickets in accordance with RFC 5077" are claimed for TLS 1.2 resumption. If resumption of TLS 1.3 sessions is supported, "PSK and tickets in accordance with RFC 8446" is selected, and the selection-based SFR [FCS\\_TLSS\\_EXT.6](#) must also be claimed.

While it is possible to perform session resumption using PSK ciphersuites in TLS 1.2, this is uncommon. Validation of key exchange and session negotiation rules for PSK ciphersuites is independent of the source of the pre-shared key and is covered in [FCS\\_TLSS\\_EXT.1](#).

This SFR is claimed if "session resumption" is selected in [FCS\\_TLSS\\_EXT.1.1](#).

## Evaluation Activities ▼

### [FCS\\_TLSS\\_EXT.5](#)

#### TSS

The evaluator shall examine the ST and confirm that the TLS server protocol description includes a description of the supported resumption mechanisms.

#### Guidance

The evaluator shall ensure the operational guidance describes instructions for any configurable features of the resumption mechanism.

#### Tests

The evaluator shall perform the following tests:

- **Test 35.1:** For each supported version, and for each supported resumption method for that version, the evaluator shall establish a compliant initial TLS session with the TOE for the version using the specified method. The evaluator shall close the successful session and initiate resumption using the specified mechanism. The evaluator shall observe that the TSF successfully establishes the resumed session in accordance with the requirements.

- **Test 35.2:** For each supported version and each supported resumption method for the version, the evaluator shall send a compliant client hello message supporting only the specific version and indicating support for the resumption method. The evaluator shall allow the TOE and test client to continue with the compliant handshake until resumption information is established but then cause a fatal error to terminate the session. The evaluator shall then send a new client hello in an attempt to resume the session with the resumption information provided and verify that the TSF does not resume the session, but instead either terminates the session or completes a full handshake, ignoring the resumption information.

**Note:** For TLS 1.2, resumption information should be established at the point the TSF sends a server hello, either acknowledging the session-based resumption or acknowledging support for ticket-based resumption and sending a new\_ticket message. A TLS 1.2 session can then be terminated by sending a modified finished message. For TLS 1.3, the new\_ticket message is sent after the finished message; once received by the client, the session can be terminated by modifying a byte of the encrypted application data.

## FCS\_TLSS\_EXT.6 TLS Server TLS 1.3 Resumption Refinements

**The inclusion of this selection-based component depends upon selection in [FCS\\_TLSS\\_EXT.5.1](#).**

### FCS\_TLSS\_EXT.6.1

The TSF shall support TLS 1.3 resumption using PSK with psk\_key\_exchange\_mode extension with the value psk\_dhe.

### FCS\_TLSS\_EXT.6.2

The TSF shall ignore early data received in TLS 1.3 sessions.

**Application Note:** This SFR is claimed when session resumption is supported for TLS 1.3. RFC 8446 allows pre-shared keys to be used directly and also allows early data to be protected using only the pre-shared key. This SFR refines the RFC to use PSK only with a supplemental DHE or ECDHE key exchange to ensure perfect forward secrecy for all sessions.

This SFR is claimed if "PSK and tickets in accordance with RFC 8446" is selected in [FCS\\_TLSS\\_EXT.5.1](#).

## Evaluation Activities ▼

### [FCS\\_TLSS\\_EXT.6](#)

#### TSS

The evaluator shall examine the ST to confirm that the TLS description includes details on session resumption for TLS 1.3, describes each application capable of using TLS 1.3 with PSK, and describes how the TSF and application respond to client attempts to use early data (including via logging or observable responses). The evaluator shall confirm that the TLS description shows that only the psk\_dhe\_ke psk\_key\_exchange\_mode is supported and that early information is ignored.

#### Guidance

The evaluator shall examine the operational guidance to verify that instructions for any configurable features that are required to meet the requirement are included.

#### Tests

The evaluator shall follow the operational guidance to configure the TSF to negotiate TLS 1.3 and shall perform the following tests:

- **Test 36.1:** The evaluator shall attempt a resumed session (as for [FCS\\_TLSS\\_EXT.5](#) Test 1) but using psk\_ke mode as the value for the psk\_key\_exchange\_mode in the resumption client hello. The evaluator shall observe that the TSF refuses to resume the session, either by completing a full TLS 1.3 handshake or by terminating the session.

**Note:** It is preferred that the TSF sends a fatal error alert message (e.g., illegal parameter) in response to this, but it is acceptable that the TSF terminates the connection silently (i.e., without sending a fatal error alert).

- **Test 36.2:** The evaluator shall initiate a resumed session (as for [FCS\\_TLSS\\_EXT.5](#) Test 1) with a test TLS 1.3 client attempting to provide early data that provokes a known reaction at the TOE if received. The evaluator shall observe that the TSF does not react to the early data, indicating that the data was ignored.

**Note:** The specific early data used may depend on the applications calling the TLS session and should be selected to initiate an observable response in the TSF or calling application



as described in the ST. For HTTPS, for example, the early data can be an HTTP POST that updates data at the TOE, which can then be observed via a user interface for the application if the data was posted or via application logging indicating that the operation failed.

## FCS\_DTLSC\_EXT.1 DTLS Client Protocol

**The inclusion of this selection-based component depends upon selection in [FCS\\_TLS\\_EXT.1.1](#).**

### FCS\_DTLSC\_EXT.1.1

The product shall implement DTLS 1.2 (RFC 6347) and [**selection:** *DTLS 1.0 (RFC 4347), no earlier DTLS versions* ] as a client that supports the ciphersuites [**selection:**

- *TLS\_RSA\_WITH\_AES\_128\_CBC\_SHA as defined in RFC 5246*
- *TLS\_RSA\_WITH\_AES\_128\_CBC\_SHA256 as defined in RFC 5246*
- *TLS\_RSA\_WITH\_AES\_256\_CBC\_SHA256 as defined in RFC 5246*
- *TLS\_RSA\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5288*
- *TLS\_DHE\_RSA\_WITH\_AES\_128\_CBC\_SHA256 as defined in RFC 5246*
- *TLS\_DHE\_RSA\_WITH\_AES\_256\_CBC\_SHA256 as defined in RFC 5246*
- *TLS\_DHE\_RSA\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5288*
- *TLS\_ECDHE\_ECDSA\_WITH\_AES\_128\_CBC\_SHA256 as defined in RFC 5289*
- *TLS\_ECDHE\_ECDSA\_WITH\_AES\_128\_GCM\_SHA256 as defined in RFC 5289*
- *TLS\_ECDHE\_ECDSA\_WITH\_AES\_256\_CBC\_SHA384 as defined in RFC 5289*
- *TLS\_ECDHE\_ECDSA\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5289*
- *TLS\_ECDHE\_RSA\_WITH\_AES\_128\_CBC\_SHA256 as defined in RFC 5289*
- *TLS\_ECDHE\_RSA\_WITH\_AES\_128\_GCM\_SHA256 as defined in RFC 5289*
- *TLS\_ECDHE\_RSA\_WITH\_AES\_256\_CBC\_SHA384 as defined in RFC 5289*
- *TLS\_ECDHE\_RSA\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5289*

] and also supports functionality for [**selection:**

- *mutual authentication*
- *none*

].

**Application Note:** If any ECDHE or DHE ciphersuites are selected, then [FCS\\_TLSC\\_EXT.5](#) is required.

If *mutual authentication* is selected, then the ST must additionally include the requirements from [FCS\\_DTLSC\\_EXT.2](#). If the TOE implements mutual authentication, this selection must be made.

Differences between DTLS 1.2 and TLS 1.2 are outlined in RFC 6347; otherwise the protocols are the same. All application notes listed for [FCS\\_TLSC\\_EXT.1.1](#) that are relevant to DTLS apply to this requirement.

### FCS\_DTLSC\_EXT.1.2

The product shall verify that the presented identifier matches the reference identifier according to RFC 6125.

**Application Note:** All application notes listed for that are relevant to DTLS apply to this requirement.

### FCS\_DTLSC\_EXT.1.3

The product shall not establish a trusted channel if the server certificate is invalid [**selection:** *with no exceptions, except when override is authorized* ].

**Application Note:** All application notes listed for that are relevant to DTLS apply to this requirement.

### FCS\_DTLSC\_EXT.1.4

The product shall [**selection, choose one of:** *terminate the DTLS session, silently discard the record* ] if a message received contains an invalid MAC or if decryption fails in the case of GCM and other AEAD ciphersuites.

## Evaluation Activities ▼

[FCS\\_DTLSC\\_EXT.1](#)  
**Tests**

The evaluator shall perform the evaluation activities listed for .

#### [FCS\\_DTLSC\\_EXT.1.1](#)

##### **Tests**

The evaluator shall perform the evaluation activities listed for [FCS\\_TLSC\\_EXT.1.1](#), but ensuring that DTLS (and not TLS) is used in each evaluation activity.

For tests which involve version numbers, note that in DTLS the on-the-wire representation is the 1's complement of the corresponding textual DTLS version numbers. This is described in Section 4.1 of RFC 6347 and RFC 4347. For example, DTLS 1.0 is represented by the bytes 0xfe 0xff, while the undefined DTLS 1.4 would be represented by the bytes 0xfe 0xfb.

#### [FCS\\_DTLSC\\_EXT.1.2](#)

##### **Tests**

The evaluator shall perform the evaluation activities listed for .

#### [FCS\\_DTLSC\\_EXT.1.4](#)

##### **TSS**

The evaluator shall verify that the TSS describes the actions that take place if a message received from the DTLS Server fails the MAC integrity check.

##### **Tests**

The evaluator shall establish a connection using a server. The evaluator will then modify at least one byte in a record message, and verify that the client discards the record or terminates the DTLS session.

## **FCS\_DTLSC\_EXT.2 DTLS Client Support for Mutual Authentication**

**The inclusion of this selection-based component depends upon selection in [FCS\\_DTLSC\\_EXT.1.1](#).**

### **FCS\_DTLSC\_EXT.2.1**

The product shall support mutual authentication using X.509v3 certificates.

**Application Note:** All application notes listed for [FCS\\_TLSC\\_EXT.2.1](#) that are relevant to DTLS apply to this requirement.

## **Evaluation Activities ▼**

#### [FCS\\_DTLSC\\_EXT.2](#)

##### **Tests**

The evaluator shall perform the evaluation activities listed for [FCS\\_TLSC\\_EXT.2.1](#).

## **FCS\_DTLSS\_EXT.1 DTLS Server Protocol**

**The inclusion of this selection-based component depends upon selection in [FCS\\_TLS\\_EXT.1.1](#).**

### **FCS\_DTLSS\_EXT.1.1**

The product shall implement DTLS 1.2 (RFC 6347) and [**selection:** DTLS 1.0 (RFC 4347), no earlier DTLS versions ] as a server that supports the ciphersuites [**selection:**

- TLS\_RSA\_WITH\_AES\_128\_CBC\_SHA as defined in RFC 5246
- TLS\_RSA\_WITH\_AES\_256\_CBC\_SHA as defined in RFC 5246
- TLS\_RSA\_WITH\_AES\_128\_CBC\_SHA256 as defined in RFC 5246
- TLS\_RSA\_WITH\_AES\_256\_CBC\_SHA256 as defined in RFC 5246
- TLS\_RSA\_WITH\_AES\_128\_GCM\_SHA256 as defined in RFC 5288
- TLS\_RSA\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5288
- TLS\_DHE\_RSA\_WITH\_AES\_128\_CBC\_SHA256 as defined in RFC 5246
- TLS\_DHE\_RSA\_WITH\_AES\_256\_CBC\_SHA256 as defined in RFC 5246
- TLS\_DHE\_RSA\_WITH\_AES\_128\_GCM\_SHA256 as defined in RFC 5288
- TLS\_DHE\_RSA\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5288
- TLS\_ECDHE\_ECDSA\_WITH\_AES\_128\_CBC\_SHA256 as defined in RFC 5289
- TLS\_ECDHE\_ECDSA\_WITH\_AES\_128\_GCM\_SHA256 as defined in RFC 5289
- TLS\_ECDHE\_ECDSA\_WITH\_AES\_256\_CBC\_SHA384 as defined in RFC 5289
- TLS\_ECDHE\_ECDSA\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5289
- TLS\_ECDHE\_RSA\_WITH\_AES\_128\_CBC\_SHA256 as defined in RFC 5289
- TLS\_ECDHE\_RSA\_WITH\_AES\_128\_GCM\_SHA256 as defined in RFC 5289

- [TLS\\_ECDHE\\_RSA\\_WITH\\_AES\\_256\\_CBC\\_SHA384](#) as defined in RFC 5289
- [TLS\\_ECDHE\\_RSA\\_WITH\\_AES\\_256\\_GCM\\_SHA384](#) as defined in RFC 5289

] and no other ciphersuites, and also supports functionality for [**selection:**

- *mutual authentication*
- *none*

].

**Application Note:** If *mutual authentication* is selected, then the ST must additionally include the requirements from [FCS\\_DTLSS\\_EXT.2](#). If the TOE implements mutual authentication, this selection must be made.

All application notes listed for [FCS\\_TLSS\\_EXT.1.1](#) that are relevant to DTLS apply to this requirement.

#### FCS\_DTLSS\_EXT.1.2

The product shall deny connections from clients requesting [**assignment:** *list of DTLS protocol versions*].

**Application Note:** Any specific DTLS version not selected in [FCS\\_DTLSS\\_EXT.1.1](#) should be assigned here. This version of the FP does not require the server to deny DTLS 1.0, and if the TOE supports DTLS 1.0 then "none" can be assigned. In a future version of this FP, DTLS 1.0 will be required to be denied.

#### FCS\_DTLSS\_EXT.1.3

The product shall not proceed with a connection handshake attempt if the DTLS Client fails validation.

**Application Note:** The process to validate the IP address of a DTLS client is specified in section 4.2.1 of RFC 6347 (DTLS 1.2) and RFC 4347 (DTLS 1.0). The server validates the DTLS client during Connection Establishment (Handshaking) and prior to sending a Server Hello message. After receiving a ClientHello, the DTLS Server sends a HelloVerifyRequest along with a cookie. The cookie is a signed message using a keyed hash function. The DTLS Client then sends another ClientHello with the cookie attached. If the DTLS server successfully verifies the signed cookie, the Client is not using a spoofed IP address.

#### FCS\_DTLSS\_EXT.1.4

The product shall perform key establishment for DTLS using [**selection:**

- *RSA with size [**selection:** 2048 bits, 3072 bits, 4096 bits, no other sizes ]*
- *Diffie-Hellman parameters with size [**selection:** 2048 bits, 3072 bits, 4096 bits, 6144 bits, 8192 bits, no other size ]*
- *Diffie-Hellman groups [**selection:** ffdhe2048, ffdhe3072, ffdhe4096, ffdhe6144, ffdhe8192, no other groups ]*
- *ECDHE parameters using elliptic curves [**selection:** secp256r1, secp384r1, secp521r1 ] and no other curves*
- *no other key establishment methods*

].

**Application Note:** If the ST lists an RSA ciphersuite in [FCS\\_DTLSS\\_EXT.1.1](#), the ST must include the RSA selection in the requirement. If the ST lists a DHE ciphersuite in [FCS\\_DTLSS\\_EXT.1.1](#), the ST must include either the Diffie-Hellman selection for parameters of a certain size, or for particular Diffie-Hellman groups. If the ST lists an ECDHE ciphersuite in [FCS\\_DTLSS\\_EXT.1.1](#), the ST must include the NIST curves selection in the requirement.

#### FCS\_DTLSS\_EXT.1.5

The product shall [**selection, choose one of:** *terminate the DTLS session, silently discard the record* ] if a message received contains an invalid MAC or if decryption fails in the case of GCM and other AEAD ciphersuites.

## Evaluation Activities ▼

### [FCS\\_DTLSS\\_EXT.1.1](#)

#### Tests

The evaluator shall perform the evaluation activities listed for [FCS\\_TLSS\\_EXT.1.1](#), but ensuring that DTLS (and not TLS) is used in each stage of the evaluation activities.

For tests which involve version numbers, note that in DTLS the on-the-wire representation is the 1's complement of the corresponding textual DTLS version numbers. This is described in Section 4.1 of RFC 6347 and RFC 4347. For example, DTLS 1.0 is represented by the bytes 0xfe 0xff,

while the undefined DTLS 1.4 would be represented by the bytes 0xfe 0xfb.

#### [FCS\\_DTLSS\\_EXT.1.2](#)

The following evaluation activities shall be conducted unless "none" is assigned.

##### **TSS**

The evaluator shall verify that the TSS contains a description of the denial of old DTLS versions consistent relative to selections in [FCS\\_DTLSS\\_EXT.1.2](#).

##### **Guidance**

The evaluator shall verify that the operational guidance includes any configuration necessary to meet this requirement.

##### **Tests**

- **Test 37.1:** The evaluator shall send a Client Hello requesting a connection with each version of DTLS specified in the selection and verify that the server denies the connection.

#### [FCS\\_DTLSS\\_EXT.1.3](#)

##### **TSS**

The evaluator shall verify that the TSS describes how the DTLS Client IP address is validated prior to issuing a ServerHello message.

##### **Tests**

Modify at least one byte in the cookie from the Server's HelloVerifyRequest message, and verify that the Server rejects the Client's handshake message.

#### [FCS\\_DTLSS\\_EXT.1.4](#)

##### **Tests**

The evaluator shall perform the evaluation activities listed for .

#### [FCS\\_DTLSS\\_EXT.1.5](#)

##### **TSS**

The evaluator shall verify that the TSS describes the actions that take place if a message received from the DTLS client fails the MAC integrity check.

##### **Tests**

The evaluator shall establish a connection using a client. The evaluator will then modify at least one byte in a record message, and verify that the server discards the record or terminates the DTLS session.

## **FCS\_DTLSS\_EXT.2 DTLS Server Support for Mutual Authentication**

**The inclusion of this selection-based component depends upon selection in [FCS\\_DTLSS\\_EXT.1.1](#).**

### **FCS\_DTLSS\_EXT.2.1**

The product shall support mutual authentication of DTLS clients using X.509v3 certificates.

**Application Note:** All application notes listed for that are relevant to DTLS apply to this requirement.

### **FCS\_DTLSS\_EXT.2.2**

The product shall not establish a trusted channel if the client certificate is invalid.

**Application Note:** All application notes listed for that are relevant to DTLS apply to this requirement.

### **FCS\_DTLSS\_EXT.2.3**

The product shall not establish a trusted channel if the Distinguished Name (DN) or Subject Alternative Name (SAN) contained in a certificate does not match one of the expected identifiers for the client.

**Application Note:** All application notes listed for that are relevant to DTLS apply to this requirement.

## **Evaluation Activities ▼**

#### [FCS\\_DTLSS\\_EXT.2.1](#)

##### **Tests**

The evaluator shall perform the evaluation activities listed for .

#### [FCS\\_DTLSS\\_EXT.2.2](#)

##### **Tests**

The evaluator shall perform the evaluation activities listed for .

[FCS\\_DTLSS\\_EXT.2.3](#)

**Tests**

*The evaluator shall perform the evaluation activities listed for .*

# Appendix C - Acronyms

Acronym	Meaning
AES	Advanced Encryption Standard
Base-PP	Base Protection Profile
CA	Certificate Authority
CBC	Cipher Block Chaining
CC	Common Criteria
CEM	Common Evaluation Methodology
CN	Common Name
cPP	Collaborative Protection Profile
DHE	Diffie-Hellman Ephemeral
DN	Distinguished Name
DNS	Domain Name Server
DTLS	Datagram Transport Layer Security
EAP	Extensible Authentication Protocol
ECDHE	Elliptic Curve Diffie-Hellman Ephemeral
ECDSA	Elliptic Curve Digital Signature Algorithm
EP	Extended Package
FP	Functional Package
GCM	Galois/Counter Mode
HTTP	Hypertext Transfer Protocol
IETF	Internet Engineering Task Force
IP	Internet Protocol
NIST	National Institute of Standards and Technology
OE	Operational Environment
PP	Protection Profile
PP-Configuration	Protection Profile Configuration
PP-Module	Protection Profile Module
RFC	Request for Comment (IETF)
RSA	Rivest Shamir Adelman
SAN	Subject Alternative Name
SAR	Security Assurance Requirement
SCSV	Signaling ciphersuite Value
SFR	Security Functional Requirement
SHA	Secure Hash Algorithm
ST	Security Target
TCP	Transmission Control Protocol
TLS	Transport Layer Security
TOE	Target of Evaluation



TSF	TOE Security Functionality
TSFI	TSF Interface
TSS	TOE Summary Specification
UDP	User Datagram Protocol
URI	Uniform Resource Identifier
URL	Uniform Resource Locator

# Appendix D - Bibliography

Identifier	Title
[CC]	<div>Common Criteria for Information Technology Security Evaluation -<ul style="list-style-type: none"><li>Part 1: Introduction and General Model, CCMB-2017-04-001, Version 3.1 Revision 5, April 2017.</li><li>Part 2: Security Functional Components, CCMB-2017-04-002, Version 3.1 Revision 5, April 2017.</li><li>Part 3: Security Assurance Components, CCMB-2017-04-003, Version 3.1 Revision 5, April 2017.</li></ul></div>