

Protection Profile for General Purpose Operating Systems



Version: 4.3-DRAFT
2019-07-01

National Information Assurance Partnership

Revision History

Version	Date	Comment
4.3	2022-04-22	Added compatibility with MDM Agent, Bluetooth, and TLS Modules. Two factor authentication.
4.2.1	2019-04-22	Formatting changes as a result of PP evaluation
4.2	2018-05-22	Multiple Technical Decisions applied
4.1	2016-03-09	Minor updates - cryptographic modes
4.0	2015-08-14	Release - significant revision

Contents

1	Introduction
1.1	Overview
1.2	Terms
1.2.1	Common Criteria Terms
1.2.2	Technical Terms
1.3	Compliant Targets of Evaluation
1.3.1	TOE Boundary
1.3.2	TOE Platform
1.4	Use Cases
2	Conformance Claims
3	Security Problem Description
3.1	Threats
3.2	Assumptions
4	Security Objectives
4.1	Security Objectives for the TOE
4.2	Security Objectives for the Operational Environment
4.3	Security Objectives Rationale
5	Security Requirements
5.1	Security Functional Requirements
5.1.1	Cryptographic Support (FCS)
5.1.2	User Data Protection (FDP)
5.1.3	Security Management (FMT)
5.1.4	Protection of the TSF (FPT)
5.1.5	Audit Data Generation (FAU)
5.1.6	Identification and Authentication (FIA)
5.1.7	TOE Access (FTA)
5.1.8	Trusted Path/Channels (FTP)
5.1.9	TOE Security Functional Requirements Rationale
5.2	Security Assurance Requirements
5.2.1	Class ASE: Security Target
5.2.2	Class ADV: Development
5.2.3	Class AGD: Guidance Documentation
5.2.4	Class ALC: Life-cycle Support
5.2.5	Class ATE: Tests
5.2.6	Class AVA: Vulnerability Assessment
Appendix A -	Implementation-based Requirements
Appendix B -	Implicitly Satisfied Requirements
Appendix C -	Entropy Documentation and Assessment
C.1	Design Description
C.2	Entropy Justification
C.3	Operating Conditions
C.4	Health Testing
Appendix D -	Validation Guidelines
Appendix E -	Acronyms
Appendix F -	Bibliography

1 Introduction

1.1 Overview

The scope of this Protection Profile (PP) is to describe the security functionality of operating systems in terms of [\[CC\]](#) and to define functional and assurance requirements for such products. An operating system is software that manages computer hardware and software resources, and provides common services for application programs. The hardware it manages may be physical or virtual.

1.2 Terms

The following sections list Common Criteria and technology terms used in this document.

1.2.1 Common Criteria Terms

Assurance	Grounds for confidence that a TOE meets the SFRs [CC] .
Base Protection Profile (Base-PP)	Protection Profile used as a basis to build a PP-Configuration.
Collaborative Protection Profile (cPP)	A Protection Profile developed by international technical communities and approved by multiple schemes.
Common Criteria (CC)	Common Criteria for Information Technology Security Evaluation (International Standard ISO/IEC 15408).
Common Criteria Testing Laboratory	Within the context of the Common Criteria Evaluation and Validation Scheme (CCEVS), an IT security evaluation facility accredited by the National Voluntary Laboratory Accreditation Program (NVLAP) and approved by the NIAP Validation Body to conduct Common Criteria-based evaluations.
Common Evaluation Methodology (CEM)	Common Evaluation Methodology for Information Technology Security Evaluation.
Distributed TOE	A TOE composed of multiple components operating as a logical whole.
Extended Package (EP)	A deprecated document form for collecting SFRs that implement a particular protocol, technology, or functionality. See Functional Packages.
Functional Package (FP)	A document that collects SFRs for a particular protocol, technology, or functionality.
Operational Environment (OE)	Hardware and software that are outside the TOE boundary that support the TOE functionality and security policy.
Protection Profile (PP)	An implementation-independent set of security requirements for a category of products.
Protection Profile Configuration (PP-Configuration)	A comprehensive set of security requirements for a product type that consists of at least one Base-PP and at least one PP-Module.
Protection Profile Module (PP-Module)	An implementation-independent statement of security needs for a TOE type complementary to one or more Base-PPs.
Security Assurance Requirement (SAR)	A requirement to assure the security of the TOE.
Security Functional Requirement (SFR)	A requirement for security enforcement by the TOE.
Security Target (ST)	A set of implementation-dependent security requirements for a specific product.

Target of Evaluation (TOE)	The product under evaluation.
TOE Security Functionality (TSF)	The security functionality of the product under evaluation.
TOE Summary Specification (TSS)	A description of how a TOE satisfies the SFRs in an ST.

1.2.2 Technical Terms

Address Space Layout Randomization (ASLR)	An anti-exploitation feature which loads memory mappings into unpredictable locations. ASLR makes it more difficult for an attacker to redirect control to code that they have introduced into the address space of a process.
Administrator	An administrator is responsible for management activities, including setting policies that are applied by the enterprise on the operating system. This administrator could be acting remotely through a management server, from which the system receives configuration policies. An administrator can enforce settings on the system which cannot be overridden by non-administrator users.
Application (app)	Software that runs on a platform and performs tasks on behalf of the user or owner of the platform, as well as its supporting documentation.
Application Programming Interface (API)	A specification of routines, data structures, object classes, and variables that allows an application to make use of services provided by another software component, such as a library. APIs are often provided for a set of libraries included with the platform.
Biometric Authentication Factor (BAF)	Authentication factor, which uses biometric sample, matched to a biometric authentication template to help establish identity.
Credential	Data that establishes the identity of a user, e.g. a cryptographic key or password.
Critical Security Parameters (CSP)	Information that is either user or system defined and is used to operate a cryptographic module in processing encryption functions including cryptographic keys and authentication data, such as passwords, the disclosure or modification of which can compromise the security of a cryptographic module or the security of the information protected by the module.
DAR Protection	Countermeasures that prevent attackers, even those with physical access, from extracting data from non-volatile storage. Common techniques include data encryption and wiping.
Data Execution Prevention (DEP)	An anti-exploitation feature of modern operating systems executing on modern computer hardware, which enforces a non-execute permission on pages of memory. DEP prevents pages of memory from containing both data and instructions, which makes it more difficult for an attacker to introduce and execute code.
Developer	An entity that writes OS software. For the purposes of this document, vendors and developers are the same.
General Purpose Operating System	A class of OSES designed to support a wide-variety of workloads consisting of many concurrent applications or services. Typical characteristics for OSES in this class include support for third-party applications, support for multiple users, and security separation between users and their respective resources. General Purpose Operating Systems also lack the real-time constraint that defines Real Time Operating Systems that RTOSes typically power routers, switches, and embedded devices.
Host-based Firewall	A software-based firewall implementation running on the OS for filtering inbound and outbound network traffic to and from processes running on the OS.
Hybrid Authentication	A hybrid authentication factor is one where a user has to submit a combination of a biometric sample and a PIN or password and both must pass. If either factor fails, the entire attempt fails.
Operating System (OS)	Software that manages physical and logical resources and provides services for applications. The terms <i>TOE</i> and <i>OS</i> are interchangeable in this document.
Personal Identification Number (PIN)	An authentication factor that is comprised of a set of numeric or alphabetic characters that may be used in addition to a biometric factor or cryptographic token to provide a hybrid authentication factor. At this time it is not considered as a stand-alone authentication mechanism. A PIN is distinct from a password in that the allowed character set and required length of a PIN is typically smaller than that of a password as it is designed to be input quickly.

Personally Identifiable Information (PII)	Any information about an individual maintained by an agency, including, but not limited to, education, financial transactions, medical history, and criminal or employment history and information which can be used to distinguish or trace an individual's identity, such as their name, social security number, date and place of birth, mother's maiden name, biometric records, etc., including any other personal information which is linked or linkable to an individual.[OMB]
Sensitive Data	Sensitive data may include all user or enterprise data or may be specific application data such as PII, emails, messaging, documents, calendar items, and contacts. Sensitive data must minimally include credentials and keys. Sensitive data shall be identified in the OS's TSS by the ST author.
User	A user is subject to configuration policies applied to the operating system by administrators. On some systems under certain configurations, a normal user can temporarily elevate privileges to that of an administrator. At that time, such a user should be considered an administrator.

1.3 Compliant Targets of Evaluation

1.3.1 TOE Boundary

The TOE boundary encompasses the OS kernel and its drivers, shared software libraries, and some application software included with the OS. The applications considered within the TOE are those that provide essential security services, many of which run with elevated privileges. Applications which are covered by more-specific Protection Profiles cannot claim evaluation as part of the OS evaluation, even when it is necessary to evaluate some of their functionality as it relates to their role as part of the OS.



Figure 1: General TOE

1.3.2 TOE Platform

The TOE platform, which consists of the physical or virtual hardware on which the TOE executes, is outside the scope of evaluation. At the same time, the security of the TOE relies upon it. Other hardware components which independently run their own software and are relevant to overall system security are also outside the scope of evaluation.

1.4 Use Cases

Requirements in this Protection Profile are designed to address the security problems in at least the following use cases. These use cases are intentionally very broad, as many specific use cases exist for an operating system. These use cases may also overlap with one another. An operating system's functionality may even be effectively extended by privileged applications installed onto it. However, these are out of scope of this PP.

[USE CASE 1] End User Devices

The OS provides a platform for end user devices such as desktops, laptops, convertibles, and tablets. These devices may optionally be bound to a directory server or management server.

As this Protection Profile does not address threats against data-at-rest, enterprises deploying operating systems in mobile scenarios should ensure that these systems include data-at-rest protection spelled out in other Protection Profiles. Specifically, this includes the Protection Profiles for *Full Drive Encryption - Encryption Engine*, *Full Drive Encryption - Authorization Acquisition*, and *Software File Encryption*. The *Protection Profile for Mobile Device Fundamentals* includes requirements for data-at-rest protection and is appropriate for many mobile devices.

[USE CASE 2] Server Systems

The OS provides a platform for server-side services, either on physical or virtual hardware. Many specific examples exist in which the OS acts as a platform for such services, including file servers, mail servers, and web servers.

[USE CASE 3] Cloud Systems

The OS provides a platform for providing cloud services running on physical or virtual hardware. An OS is typically part of offerings identified as Infrastructure as a Service (IaaS), Software as a Service (SaaS), and Platform as a Service (PaaS).

This use case typically involves the use of virtualization technology which should be evaluated against the *Protection Profile for Server Virtualization*.

2 Conformance Claims

Conformance Statement

An ST must claim exact conformance to this PP, as defined in the CC and CEM addenda for Exact Conformance, Selection-based SFRs, and Optional SFRs (dated May 2017).

The following PP-Modules are allowed to be specified in a PP-Configuration with this PP.

- [PP-Module for Virtual Private Network \(VPN\) Clients, version 2.4](#)
- [PP-Module for PP-Module for Bluetooth, version 1.0](#)
- [PP-Module for Mobile Device Management Agent, version 1.0](#)

CC Conformance Claims

This PP is conformant to Parts 2 (extended) and 3 (conformant) of Common Criteria Version 3.1, Revision 5.

PP Claim

This PP does not claim conformance to any Protection Profile.

Package Claim

This PP is [Functional Package for Secure Shell \(SSH\), version 1.0](#) Conformant and [Functional Package for Transport Layer Security \(TLS\), version 1.1](#) Conformant .

3 Security Problem Description

The security problem is described in terms of the threats that the OS is expected to address, assumptions about the operational environment, and any organizational security policies that the OS is expected to enforce.

3.1 Threats

T.NETWORK_ATTACK

An attacker is positioned on a communications channel or elsewhere on the network infrastructure. Attackers may engage in communications with applications and services running on or part of the OS with the intent of compromise. Engagement may consist of altering existing legitimate communications.

T.NETWORK_EAVESDROP

An attacker is positioned on a communications channel or elsewhere on the network infrastructure. Attackers may monitor and gain access to data exchanged between applications and services that are running on or part of the OS.

T.LOCAL_ATTACK

An attacker may compromise applications running on the OS. The compromised application may provide maliciously formatted input to the OS through a variety of channels including unprivileged system calls and messaging via the file system.

T.LIMITED_PHYSICAL_ACCESS

An attacker may attempt to access data on the OS while having a limited amount of time with the physical device.

3.2 Assumptions

A.PLATFORM

The OS relies upon a trustworthy computing platform for its execution. This underlying platform is out of scope of this PP.

A.PROPER_USER

The user of the OS is not willfully negligent or hostile, and uses the software in compliance with the applied enterprise security policy. At the same time, malicious software could act *as* the user, so requirements which confine malicious subjects are still in scope.

A.PROPER_ADMIN

The administrator of the OS is not careless, willfully negligent or hostile, and administers the OS within compliance of the applied enterprise security policy.

4 Security Objectives

4.1 Security Objectives for the TOE

O.ACCOUNTABILITY

Conformant OSES ensure that information exists that allows administrators to discover unintentional issues with the configuration and operation of the operating system and discover its cause. Gathering event information and immediately transmitting it to another system can also enable incident response in the event of system compromise.

O.INTEGRITY

Conformant OSES ensure the integrity of their update packages. OSES are seldom if ever shipped without errors, and the ability to deploy patches and updates with integrity is critical to enterprise network security. Conformant OSES provide execution environment-based mitigations that increase the cost to attackers by adding complexity to the task of compromising systems.

O.MANAGEMENT

To facilitate management by users and the enterprise, conformant OSES provide consistent and supported interfaces for their security-relevant configuration and maintenance. This includes the deployment of applications and application updates through the use of platform-supported deployment mechanisms and formats, as well as providing mechanisms for configuration and application execution control.

O.PROTECTED_STORAGE

To address the issue of loss of confidentiality of credentials in the event of loss of physical control of the storage medium, conformant OSES provide data-at-rest protection for credentials. Conformant OSES also provide access controls which allow users to keep their files private from other users of the same system.

O.PROTECTED_COMMS

To address both passive (eavesdropping) and active (packet modification) network attack threats, conformant OSES provide mechanisms to create trusted channels for CSP and sensitive data. Both CSP and sensitive data should not be exposed outside of the platform.

4.2 Security Objectives for the Operational Environment

The following security objectives for the operational environment assist the OS in correctly providing its security functionality. These track with the assumptions about the environment.

OE.PLATFORM

The OS relies on being installed on trusted hardware.

OE.PROPER_USER

The user of the OS is not willfully negligent or hostile, and uses the software within compliance of the applied enterprise security policy. Standard user accounts are provisioned in accordance with the least privilege model. Users requiring higher levels of access should have a separate account dedicated for that use.

OE.PROPER_ADMIN

The administrator of the OS is not careless, willfully negligent or hostile, and administers the OS within compliance of the applied enterprise security policy.

4.3 Security Objectives Rationale

This section describes how the assumptions, threats, and organizational security policies map to the security objectives.

Table 1: Security Objectives Rationale

Threat, Assumption, or OSP	Security Objectives	Rationale
T.NETWORK_ATTACK	O.PROTECTED_COMMS	The threat T.NETWORK_ATTACK is countered by O.PROTECTED_COMMS as this provides for integrity of transmitted data.
	O.INTEGRITY	The threat T.NETWORK_ATTACK is countered by O.INTEGRITY as this provides for integrity of software that is installed onto the system from the network.
	O.MANAGEMENT	The threat T.NETWORK_ATTACK is countered by O.MANAGEMENT as this provides for the ability to configure the OS to defend against network attack.
	O.ACCOUNTABILITY	The threat T.NETWORK_ATTACK is countered by O.ACCOUNTABILITY as this provides a mechanism for the OS to report behavior that may indicate a network attack has occurred.

T.NETWORK_EAVESDROP	O.PROTECTED_COMMS	The threat T.NETWORK_EAVESDROP is countered by O.PROTECTED_COMMS as this provides for confidentiality of transmitted data.
	O.MANAGEMENT	The threat T.NETWORK_EAVESDROP is countered by O.MANAGEMENT as this provides for the ability to configure the OS to protect the confidentiality of its transmitted data.
T.LOCAL_ATTACK	O.INTEGRITY	The objective O.INTEGRITY protects against the use of mechanisms that weaken the TOE with regard to attack by other software on the platform.
	O.ACCOUNTABILITY	The objective O.ACCOUNTABILITY protects against local attacks by providing a mechanism to report behavior that may indicate a local attack is occurring or has occurred.
T.LIMITED_PHYSICAL_ACCESS	O.PROTECTED_STORAGE	The objective O.PROTECTED_STORAGE protects against unauthorized attempts to access physical storage used by the TOE.
A.PLATFORM	OE.PLATFORM	The operational environment objective OE.PLATFORM is realized through A.PLATFORM.
A.PROPER_USER	OE.PROPER_USER	The operational environment objective OE.PROPER_USER is realized through A.PROPER_USER.
A.PROPER_ADMIN	OE.PROPER_ADMIN	The operational environment objective OE.PROPER_ADMIN is realized through A.PROPER_ADMIN.

5 Security Requirements

This chapter describes the security requirements which have to be fulfilled by the product under evaluation. Those requirements comprise functional components from Part 2 and assurance components from Part 3 of [CC]. The following conventions are used for the completion of operations:

- **Refinement** operation (denoted by **bold text** or ~~striktthrough-text~~): is used to add details to a requirement (including replacing an assignment with a more restrictive selection) or to remove part of the requirement that is made irrelevant through the completion of another operation, and thus further restricts a requirement.
- **Selection** (denoted by *italicized text*): is used to select one or more options provided by the [CC] in stating a requirement.
- **Assignment** operation (denoted by *italicized text*): is used to assign a specific value to an unspecified parameter, such as the length of a password. Showing the value in square brackets indicates assignment.
- **Iteration** operation: is indicated by appending the SFR name with a slash and unique identifier suggesting the purpose of the operation, e.g. "/EXAMPLE1."

5.1 Security Functional Requirements

5.1.1 Cryptographic Support (FCS)

FCS_CKM.1 Cryptographic Key Generation (Refined)

FCS_CKM.1.1

The OS shall generate **asymmetric** cryptographic keys in accordance with a specified cryptographic key generation algorithm **[selection]**:

- ***RSA schemes using cryptographic key sizes of 2048-bit or greater that f-component meet the following: FIPS PUB 186-4, "Digital Signature Standard (DSS)", Appendix B.3***
- ***ECC schemes using "NIST curves" P-256, P-384 and [selection: P-521, no other curves] that meet the following: FIPS PUB 186-4, "Digital Signature Standard (DSS)", Appendix B.4***
- ***FFC schemes using cryptographic key sizes of 2048-bit or greater that meet the following: FIPS PUB 186-4, "Digital Signature Standard (DSS)", Appendix B.1***
- ***FFC Schemes using Diffie-Hellman Group 14 that meet the following: RFC 3526***
- ***FFC Schemes using safe primes that meet the following: 'NIST Special Publication 800-56A Revision 3, "Recommendation for Pair-Wise Key Establishment Schemes***

1 .

Application Note: The ST author will select all key generation schemes used for key establishment and entity authentication. When key generation is used for key establishment, the schemes in FCS_CKM.2 and selected cryptographic protocols must match the selection. When key generation is used for entity authentication, the public key is expected to be associated with an X.509v3 certificate.

If the OS acts only as a receiver in the RSA key establishment scheme, the OS does not need to implement RSA key generation.

Evaluation Activities ▼

[FCS_CKM.1](#)

Tests

The evaluator will ensure that the TSS identifies the key sizes supported by the OS. If the ST specifies more than one scheme, the evaluator will examine the TSS to verify that it identifies the usage for each scheme.

The evaluator will verify that the AGD guidance instructs the administrator how to configure the OS to use the selected key generation scheme(s) and key size(s) for all uses defined in this PP.

Evaluation Activity Note: The following tests may require the vendor to furnish a developer environment and developer tools that are typically not available to end-users of the OS.

The following content should be included if:

- [RSA schemes using cryptographic key sizes of 2048-bit or greater that f-component meet the following: FIPS PUB 186-4, "Digital Signature Standard \(DSS\)", Appendix B.3](#) , is selected from [FCS_CKM.1.1](#)

Key Generation for FIPS PUB 186-4 RSA Schemes

The evaluator will verify the implementation of RSA Key Generation by the OS using the Key Generation test. This test verifies the ability of the TSF to correctly produce values for the key components including the public verification exponent e , the private prime factors p and

q , the public modulus n and the calculation of the private signature exponent d . Key Pair generation specifies 5 ways (or methods) to generate the primes p and q . These include:

1. Random Primes:

- Provable primes
- Probable primes

2. Primes with Conditions:

- Primes p_1, p_2, q_1, q_2, p and q shall all be provable primes
- Primes p_1, p_2, q_1 , and q_2 shall be provable primes and p and q shall be probable primes
- Primes p_1, p_2, q_1, q_2, p and q shall all be probable primes

To test the key generation method for the Random Provable primes method and for all the Primes with Conditions methods, the evaluator must seed the TSF key generation routine with sufficient data to deterministically generate the RSA key pair. This includes the random seed(s), the public exponent of the RSA key, and the desired key length. For each key length supported, the evaluator shall have the TSF generate 25 key pairs. The evaluator will verify the correctness of the TSF's implementation by comparing values generated by the TSF with those generated from a known good implementation.

If possible, the Random Probable primes method should also be verified against a known good implementation as described above. Otherwise, the evaluator will have the TSF generate 10 keys pairs for each supported key length $nlen$ and verify:

- $n = p \cdot q$,
- p and q are probably prime according to Miller-Rabin tests,
- $GCD(p-1, e) = 1$,
- $GCD(q-1, e) = 1$,
- $2^{16} \leq e \leq 2^{256}$ and e is an odd integer,
- $|p-q| > 2^{nlen/2 - 100}$,
- $p \geq 2^{nlen/2 - 1/2}$,
- $q \geq 2^{nlen/2 - 1/2}$,
- $2^{(nlen/2)} < d < LCM(p-1, q-1)$,
- $e \cdot d = 1 \bmod LCM(p-1, q-1)$.

The following content should be included if:

- [ECC schemes using "NIST curves"](#), is selected from [FCS_CKM.1.1](#)

Key Generation for Elliptic Curve Cryptography (ECC)

FIPS 186-4 ECC Key Generation Test

For each supported NIST curve, i.e., P-256, P-384 and P-521, the evaluator will require the implementation under test (IUT) to generate 10 private/public key pairs. The private key shall be generated using an approved random bit generator (RBG). To determine correctness, the evaluator will submit the generated key pairs to the public key verification (PKV) function of a known good implementation.

FIPS 186-4 Public Key Verification (PKV) Test

For each supported NIST curve, i.e., P-256, P-384 and P-521, the evaluator will generate 10 private/public key pairs using the key generation function of a known good implementation and modify five of the public key values so that they are incorrect, leaving five values unchanged (i.e., correct). The evaluator will obtain in response a set of 10 PASS/FAIL values.

The following content should be included if:

- [FFC schemes using cryptographic key sizes of 2048-bit or greater that meet the following: FIPS PUB 186-4, "Digital Signature Standard \(DSS\)", Appendix B.1](#), is selected from [FCS_CKM.1.1](#)

Key Generation for Finite-Field Cryptography (FFC)

The evaluator will verify the implementation of the Parameters Generation and the Key Generation for FFC by the TOE using the Parameter Generation and Key Generation test. This test verifies the ability of the TSF to correctly produce values for the field prime p , the cryptographic prime q (dividing $p-1$), the cryptographic group generator g , and the calculation of the private key x and public key y .

The Parameter generation specifies 2 ways (or methods) to generate the cryptographic prime q and the field prime p :

- Cryptographic and Field Primes:
 - Primes q and p shall both be provable primes
 - Primes q and field prime p shall both be probable primes

and two ways to generate the cryptographic group generator g :

- Cryptographic Group Generator:
 - Generator g constructed through a verifiable process
 - Generator g constructed through an unverifiable process

The Key generation specifies 2 ways to generate the private key x :

- Private Key:
 - $len(q)$ bit output of RBG where $1 \leq x \leq q-1$
 - $len(q) + 64$ bit output of RBG, followed by a mod $q-1$ operation where $1 \leq x \leq q-1$

The security strength of the RBG must be at least that of the security offered by the FFC parameter set. To test the cryptographic and field prime generation method for the provable primes method and/or the group generator g for a verifiable process, the evaluator must seed the TSF parameter generation routine with sufficient data to deterministically generate the parameter set. For each key length supported, the evaluator will have the TSF generate 25 parameter sets and key pairs. The evaluator will verify the correctness of the TSF's implementation by comparing values generated by the TSF with those generated from a known good implementation. Verification must also confirm:

- $g \neq 0,1$
- q divides $p-1$
- $g^q \bmod p = 1$
- $g^x \bmod p = y$

for each FFC parameter set and key pair.

The following content should be included if:

- [FFC Schemes using Diffie-Hellman Group 14, FFC Schemes using safe primes that meet the following: 'NIST Special Publication 800-56A Revision 3, "Recommendation for Pair-Wise Key Establishment Schemes', is selected from FCS_CKM.1.1](#)

Diffie-Hellman Group 14 and FFC Schemes using "safe-prime" groups

Testing for FFC Schemes using Diffie-Hellman group 14 and/or "safe-prime" groups is done as part of testing in [FCS_CKM.2.1](#)

FCS_CKM.2 Cryptographic Key Establishment (Refined)

FCS_CKM.2.1

The OS shall **implement functionality to perform cryptographic key establishment** in accordance with a specified cryptographic key establishment method: [selection:

- RSA-based key establishment schemes that meets the following: RSAES-PKCS1-v1_5 as specified in Section 7.2 of RFC 8017, "Public-Key Cryptography Standards (PKCS) #1: RSA Cryptography Specifications Version 2.2
- Elliptic curve-based key establishment schemes that meets the following: NIST Special Publication 800-56A Revision 3, "Recommendation for Pair-Wise Key Establishment Schemes Using Discrete Logarithm Cryptography"
- Finite field-based key establishment schemes that meets the following: NIST Special Publication 800-56A Revision 3, "Recommendation for Pair-Wise Key Establishment Schemes Using Discrete Logarithm Cryptography"
- Key establishment scheme using Diffie-Hellman group 14 that meets the following: RFC 3526

].

Application Note: The ST author will select all key establishment schemes used for the selected cryptographic protocols.

The elliptic curves used for the key establishment scheme shall correlate with the curves specified in [FCS_CKM.1.1](#). The domain parameters used for the finite field-based key establishment scheme are specified by the key generation according to [FCS_CKM.1.1](#). The finite field-based key establishment schemes that conform to NIST SP 800-56A Revision 3 correspond to the "safe-prime" groups selection in [FCS_CKM.1.1](#).

Evaluation Activities ▼

[FCS_CKM.2](#)

Tests

The evaluator will ensure that the supported key establishment schemes correspond to the key generation schemes identified in [FCS_CKM.1.1](#). If the ST specifies more than one scheme, the evaluator will examine the TSS to verify that it identifies the usage for each scheme.

The evaluator will verify that the AGD guidance instructs the administrator how to configure the OS to use the selected key establishment scheme(s).

Evaluation Activity Note: The following tests require the developer to provide access to a test platform that provides the evaluator with tools that are typically not found on factory products.

Key Establishment Schemes

The evaluator will verify the implementation of the key establishment schemes supported by the OS using the applicable tests below.

The following content should be included if:

- [Elliptic curve-based key establishment schemes that meets the following: NIST Special Publication 800-56A Revision 3, "Recommendation for Pair-Wise Key Establishment Schemes Using Discrete Logarithm Cryptography", Finite field-based key establishment schemes that meets the following: NIST Special Publication 800-56A Revision 3, "Recommendation for Pair-Wise Key Establishment Schemes Using Discrete Logarithm](#)

Cryptography”, is selected from [FCS_CKM.2.1](#)

SP800-56A Key Establishment Schemes

The evaluator will verify the OS's implementation of SP800-56A key agreement schemes using the following Function and Validity tests. These validation tests for each key agreement scheme verify that the OS has implemented the components of the key agreement scheme according to the specifications in the Recommendation. These components include the calculation of the discrete logarithm cryptography (DLC) primitives (the shared secret value Z) and the calculation of the derived keying material (DKM) via the Key Derivation Function (KDF). If key confirmation is supported, the evaluator will also verify that the components of key confirmation have been implemented correctly, using the test procedures described below. This includes the parsing of the DKM, the generation of MAC data and the calculation of MAC tag.

Function Test

The Function test verifies the ability of the OS to implement the key agreement schemes correctly. To conduct this test the evaluator will generate or obtain test vectors from a known good implementation of the OS's supported schemes. For each supported key agreement scheme-key agreement role combination, KDF type, and, if supported, key confirmation role- key confirmation type combination, the tester will generate 10 sets of test vectors. The data set consists of the NIST approved curve (ECC) per 10 sets of public keys. These keys are static, ephemeral or both depending on the scheme being tested.

The evaluator will obtain the DKM, the corresponding OS's public keys (static and/or ephemeral), the MAC tag(s), and any inputs used in the KDF, such as the Other Information field OI and OS id fields.

If the OS does not use a KDF defined in SP 800-56A, the evaluator will obtain only the public keys and the hashed value of the shared secret.

The evaluator will verify the correctness of the TSF's implementation of a given scheme by using a known good implementation to calculate the shared secret value, derive the keying material DKM, and compare hashes or MAC tags generated from these values.

If key confirmation is supported, the OS will perform the above for each implemented approved MAC algorithm.

Validity Test

The Validity test verifies the ability of the OS to recognize another party's valid and invalid key agreement results with or without key confirmation. To conduct this test, the evaluator will obtain a list of the supporting cryptographic functions included in the SP800-56A key agreement implementation to determine which errors the OS should be able to recognize. The evaluator generates a set of 30 test vectors consisting of data sets including domain parameter values or NIST approved curves, the evaluator's public keys, the OS's public/private key pairs, MAC tag, and any inputs used in the KDF, such as the other info and OS id fields.

The evaluator will inject an error in some of the test vectors to test that the OS recognizes invalid key agreement results caused by the following fields being incorrect: the shared secret value Z, the DKM, the other information field OI, the data to be MAC'd, or the generated MAC tag. If the OS contains the full or partial (only ECC) public key validation, the evaluator will also individually inject errors in both parties' static public keys, both parties' ephemeral public keys and the OS's static private key to assure the OS detects errors in the public key validation function and/or the partial key validation function (in ECC only). At least two of the test vectors will remain unmodified and therefore should result in valid key agreement results (they should pass).

The OS will use these modified test vectors to emulate the key agreement scheme using the corresponding parameters. The evaluator will compare the OS's results with the results using a known good implementation verifying that the OS detects these errors.

The following content should be included if:

- [RSA-based key establishment schemes that meets the following: RSAES-PKCS1-v1_5 as specified in Section 7.2 of RFC 8017, "Public-Key Cryptography Standards \(PKCS\) #1: RSA Cryptography Specifications Version 2.2, is selected from FCS_CKM.2.1](#)

RSAES-PKCS1-v1_5 Key Establishment Schemes

The evaluator will verify the correctness of the TSF's implementation of RSAES-PKCS1-v1_5 by using a known good implementation for each protocol selected in [FTP_ITC_EXT.1](#) that uses RSAES-PKCS1-v1_5.

The following content should be included if:

- [Key establishment scheme using Diffie-Hellman group 14 that meets the following: RFC 3526, is selected from FCS_CKM.2.1](#)

Diffie-Hellman Group 14

The evaluator will verify the correctness of the TSF's implementation of Diffie-Hellman group 14 by using a known good implementation for each protocol selected in [FTP_ITC_EXT.1](#) that uses Diffie-Hellman Group 14.

The following content should be included if:

- [Finite field-based key establishment schemes that meets the following: NIST Special](#)

FFC Schemes using "safe-prime" groups (identified in Appendix D of SP 800-56A Revision 3)

The evaluator will verify the correctness of the TSF's implementation of "safe-prime" groups by using a known good implementation for each protocol selected in [FTP_ITC_EXT.1](#) that uses "safe-prime" groups. This test must be performed for each "safe-prime" group that each protocol uses.

FCS_CKM_EXT.4 Cryptographic Key Destruction

FCS_CKM_EXT.4.1

The OS shall destroy cryptographic keys and key material in accordance with a specified cryptographic key destruction method [**selection**:

- For volatile memory, the destruction shall be executed by a [**selection**:
 - single overwrite consisting of [**selection**: a pseudo-random pattern using the TSF's RBG, zeroes, ones, a new value of a key, [**assignment**: any value that does not contain any CSP]]
 - removal of power to the memory
 - destruction of reference to the key directly followed by a request for garbage collection]
 - For non-volatile memory that consists of [**selection**:
 - destruction of all key encrypting keys protecting the target key according to [FCS_CKM_EXT.4.1](#), where none of the KEKs protecting the target key are derived
 - the invocation of an interface provided by the underlying platform that [**selection**:
 - logically addresses the storage location of the key and performs a [**selection**: single, [**assignment**: ST author defined multi-pass]] overwrite consisting of [**selection**: zeroes, ones, pseudo-random pattern, a new value of a key of the same size, [**assignment**: any value that does not contain any CSP]]
 - instructs the underlying platform to destroy the abstraction that represents the key
-]

Application Note: The interface referenced in the requirement could take different forms, the most likely of which is an application programming interface to an OS kernel. There may be various levels of abstraction visible. For instance, in a given implementation that overwrites a key stored in non-volatile memory, the application may have access to the file system details and may be able to logically address specific memory locations. In another implementation, that instructs the underlying platform to destroy the representation of a key stored in non-volatile memory, the application may simply have a handle to a resource and can only ask the platform to delete the resource, as may be the case with a platform's secure key store. The latter implementation should only be used for the most restricted access. The level of detail to which the TOE has access will be reflected in the TSS section of the ST.

Several selections allow assignment of a 'value that does not contain any CSP'. This means that the TOE uses some other specified data not drawn from a source that may contain key material or reveal information about key material, and not being any of the particular values listed as other selection options. The point of the phrase 'does not contain any CSP' is to ensure that the overwritten data is carefully selected, and not taken from a general 'pool' that might contain current or residual data that itself requires confidentiality protection.

For the selection [destruction of all key encrypting keys protecting the target key according to FCS_CKM_EXT.4.1](#), a key can be considered destroyed by destroying the key that protects the key. If a key is wrapped or encrypted it is not necessary to "overwrite" that key, overwriting the key that is used to wrap or encrypt the key used to encrypt/decrypt data, using the appropriate method for the memory type involved, will suffice. For example, if a product uses a Key Encryption Key (KEK) to encrypt a Data Encryption Key (DEK), destroying the KEK using one of the methods in [FCS_CKM_EXT.4](#) is sufficient, since the DEK would no longer be usable (of course, presumes the DEK is still encrypted and the KEK cannot be recovered or re-derived.).

FCS_CKM_EXT.4.2

The OS shall destroy all keys and key material when no longer needed.

Application Note: For the purposes of this requirement, key material refers to

authentication data, passwords, secret/private symmetric keys, private asymmetric keys, data used to derive keys, values derived from passwords, etc. Key destruction procedures are performed in accordance with [FCS_CKM_EXT.4.1](#).

Evaluation Activities ▼

[FCS_CKM_EXT.4](#)

TSS

The evaluator examines the TSS to ensure it describes how the keys are managed in volatile memory. This description includes details of how each identified key is introduced into volatile memory (e.g. by derivation from user input, or by unwrapping a wrapped key stored in non-volatile memory) and how they are overwritten.

The evaluator will check to ensure the TSS lists each type of key that is stored in in non-volatile memory, and identifies how the TOE interacts with the underlying platform to manage keys (e.g., store, retrieve, destroy). The description includes details on the method of how the TOE interacts with the platform, including an identification and description of the interfaces it uses to manage keys (e.g., file system APIs, platform key store APIs).

If the ST makes use of the open assignment and fills in the type of pattern that is used, the evaluator examines the TSS to ensure it describes how that pattern is obtained and used. The evaluator will verify that the pattern does not contain any CSPs.

The evaluator will check that the TSS identifies any configurations or circumstances that may not strictly conform to the key destruction requirement.

If the selection [FCS_CKM_EXT.4.1](#) is included the evaluator will examine the TOE's keychain in the TSS and identify each instance when a key is destroyed by this method. In each instance the evaluator will verify all keys capable of decrypting the target key are destroyed in accordance with a specified key destruction method in [FCS_CKM_EXT.4.1](#). The evaluator will verify that all of the keys capable of decrypting the target key are not able to be derived to reestablish the keychain after their destruction.

Guidance

Operational Guidance

There are a variety of concerns that may prevent or delay key destruction in some cases. The evaluator will check that the guidance documentation identifies configurations or circumstances that may not strictly conform to the key destruction requirement, and that this description is consistent with the relevant parts of the TSS and any other relevant Required Supplementary Information. The evaluator will check that the guidance documentation provides guidance on situations where key destruction may be delayed at the physical layer and how such situations can be avoided or mitigated if possible.

Some examples of what is expected to be in the documentation are provided here.

When the TOE does not have full access to the physical memory, it is possible that the storage may be implementing wear-leveling and garbage collection. This may create additional copies of the key that are logically inaccessible but persist physically. In this case, to mitigate this the drive should support the TRIM command and implements garbage collection to destroy these persistent copies when not actively engaged in other tasks.

Drive vendors implement garbage collection in a variety of different ways, as such there is a variable amount of time until data is truly removed from these solutions. There is a risk that data may persist for a longer amount of time if it is contained in a block with other data not ready for erasure. To reduce this risk, the operating system and file system of the OE should support TRIM, instructing the non-volatile memory to erase copies via garbage collection upon their deletion. If a RAID array is being used, only set-ups that support TRIM are utilized. If the drive is connected via PCI-Express, the operating system supports TRIM over that channel.

The drive should be healthy and contains minimal corrupted data and should be end-of-lifed before a significant amount of damage to drive health occurs, this minimizes the risk that small amounts of potentially recoverable data may remain in damaged areas of the drive.

Tests

- **Test 1:** Applied to each key held as in volatile memory and subject to destruction by overwrite by the TOE (whether or not the value is subsequently encrypted for storage in volatile or non-volatile memory). In the case where the only selection made for the destruction method key was removal of power, then this test is unnecessary. The evaluator will:
 1. Record the value of the key in the TOE subject to clearing.
 2. Cause the TOE to perform a normal cryptographic processing with the key from Step #1.
 3. Cause the TOE to clear the key.
 4. Cause the TOE to stop the execution but not exit.
 5. Cause the TOE to dump the entire memory of the TOE into a binary file.
 6. Search the content of the binary file created in Step #5 for instances of the known key value from Step #1.

Steps 1-6 ensure that the complete key does not exist anywhere in volatile memory. If a

copy is found, then the test fails.

- **Test 2:** Applied to each key held in non-volatile memory and subject to destruction by the TOE. The evaluator will use special tools (as needed), provided by the TOE developer if necessary, to ensure the tests function as intended.
 1. Identify the purpose of the key and what access should fail when it is deleted. (e.g. the data encryption key being deleted would cause data decryption to fail.)
 2. Cause the TOE to clear the key.
 3. Have the TOE attempt the functionality that the cleared key would be necessary for.The test succeeds if step 3 fails.

- **Test 3:**

Tests 3 and 4 do not apply for the selection instructing the underlying platform to destroy the representation of the key as the TOE has no visibility into the inner workings and completely relies on the underlying platform.

The following tests are used to determine if the TOE is able to request the platform to overwrite the key with a TOE supplied pattern.

Applied to each key held in non-volatile memory and subject to destruction by overwrite by the TOE. The evaluator will use a tool that provides a logical view of the media (e.g., MBR file system):

1. Record the value of the key in the TOE subject to clearing.
 2. Cause the TOE to perform a normal cryptographic processing with the key from Step #1.
 3. Cause the TOE to clear the key.
 4. Search the logical view that the key was stored in for instances of the known key value from Step #1. If a copy is found, then the test fails.
- **Test 4:** Applied to each key held as non-volatile memory and subject to destruction by overwrite by the TOE. The evaluator will use a tool that provides a logical view of the media:
 1. Record the logical storage location of the key in the TOE subject to clearing.
 2. Cause the TOE to perform a normal cryptographic processing with the key from Step #1.
 3. Cause the TOE to clear the key.
 4. Read the logical storage location in Step #1 of non-volatile memory to ensure the appropriate pattern is utilized.

The test succeeds if correct pattern is used to overwrite the key in the memory location. If the pattern is not found the test fails.

FCS_COP.1/ENCRYPT Cryptographic Operation - Encryption/Decryption (Refined)

FCS_COP.1.1/ENCRYPT

The **OS** shall perform [encryption/decryption services for data] in accordance with a specified cryptographic algorithm **[selection:**

- **AES-XTS (as defined in NIST SP 800-38E)**
- **AES-CBC (as defined in NIST SP 800-38A)**

] and [selection:

- **AES-CCMP (as defined in FIPS PUB 197, NIST SP 800-38C and IEEE 802.11-2012)**
- **AES Key Wrap (KW) (as defined in NIST SP 800-38F)**
- **AES Key Wrap with Padding (KWP) (as defined in NIST SP 800-38F)**
- **AES-GCM (as defined in NIST SP 800-38D)**
- **AES-CCM (as defined in NIST SP 800-38C)**
- **AES-CCMP-256 (as defined in NIST SP 800-38C and IEEE 802.11ac-2013)**
- **AES-GCMP-256 (as defined in NIST SP 800-38D and IEEE 802.11ac-2013)**
- **AES-CTR (as defined in NIST SP 800-38A)**
- **no other modes**

] and cryptographic key sizes [selection: 128-bit, 256-bit] that meet the following: [assignment: list of standards].

Application Note: AES CCMP (which uses AES in CCM as specified in SP 800-38C) becomes mandatory and must be selected if the ST includes the WLAN Client EP.

For the second selection, the ST author should choose the mode or modes in which AES operates. For the third selection, the ST author should choose the key sizes that are supported by this functionality.

If **SSH** is selected in **FTP_ITC_EXT.1.1**, then **AES-CTR** must be selected.

Validation Guidelines:

Rule #1

[FCS_COP.1/ENCRYPT](#)**Tests**

The evaluator will verify that the AGD documents contains instructions required to configure the OS to use the required modes and key sizes. The evaluator will execute all instructions as specified to configure the OS to the appropriate state. The evaluator will perform all of the following tests for each algorithm implemented by the OS and used to satisfy the requirements of this PP:

AES-CBC Known Answer Tests

There are four Known Answer Tests (KATs), described below. In all KATs, the plaintext, ciphertext, and IV values will be 128-bit blocks. The results from each test may either be obtained by the evaluator directly or by supplying the inputs to the implementer and receiving the results in response. To determine correctness, the evaluator will compare the resulting values to those obtained by submitting the same inputs to a known good implementation.

- KAT-1. To test the encrypt functionality of AES-CBC, the evaluator will supply a set of 10 plaintext values and obtain the ciphertext value that results from AES-CBC encryption of the given plaintext using a key value of all zeros and an IV of all zeros. Five plaintext values will be encrypted with a 128-bit all-zeros key, and the other five will be encrypted with a 256-bit all-zeros key. To test the decrypt functionality of AES-CBC, the evaluator will perform the same test as for encrypt, using 10 ciphertext values as input and AES-CBC decryption.
- KAT-2. To test the encrypt functionality of AES-CBC, the evaluator will supply a set of 10 key values and obtain the ciphertext value that results from AES-CBC encryption of an all-zeros plaintext using the given key value and an IV of all zeros. Five of the keys will be 128-bit keys, and the other five will be 256-bit keys. To test the decrypt functionality of AES-CBC, the evaluator will perform the same test as for encrypt, using an all-zero ciphertext value as input and AES-CBC decryption.
- KAT-3. To test the encrypt functionality of AES-CBC, the evaluator will supply the two sets of key values described below and obtain the ciphertext value that results from AES encryption of an all-zeros plaintext using the given key value and an IV of all zeros. The first set of keys will have 128 128-bit keys, and the second set will have 256 256-bit keys. Key i in each set will have the leftmost i bits be ones and the rightmost $N-i$ bits be zeros, for i in $[1, N]$. To test the decrypt functionality of AES-CBC, the evaluator will supply the two sets of key and ciphertext value pairs described below and obtain the plaintext value that results from AES-CBC decryption of the given ciphertext using the given key and an IV of all zeros. The first set of key/ciphertext pairs will have 128 128-bit key/ciphertext pairs, and the second set of key/ciphertext pairs will have 256 256-bit key/ciphertext pairs. Key i in each set will have the leftmost i bits be ones and the rightmost $N-i$ bits be zeros, for i in $[1, N]$. The ciphertext value in each pair will be the value that results in an all-zeros plaintext when decrypted with its corresponding key.
- KAT-4. To test the encrypt functionality of AES-CBC, the evaluator will supply the set of 128 plaintext values described below and obtain the two ciphertext values that result from AES-CBC encryption of the given plaintext using a 128-bit key value of all zeros with an IV of all zeros and using a 256-bit key value of all zeros with an IV of all zeros, respectively. Plaintext value i in each set will have the leftmost i bits be ones and the rightmost $128-i$ bits be zeros, for i in $[1, 128]$.

To test the decrypt functionality of AES-CBC, the evaluator will perform the same test as for encrypt, using ciphertext values of the same form as the plaintext in the encrypt test as input and AES-CBC decryption.

AES-CBC Multi-Block Message Test

The evaluator will test the encrypt functionality by encrypting an i -block message where $1 < i \leq 10$. The evaluator will choose a key, an IV and plaintext message of length i blocks and encrypt the message, using the mode to be tested, with the chosen key and IV. The ciphertext will be compared to the result of encrypting the same plaintext message with the same key and IV using a known good implementation. The evaluator will also test the decrypt functionality for each mode by decrypting an i -block message where $1 < i \leq 10$. The evaluator will choose a key, an IV and a ciphertext message of length i blocks and decrypt the message, using the mode to be tested, with the chosen key and IV. The plaintext will be compared to the result of decrypting the same ciphertext message with the same key and IV using a known good implementation.

AES-CBC Monte Carlo Tests

The evaluator will test the encrypt functionality using a set of 200 plaintext, IV, and key 3-tuples. 100 of these will use 128 bit keys, and 100 will use 256 bit keys. The plaintext and IV values will be 128-bit blocks. For each 3-tuple, 1000 iterations will be run as follows:

```
# Input: PT, IV, Key
for i = 1 to 1000:
  if i == 1:
    CT[1] = AES-CBC-Encrypt(Key, IV, PT)
    PT = IV
  else:
    CT[i] = AES-CBC-Encrypt(Key, PT)
    PT = CT[i-1]
```

The ciphertext computed in the 1000th iteration (i.e., CT[1000]) is the result for that trial. This result will be compared to the result of running 1000 iterations with the same values using a known good implementation.

The evaluator will test the decrypt functionality using the same test as for encrypt, exchanging CT and PT and replacing AES-CBC-Encrypt with AES-CBC-Decrypt.

AES-GCM Monte Carlo Tests

The evaluator will test the authenticated encrypt functionality of AES-GCM for each combination of the following input parameter lengths:

- 128 bit and 256 bit keys
- Two plaintext lengths. One of the plaintext lengths will be a non-zero integer multiple of 128 bits, if supported. The other plaintext length will not be an integer multiple of 128 bits, if supported.
- Three AAD lengths. One AAD length will be 0, if supported. One AAD length will be a non-zero integer multiple of 128 bits, if supported. One AAD length will not be an integer multiple of 128 bits, if supported.
- Two IV lengths. If 96 bit IV is supported, 96 bits will be one of the two IV lengths tested.

The evaluator will test the encrypt functionality using a set of 10 key, plaintext, AAD, and IV tuples for each combination of parameter lengths above and obtain the ciphertext value and tag that results from AES-GCM authenticated encrypt. Each supported tag length will be tested at least once per set of 10. The IV value may be supplied by the evaluator or the implementation being tested, as long as it is known.

The evaluator will test the decrypt functionality using a set of 10 key, ciphertext, tag, AAD, and IV 5-tuples for each combination of parameter lengths above and obtain a Pass/Fail result on authentication and the decrypted plaintext if Pass. The set will include five tuples that Pass and five that Fail.

The results from each test may either be obtained by the evaluator directly or by supplying the inputs to the implementer and receiving the results in response. To determine correctness, the evaluator will compare the resulting values to those obtained by submitting the same inputs to a known good implementation.

AES-CCM Tests

The evaluator will test the generation-encryption and decryption-verification functionality of AES-CCM for the following input parameter and tag lengths:

- 128 bit and 256 bit keys
- Two payload lengths. One payload length will be the shortest supported payload length, greater than or equal to zero bytes. The other payload length will be the longest supported payload length, less than or equal to 32 bytes (256 bits).
- Two or three associated data lengths. One associated data length will be 0, if supported. One associated data length will be the shortest supported payload length, greater than or equal to zero bytes. One associated data length will be the longest supported payload length, less than or equal to 32 bytes (256 bits). If the implementation supports an associated data length of 216 bytes, an associated data length of 216 bytes will be tested.
- Nonce lengths. All supported nonce lengths between 7 and 13 bytes, inclusive, will be tested.
- Tag lengths. All supported tag lengths of 4, 6, 8, 10, 12, 14 and 16 bytes will be tested.

To test the generation-encryption functionality of AES-CCM, the evaluator will perform the following four tests:

- **Test 1:** For EACH supported key and associated data length and ANY supported payload, nonce and tag length, the evaluator will supply one key value, one nonce value and 10 pairs of associated data and payload values and obtain the resulting ciphertext.
- **Test 2:** For EACH supported key and payload length and ANY supported associated data, nonce and tag length, the evaluator will supply one key value, one nonce value and 10 pairs of associated data and payload values and obtain the resulting ciphertext.
- **Test 3:** For EACH supported key and nonce length and ANY supported associated data, payload and tag length, the evaluator will supply one key value and 10 associated data, payload and nonce value 3-tuples and obtain the resulting ciphertext.
- **Test 4:** For EACH supported key and tag length and ANY supported associated data, payload and nonce length, the evaluator will supply one key value, one nonce value and 10 pairs of associated data and payload values and obtain the resulting ciphertext.

To determine correctness in each of the above tests, the evaluator will compare the ciphertext with the result of generation-encryption of the same inputs with a known good implementation.

To test the decryption-verification functionality of AES-CCM, for EACH combination of supported associated data length, payload length, nonce length and tag length, the evaluator will supply a key value and 15 nonce, associated data and ciphertext 3-tuples and obtain either a FAIL result or a PASS result with the decrypted payload. The evaluator will supply 10 tuples that should FAIL and 5 that should PASS per set of 15.

Additionally, the evaluator will use tests from the IEEE 802.11-02/362r6 document "Proposed Test vectors for IEEE 802.11 TGi", dated September 10, 2002, Section 2.1 AESCCMP Encapsulation Example and Section 2.2 Additional AES CCMP Test Vectors to further verify the IEEE 802.11-2007 implementation of AES-CCMP.

AES-GCM Test

The evaluator will test the authenticated encrypt functionality of AES-GCM for each combination of the following input parameter lengths:

- 128 bit and 256 bit keys
- Two plaintext lengths. One of the plaintext lengths will be a non-zero integer multiple of 128 bits, if supported. The other plaintext length will not be an integer multiple of 128 bits, if supported.
- Three AAD lengths. One AAD length will be 0, if supported. One AAD length will be a non-zero integer multiple of 128 bits, if supported. One AAD length will not be an integer multiple of 128 bits, if supported.
- Two IV lengths. If 96 bit IV is supported, 96 bits will be one of the two IV lengths tested.

The evaluator will test the encrypt functionality using a set of 10 key, plaintext, AAD, and IV tuples for each combination of parameter lengths above and obtain the ciphertext value and tag that results from AES-GCM authenticated encrypt. Each supported tag length will be tested at least once per set of 10. The IV value may be supplied by the evaluator or the implementation being tested, as long as it is known.

The evaluator will test the decrypt functionality using a set of 10 key, ciphertext, tag, AAD, and IV 5-tuples for each combination of parameter lengths above and obtain a Pass/Fail result on authentication and the decrypted plaintext if Pass. The set will include five tuples that Pass and five that Fail.

The results from each test may either be obtained by the evaluator directly or by supplying the inputs to the implementer and receiving the results in response. To determine correctness, the evaluator will compare the resulting values to those obtained by submitting the same inputs to a known good implementation.

XTS-AES Test

The evaluator will test the encrypt functionality of XTS-AES for each combination of the following input parameter lengths:

- 256 bit (for AES-128) and 512 bit (for AES-256) keys
- Three data unit (i.e., plaintext) lengths. One of the data unit lengths will be a nonzero integer multiple of 128 bits, if supported. One of the data unit lengths will be an integer multiple of 128 bits, if supported. The third data unit length will be either the longest supported data unit length or 216 bits, whichever is smaller.

using a set of 100 (key, plaintext and 128-bit random tweak value) 3-tuples and obtain the ciphertext that results from XTS-AES encrypt.

The evaluator may supply a data unit sequence number instead of the tweak value if the implementation supports it. The data unit sequence number is a base-10 number ranging between 0 and 255 that implementations convert to a tweak value internally.

The evaluator will test the decrypt functionality of XTS-AES using the same test as for encrypt, replacing plaintext values with ciphertext values and XTS-AES encrypt with XTS-AES decrypt.

AES Key Wrap (AES-KW) and Key Wrap with Padding (AES-KWP) Test

The evaluator will test the authenticated encryption functionality of AES-KW for EACH combination of the following input parameter lengths:

- 128 and 256 bit key encryption keys (KEKs)
- Three plaintext lengths. One of the plaintext lengths will be two semi-blocks (128 bits). One of the plaintext lengths will be three semi-blocks (192 bits). The third data unit length will be the longest supported plaintext length less than or equal to 64 semi-blocks (4096 bits).

using a set of 100 key and plaintext pairs and obtain the ciphertext that results from AES-KW authenticated encryption. To determine correctness, the evaluator will use the AES-KW authenticated-encryption function of a known good implementation.

The evaluator will test the authenticated-decryption functionality of AES-KW using the same test as for authenticated-encryption, replacing plaintext values with ciphertext values and AES-KW authenticated-encryption with AES-KW authenticated-decryption.

The evaluator will test the authenticated-encryption functionality of AES-KWP using the same test as for AES-KW authenticated-encryption with the following change in the three plaintext lengths:

- One plaintext length will be one octet. One plaintext length will be 20 octets (160 bits).
- One plaintext length will be the longest supported plaintext length less than or equal to 512 octets (4096 bits).

The evaluator will test the authenticated-decryption functionality of AES-KWP using the same test as for AES-KWP authenticated-encryption, replacing plaintext values with ciphertext values and AES-KWP authenticated-encryption with AES-KWP authenticated-decryption.

FCS_COP.1/HASH Cryptographic Operation - Hashing (Refined)

FCS_COP.1.1/HASH

The **OS** shall perform [cryptographic hashing services] in accordance with a specified cryptographic algorithm **[selection:**

- **SHA-1**

- **SHA-256**
- **SHA-384**
- **SHA-512**

] and message digest sizes [selection:

- **160 bits**
- **256 bits**
- **384 bits**
- **512 bits**

] that meet the following: [FIPS Pub 180-4].

Application Note: Per NIST SP 800-131A, SHA-1 for generating digital signatures is no longer allowed, and SHA-1 for verification of digital signatures is strongly discouraged as there is risk in accepting these signatures.

Vendors are strongly encouraged to implement updated protocols that support the SHA-2 family; until updated protocols are supported, this PP allows support for SHA-1 implementations in compliance with SP 800-131A.

The intent of this requirement is to specify the hashing function. The hash selection must support the message digest size selection. The hash selection should be consistent with the overall strength of the algorithm used.

Evaluation Activities ▼

[FCS_COP.1/HASH](#)

Tests

The evaluator will check that the association of the hash function with other application cryptographic functions (for example, the digital signature verification function) is documented in the TSS.

The TSF hashing functions can be implemented in one of two modes. The first mode is the byte-oriented mode. In this mode the TSF only hashes messages that are an integral number of bytes in length; i.e., the length (in bits) of the message to be hashed is divisible by 8. The second mode is the bit-oriented mode. In this mode the TSF hashes messages of arbitrary length. As there are different tests for each mode, an indication is given in the following sections for the bit-oriented vs. the byte-oriented testmacs. The evaluator will perform all of the following tests for each hash algorithm implemented by the TSF and used to satisfy the requirements of this PP.

The following tests require the developer to provide access to a test application that provides the evaluator with tools that are typically not found in the production application.

- **Test 1: Short Messages Test (Bit oriented Mode)** - The evaluator will generate an input set consisting of $m+1$ messages, where m is the block length of the hash algorithm. The length of the messages range sequentially from 0 to m bits. The message text will be pseudorandomly generated. The evaluator will compute the message digest for each of the messages and ensure that the correct result is produced when the messages are provided to the TSF.
- **Test 2: Short Messages Test (Byte oriented Mode)** - The evaluator will generate an input set consisting of $m/8+1$ messages, where m is the block length of the hash algorithm. The length of the messages range sequentially from 0 to $m/8$ bytes, with each message being an integral number of bytes. The message text will be pseudorandomly generated. The evaluator will compute the message digest for each of the messages and ensure that the correct result is produced when the messages are provided to the TSF.
- **Test 3: Selected Long Messages Test (Bit oriented Mode)** - The evaluator will generate an input set consisting of m messages, where m is the block length of the hash algorithm. The length of the i th message is $512 + 99 \cdot i$, where $1 \leq i \leq m$. The message text will be pseudorandomly generated. The evaluator will compute the message digest for each of the messages and ensure that the correct result is produced when the messages are provided to the TSF.
- **Test 4: Selected Long Messages Test (Byte oriented Mode)** - The evaluator will generate an input set consisting of $m/8$ messages, where m is the block length of the hash algorithm. The length of the i th message is $512 + 8 \cdot 99 \cdot i$, where $1 \leq i \leq m/8$. The message text will be pseudorandomly generated. The evaluator will compute the message digest for each of the messages and ensure that the correct result is produced when the messages are provided to the TSF.
- **Test 5: Pseudorandomly Generated Messages Test** - This test is for byte-oriented implementations only. The evaluator will randomly generate a seed that is n bits long, where n is the length of the message digest produced by the hash function to be tested. The evaluator will then formulate a set of 100 messages and associated digests by following the algorithm provided in Figure 1 of [SHAVS]. The evaluator will then ensure that the correct result is produced when the messages are provided to the TSF.

FCS_COP.1/SIGN Cryptographic Operation - Signing (Refined)

FCS_COP.1.1/SIGN

The **OS** shall perform [cryptographic signature services (generation and

verification)] in accordance with a specified cryptographic algorithm [selection:

- **RSA schemes using cryptographic key sizes of 2048-bit or greater that meet the following: FIPS PUB 186-4, "Digital Signature Standard (DSS)", Section 4**
- **ECDSA schemes using "NIST curves" P-256, P-384 and [selection: P-521, no other curves] that meet the following: FIPS PUB 186-4, "Digital Signature Standard (DSS)", Section 5**

] and cryptographic key sizes [assignment: cryptographic algorithm] that meet the following: [assignment: list of standards].

Application Note: The ST Author should choose the algorithm implemented to perform digital signatures; if more than one algorithm is available, this requirement should be iterated to specify the functionality. For the algorithm chosen, the ST author should make the appropriate assignments/selections to specify the parameters that are implemented for that algorithm.

Evaluation Activities ▼

[FCS_COP.1/SIGN](#)

Tests

The evaluator will perform the following activities based on the selections in the ST.

The following tests require the developer to provide access to a test application that provides the evaluator with tools that are typically not found in the production application.

ECDSA Algorithm Tests

- **Test 1:** ECDSA FIPS 186-4 Signature Generation Test. For each supported NIST curve (i.e., P-256, P-384 and P-521) and SHA function pair, the evaluator will generate 10 1024-bit long messages and obtain for each message a public key and the resulting signature values R and S. To determine correctness, the evaluator will use the signature verification function of a known good implementation.
- **Test 2:** ECDSA FIPS 186-4 Signature Verification Test. For each supported NIST curve (i.e., P-256, P-384 and P-521) and SHA function pair, the evaluator will generate a set of 10 1024-bit message, public key and signature tuples and modify one of the values (message, public key or signature) in five of the 10 tuples. The evaluator will verify that 5 responses indicate success and 5 responses indicate failure.

RSA Signature Algorithm Tests

- **Test 1:** Signature Generation Test. The evaluator will verify the implementation of RSA Signature Generation by the OS using the Signature Generation Test. To conduct this test the evaluator must generate or obtain 10 messages from a trusted reference implementation for each modulus size/SHA combination supported by the TSF. The evaluator will have the OS use its private key and modulus value to sign these messages. The evaluator will verify the correctness of the TSF' signature using a known good implementation and the associated public keys to verify the signatures.
- **Test 2:** Signature Verification Test. The evaluator will perform the Signature Verification test to verify the ability of the OS to recognize another party' valid and invalid signatures. The evaluator will inject errors into the test vectors produced during the Signature Verification Test by introducing errors in some of the public keys, e, messages, IR format, and/or signatures. The evaluator will verify that the OS returns failure when validating each signature.

FCS_COP.1/KEYHMAC Cryptographic Operation - Keyed-Hash Message Authentication (Refined)

FCS_COP.1.1/KEYHMAC

The OS shall perform [keyed-hash message authentication services] in accordance with a specified cryptographic algorithm [selection: **SHA-1, SHA-256, SHA-384, SHA-512**] with key sizes [assignment: **key size (in bits) used in HMAC**] and message digest sizes [selection: 160 bits, 256 bits, 384 bits, 512 bits] that meet the following: [FIPS Pub 198-1 The Keyed-Hash Message Authentication Code and FIPS Pub 180-4 Secure Hash Standard].

Application Note: The intent of this requirement is to specify the keyed-hash message authentication function used for key establishment purposes for the various cryptographic protocols used by the OS (e.g., trusted channel). The hash selection must support the message digest size selection. The hash selection should be consistent with the overall strength of the algorithm used for [FCS_COP.1/HASH](#).

Evaluation of SHA-1 is currently permitted in order to allow for evaluation of TLS or DTLS ciphersuites that may be selected in the TLS Package.

Evaluation Activities ▼

Tests

The evaluator will perform the following activities based on the selections in the ST.

For each of the supported parameter sets, the evaluator will compose 15 sets of test data. Each set consists of a key and message data. The evaluator will have the OS generate HMAC tags for these sets of test data. The resulting MAC tags will be compared against the result of generating HMAC tags with the same key and IV using a known-good implementation.

FCS_RBG_EXT.1 Random Bit Generation

FCS_RBG_EXT.1.1

The OS shall perform all deterministic random bit generation (DRBG) services in accordance with NIST Special Publication 800-90A using [selection:

- *Hash_DRBG (any)*
- *HMAC_DRBG (any)*
- *CTR_DRBG (AES)*

] .

Application Note: NIST SP 800-90A contains three different methods of generating random numbers; each of these, in turn, depends on underlying cryptographic primitives (hash functions/ciphers). The ST author will select the function used and include the specific underlying cryptographic primitives used in the requirement or in the TSS. While any of the identified hash functions (SHA-1, SHA-224, SHA-256, SHA-384, SHA-512) are allowed for Hash_DRBG or HMAC_DRBG, only AES-based implementations for CTR_DRBG are allowed.

FCS_RBG_EXT.1.2

The deterministic RBG used by the OS shall be seeded by an entropy source that accumulates entropy from a [selection:

- *software-based noise source*
- *platform-based noise source*

] with a minimum of [selection:

- *128 bits*
- *256 bits*

] of entropy at least equal to the greatest security strength (according to NIST SP 800-57) of the keys and hashes that it will generate.

Application Note: For the first selection in this requirement, the ST author selects 'software-based noise source' if any additional noise sources are used as input to the DRBG.

In the second selection in this requirement, the ST author selects the appropriate number of bits of entropy that corresponds to the greatest security strength of the algorithms included in the ST. Security strength is defined in Tables 2 and 3 of NIST SP 800-57A. For example, if the implementation includes 2048-bit RSA (security strength of 112 bits), AES 128 (security strength 128 bits), and HMAC-SHA-256 (security strength 256 bits), then the ST author would select 256 bits.

Evaluation Activities ▼[FCS_RBG_EXT.1](#)**Tests**

The evaluator will perform the following tests:

The evaluator will perform 15 trials for the RNG implementation. If the RNG is configurable, the evaluator will perform 15 trials for each configuration. The evaluator will also confirm that the operational guidance contains appropriate instructions for configuring the RNG functionality.

If the RNG has prediction resistance enabled, each trial consists of (1) instantiate DRBG, (2) generate the first block of random bits (3) generate a second block of random bits (4) uninstantiate. The evaluator verifies that the second block of random bits is the expected value. The evaluator will generate eight input values for each trial. The first is a count (0 - 14). The next three are entropy input, nonce, and personalization string for the instantiate operation. The next two are additional input and entropy input for the first call to generate. The final two are additional input and entropy input for the second call to generate. These values are randomly generated. "generate one block of random bits" means to generate random bits with number of returned bits equal to the Output Block Length (as defined in NIST SP 800-90A).

If the RNG does not have prediction resistance, each trial consists of (1) instantiate DRBG, (2) generate the first block of random bits (3) reseed, (4) generate a second block of random bits (5) uninstantiate. The evaluator verifies that the second block of random bits is the expected value. The evaluator will generate eight input values for each trial. The first is a count (0 - 14). The next three are entropy input, nonce, and personalization string for the instantiate operation. The

fifth value is additional input to the first call to generate. The sixth and seventh are additional input and entropy input to the call to reseed. The final value is additional input to the second generate call.

The following list contains more information on some of the input values to be generated/selected by the evaluator.

- **Entropy input:** The length of the entropy input value must equal the seed length.
- **Nonce:** If a nonce is supported (CTR_DRBG with no Derivation Function does not use a nonce), the nonce bit length is one-half the seed length.
- **Personalization string:** The length of the personalization string must be less than or equal to seed length. If the implementation only supports one personalization string length, then the same length can be used for both values. If more than one string length is support, the evaluator will use personalization strings of two different lengths. If the implementation does not use a personalization string, no value needs to be supplied.
- **Additional input:** The additional input bit lengths have the same defaults and restrictions as the personalization string lengths.

Documentation will be produced - and the evaluator will perform the activities - in accordance with [Appendix C - Entropy Documentation and Assessment](#) and the [Clarification to the Entropy Documentation and Assessment Annex](#).

In the future, specific statistical testing (in line with NIST SP 800-90B) will be required to verify the entropy estimates.

FCS_STO_EXT.1 Storage of Sensitive Data

FCS_STO_EXT.1.1

The OS shall implement functionality to encrypt sensitive data stored in non-volatile storage and provide interfaces to applications to invoke this functionality.

Application Note: Sensitive data will be identified in the TSS by the ST author, and minimally includes credentials and keys. The interface for invoking the functionality could take a variety of forms: it could consist of an API, or simply well-documented conventions for accessing credentials stored as files.

Evaluation Activities ▼

[FCS_STO_EXT.1](#)

TSS

The evaluator will check the TSS to ensure that it lists all persistent sensitive data for which the OS provides a storage capability. For each of these items, the evaluator will confirm that the TSS lists for what purpose it can be used, and how it is stored. The evaluator will confirm that cryptographic operations used to protect the data occur as specified in [FCS_COP.1/HASH](#).

The evaluator will also consult the developer documentation to verify that an interface exists for applications to securely store credentials.

5.1.2 User Data Protection (FDP)

FDP_ACF_EXT.1 Access Controls for Protecting User Data

FDP_ACF_EXT.1.1

The OS shall implement access controls which can prohibit unprivileged users from accessing files and directories owned by other users.

Application Note: Effective protection by access controls may also depend upon system configuration. This requirement is designed to ensure that, for example, files and directories owned by one user in a multi user system can be protected from access by another user in that system.

Evaluation Activities ▼

[FDP_ACF_EXT.1](#)

TSS

The evaluator will confirm that the TSS comprehensively describes the access control policy enforced by the OS. The description must include the rules by which accesses to particular files and directories are determined for particular users. The evaluator will inspect the TSS to ensure that it describes the access control rules in such detail that given any possible scenario between a user and a file governed by the OS the access control decision is unambiguous.

Tests

The evaluator will create two new standard user accounts on the system and conduct the

following tests:

- **Test 1:** The evaluator will authenticate to the system as the first user and create a file within that user's home directory. The evaluator will then log off the system and log in as the second user. The evaluator will then attempt to read the file created in the first user's home directory. The evaluator will ensure that the read attempt is denied.
- **Test 2:** The evaluator will authenticate to the system as the first user and create a file within that user's home directory. The evaluator will then log off the system and log in as the second user. The evaluator will then attempt to modify the file created in the first user's home directory. The evaluator will ensure that the modification is denied.
- **Test 3:** The evaluator will authenticate to the system as the first user and create a file within that user's user directory. The evaluator will then log off the system and log in as the second user. The evaluator will then attempt to delete the file created in the first user's home directory. The evaluator will ensure that the deletion is denied.
- **Test 4:** The evaluator will authenticate to the system as the first user. The evaluator will attempt to create a file in the second user's home directory. The evaluator will ensure that the creation of the file is denied.
- **Test 5:** The evaluator will authenticate to the system as the first user and attempt to modify the file created in the first user's home directory. The evaluator will ensure that the modification of the file is accepted.
- **Test 6:** The evaluator will authenticate to the system as the first user and attempt to delete the file created in the first user's directory. The evaluator will ensure that the deletion of the file is accepted.

FDP_IFC_EXT.1 Information flow control

This is a selection-based component. Its inclusion depends upon selection from [FTP_ITC_EXT.1.1](#) .

This component may also be included in the ST as if optional.

FDP_IFC_EXT.1.1

The OS shall [**selection:**

- provide an interface which allows a VPN client to protect all IP traffic using IPsec
- provide a VPN client that can protect all IP traffic using IPsec

] with the exception of IP traffic required to establish the VPN connection and [**selection:** signed updates directly from the OS vendor, no other traffic] .

Application Note: Typically, the traffic required to establish the VPN connection is referred to as "Control Plane" traffic, whereas the IP traffic protected by the IPsec VPN is referred to as "Data Plane" traffic. All Data Plane traffic must flow through the VPN connection and the VPN must not split-tunnel. If no native IPsec client is validated or third-party VPN clients may also implement the required Information Flow Control, the first option will be selected. In these cases, the TOE provides an API to third-party VPN clients that allows them to configure the TOE's network stack to perform the required Information Flow Control.

If the TSF implements a native VPN client, then the ST author will select [provide a VPN client](#) and includes the PP-Module for VPN Client as part of the ST.

In the future, this requirement may also make a distinction between the current requirement (which requires that when the IPsec trusted channel is enabled, all traffic from the TSF is routed through that channel) and having an option to force the establishment of an IPsec trusted channel to allow any communication by the TSF.

Evaluation Activities ▼

[FDP_IFC_EXT.1](#)

TSS

The evaluator will verify that the TSS section of the ST describes the routing of IP traffic when a VPN client is enabled. The evaluator will ensure that the description indicates which traffic does not go through the VPN and which traffic does, and that a configuration exists for each in which only the traffic identified by the ST author as necessary for establishing the VPN connection (IKE traffic and perhaps HTTPS or DNS traffic) is not encapsulated by the VPN protocol (IPsec).

Tests

The evaluator will perform the following test:

- **Test 1:**
 - **Step 1:** The evaluator will enable a network connection. The evaluator will sniff packets while performing running applications that use the network such as web browsers and email clients. The evaluator will verify that the sniffer captures the

- traffic generated by these actions, turn off the sniffing tool, and save the session data.
- **Step 2:** The evaluator will configure an IPsec VPN client that supports the routing specified in this requirement. The evaluator will turn on the sniffing tool, establish the VPN connection, and perform the same actions with the device as performed in the first step. The evaluator will verify that the sniffing tool captures traffic generated by these actions, turn off the sniffing tool, and save the session data.
 - **Step 3:** The evaluator will examine the traffic from both step one and step two to verify that all non-expected Data Plane traffic in Step 2 is encapsulated by IPsec. The evaluator will examine the Security Parameter Index (SPI) value present in the encapsulated packets captured in Step 2 from the TOE to the Gateway and will verify this value is the same for all actions used to generate traffic through the VPN. Note that it is expected that the SPI value for packets from the Gateway to the TOE is different than the SPI value for packets from the TOE to the Gateway.
 - **Step 4:** The evaluator will perform a ping on the TOE host on the local network and verify that no packets sent are captured with the sniffer. The evaluator will attempt to send packets to the TOE outside the VPN tunnel (i.e. not through the VPN gateway), including from the local network, and verify that the TOE discards them.

5.1.3 Security Management (FMT)

FMT_MOF_EXT.1 Management of security functions behavior

FMT_MOF_EXT.1.1

The OS shall restrict the ability to perform the function indicated in the "Administrator" column in [FMT_SMF_EXT.1.1](#) to the administrator.

Application Note: The functions with an "X" in the "Administrator" column must be restricted to (or overridden by) the administrator in the TOE. The functions with an "O" in the "Administrator" column may be restricted to (or overridden by) the administrator when implemented in the TOE at the discretion of the ST author. For such functions, the ST author indicates this by replacing an "O" with an "X" in the ST.

Evaluation Activities ▼

[FMT_MOF_EXT.1](#)

TSS

The evaluator will verify that the TSS describes those management functions that are restricted to Administrators, including how the user is prevented from performing those functions, or not able to use any interfaces that allow access to that function.

Tests

The evaluator will also perform the following test.

- **Test 1:** For each function that is indicated as restricted to the administrator, the evaluation will perform the function as an administrator, as specified in the Operational Guidance, and determine that it has the expected effect as outlined by the Operational Guidance and the SFR. The evaluator will then perform the function (or otherwise attempt to access the function) as a non-administrator and observe that they are unable to invoke that functionality.

FMT_SMF_EXT.1 Specification of Management Functions

FMT_SMF_EXT.1.1

The OS shall be capable of performing the following management functions:

#	Management Function	Administrator	User
1	Enable/disable [selection: screen lock, session timeout]	M	O
2	Configure [selection: screen lock, session] inactivity timeout	M	O
3	import keys/secrets into the secure key storage	O	O
4	Configure local audit storage capacity	O	O
5	Configure minimum password length	O	O
6	Configure minimum number of special characters in password	O	O
7	Configure minimum number of numeric characters in password	O	O

8	Configure minimum number of uppercase characters in password	O	O
9	Configure minimum number of lowercase characters in password	O	O
10	Configure lockout policy for unsuccessful authentication attempts through [selection: <i>timeouts between attempts, limiting number of attempts during a time period</i>]	O	O
11	Configure host-based firewall	O	O
12	Configure name/address of directory server with which to bind	O	O
13	Configure name/address of remote management server from which to receive management settings	O	O
14	Configure name/address of audit/logging server to which to send audit/logging records	O	O
15	Configure audit rules	O	O
16	Configure name/address of network time server	O	O
17	Enable/disable automatic software update	O	O
18	Configure WiFi interface	O	O
19	Enable/disable Bluetooth interface	O	O
20	Enable/disable [assignment: <i>list of other external interfaces</i>]	O	O
21	[assignment: <i>list of other management functions to be provided by the TSF</i>]	O	O

Application Note: The ST should indicate which of the optional management functions are implemented in the TOE. This can be done by copying the above table into the ST and adjusting the "Administrator" and "User" columns to "X" according to which capabilities are present or not present, and for which privilege level. The Application Note for [FMT_MOF_EXT.1](#) explains how to indicate Administrator or User capability.

The terms "Administrator" and "User" are defined in [Section glossary](#). The intent of this requirement is to ensure that the ST is populated with the relevant management functions that are provided by the OS.

Sophisticated account management policies, such as intricate password complexity requirements and handling of temporary accounts, are a function of directory servers. The OS can enroll in such account management and enable the overall information system to achieve such policies by binding to a directory server.

Evaluation Activities ▼

[FMT_SMF_EXT.1](#)

Guidance

The evaluator will verify that every management function captured in the ST is described in the operational guidance and that the description contains the information required to perform the management duties associated with the management function.

Tests

The evaluator will test the OS's ability to provide the management functions by configuring the operating system and testing each option selected from above. The evaluator is expected to test these functions in all the ways in which the ST and guidance documentation state the configuration can be managed.

5.1.4 Protection of the TSF (FPT)

FPT_ACF_EXT.1 Access controls

FPT_ACF_EXT.1.1

The OS shall implement access controls which prohibit unprivileged users from modifying:

- Kernel and its drivers/modules
- Security audit logs
- Shared libraries
- System executables
- System configuration files
- **[assignment: other objects]**

FPT_ACF_EXT.1.2

The OS shall implement access controls which prohibit unprivileged users from reading:

- Security audit logs
- System-wide credential repositories
- **[assignment: list of other objects]**

Application Note: "Credential repositories" refer, in this case, to structures containing cryptographic keys or passwords.

Evaluation Activities ▼

[FPT_ACF_EXT.1](#)

TSS

The evaluator will confirm that the TSS specifies the locations of kernel drivers/modules, security audit logs, shared libraries, system executables, and system configuration files. Every file does not need to be individually identified, but the system's conventions for storing and protecting such files must be specified.

Tests

The evaluator will create an unprivileged user account. Using this account, the evaluator will ensure that the following tests result in a negative outcome (i.e., the action results in the OS denying the evaluator permission to complete the action):

- **Test 1:** The evaluator will attempt to modify all kernel drivers and modules.
- **Test 2:** The evaluator will attempt to modify all security audit logs generated by the logging subsystem.
- **Test 3:** The evaluator will attempt to modify all shared libraries that are used throughout the system.
- **Test 4:** The evaluator will attempt to modify all system executables.
- **Test 5:** The evaluator will attempt to modify all system configuration files.
- **Test 6:** The evaluator will attempt to modify any additional components selected.

The evaluator will create an unprivileged user account. Using this account, the evaluator will ensure that the following tests result in a negative outcome (i.e., the action results in the OS denying the evaluator permission to complete the action):

- **Test 1:** The evaluator will attempt to read security audit logs generated by the auditing subsystem
- **Test 2:** The evaluator will attempt to read system-wide credential repositories
- **Test 3:** The evaluator will attempt to read any other object specified in the assignment

FPT_ASLR_EXT.1 Address Space Layout Randomization

FPT_ASLR_EXT.1.1

The OS shall always randomize process address space memory locations with **[selection: 8, [assignment: number greater than 8]]** bits of entropy except for **[assignment: list of explicit exceptions]**.

Evaluation Activities ▼

[FPT_ASLR_EXT.1](#)

Tests

The evaluator will select 3 executables included with the TSF. If the TSF includes a web browser it must be selected. If the TSF includes a mail client it must be selected. For each of these apps, the evaluator will launch the same executables on two separate instances of the OS on identical hardware and compare all memory mapping locations. The evaluator will ensure that no memory mappings are placed in the same location. If the rare chance occurs that two mappings are the same for a single executable and not the same for the other two, the evaluator will repeat the test with that executable to verify that in the second test the mappings are different. This test can also be completed on the same hardware and rebooting between application launches.

FPT_SBOP_EXT.1 Stack Buffer Overflow Protection

FPT_SBOP_EXT.1.1

The OS shall [**selection:** *employ stack-based buffer overflow protections, not store parameters/variables in the same data structures as control flow values*].

Application Note: Many OSes store control flow values (i.e. return addresses) in stack data structures that also contain parameters and variables. For these OSes, it is expected that most of the OS, to include the kernel, libraries, and application software from the OS vendor be compiled with stack-based buffer overflow protection enabled. OSes that store parameters and variables separately from control flow values do not need additional stack protections.

Evaluation Activities ▼

[FPT_SBOP_EXT.1](#)

Tests

For stack-based OSes, the evaluator will determine that the TSS contains a description of stack-based buffer overflow protections used by the OS. These are referred to by a variety of terms, such as stack cookie, stack guard, and stack canaries. The TSS must include a rationale for any binaries that are not protected in this manner. The evaluator will also preform the following test:

- **Test 1:** The evaluator will inventory the kernel, libraries, and application binaries to determine those that do not implement stack-based buffer overflow protections. This list should match up with the list provided in the TSS.

For OSes that store parameters/variables separately from control flow values, the evaluator will verify that the TSS describes what data structures control values, parameters, and variables are stored. The evaluator will also ensure that the TSS includes a description of the safeguards that ensure parameters and variables do not intermix with control flow values.

FPT_SRP_EXT.1 Software Restriction Policies

This is an objective component.

FPT_SRP_EXT.1.1

The OS shall restrict execution to only programs which match an administrator-specified [**selection:**

- *file path*
- *file digital signature*
- *version*
- *hash*
- [**assignment:** *other characteristics*]

].

Application Note: The assignment permits implementations which provide a low level of granularity such as a volume. The restriction is only against direct execution of executable programs. It does not forbid interpreters which may take data as an input, even if this data can subsequently result in arbitrary computation.

Evaluation Activities ▼

[FPT_SRP_EXT.1](#)

Tests

For each selection specified in the ST, the evaluator will ensure that the corresponding tests result in a negative outcome (i.e., the action results in the OS denying the evaluator permission to complete the action):

- **Test 1:** The evaluator will configure the OS to only allow code execution from the core OS directories. The evaluator will then attempt to execute code from a directory that is in the allowed list. The evaluator will ensure that the code they attempted to execute has been executed.
- **Test 2:** The evaluator will configure the OS to only allow code execution from the core OS directories. The evaluator will then attempt to execute code from a directory that is not in the allowed list. The evaluator will ensure that the code they attempted to execute has not been executed.
- **Test 3:** The evaluator will configure the OS to only allow code that has been signed by the OS vendor to execute. The evaluator will then attempt to execute code signed by the OS vendor. The evaluator will ensure that the code they attempted to execute has been executed.
- **Test 4:** The evaluator will configure the OS to only allow code that has been signed by the OS vendor to execute. The evaluator will then attempt to execute code signed by another digital authority. The evaluator will ensure that the code they attempted to execute has not been executed.
- **Test 5:** The evaluator will configure the OS to allow execution of a specific application

based on version. The evaluator will then attempt to execute the same version of the application. The evaluator will ensure that the code they attempted to execute has been executed.

- **Test 6:** The evaluator will configure the OS to allow execution of a specific application based on version. The evaluator will then attempt to execute an older version of the application. The evaluator will ensure that the code they attempted to execute has not been executed.
- **Test 7:** The evaluator will configure the OS to allow execution based on the hash of the application executable. The evaluator will then attempt to execute the application with the matching hash. The evaluator will ensure that the code they attempted to execute has been executed.
- **Test 8:** The evaluator will configure the OS to allow execution based on the hash of the application executable. The evaluator will modify the application in such a way that the application hash is changed. The evaluator will then attempt to execute the application with the matching hash. The evaluator will ensure that the code they attempted to execute has not been executed.

FPT_TST_EXT.1 Boot Integrity

FPT_TST_EXT.1.1

The OS shall verify the integrity of the bootchain up through the OS kernel and [selection:

- all executable code stored in mutable media
- [assignment: list of other executable code]
- no other executable code

] prior to its execution through the use of [selection:

- a digital signature using a hardware-protected asymmetric key
- a digital signature using an X509 certificate with hardware-based protection
- a hardware-protected hash

].

Application Note: The bootchain of the OS is the sequence of software, to include the OS loader, the kernel, system drivers or modules, and system files, which ultimately result in loading the OS. The first part of the OS, usually referred to as the first-stage bootloader, must be loaded by the platform. Assessing its integrity, while critical, is the platform's responsibility; and therefore outside the scope of this PP. All software loaded after this stage is potentially within the control of the OS and is in scope.

The verification may be transitive in nature: a hardware-protected public key, X509 certificate or hash may be used to verify the mutable bootloader code which contains a key, certificate, or hash used by the bootloader to verify the mutable OS kernel code, which contains a key, certificate, or hash to verify the next layer of executable code, and so on. However, the way in which the hardware stores and protects these keys is out of scope.

If all executable code (including bootloader(s), kernel, device drivers, pre-loaded applications, user-loaded applications, and libraries) is verified, "all executable code stored in mutable media" should be selected.

Evaluation Activities ▼

FPT_TST_EXT.1

TSS

The evaluator will verify that the TSS section of the ST includes a comprehensive description of the boot procedures, including a description of the entire bootchain, for the TSF. The evaluator will ensure that the OS cryptographically verifies each piece of software it loads in the bootchain to include bootloaders and the kernel. Software loaded for execution directly by the platform (e.g. first-stage bootloaders) is out of scope. For each additional category of executable code verified before execution, the evaluator will verify that the description in the TSS describes how that software is cryptographically verified.

The evaluator will verify that the TSS contains a description of the protection afforded to the mechanism performing the cryptographic verification.

Tests

The evaluator will also perform the following tests:

- **Test 1:** The evaluator will perform actions to cause TSF software to load and observe that the integrity mechanism does not flag any executables as containing integrity errors and that the OS properly boots.
- **Test 2:** The evaluator will modify a TSF executable that is part of the bootchain verified by the TSF (i.e. Not the first-stage bootloader) and attempt to boot. The evaluator will ensure that an integrity violation is triggered and the OS does not boot (Care must be taken so that the integrity violation is determined to be the cause of the failure to load the module, and

not the fact that in such a way to invalidate the structure of the module.).

- **Test 3:** If the ST author indicates that the integrity verification is performed using public key in an X509 certificate, the evaluator will verify that the update mechanism includes a certificate validation according to [FIA_X509_EXT.1](#) for all certificates in the chain from the certificate used for boot integrity to a certificate in the trust store that are not themselves in the trust store. This means that, for each X509 certificate in this chain that is not a trust store element, the evaluator must ensure that revocation information is available to the TOE during the bootstrap mechanism (before the TOE becomes fully operational).

FPT_TUD_EXT.1 Trusted Update

FPT_TUD_EXT.1.1

The OS shall provide the ability to check for updates to the OS software itself and shall use a digital signature scheme specified in [FCS_COP.1/SIGN](#) to validate the authenticity of the response.

Application Note: This requirement is about the ability to check for the availability of authentic updates, while the installation of authentic updates is covered by [FPT_TUD_EXT.1.2](#). Use of the digital signature scheme ensures that an attacker cannot influence the response, regarding of whether updates are available.

FPT_TUD_EXT.1.2

The OS shall [**selection:** *cryptographically verify, invoke platform-provided functionality to cryptographically verify*] updates to itself using a digital signature prior to installation using schemes specified in [FCS_COP.1/SIGN](#).

Application Note: The intent of the requirement is to ensure that only digitally signed and verified TOE updates are applied to the TOE.

Evaluation Activities ▼

[FPT_TUD_EXT.1](#)

Tests

The evaluator will check for an update using procedures described in the documentation and verify that the OS provides a list of available updates. Testing this capability may require installing and temporarily placing the system into a configuration in conflict with secure configuration guidance which specifies automatic update.

The evaluator is also to ensure that the response to this query is authentic by using a digital signature scheme specified in [FCS_COP.1/SIGN](#). The digital signature verification may be performed as part of a network protocol occurs over a trusted channel as described in [FTP_ITC_EXT.1](#).) If the signature verification is not performed as part of a trusted channel, the evaluator will send a query response with a bad signature and verify that the signature verification fails. The evaluator will then send a query response with a good signature and verify that the signature verification is successful.

For the following tests, the evaluator will initiate the download of an update and capture the update prior to installation. The download could originate from the vendor's website, an enterprise-hosted update repository, or another system (e.g. network peer). All supported origins for the update must be indicated in the TSS and evaluated.

- **Test 1:** The evaluator will ensure that the update has a digital signature belonging to the vendor prior to its installation. The evaluator will modify the downloaded update in such a way that the digital signature is no longer valid. The evaluator will then attempt to install the modified update. The evaluator will ensure that the OS does not install the modified update.
- **Test 2:** The evaluator will ensure that the update has a digital signature belonging to the vendor. The evaluator will then attempt to install the update (or permit installation to continue). The evaluator will ensure that the OS successfully installs the update.

FPT_TUD_EXT.2 Trusted Update for Application Software

FPT_TUD_EXT.2.1

The OS shall provide the ability to check for updates to application software and shall use a digital signature scheme specified in [FCS_COP.1/SIGN](#) to validate the authenticity of the response.

Application Note: This requirement is about the ability to check for authentic updates, while the actual installation of such updates is covered by [FPT_TUD_EXT.2.2](#). Use of the digital signature scheme ensures that an attacker cannot influence the response, regarding of whether updates are available.

FPT_TUD_EXT.2.2

The OS shall cryptographically verify the integrity of updates to applications using a digital signature specified by [FCS_COP.1/SIGN](#) prior to installation.

[FPT_TUD_EXT.2](#)**Tests**

The evaluator will check for updates to application software using procedures described in the documentation and verify that the OS provides a list of available updates. Testing this capability may require temporarily placing the system into a configuration in conflict with secure configuration guidance which specifies automatic update.

The evaluator is also to ensure that the response to this query is authentic by using a digital signature scheme specified in [FCS_COP.1/SIGN](#). The digital signature verification may be performed as part of a network protocol as described in [FTP_ITC_EXT.1](#). If the signature verification is not performed as part of a trusted channel, the evaluator will send a query response with a bad signature and verify that the signature verification fails. The evaluator will then send a query response with a good signature and verify that the signature verification is successful.

The evaluator will initiate an update to an application. This may vary depending on the application, but it could be through the application vendor's website, a commercial app store, or another system. All origins supported by the OS must be indicated in the TSS and evaluated. However, this only includes those mechanisms for which the OS is providing a trusted installation and update functionality. It does not include user or administrator-driven download and installation of arbitrary files.

- **Test 1:** The evaluator will ensure that the update has a digital signature which chains to the OS vendor or another trusted root managed through the OS. The evaluator will modify the downloaded update in such a way that the digital signature is no longer valid. The evaluator will then attempt to install the modified update. The evaluator will ensure that the OS does not install the modified update.
- **Test 2:** The evaluator will ensure that the update has a digital signature belonging to the OS vendor or another trusted root managed through the OS. The evaluator will then attempt to install the update. The evaluator will ensure that the OS successfully installs the update.

FPT_W^X_EXT.1 Write XOR Execute Memory Pages

FPT_W^X_EXT.1.1

The OS shall prevent allocation of any memory region with both write and execute permissions except for [assignment: list of exceptions].

Application Note: Requesting a memory mapping with both write and execute permissions subverts the platform protection provided by DEP. If the OS provides no exceptions (such as for just-in-time compilation), then "no exceptions" should be indicated in the assignment. Full realization of this requirement requires hardware support, but this is commonly available.

[FPT_W^X_EXT.1](#)**TSS**

The evaluator will inspect the vendor-provided developer documentation and verify that no memory-mapping can be made with write and execute permissions except for the cases listed in the assignment.

Tests

The evaluator will also perform the following tests.

- **Test 1:** The evaluator will acquire or construct a test program which attempts to allocate memory that is both writable and executable. The evaluator will run the program and confirm that it fails to allocate memory that is both writable and executable.
- **Test 2:** The evaluator will acquire or construct a test program which allocates memory that is executable and then subsequently requests additional write/modify permissions on that memory. The evaluator will run the program and confirm that at no time during the lifetime of the process is the memory both writable and executable.
- **Test 3:** The evaluator will acquire or construct a test program which allocates memory that is writable and then subsequently requests additional execute permissions on that memory. The evaluator will run the program and confirm that at no time during the lifetime of the process is the memory both writable and executable.

5.1.5 Audit Data Generation (FAU)**FAU_GEN.1 Audit Data Generation (Refined)**

FAU_GEN.1.1

The OS shall be able to generate an audit record of the following auditable

events:

- a. Start-up and shut-down of the audit functions;
 - b. All auditable events for the [not specified] level of audit; and [
 - c.
 - Authentication events (Success/Failure);
 - Use of privileged/special rights events (Successful and unsuccessful security, audit, and configuration changes);
 - Privilege or role escalation events (Success/Failure);
 - **[selection:**
 - File and object events (Successful and unsuccessful attempts to create, access, delete, modify, modify permissions)
 - User and Group management events (Successful and unsuccessful add, delete, modify, disable, enable, and credential change)
 - Audit and log data access events (Success/Failure)
 - Cryptographic verification of software (Success/Failure)
 - Attempted application invocation with arguments (Success/Failure e.g. due to software restriction policy)
 - System reboot, restart, and shutdown events (Success/Failure)
 - Kernel module loading and unloading events (Success/Failure)
 - Administrator or root-level access events (Success/Failure)
 - **[assignment:** other specifically defined auditable events].
-]
-].

FAU_GEN.1.2

The **OS** shall record within each audit record at least the following information:

- a. Date and time of the event, type of event, subject identity (if applicable), and outcome (success or failure) of the event; and
- b. For each audit event type, based on the auditable event definitions of the functional components included in the PP/ST, **[assignment:** other audit relevant information]

Application Note: The term *subject* here is understood to be the user that the process is acting on behalf of. If no auditable event definitions of functional components are provided, then no additional audit-relevant information is required.

Evaluation Activities ▼

FAU_GEN.1

Guidance

The evaluator will check the administrative guide and ensure that it lists all of the auditable events. The evaluator will check to make sure that every audit event type selected in the ST is included.

The evaluator will check the administrative guide and ensure that it provides a format for audit records. Each audit record format type must be covered, along with a brief description of each field. The evaluator will ensure that the fields contains the information required.

Tests

The evaluator will test the OS's ability to correctly generate audit records by having the TOE generate audit records for the events listed in the ST. This should include all instance types of an event specified. When verifying the test results, the evaluator will ensure the audit records generated during testing match the format specified in the administrative guide, and that the fields in each audit record have the proper entries.

The evaluator will test the OS's ability to correctly generate audit records by having the TOE generate audit records for the events listed in the ST. The evaluator will ensure the audit records generated during testing match the format specified in the administrative guide, and that the fields in each audit record provide the required information.

5.1.6 Identification and Authentication (FIA)

FIA_AFL.1 Authentication failure handling (Refined)

FIA_AFL.1.1

The **OS** shall detect when **[selection:**

- **[assignment:** positive integer number]
- an administrator configurable positive integer within **[assignment:** range of acceptable values]

] unsuccessful authentication attempts occur related to **events with [selection:**

- **authentication based on user name and password**
- **authentication based on user name and a PIN that releases an asymmetric key stored in OE-protected storage**
- **authentication based on X.509 certificates**

1 .

FIA_AFL.1.2

When the defined number of unsuccessful authentication attempts for an account has been **met**, the **OS** shall: **[selection: Account Lockout, Account Disablement, Mandatory Credential Reset, [assignment: list of actions]]**

Application Note: The action to be taken will be populated in the assignment of the ST and defined in the administrator guidance.

Evaluation Activities ▼

FIA_AFL.1

Tests

The evaluator will set an administrator-configurable threshold for failed attempts, or note the ST-specified assignment. The evaluator will then (per selection) repeatedly attempt to authenticate with an incorrect password, PIN, or certificate until the number of attempts reaches the threshold. Note that the authentication attempts and lockouts must also be logged as specified in [FAU_GEN.1](#).

- **Test 1:** The evaluator will attempt to authenticate repeatedly to the system with a known bad password. Once the defined number of failed authentication attempts has been reached the evaluator will ensure that the account that was being used for testing has had the actions detailed in the assignment list above applied to it. The evaluator will ensure that an event has been logged to the security event log detailing that the account has had these actions applied.
- **Test 2:** The evaluator will attempt to authenticate repeatedly to the system with a known bad certificate. Once the defined number of failed authentication attempts has been reached the evaluator will ensure that the account that was being used for testing has had the actions detailed in the assignment list above applied to it. The evaluator will ensure that an event has been logged to the security event log detailing that the account has had these actions applied.
- **Test 3:** The evaluator will attempt to authenticate repeatedly to the system using both a bad password and a bad certificate. Once the defined number of failed authentication attempts has been reached the evaluator will ensure that the account that was being used for testing has had the actions detailed in the assignment list above applied to it. The evaluator will ensure that an event has been logged to the security event log detailing that the account has had these actions applied.

FIA_UAU.5 Multiple Authentication Mechanisms (Refined)

FIA_UAU.5.1

The **OS** shall provide the following authentication mechanisms **[selection:**

- **authentication based on user name and password**
- **authentication based on user name and a PIN that releases an asymmetric key stored in OE-protected storage**
- **combination of authentication based on user name, password, and time-based one-time password**
- **combination of authentication based on user name, password, and biometric identification factor**
- **authentication based on X.509 certificates**
- **for use in SSH only, SSH public key-based authentication as specified by the [Functional Package for Secure Shell \(SSH\), version 1.0](#)**

] to support user authentication.

Application Note: The [for use in SSH only, SSH public key-based authentication as specified by the Functional Package for Secure Shell \(SSH\), version 1.0](#) selection can only be included, and must be included, if [FTP_ITC_EXT.1.1](#) selects [SSH](#).

FIA_UAU.5.2

The **OS** shall authenticate any user's claimed identity according to the **[assignment: rules describing how the multiple authentication mechanisms provide authentication]**.

Application Note: For all authentication mechanisms specified in [FIA_UAU.5.1](#), the TSS will describe the rules as to how each authentication mechanism is used. Example rules are how the authentication mechanism authenticates the user (i.e. how does the TSF verify that the correct password or authentication factor is

used), the result of a successful authentication (i.e. is the user input used to derive or unlock a key) and which authentication mechanism can be used at which authentication factor interfaces (i.e. if there are times, for example, after a reboot, that only specific authentication mechanisms can be used). Rules regarding how the authentication factors interact in terms of unsuccessful authentication are covered in [FIA_AFL.1](#).

Evaluation Activities ▼

[FIA_UAU.5](#)

TSS

The evaluator will ensure that the TSS describes each mechanism provided to support user authentication and the rules describing how the authentication mechanism(s) provide authentication.

Guidance

The evaluator will verify that configuration guidance for each authentication mechanism is addressed in the AGD guidance.

Tests

If user name and password authentication is selected, the evaluator will configure the OS with a known user name and password and conduct the following tests:

- **Test 1:** *The evaluator will attempt to authenticate to the OS using the known user name and password. The evaluator will ensure that the authentication attempt is successful.*
- **Test 2:** *The evaluator will attempt to authenticate to the OS using the known user name but an incorrect password. The evaluator will ensure that the authentication attempt is unsuccessful.*

If user name and PIN that releases an asymmetric key is selected, the evaluator will examine the TSS for guidance on supported protected storage and will then configure the TOE or OE to establish a PIN which enables release of the asymmetric key from the protected storage (such as a TPM, a hardware token, or isolated execution environment) with which the OS can interface. The evaluator will then conduct the following tests:

- **Test 1:** *The evaluator will attempt to authenticate to the OS using the known user name and PIN. The evaluator will ensure that the authentication attempt is successful.*
- **Test 2:** *The evaluator will attempt to authenticate to the OS using the known user name but an incorrect PIN. The evaluator will ensure that the authentication attempt is unsuccessful.*

If X.509 certificate authentication is selected, the evaluator will generate an X.509v3 certificate for a user with the Client Authentication Enhanced Key Usage field set. The evaluator will provision the OS for authentication with the X.509v3 certificate. The evaluator will ensure that the certificates are validated by the OS as per [FIA_X509_EXT.1.1](#) and then conduct the following tests:

- **Test 1:** *The evaluator will attempt to authenticate to the OS using the X.509v3 certificate. The evaluator will ensure that the authentication attempt is successful.*
- **Test 2:** *The evaluator will generate a second certificate identical to the first except for the public key and any values derived from the public key. The evaluator will attempt to authenticate to the OS with this certificate. The evaluator will ensure that the authentication attempt is unsuccessful.*
- **Test 1:** *For each authentication mechanism selected, the evaluator will enable that mechanism and verify that it can be used to authenticate the user at the specified authentication factor interfaces.*
- **Test 2:** *For each authentication mechanism rule, the evaluator will ensure that the authentication mechanism(s) behave as documented in the TSS.*

FIA_X509_EXT.1 X.509 Certificate Validation

FIA_X509_EXT.1.1

The OS shall implement functionality to validate certificates in accordance with the following rules:

- RFC 5280 certificate validation and certificate path validation
- The certificate path must terminate with a trusted CA certificate
- The OS shall validate a certificate path by ensuring the presence of the basicConstraints extension, that the CA flag is set to TRUE for all CA certificates, and that any path constraints are met.
- The TSF shall validate that any CA certificate includes "Certificate Signing" as a purpose the key usage field
- The OS shall validate the revocation status of the certificate using **[selection: OCSP as specified in RFC 6960, CRL as specified in RFC 5759, an OCSP TLS Status Request Extension (OCSP stapling) as specified in RFC 6066, OCSP TLS Multi-Certificate Status Request Extension (i.e., OCSP Multi-Stapling) as specified in RFC 6961]**
- The OS shall validate the extendedKeyUsage field according to the

following rules:

- Certificates used for trusted updates and executable code integrity verification shall have the Code Signing Purpose (id-kp 3 with OID 1.3.6.1.5.5.7.3.3) in the extendedKeyUsage field.
- Server certificates presented for TLS shall have the Server Authentication purpose (id-kp 1 with OID 1.3.6.1.5.5.7.3.1) in the extendedKeyUsage field.
- Client certificates presented for TLS shall have the Client Authentication purpose (id-kp 2 with OID 1.3.6.1.5.5.7.3.2) in the EKU field.
- S/MIME certificates presented for email encryption and signature shall have the Email Protection purpose (id-kp 4 with OID 1.3.6.1.5.5.7.3.4) in the EKU field.
- OCSP certificates presented for OCSP responses shall have the OCSP Signing Purpose (id-kp 9 with OID 1.3.6.1.5.5.7.3.9) in the EKU field.
- Server certificates presented for EST shall have the CMC Registration Authority (RA) purpose (id-kp-cmcRA with OID 1.3.6.1.5.5.7.3.28) in the EKU field. (conditional)

Application Note: [FIA_X509_EXT.1.1](#) lists the rules for validating certificates. The ST author will select whether revocation status is verified using OCSP or CRLs. [FIA_X509_EXT.2](#) requires that certificates are used for HTTPS, TLS, and DTLS; this use requires that the *extendedKeyUsage* rules are verified.

FIA_X509_EXT.1.2

The OS shall only treat a certificate as a CA certificate if the *basicConstraints* extension is present and the CA flag is set to TRUE.

Application Note: This requirement applies to certificates that are used and processed by the TSF and restricts the certificates that may be added as trusted CA certificates.

Evaluation Activities ▼

[FIA_X509_EXT.1](#)

TSS

The evaluator will ensure the TSS describes where the check of validity of the certificates takes place. The evaluator ensures the TSS also provides a description of the certificate path validation algorithm.

Tests

The tests described must be performed in conjunction with the other certificate services evaluation activities, including the functions in [FIA_X509_EXT.2.1](#). The tests for the *extendedKeyUsage* rules are performed in conjunction with the uses that require those rules. The evaluator will create a chain of at least four certificates: the node certificate to be tested, two Intermediate CAs, and the self-signed Root CA.

- **Test 1:** The evaluator will demonstrate that validating a certificate without a valid certification path results in the function failing, for each of the following reasons, in turn: by establishing a certificate path in which one of the issuing certificates is not a CA certificate, by omitting the *basicConstraints* field in one of the issuing certificates, by setting the *basicConstraints* field in an issuing certificate to have *CA=False*, by omitting the CA signing bit of the key usage field in an issuing certificate, and by setting the path length field of a valid CA field to a value strictly less than the certificate path. The evaluator will then establish a valid certificate path consisting of valid CA certificates, and demonstrate that the function succeeds. The evaluator will then remove trust in one of the CA certificates, and show that the function fails.
- **Test 2:** The evaluator will demonstrate that validating an expired certificate results in the function failing.
- **Test 3:** The evaluator will test that the OS can properly handle revoked certificates - conditional on whether CRL, OCSP, OCSP stapling, or OCSP multi-stapling is selected; if multiple methods are selected, then a test will be performed for each method. The evaluator will test revocation of the node certificate and revocation of the intermediate CA certificate (i.e. the intermediate CA certificate should be revoked by the root CA). If OCSP stapling per RFC 6066 is the only supported revocation method, testing revocation of the intermediate CA certificate is omitted. The evaluator will ensure that a valid certificate is used, and that the validation function succeeds. The evaluator then attempts the test with a certificate that has been revoked (for each method chosen in the selection) to ensure when the certificate is no longer valid that the validation function fails.
- **Test 4:** If any OCSP option is selected, the evaluator will configure the OCSP server or use a man-in-the-middle tool to present a certificate that does not have the OCSP signing purpose and verify that validation of the OCSP response fails. If CRL is selected, the evaluator will configure the CA to sign a CRL with a certificate that does not have the *cRLsign* key usage bit set and verify that validation of the CRL fails.
- **Test 5:** The evaluator will modify any byte in the first eight bytes of the certificate and demonstrate that the certificate fails to validate. (The certificate will fail to parse correctly.)
- **Test 6:** The evaluator will modify any byte in the last byte of the certificate and

demonstrate that the certificate fails to validate. (The signature on the certificate will not validate.)

- **Test 7:** The evaluator will modify any byte in the public key of the certificate and demonstrate that the certificate fails to validate. (The signature of the certificate will not validate.)

The following content should be included if:

- [ECDSA schemes using "NIST curves" P-256, P-384 and \[selection: P-521, no other curves \] that meet the following: FIPS PUB 186-4, "Digital Signature Standard \(DSS\)", Section 5](#), is selected from [FCS_COP.1.1/SIGN](#)
 - **Test 1:** The evaluator will establish a valid, trusted certificate chain consisting of an EC leaf certificate, an EC Intermediate CA certificate not designated as a trust anchor, and an EC certificate designated as a trusted anchor, where the elliptic curve parameters are specified as a named curve. The evaluator will confirm that the TOE validates the certificate chain.
 - **Test 2:** The evaluator will replace the intermediate certificate in the certificate chain for Test 8a with a modified certificate, where the modified intermediate CA has a public key information field where the EC parameters uses an explicit format version of the Elliptic Curve parameters in the public key information field of the intermediate CA certificate from Test 8a, and the modified Intermediate CA certificate is signed by the trusted EC root CA, but having no other changes. The evaluator will confirm the TOE treats the certificate as invalid.

The tests described must be performed in conjunction with the other certificate services evaluation activities, including the functions in [FIA_X509_EXT.2.1](#). The evaluator will create a chain of at least four certificates: the node certificate to be tested, two Intermediate CAs, and the self-signed Root CA.

- **Test 1:** The evaluator will construct a certificate path, such that the certificate of the CA issuing the OS's certificate does not contain the basicConstraints extension. The validation of the certificate path fails.
- **Test 2:** The evaluator will construct a certificate path, such that the certificate of the CA issuing the OS's certificate has the CA flag in the basicConstraints extension not set. The validation of the certificate path fails.
- **Test 3:** The evaluator will construct a certificate path, such that the certificate of the CA issuing the OS's certificate has the CA flag in the basicConstraints extension set to TRUE. The validation of the certificate path succeeds.

FIA_X509_EXT.2 X.509 Certificate Authentication

FIA_X509_EXT.2.1

The OS shall use X.509v3 certificates as defined by RFC 5280 to support authentication for TLS and [selection: DTLS, HTTPS, [assignment: other protocols], no other protocols] connections.

Evaluation Activities ▼

[FIA_X509_EXT.2](#)

Tests

The evaluator will acquire or develop an application that uses the OS TLS mechanism with an X.509v3 certificate. The evaluator will then run the application and ensure that the provided certificate is used to authenticate the connection.

The evaluator will repeat the activity for any other selections listed.

5.1.7 TOE Access (FTA)

FTA_TAB.1 Default TOE access banners

This is an optional component. However, applied modules or packages might redefine it as mandatory.

FTA_TAB.1.1

Before establishing a user session, the **OS** shall display an advisory warning message regarding unauthorized use of the OS.

Evaluation Activities ▼

[FTA_TAB.1](#)

Tests

The evaluator will configure the OS, per instructions in the OS manual, to display the advisory warning message "TEST TEST Warning Message TEST TEST". The evaluator will then log out

and confirm that the advisory message is displayed before logging in can occur.

5.1.8 Trusted Path/Channels (FTP)

FTP_ITC_EXT.1 Trusted channel communication

FTP_ITC_EXT.1.1

The OS shall use [**selection:**

- *TLS as conforming to the [Functional Package for Transport Layer Security \(TLS\), version 1.1](#)*
- *DTLS as conforming to the [Functional Package for Transport Layer Security \(TLS\), version 1.1](#)*
- *IPsec*
- *SSH as conforming to the [Functional Package for Secure Shell \(SSH\), version 1.0](#)*

] to provide a trusted communication channel between itself and authorized IT entities supporting the following capabilities: [**selection:** *audit server, authentication server, management server, [assignment: other capabilities]*] that is logically distinct from other communication channels and provides assured identification of its end points and protection of the channel data from disclosure and detection of modification of the channel data.

Application Note: The ST author must include the security functional requirements for the trusted channel protocol selected in [FTP_ITC_EXT.1.1](#) in the main body of the ST.

If the ST author selects [TLS](#) or [DTLS](#), the TSF will be validated against requirements from the [Functional Package for Transport Layer Security \(TLS\), version 1.1](#). The TSF can act as TLS client or server, or both.

If the ST author selects [SSH](#), the TSF will be validated against the [Functional Package for Secure Shell \(SSH\), version 1.0](#).

Validation Guidelines:

Rule #1

Evaluation Activities ▼

[FTP_ITC_EXT.1](#)

Tests

The evaluator will configure the OS to communicate with another trusted IT product as identified in the second selection. The evaluator will monitor network traffic while the OS performs communication with each of the servers identified in the second selection. The evaluator will ensure that for each session a trusted channel was established in conformance with the protocols identified in the first selection.

FTP_TRP.1 Trusted Path

FTP_TRP.1.1

The **OS** shall provide a communication path between itself and [**selection:** *remote, local*] users that is logically distinct from other communication paths and provides assured identification of its endpoints and protection of the communicated data from [modification, disclosure].

Application Note: This requirement ensures that all remote administrative actions are protected. Authorized remote administrators must initiate all communication with the OS via a trusted path and all communication with the OS by remote administrators must be performed over this path. The data passed in this trusted communication channel is encrypted as defined in [FTP_ITC_EXT.1.1](#). If local users access is selected and no unprotected traffic is sent to remote users, then this requirement is met. If remote users access is selected, the ST author must include the security functional requirements for the trusted channel protocol selected in [FTP_ITC_EXT.1.1](#) in the main body of the ST.

This requirement is tested with the evaluation activities for [FTP_TRP.1.3](#).

FTP_TRP.1.2

The **OS** shall permit [**selection:** *the TSF, local users, remote users*] to initiate communication via the trusted path.

Application Note: This requirement is tested with the evaluation activities for [FTP_TRP.1.3](#).

FTP_TRP.1.3

The **OS** shall require use of the trusted path for *[[all remote administrative actions]]*.

Application Note: This requirement ensures that authorized remote administrators initiate all communication with the OS via a trusted path, and that all communication with the OS by remote administrators is performed over this path. The data passed in this trusted communication channel is encrypted as defined in [FTP_ITC_EXT.1](#).

The evaluation activities for this requirement also test requirements [FTP_TRP.1.1](#) and [FTP_TRP.1.2](#)

Evaluation Activities ▼

[FTP_TRP.1](#)

TSS

The evaluator will examine the TSS to determine that the methods of remote OS administration are indicated, along with how those communications are protected. The evaluator will also confirm that all protocols listed in the TSS in support of OS administration are consistent with those specified in the requirement, and are included in the requirements in the ST.

Guidance

The evaluator will confirm that the operational guidance contains instructions for establishing the remote administrative sessions for each supported method.

Tests

The evaluator will also perform the following tests:

- **Test 1:** *The evaluator will ensure that communications using each remote administration method is tested during the course of the evaluation, setting up the connections as described in the operational guidance and ensuring that communication is successful.*
- **Test 2:** *For each method of remote administration supported, the evaluator will follow the operational guidance to ensure that there is no available interface that can be used by a remote user to establish a remote administrative sessions without invoking the trusted path.*
- **Test 3:** *The evaluator will ensure, for each method of remote administration, the channel data is not sent in plaintext.*
- **Test 4:** *The evaluator will ensure, for each method of remote administration, modification of the channel data is detected by the OS.*

5.1.9 TOE Security Functional Requirements Rationale

The following rationale provides justification for each security objective for the TOE, showing that the SFRs are suitable to meet and achieve the security objectives:

Table 2: SFR Rationale

Objective	Addressed by	Rationale
O.ACCOUNTABILITY	FAU_GEN.1	Supports the objective by requiring that critical event information be gathered by the TOE.
	FTP_ITC_EXT.1	Supports the objective by ensuring that audit information can be securely transmitted to remote systems for analysis.
O.INTEGRITY	FPT_SBOP_EXT.1 FPT_ASLR_EXT.1	Supports the objective by requiring that OS applications be hardened against buffer overflow attacks
	FPT_TUD_EXT.1	Supports the objective by requiring that the OS be able to check for critical updates.
	FPT_TUD_EXT.2	Supports the objective by requiring that the OS verify updates before applying them.
	FCS_COP.1/HASH	Supports the objective by requiring the TSF to implement hash algorithms that are used in support of protected communications.
	FCS_COP.1/SIGN	Supports the objective by requiring the TSF to implement digital signature algorithms that are used in support of protected communications.
	FCS_COP.1/KEYHMAC	Supports the objective by requiring the TSF to implement HMAC algorithms that are used in support of protected communications.
	FPT_ACF_EXT.1	Supports the objective by requiring the TSF restrict unprivileged users from changing critical components.
	FPT_SRP_EXT.1	Supports the objective by requiring the TSF to implement a configurable whitelisting mechanism.
	FIA_X509_EXT.1	Supports the objective by requiring the TSF to validate

		certificates using industry standards.
	FPT_TST_EXT.1	Supports the objective by requiring the TSF to verify executable code critical to its operation.
	FTP_ITC_EXT.1	Supports the objective by requiring the OS to provide a trusted channel for critical communication.
	FPT_W^X_EXT.1	Supports the objective by requiring the OS to executable only non-writable memory.
	FIA_AFL.1	Supports the objective by requiring the TSF to respond accordingly when the number of failed authentication attempts reaches a specified threshold.
	FIA_UAU.5	Supports the objective by requiring the OS to provide standard authentication mechanisms.
O.MANAGEMENT	FMT_MOF_EXT.1	Supports this objective by requiring the TOE to restrict the ability to perform certain management functions to a privileged user.
	FMT_SMF_EXT.1	Supports this objective by requiring the TOE to implement specific management functions.
	FTA_TAB.1	Supports this objective by requiring the TOE to implement a trusted path between the itself and users.
	FTP_TRP.1	Supports this objective by requiring a trusted path between users and the OS.
O.PROTECTED_STORAGE	FCS_STO_EXT.1	Supports this objective by requiring the OS to provide encrypted storage.
	FCS_RBG_EXT.1	Supports this objective by requiring the OS to generate random bits according to industry standards.
	FCS_COP.1/ENCRYPT	Supports this objective requiring the OS to perform encryption according to industry stands.
	FDP_ACF_EXT.1	Supports this objective by requiring the OS to implement access controls.
O.PROTECTED_COMMS	FCS_RBG_EXT.1	Supports this objective by requiring the OS to generate random bits according to industry standards.
	FCS_CKM.1	Supports this objective by requiring the TSF to generate asymmetric cryptographic keys to industry standards.
	FCS_CKM.2	Supports this objective by requiring the TSF to perform key establishment according to industry standards.
	FCS_CKM_EXT.4	Supports this objective by requiring the TSF to destroy key material according to industry standards.
	FCS_COP.1/ENCRYPT	Supports this objective by requiring the TSF to encrypt data according to industry standards
	FCS_COP.1/HASH	Supports this objective by requiring the TSF to hash data according to industry standards.
	FCS_COP.1/SIGN	Supports this objective by requiring the TSF to cryptographically sign data according to industry standards.
	FCS_COP.1/KEYHMAC	Supports this objective by requiring the TSF to perform keyed hashes according to industry standards.
	FDP_IFC_EXT.1	Supports this objective by requiring the TSF to be compatible with at least one VPN.
	FIA_X509_EXT.1	Supports the objective by requiring the TSF to validate certificates using industry standards.
	FIA_X509_EXT.2	Supports this objective by requiring the TSF to validate TLS and related encrypted connections with x509 certificates.
	FTP_ITC_EXT.1	Supports the objective by requiring the OS to provide a trusted channel for critical communication.

5.2 Security Assurance Requirements

The Security Objectives in [Section 4 Security Objectives](#) were constructed to address threats identified in [Section 3.1 Threats](#). The Security Functional Requirements (SFRs) in [Section 5.1 Security Functional Requirements](#) are a formal instantiation of the Security Objectives. The PP identifies the Security Assurance Requirements (SARs) to frame the extent to which the evaluator assesses the documentation applicable for the evaluation and performs independent testing.

This section lists the set of SARs from CC part 3 that are required in evaluations against this PP. Individual evaluation activities to be performed are specified both in [Section 5 Security Requirements](#) as well as in this section.

The general model for evaluation of TOEs against STs written to conform to this PP is as follows: After the ST has been approved for evaluation, the ITSEF will obtain the OS, supporting environmental IT, and the administrative/user guides for the OS. The ITSEF is expected to perform actions mandated by the Common Evaluation Methodology (CEM) for the ASE and ALC SARs. The ITSEF also performs the evaluation activities contained within [Section 5 Security Requirements](#), which are intended to be an interpretation of the other CEM assurance requirements as they apply to the specific technology instantiated in the OS. The evaluation activities that are captured in [Section 5 Security Requirements](#) also provide clarification as to what the developer needs to provide to demonstrate the OS is compliant with the PP.

5.2.1 Class ASE: Security Target

The following ASE components as defined in [\[CEM\]](#) are required:

- Conformance claims (ASE_CCL.1)
- Extended components definition (ASE_ECD.1)
- ST introduction (ASE_INT.1)
- Security objectives (ASE_OBJ.2)
- Derived security requirements (ASE_REQ.2)
- Security Problem Definition (ASE_SPD.1)
- TOE summary specification (ASE_TSS.1)

The requirements for exact conformance of the Security Target are described in [Section 2 Conformance Claims](#).

5.2.2 Class ADV: Development

The information about the OS is contained in the guidance documentation available to the end user as well as the TSS portion of the ST. The OS developer must concur with the description of the product that is contained in the TSS as it relates to the functional requirements. The evaluation activities contained in [Section 5.1 Security Functional Requirements](#) should provide the ST authors with sufficient information to determine the appropriate content for the TSS section.

ADV_FSP.1 Basic Functional Specification (ADV_FSP.1)

The functional specification describes the TSFIs. It is not necessary to have a formal or complete specification of these interfaces. Additionally, because OSEs conforming to this PP will necessarily have interfaces to the Operational Environment that are not directly invocable by OS users, there is little point specifying that such interfaces be described in and of themselves since only indirect testing of such interfaces may be possible. For this PP, the activities for this family should focus on understanding the interfaces presented in the TSS in response to the functional requirements and the interfaces presented in the AGD documentation. No additional "functional specification" documentation is necessary to satisfy the evaluation activities specified. The interfaces that need to be evaluated are characterized through the information needed to perform the assurance activities listed, rather than as an independent, abstract list.

Developer action elements:

ADV_FSP.1.1D

The developer shall provide a functional specification.

ADV_FSP.1.2D

The developer shall provide a tracing from the functional specification to the SFRs.

Application Note: As indicated in the introduction to this section, the functional specification is comprised of the information contained in the AGD_OPE and AGD_PRE documentation. The developer may reference a website accessible to application developers and the evaluator. The evaluation activities in the functional requirements point to evidence that should exist in the documentation and TSS section; since these are directly associated with the SFRs, the tracing in element [ADV_FSP.1.2D](#) is implicitly already done and no additional documentation is necessary.

Content and presentation elements:

ADV_FSP.1.1C

The functional specification shall describe the purpose and method of use for each SFR-enforcing and SFR-supporting TSFI.

ADV_FSP.1.2C

The functional specification shall identify all parameters associated with each

SFR-enforcing and SFR-supporting TSFI.

ADV_FSP.1.3C

The functional specification shall provide rationale for the implicit categorization of interfaces as SFR-non-interfering.

ADV_FSP.1.4C

The tracing shall demonstrate that the SFRs trace to TSFIs in the functional specification.

Evaluator action elements:

ADV_FSP.1.1E

The evaluator will confirm that the information provided meets all requirements for content and presentation of evidence.

ADV_FSP.1.2E

The evaluator will determine that the functional specification is an accurate and complete instantiation of the SFRs.

Evaluation Activities ▼

ADV_FSP.1

There are no specific evaluation activities associated with these SARs, except ensuring the information is provided. The functional specification documentation is provided to support the evaluation activities described in [Section 5.1 Security Functional Requirements](#), and other activities described for AGD, ATE, and AVA SARs. The requirements on the content of the functional specification information is implicitly assessed by virtue of the other evaluation activities being performed; if the evaluator is unable to perform an activity because there is insufficient interface information, then an adequate functional specification has not been provided.

5.2.3 Class AGD: Guidance Documentation

The guidance documents will be provided with the ST. Guidance must include a description of how the IT personnel verifies that the Operational Environment can fulfill its role for the security functionality. The documentation should be in an informal style and readable by the IT personnel. Guidance must be provided for every operational environment that the product supports as claimed in the ST. This guidance includes instructions to successfully install the TSF in that environment; and Instructions to manage the security of the TSF as a product and as a component of the larger operational environment. Guidance pertaining to particular security functionality is also provided; requirements on such guidance are contained in the Evaluation Activities specified with each requirement.

AGD_OPE.1 Operational User Guidance (AGD_OPE.1)

Developer action elements:

AGD_OPE.1.1D

The developer shall provide operational user guidance.

Application Note: The operational user guidance does not have to be contained in a single document. Guidance to users, administrators and application developers can be spread among documents or web pages. Rather than repeat information here, the developer should review the evaluation activities for this component to ascertain the specifics of the guidance that the evaluator will be checking for. This will provide the necessary information for the preparation of acceptable guidance.

Content and presentation elements:

AGD_OPE.1.1C

The operational user guidance shall describe, for each user role, the user-accessible functions and privileges that should be controlled in a secure processing environment, including appropriate warnings.

Application Note: User and administrator are to be considered in the definition of user role.

AGD_OPE.1.2C

The operational user guidance shall describe, for each user role, how to use the available interfaces provided by the OS in a secure manner.

AGD_OPE.1.3C

The operational user guidance shall describe, for each user role, the available functions and interfaces, in particular all security parameters under the control of the user, indicating secure values as appropriate.

Application Note: This portion of the operational user guidance should be presented in the form of a checklist that can be quickly executed by IT personnel

(or end-users, when necessary) and suitable for use in compliance activities. When possible, this guidance is to be expressed in the eXtensible Configuration Checklist Description Format (XCCDF) to support security automation. Minimally, it should be presented in a structured format which includes a title for each configuration item, instructions for achieving the secure configuration, and any relevant rationale.

AGD_OPE.1.4C

The operational user guidance shall, for each user role, clearly present each type of security-relevant event relative to the user-accessible functions that need to be performed, including changing the security characteristics of entities under the control of the TSF.

AGD_OPE.1.5C

The operational user guidance shall identify all possible modes of operation of the OS (including operation following failure or operational error), their consequences, and implications for maintaining secure operation.

AGD_OPE.1.6C

The operational user guidance shall, for each user role, describe the security measures to be followed in order to fulfill the security objectives for the operational environment as described in the ST.

AGD_OPE.1.7C

The operational user guidance shall be clear and reasonable.

Evaluator action elements:

AGD_OPE.1.1E

The evaluator will confirm that the information provided meets all requirements for content and presentation of evidence.

Evaluation Activities ▼

AGD_OPE.1

Some of the contents of the operational guidance are verified by the evaluation activities in [Section 5.1 Security Functional Requirements](#) and evaluation of the OS according to the [\[CEM\]](#). The following additional information is also required. If cryptographic functions are provided by the OS, the operational guidance will contain instructions for configuring the cryptographic engine associated with the evaluated configuration of the OS. It will provide a warning to the administrator that use of other cryptographic engines was not evaluated nor tested during the CC evaluation of the OS. The documentation must describe the process for verifying updates to the OS by verifying a digital signature - this may be done by the OS or the underlying platform. The evaluator will verify that this process includes the following steps: Instructions for obtaining the update itself. This should include instructions for making the update accessible to the OS (e.g., placement in a specific directory). Instructions for initiating the update process, as well as discerning whether the process was successful or unsuccessful. This includes generation of the hash/digital signature. The OS will likely contain security functionality that does not fall in the scope of evaluation under this PP. The operational guidance will make it clear to an administrator which security functionality is covered by the evaluation activities.

AGD_PRE.1 Preparative Procedures (AGD_PRE.1)

Developer action elements:

AGD_PRE.1.1D

The developer shall provide the OS, including its preparative procedures.

Application Note: As with the operational guidance, the developer should look to the evaluation activities to determine the required content with respect to preparative procedures.

Content and presentation elements:

AGD_PRE.1.1C

The preparative procedures shall describe all the steps necessary for secure acceptance of the delivered OS in accordance with the developer's delivery procedures.

AGD_PRE.1.2C

The preparative procedures shall describe all the steps necessary for secure installation of the OS and for the secure preparation of the operational environment in accordance with the security objectives for the operational environment as described in the ST.

Evaluator action elements:

AGD_PRE.1.1E

The evaluator will confirm that the information provided meets all requirements

for content and presentation of evidence.

AGD_PRE.1.2E

The evaluator will apply the preparative procedures to confirm that the OS can be prepared securely for operation.

Evaluation Activities ▼

[AGD_PRE.1](#)

As indicated in the introduction above, there are significant expectations with respect to the documentation—especially when configuring the operational environment to support OS functional requirements. The evaluator will check to ensure that the guidance provided for the OS adequately addresses all platforms claimed for the OS in the ST.

5.2.4 Class ALC: Life-cycle Support

At the assurance level provided for OSes conformant to this PP, life-cycle support is limited to end-user-visible aspects of the life-cycle, rather than an examination of the OS vendor's development and configuration management process. This is not meant to diminish the critical role that a developer's practices play in contributing to the overall trustworthiness of a product; rather, it is a reflection on the information to be made available for evaluation at this assurance level.

ALC_CMC.1 Labeling of the TOE (ALC_CMC.1)

This component is targeted at identifying the OS such that it can be distinguished from other products or versions from the same vendor and can be easily specified when being procured by an end user.

Developer action elements:

ALC_CMC.1.1D

The developer shall provide the OS and a reference for the OS.

Content and presentation elements:

ALC_CMC.1.1C

The OS shall be labeled with a unique reference.

Application Note: Unique reference information includes:

- OS Name
- OS Version
- OS Description
- Software Identification (SWID) tags, if available

Evaluator action elements:

ALC_CMC.1.1E

The evaluator will confirm that the information provided meets all requirements for content and presentation of evidence.

Evaluation Activities ▼

[ALC_CMC.1](#)

The evaluator will check the ST to ensure that it contains an identifier (such as a product name/version number) that specifically identifies the version that meets the requirements of the ST. Further, the evaluator will check the AGD guidance and OS samples received for testing to ensure that the version number is consistent with that in the ST. If the vendor maintains a web site advertising the OS, the evaluator will examine the information on the web site to ensure that the information in the ST is sufficient to distinguish the product.

ALC_CMS.1 TOE CM Coverage (ALC_CMS.1)

Given the scope of the OS and its associated evaluation evidence requirements, this component's evaluation activities are covered by the evaluation activities listed for [ALC_CMC.1](#).

Developer action elements:

ALC_CMS.1.1D

The developer shall provide a configuration list for the OS.

Content and presentation elements:

ALC_CMS.1.1C

The configuration list shall include the following: the OS itself; and the evaluation evidence required by the SARs.

ALC_CMS.1.2C

The configuration list shall uniquely identify the configuration items.

Evaluator action elements:

ALC_CMS.1.1E

The evaluator will confirm that the information provided meets all requirements for content and presentation of evidence.

Evaluation Activities ▼

[ALC_CMS.1](#)

The "evaluation evidence required by the SARs" in this PP is limited to the information in the ST coupled with the guidance provided to administrators and users under the AGD requirements. By ensuring that the OS is specifically identified and that this identification is consistent in the ST and in the AGD guidance (as done in the evaluation activity for [ALC_CMC.1](#)), the evaluator implicitly confirms the information required by this component. Life-cycle support is targeted aspects of the developer's life-cycle and instructions to providers of applications for the developer's devices, rather than an in-depth examination of the TSF manufacturer's development and configuration management process. This is not meant to diminish the critical role that a developer's practices play in contributing to the overall trustworthiness of a product; rather, it's a reflection on the information to be made available for evaluation.

The evaluator will ensure that the developer has identified (in guidance documentation for application developers concerning the targeted platform) one or more development environments appropriate for use in developing applications for the developer's platform. For each of these development environments, the developer will provide information on how to configure the environment to ensure that buffer overflow protection mechanisms in the environment(s) are invoked (e.g., compiler and linker flags). The evaluator will ensure that this documentation also includes an indication of whether such protections are on by default, or have to be specifically enabled. The evaluator will ensure that the TSF is uniquely identified (with respect to other products from the TSF vendor), and that documentation provided by the developer in association with the requirements in the ST is associated with the TSF using this unique identification.

ALC_TSU_EXT.1 Timely Security Updates

This component requires the OS developer, in conjunction with any other necessary parties, to provide information as to how the end-user devices are updated to address security issues in a timely manner. The documentation describes the process of providing updates to the public from the time a security flaw is reported/discovered, to the time an update is released. This description includes the parties involved (e.g., the developer, carriers(s)) and the steps that are performed (e.g., developer testing, carrier testing), including worst case time periods, before an update is made available to the public.

Developer action elements:

ALC_TSU_EXT.1.1D

The developer shall provide a description in the TSS of how timely security updates are made to the OS.

ALC_TSU_EXT.1.2D

The developer shall provide a description in the TSS of how users are notified when updates change security properties or the configuration of the product.

Content and presentation elements:

ALC_TSU_EXT.1.1C

The description shall include the process for creating and deploying security updates for the OS software.

ALC_TSU_EXT.1.2C

The description shall include the mechanisms publicly available for reporting security issues pertaining to the OS.

Note: The reporting mechanism could include web sites, email addresses, as well as a means to protect the sensitive nature of the report (e.g., public keys that could be used to encrypt the details of a proof-of-concept exploit).

Evaluator action elements:

ALC_TSU_EXT.1.1E

The evaluator will confirm that the information provided meets all requirements for content and presentation of evidence.

Evaluation Activities ▼

[ALC_TSU_EXT.1](#)

The evaluator will verify that the TSS contains a description of the timely security update process used by the developer to create and deploy security updates. The evaluator will verify that this description addresses the entire application. The evaluator will also verify that, in addition to the OS developer's process, any third-party processes are also addressed in the description. The evaluator will also verify that each mechanism for deployment of security updates is described.

The evaluator will verify that, for each deployment mechanism described for the update process, the TSS lists a time between public disclosure of a vulnerability and public availability of the security update to the OS patching this vulnerability, to include any third-party or carrier delays in deployment. The evaluator will verify that this time is expressed in a number or range of days.

The evaluator will verify that this description includes the publicly available mechanisms (including either an email address or website) for reporting security issues related to the OS. The evaluator will verify that the description of this mechanism includes a method for protecting the report either using a public key for encrypting email or a trusted channel for a website.

5.2.5 Class ATE: Tests

Testing is specified for functional aspects of the system as well as aspects that take advantage of design or implementation weaknesses. The former is done through the ATE_IND family, while the latter is through the AVA_VAN family. At the assurance level specified in this PP, testing is based on advertised functionality and interfaces with dependency on the availability of design information. One of the primary outputs of the evaluation process is the test report as specified in the following requirements.

ATE_IND.1 Independent Testing - Conformance (ATE_IND.1)

Testing is performed to confirm the functionality described in the TSS as well as the administrative (including configuration and operational) documentation provided. The focus of the testing is to confirm that the requirements specified in [Section 5.1 Security Functional Requirements](#) being met, although some additional testing is specified for SARs in [Section 5.2 Security Assurance Requirements](#). The evaluation activities identify the additional testing activities associated with these components. The evaluator produces a test report documenting the plan for and results of testing, as well as coverage arguments focused on the platform/OS combinations that are claiming conformance to this PP. Given the scope of the OS and its associated evaluation evidence requirements, this component's evaluation activities are covered by the evaluation activities listed for [ALC_CMC.1](#).

Developer action elements:

ATE_IND.1.1D

The developer shall provide the OS for testing.

Content and presentation elements:

ATE_IND.1.1C

The OS shall be suitable for testing.

Evaluator action elements:

ATE_IND.1.1E

The evaluator *shall confirm* that the information provided meets all requirements for content and presentation of evidence.

ATE_IND.1.2E

The evaluator will test a subset of the TSF to confirm that the TSF operates as specified.

Application Note: The evaluator will test the OS on the most current fully patched version of the platform.

Evaluation Activities ▼

[ATE_IND.1](#)

The evaluator will prepare a test plan and report documenting the testing aspects of the system, including any application crashes during testing. The evaluator will determine the root cause of any application crashes and include that information in the report. The test plan covers all of the testing actions contained in the [\[CEM\]](#) and the body of this PP's evaluation activities.

While it is not necessary to have one test case per test listed in an evaluation activity, the evaluator must document in the test plan that each applicable testing requirement in the ST is covered. The test plan identifies the platforms to be tested, and for those platforms not included in the test plan but included in the ST, the test plan provides a justification for not testing the platforms. This justification must address the differences between the tested platforms and the untested platforms, and make an argument that the differences do not affect the testing to be performed. It is not sufficient to merely assert that the differences have no affect; rationale must be provided. If all platforms claimed in the ST are tested, then no rationale is necessary. The test plan describes the composition of each platform to be tested, and any setup that is necessary beyond what is contained in the AGD documentation. It should be noted that the evaluator is expected to follow the AGD documentation for installation and setup of each platform either as

part of a test or as a standard pre-test condition. This may include special test drivers or tools. For each driver or tool, an argument (not just an assertion) should be provided that the driver or tool will not adversely affect the performance of the functionality by the OS and its platform.

This also includes the configuration of the cryptographic engine to be used. The cryptographic algorithms implemented by this engine are those specified by this PP and used by the cryptographic protocols being evaluated (IPsec, TLS). The test plan identifies high-level test objectives as well as the test procedures to be followed to achieve those objectives. These procedures include expected results.

The test report (which could just be an annotated version of the test plan) details the activities that took place when the test procedures were executed, and includes the actual results of the tests. This will be a cumulative account, so if there was a test run that resulted in a failure; a fix installed; and then a successful re-run of the test, the report would show a "fail" and "pass" result (and the supporting details), and not just the "pass" result.

5.2.6 Class AVA: Vulnerability Assessment

For the first generation of this protection profile, the evaluation lab is expected to survey open sources to discover what vulnerabilities have been discovered in these types of products. In most cases, these vulnerabilities will require sophistication beyond that of a basic attacker. Until penetration tools are created and uniformly distributed to the evaluation labs, the evaluator will not be expected to test for these vulnerabilities in the OS. The labs will be expected to comment on the likelihood of these vulnerabilities given the documentation provided by the vendor. This information will be used in the development of penetration testing tools and for the development of future protection profiles.

AVA_VAN.1 Vulnerability Survey (AVA_VAN.1)

Developer action elements:

AVA_VAN.1.1D

The developer shall provide the OS for testing.

Content and presentation elements:

AVA_VAN.1.1C

The OS shall be suitable for testing.

Evaluator action elements:

AVA_VAN.1.1E

The evaluator will confirm that the information provided meets all requirements for content and presentation of evidence.

AVA_VAN.1.2E

The evaluator will perform a search of public domain sources to identify potential vulnerabilities in the OS.

Application Note: Public domain sources include the Common Vulnerabilities and Exposures (CVE) dictionary for publicly-known vulnerabilities. Public domain sources also include sites which provide free checking of files for viruses.

AVA_VAN.1.3E

The evaluator will conduct penetration testing, based on the identified potential vulnerabilities, to determine that the OS is resistant to attacks performed by an attacker possessing Basic attack potential.

Evaluation Activities ▼

AVA_VAN.1

The evaluator will generate a report to document their findings with respect to this requirement. This report could physically be part of the overall test report mentioned in ATE_IND, or a separate document. The evaluator performs a search of public information to find vulnerabilities that have been found in similar applications with a particular focus on network protocols the application uses and document formats it parses. The evaluator documents the sources consulted and the vulnerabilities found in the report.

For each vulnerability found, the evaluator either provides a rationale with respect to its non-applicability, or the evaluator formulates a test (using the guidelines provided in ATE_IND) to confirm the vulnerability, if suitable. Suitability is determined by assessing the attack vector needed to take advantage of the vulnerability. If exploiting the vulnerability requires expert skills and an electron microscope, for instance, then a test would not be suitable and an appropriate justification would be formulated.

Appendix A - Implementation-based Requirements

Implementation-based Requirements are dependent on the TOE implementing a particular function. If the TOE fulfills any of these requirements, the vendor must either add the related SFR or disable the functionality for the evaluated configuration.

Appendix B - Implicitly Satisfied Requirements

This appendix lists requirements that should be considered satisfied by products successfully evaluated against this PP. These requirements are not featured explicitly as SFRs and should not be included in the ST. They are not included as standalone SFRs because it would increase the time, cost, and complexity of evaluation. This approach is permitted by [\[CC\]](#) Part 1, 8.2 Dependencies between components.

This information benefits systems engineering activities which call for inclusion of particular security controls. Evaluation against the PP provides evidence that these controls are present and have been evaluated.

Requirement	Rationale for Satisfaction
-------------	----------------------------

FIA_UAU.1 - Timing of authentication	FIA_AFL.1 implicitly requires that the OS perform all necessary actions, including those on behalf of the user who has not been authenticated, in order to authenticate; therefore it is duplicative to include these actions as a separate assignment and test.
--------------------------------------	--

FIA_UID.1 - Timing of identification	FIA_AFL.1 implicitly requires that the OS perform all necessary actions, including those on behalf of the user who has not been identified, in order to authenticate; therefore it is duplicative to include these actions as a separate assignment and test.
--------------------------------------	---

FMT_SMR.1 - Security roles	FMT_MOF_EXT.1 specifies role-based management functions that implicitly defines user and privileged accounts; therefore, it is duplicative to include separate role requirements.
----------------------------	---

FPT_STM.1 - Reliable time stamps	FAU_GEN.1.2 explicitly requires that the OS associate timestamps with audit records; therefore it is duplicative to include a separate timestamp requirement.
----------------------------------	---

FTA_SSL.1 - TSF-initiated session locking	FMT_MOF_EXT.1 defines requirements for managing session locking; therefore, it is duplicative to include a separate session locking requirement.
---	--

FTA_SSL.2 - User-initiated locking	FMT_MOF_EXT.1 defines requirements for user-initiated session locking; therefore, it is duplicative to include a separate session locking requirement.
------------------------------------	--

FAU_STG.1 - Protected audit trail storage	FPT_ACF_EXT.1 defines a requirement to protect audit logs; therefore, it is duplicative to include a separate protection of audit trail requirements.
---	---

FAU_GEN.2 - User identity association	FAU_GEN.1.2 explicitly requires that the OS record any user account associated with each event; therefore, it is duplicative to include a separate requirement to associate a user account with each event.
---------------------------------------	---

FAU_SAR.1 - Audit review	FPT_ACF_EXT.1.2 requires that audit logs (and other objects) are protected from reading by unprivileged users; therefore, it is duplicative to include a separate requirement to protect only the audit information.
--------------------------	--

Appendix C - Entropy Documentation and Assessment

This appendix describes the required supplementary information for the entropy source used by the OS.

The documentation of the entropy source should be detailed enough that, after reading, the evaluator will thoroughly understand the entropy source and why it can be relied upon to provide sufficient entropy. This documentation should include multiple detailed sections: design description, entropy justification, operating conditions, and health testing. This documentation is not required to be part of the TSS.

C.1 Design Description

Documentation will include the design of the entropy source as a whole, including the interaction of all entropy source components. Any information that can be shared regarding the design should also be included for any third-party entropy sources that are included in the product.

The documentation will describe the operation of the entropy source to include, how entropy is produced, and how unprocessed (raw) data can be obtained from within the entropy source for testing purposes. The documentation should walk through the entropy source design indicating where the entropy comes from, where the entropy output is passed next, any post-processing of the raw outputs (hash, XOR, etc.), if/where it is stored, and finally, how it is output from the entropy source. Any conditions placed on the process (e.g., blocking) should also be described in the entropy source design. Diagrams and examples are encouraged.

This design must also include a description of the content of the security boundary of the entropy source and a description of how the security boundary ensures that an adversary outside the boundary cannot affect the entropy rate.

If implemented, the design description will include a description of how third-party applications can add entropy to the RBG. A description of any RBG state saving between power-off and power-on will be included.

C.2 Entropy Justification

There should be a technical argument for where the unpredictability in the source comes from and why there is confidence in the entropy source delivering sufficient entropy for the uses made of the RBG output (by this particular OS). This argument will include a description of the expected min-entropy rate (i.e. the minimum entropy (in bits) per bit or byte of source data) and explain that sufficient entropy is going into the OS randomizer seeding process. This discussion will be part of a justification for why the entropy source can be relied upon to produce bits with entropy.

The amount of information necessary to justify the expected min-entropy rate depends on the type of entropy source included in the product.

For developer provided entropy sources, in order to justify the min-entropy rate, it is expected that a large number of raw source bits will be collected, statistical tests will be performed, and the min-entropy rate determined from the statistical tests. While no particular statistical tests are required at this time, it is expected that some testing is necessary in order to determine the amount of min-entropy in each output.

For third-party provided entropy sources, in which the OS vendor has limited access to the design and raw entropy data of the source, the documentation will indicate an estimate of the amount of min-entropy obtained from this third-party source. It is acceptable for the vendor to "assume" an amount of min-entropy, however, this assumption must be clearly stated in the documentation provided. In particular, the min-entropy estimate must be specified and the assumption included in the ST.

Regardless of type of entropy source, the justification will also include how the DRBG is initialized with the entropy stated in the ST, for example by verifying that the min-entropy rate is multiplied by the amount of source data used to seed the DRBG or that the rate of entropy expected based on the amount of source data is explicitly stated and compared to the statistical rate. If the amount of source data used to seed the DRBG is not clear or the calculated rate is not explicitly related to the seed, the documentation will not be considered complete.

The entropy justification will not include any data added from any third-party application or from any state saving between restarts.

C.3 Operating Conditions

The entropy rate may be affected by conditions outside the control of the entropy source itself. For example, voltage, frequency, temperature, and elapsed time after power-on are just a few of the factors that may affect the operation of the entropy source. As such, documentation will also include the range of operating conditions under which the entropy source is expected to generate random data. It will clearly describe the measures that have been taken in the system design to ensure the entropy source continues to operate under those conditions. Similarly, documentation will describe the conditions under which the entropy source is known to malfunction or become inconsistent. Methods used to detect failure or degradation of the source will be included.

C.4 Health Testing

More specifically, all entropy source health tests and their rationale will be documented. This includes a description of the health tests, the rate and conditions under which each health test is performed (e.g., at start, continuously, or on-demand), the expected results for each health test, and rationale indicating why each test is believed to be appropriate for detecting one or more failures in the entropy source.

Appendix D - Validation Guidelines

This appendix contains "rules" specified by the PP Authors that indicate whether certain selections require the making of other selections in order for a Security Target to be valid. For example, selecting "HMAC-SHA-3-384" as a supported keyed-hash algorithm would require that "SHA-3-384" be selected as a hash algorithm.

This appendix contains only such "rules" as have been defined by the PP Authors, and does not necessarily represent all such dependencies in the document.

Rule #1

OR	From FCS_COP.1.1/ENCRYPT : * select AES-CTR From FTP_ITC_EXT.1.1 : * select SSH
	From FTP_ITC_EXT.1.1 : Choose something other than: * SSH

Appendix E - Acronyms

Acronym	Meaning
AES	Advanced Encryption Standard
API	Application Programming Interface
ASLR	Address Space Layout Randomization
BAF	Biometric Authentication Factor
Base-PP	Base Protection Profile
CC	Common Criteria
CEM	Common Evaluation Methodology
CESG	Communications-Electronics Security Group
CMC	Certificate Management over CMS
CMS	Cryptographic Message Syntax
CN	Common Names
CRL	Certificate Revocation List
CSA	Computer Security Act
CSP	Critical Security Parameters
DAR	Data At Rest
DEP	Data Execution Prevention
DES	Data Encryption Standard
DHE	Diffie-Hellman Ephemeral
DNS	Domain Name System
DRBG	Deterministic Random Bit Generator
DSS	Digital Signature Standard
DT	Date/Time Vector
DTLS	Datagram Transport Layer Security
EAP	Extensible Authentication Protocol
ECDHE	Elliptic Curve Diffie-Hellman Ephemeral
ECDSA	Elliptic Curve Digital Signature Algorithm
EP	Extended Package
EST	Enrollment over Secure Transport
FIPS	Federal Information Processing Standards
FP	Functional Package
HMAC	Hash-based Message Authentication Code
HTTP	Hypertext Transfer Protocol
HTTPS	Hypertext Transfer Protocol Secure
IETF	Internet Engineering Task Force
IP	Internet Protocol
ISO	International Organization for Standardization
IT	Information Technology
ITSEF	Information Technology Security Evaluation Facility
NIAP	National Information Assurance Partnership

NIST	National Institute of Standards and Technology
OCSF	Online Certificate Status Protocol
OE	Operational Environment
OID	Object Identifier
OMB	Office of Management and Budget
OS	Operating System
PII	Personally Identifiable Information
PIN	Personal Identification Number
PKI	Public Key Infrastructure
PP	Protection Profile
PP-Configuration	Protection Profile Configuration
PP-Module	Protection Profile Module
RBG	Random Bit Generator
RFC	Request for Comment
RNG	Random Number Generator
S/MIME	Secure/Multi-purpose Internet Mail Extensions
SAN	Subject Alternative Name
SAR	Security Assurance Requirement
SFR	Security Functional Requirement
SHA	Secure Hash Algorithm
SIP	Session Initiation Protocol
ST	Security Target
SWID	Software Identification
TLS	Transport Layer Security
TOE	Target of Evaluation
TSF	TOE Security Functionality
TSFI	TSF Interface
TSS	TOE Summary Specification
URI	Uniform Resource Identifier
URL	Uniform Resource Locator
USB	Universal Serial Bus
VPN	Virtual Private Network
XCCDF	eXtensible Configuration Checklist Description Format
XOR	Exclusive Or
app	Application
cPP	Collaborative Protection Profile

Appendix F - Bibliography

Identifier	Title
[CC]	Common Criteria for Information Technology Security Evaluation - <ul style="list-style-type: none">• Part 1: Introduction and General Model, CCMB-2017-04-001, Version 3.1 Revision 5, April 2017.• Part 2: Security Functional Components, CCMB-2017-04-002, Version 3.1 Revision 5, April 2017.• Part 3: Security Assurance Components, CCMB-2017-04-003, Version 3.1 Revision 5, April 2017.
[CSA]	Computer Security Act of 1987 , H.R. 145, June 11, 1987.
[OMB]	Reporting Incidents Involving Personally Identifiable Information and Incorporating the Cost for Security in Agency Information Technology Investments , OMB M-06-19, July 12, 2006.
[CEM]	Common Evaluation Methodology for Information Technology Security - Evaluation Methodology , CCMB-2017-04-004, Version 3.1, Revision 5, April 2017.
[NCSC]	National Cyber Security Centre - End User Device (EUD) Security Guidance
[x509]	Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile , May 2008.