

# **PP-Module for Wireless Intrusion Detection/Prevention Systems (WIDS/WIPS)**



Version: 1.0  
2020-09-30

**National Information Assurance Partnership**

## Revision History

---

| Version | Date       | Comment                               |
|---------|------------|---------------------------------------|
| 1.0     | 2020-09-30 | Initial Release - PP-Module for NDcPP |

## Contents

---

|   |   |
|---|---|
| 1   | Introduction  |
| 1.1   | Overview  |
| 1.2   | Terms   |
| 1.2.1   | Common Criteria Terms                               |
| 1.2.2   | Technical Terms                                     |
| 1.3   | Compliant Targets of Evaluation                     |
| 1.3.1   | TOE Boundary  |
| 1.4   | Use Cases   |
| 2   | Conformance Claims                                  |
| 3   | Security Problem Description                        |
| 3.1   | Threats   |
| 3.2   | Assumptions   |
| 3.3   | Organizational Security Policies                    |
| 4   | Security Objectives                                 |
| 4.1   | Security Objectives for the TOE                     |
| 4.2   | Security Objectives for the Operational Environment |
| 4.3   | Security Objectives Rationale                       |
| 5   | Security Requirements                               |
| 5.1   | NDcPP Security Functional Requirements Direction    |
| 5.1.1   | Modified SFRs                                       |
| 5.1.1.1   | Security Audit (FAU)                                |
| 5.1.1.2   | Communications (FCO)                                |
| 5.1.1.3   | Protection of the TSF (FPT)                         |
| 5.1.1.4   | Trusted Paths/Channels (FTP)                        |
| 5.2   | TOE Security Functional Requirements                |
| 5.2.1   | Security Audit (FAU)                                |
| 5.2.2   | User Data Protection (FDP)                          |
| 5.2.3   | Security Management (FMT)                           |
| 5.3   | TOE Security Functional Requirements Rationale      |
| 5.4   | TOE Security Assurance Requirements                 |
| 6   | Consistency Rationale                               |
| 6.1   | Collaborative Protection Profile for Network Device |
| 6.1.1   | Consistency of TOE Type                             |
| 6.1.2   | Consistency of Security Problem Definition          |
| 6.1.3   | Consistency of Objectives                           |
| 6.1.4   | Consistency of Requirements                         |
| Appendix A - Optional SFRs                                  |   |
| A.1   | Strictly Optional Requirements                      |
| A.1.1   | Security Audit (FAU)                                |
| A.2   | Objective Requirements                              |
| A.2.1   | Security Audit (FAU)                                |
| A.2.2   | Protection of the TSF (FPT)                         |
| A.3   | Implementation-dependent Requirements               |
| Appendix B - Selection-based Requirements                   |   |
| B.1   | Security Audit (FAU)                                |
| Appendix C - Extended Component Definitions                 |   |
| C.1   | Extended Components Table                           |
| C.2   | Extended Component Definitions                      |
| C.2.1   | Security Audit (FAU)                                |
| C.2.1.1   | FAU_ARP_EXT Security Alarm Filtering                |
| C.2.1.2   | FAU_IDS_EXT Intrusion Detection Methods             |
| C.2.1.3   | FAU_INV_EXT Environmental Inventory                 |
| C.2.1.4   | FAU_RPT_EXT Reporting Methods                       |
| C.2.1.5   | FAU_WID_EXT Wireless Intrusion Detection            |
| C.2.1.6   | FAU_ANO_EXT Anomaly-Based Intrusion Detection       |
| C.2.1.7   | FAU_SIG_EXT Signature-Based Intrusion Detection     |
| C.2.1.8   | FAU_MAC_EXT Device Impersonation                    |
| C.2.1.9   | FAU_WIP_EXT Wireless Intrusion Prevention           |
| Appendix D - Implicitly Satisfied Requirements              |   |
| Appendix E - Allocation of Requirements in Distributed TOEs |   |
| Appendix F - Entropy Documentation and Assessment           |   |
| Appendix G - Acronyms                                       |   |
| Appendix H - Bibliography                                   |   |

# 1 Introduction

## 1.1 Overview

This Protection Profile Module (PP-Module) describes security requirements for a 802.11 Wireless Intrusion Detection System (WIDS) defined to be an IEEE 802.11 network intrusion detection product located at the edge of a private network that can collect, inspect, and analyze real-time network traffic and alert the administrator of policy violations. This PP-Module is intended to provide a minimal baseline set of requirements that are targeted at mitigating well defined and described threats.

This PP-Module contains optional requirements for a Wireless Intrusion Protection System (WIPS), a security product that in addition to the 802.11 WIDS capability, provides network security administrators with the additional ability to react in real-time to potentially malicious wireless (IEEE 802.11) network traffic.

This PP-Module is intended for use with the following Base-PP:

- collaborative Protection Profile for Network Devices (NDcPP), Version 2.2e

A TOE that conforms to a PP-Configuration containing this PP-Module must be a 'Distributed TOE' as defined in the NDcPP. The expectation for this PP-Module is that a WIDS must include distributed sensor nodes to ensure that the full physical range of a wireless network to ensure that user interactions with the network cannot evade detection.

## 1.2 Terms

The following sections list Common Criteria and technology terms used in this document.

### 1.2.1 Common Criteria Terms

|   |   |
|---|---|
| Assurance   | Grounds for confidence that a TOE meets the SFRs <a href="#">[CC]</a> .   |
| Base Protection Profile (Base-PP)                   | Protection Profile used as a basis to build a PP-Configuration.   |
| Collaborative Protection Profile (cPP)              | A Protection Profile developed by international technical communities and approved by multiple schemes.   |
| Common Criteria (CC)                                | Common Criteria for Information Technology Security Evaluation (International Standard ISO/IEC 15408).  |
| Common Criteria Testing Laboratory                  | Within the context of the Common Criteria Evaluation and Validation Scheme (CCEVS), an IT security evaluation facility accredited by the National Voluntary Laboratory Accreditation Program (NVLAP) and approved by the NIAP Validation Body to conduct Common Criteria-based evaluations. |
| Common Evaluation Methodology (CEM)                 | Common Evaluation Methodology for Information Technology Security Evaluation.   |
| Distributed TOE                                     | A TOE composed of multiple components operating as a logical whole.   |
| Extended Package (EP)                               | A deprecated document form for collecting SFRs that implement a particular protocol, technology, or functionality. See Functional Packages.   |
| Functional Package (FP)                             | A document that collects SFRs for a particular protocol, technology, or functionality.  |
| Operational Environment (OE)                        | Hardware and software that are outside the TOE boundary that support the TOE functionality and security policy.   |
| Protection Profile (PP)                             | An implementation-independent set of security requirements for a category of products.  |
| Protection Profile Configuration (PP-Configuration) | A comprehensive set of security requirements for a product type that consists of at least one Base-PP and at least one PP-Module.   |

|                                       |   |
|---------------------------------------|---|
| Protection Profile Module (PP-Module) | An implementation-independent statement of security needs for a TOE type complementary to one or more Base-PPs. |
| Security Assurance Requirement (SAR)  | A requirement to assure the security of the TOE.  |
| Security Functional Requirement (SFR) | A requirement for security enforcement by the TOE.  |
| Security Target (ST)                  | A set of implementation-dependent security requirements for a specific product.                                 |
| Target of Evaluation (TOE)            | The product under evaluation.   |
| TOE Security Functionality (TSF)      | The security functionality of the product under evaluation.   |
| TOE Summary Specification (TSS)       | A description of how a TOE satisfies the SFRs in an ST.   |

## 1.2.2 Technical Terms

|   |  |
|---|--|
| Access Point (AP)                           | A device that provides the network interface that enables 802.11 wireless client hosts to access a wired network.  |
| End User Device (EUD)                       | An 802.11 enabled device that has the ability to process, transmit, and/or store information.  |
| Service Set Identifier (SSID)               | The primary name associated with an 802.11 wireless local area network (WLAN).   |
| Wireless Intrusion Detection System (WIDS)  | A security product that provides network security administrators with the ability to monitor, collect, and log real-time to potentially malicious wireless (IEEE 802.11) network traffic.  |
| Wireless Intrusion Prevention System (WIPS) | A security product that provides network security administrators with the ability to monitor, collect, log, and react in real-time to potentially malicious wireless (IEEE 802.11) network traffic.                                |
| Wireless Local Area Network (WLAN)          | An 802.11 wireless computer network that links two or more devices using wireless communication to form a local area network (LAN) within a limited area such as a home, school, computer laboratory, campus, office building etc. |

## 1.3 Compliant Targets of Evaluation

### 1.3.1 TOE Boundary


This PP-Module specifically addresses WIDS/WIPS. A conformant WIDS is a product that can monitor, collect, inspect, and analyze real-time network traffic and alert the administrator of policy violations. WIPS functionality is not required to conform to this PP-Module, and it is optional for the TOE to have the additional ability to react in real-time to potentially malicious wireless (IEEE 802.11) network traffic.

A WIDS/WIPS TOE consists of multiple sensors that passively scan the RF environment on the WLAN radio frequency spectrum and a centralized mechanism such as a Server or Controller that processes the data collected by the sensors. Conformant TOEs must use a secure communication path(s) between WIDS/WIPS components.

A WIDS/WIPS can be Integrated (be part of the WLAN infrastructure) or Standalone (independent from WLAN) architecture depending on vendor implementation. The two different architectures are illustrated in [Figure 1](#) below. The TOE boundary is indicated by the yellow box.

A WIDS/WIPS is expected to inspect layers 1 and 2 network traffic, per the OSI network model, and monitor wireless frames in the RF spectrum utilized by IEEE 802.11 a, b, g, n, and ac. Monitoring and inspection of other technologies (e.g., cellular) and protocols are optional.

Conformant TOEs will detect potentially malicious network traffic using various approaches. Broadly speaking, the traffic analysis could be based on identification of 'known' threats, or 'unknown' threats. Identification of 'known' threats may be performed through pattern matching, (e.g. by matching strings of characters within a frame with known patterns, or by matching traffic patterns common with reconnaissance or denial of service (DoS) attacks). Identification of 'unknown' threats may be performed through use of various forms of anomaly detection whereby the WIDS/WIPS is provided with (or learns/creates) a definition of expected/typical traffic patterns, such that it's able to detect and react to anomalous (unexpected/atypical) traffic patterns.



**Figure 1: General TOE**

## 1.4 Use Cases

### [USE CASE 1] Use Case 1

A WIDS consists of sensors (preferably dedicated) and a central controller working together to provide 24/7 monitoring, primarily to the 802.11 Wireless Local Area Network (WLAN) spectrum and protocol, to detect, identify, and geo-locate WLAN devices within a controlled space.

The WIDS may be capable of detecting or monitoring traffic other than 802.11 WLAN, such as 802.15.4 based protocols, which enhances the security of the controlled space. However, a WIDS is not required to monitor additional protocols outside of 802.11. A WIDS monitors all 802.11 WLAN traffic emanating from and traversing the controlled space, thus inadvertent collection of any 802.11 signals is possible when operating a WIDS.

# 2 Conformance Claims

## Conformance Statement

This PP-Module inherits exact conformance as required from the specified Base-PP and as defined in the CC and CEM addenda for Exact Conformance, Selection-based SFRs, and Optional SFRs (dated May 2017).

The following PPs and PP-Modules are allowed to be specified in a PP-Configuration with this PP-Module.

- [Network Device, version 2.2e](#)

## CC Conformance Claims

This Module is conformant to Parts 2 (extended) and 3 (conformant) of Common Criteria Version 3.1, Revision 5.

## PP Claim

This Module does not claim conformance to any Protection Profile.

## Package Claim

This Module does not claim conformance to any packages.

# 3 Security Problem Description

WIDS address a range of security threats related to detection of and reaction to potentially malicious WLAN traffic. The malicious traffic may pose a threat to one or more endpoints on the monitored networks, to the network infrastructure, or to the TOE itself. Attacks against a WLAN could compromise the confidentiality and integrity of WLAN users and system data as well as the availability of the WLAN to legitimate users.

The term “monitored network” is used here to represent any WLAN and/or wired network that the TOE is configured to monitor and detect intrusions on. This extends to the wired networks as intrusions on the wireless network can also be damaging to the wired infrastructure. The WIDS/WIPS also protect the wired infrastructure by detecting rogue devices that are directly connected to the wired infrastructure, which may expose the wired network, or unauthorized WLAN devices deployed in a no-wireless zone.

The proper installation, configuration, and administration of the WIDS is critical to its correct operation. A site is responsible for developing its security policy and configuring a rule set that the WIDS will enforce and provide an appropriate response to meet their needs, relative to their own risk analysis and their perceived threats.

Note that this PP-Module does not repeat the threats identified in the NDcPP, though they all apply given the conformance and hence dependence of this PP-Module on the NDcPP. Note also that while the NDcPP contains only threats to the ability of the TOE to provide its security functions, this PP-Module addresses only threats to resources in the operational environment. Together the threats of the NDcPP and those defined in this PP-Module define the comprehensive set of security threats addressed by a WIDS TOE.

## 3.1 Threats

---

### **T.UNAUTHORIZED\_DISCLOSURE\_OF\_INFORMATION**

A malicious actor may take advantage of unintended/unauthorized disclosure of sensitive information on a protected WLAN, such as sending unencrypted sensitive data, without detection. A malicious actor may also force the modification or disclosure of data in transit between distributed components of a WIDS to impede or gain visibility into its data collection capabilities.

### **T.UNAUTHORIZED\_ACCESS**

An attacker may attempt to gain unauthorized access to a network, endpoints, or services, by methods such as impersonation of an authorized AP to get an EUD to connect to the unauthorized AP. If malicious external APs or EUDs are able to communicate with APs or EUDs on the protected WLAN, then those devices may be susceptible to the unauthorized disclosure of information.

### **T.DISRUPTION**

Attacks against the WLAN infrastructure might lead to denial of service (DoS) attacks within a protected WLAN. A wireless DoS may occur in two ways: at the physical layer through RF Jamming, or at the data link layer through packet injection.

## 3.2 Assumptions

---

These assumptions are made on the Operational Environment (OE) in order to be able to ensure that the security functionality specified in the PP-Module can be provided by the TOE. If the TOE is placed in an OE that does not meet these assumptions, the TOE may no longer be able to provide all of its security functionality.

### **A.CONNECTIONS**

It is assumed that the TOE is connected to distinct networks in a manner that ensures that the TOE's security policies will be enforced on all applicable network traffic flowing among the attached networks.

### **A.PROPER\_ADMIN**

The administrator of the WIDS is not careless, willfully negligent or hostile, and administers the WIDS within compliance of the applied enterprise security policy.

## 3.3 Organizational Security Policies

---

An organization deploying the TOE is expected to satisfy the organizational security policy listed below in addition to all organizational security policies defined by the claimed Base-PP.

### **P.ANALYZE**

Analytical processes and information to derive conclusions about potential intrusions must be applied to WIDS data and appropriate response actions taken.

# 4 Security Objectives

## 4.1 Security Objectives for the TOE

### O.SYSTEM\_MONITORING

To be able to analyze and react to potential network policy violations, the WIDS must be able to collect and store essential data elements of network traffic on monitored networks. A conformant TOE may also implement a self-protection mechanism to ensure that undetected network policy violations cannot occur when a sensor is unavailable.

Addressed by: [FAU\\_GEN\\_EXT.1](#) (from Base-PP), [FAU\\_STG\\_EXT.1](#) (from Base-PP), [FAU\\_GEN.1/WIDS](#), [FAU\\_RPT\\_EXT.1](#), [FAU\\_STG\\_EXT.1/PCAP](#), [FPT\\_FLS.1](#) (objective)

### O.WIDS\_ANALYZE

The WIDS must be able to analyze collected or observed WLAN activity on monitored network to identify potential violations of approved WLAN policies, unauthorized connections involving internal WLAN devices, and non-secure communications.

Addressed by: [FAU\\_ARP.1](#), [FAU\\_ARP\\_EXT.1](#), [FAU\\_IDS\\_EXT.1](#), [FAU\\_INV\\_EXT.1](#), [FAU\\_INV\\_EXT.2](#), [FAU\\_INV\\_EXT.3](#), [FAU\\_SAA.1](#), [FAU\\_WID\\_EXT.1](#), [FAU\\_WID\\_EXT.2](#), [FDP\\_IFC.1](#), [FAU\\_WID\\_EXT.3](#) (optional), [FAU\\_WID\\_EXT.4](#) (optional), [FAU\\_ANO\\_EXT.1](#) (selection-based), [FAU\\_SIG\\_EXT.1](#) (selection-based), [FAU\\_INV\\_EXT.4](#) (objective), [FAU\\_INV\\_EXT.5](#) (objective), [FAU\\_MAC\\_EXT.1](#) (objective)

### O.WIDS\_REACT

The TOE must be able to react, as configured by the administrators, to configured policy violations or other potential malicious activity.

Addressed by: [FAU\\_ARP.1](#), [FAU\\_SAA.1](#), [FMT\\_SMF.1/WIDS](#), [FAU\\_ANO\\_EXT.1](#) (selection-based), [FAU\\_WIP\\_EXT.1](#) (objective)

### O.TOE\_ADMINISTRATION

To address the threat of unauthorized administrator access that is defined in the Base-PP, conformant TOEs will provide the functions necessary for an administrator to configure the WIDS capabilities of the TOE. A conformant TOE may also implement a self-protection mechanism to ensure that a TSF failure cannot be used as a way to modify the TOE's configuration without authorization.

Addressed by: [FMT\\_SMF.1/WIDS](#), [FPT\\_FLS.1](#) (objective)

### O.TRUSTED\_COMMUNICATIONS

To further address the threat of untrusted communications channels that is defined in the Base-PP, conformant TOEs will provide trusted communications between distributed components if any exist.

## 4.2 Security Objectives for the Operational Environment

The OE of the TOE implements technical and procedural measures to assist the TOE in correctly providing its security functionality (which is defined by the security objectives for the TOE). The security objectives for the OE consist of a set of statements describing the goals that the OE should achieve. This section defines the security objectives that are to be addressed by the IT domain or by non-technical or procedural means. The assumptions identified in Section 3 are incorporated as security objectives for the environment. The following security objectives for the operational environment assist the TOE in correctly providing its security functionality. These track the assumptions about the environment.

### OE.CONNECTIONS

TOE administrators will ensure that the TOE is installed in a manner that will allow the TOE to effectively enforce its policies on the network traffic of monitored networks.

### OE.PROPER\_ADMIN

The administrator of the WIDS is not careless, willfully negligent or hostile, and administers the WIDS within compliance of the applied enterprise security policy.

## 4.3 Security Objectives Rationale

This section describes how the assumptions, threats, and organizational security policies map to the security objectives.

Table 1: Security Objectives Rationale

| Threat, Assumption, or OSP                               | Security Objectives                 | Rationale  |
|--|-------------------------------------|--|
| <a href="#">T.UNAUTHORIZED_DISCLOSURE_OF_INFORMATION</a> | <a href="#">O.SYSTEM_MONITORING</a> | The threat <a href="#">T.UNAUTHORIZED_DISCLOSURE_OF_INFORMATION</a> is countered by <a href="#">O.SYSTEM_MONITORING</a> as this provides for |



|                       |                          |   |
|-----------------------|--------------------------|---|
|                       |                          | visibility into the network which enables detection of network violations.  |
|                       | O.TRUSTED_COMMUNICATIONS | The threat T.UNAUTHORIZED_DISCLOSURE_OF_INFORMATION is countered by O.TRUSTED_COMMUNICATIONS as this ensures that data in transit is protected from unauthorized disclosure through authentication of endpoints and use of trusted protocols. |
|                       | O.WIDS_ANALYZE           | The threat T.UNAUTHORIZED_DISCLOSURE_OF_INFORMATION is countered by O.WIDS_ANALYZE as this provides detection of potential violations of approved network usage.  |
|                       | O.WIDS_REACT             | The threat T.UNAUTHORIZED_DISCLOSURE_OF_INFORMATION is countered by O.WIDS_REACT as this provides containment of unauthorized APs and EUDs.   |
| T.UNAUTHORIZED_ACCESS | O.SYSTEM_MONITORING      | The threat T.UNAUTHORIZED_ACCESS is countered by O.SYSTEM_MONITORING as this provides for visibility into the network which enables detection of unauthorized APs and EUDs.   |
|                       | O.WIDS_ANALYZE           | The threat T.UNAUTHORIZED_ACCESS is countered by O.WIDS_ANALYZE as this provides detection of potential violations of approved network usage.   |
|                       | O.WIDS_REACT             | The threat T.UNAUTHORIZED_ACCESS is countered by O.WIDS_REACT as this provides containment of unauthorized APs and EUDs.  |
|                       | O.TOE_ADMINISTRATION     | The threat T.UNAUTHORIZED_ACCESS is countered by O.TOE_ADMINISTRATION.  |
| T.DISRUPTION          | O.SYSTEM_MONITORING      | The threat T.DISRUPTION is countered by O.SYSTEM_MONITORING as this provides for visibility into the network which enables detection of DoS attacks.  |
|                       | O.WIDS_ANALYZE           | The threat T.DISRUPTION is countered by O.WIDS_ANALYZE as this provides for detection of potential violations of approved network usage.  |
|                       | O.WIDS_REACT             | The threat T.DISRUPTION is countered by O.WIDS_REACT as this provides containment of unauthorized APs and EUDs.   |
| A.CONNECTIONS         | OE.CONNECTIONS           | The operational environment objective OE.CONNECTIONS is realized through A.CONNECTIONS.   |
| A.PROPER_ADMIN        | OE.PROPER_ADMIN          | The operational environment objective OE.PROPER_ADMIN is realized through A.PROPER_ADMIN.   |
| P.ANALYZE             | O.WIDS_ANALYZE           | The organizational security policy P.ANALYZE is facilitated through O.WIDS_ANALYZE.   |

# 5 Security Requirements

This chapter describes the security requirements which have to be fulfilled by the product under evaluation. Those requirements comprise functional components from Part 2 and assurance components from Part 3 of [CC]. The following conventions are used for the completion of operations:

- **Refinement** operation (denoted by **bold text** or ~~striketrough text~~): is used to add details to a requirement (including replacing an assignment with a more restrictive selection) or to remove part of the requirement that is made irrelevant through the completion of another operation, and thus further restricts a requirement.
- **Selection** (denoted by *italicized text*): is used to select one or more options provided by the [CC] in stating a requirement.
- **Assignment** operation (denoted by *italicized text*): is used to assign a specific value to an unspecified parameter, such as the length of a password. Showing the value in square brackets indicates assignment.
- **Iteration** operation: is indicated by appending the SFR name with a slash and unique identifier suggesting the purpose of the operation, e.g. "/EXAMPLE1."

## 5.1 NDcPP Security Functional Requirements Direction

In a PP-Configuration that includes NDcPP, the TOE is expected to rely on some of the security functions implemented by the Network Device as a whole and evaluated against the NDcPP. The following sections describe any modifications that the ST author must make to the SFRs defined in the NDcPP in addition to what is mandated by [Section 5.2 TOE Security Functional Requirements](#).

### 5.1.1 Modified SFRs

The SFRs listed in this section are defined in the NDcPP and relevant to the secure operation of the TOE.

#### 5.1.1.1 Security Audit (FAU)

##### FAU\_GEN\_EXT.1 Security Audit Data Generation for Distributed TOE Components

FAU\_GEN\_EXT.1.1

The TSF shall be able to generate audit records for each TOE component. The audit records generated by the TSF of each TOE component shall include the subset of security relevant audit events which can occur on the TOE component.

**Application Note:** This SFR is selection-based in the Base-PP but is mandated by this PP-Module because the ST author must claim a distributed TOE selection in [FAU\\_STG\\_EXT.1.2](#).

#### Evaluation Activities ▼

##### [FAU\\_GEN\\_EXT.1](#)

*There is no change to the EAs specified for this SFR in the NDcPP SD. The PP-Module modifies this SFR to make its inclusion mandatory rather than selection-based, but there is no change to how the SFR must be implemented.*

##### FAU\_STG\_EXT.1 Protected Audit Event Storage

FAU\_STG\_EXT.1.1

The TSF shall be able to transmit the generated audit data to an external IT entity using a trusted channel according to [FTP\\_ITC.1](#).

FAU\_STG\_EXT.1.2

The TSF shall be able to store generated audit data on the TOE itself. In addition **[selection:**

- *The TOE shall be a distributed TOE that stores audit data on the following TOE components: **[assignment:** identification of TOE components],*
- *The TOE shall be a distributed TOE with storage of audit data provided externally for the following TOE components: **[assignment:** list of TOE components that do not store audit data locally and the other TOE components to which they transmit their generated audit data]*

**].**

**Application Note:** This SFR is modified from its definition in the Base-PP by removing the selection option for the TOE to be standalone. A TOE that conforms to this PP-Module is expected to be distributed.

#### Evaluation Activities ▼

#### [FAU\\_STG\\_EXT.1](#)

*There is no change to the EAs specified for this SFR in the NDcPP SD. The PP-Module modifies this SFR to remove one of the possible selection items, but there is no change to how the SFR is to be implemented.*

### 5.1.1.2 Communications (FCO)

#### FCO\_CPC\_EXT.1 Communication Partner Control

##### FCO\_CPC\_EXT.1.1

The TSF shall require a Security Administrator to enable communications between any pair of TOE components before such communication can take place.

##### FCO\_CPC\_EXT.1.2

The TSF shall implement a registration process in which components establish and use a communications channel that uses **[selection:**

- *A channel that meets the secure channel requirements in **[selection:** [FTP\\_ITC.1](#), [FPT\\_ITT.1](#)],*
- *A channel that meets the secure registration channel requirements in [FTP\\_TRP.1/Join](#),*
- *No channel*

**] for at least TSF data.**

##### FCO\_CPC\_EXT.1.3

The TSF shall enable a Security Administrator to disable communications between any pair of TOE components.

**Application Note:** This SFR is optional in the NDcPP but is mandated by this PP-Module because the WIDS TOE is expected to be a distributed system.

#### Evaluation Activities ▼

#### [FCO\\_CPC\\_EXT.1](#)

*There is no change to the EAs specified for this SFR in the NDcPP SD. The PP-Module modifies this SFR to make its inclusion mandatory rather than optional, but there is no change to how the SFR is to be implemented.*

### 5.1.1.3 Protection of the TSF (FPT)

#### FPT\_ITT.1 Basic Internal TSF Data Transfer Protection

##### FPT\_ITT.1.1

The TSF shall protect TSF data from disclosure and detect its modification when it is transmitted between separate parts of the TOE through the use of **[selection:** *IPsec, SSH, TLS, DTLS, HTTPS*].

**Application Note:** [FPT\\_ITT.1](#) is optional in NDcPP, however, since a WIDS/WIPS TOE is distributed, [FPT\\_ITT.1](#) shall be included in the ST and is applicable to the data transmitted between the sensors and controller. This requirement ensures all communications between components of a distributed TOE is protected through the use of an encrypted communications channel. The data passed in this trusted communication channel are encrypted as defined in the protocol chosen in the selection. The ST author chooses the mechanisms supported by the TOE, and then ensures that the detailed protocol requirements in Appendix B of NDcPP corresponding to their selection are included in the ST, if not already present.

#### Evaluation Activities ▼

#### [FPT\\_ITT.1](#)

*There is no change to the EAs specified for this SFR in the NDcPP SD. The PP-Module modifies this SFR to make its inclusion mandatory rather than optional, but there is no change to how the SFR is to be implemented.*

### 5.1.1.4 Trusted Paths/Channels (FTP)

#### FTP\_ITC.1 Inter-TSF trusted channel

The TSF shall be capable of using [**selection:** *IPsec, SSH, TLS, DTLS, HTTPS*] to provide a trusted communication channel between itself and authorized IT entities supporting the following capabilities: audit server, [**selection:** *authentication server, database server, [assignment: other capabilities], no other capabilities*] that is logically distinct from other communication channels and provides assured identification of its end points and protection of the channel data from disclosure and detection of modification of the channel data.

**Application Note:** This SFR is modified from its definition in the Base-PP by adding a selection for a database server capability. If the TSF uses a separate database server to support its security-relevant functionality, this selection must be included in the ST.

The intent of the database server is to store WIDS/WIPS data that must be queryable, such as events/alarms, triangulation calculations, wireless spectrum analysis (including RF jammer/Denial of Service (DoS)), and packet capture analysis. Authorized Administrators must be permitted to view alarms, raw event data, and any other data stored in the database. The Administrator must access the database through a trusted channel if done so remotely.

The intent of this requirement is to provide a means by which a cryptographic protocol may be used to protect external communications with authorized IT entities that the TOE interacts with to perform its functions. The TOE uses at least one of the listed protocols for communications with the server that collects the audit information.

If other authorized IT entities are protected, the ST author makes the appropriate assignments (for those entities) and selections (for the protocols that are used to protect those connections). The ST author selects the mechanism or mechanisms supported by the TOE, and then ensures that the detailed protocol requirements in Appendix B of NDcPP corresponding to their selection are included in the ST.

## Evaluation Activities ▼

### [FTP\\_ITC.1](#)

*There is no change to the EAs specified for this SFR in the NDcPP SD. If 'database server' is selected in [FTP\\_ITC.1.1](#), the evaluator shall ensure that the required tests are performed on that external interface in addition to the other claimed interfaces.*

*The evaluator shall also perform test 4 for this SFR in the NDcPP SD, which is objective in NDcPP.*

## 5.2 TOE Security Functional Requirements

The following section describes the SFRs that must be satisfied by any TOE that claims conformance to this PP-Module. These SFRs must be claimed regardless of which PP-Configuration is used to define the TOE.

### 5.2.1 Security Audit (FAU)

#### FAU\_ARP.1 Security Alarms

##### FAU\_ARP.1.1

The TSF shall **display an alert to Authorized Administrator in sufficient detail to include identity of APs and EUDs involved, signal strength, accurate event timestamp, description of alert and severity level and [selection: capture raw frame traffic that triggered the violation, no other actions]** upon detection of a potential security violation.

**Application Note:** If "capture raw frame traffic that triggers the violation" is selected then [FAU\\_STG\\_EXT.1/PCAP](#) must be included in the ST.

[FAU\\_SAA.1](#) defines the rules for monitoring the wireless traffic to detect for potential security violations. [FAU\\_INV\\_EXT.2](#) defines the information the TOE needs to collect for all APs and EUDs within range of the the TOE's sensors. Device attributes can then be individually filtered and/or selected in order to be displayed as part of the alert.

## Evaluation Activities ▼

### [FAU\\_ARP.1](#)

### TSS

The evaluator shall verify that the TSS describes where to find the WIDS alerts on the Administrator console/interface.

### Guidance

The evaluator shall use the operational guidance for instructions on where the alerts generated are displayed within the WIDS interface. If "capture raw frame traffic that triggers the violation is selected", the evaluator shall use the operational guidance to configure the traffic capture capabilities.

### Tests

- **Test 1:** The evaluator shall perform a series of events or generate traffic that would successfully trigger an alert for each of the rules defined in [FAU\\_SAA.1](#). The evaluator should verify and record whether the TOE generated the alert for each rule, and provided sufficient details. The evaluator should also record the events or traffic that was generated as each alert was attempted to be triggered and record the details provided by the TOE in the alert.
- **Test 2:** [conditional] If capturing of raw frames was selected, verify that the packet capture was triggered and stored as appropriate.

## FAU\_ARP\_EXT.1 Security Alarm Filtering

### FAU\_ARP\_EXT.1.1

The TSF shall provide the ability to apply [assignment: methods of selection] to selectively exclude alerts from being generated.

## Evaluation Activities ▼

### [FAU\\_ARP\\_EXT.1](#)

#### TSS

The evaluator shall verify that the TSS describes the ability of the TOE to filter WIDS/WIPS alerts.

#### Guidance

The evaluator shall verify that the operational guidance includes instructions on enabling and disabling alerts.

#### Tests

- **Test 1:**
  - **Step 1:** The evaluator shall use the operational guidance to enable/disable detection of available detection capabilities through the WIDS administrator interface. The evaluator shall then generate traffic that would successfully trigger the alert. The evaluator should verify that the TOE generated the alert.
  - **Step 2:** The evaluator shall disable the alert. The evaluator shall then generate events as in previous test that should successfully trigger the alert. The evaluator shall verify that the TOE did not generate an alert.

## FAU\_GEN.1/WIDS Audit Data Generation (WIDS)

### FAU\_GEN.1.1/WIDS

The TSF shall be able to generate an audit record of the following auditable events:

- a. Start-up and shutdown of the audit functions;
- b. All auditable events for the [not specified] level of audit;
- c. [Auditable events listed in the Auditable Events table ([Table 2](#));
- d. Failure of wireless sensor communication].

| Requirement  | Auditable Events                                   | Additional Audit Record Contents |
|--|--|----------------------------------|
| <a href="#">FAU_ANO_EXT.1</a><br>(selection-based) | None   | None                             |
| <a href="#">FAU_ARP.1</a>                          | Actions taken due to potential security violations | None                             |
| <a href="#">FAU_ARP_EXT.1</a>                      | None   | None                             |

|                                      |   |   |
|--------------------------------------|---|---|
| FAU_GEN.1/WIDS                       | None  | None  |
| FAU_IDS_EXT.1                        | None  | None  |
| FAU_INV_EXT.1                        | Presence of allowedlisted device                            | Type of device (AP or EUD), MAC Address   |
| FAU_INV_EXT.2                        | None  | None  |
| FAU_INV_EXT.3                        | Location of AP or EUD                                       | MAC Address, device type, classification of device, sensor(s) that detected device, signal strength as received by detecting sensor(s), proximity to detecting sensor(s)  |
| FAU_INV_EXT.4 (objective)            | None  | None  |
| FAU_INV_EXT.5 (objective)            | None  | None  |
| FAU_MAC_EXT.1 (objective)            | None  | None  |
| FAU_RPT_EXT.1                        | None  | None  |
| FAU_SAA.1                            | None  | None  |
| FAU_SIG_EXT.1 (selection-based)      | None  | None  |
| FAU_STG_EXT.1/PCAP (selection-based) | None  | None  |
| FAU_WID_EXT.1                        | Detection of rogue AP or EUD                                | None  |
|                                      | Detection of unauthorized SSID                              | None  |
| FAU_WID_EXT.2                        | Sensor wireless transmission capabilities                   | Wireless transmission capabilities are turned on  |
| FAU_WID_EXT.3 (optional)             | Detection of network devices operating in selected RF bands | Frequency band, channel used within frequency band, identification information (MAC address if applicable or other similar unique ID), device technology (i.e., cellular), sensor(s) that detected devices  |
| FAU_WID_EXT.4 (optional)             | None  | None  |
| FAU_WIP_EXT.1 (objective)            | Isolation of AP or EUD                                      | Description of violation, type of containment used, was containment triggered manually or automatically, sensor performing the containment (if wireless), details about the device (s) being contained (classification, device type, MAC address) |
| FDP_IFC.1                            | None  | None  |
| FMT_SMF.1/WIDS                       | None  | None  |
| FPT_FLS.1 (objective)                | Information about failure                                   | Indication that there was a failure, type of failure, device that failed, and time of failure   |

Table 2: Auditable Events

**Application Note:** The auditable events defined in [Table 2](#) are for the SFRs that are explicitly defined in this PP-Module and are intended to extend FAU\_GEN.1

in the Base-PP. The events in the Auditable Events table should be combined with those of the NDcPP in the context of a conforming Security Target. The Auditable Events ([Table 2](#)) includes optional and objective SFRs. The auditing of optional and objective SFRs is only required if that SFR is included in the ST.

Per [FAU\\_STG\\_EXT.1](#) in the Base-PP, the TOE must support transfer of the audit data to an external IT entity using a trusted channel.

FAU\_GEN.1.2/WIDS

The TSF shall record within each audit record at least the following information:

- a. Date and time of the event, type of event, and subject identity (if applicable);
- b. For each audit event type, based on the auditable event definitions of the functional components included in the PP/ST, [*auditable events listed in Auditable Events table ([Table 2](#))*].

**Application Note:** The subject identity in this case is the allowlisted inventory item.

## Evaluation Activities ▼

[FAU\\_GEN.1/WIDS](#)

### TSS

*There are no TSS evaluation activities for this SFR.*

### Guidance

*There are no operational guidance activities for this SFR.*

### Tests

*The evaluator shall test the TOE's ability to correctly generate audit records by having the TOE generate audit records in accordance with the evaluation activities associated with the functional requirements in this PP-Module. When verifying the test results, the evaluator shall ensure the audit records generated during testing match the format specified in the administrative guide, and that the fields in each audit record have the proper entries.*

*Note that the testing here can be accomplished in conjunction with the testing of the security mechanisms directly.*

## FAU\_IDS\_EXT.1 Intrusion Detection System - Intrusion Detection Methods

FAU\_IDS\_EXT.1.1

The TSF shall detect intrusions using[**selection:** *anomaly-based, signature-based, [assignment: other detection method]*] methods.

**Application Note:** At least one detection method must be selected. If multiple detection methods are supported, each supported method must be selected.

If anomaly-based detection is selected, then [FAU\\_ANO\\_EXT.1](#) shall be included in the ST. If signature-based detection is selected, then [FAU\\_SIG\\_EXT.1](#) shall be included in the ST.

## Evaluation Activities ▼

[FAU\\_IDS\\_EXT.1](#)

### TSS

*The evaluator shall verify that the TSS includes which intrusion detection method(s) the TOE utilizes. If multiple methods are selected, the evaluator shall confirm that the TSS describes how the different methods are incorporated.*

### Guidance

*The evaluator shall verify that the operational guidance provides instructions on how to configure the TOE in order for it to detect such intrusions.*

### Tests

*Depending on the detection technique used by the TOE, the evaluator shall confirm and note the existence of the capability and test for the appropriate selection-based requirements.*

## FAU\_INV\_EXT.1 Environmental Inventory

FAU\_INV\_EXT.1.1

The TSF shall determine if a given AP is authorized based on [**selection:** *MAC*]



addresses, [**assignment:** other unique device identifier]]

FAU\_INV\_EXT.1.2

The TSF shall determine if a given EUD is authorized based on [**selection:** MAC addresses, [**assignment:** other unique device identifier]]

FAU\_INV\_EXT.1.3

The TSF shall detect the presence of non-allowlisted EUDs and APs in the Operational Environment.

**Application Note:** This inventory is used as an allowlist to indicate to the WIDS which APs and EUDs are authorized members of the wireless network. The inventory of authorized APs and EUDs is configured by [FMT\\_SMF.1/WIDS](#). The terminology used to describe an inventoried or allowlisted device may vary by vendor product. This PP-Module utilizes allowlisted to describe APs and EUDs that are part of the inventory and non-allowlisted to describe APs and EUDs that are not part of the inventory.

## Evaluation Activities ▼

### [FAU\\_INV\\_EXT.1](#)

#### **TSS**

*The evaluator shall verify that the TSS describes how the presence of authorized EUDs and APs is presented by the TOE. The evaluator shall verify that the TSS includes where in the WIDS interface the list of detected APs and EUDs is displayed.*

#### **Guidance**

*The evaluator shall verify that the operational guidance provides instructions on how to view authorized and unauthorized APs and EUDs that are within range of the TOE sensors.*

#### **Tests**

##### • **Test 1:**

- **Step 1:** Per guidance in [FMT\\_SMF.1/WIDS](#), add MAC Addresses or other unique device identifier for an AP and EUD to the allowlist.
- **Step 2:** Deploy the AP and EUD that were added to allowlist within the range of the TOE's sensors.
- **Step 3:** Verify that the devices are classified as authorized.
- **Step 4:** Remove the EUD from the allowlist.
- **Step 5:** Verify that the EUD is classified as unauthorized.
- **Step 6:** Remove the AP from the allowlist.
- **Step 7:** Verify that the AP is classified as unauthorized.

##### • **Test 2:**

- **Step 1:** Deploy an allowlisted AP and EUD, and connect the EUD to the AP.
- **Step 2:** Verify that the list of detected APs and EUDs contains the allowlisted AP and EUD that were just deployed.
- **Step 3:** If the AP and EUD are detected verify that they are classified as allowlisted devices.

##### • **Test 3:**

- **Step 1:** Deploy a non-allowlisted AP and EUD and connect the EUD to the AP.
- **Step 2:** Verify that the list of detected APs and EUDs contains the non-allowlisted AP and EUD that were just deployed.
- **Step 3:** If the AP and EUD are detected verify that they are not classified as allowlisted devices.

## FAU\_INV\_EXT.2 Characteristics of Environmental Objects

FAU\_INV\_EXT.2.1

The TSF shall detect the

- Current RF band
- Current channel
- MAC Address
- Received signal strength
- Device detection timestamps
- Classification of APs and EUDs
- [**selection:** [**assignment:** other details], no other details]

of all APs and EUDs within range of the TOE's wireless sensors.

FAU\_INV\_EXT.2.2

The TSF shall detect the following additional details for all APs within range of the TOE's wireless sensors:



- encryption
- number of connected EUDs.
- Received frames/packets
- Beacon rate
- SSID of AP (if not hidden).

**Application Note:** For detection of encryption type, the TSF should be able to differentiate between the different WLAN encryption methods and when no encryption is in use.

FAU\_INV\_EXT.2.3

The TSF shall detect the follow additional details for all EUDs within range of the TOE's wireless sensors:

- SSID and BSSID of AP it is connected to.
- DHCP configuration.

## Evaluation Activities ▼

### [FAU\\_INV\\_EXT.2](#)

#### **TSS**

*The evaluator shall verify that the TSS explains the capability of detecting the information specified in the requirements for all APs and EUDs within the TOE's wireless range.*

#### **Guidance**

*The evaluator shall review the operational guidance in order to verify that there are instructions that show how to locate the device inventory mentioned above.*

#### **Tests**

##### • **Test 1:**

- **Step 1:** Deploy an allowlisted AP, non-allowlisted AP and two allowlisted EUDs.
- **Step 2:** Connect one allowlisted EUD to the allowlisted AP and one to the non-allowlisted AP.
- **Step 3:** Check the WIDS user interface for a list of detected APs and EUDs.
- **Step 4:** Verify that current RF band, current channel, MAC Address, received signal strength, device detection timestamps, classification of device, are part of the information presented on the WIDS user interface for all the APs and EUDs detected. For APs verify that encryption, number of connected EUDs, SSID (if not hidden), received frames/packets and beacon rate are presented. For EUDs verify that the SSID and BSSID of AP it is connected and DHCP configuration is presented.

## FAU\_INV\_EXT.3 Location of Environmental Objects

FAU\_INV\_EXT.3.1

The TSF shall detect the physical location of APs and EUDs to within [assignment: value equal or less than 25] feet of their actual location.

FAU\_INV\_EXT.3.2

The TSF shall detect received signal strength and [selection: RF power levels above a predetermined threshold, no other characteristics] of hardware operating within range of the TOE's wireless sensors.

## Evaluation Activities ▼

### [FAU\\_INV\\_EXT.3](#)

#### **TSS**

*The evaluator shall verify that the TSS includes information on location tracking, optimal number of sensors and sensor placement to meet the required level of accuracy.*

*The evaluator shall verify that the TSS contains information regarding the TSF's ability to record signal strength of hardware operating within range of its sensors.*

#### **Guidance**

*The evaluator shall review the operational guidance for instructions on how to configure location tracking, how to load a location map (if applicable), and where in the TSF administrator interface the location of APs and EUDs can be viewed.*

*If the option for detection of RF power levels above a predetermined threshold is selected, the evaluator shall use the operational guidance to set or check what the threshold is in a given test. The evaluator should also verify that the operational guidance provides instruction on how to configure the TOE to generate an alert when the threshold is exceeded.*

## Tests

### • Test 1:

- **Step 1:** Deploy an AP within range of the sensors.
- **Step 2:** Verify the TSF provides location tracking information about the AP.
- **Step 3:** Verify the AP location presented is within 25 feet actual location.

### • Test 2:

- **Step 1:** Deploy an AP within range of the sensors.
- **Step 2:** Check the WIDS user interface for a list of detected APs and EUDs.
- **Step 3:** Verify that the current received signal strength is part of the information presented on the WIDS user interface about the APs and EUDs.

## FAU\_RPT\_EXT.1 Intrusion Detection System - Reporting Methods

### FAU\_RPT\_EXT.1.1

The TSF shall provide [**selection:**

- Syslog using [**selection:** defined API, Syslog, [**assignment:** other detection method]],
- SNMP trap reporting using [**selection:** defined API, Simple Network Management Protocol (SNMP), [**assignment:** other detection method]]

] for reporting of collected data.

**Application Note:** Syslog and/or SNMP trap reporting can be used. At least one reporting method must be selected.

### FAU\_RPT\_EXT.1.2

The TSF shall provide the ability to import data, such as an allowlist of APs and EUDs, and WIDS/WIPS configuration files from the system using [**selection:** custom API, Syslog, common log format, CSV, [**assignment:** vendor detection method]].

**Application Note:** The system must provide the ability to interact with an extensible interface to a third party wireless monitoring system for the purposes of importing data from the wireless system.

## Evaluation Activities ▼

### FAU\_RPT\_EXT.1

#### TSS

The evaluator shall verify that the TSS includes which method the TOE utilizes.

#### Guidance

There are no operational guidance activities for this SFR.

#### Tests

Depending on the detection technique used by the TOE, the evaluator shall confirm and note the existence of the capability.

### • Test 1:

- **Step 1:** Deploy an allowlisted AP and connect it to the protected wired infrastructure via wire.
- **Step 2:** Confirm that the TSF can observe and capture traffic and events generated by the AP.
- **Step 3:** Confirm that the TSF can use the reporting mechanisms specified in the TSS.
- **Step 4:** Verify that the TSF can import and export observable event data in each of the formats specified in the TSS.

## FAU\_SAA.1 Potential Violation Analysis

### FAU\_SAA.1.1

The TSF shall be able to apply a set of rules for monitoring **the wireless traffic** and based upon these rules indicate a potential **malicious action**.

### FAU\_SAA.1.2

The TSF shall enforce the following rules for monitoring **wireless traffic**:

- Accumulation or combination of [**assignment:** subset of defined auditable events] known to indicate a potential security violation,
- Detection of non-allowlisted AP,
- Detection of non-allowlisted EUD,
- Detection of authorized EUD establishing peer-to-peer connection with any

- other EUD,
- e. Detection of EUD bridging two network interfaces,
- f. Detection of unauthorized point-to-point wireless bridges by allowlisted APs,
- g. Alert generated by violation of user defined signature,
- h. Detection of ICS connection,
- i. Detection of traffic with excessive transmit power level,
- j. Detection of MAC spoofing,
- k. Detection of unauthorized AP broadcasting authorized SSIDs,
- l. Detection of authorized AP broadcasting an unauthorized SSID,
- m. Detection of allowlisted EUD connected to unauthorized SSID,
- n. Detection of NULL SSID associations,
- o. Detection of active probing,
- p. Detection of packet flooding/DoS/DDoS,
- q. Detection of RF-based denial of service,
- r. Detection of deauthentication flooding,
- s. Detection of disassociation flooding,
- t. Detection of request-to-send/clear-to-send abuse,
- u. Detection of unauthorized authentication scheme use,
- v. Detection of unauthorized encryption scheme use,
- w. Detection of unencrypted traffic,
- x. Detection of allowlisted EUD or AP that is using weak/outdated WLAN protocols and protocol implementations,
- y. Detection of extremely high numbers of client devices using a particular allowlisted AP,
- z. Detection of a high number of failed attempts to join the WLAN in a short period of time,
- aa. Detection of the use of active WLAN scanners (e.g. wardriving tools) to generate WLAN traffic, such as Probes, Auths, and Assoc frames,
- ab. Detection of the physical location of an identified WLAN threat by using triangulation,
- ac. Detection of an SSID using weak/unsupported/disallowed encryption options,
- ad. Detection of AP SSID larger than 32 bytes,
- ae. **[assignment]:** any other rules].

**Application Note:** These rules are used to detect a potential security violation. Maintenance of the rules by adding, modifying or deletion of rules from the set of rules is handled by [FMT\\_SMF.1/WIDS](#).

If a potential security violation is detected the alert generated for the Administrator is handled by [FAU\\_ARP.1](#).

## Evaluation Activities ▼

### [FAU\\_SAA.1](#)

#### **TSS**

The evaluator shall verify that the TSS describes the ability of the TOE to detect the network behavior described by the SFR. The evaluator shall verify that the TSS describes the methods that the TOE uses to detect the presence of unauthorized connections and unauthorized network traffic. The evaluator shall examine the TSS to verify that it describes the denial of service attacks that can be detected by the TOE. The evaluator shall verify that the TSS describes the ability of the TOE to detect when unauthorized WLAN authentication schemes and encryption schemes are used. The evaluator shall verify that the TSS describes the ability of the TOE to detect when unauthorized APs and EUDs send or receive unencrypted data.

#### **Guidance**

If the ability of the TSF to detect the different potential security violations is configurable, the evaluator shall verify that the operational guidance provides instructions on how to configure the TOE.

#### **Tests**

- **Test 1: Detection of non-allowlisted AP:**
  - **Step 1:** Deploy a non-allowlisted AP.
  - **Step 2:** Verify that the AP is detected as a non-allowlisted AP.
- **Test 2: Detection of non-allowlisted EUD:**
  - **Step 1:** Deploy a non-allowlisted EUD.
  - **Step 2:** Verify that the EUD is detected as a non-allowlisted EUD.
- **Test 3: Detection of authorized EUD establishing peer-to-peer connection with any other EUD:**
  - **Test 3.1:** Create the following connections between two allowlisted EUDs.

- Windows Ad Hoc Connection
    - Mac OS Ad Hoc
    - Linux Ad Hoc
    - Wi-Fi Direct
  - **Test 3.2:** Create the following connections between one allowlisted EUD and a non-allowlisted EUD
    - Windows Ad Hoc Connection
    - Mac OS Ad Hoc
    - Linux Ad Hoc
    - Wi-Fi Direct
- Verify that alerts were generated by each of the connections in each test.
- **Test 4: Detection of EUD bridging two network interfaces:**  
Bridge two network interfaces on an allowlisted EUD (one must be the wireless card listed as allowlisted).
    - **Step 1:** Create a Windows Hosted Network with an allowlisted EUD.
    - **Step 2:** Connect a different allowlisted EUD to the network.
- Verify that alerts were generated by each of the connections in each test.
- **Test 5: Detection of unauthorized point to point wireless bridges by allowlisted APs:**
    - **Step 1:** Setup a point-to-point wireless bridge using allowlisted APs in the range of the wireless sensors.
    - **Step 2:** Verify that the TSF detects the bridge.
  - **Test 6: Alert generated by violation of user defined signature:**
    - **Step 1:** Setup a user defined detection signature.
    - **Step 2:** Verify that the TSF generates an alert once the rules of signature have been violated.
  - **Test 7: Detection of ICS connection:**
    - **Step 1:** Setup an Internet Connection Sharing (ICS) connection.
    - **Step 2:** Verify that the TSF detects the establishment of the ICS connection.
  - **Test 8: Detection of traffic with excessive transmit power level:**
    - **Step 1:** Configure a source of network traffic that can exceed the maximum transmit power levels of 100mW on 2.4 GHz, 200mW on 5 GHz, and 250mW on 6 GHz.
    - **Step 2:** Configure a user defined signature to detects traffic with transmit power levels that exceed the maximum.
    - **Step 3:** Commence with the transmission of network traffic at excessive power levels.
    - **Step 4:** Collect wireless traffic with range of the TSF.
    - **Step 5:** Verify that the TSF detects wireless traffic that exceeds 100mW on 2.4 GHz, 200mW on 5 GHz, and 250mW on 6 GHz.
  - **Test 9: Detection of MAC spoofing:**
    - **Test 9.1:**
      - **Step 1:** Spoof mac address of allowliste EUD connected to an allowlisted AP on a second EUD.
      - **Step 2:** Connect EUD with spoofed MAC address to another allowlisted AP while the valid EUD it is spoofing is connected to the first AP.
      - **Step 3:** Verify that the TSF detected the MAC spoofing.
    - **Test 9.2:**
      - **Step 1:** Spoof mac address of allowliste AP on a second AP.
      - **Step 2:** Verify that the TSF detected the MAC spoofing.
  - **Test 10: Detection of unauthorized AP broadcasting authorized SSIDs:**
    - **Step 1:** Configure a non-allowlisted AP to operate on a set channel on the 2.4 GHz band broadcasting an authorized SSID.
    - **Step 2:** Verify that the TSF detects the non-allowlisted AP broadcasting an authorized SSID.
    - **Step 3:** Repeat the test utilizing the 5 GHz band.
    - **Step 4:** Repeat the test utilizing the 6 GHz band.
  - **Test 11: Detection of authorized AP broadcasating an unathorized SSID:**
    - **Step 1:** Configure an allowlisted AP to operate on a set channel on the 2.4 GHz band broadcasting an unauthorized SSID.
    - **Step 2:** Verify that the TSF detects the non-allowlisted AP broadcasting an authorized SSID.

- **Step 3:** Repeat the test utilizing the 5 GHz band.
- **Step 4:** Repeat the test utilizing the 6 GHz band.
- **Test 12: Detection of allowlisted EUD connected to unauthorized SSID:**
  - **Step 1:** Configure an allowlisted AP to operate on a set channel on the 2.4 GHz band with an unauthorized SSID.
  - **Step 2:** Connect an allowlisted EUD to the AP.
  - **Step 3:** Verify that the TSF detects the allowlisted EUD associated to the allowlisted AP broadcasting an unauthorized SSID.
  - **Step 4:** Repeat the test utilizing the 5 GHz band.
  - **Step 5:** Repeat the test utilizing the 6 GHz band.
- **Test 13: Detection of NULL SSID associations:**
  - **Step 1:** Deploy allowlisted AP.
  - **Step 2:** Configure the AP to have null SSID.
  - **Step 3:** Attempt to connect an allowlisted EUD to the AP without supplying the correct AP SSID.
  - **Step 4:** Verify that the AP does not permit the EUD to complete an association by returning a Probe Request.
  - **Step 5:** If an association does occur, confirm that an alert is triggered due to a violation of policy.
- **Test 14: Detection of active probing:**
  - **Step 1:** Perform an active scan on the subnet of the WLAN.
  - **Step 2:** Record tools used and type of scan performed.
  - **Step 3:** Verify that the TSF detects the active probing.
- **Test 15: Detection of packet flooding/DoS/DDoS:**
  - **Step 1:** Generate a large amount of TCP and UDP traffic from a single EUD.
  - **Step 2:** Verify that the TSF detects the network-based DoS.
  - **Step 3:** Generate a large amount of TCP and UDP traffic from multiple EUDs.
  - **Step 4:** Verify that the TSF detects the network-based DDoS.
- **Test 16: Detection of RF-based denial of service:**
  - **Step 1:** Deploy an allowlisted AP and configure to stay in a particular channel.
  - **Step 2:** Connect an allowlisted EUD to the AP.
  - **Step 3:** Use an RF Jammer or signal generator on the same frequency as the AP and EUD to create a RF-based DoS.
  - **Step 4:** Verify that the TOE detects the RF-based DoS.
- **Test 17: Detection of deauthentication flooding:**
  - **Test 17.1:**
    - **Step 1:** Deploy allowlisted AP and configure to a set channel.
    - **Step 2:** Connect an allowlisted EUD to the AP.
    - **Step 3:** Send an flood of deauthentication frames to the EUD using the MAC address of allowlisted AP it is connected to.
    - **Step 4:** Verify that the TSF detects the deauthentication flood.
  - **Test 17.2:**
    - **Step 1:** Deploy allowlisted AP and configure to a set channel.
    - **Step 2:** Connect an allowlisted EUD to the AP.
    - **Step 3:** Send an flood of deauthentication frames with the MAC address of allowlisted AP as the source and destination as a broadcast.
    - **Step 4:** Verify that the TSF detects the deauthentication flood.
- **Test 18: Detection of disassociation flooding:**
  - **Step 1:** Deploy an allowlisted AP and connect authorized EUDs.
  - **Step 2:** Generate disassociation frames from an unauthorized EUD.
  - **Step 3:** Verify that the TSF detected the disassociation flooding.
- **Test 19: Detection of request-to-send/clear-to-send abuse:**
  - **Step 1:** Deploy allowlisted AP and configure to a set channel.
  - **Step 2:** Connect two allowlisted EUDs to the AP.
  - **Step 3:** Send an flood of CTS frames to reserve RF medium.
  - **Step 4:** Verify that the TSF detects the CTS abuse.
- **Test 20: Detection of unauthorized authentication scheme use:**



The evaluator shall configure the TOE, per [FMT\\_SMF.1/WIDS](#), with 802.1x authentication as the only mode of authorized WLAN authentication scheme.

- **Test 20.1:**
  - **Step 1:** Deploy an allowlisted AP with open authentication.
  - **Step 2:** Connect an allowlisted EUD to AP.
  - **Step 3:** Verify that the TSF detects the AP and the EUD using unauthorized authentication schemes.
- **Test 20.2:**
  - **Step 1:** Deploy an allowlisted AP that uses pre-shared key authentication.
  - **Step 2:** Connect an allowlisted EUD to AP.
  - **Step 3:** Verify that the TSF detects the AP and the EUD using unauthorized authentication schemes.
- **Test 21: Detection of unauthorized encryption scheme use:**
  - **Test 21.1:**
    - **Step 1:** Configure the TOE with 128 bit AES encryption type as the only allowed encryption scheme.
    - **Step 2:** Deploy an allowlisted AP with no encryption.
    - **Step 3:** Connect an allowlisted EUD to AP.
    - **Step 4:** Verify that the TOE detects the AP and the EUD using unauthorized encryption schemes.
  - **Test 21.2:**
    - **Step 1:** Configure the TOE with 128 bit AES encryption type as the only allowed encryption scheme.
    - **Step 2:** Deploy an allowlisted AP that uses TKIP encryption only.
    - **Step 3:** Connect an allowlisted EUD to AP.
    - **Step 4:** Verify that the TSF detects the AP and the EUD using unauthorized encryption schemes.
- **Test 22: Detection of unencrypted traffic:**
  - **Test 22.1:**
    - **Step 1:** Deploy an allowlisted AP with no encryption.
    - **Step 2:** Connect an allowlisted EUD to AP and generate traffic.
    - **Step 3:** Verify that the TOE detects unencrypted data frames being sent between the allowlisted AP and EUD.
    - **Step 4:** Connect a non-allowlisted EUD to AP and generate traffic.
    - **Step 5:** Verify that the TSF detects unencrypted data frames being sent between the allowlisted AP and non-allowlisted EUD.
  - **Test 22.2:**
    - **Step 1:** Deploy a non-allowlisted AP with no encryption.
    - **Step 2:** Connect an allowlisted EUD to AP and generate traffic.
    - **Step 3:** Verify that the TSF detects unencrypted data frames being between the non-allowlisted AP and allowlisted EUD.
- **Test 23: Detection of allowlisted EUD or AP that is using weak/outdated WLAN protocols and protocol implementations:**
  - **Step 1:** Deploy an allowlisted AP that utilizes the 802.11g or older WLAN protocol.
  - **Step 2:** Verify that the TSF detects the weak/outdated WLAN protocol and generates an alert.
- **Test 24: Detection of extremely high numbers of client devices using a particular allowlisted AP:**
  - **Step 1:** Deploy an allowlisted AP.
  - **Step 2:** Configure a threshold amount of client devices that can use a particular AP.
  - **Step 3:** Connect enough client devices to the AP to purposely exceed the defined threshold.
  - **Step 4:** Verify that the TSF detects when the client usage exceeds the threshold.
- **Test 25: Detection of a high number of failed attempts to join the WLAN in a short period of time:**
  - **Step 1:** Deploy an allowlisted AP.
  - **Step 2:** Configure a threshold amount of connection attempts that can occur in a particular timeframe.
  - **Step 3:** Attempt to authenticate to the AP with enough client devices to purposely exceed the defined threshold.
  - **Step 4:** Verify that the TSF detects when the connection attempts within the specic

timeframe exceeds the threshold.

- **Test 26: Detection of the use of active WLAN scanners (e.g. wardriving tools) to generate WLAN traffic:**
  - **Step 1:** Deploy an allowlisted AP.
  - **Step 2:** Verify that the TSF detects when WLAN scanners are the source of WLAN traffic.
- **Test 27: Detection of the physical location of an identified WLAN threat by using triangulation:**
  - **Step 1:** Deploy a non-allowlisted AP or EUD within range of the TSF.
  - **Step 2:** Verify that the TSF can track and locate the AP or EUD to within 5 meters.
- **Test 28: Detection of an SSID using weak/unsupported/disallowed encryption options:**
  - **Step 1:** Deploy an allowlisted AP and configure its encryption options.
  - **Step 2:** Change the encryption options the AP advertises.
  - **Step 3:** Verify that the TSF detects when the AP's encryption options change.
- **Test 29: Detection of AP SSID larger than 32 bytes:**
  - **Step 1:** Deploy an allowlisted AP and configure its SSID to be larger than 32 bytes.
  - **Step 2:** Configure a user defined signature on the WIDS to detect when an SSID is larger than 32 bytes.
  - **Step 3:** Verify that the TSF detects when the AP's SSID is larger than 32 bytes.

## FAU\_WID\_EXT.1 Wireless Intrusion Detection - Malicious Environmental Objects

### FAU\_WID\_EXT.1.1

The TSF shall distinguish between benign and malicious APs and EUDs based on if the APs and EUDs are authorized and [**selection:** *automatic detection metrics, no other method*].

**Application Note:** [FAU\\_INV\\_EXT.1](#) defines that an AP or EUD is authorized based on if the AP/EUD is allowlisted as configured in [FMT\\_SMF.1](#). A non-allowlisted device does not always have to be conducting malicious activity. However, it is acceptable to equate an allowlisted AP/EUD as both authorized/benign and a nonallowlisted AP/EUD as both not authorized and thus malicious. If the TOE supports automatic malicious device detection, based on in-depth network traffic analysis, "automatic detection metrics" must be selected. This can be used to further distinguish if the AP/EUD is benign or malicious. If the TOE does not support automatic detection metrics, "no other method" must be selected.

### FAU\_WID\_EXT.1.2

The TSF shall provide the ability to determine if a given SSID is authorized.

**Application Note:** [FMT\\_SMF.1/WIDS](#) defines the subset of authorized SSID(s).

## Evaluation Activities ▼

### [FAU\\_WID\\_EXT.1](#)

#### **TSS**

The evaluator shall verify that the TSS describes how the TOE detects malicious APs/EUDs and whether the TOE supports automatic detection. The evaluator shall verify that the TSS includes how the TOE determines if a given SSID is authorized.

#### **Guidance**

If TOE supports automatic detection, the evaluator shall verify that the operational guidance contains instructions for configuring the automatic detection metrics. The evaluator shall verify that the operational guidance provides instructions on how to configure SSIDs as authorized.

#### **Tests**

For test 1 and 2 below the evaluator shall verify that the TOE detects and appropriately classifies the APs and EUDs. It is acceptable if the TOE uses different but equivalent descriptors for the classification. If the TOE does not support automatic detection metrics and equates a non-allowlisted AP/EUD as malicious, then it is sufficient that the classification given to the AP/EUD in step 1 is the same as in step 2. If the TOE supports automatic detection metrics and distinguishes between a non-allowlisted AP/EUD and a malicious AP/EUD, then the classification

for the AP/EUD should differ between step 1 and step 2.

- **Test 1:**

- **Step 1:** Deploy a non-allowlisted AP in the area of the WIDS sensor, but take no action against the network. Verify that the AP is classified as non-authorized.
- **Step 2:** Deploy a non-allowlisted AP in the area of the WIDS sensor and launch an attack against the network. This can be any variation of Fake AP, Spoof AP, Flood or DoS attack.
- **Step 3:** Verify that the AP is classified as malicious.

- **Test 2:**

- **Step 1:** Deploy a non-allowlisted EUD in the area of the WIDS sensor, but take no action against the network. Verify that the EUD is classified as non-authorized.
- **Step 2:** Launch an RF Flooding, DoD/DDoS, masqueraded or spoofing attack against authorized AP with an unauthorized EUD.
- **Step 3:** Verify that the EUD is classified as malicious.

- **Test 3:**

- **Step 1:** Deploy an AP with an unauthorized SSID in the area of the WIDS sensor.
- **Step 2:** Verify that the TOE detects the unauthorized SSID.

## FAU\_WID\_EXT.2 Wireless Intrusion Detection - Passive Information Flow Monitoring

### FAU\_WID\_EXT.2.1

The TSF shall [**selection:** *simultaneously, nonsimultaneously*] monitor and analyze network traffic matching the 802.11 monitoring SFP for all channels in the following RF frequencies:

- 2.4 GHz
- 5.0 GHz
- 6.0 GHz

and [**selection:**

- [**assignment:** *specified Wi-Fi channels*] in the 4.9 GHz regulatory domain,
- channels outside regulatory domain,
- non-standard channel frequencies,
- no other domains

].

**Application Note:** If "nonsimultaneously" is selected, then "Define the amount of time sensor monitors a specific channel" must be selected in [FMT\\_SMF.1/WIDS](#).

The "802.11 monitoring SFP" is a security function policy and the SFRs that reference this policy describe what the policy does. The "802.11 monitoring SFP" is established in [FDP\\_IFC.1](#) and defined through [FAU\\_WID\\_EXT.1](#), [FAU\\_WID\\_EXT.2](#), in addition to optional SFRs [FAU\\_WID\\_EXT.3](#) and [FAU\\_WID\\_EXT.4](#). A vendor does not have to formally define this policy, it only needs to comply with the SFRs.

### FAU\_WID\_EXT.2.2

The TSF shall provide wireless sensors to detect network traffic matching the 802.11 monitoring SFP that [**selection:** *can be configured to prevent transmission of data, does not transmit data*].

**Application Note:** If "can be configured to prevent transmission of data" is selected then "Enable/Disable transmission of data by wireless sensor" must be selected in [FMT\\_SMF.1/WIDS](#).

The intent of this SFR is to employ WIDS sensors that can have all wireless transmission capabilities disabled for instances where a site wishes to implement a no wireless policy.

The "802.11 monitoring SFP" is a security function policy and the SFRs that reference this policy describe what the policy does. The "802.11 monitoring SFP" is established in [FDP\\_IFC.1](#) and defined through [FAU\\_WID\\_EXT.1](#), [FAU\\_WID\\_EXT.2](#), in addition to optional SFRs [FAU\\_WID\\_EXT.3](#) and [FAU\\_WID\\_EXT.4](#). A vendor does not have to formally define this policy, it only needs to comply with the SFRs.

### FAU\_WID\_EXT.2.3

The TSF shall perform stateful frame inspection and log attacks spanning multiple frames.

**Application Note:** Attackers possess the capability to distribute an attack across multiple frames in an attempt to avoid traditional detection measures that solely focus on packet headers. Stateful frame inspection will allow for the



## Evaluation Activities ▼

### [FAU\\_WID\\_EXT.2](#)

#### **TSS**

The evaluator shall verify that the TSS includes which channels the TOE can detect and monitor. Additionally, the TSS shall include whether the TOE simultaneously or nonsimultaneously monitors network traffic across these channels. The evaluator shall verify that the TSS includes information on if the sensors are completely passive, by default, or if the sensors ability to transmit data is configurable.

#### **Guidance**

The evaluator shall review the operational guidance for how to configure the TOE to monitor the channels as selected in the SFR. If the sensor ability to transmits data is configurable, the evaluator shall review the operational guidance for how to disable wireless transmissions from the sensor. The evaluator shall verify that the operational guidance provides instructions on how to specify and confirm that stateful frame capture and inspection is being performed.

#### **Tests**

##### **Channels Monitored**

- **Test 1:** Channels on On 5GHz band
  - **Step 1:** Configure the TSF to monitor the channels as selected in the SFR.
  - **Step 2:** Deploy an AP on at least 2 different channels within the regulatory domain on 5GHz band.
  - **Step 3:** Deploy an AP on at least 2 different channels outside the regulatory domain on 5GHz band.
  - **Step 4:** Verify that the AP gets detected on each channel tested.
- **Test 2:** Channels on 2.4 GHz band
  - **Step 1:** Configure the TSF to monitor the channels as selected in the SFR.
  - **Step 2:** Deploy AP on at least 2 different channels within the regulatory domain on 2.4 GHz band.
  - **Step 3:** Deploy AP on at least 2 different channels outside the regulatory domain on 2.4 GHz band.
  - **Step 4:** Verify that the AP gets detected on each channel tested.
- **Test 3:** Channels on 4.9 GHz band (if selected)
  - **Step 1:** Configure the TSF to monitor the channels specified in the SFR.
  - **Step 2:** Deploy AP and set to channels within the 4.9 GHz band outlined in the TSS.
  - **Step 3:** Verify that the AP gets detected on each channel tested.
- **Test 4:** Channels on 6 GHz band (if selected)
  - **Step 1:** Configure the TSF to monitor the channels specified in the SFR.
  - **Step 2:** Deploy AP and set to channels within the 6 GHz band outlined in the TSS.
  - **Step 3:** Verify that the AP gets detected on each channel tested.
- **Test 5:** Non-standard channel frequencies (if selected)
  - **Step 1:** Configure the TSF to monitor the channels as selected in the SFR.
  - **Step 2:** Deploy AP on at least 2 different channels on non-standard channel frequencies.
  - **Step 3:** Verify that the AP gets detected on each channel tested.

##### **Wireless Sensor Transmission of Data**

If the TOE provides the ability to disable wireless transmission, the evaluator shall follow the operational guidance to configure the sensor to not transmit wirelessly. The evaluator shall then deploy a signal analyzer in order to check for wireless emanations from the TOE.

Repeat the two tests below, for both the 2.4 GHz, 5 GHz, and 6 GHz band.

- **Test 1:**
  - **Step 1:** Boot a sensor and using the signal analyzer observe to check if any emanations are coming from the sensor.
  - **Step 2:** Verify that the signal analyzer does not pick up emanations from the sensor.
- **Test 2:**
  - **Step 1:** During normal sensor operations, observe the analyzer for about 10 minutes to check if any emanations are coming from the sensor.
  - **Step 2:** Verify that the signal analyzer does not pick up emanations from the sensor.

##### **Stateful Frame Inspection**

- **Test 1:**
  - **Step 1:** Deploy allowlisted AP.
  - **Step 2:** Connect an allowlisted EUD to the AP.

- **Step 3:** Deploy a protocol analyzer or native capability within the WIDS Controller between the AP and EUD.
- **Step 4:** Verify from the network traffic packet capture that all frames are being inspected to validate their connection state from the TSF

## 5.2.2 User Data Protection (FDP)

### FDP\_IFC.1 Subset Information Flow Control

FDP\_IFC.1.1

The TSF shall enforce the [802.11 monitoring SFP] on [all IEEE 802.11 a, b, g, n, ac frame types and subtypes between:

- authorized APs and authorized EUDs
- authorized APs and unauthorized EUDs
- unauthorized APs and authorized EUDs].

**Application Note:** "Authorized" EUDs/APs are those that are assigned to the allowlist as defined by [FMT\\_SMF.1/WIDS](#).

The "802.11 monitoring SFP" is a security function policy and the SFRs that reference this policy describe what the policy does. The "802.11 monitoring SFP" is established in [FDP\\_IFC.1](#) and defined through [FAU\\_WID\\_EXT.1](#), [FAU\\_WID\\_EXT.2](#), in addition to optional SFRs [FAU\\_WID\\_EXT.3](#) and [FAU\\_WID\\_EXT.4](#). A vendor does not have to formally define this policy, it only needs to comply with the SFRs.

### Evaluation Activities ▼

[FDP\\_IFC.1](#)

#### TSS

There are no TSS evaluation activities for this SFR.

#### Guidance

If this functionality is configurable, the evaluator shall verify that the operational guidance provides instructions on how to configure the TOE to monitor different types of IEEE 802.11 frame types and subtypes.

#### Tests

- **Test 1:**
  - Deploy an allowlisted AP/WIDS
  - Start a traffic capture from the AP/WIDS sensor
  - Send a set number of frames to the sensor for all IEEE 802.11 a, b, g, n, ac frame types and subtypes from/to the following:
    - authorized APs and authorized EUDs
    - authorized APs and unauthorized EUDs
    - unauthorized APs and authorized EUDs
  - Verify that there are frames from all the types and subtypes in the capture.

## 5.2.3 Security Management (FMT)

### FMT\_SMF.1/WIDS Specification of Management Functions (WIDS)

FMT\_SMF.1.1/WIDS

The TSF shall be capable of performing the following management functions for WIDS functionality:

- Define an inventory of authorized APs based on [**selection:** MAC addresses, **assignment:** other unique device identifier]],
- Define an inventory of authorized EUDs based on MAC addresses,
- Define rules for monitoring and alerting on the wireless traffic,
- Define authorized SSID(s),
- Define authorized WLAN authentication schemes,
- Define authorized WLAN encryption schemes,
- [**selection:**
  - Specify periods of network activity that constitute baseline of expected behavior,
  - Define anomaly activity,
  - Define classification rules to detect rogue APs,
  - [**selection:** enable, disable] transmission of data by wireless sensor,
  - Define attack signatures,
  - Define rules for overwriting previous packet captures,

- Define the amount of time sensor monitors a specific [**selection:** frequency, channel],
- Define authorized and unauthorized TCP/IP and UDP traffic,
- Define known malicious activity ports,
- No other capabilities

].

**Application Note:** Define authorized WLAN authentication and encryption schemes does not enforce, but rather establishes a baseline to determine if an unauthorized scheme is used.

If [FAU\\_ANO\\_EXT.1](#) is included in the ST, "Specification of periods of network activity that constitute baseline of expected behavior" must be selected. If [FAU\\_ANO\\_EXT.1](#) is included in the ST and "manual configuration by administrators" is selected in [FAU\\_ANO\\_EXT.1](#), then "Definition of anomaly activity" must be selected.

If "can be configured to prevent transmission of data" is selected in [FAU\\_WID\\_EXT.2](#) then "Enable/Disable transmission of data by wireless sensor" must be selected.

It is expected that an Authorized Administrator will be responsible for configuring the AP to operate on a specific frequency pursuant to the 802.11 standard. The TSF will have the ability to adjust the amount of time it passively monitors and captures WLAN traffic on a given frequency and channel.

## Evaluation Activities ▼

### [FMT\\_SMF.1/WIDS](#)

#### **TSS**

*The evaluator shall review the TSS to verify that it includes information the ability of the TOE to define inventory of authorized APs and EUDs.*

*The evaluator shall verify that the TSS describes the ability of the TOE to allow authorized administrators to define authorized WLAN authentication schemes.*

#### **Guidance**

*The evaluator shall review the operational guidance for instructions on how to configure and change classification of APs and EUDs to indicate that they are part of the allowlist.*

*The evaluator shall review the operational guidance to determine how to configure which SSIDs are permitted on the network.*

*The evaluator shall examine the operational guidance to verify that it provides instructions on how to define a WLAN authentication scheme as authorized or unauthorized for the purposes of detection.*

*The evaluator shall examine the operational guidance to verify that it provides instructions on how to define a WLAN encryption scheme as authorized or unauthorized for the purposes of detection.*

#### **Tests**

- **Test 1:** The evaluator shall define an inventory of authorized APs and EUDs. The ability to detect allowlisted and non-allowlisted APs and EUDs will be tested in [FAU\\_INV\\_EXT.1](#) and [FAU\\_SAA.1](#).
- **Test 2:** The evaluator shall define authorized SSIDs. The ability to detect authorized and unauthorized SSIDs will be tested in [FAU\\_WID\\_EXT.2.3](#) and [FAU\\_SAA.1](#).
- **Test 3:** The evaluator shall configure the TSF with a set of allowed authentication and encryption schemes. The ability to detect violation of this policy will be tested in [FAU\\_SAA.1](#).
- **Test 4:** (conditional): If "Define the amount of time sensor monitors a specific frequency or channel" is selected:
  - **Step 1:** Deploy an allowlisted AP and connect it to the protected wired infrastructure via wire.
  - **Step 2:** Confirm that the TSF can observe and capture traffic and events generated by the AP.
  - **Step 3:** Verify that the TSF can be configured to capture traffic on a specific channel for specific interval of time, and assign a specified frequency and time interval.
  - **Step 4:** Confirm that the TSF remains on the frequency and channel for the time period specified.

The following rationale provides justification for each security objective for the TOE, showing that the SFRs are suitable to meet and achieve the security objectives:

**Table 3: SFR Rationale**

| Objective           | Addressed by  | Rationale  |
|---------------------|---|--|
| O.SYSTEM_MONITORING | FAU_GEN_EXT.1 (from Base-PP)  | FAU_GEN_EXT.1 supports the objective by requiring the TSF to identify the records of its own operation that its various components generate.   |
|                     | FAU_STG_EXT.1 (from Base-PP)  | FAU_STG_EXT.1 supports the objective by requiring the TSF to implement an external storage method for the records it generates of its own operation.   |
|                     | FAU_GEN.1/WIDS  | FAU_GEN.1/WIDS supports the objective by defining the auditable events that the TSF must implement in support of the behavior this PP-Module defines.  |
|                     | FAU_RPT_EXT.1   | FAU_RPT_EXT.1 supports the objective by requiring the TSF to implement an external import and reporting mechanism for its monitoring data to integrate with third-party components.  |
|                     | FAU_STG_EXT.1/PCAP  | FAU_STG_EXT.1/PCAP supports the objective by defining an optional reporting mechanism for monitored data.  |
|                     | FPT_FLS.1 (objective)   | FPT_FLS.1 supports the objective by ensuring that a potential sensor failure triggers the TOE to fail into a secure state which prevents undetected wireless communications.   |
| O.WIDS_ANALYZE      | FAU_ARP.1, FAU_ARP_EXT.1, FAU_IDS_EXT.1, FAU_INV_EXT.1, FAU_INV_EXT.2, FAU_INV_EXT.3, FAU_SAA.1, FAU_WID_EXT.1, FAU_WID_EXT.2, FDP_IFC.1, FAU_WID_EXT.3 (optional), FAU_WID_EXT.4 (optional), FAU_ANO_EXT.1 (selection-based), FAU_SIG_EXT.1 (selection-based), FAU_INV_EXT.4 (objective), FAU_INV_EXT.5 (objective), FAU_MAC_EXT.1 (objective) | <p>FAU_ARP.1 supports the objective by defining how the TSF must react when data consistent with an IDS violation is collected.</p> <p>FAU_ARP_EXT.1 supports the objective by defining a filtering method that the TSF may implement to suppress certain reactions.</p> <p>FAU_IDS_EXT.1 supports the objective by defining the specific IDS methods that the TSF may implement to detect potential malicious activity.</p> <p>FAU_INV_EXT.1 supports the objective by defining how the TSF takes an inventory of allowed and</p> |

disallowed devices in its operational environment.

[FAU\\_INV\\_EXT.2](#) supports the objective by requiring the TSF to collect and report on specific properties of inventoried devices.

[FAU\\_INV\\_EXT.3](#) supports the objective by requiring the TSF to implement measures that can be used to determine the physical location of inventoried devices.

[FAU\\_SAA.1](#) supports the objective by defining the specific conditions that the TSF must apply to determine if collected data is indicative of potential malicious activity.

[FAU\\_WID\\_EXT.1](#) supports the objective by requiring the TSF to implement a method to distinguish between benign and malicious devices in its operational environment.

[FAU\\_WID\\_EXT.2](#) supports the objective by requiring the TSF to implement stateful monitoring of network traffic on various RF bands.

[FDP\\_IFC.1](#) supports the objective by defining the specific network traffic that the TSF must have the ability to monitor.

[FAU\\_WID\\_EXT.3](#) supports the objective by optionally requiring the TSF to detect network devices operating on frequency bands beyond what is required by [FAU\\_WID\\_EXT.2](#).

[FAU\\_WID\\_EXT.4](#) supports the objective by optionally requiring the TOE to implement wireless spectrum analysis functionality on a dedicated sensor.

[FAU\\_ANO\\_EXT.1](#) supports the objective by defining the specific anomaly-based detection mechanisms that the TSF is required to implement if it claims to support anomaly-based detection.

[FAU\\_SIG\\_EXT.1](#) supports the objective by requiring the TSF to support user-defined and customizable attack signatures if it claims to support signature-based detection.

|  |   |  |
|--|---|--|
|  |   | <p><a href="#">FAU_INV_EXT.4</a> supports the objective by optionally requiring the TSF to detect when unauthorized wireless devices connect to a protected network over a wired interface.</p> <p><a href="#">FAU_INV_EXT.5</a> supports the objective by optionally requiring the TSF to include a signal library.</p> <p><a href="#">FAU_MAC_EXT.1</a> supports the objective by optionally requiring the TSF to detect potential device impersonation through MAC spoofing.</p>  |
| <a href="#">O.WIDS_REACT</a>             | <p><a href="#">FAU_ARP.1</a>, <a href="#">FAU_SAA.1</a>, <a href="#">FMT_SMF.1/WIDS</a>, <a href="#">FAU_ANO_EXT.1</a> (selection-based), <a href="#">FAU_WIP_EXT.1</a> (objective)</p> | <p><a href="#">FAU_ARP.1</a> supports the objective by defining how the TSF reacts when anomalous or potentially malicious traffic is detected.</p> <p><a href="#">FAU_SAA.1</a> supports the objective by defining potentially malicious traffic patterns that the TSF must detect.</p> <p><a href="#">FMT_SMF.1/WIDS</a> supports the objective by allowing administrators to define potentially malicious or anomalous behavior.</p> <p><a href="#">FAU_ANO_EXT.1</a> supports the objective by optionally requiring the TSF to detect when traffic is detected that meets a condition for anomalous behavior.</p> <p><a href="#">FAU_WIP_EXT.1</a> supports the objective by requiring the TSF to implement wireless containment as a method of enforcing wireless intrusion prevention.</p> |
| <a href="#">O.TOE_ADMINISTRATION</a>     | <p><a href="#">FMT_SMF.1/WIDS</a>, <a href="#">FPT_FLS.1</a> (objective)</p>  | <p><a href="#">FMT_SMF.1/WIDS</a> supports the objective by requiring the TSF to implement management functions that support its configuration.</p> <p><a href="#">FPT_FLS.1</a> supports the objective by ensuring that a potential compromise of the TSF triggers the TOE to fail into a secure state, which prevents unauthorized administration.</p>   |
| <a href="#">O.TRUSTED_COMMUNICATIONS</a> | <p><a href="#">FCO_CPC_EXT.1</a> (from Base-PP)</p>   | <p><a href="#">FCO_CPC_EXT.1</a> supports the objective by ensuring that distributed components are properly registered and</p>  |

|  |   |
|--|---|
|  | authenticated.  |
| <a href="#">FPT_ITT.1</a> (from Base-PP) | <a href="#">FPT_ITT.1</a> supports the objective by defining the trusted communications protocol used to secure communications between TOE components.                          |
| <a href="#">FTP_ITC.1</a> (from Base-PP) | <a href="#">FTP_ITC.1</a> supports the objective by defining the trusted communications protocol used to secure communications between the TOE and its operational environment. |

## 5.4 TOE Security Assurance Requirements

---

This PP-Module does not define any SARs beyond those defined within the Base-PP to which it can claim conformance. It is important to note that a TOE that is evaluated against this PP-Module is inherently evaluated against the NDcPP as well. This PP includes a number of EAs associated with both Security Functional Requirements (SFRs) and SARs. Additionally, this PP-Module includes a number of SFR-based EAs that similarly refine the SARs of the Base-PP. The evaluation laboratory will evaluate the TOE against the chosen Base-PP and supplement that evaluation with the necessary SFRs that are taken from this PP-Module.



# 6 Consistency Rationale

## 6.1 Collaborative Protection Profile for Network Device

### 6.1.1 Consistency of TOE Type

When this PP-Module extends the Network Device cPP, the TOE type for the overall TOE is still WIDS/WIPS products.

### 6.1.2 Consistency of Security Problem Definition

| PP-Module Threat, Assumption, OSP                        | Consistency Rationale  |
|--|--|
| <a href="#">T.UNAUTHORIZED_DISCLOSURE_OF_INFORMATION</a> | This threat is similar to the T.UNDETECTED_ACTIVITY threat in the Base-PP but it applies to the attacker performing malicious actions on the network monitored by the TOE rather than against the TOE itself.  |
| <a href="#">T.UNAUTHORIZED_ACCESS</a>                    | This threat is similar to the T.UNAUTHORIZED_ADMINISTRATOR_ACCESS threat in the Base-PP but it applies to the attacker gaining unauthorized access to an asset on the network monitored by the TOE rather than against the TOE itself.   |
| <a href="#">T.DISRUPTION</a>                             | This threat is for a denial-of-service attack against an asset on the network monitored by the TOE. The Base-PP does not define any threats for availability but there is no consistency issue here because the threat applies to an interface that doesn't exist in the Base-PP.  |
| <a href="#">A.CONNECTIONS</a>                            | This assumption defines the TOE's placement in a network such that it is able to perform its required security functionality. The Base-PP does not define any assumptions about the TOE's architectural deployment so there is no conflict here.   |
| <a href="#">A.PROPER_ADMIN</a>                           | This assumption is comparable to the A.TRUSTED_ADMINISTRATOR assumption from the Base-PP, applied to the specific administrative functions defined in this PP-Module.  |
| <a href="#">P.ANALYZE</a>                                | This organizational security policy expects the data produced by the TSF about the behavior of external entities to be used in an organization's analytical process. There is no conflict with the Base-PP because the Base-PP does not define any functionality for the TOE to produce data about any entities other than itself. |

### 6.1.3 Consistency of Objectives

The objectives for the TOEs are consistent with the NDcPP based on the following rationale:

| PP-Module TOE Objective              | Consistency Rationale   |
|--------------------------------------|---|
| <a href="#">O.SYSTEM_MONITORING</a>  | The Base-PP does not define any TOE objectives. However, it does define requirements for the collection and secure remote transmission of audit data. The PP-Module adds requirements for the similar handling of network traffic data.   |
| <a href="#">O.WIDS_ANALYZE</a>       | This objective refers to behavior on wireless interfaces that are beyond the original scope of the Base-PP.   |
| <a href="#">O.WIDS_REACT</a>         | This objective refers to behavior on wireless interfaces that are beyond the original scope of the Base-PP.   |
| <a href="#">O.TOE_ADMINISTRATION</a> | The Base-PP does not define any TOE objectives. However, it does define requirements for the execution of security-relevant management functions. The PP-Module expands upon this by adding requirements for the security-relevant management functions that are introduced by the PP-Module. |



|                                  |  |
|----------------------------------|--|
| <b>OE.TRUSTED_COMMUNICATIONS</b> | The Base-PP does not define any TOE objectives. However, it clearly intends to ensure that communications are trusted because the SFRs the PP-Module uses to demonstrate this objective is satisfied are derived from the Base-PP. |
|----------------------------------|--|

The objectives for the TOE's OE are consistent with the NDcPP based on the following rationale:

| <b>PP-Module OE Objective</b> | <b>Consistency Rationale</b>  |
|-------------------------------|---|
| <b>OE.CONNECTIONS</b>         | This objective expects the TOE to be placed in a network such that it is able to perform its required security functionality. The Base-PP does not define any objectives about the TOE's architectural deployment so there is no conflict here. |
| <b>OE.PROPER_ADMIN</b>        | This objective is comparable to the OE.TRUSTED_ADMIN objective from the Base-PP, applied to the specific administrative functions defined in this PP-Module.  |

#### 6.1.4 Consistency of Requirements

This PP-Module identifies several SFRs from the NDcPP that are needed to support Wireless Intrusion Detection/Prevention Systems (WIDS/WIPS) functionality. This is considered to be consistent because the functionality provided by the NDcPP is being used for its intended purpose. The PP-Module also identifies a number of modified SFRs from the NDcPP that are used entirely to provide functionality for Wireless Intrusion Detection/Prevention Systems (WIDS/WIPS). The rationale for why this does not conflict with the claims defined by the NDcPP are as follows:

| <b>PP-Module Requirement</b> | <b>Consistency Rationale</b>   |
|------------------------------|--|
| <b>Modified SFRs</b>         |  |
| <b>FAU_GEN_EXT.1</b>         | This PP-Module mandates the inclusion of this selection-based SFR because a TOE that conforms to this PP-Module will always be deployed in a configuration that requires this SFR to be claimed. |
| <b>FAU_STG_EXT.1</b>         | This PP-Module modifies the Base-PP SFR to remove a selection that is not permitted by the TOE architecture that it specifies.   |
| <b>FCO_CPC_EXT.1</b>         | This PP-Module mandates the inclusion of this optional SFR because it is required to implement functionality required by this PP-Module.   |
| <b>FPT_ITT.1</b>             | This PP-Module mandates the inclusion of this optional SFR because it is required to implement functionality required by this PP-Module.   |
| <b>FTP_ITC.1</b>             | This PP-Module refines the Base-PP SFR to add a selection for a specific external entity that may be applicable to a TOE that conforms to this PP-Module.  |

#### **Additional SFRs**

This PP-Module does not add any requirements when the NDcPP is the base.

#### **Mandatory SFRs**

|                       |   |
|-----------------------|---|
| <b>FAU_ARP.1</b>      | This SFR defines operations to be performed on collected WIDS data, which is collected using an external interface defined in this PP-Module that extends the logical scope of the TOE beyond what the Base-PP defines. |
| <b>FAU_ARP_EXT.1</b>  | This SFR defines operations to be performed on collected WIDS data, which is collected using an external interface defined in this PP-Module that extends the logical scope of the TOE beyond what the Base-PP defines. |
| <b>FAU_GEN.1/WIDS</b> | This SFR iterates the FAU_GEN.1 SFR defined in the Base-PP to define auditable events for the functionality that is specific to this PP-Module.   |
| <b>FAU_IDS_EXT.1</b>  | This SFR defines operations to be performed on collected WIDS data, which is collected using an external interface defined in this PP-Module that extends the logical scope of the TOE beyond what the Base-PP defines. |
| <b>FAU_INV_EXT.1</b>  | This SFR defines operations to be performed on assets in the TOE's operational environment, which is behavior defined in this PP-Module that extends the logical scope of the TOE beyond what the Base-PP defines.      |
| <b>FAU_INV_EXT.2</b>  | This SFR defines operations to be performed on assets in the TOE's operational environment, which is behavior defined in this PP-Module that extends the logical scope of the TOE beyond what the Base-PP defines.      |

|   |   |
|---|---|
| FAU_INV_EXT.3   | This SFR defines operations to be performed on assets in the TOE's operational environment, which is behavior defined in this PP-Module that extends the logical scope of the TOE beyond what the Base-PP defines.  |
| FAU_RPT_EXT.1   | This SFR defines operations to be performed on collected WIDS data, which is collected using an external interface defined in this PP-Module that extends the logical scope of the TOE beyond what the Base-PP defines.   |
| FAU_SAA.1   | This SFR defines operations to be performed on collected WIDS data, which is collected using an external interface defined in this PP-Module that extends the logical scope of the TOE beyond what the Base-PP defines.   |
| FAU_WID_EXT.1   | This SFR defines operations to be performed on assets in the TOE's operational environment, which is behavior defined in this PP-Module that extends the logical scope of the TOE beyond what the Base-PP defines.  |
| FAU_WID_EXT.2   | This SFR defines operations to be performed on assets in the TOE's operational environment, which is behavior defined in this PP-Module that extends the logical scope of the TOE beyond what the Base-PP defines.  |
| FDP_IFC.1   | This SFR defines operations to be performed on assets in the TOE's operational environment, which is behavior defined in this PP-Module that extends the logical scope of the TOE beyond what the Base-PP defines.  |
| FMT_SMF.1/WIDS  | This SFR iterates the FMT_SMF.1 SFR defined in the Base-PP to define management functions for the functionality that is specific to this PP-Module.   |
| <b>Optional SFRs</b>  |   |
| FAU_WID_EXT.3   | This SFR defines operations to be performed on assets in the TOE's operational environment, which is behavior defined in this PP-Module that extends the logical scope of the TOE beyond what the Base-PP defines.  |
| FAU_WID_EXT.4   | This SFR defines an optional capability for a distributed component to be dedicated to one particular function. This function (wireless spectrum analysis) is defined in this PP-Module that extends the logical scope of the TOE beyond what the Base-PP defines.  |
| <b>Selection-based SFRs</b>   |   |
| FAU_ANO_EXT.1   | This SFR defines operations to be performed on collected WIDS data, which is collected using an external interface defined in this PP-Module that extends the logical scope of the TOE beyond what the Base-PP defines.   |
| FAU_SIG_EXT.1   | This SFR defines operations to be performed on collected WIDS data, which is collected using an external interface defined in this PP-Module that extends the logical scope of the TOE beyond what the Base-PP defines.   |
| FAU_STG_EXT.1/PCAP  | This SFR iterates the FAU_STG_EXT.1 SFR defined in the Base-PP for storage of audit data and applies it to storage of packet captures.  |
| <b>Objective SFRs</b>   |   |
| FAU_INV_EXT.4   | This SFR defines operations to be performed on assets in the TOE's operational environment, which is behavior defined in this PP-Module that extends the logical scope of the TOE beyond what the Base-PP defines.  |
| FAU_INV_EXT.5   | This SFR defines operations to be performed on assets in the TOE's operational environment, which is behavior defined in this PP-Module that extends the logical scope of the TOE beyond what the Base-PP defines.  |
| FAU_MAC_EXT.1   | This SFR defines operations to be performed on assets in the TOE's operational environment, which is behavior defined in this PP-Module that extends the logical scope of the TOE beyond what the Base-PP defines.  |
| FAU_WIP_EXT.1   | This SFR defines WIPS behavior in response to detection of potential malicious activity in the TOE's operational environment. This extends the logical scope of the TOE beyond what the Base-PP defines.  |
| FPT_FLS.1   | This SFR defines preservation of a secure state in the event that a failure condition is detected. The Base-PP does not define an SFR for this behavior but this SFR mitigates the T.SECURITY_FUNCTIONALITY_FAILURE threat defined in the Base-PP, so it is clear that this behavior is consistent with the security expectations of the Base-PP. |
| <b>Implementation-based SFRs</b>                                      |   |
| This PP-Module does not define any Implementation-based requirements. |   |



# Appendix A - Optional SFRs

## A.1 Strictly Optional Requirements

### A.1.1 Security Audit (FAU)

#### FAU\_WID\_EXT.3 Wireless Intrusion Detection - Non-Wireless Spectrum Monitoring

FAU\_WID\_EXT.3.1

The TSF shall detect the presence of network devices that operate in the following RF bands: [**selection:** 3.6 GHz, 60 GHz, sub-GHz (0-900 MHz), all cellular bands].

**Application Note:** This SFR refers to Non-WLAN (IEEE 802.11 a, b, g, n, and ac) network devices that operate in the specified frequencies. There is an understanding that this capability requires a TOE to use specialized, licensed radio systems. This SFR will allow for the introduction of an open API, set of defined interoperability standards, or other proprietary solution(s), to allow for third-party integrations.

#### Evaluation Activities ▼

[FAU\\_WID\\_EXT.3](#)

**TSS**

The evaluator shall verify that the TSS includes the set of RF bands and technologies that the TSF can detect the use of. The TSS should also include instructions on how to enable and the hardware that is necessary for the additional band detection.

**Guidance**

The evaluator shall verify that the operational guidance describes how to enable and configure detection of the technologies included in the ST as well as the hardware that is needed to perform this function.

**Tests**

The evaluator shall enable and configure detection of the selected technologies.

- **Test 1:** Deploy a device within the given technology and verify that the TSF detects the device.

#### FAU\_WID\_EXT.4 Wireless Intrusion Detection - Wireless Spectrum Analysis

FAU\_WID\_EXT.4.1

The TSF shall provide a dedicated sensor for wireless spectrum analysis.

#### Evaluation Activities ▼

[FAU\\_WID\\_EXT.4](#)

**TSS**

The evaluator shall verify that the TSS to verify that the TOE provides a dedicated sensor for wireless spectrum analysis.

**Guidance**

The evaluator shall verify that the operational guidance describes how to enable and configure dedicated spectrum analysis as well as the hardware that is needed to perform this function.

**Tests**

The evaluator shall enable and configure dedicated spectrum analysis and test the capabilities listed in the TSS.

## A.2 Objective Requirements

### A.2.1 Security Audit (FAU)

#### FAU\_INV\_EXT.4 Detection of Unauthorized Connections

FAU\_INV\_EXT.4.1

The TSF shall detect when non-allowlisted APs have a wired connection to the internal corporate network.

## Evaluation Activities ▼

### [FAU\\_INV\\_EXT.4](#)

#### **TSS**

*The evaluator shall verify that the TSS includes guidance on whether the TSF has the capability of detecting APs connecting to the protected wired network infrastructure. If the capability is present the TSS shall include configuration guidance for this feature.*

#### **Guidance**

*The evaluator shall review the operational guidance for instructions on how to configure the WIDS to detect unauthorized APs connected to the protected wired infrastructure.*

#### **Tests**

- **Test 1:**
  - **Step 1:** Deploy a non-allowlisted AP.
  - **Step 2:** Connect the AP via wire to the protected network infrastructure.
  - **Step 3:** Check the WIDS user interface for a list of detected APs and EUDs.
  - **Step 4:** Verify that the rogue AP is detected and an alert generated on the detection of an AP connected to the protected wired infrastructure.

### **FAU\_INV\_EXT.5 Signal Library**

#### FAU\_INV\_EXT.5.1

The TSF shall include a signal library.

**Application Note:** The TSF will need to have the ability to import, export, or update the existing signal library.

## Evaluation Activities ▼

### [FAU\\_INV\\_EXT.5](#)

#### **TSS**

*There are no TSS evaluation activities for this SFR.*

#### **Guidance**

*The evaluator shall review the operational guidance for instructions on how to locate and verify that the WIDS comes preloaded with a signal library, as well as possesses the ability to import, export, and update the existing signal library if present.*

#### **Tests**

*Depending on operation guidance provided for the TOE, the evaluator shall confirm and note the existence of the signal library, and test for the ability to import, export, and update the signal library.*

- **Test 1:**
  - **Step 1:** Deploy an allowlisted AP and connect it to the protected wired infrastructure via wire.
  - **Step 2:** Confirm and note whether the TSF has an existing signal library.
  - **Step 3:** If existence is confirmed, verify that the TSF can import, export, and update the existing signal library.

### **FAU\_MAC\_EXT.1 Device Impersonation**

#### FAU\_MAC\_EXT.1.1

The TSF shall detect when two sensors in non-overlapping locations receive traffic from the same MAC address simultaneously.

**Application Note:** The intent of this SFR is to detect MAC spoofing where an attacker is able to cause the allowlisted EUD to disconnect and promptly connects a non-allowlisted device using the MAC address of the allowlisted EUD.

#### FAU\_MAC\_EXT.1.2

The TSF shall detect when two sensors in non-overlapping locations receive traffic from the MAC addresses of non-allowlisted EUDs within an Authorized administrator-configurable timeframe based on distance between sensors.

**Application Note:** The intent of this SFR is to allow the administrator to determine the time that should be allowed between an allowlisted EUD connecting in two distant locations.

### FAU\_MAC\_EXT.1

#### TSS

The evaluator shall verify that the TSS describes the behavior of the TOE when two sensors in non-overlapping locations receive traffic from the same MAC address simultaneously.

#### Guidance

The evaluator shall verify that the operational guidance provides instructions on how to deploy the TOE in a manner that allows the TSF to detect when two sensors in non-overlapping locations receive traffic from the same MAC address simultaneously (i.e. information about the range and placement of sensors to ensure non-overlapping coverage).

The evaluator shall verify that the operational guidance provides instructions on how to configure the timeframe that should be allowed between two subsequent attempts for an EUD to connect from two separate locations.

#### Tests

##### • Test 1:

- **Step 1:** Setup an allowlisted AP (Location 1).
- **Step 2:** Connect an allowlisted EUD to AP.
- **Step 3:** Setup a second allowlisted AP and a non-allowlisted EUD in a separate non-overlapping location where the WIDS also has sensors. Or simulate the distant non-overlapping locations by deploying the second AP in a shielded environment connected to the valid network (Location 2).
- **Step 4:** Spoof the MAC address of the EUD in location 1 with the EUD in location 2 and connect it to the allowlisted AP in location 2. Make sure both EUDs are connected at the same time.
- **Step 5:** Verify that the TSF detected and generated an alert.

##### • Test 2:

- **Step 1:** Configure the timeframe allowed between connection of two EUDs in two separate locations (Location 1, Location 2).
- **Step 2:** Setup an allowlisted AP (Location 1).
- **Step 3:** Connect an allowlisted EUD to AP.
- **Step 4:** Setup a second allowlisted AP and a non-allowlisted EUD in a separate non-overlapping location where the WIDS also has sensors. Or simulate the distant non-overlapping locations by deploying the second AP in a shielded environment connected to the valid network (Location 2).
- **Step 5:** Spoof the MAC address of the EUD in location 1 with the EUD in location 2 and connect it to the allowlisted AP in location 2. Make sure that the time between connections is shorter than the time timeframe allowed/configured.
- **Step 6:** Verify that the TSF detected and generated an alert.

## FAU\_WIP\_EXT.1 Wireless Intrusion Prevention

### FAU\_WIP\_EXT.1.1

The TSF shall allow an Authorized Administrator to isolate a wireless AP or EUD from the network monitored by the TSF using the following methods: [**selection:** wireless containment, wire-side containment of an unauthorized AP connected to the internal corporate wired network].

**Application Note:** It is expected that an Authorized Administrator will be responsible for confirming the AP or EUD as a rogue AP or EUD to initiate wireless containment.

In this SFR the containment of an unauthorized AP connected to the internal corporate wired network refers to an unauthorized AP that is physically connected (via wire) to the protected internal wired infrastructure.

### FAU\_WIP\_EXT.1

#### TSS

The evaluator shall verify that the TSS includes a list of available containment methods on the TSF and how to configure them.

#### Guidance

There are no operational guidance activities for this SFR.

#### Tests

Configure the containment methods available on the TSF and perform the following test for each

method.

- **Test 1:**

- **Step 1:** Deploy a non-allowlisted AP and connect to the protected wired infrastructure via wire (make sure it gets classified as rogue, or manually classify as such).
- **Step 2:** Connect an allowlisted EUD to the AP.
- **Step 3:** Verify that TSF generates an alert, breaks the connection of the allowlisted EUD from the rogue AP, and contains the rogue AP.

## A.2.2 Protection of the TSF (FPT)

### FPT\_FLS.1 Basic Internal TSF Data Transfer Protection

FPT\_FLS.1.1

The TSF shall preserve a secure state when the following types of failures occur: [sensor functionality failure, potential compromise of the TSF].

**Application Note:** At minimum, the preservation of a secure state requires the generation of audit records when the defined failure conditions occur.

### Evaluation Activities ▼

[FPT\\_FLS.1](#)

#### **TSS**

The evaluator shall review the TSS section to determine that the TOE's implementation of the fail secure functionality is documented. The evaluator shall examine the TSS section to ensure that all failure modes specified in the ST are described.

#### **Guidance**

The evaluator shall review the operational guidance to verify that it identifies the potential TOE failures, how the TSF preserves a secure state following these failures, and any actions that are required to restore the TOE to normal operation following the transition to a failure state.

#### **Tests**

- **Test 1:** For each failure mode specified in the ST, the evaluator shall ensure that the TOE attains a secure state after initiating each failure mode type.

## A.3 Implementation-dependent Requirements

This PP-Module does not define any Implementation-dependent SFRs.



# Appendix B - Selection-based Requirements

## B.1 Security Audit (FAU)

### FAU\_ANO\_EXT.1 Anomaly-Based Intrusion Detection

*The inclusion of this selection-based component depends upon selection in [FAU\\_IDS\\_EXT.1.1](#).*

FAU\_ANO\_EXT.1.1

The TSF shall support the definition of [**selection:** *baselines ('expected and approved'), anomaly ('unexpected') traffic patterns*] including the specification of [**selection:**

- *throughput (data elements (e.g. bytes, packets, etc.) per time period (e.g. minutes, hours, days)),*
- *time of day,*
- *frequency,*
- *thresholds,*
- [**assignment:** *other methods*]

] and the following network protocol fields:

- all management and control frame header elements.

FAU\_ANO\_EXT.1.2

The TSF shall support the definition of anomaly activity through [**selection:** *manual configuration by administrators, automated configuration*].

**Application Note:** The "baseline" and "anomaly" can be something manually defined/configured by a TOE administrator (or importing definitions), or something that the TOE is able to automatically define/create by inspecting network traffic over a period of time (a.k.a. "profiling").

### Evaluation Activities ▼

[FAU\\_ANO\\_EXT.1](#)

**TSS**

*The evaluator shall verify that the TSS describes the composition and construction of baselines or anomaly-based attributes specified in the SFR. The evaluator shall verify that the TSS provides a description of how baselines are defined and implemented by the TSF, or a description of how anomaly-based rules are defined and configured by the administrator.*

*The evaluator shall verify that the TSS describes the available modes of configuration (manual or automatic) and how to configure or import the baseline.*

**Guidance**

*The evaluator shall verify that the operational guidance describes how to configure baseline and/or anomalous traffic patterns based on what is stated in the TSS.*

*The evaluator shall verify that the operational guidance describes how to perform automatic and/or manual definition of anomaly activity based on what is selected in the ST.*

**Tests**

*The evaluator shall use the instructions in the operational guidance to configure baselines or anomaly-based rules through automated and/or manual means based on what is selected in the ST. The evaluator shall send traffic that does not match the baseline or matches the anomaly-based rule and verify the TSF detects the anomalous behavior and generates an alert.*

### FAU\_SIG\_EXT.1 Signature-Based Intrusion Detection

*The inclusion of this selection-based component depends upon selection in [FAU\\_IDS\\_EXT.1.1](#).*

FAU\_SIG\_EXT.1.1

The TSF shall support user-defined and customizable attack signatures.

### Evaluation Activities ▼



#### [FAU\\_SIG\\_EXT.1](#)

##### **TSS**

*The evaluator shall verify that the TSS describes the user-defined and customizable attack signatures that the TOE can define.*

##### **Guidance**

*The evaluator shall verify that the operational guidance provides information on how to configure user-defined and customizable attack signatures, including a description of the customization options that are available.*

##### **Tests**

- **Test 1:**
  - **Step 1:** Craft a signature with the available fields indicated in the TSS.
  - **Step 2:** Send a crafted frame that matches the signature to an allowlisted EUD
  - **Step 3:** Verify that the TSF triggers an alert based on the newly defined signature.

#### **FAU\_STG\_EXT.1/PCAP Protected Audit Event Storage (Packet Captures)**

*The inclusion of this selection-based component depends upon selection in [FAU\\_ARP.1.1](#).*

##### FAU\_STG\_EXT.1.1/PCAP

The TSF shall be able to transmit the generated **packet captures** to an external IT entity **hosting a protocol analyzer** using a trusted channel according to [FTP\\_ITC.1](#).

**Application Note:** Per [FAU\\_STG\\_EXT.1](#) in the Base-PP, the TOE must support transfer of the audit data to an external IT entity using a trusted channel per [FTP\\_ITC.1](#). Note that this PP-Module modifies [FTP\\_ITC.1](#) from the Base-PP. If "capture raw frame traffic that triggers the violation" is selected in [FAU\\_ARP.1](#), then this SFR must be included in the ST, and this iteration is for the PCAPs generated as a selectable action completed upon detection of a potential security violation in [FAU\\_ARP.1](#).

##### FAU\_STG\_EXT.1.2/PCAP

The TSF shall be able to store generated **packet captures** on the TOE itself. In addition [**selection:**

- The TOE shall be a distributed TOE that stores **packet capture** data on the following TOE components: [**assignment:** identification of TOE components],
- The TOE shall be a distributed TOE with storage of **packet capture** data provided externally for the following TOE components: [**assignment:** list of TOE components that do not store packet capture data locally and the other TOE components to which they transmit their generated packet capture data]

].

##### FAU\_STG\_EXT.1.3/PCAP

The TSF shall [**selection:** drop new **packet capture** data, overwrite previous **packet captures** according to the following rule: [**assignment:** rule for overwriting previous packet captures], [**assignment:** other action]] when the local storage space for **packet capture** data is full.

#### **Evaluation Activities** ▼

##### [FAU\\_STG\\_EXT.1/PCAP](#)

##### **TSS**

*The evaluator shall verify that the TSS includes the list of trusted channels (as specified in [FTP\\_ITC.1](#)) available in the TSF to transmit packet captures to an external entity. The evaluator shall verify that the TSS describes the ability of the TOE to store packet capture data within itself, how much storage space is available for packet capture data and where that data is stored. The evaluator shall verify that the TSS describes the behavior of the TOE when local storage space for packet capture data is exhausted and whether this behavior is configurable.*

##### **Guidance**

*The evaluator shall verify that the operational guidance provides instructions on how to configure the trusted channel. If the behavior of the TOE when local storage space for packet capture data is exhausted is configurable, the evaluator shall verify that the operational guidance provides information on what the configurable behaviors are and how they can be set.*

##### **Tests**

- **Test 1:** The evaluator shall configure packet captures according to the guidance specified. The evaluator shall then trigger an event that starts a capture and verify through the tests in [FTP ITC.1](#) that the captured traffic being sent to the external device is being sent through a trusted channel.
- **Test 2:** The evaluator shall configure packet captures to be stored on the TSF according to the guidance specified. The evaluator shall then trigger an event that starts a capture and verify that the packet capture was stored on the TSF.
- **Test 3:** The evaluator shall define packet data retention and deletion rules on the TSF according to the guidance specified and test the functionality of the specified rules.

# Appendix C - Extended Component Definitions

This appendix contains the definitions for all extended requirements specified in the Module.

## C.1 Extended Components Table

All extended components specified in the Module are listed in this table:

| Table 4: Extended Component Definitions |  |
|---|--|
| Functional Class                        | Functional Components  |
| Security Audit (FAU)                    | FAU_ANO_EXT Anomaly-Based Intrusion Detection<br>FAU_ARP_EXT Security Alarm Filtering<br>FAU_IDS_EXT Intrusion Detection Methods<br>FAU_INV_EXT Environmental Inventory<br>FAU_MAC_EXT Device Impersonation<br>FAU_RPT_EXT Reporting Methods<br>FAU_SIG_EXT Signature-Based Intrusion Detection<br>FAU_WID_EXT Wireless Intrusion Detection<br>FAU_WIP_EXT Wireless Intrusion Prevention |

## C.2 Extended Component Definitions

### C.2.1 Security Audit (FAU)


This Module defines the following extended components as part of the FAU class originally defined by CC Part 2:

#### C.2.1.1 FAU\_ARP\_EXT Security Alarm Filtering

##### Family Behavior

This family defines requirements for suppression of audit events. It is intended to complement the FAU\_ARP family already defined in CC Part 2.

##### Component Leveling



[FAU\\_ARP\\_EXT.1](#), Security Alarm Filtering, requires the TSF to implement a filtering mechanism to selectively suppress the generation of security alarms.

##### Management: FAU\_ARP\_EXT.1

No specific management functions have been identified.

##### Audit: FAU\_ARP\_EXT.1

There are no auditable events foreseen.

##### FAU\_ARP\_EXT.1 Security Alarm Filtering

- Hierarchical to: No other components.
- Dependencies to: [FAU\\_ARP.1](#) Security Alarms

##### FAU\_ARP\_EXT.1.1


The TSF shall provide the ability to apply [**assignment:** *methods of selection*] to selectively exclude alerts from being generated.

#### C.2.1.2 FAU\_IDS\_EXT Intrusion Detection Methods

##### Family Behavior

This family defines requirements for supported methods of intrusion detection.

##### Component Leveling



[FAU\\_IDS\\_EXT.1](#), Intrusion Detection System - Intrusion Detection Methods, requires the TSF to specify the methods of intrusion detection that it supports.

### Management: FAU\_IDS\_EXT.1

No specific management functions are identified.

### Audit: FAU\_IDS\_EXT.1

There are no auditable events foreseen.

### FAU\_IDS\_EXT.1 Intrusion Detection System - Intrusion Detection Methods

Hierarchical to: No other components.

Dependencies to: No dependencies.

#### FAU\_IDS\_EXT.1.1


The TSF shall detect intrusions using [assignment: *detection strategies*] methods.

## C.2.1.3 FAU\_INV\_EXT Environmental Inventory

### Family Behavior

This family defines requirements for detection and inventorying of network assets in the TOE's operational environment.

### Component Leveling



[FAU\\_INV\\_EXT.1](#), Environmental Inventory, requires the TSF to determine if inventoried objects are authorized or unauthorized.

[FAU\\_INV\\_EXT.2](#), Characteristics of Environmental Objects, requires the TSF to discover network assets in its operational environment and maintain an inventory of them based on collected attributes.

[FAU\\_INV\\_EXT.3](#), Location of Environmental Objects, requires the TSF to approximate the physical location of network assets in its operational environment based on triangulation of wireless emissions.

[FAU\\_INV\\_EXT.4](#), Detection of Unauthorized Connections, requires the TSF to identify if an unauthorized network asset in its inventory is attempting to access a protected network using a wired connection.

[FAU\\_INV\\_EXT.5](#), Signal Library, requires the TSF to maintain a signal library.

### Management: FAU\_INV\_EXT.1

The following actions could be considered for the management functions in FMT:

- Definition of inventory of authorized APs based on MAC address
- Definition of inventory of authorized EUDs based on MAC address

### Audit: FAU\_INV\_EXT.1

The following actions should be auditable if FAU\_GEN Security Audit Data Generation is included in the PP/ST:

- Presence of allowlisted device

### FAU\_INV\_EXT.1 Environmental Inventory

Hierarchical to: No other components.

Dependencies to: [FAU\\_INV\\_EXT.2](#) Characteristics of Environmental Objects

#### FAU\_INV\_EXT.1.1

The TSF shall determine if a given AP is authorized based on [selection: *MAC addresses*, [assignment: *other unique device identifier*]]

#### FAU\_INV\_EXT.1.2

The TSF shall determine if a given EUD is authorized based on [selection: *MAC addresses*, [assignment: *other unique device identifier*]]

#### FAU\_INV\_EXT.1.3

The TSF shall detect the presence of non-allowlisted EUDs and APs in the Operational Environment.

## **Management: FAU\_INV\_EXT.2**

The following actions could be considered for the management functions in FMT:

- Definition of classification rules to detect rogue APs

## **Audit: FAU\_INV\_EXT.2**

There are no auditable events foreseen.

### **FAU\_INV\_EXT.2 Characteristics of Environmental Objects**

Hierarchical to: No other components.

Dependencies to: No dependencies.

#### **FAU\_INV\_EXT.2.1**

The TSF shall detect the

- Current RF band
- Current channel
- MAC Address
- Received signal strength
- Device detection timestamps
- Classification of APs and EUDs
- [**selection:** *[assignment: other details], no other details*]

of all APs and EUDs within range of the TOE's wireless sensors.

#### **FAU\_INV\_EXT.2.2**

The TSF shall detect the following additional details for all APs within range of the TOE's wireless sensors:

- encryption
- number of connected EUDs.
- Received frames/packets
- Beacon rate
- SSID of AP (if not hidden).

#### **FAU\_INV\_EXT.2.3**

The TSF shall detect the follow additional details for all EUDs within range of the TOE's wireless sensors:

- SSID and BSSID of AP it is connected to.
- DHCP configuration.

## **Management: FAU\_INV\_EXT.3**

No specific management functions are identified.

## **Audit: FAU\_INV\_EXT.3**

The following actions should be auditable if FAU\_GEN Security Audit Data Generation is included in the PP/ST:

- Physical location and identification of AP or EUD

### **FAU\_INV\_EXT.3 Location of Environmental Objects**

Hierarchical to: No other components.

Dependencies to: [FAU\\_INV\\_EXT.2](#) Characteristics of Environmental Objects

#### **FAU\_INV\_EXT.3.1**

The TSF shall detect the physical location of APs and EUDs to within [**assignment:** *value equal or less than 25*] feet of their actual location.

#### **FAU\_INV\_EXT.3.2**

The TSF shall detect received signal strength and [**selection:** *RF power levels above a predetermined threshold, no other characteristics*] of hardware operating within range of the TOE's wireless sensors.

## **Management: FAU\_INV\_EXT.4**

No specific management functions are identified.

## **Audit: FAU\_INV\_EXT.4**

There are no auditable events foreseen.

## FAU\_INV\_EXT.4 Detection of Unauthorized Connections

Hierarchical to: No other components.

Dependencies to: [FAU\\_INV\\_EXT.1](#) Environmental Inventory

### FAU\_INV\_EXT.4.1

The TSF shall detect when non-allowlisted APs have a wired connection to the internal corporate network.

## Management: FAU\_INV\_EXT.5

No specific management functions are identified.

## Audit: FAU\_INV\_EXT.5

There are no auditable events foreseen.

## FAU\_INV\_EXT.5 Signal Library

Hierarchical to: No other components.

Dependencies to: No dependencies.

### FAU\_INV\_EXT.5.1

The TSF shall include a signal library.

## C.2.1.4 FAU\_RPT\_EXT Reporting Methods

### Family Behavior

This family defines requirements for the format of generated reports.

### Component Leveling

FAU\_RPT\_EXT ———— [1]

[FAU\\_RPT\\_EXT.1](#), Intrusion Detection System - Reporting Methods, requires the TSF to implement a specified reporting mechanism for collected data for compatibility with third parties that may consume this data.

## Management: FAU\_RPT\_EXT.1

No specific management functions are identified.

## Audit: FAU\_RPT\_EXT.1

There are no auditable events foreseen.

## FAU\_RPT\_EXT.1 Intrusion Detection System - Reporting Methods

Hierarchical to: No other components.

Dependencies to: FAU\_GEN.1 Audit Data Generation

### FAU\_RPT\_EXT.1.1

The TSF shall provide [**selection:**

- Syslog using [**selection:** defined API, Syslog, [**assignment:** other detection method]],
- SNMP trap reporting using [**selection:** defined API, Simple Network Management Protocol (SNMP), [**assignment:** other detection method]]

] for reporting of collected data.

### FAU\_RPT\_EXT.1.2

The TSF shall provide the ability to import data, such as an allowlist of APs and EUDs, and WIDS/WIPS configuration files from the system using [**selection:** custom API, Syslog, common log format, CSV, [**assignment:** vendor detection method]].

## C.2.1.5 FAU\_WID\_EXT Wireless Intrusion Detection

### Family Behavior

This family defines requirements for data collection of potentially malicious wireless network activity.

### Component Leveling



[FAU\\_WID\\_EXT.1](#), Wireless Intrusion Detection - Malicious Environmental Objects, requires the TSF to implement a mechanism to distinguish between authorized and unauthorized network assets.

[FAU\\_WID\\_EXT.2](#), Wireless Intrusion Detection - Passive Information Flow Monitoring, requires the TSF to surveil certain wireless frequency bands and perform stateful inspection of traffic on them.

[FAU\\_WID\\_EXT.3](#), Wireless Intrusion Detection - Non-Wireless Spectrum Monitoring, requires the TSF to surveil certain radio frequency bands that fall outside the typical wireless spectrum used by consumer-grade electronics.

[FAU\\_WID\\_EXT.4](#), Wireless Intrusion Detection - Wireless Spectrum Analysis, requires the TSF to implement wireless spectrum analysis in a dedicated physical component.

### Management: FAU\_WID\_EXT.1

The following actions could be considered for the management functions in FMT:

- Definition of authorized SSID(s)
- Definition of authorized WLAN authentication schemes
- Definition of authorized WLAN encryption schemes
- Definition of authorized WLAN traffic schemes

### Audit: FAU\_WID\_EXT.1

The following actions should be auditable if FAU\_GEN Security Audit Data Generation is included in the PP/ST:

- Detection of rogue AP or EUD
- Detection of unauthorized SSID

### FAU\_WID\_EXT.1 Wireless Intrusion Detection - Malicious Environmental Objects

Hierarchical to: No other components.

Dependencies to: [FAU\\_INV\\_EXT.1](#) Environmental Inventory

#### FAU\_WID\_EXT.1.1

The TSF shall distinguish between benign and malicious APs and EUDs based on if the APs and EUDs are authorized and [**selection:** *automatic detection metrics, no other method*].

#### FAU\_WID\_EXT.1.2

The TSF shall provide the ability to determine if a given SSID is authorized.

### Management: FAU\_WID\_EXT.2

The following actions could be considered for the management functions in FMT:

- Definition of authorized and unauthorized TCP/IP and UDP traffic
- Definition of known malicious activity ports
- Definition of the amount of time that a sensor monitors a specific frequency or channel

### Audit: FAU\_WID\_EXT.2

The following actions should be auditable if FAU\_GEN Security Audit Data Generation is included in the PP/ST:

- Sensor wireless transmission capabilities

### FAU\_WID\_EXT.2 Wireless Intrusion Detection - Passive Information Flow Monitoring

Hierarchical to: No other components.

Dependencies to: No dependencies.

#### FAU\_WID\_EXT.2.1

The TSF shall [**selection:** *simultaneously, nonsimultaneously*] monitor and analyze network traffic matching the 802.11 monitoring SFP for all channels in the following RF frequencies:

- 2.4 GHz
- 5.0 GHz
- 6.0 GHz

and [**selection:**

- [**assignment:** *specified Wi-Fi channels*] in the 4.9 GHz regulatory domain,



- *channels outside regulatory domain,*
- *non-standard channel frequencies,*
- *no other domains*

].

#### **FAU\_WID\_EXT.2.2**

The TSF shall provide wireless sensors to detect network traffic matching the 802.11 monitoring SFP that [selection: *can be configured to prevent transmission of data, does not transmit data*].

#### **FAU\_WID\_EXT.2.3**

The TSF shall perform stateful frame inspection and log attacks spanning multiple frames.

#### **Management: FAU\_WID\_EXT.3**

No specific management functions are identified.

#### **Audit: FAU\_WID\_EXT.3**

The following actions should be auditable if FAU\_GEN Security Audit Data Generation is included in the PP/ST:

- Detection of network devices operating in selected RF bands

#### **FAU\_WID\_EXT.3 Wireless Intrusion Detection - Non-Wireless Spectrum Monitoring**

Hierarchical to: No other components.

Dependencies to: No dependencies.

##### **FAU\_WID\_EXT.3.1**

The TSF shall detect the presence of network devices that operate in the following RF bands: [assignment: *list of RF bands*].

#### **Management: FAU\_WID\_EXT.4**

No specific management functions are identified.

#### **Audit: FAU\_WID\_EXT.4**

There are no auditable events foreseen.

#### **FAU\_WID\_EXT.4 Wireless Intrusion Detection - Wireless Spectrum Analysis**

Hierarchical to: No other components.

Dependencies to:

[[FAU\\_WID\\_EXT.2](#) Wireless Intrusion Detection - Passive Information Flow Monitoring, or  
[FAU\\_WID\\_EXT.3](#) Wireless Intrusion Detection - Non-Wireless Spectrum Monitoring]

##### **FAU\_WID\_EXT.4.1**

The TSF shall provide a dedicated sensor for wireless spectrum analysis.

### **C.2.1.6 FAU\_ANO\_EXT Anomaly-Based Intrusion Detection**

#### **Family Behavior**

This family defines requirements for detection of malicious network activity based on anomalous behavior.

#### **Component Leveling**

FAU ANO EXT ———— [1]

[FAU\\_ANO\\_EXT.1](#), Anomaly-Based Intrusion Detection, requires the TSF to define how it determines anomalous network traffic that may be indicative of malicious activity.

#### **Management: FAU\_ANO\_EXT.1**

The following actions could be considered for the management functions in FMT:

- Specification of periods of network activity that constitute baselines of expected behavior
- Definition of anomaly activity

#### **Audit: FAU\_ANO\_EXT.1**

There are no auditable events foreseen.

## FAU\_ANO\_EXT.1 Anomaly-Based Intrusion Detection

Hierarchical to: No other components.

Dependencies to: [FAU\\_IDS\\_EXT.1](#) Intrusion Detection System - Intrusion Detection Methods

### FAU\_ANO\_EXT.1.1

The TSF shall support the definition of [**selection:** *baselines ('expected and approved'), anomaly ('unexpected') traffic patterns*] including the specification of [**selection:**

- *throughput (data elements (e.g. bytes, packets, etc.) per time period (e.g. minutes, hours, days)),*
- *time of day,*
- *frequency,*
- *thresholds,*
- [**assignment:** *other methods*]

] and the following network protocol fields:

- all management and control frame header elements.

### FAU\_ANO\_EXT.1.2

The TSF shall support the definition of anomaly activity through [**selection:** *manual configuration by administrators, automated configuration*].

## C.2.1.7 FAU\_SIG\_EXT Signature-Based Intrusion Detection

### Family Behavior

This family defines requirements for detection of malicious network activity based on traffic signatures.

### Component Leveling

FAU\_SIG\_EXT ———— 1

[FAU\\_SIG\\_EXT.1](#), Signature-Based Intrusion Detection, requires the TSF to support the definition of traffic signatures that can be compared to observed network traffic for the purpose of identifying potential malicious activity.

### Management: FAU\_SIG\_EXT.1

The following actions could be considered for the management functions in FMT:

- Definition of attack signatures

### Audit: FAU\_SIG\_EXT.1

There are no auditable events foreseen.

## FAU\_SIG\_EXT.1 Signature-Based Intrusion Detection

Hierarchical to: No other components.

Dependencies to: [FAU\\_IDS\\_EXT.1](#) Intrusion Detection System - Intrusion Detection Methods

### FAU\_SIG\_EXT.1.1

The TSF shall support user-defined and customizable attack signatures.

## C.2.1.8 FAU\_MAC\_EXT Device Impersonation

### Family Behavior

This family defines requirements for detection of potential device impersonation on the basis of MAC address spoofing.

### Component Leveling

FAU\_MAC\_EXT ———— 1

[FAU\\_MAC\\_EXT.1](#), Device Impersonation, requires the TSF to detect possible MAC address spoofing using various methods.

### Management: FAU\_MAC\_EXT.1

No specific management functions are identified.

### Audit: FAU\_MAC\_EXT.1

There are no auditable events foreseen.

## FAU\_MAC\_EXT.1 Device Impersonation

Hierarchical to: No other components.

Dependencies to: [FAU\\_INV\\_EXT.2](#) Characteristics of Environmental Objects

### FAU\_MAC\_EXT.1.1

The TSF shall detect when two sensors in non-overlapping locations receive traffic from the same MAC address simultaneously.

### FAU\_MAC\_EXT.1.2

The TSF shall detect when two sensors in non-overlapping locations receive traffic from the MAC addresses of non-allowlisted EUDs within an Authorized administrator-configurable timeframe based on distance between sensors.

## C.2.1.9 FAU\_WIP\_EXT Wireless Intrusion Prevention

### Family Behavior

This family defines requirements for wireless intrusion prevention.

### Component Leveling

FAU\_WIP\_EXT — [1]

[FAU\\_WIP\\_EXT.1](#), Wireless Intrusion Prevention, requires the TSF to support reactive behavior if potential malicious traffic is observed to be originating from or targeted to a particular network asset.

### Management: FAU\_WIP\_EXT.1

The following actions could be considered for the management functions in FMT:

- Enabling or disabling transmission of data by wireless sensor

### Audit: FAU\_WIP\_EXT.1

The following actions should be auditable if FAU\_GEN Security Audit Data Generation is included in the PP/ST:

- Isolation of AP or EUD

## FAU\_WIP\_EXT.1 Wireless Intrusion Prevention

Hierarchical to: No other components.

Dependencies to: [FAU\\_WID\\_EXT.1](#) Wireless Intrusion Detection - Malicious Environmental Objects

### FAU\_WIP\_EXT.1.1

The TSF shall allow an Authorized Administrator to isolate a wireless AP or EUD from the network monitored by the TSF using the following methods: [**selection:** *wireless containment, wire-side containment of an unauthorized AP connected to the internal corporate wired network*].

# Appendix D - Implicitly Satisfied Requirements

This appendix lists requirements that should be considered satisfied by products successfully evaluated against this Module. These requirements are not featured explicitly as SFRs and should not be included in the ST. They are not included as standalone SFRs because it would increase the time, cost, and complexity of evaluation. This approach is permitted by [\[CC\]](#) Part 1, 8.2 Dependencies between components.

This information benefits systems engineering activities which call for inclusion of particular security controls. Evaluation against the PP provides evidence that these controls are present and have been evaluated.

| Requirement                                    | Rationale for Satisfaction  |
|--|---|
| FDP_IFF.1 - Information Flow Control Functions | CC Part 2 specifies FDP_IFF.1 as a dependency of <a href="#">FDP_IFC.1</a> because the TSF must define the information flow control SFP rules associated with a given SFP. This dependency is implicitly addressed through <a href="#">FAU_WID_EXT.2</a> , which defines the rules for the 802.11 monitoring SFP defined by <a href="#">FDP_IFC.1</a> . |

# Appendix E - Allocation of Requirements in Distributed TOEs

For a distributed TOE, the security functional requirements in this PP-Module need to be met by the TOE as a whole, but not all SFRs will necessarily be implemented by all components. The following categories are defined in order to specify when each SFR must be implemented by a component:

- **All Components ("All")** - All components that comprise the distributed TOE must independently satisfy the requirement.
- **At least one Component ("One")** - This requirement must be fulfilled by at least one component within the distributed TOE.
- **Feature Dependent ("Feature Dependent")** - These requirements will only be fulfilled where the feature is implemented by the distributed TOE component (note that the requirement to meet the PP-Module as a whole requires that at least one component implements these requirements if they are claimed by the TOE).

The table below specifies how each of the SFRs in this PP-Module must be met, using the categories above.

| Requirement                        | Description  | Distributed TOE SFR Allocation |
|------------------------------------|--|--------------------------------|
| <a href="#">FAU_ANO_EXT.1</a>      | Anomaly-Based Intrusion Detection                                  | Feature Dependent              |
| <a href="#">FAU_ARP.1</a>          | Security Alarms  | One                            |
| <a href="#">FAU_ARP_EXT.1</a>      | Security Alarm Filtering   | One                            |
| <a href="#">FAU_GEN.1/WIDS</a>     | Audit Data Generation (WIDS)                                       | Feature Dependent              |
| <a href="#">FAU_IDS_EXT.1</a>      | Intrusion Detection System - Intrusion Detection Methods           | Feature Dependent              |
| <a href="#">FAU_INV_EXT.1</a>      | Environmental Inventory  | Feature Dependent              |
| <a href="#">FAU_INV_EXT.2</a>      | Characteristics of Environmental Objects                           | Feature Dependent              |
| <a href="#">FAU_INV_EXT.3</a>      | Location of Environmental Objects                                  | Feature Dependent              |
| <a href="#">FAU_INV_EXT.4</a>      | Detection of Unauthorized Connections                              | Feature Dependent              |
| <a href="#">FAU_INV_EXT.5</a>      | Signal Library   | Feature Dependent              |
| <a href="#">FAU_MAC_EXT.1</a>      | Device Impersonation   | Feature Dependent              |
| <a href="#">FAU_RPT_EXT.1</a>      | Intrusion Detection System - Reporting Methods                     | Feature Dependent              |
| <a href="#">FAU_SAA.1</a>          | Potential Violation Analysis                                       | Feature Dependent              |
| <a href="#">FAU_SIG_EXT.1</a>      | Signature-Based Intrusion Detection                                | Feature Dependent              |
| <a href="#">FAU_STG_EXT.1/PCAP</a> | Protected Audit Event Storage (Packet Captures)                    | Feature Dependent              |
| <a href="#">FAU_WID_EXT.1</a>      | Wireless Intrusion Detection - Malicious Environmental Objects     | Feature Dependent              |
| <a href="#">FAU_WID_EXT.2</a>      | Wireless Intrusion Detection - Passive Information Flow Monitoring | Feature Dependent              |
| <a href="#">FAU_WID_EXT.3</a>      | Wireless Intrusion Detection - Non-Wireless Spectrum Monitoring    | Feature Dependent              |
| <a href="#">FAU_WID_EXT.4</a>      | Wireless Intrusion Detection - Wireless Spectrum Analysis          | Feature Dependent              |
| <a href="#">FAU_WIP_EXT.1</a>      | Wireless Intrusion Prevention                                      | Feature Dependent              |
| <a href="#">FDP_IFC.1</a>          | Subset Information Flow Control                                    | Feature Dependent              |
| <a href="#">FMT_SMF.1/WIDS</a>     | Specification of Management Functions (WIDS)                       | Feature Dependent              |
| <a href="#">FPT_FLS.1</a>          | Basic Internal TSF Data Transfer Protection                        | Feature Dependent              |

# Appendix F - Entropy Documentation and Assessment

The TOE does not require any additional supplementary information to describe its entropy sources beyond the requirements outlined in the Base-PP.

# Appendix G - Acronyms

| Acronym          | Meaning                              |
|------------------|--------------------------------------|
| AES              | Advanced Encryption Standard         |
| AP               | Access Point                         |
| BSSID            | Basic Service Set Identifier         |
| Base-PP          | Base Protection Profile              |
| CC               | Common Criteria                      |
| CEM              | Common Evaluation Methodology        |
| DoS              | Denial of Service                    |
| EP               | Extended Package                     |
| EUD              | End User Device                      |
| FP               | Functional Package                   |
| HTTPS            | Hypertext Transfer Protocol Secure   |
| IPsec            | Internet Protocol Security           |
| MAC              | Media Access Control                 |
| OE               | Operational Environment              |
| PP               | Protection Profile                   |
| PP-Configuration | Protection Profile Configuration     |
| PP-Module        | Protection Profile Module            |
| SAR              | Security Assurance Requirement       |
| SFR              | Security Functional Requirement      |
| SSH              | Secure Shell                         |
| SSID             | Service Set Identifier               |
| ST               | Security Target                      |
| TKIP             | Temporal Key Integrity Protocol      |
| TLS              | Transport Layer Security             |
| TOE              | Target of Evaluation                 |
| TSF              | TOE Security Functionality           |
| TSFI             | TSF Interface                        |
| TSS              | TOE Summary Specification            |
| WEP              | Wired Equivalent Protocol            |
| WIDS             | Wireless Intrusion Detection System  |
| WIPS             | Wireless Intrusion Prevention System |
| WLAN             | Wireless Local Area Network          |
| WPA              | WLAN Protected Access                |
| cPP              | Collaborative Protection Profile     |



# Appendix H - Bibliography

| Identifier | Title   |
|------------|---|
| [CC]       | Common Criteria for Information Technology Security Evaluation - <ul style="list-style-type: none"><li>• <a href="#">Part 1: Introduction and General Model</a>, CCMB-2017-04-001, Version 3.1 Revision 5, April 2017.</li><li>• <a href="#">Part 2: Security Functional Components</a>, CCMB-2017-04-002, Version 3.1 Revision 5, April 2017.</li><li>• <a href="#">Part 3: Security Assurance Components</a>, CCMB-2017-04-003, Version 3.1 Revision 5, April 2017.</li></ul> |
| [NDcPP]    | <a href="#">collaborative Protection Profile for Network Devices</a> , Version 2.2e, March 23, 2020   |
| [NDcPP SD] | <a href="#">Supporting Document - Evaluation Activities for Network Device cPP</a> , Version 2.2, December 2019   |