

Comment: Comment-1-  
Comment: Comment-2-  
Comment: Comment-3-

# PP-Module for LiFi Access Systems



Version: 1.0  
2026-01-26

**National Information Assurance Partnership**

# Revision History

---

| Version | Date       | Comment         |
|---------|------------|-----------------|
| 1.0     | 2026-01-26 | Initial Release |

# Contents

---

- 1 Introduction
  - 1.1 Overview
  - 1.2 Terms
    - 1.2.1 Common Criteria Terms
    - 1.2.2 Technical Terms
  - 1.3 Compliant Targets of Evaluation
    - 1.3.1 TOE Boundary
  - 1.4 Use Cases
  - 1.5 Implementation-Based Features
    - 1.5.1 802.11bb Support
    - 1.5.2 Distributed TOE
    - 1.5.3 G.vlc Support
- 2 Conformance Claims
- 3 Security Problem Definition
  - 3.1 Threats
  - 3.2 Assumptions
  - 3.3 Organizational Security Policies
- 4 Security Objectives
  - 4.1 Security Objectives for the Operational Environment
  - 4.2 Security Objectives Rationale
- 5 Security Requirements
  - 5.1 Protection Profile for Network Device Security Functional Requirements Direction
    - 5.1.1 Modified SFRs
  - 5.2 TOE Security Functional Requirements
    - 5.2.1 Auditable Events for Mandatory SFRs
    - 5.2.2 Security Audit (FAU)
    - 5.2.3 Cryptographic Support (FCS)
    - 5.2.4 Identification and Authentication (FIA)
    - 5.2.5 Security Management (FMT)
    - 5.2.6 Protection of the TSF (FPT)
    - 5.2.7 TOE Access (FTA)
    - 5.2.8 Trusted Path/Channels (FTP)
  - 5.3 TOE Security Functional Requirements Rationale
- 6 Consistency Rationale
  - 6.1 Protection Profile for Network Device
    - 6.1.1 Consistency of TOE Type
    - 6.1.2 Consistency of Security Problem Definition
    - 6.1.3 Consistency of OE Objectives
    - 6.1.4 Consistency of Requirements
- Appendix A - Optional SFRs

|              |                                                                        |
|--------------|------------------------------------------------------------------------|
| A.1          | Strictly Optional Requirements                                         |
| A.2          | Objective Requirements                                                 |
| A.3          | Implementation-dependent Requirements                                  |
| A.3.1        | Auditable Events for Implementation-Dependent SFRs                     |
| A.3.2        | SFRs for 802.11bb Implementations                                      |
| A.3.3        | SFRs for Distributed TOE Implementations                               |
| A.3.4        | SFRs for G.vlc Implementations                                         |
| Appendix B - | Selection-based Requirements                                           |
| B.1          | Auditable Events for Selection-based SFRs                              |
| B.2          | Cryptographic Support (FCS)                                            |
| Appendix C - | Extended Component Definitions                                         |
| C.1          | Extended Components Table                                              |
| C.2          | Extended Component Definitions                                         |
| C.2.1        | Cryptographic Support (FCS)                                            |
| C.2.1.1      | FCS_RADSEC_EXT RadSec                                                  |
| C.2.2        | Identification and Authentication (FIA)                                |
| C.2.2.1      | FIA_8021X_EXT 802.1X Port Access Entity (Authenticator) Authentication |
| C.2.3        | Protection of the TSF (FPT)                                            |
| C.2.3.1      | FPT_ACF_EXT Access Controls                                            |
| C.2.3.2      | FPT_ASLR_EXT Address Space Layout Randomization                        |
| C.2.3.3      | FPT_SBOP_EXT Stack Buffer Overflow Protection                          |
| C.2.3.4      | FPT_W^X_EXT Write XOR Execute Memory Pages                             |
| C.2.4        | Security Management (FMT)                                              |
| C.2.4.1      | FMT_SMR_EXT Security Management Restrictions                           |
| Appendix D - | Acronyms                                                               |
| Appendix E - | Bibliography                                                           |

# 1 Introduction

## 1.1 Overview

The scope of the LiFi Access System ~~PP-Module~~ is to describe the security functionality of a LiFi access system product in terms of [CC] and to define functional and assurance requirements for such products. This ~~PP-Module~~ is intended for use with the following ~~Base-PPs~~:

- collaborative Protection Profile for Network Devices, Version 4.0

A conformant ~~TOE~~ will claim conformance to a ~~PP-Configuration~~ that includes the ~~Base-PP~~ identified above, this ~~PP-Module~~, and any of the ~~PP-Modules~~ or packages identified in Section 2.

This ~~Base-PP~~ is valid because a LiFi Access System is a specific function for a purpose-built network device.

## 1.2 Terms

The following sections list Common Criteria and technology terms used in this document.

### 1.2.1 Common Criteria Terms

|                                        |                                                                                                                                                                                                                                                                                             |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Assurance                              | Grounds for confidence that a TOE meets the SFRs [CC].                                                                                                                                                                                                                                      |
| Base Protection Profile (Base-PP)      | Protection Profile used as a basis to build a PP-Configuration.                                                                                                                                                                                                                             |
| Collaborative Protection Profile (cPP) | A Protection Profile developed by international technical communities and approved by multiple schemes.                                                                                                                                                                                     |
| Common Criteria (CC)                   | Common Criteria for Information Technology Security Evaluation (International Standard ISO/IEC 15408).                                                                                                                                                                                      |
| Common Criteria Testing Laboratory     | Within the context of the Common Criteria Evaluation and Validation Scheme (CCEVS), an IT security evaluation facility accredited by the National Voluntary Laboratory Accreditation Program (NVLAP) and approved by the NIAP Validation Body to conduct Common Criteria-based evaluations. |
| Common Evaluation Methodology (CEM)    | Common Evaluation Methodology for Information Technology Security Evaluation.                                                                                                                                                                                                               |
| Distributed TOE                        | A TOE composed of multiple components operating as a logical whole.                                                                                                                                                                                                                         |
| Operational Environment (OE)           | Hardware and software that are outside the TOE boundary that support the TOE functionality and security policy.                                                                                                                                                                             |
| Protection Profile (PP)                | An implementation-independent set of security requirements for a category of products.                                                                                                                                                                                                      |

|                                                     |                                                                                                                                   |
|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Protection Profile Configuration (PP-Configuration) | A comprehensive set of security requirements for a product type that consists of at least one Base-PP and at least one PP-Module. |
| Protection Profile Module (PP-Module)               | An implementation-independent statement of security needs for a TOE type complementary to one or more Base-PPs.                   |
| Security Assurance Requirement (SAR)                | A requirement to assure the security of the TOE.                                                                                  |
| Security Functional Requirement (SFR)               | A requirement for security enforcement by the TOE.                                                                                |
| Security Target (ST)                                | A set of implementation-dependent security requirements for a specific product.                                                   |
| Target of Evaluation (TOE)                          | The product under evaluation.                                                                                                     |
| TOE Security Functionality (TSF)                    | The security functionality of the product under evaluation.                                                                       |
| TOE Summary Specification (TSS)                     | A description of how a TOE satisfies the SFRs in an ST.                                                                           |

## 1.2.2 Technical Terms

|                               |                                                                                                                                                                                                                                |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Access Point (AP)             | A device that provides the network interface that enables wireless client hosts to access a wired network.                                                                                                                     |
| LiFi                          | A wireless computer network that links two or more devices using modulated optical communication to form a local area network within a limited area such as a home, school, computer laboratory, campus, office building, etc. |
| Service Set Identifier (SSID) | The primary name associated with an 802.11 wireless local area network (WLAN).                                                                                                                                                 |

## 1.3 Compliant Targets of Evaluation

This PP-Module specifically addresses LiFi (IEEE 802.11bb, ITU G.9991) access systems (AS). A compliant LiFi AS is a system composed of hardware and software that is connected to a network and has an infrastructure role in the overall enterprise network. In particular, a LiFi AS establishes a secure wireless (IEEE 802.11, IEEE802.1x, IEEE 802.1AE) link that provides an authenticated and encrypted path to an enterprise network and thereby decreases the risk of exposure of information transiting “over-the-air”.

Since this PP-Module extends the NDcPP, conformant TOEs are obligated to implement the functionality required in the NDcPP along with the additional functionality defined in this PP-Module in response to the threat environment discussed subsequently herein.

The TOE encompasses the OS kernel drivers, shared software libraries, and some application software included with the OS. The applications considered within the TOE are those that provide essential LiFi services that make up the LiFi link and security. Examples are management services that implement configuration functions specified in this PP-Module, host services that manage client authentication to the access point, and the libraries and modules

that provide security implementation of the LiFi link. This applies to each separate **TOE** component that are being used to meet the security requirements proposed.

### 1.3.1 TOE Boundary

The physical boundary for a **TOE** that conforms to this **PP-Module** is one or more physical network appliances (in a standalone or distributed configuration) that provides generalized network device functionality such as auditing, identification and authentication, and cryptographic services for network communications, as well as specialized functionality for facilitating remote network access via LiFi communications. The **TOE**'s logical boundary includes all functionality required by the claimed **Base-PP**, this **PP-Module**, and any other **PP-Modules** which may be claimed by the **ST** author as a part of a **PP-Configuration** that includes this **PP-Module**. Product functionality for which no **PP-Module** exists, or for which no **SFR** within a relevant **PP-Module** exists to capture, are considered to be non-interfering with respect to the **TSE**. In other words, they may be present or enabled in the evaluated configuration of the **TOE** but their presence must not degrade or interrupt the enforcement of functions within the **TOE**'s logical boundary.

Note that while the **Base-PP** permits the **TOE** either to be a physical or virtual network appliance, LiFi devices require the use of specialized hardware that will not be present on commodity servers, and it is therefore expected that any **TOE** that conforms to this **PP-Module** will be one or more dedicated physical devices.




Figure 1: High Level **TOE** Implementation

## 1.4 Use Cases

### [USE CASE 1] Standalone Device

The **TOE** is a standalone network device that serves as a single network endpoint that provides connectivity to LiFi clients.

### [USE CASE 2] Distributed System

The **TOE** is a distributed system consisting of multiple network devices that collectively serve as the LiFi network endpoint. In addition to claiming the relevant "Distributed **TOE**" requirement in the **NDcPP**, this use case also requires the **TOE** to claim the optional **SFR** [FCS\\_CKM.2/DISTRIB](#) to describe the key distribution method between distributed **TOE** components.

## 1.5 Implementation-Based Features

A conformant **TOE** may implement either 802.11bb or G.vlc. Depending on which is supported, different requirements will apply to the **TOE** as they each implement different methods of protection of data in transit.

### 1.5.1 802.11bb Support

The ~~TOE~~ implements LiFi using IEEE 802.11bb. Data in transit is protected using either ~~IPsec~~ or RadSec (RADIUS over ~~TLS~~).

If this feature is implemented by the ~~TOE~~, the following requirements must be claimed in the ~~ST~~:

- ~~FCS\_CKM.1/WPA~~
- ~~FCS\_CKM.2/GTK~~
- ~~FCS\_CKM.2/PMK~~
- ~~FTP\_ITC.1/Client~~

### 1.5.2 Distributed TOE

A specific subtype of a ~~TOE~~ that supports 802.11bb is a distributed architecture. When the ~~TOE~~ implements this feature, it uses a key distribution mechanism to pass keys between distributed components so that a remote client may persistently maintain a connection to different connections in transit (e.g., when moving to different floors of a building).

If this feature is implemented by the ~~TOE~~, the following requirements must be claimed in the ~~ST~~:

- ~~FCS\_CKM.2/DISTRIB~~

### 1.5.3 G.vlc Support

The ~~TSF~~ implements LiFi using ITU-T G.9991 (aka G.vlc). Data in transit is protected using MACsec. When the ~~TOE~~ implements this feature, it must also claim conformance to the ~~PP-Module~~ for MACsec Ethernet Encryption.

If this feature is implemented by the ~~TOE~~, the following requirements must be claimed in the ~~ST~~:

- ~~FTP\_ITC.1/Gvlc~~

# 2 Conformance Claims

## Conformance Statement

An ST must claim exact conformance to this PP-Module.

The evaluation methods used for evaluating the TOE are a combination of the workunits defined in [\[CEM\]](#) as well as the Evaluation Activities for ensuring that individual SFRs and SARs have a sufficient level of supporting evidence in the Security Target and guidance documentation and have been sufficiently tested by the laboratory as part of completing ATE\_IND.1. Any functional packages this PP claims similarly contain their own Evaluation Activities that are used in this same manner.

## CC Conformance Claims

This PP-Module is conformant to Part 2 (extended) and Part 3 (conformant) of Common Criteria CC:2022, Revision 1.

## PP Claim

This PP-Module does not claim conformance to any Protection Profile.

The following PPs and PP-Modules are allowed to be specified in a PP-Configuration with this PP-Module:

- collaborative Protection Profile for Network Devices, Version 4.0
- PP-Module for MACsec Ethernet Encryption, version 2.0

## Package Claim

- This PP-Module is Functional Package for Transport Layer Security Version 2.1 conformant.
- This PP-Module is Functional Package for X.509 Version 1.0 conformant.
- This PP-Module does not conform to any assurance packages.

The functional packages to which the PP conforms may include SFRs that are not mandatory to claim for the sake of conformance. An ST that claims one or more of these functional packages may include any non-mandatory SFRs that are appropriate to claim based on the capabilities of the TSF and on any triggers for their inclusion based inherently on the SFR selections made.



# 3 Security Problem Definition

This PP-Module is written to address the situation where a distributed network device facilitates end user access to a network via LiFi. The threats are similar to those that are typical of network devices as a whole, but may be exploited differently because of the mechanisms that are unique to this particular type of product.

## 3.1 Threats

---

### T.DATA\_INTEGRITY

Devices on a protected network may be exposed to threats presented by devices located outside the protected network, which may attempt to modify the data without authorization. If known malicious external devices are able to communicate with devices on the protected network or if devices on the protected network can establish communications with those external devices then the data contained within the communications may be susceptible to a loss of integrity.

### T.NETWORK\_ACCESS

Devices located outside the protected network may seek to exercise services located on the protected network that are intended to be only accessed from inside the protected network or only accessed by entities using an authenticated path into the protected network.

### T.NETWORK\_ATTACK

An attacker is positioned on a communications channel or elsewhere on the network infrastructure. Attackers may engage in communications with applications and services running on or part of the TOE with the intent of compromise. Engagement may consist of altering existing legitimate communications.

### T.NETWORK\_DISCLOSURE

Devices on a protected network may be exposed to threats presented by devices located outside the protected network, which may attempt to conduct unauthorized activities. If malicious external devices are able to communicate with devices on the protected network, or if devices on the protected network can establish communications with those external devices (e.g., as a result of nonexistent or insufficient data encryption that exposes the data in transit to rogue elements), then those internal devices may be susceptible to the unauthorized disclosure of information.

### T.REPLAY\_ATTACK

If an unauthorized individual successfully gains access to the system, the adversary may have the opportunity to conduct a "replay" attack. This method of attack allows the individual to capture packets transversing throughout the wireless network and send the packets later, possibly unknown by the intended receiver.

## 3.2 Assumptions

---

These assumptions are made on the Operational Environment (OE) in order to be able to ensure that the security functionality specified in the PP-Module can be provided by the TOE. If the TOE is placed in an OE that does not meet these assumptions, the TOE may no longer be able to provide all of its security functionality.

### A.MANAGED\_CONFIG

Depending on configuration and capability, the product may or may not be configuration-managed by the enterprise or bound to directory services to support multi-user login.

#### **A.NETWORK\_CONNECTIVITY**

The platform is connected to a network. For purposes of sending/receiving data, to include software updates, the platform is connected to other entities. Other entities on the network are not inherently trustable.

#### **A.NON\_SECURITY\_FUNCTIONS**

The product implements some security-relevant functionality that does not require evaluation (e.g., network time synchronization, process scheduling, and virtual memory management including process separation).

#### **A.PROPER\_USER**

Users are not malicious in nature, though they may inadvertently or intentionally engage in risky behavior.

#### **A.THIRD\_PARTY\_SOFTWARE**

The product runs application software developed by a third party. The applications are not intentionally developed to be malicious, but can contain inadvertent coding errors. These errors introduce risk that control of an application may be seized by a malicious entity. The product shall confine these applications within the originally designated operating environment.

### **3.3 Organizational Security Policies**

---

An organization deploying the TOE is expected to satisfy the organizational security policy listed below in addition to all organizational security policies defined by the claimed Base-PP.

This document does not define any additional OSPs.

# 4 Security Objectives

## 4.1 Security Objectives for the Operational Environment

The OE of the TOE implements technical and procedural measures to assist the TOE in correctly providing its security functionality (which is defined by the security objectives for the TOE). The security objectives for the OE consist of a set of statements describing the goals that the OE should achieve. This section defines the security objectives that are to be addressed by the IT domain or by non-technical or procedural means. The assumptions identified in Section 3 are incorporated as security objectives for the environment.

**OE.MANAGED\_CONFIG**

The product is compatible with enterprise architecture that allows for managed configuration, subject authorization via directory services, or both.

**OE.NETWORK\_CONNECTIVITY**

The operational environment facilitates the use of network connectivity by authorized subjects.

**OE.NON\_SECURITY\_FUNCTIONS**

The product has functionality outside of its logical security boundary to satisfy organizational requirements that are unrelated to what this PP-Module defines.

**OE.PROPER\_USER**

Users of the system are adequately vetted to ensure that they are non-malicious.

**OE.THIRD\_PARTY\_SOFTWARE**

The operational environment permits the use of third-party software on organization-owned hardware to enforce necessary functions.

## 4.2 Security Objectives Rationale

This section describes how the assumptions and organizational security policies map to operational environment security objectives.

Table 1: Security Objectives Rationale

| Assumption or OSP                        | Security Objectives                       | Rationale                                                                                                                                      |
|------------------------------------------|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">A.MANAGED_CONFIG</a>         | <a href="#">OE.MANAGED_CONFIG</a>         | The operational environment objective <a href="#">OE.MANAGED_CONFIG</a> is realized through <a href="#">A.MANAGED_CONFIG</a> .                 |
| <a href="#">A.NETWORK_CONNECTIVITY</a>   | <a href="#">OE.NETWORK_CONNECTIVITY</a>   | The operational environment objective <a href="#">OE.NETWORK_CONNECTIVITY</a> is realized through <a href="#">A.NETWORK_CONNECTIVITY</a> .     |
| <a href="#">A.NON_SECURITY_FUNCTIONS</a> | <a href="#">OE.NON_SECURITY_FUNCTIONS</a> | The operational environment objective <a href="#">OE.NON_SECURITY_FUNCTIONS</a> is realized through <a href="#">A.NON_SECURITY_FUNCTIONS</a> . |

|                        |                         |                                                                                                                                            |
|------------------------|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| A.PROPER_USER          | OE.PROPER_USER          | The operational environment objective <a href="#">OE.PROPER_USER</a> is realized through <a href="#">A.PROPER_USER</a> .                   |
| A.THIRD_PARTY_SOFTWARE | OE.THIRD_PARTY_SOFTWARE | The operational environment objective <a href="#">OE.THIRD_PARTY_SOFTWARE</a> is realized through <a href="#">A.THIRD_PARTY_SOFTWARE</a> . |

# 5 Security Requirements

This chapter describes the security requirements which have to be fulfilled by the product under evaluation. Those requirements comprise functional components from Part 2 and assurance components from Part 3 of [CC]. The following conventions are used for the completion of operations:

- **Refinement** operation (denoted by **bold text** or ~~strikethrough text~~): Is used to add details to a requirement or to remove part of the requirement that is made irrelevant through the completion of another operation, and thus further restricts a requirement.
- **Selection** (denoted by *italicized text*): Is used to select one or more options provided by the [CC] in stating a requirement.
- **Assignment** operation (denoted by *italicized text*): Is used to assign a specific value to an unspecified parameter, such as the length of a password. Showing the value in square brackets indicates assignment.
- **Iteration** operation: Is indicated by appending the SFR name with a slash and unique identifier suggesting the purpose of the operation, e.g. "/EXAMPLE1."

## 5.1 Protection Profile for Network Device Security Functional Requirements Direction

In a PP-Configuration that includes the NDcPP, the TOE is expected to rely on some of the security functions implemented by the network device as a whole and evaluated against the Base-PP. In this case, the following sections describe any modifications that the ST author must make to the SFRs defined in the Base-PP in addition to what is mandated by section 5.2.

### 5.1.1 Modified SFRs

This PP-Module does not modify any SFRs defined by the ND PP.

## 5.2 TOE Security Functional Requirements

The following section describes the SFRs that must be satisfied by any TOE that claims conformance to this PP-Module. These SFRs must be claimed regardless of which PP-Configuration is used to define the TOE.

### 5.2.1 Auditable Events for Mandatory SFRs

Table 2: Auditable Events for Mandatory Requirements

| Requirement                  | Auditable Events    | Additional Audit Record Contents              |
|------------------------------|---------------------|-----------------------------------------------|
| FAU_GEN.1/LiFi               | No events specified | N/A                                           |
| FCS_COP.1/LiFiDataEncryption | No events specified | N/A                                           |
| FIA_8021X_EXT.1              | None                | Provided client identity (e.g., MAC address). |

|                 |                                                                              |                                                                                                              |
|-----------------|------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| FIA_UAU.6       | None                                                                         | Origin of the attempt (e.g., IP address)                                                                     |
| FMT_SMF.1/LiFi  | No events specified                                                          | N/A                                                                                                          |
| FMT_SMR_EXT.1   | No events specified                                                          | N/A                                                                                                          |
| FPT_ACF_EXT.1   | Unauthorized attempts to perform operations against protected data           | No additional information                                                                                    |
| FPT_ASLR_EXT.1  | No events specified                                                          | N/A                                                                                                          |
| FPT_FLS.1       | No events specified                                                          | N/A                                                                                                          |
| FPT_SBOP_EXT.1  | No events specified                                                          | N/A                                                                                                          |
| FPT_W^X_EXT.1   | No events specified                                                          | N/A                                                                                                          |
| FTA_TSE.1       | Denial of a session establishment due to the session establishment mechanism | <ul style="list-style-type: none"> <li>Reason for denial</li> <li>Origin of establishment attempt</li> </ul> |
| FTP_ITC.1/8021X | Failed attempts to establish a trusted channel (including IEEE 802.11)       | Identification of the initiator and target of channel                                                        |
|                 | Detection of modification of channel data                                    | Identification of the initiator and target of channel                                                        |

## 5.2.2 Security Audit (FAU)

### FAU\_GEN.1/LiFi Audit Data Generation (LiFi)

#### FAU\_GEN.1.1/LiFi

The TSE shall be able to generate an audit record of the following auditable events:

- Start-up and shutdown of the audit functions
- All auditable events for the [not specified] level of audit; and
- [[auditable events defined in Table 2, auditable events defined in Table 8, auditable events defined in Table 10].
- Failure of wireless sensor communication]

**Application Note:** A TOE that conforms to a Protection Profile Configuration (PP-Configuration) containing this PP-Module either can be a standalone or distributed TOE as defined in the NDcPP. For distributed TOEs, the expectation for this PP-Module is that a LiFi AS is composed of a single controller and one or more access points (APs). If the TOE is a distributed system across multiple components then they must be capable of sending audit data to the controller. If the TOE is a standalone system, audit data should be stored on the component that generates it.

The auditable events defined in Table 2, Table 8, and Table 10 are for the SFRs that are explicitly defined in this PP-Module and are intended to extend FAU\_GEN.1 in the Base-PP. The events in the Auditable Events table should be combined with those of the NDcPP in the context of a conforming Security Target. This table includes rows for all SFRs in the PP-Module. For any SFRs the ST claims, the corresponding

audit events must also be claimed in the table. If the ST does not claim a particular SER, then there is likewise no expectation that the auditable events for that SER are required.

Per FAU\_STG\_EXT.1 in the Base-PP, the TOE must support transfer of the audit data to an external IT entity using a trusted channel.

FAU\_GEN.1.2/LiFi

- The TSF shall record within each audit record at least the following information:
- a. Date and time of the event, type of event, subject identity (if applicable), and the outcome (success or failure) of the event; and
  - b. For each audit event type, based on the auditable event definitions of the functional components included in the PP/ST, [additional information defined in table for each auditable event, where applicable].

Evaluation Activities ▼

*FAU\_GEN.1/LiFi*

**TSS**

*There are no TSS evaluation activities for this SER.*

**Guidance**

*There are no operational guidance activities for this SER.*

**Tests**

*The evaluator shall complete the evaluation activity for FAU\_GEN.1 as described in the NDcPP for the auditable events defined in the PP-Module in addition to the applicable auditable events that are defined in the NDcPP. The evaluator shall also ensure that the administrative actions defined for this PP-Module are appropriately audited.*

5.2.3 Cryptographic Support (FCS)

FCS\_COP.1/LiFiDataEncryption Cryptographic Operation (Data Encryption and Decryption for LiFi

FCS\_COP.1.1/LiFiDataEncryption

The TSF shall perform [symmetric-key encryption and decryption] in accordance with a specified cryptographic algorithm [selection: Cryptographic Algorithm] and cryptographic key sizes [selection: Cryptographic Key Sizes] that meet the following: [selection: List of Standards]

The following table provides the allowable choices for completion of the selection operations in FCS\_COP.1/LiFiDataEncryption. At minimum, AES-GCMP must be selected.

Table 3: Allowable choices for FCS\_COP.1/LiFiDataEncryption

| Identifier | Cryptographic Algorithm | Cryptographic Key Sizes | List of Standards |
|------------|-------------------------|-------------------------|-------------------|
|------------|-------------------------|-------------------------|-------------------|

|          |                                                                                                                                                                    |          |                                                                           |
|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|---------------------------------------------------------------------------|
| AES-GCMP | AES in Galois Counter Mode Protocol                                                                                                                                | 256 bits | ISO/IEC 18033-3:2010 (Subclause 5.2), NIST SP 800-38D, IEEE 802.11ax-2021 |
| AES-CBC  | AES in CBC mode with non-repeating and unpredictable IVs                                                                                                           | 256 bits | ISO/IEC 18033-3:2010 (Subclause 5.2), ISO/IEC 10116:2017 (Clause 7)       |
| AES-CCMP | AES in CCM mode Protocol                                                                                                                                           | 256 bits | ISO/IEC 18033-3:2010 (Subclause 5.2), NIST SP 800-38C, IEEE 802.11-2020   |
| AES-GCM  | AES in GCM mode with non-repeating IVs using [selection: deterministic, RBG-based], IV construction; the tag must be of length [selection: 96, 104, 112, 120, 128] | 256 bits | ISO/IEC 18033-3:2010 (Subclause 5.2), ISO/IEC 19772:2020 (Clause 10)      |

**Application Note:** This requirement includes cryptographic algorithms defined in the Base-PP because it applies to the cryptographic algorithms used specifically in support of LiFi communications, some of which can be used for other purposes. If any of the algorithms claimed in support of LiFi communications are used by the TSF solely for that purpose, it is not necessary to duplicate the claim in the Base-PP SFR. For example, if the TOE implements AES-CBC solely for LiFi communications, the Base-PP requirement FCS\_COP.1/SKC does not need to replicate the AES-CBC claim made here. 256-bit GCMP is required in order to comply with FCS\_CKM.1/WPA. AES-CCMP, if claimed, is required to use 256-bit keys for IEEE 802.11ax-2021 connections.

## Evaluation Activities ▼

### *FCS\_COP.1/LiFiDataEncryption* *TSS*

*The evaluator shall examine the TSS to verify that it describes how the TOE generates a key based on output from a random bit generator as specified in FCS\_RBG.1. The evaluator shall review the TSS to verify that it describes how the functionality described by FCS\_RBG.1 is invoked.*

*The evaluator shall examine the TSS to verify that it identifies the usage and key lifecycle for keys generated using each selected algorithm.*

### *Guidance*



The evaluator shall verify that the guidance instructs the administrator how to configure the TOE to generate keys for the selected key generation algorithms for all key types and uses identified in the TSS.

## Tests

If the TOE claims support for AES-CBC, AES-GCM, or AES-GCMP, the evaluator shall perform the testing defined in the Base-PP's FCS\_COP.1/SKC\_SFR for the applicable modes.

## AES-CCM Tests

The evaluator will test the generation-encryption and decryption-verification functionality of AES-CCM for the following input parameter and tag lengths:

### 128 bit and 256 bit keys

**Two payload lengths.** One payload length will be the shortest supported payload length, greater than or equal to zero bytes. The other payload length will be the longest supported payload length, less than or equal to 32 bytes (256 bits).

**Two or three associated data lengths.** One associated data length will be 0, if supported. One associated data length will be the shortest supported payload length, greater than or equal to zero bytes. One associated data length will be the longest supported payload length, less than or equal to 32 bytes (256 bits). If the implementation supports an associated data length of 216 bytes, an associated data length of 216 bytes will be tested.

**Nonce lengths.** All supported nonce lengths between 7 and 13 bytes, inclusive, will be tested.

**Tag lengths.** All supported tag lengths of 4, 6, 8, 10, 12, 14, and 16 bytes will be tested.

Due to the restrictions that IEEE 802.11 specifies for this mode (nonce length of 13 and tag length of 8), it is acceptable to test a subset of the supported lengths as long as the selections fall into the ranges specified above. In this case, the evaluator will ensure that these are the only supported lengths. To test the generation-encryption functionality of AES-CCM, the evaluator will perform the following four tests:

- Test FCS\_COP.1/LiFiDataEncryption:1: For each supported key and associated data length and any supported payload, nonce and tag length, the evaluator will supply one key value, one nonce value and 10 pairs of associated data and payload values, and obtain the resulting ciphertext.
- Test FCS\_COP.1/LiFiDataEncryption:2: For each supported key and payload length and any supported associated data, nonce and tag length, the evaluator will supply one key value, one nonce value and 10 pairs of associated data and payload values, and obtain the resulting ciphertext.
- Test FCS\_COP.1/LiFiDataEncryption:3: For each supported key and nonce length and any supported associated data, payload, and tag length, the evaluator will supply one key value and 10 associated data, payload and nonce value 3-tuples, and obtain the resulting ciphertext.
- Test FCS\_COP.1/LiFiDataEncryption:4: For each supported key and tag length and any supported associated data, payload, and nonce length, the evaluator will supply one key value, one nonce value and 10 pairs of associated data and payload values and, obtain the resulting ciphertext.

To determine correctness in each of the above tests, the evaluator will compare the ciphertext with the result of generation-encryption of the same inputs with a known good implementation.

To test the decryption-verification functionality of AES-CCM, for each combination of supported associated data length, payload length, nonce length, and tag length, the evaluator will supply a key value and 15 nonce, associated data and ciphertext 3-tuples, and obtain either a fail result or a pass result with the decrypted payload. The evaluator will supply 10 tuples that should fail and 5 that should pass per set of 15.

Additionally, the evaluator will use tests from the IEEE 802.11-02/362r6 document “Proposed Test vectors for IEEE 802.11 TGi”, dated September 10, 2002, Section 2.1 AES-CCMP Encapsulation Example and Section 2.2 Additional AES-CCMP Test Vectors to verify further the IEEE 802.11-2020 implementation of AES-CCMP.

## 5.2.4 Identification and Authentication (FIA)

### FIA\_8021X\_EXT.1 802.1X Authentication

#### FIA\_8021X\_EXT.1.1

The TSSF shall conform to IEEE Standard 802.1X for a Port Access Entity (PAE) in the “Authenticator” role.

#### FIA\_8021X\_EXT.1.2

The TSSF shall support communications to a RADIUS authentication server conforming to RFCs 2865, 2866, and 3579.

#### FIA\_8021X\_EXT.1.3

The TSSF shall ensure that no access to its 802.1X controlled port is given to the wireless client prior to successful completion of this authentication exchange.

**Application Note:** This requirement covers the TOE's role as the authenticator in an 802.1X authentication exchange. If the exchange is completed successfully, the TOE will obtain the PMK from the RADIUS server and perform the four-way handshake with the wireless client (supplicant) to begin 802.11 communications. As indicated previously, there are at least three communication paths present during the exchange; two with the TOE as an endpoint and one with the TOE acting as a transfer point only. The TOE establishes an Extensible Authentication Protocol (EAP) over Local Area Network (EAPOL) connection with the wireless client as specified in 802.1X-2007. The TOE also establishes (or has established) a RADIUS protocol connection protected either by IPsec or RadSec (TLS) with the RADIUS server. The wireless client and RADIUS server establish an EAP-TLS session (RFC 5216); in this transaction the TOE merely takes the EAP-TLS packets from its EAPOL/RADIUS endpoint and transfers them to the other endpoint. Because the specific authentication method (TLS in this case) is opaque to the TOE, there are no requirements with respect to RFC 5126 in this PP-Module. However, the base RADIUS protocol (2865) has an update (3579) that will need to be addressed in the implementation and evaluation activities. RADIUS accounting is implemented via conformance to RFC 2866.

Additionally, RFC 5080 contains implementation issues that will need to be addressed by developers but which levy no new requirements. The point of performing 802.1X authentication is to provide access to the network (assuming the authentication was successful and that all 802.11 negotiations are performed successfully); in the terminology of 802.1X, this means the wireless client has access to the "controlled port" maintained by the TOE.

## Evaluation Activities ▼

[FIA\\_8021X\\_EXT.1](#)  
TSS

In order to show that the ~~TSS~~ implements the 802.1X-2010 standard correctly, the evaluator will ensure that the ~~TSS~~ contains the following information:

- The sections (clauses) of the standard that the ~~TOE~~ implements
- For each identified section, any options selected in the implementation allowed by the standards are specified
- For each identified section, any non-conformance is identified and described, including a justification for the non-conformance

Because the connection to the ~~RADIUS~~ server will be contained in an ~~IPsec~~ or RadSec (~~TLS~~) tunnel, the security mechanisms detailed in the RFCs identified in the requirement are not relied on to provide protection for these communications. Consequently, no extensive analysis of the RFCs is required. However, the evaluator will ensure that the ~~TSS~~ describes the measures (documentation, testing) that are taken by the product developer to ensure that the ~~TOE~~ conforms to the RFCs listed in this requirement.

### Guidance

There are no guidance evaluation activities for this component.

### Tests

The evaluator will perform the following tests:

- Test FIA\_8021X\_EXT.1:1: The evaluator will demonstrate that a wireless client has no access to the test network. After successfully authenticating with a ~~RADIUS~~ server through the ~~TOE~~, the evaluator will demonstrate that the wireless client does have access to the test network.
- Test FIA\_8021X\_EXT.1:2: The evaluator will demonstrate that a wireless client has no access to the test network. The evaluator will attempt to authenticate using an invalid client certificate, such that the ~~EAP-TLS~~ negotiation fails. This should result in the wireless client still being unable to access the test network.
- Test FIA\_8021X\_EXT.1:3: The evaluator will demonstrate that a wireless client has no access to the test network. The evaluator will attempt to authenticate using an invalid ~~RADIUS~~ certificate, such that the ~~EAP-TLS~~ negotiation fails. This should result in the wireless client still being unable to access the test network.

**Note:** Tests 2 and 3 above are not tests that "~~EAP-TLS~~ works," although that is a by-product of the test. The test is actually that a failed authentication (under two failure modes) results in denial of access to the network, which demonstrates the enforcement of [FIA\\_8021X\\_EXT.1.3](#).

## FIA\_UAU.6 Re-authenticating

### FIA\_UAU.6.1

The ~~TSS~~ shall re-authenticate the user under the conditions [when the user changes their password, [**selection:** following ~~TSS~~-initiated session locking, [**assignment:** other conditions], no other conditions]].

### Evaluation Activities ▼

#### [FIA\\_UAU.6](#)

#### ~~TSS~~

There are no ~~TSS~~ evaluation activities for this component.

### **Guidance**

*There are no guidance evaluation activities for this component.*

### **Tests**

*The evaluator will attempt to change their password as directed by the operational guidance. While making this attempt, the evaluator will verify that re-authentication is required.*

*If other re-authentication conditions are specified, the evaluator will cause those conditions to occur and verify that the TSE re-authenticates the authenticated user.*

## **5.2.5 Security Management (FMT)**

### **FMT\_SMF.1/LiFi Specification of Management Functions**

#### **FMT\_SMF.1.1/LiFi**

The TSE shall be capable of performing the following management functions:  
[configuration of the security policy for each wireless network, including:

- Security type
- Client credentials to be used for authentication
- [**selection:** authentication protocol, Service Set Identifier (SSID) if the SSID is broadcast, no other security policy elements]

].

### **Evaluation Activities ▼**

#### **FMT\_SMF.1/LiFi**

##### **TSS**

*The evaluator shall examine the TSS to verify that it describes the security policy configuration in terms of the attributes claimed in the SER.*

*The evaluator shall also confirm that the TSS includes a description of how connection attempts from clients that are not operating on an approved security type are handled.*

### **Guidance**

*The evaluator shall examine the operational guidance to verify that it includes procedures for configuring the security policy of the wireless network including all attributes claimed in the ST.*

### **Tests**

*The evaluator shall perform the following tests:*

- Test FMT\_SMF.1/LiFi:1: For each security type specified in the TSS, configure the network to the approved security type and verify that the client can establish a connection. Maintaining the same SSID, change the security type of the client to a non-approved security type and attempt to establish a connection. Verify that the connection was unsuccessful.
- Test FMT\_SMF.1/LiFi:2: For each authentication protocol specified in the TSS, configure the network accordingly per the AGD. Verify that the client connection attempt is successful when

using the correct client credentials and that the connection is unsuccessful when incorrect authentication credentials are used.

- Test FMT\_SMF.1/LiFi:3: {Conditional: SSID is broadcasted} The evaluator shall configure the SSID to be broadcasted. Using a network sniffing tool, the evaluator shall capture a beacon frame and confirm that the SSID is included. The evaluator shall then configure the SSID to be hidden. Using a network sniffing tool, the evaluator shall capture a beacon frame and confirm that the SSID is not listed.

## FMT\_SMR\_EXT.1 No Administration from Client

### FMT\_SMR\_EXT.1.1

The TSF shall ensure that the ability to administer remotely the TOE from a wireless client shall be disabled by default.

## Evaluation Activities ▼

### *FMT\_SMR\_EXT.1*

#### **TSS**

There are no TSS evaluation activities for this component.

#### **Guidance**

The evaluator will review the operational guidance to ensure that it contains instructions for administering the TOE both locally and remotely, including any configuration that needs to be performed on the client for remote administration. The evaluator will confirm that the TOE does not permit remote administration from a wireless client by default.

#### **Tests**

The evaluator will demonstrate that after configuring the TOE for first use from the operational guidance, it is possible to establish an administrative session with the TOE on the “wired” portion of the device. They will then demonstrate that an identically configured wireless client that can successfully connect to the TOE cannot be used to perform administration.

## 5.2.6 Protection of the TSF (FPT)

### FPT\_ACF\_EXT.1 Access Controls

#### FPT\_ACF\_EXT.1.1

The TSF shall implement access controls which prohibit unprivileged users from modifying:

- Kernel and its drivers/modules
- Security audit logs
- Shared libraries
- System executables
- System configuration files
- [assignment: other objects]

## FPT\_ACF\_EXT.1.2

The TSS shall implement access controls which prohibit unprivileged users from reading:

- Security audit logs
- System-wide credential repositories
- [assignment: list of other objects]

**Application Note:** "Credential repositories" refer, in this case, to structures containing cryptographic keys or passwords.

## Evaluation Activities ▼

### FPT\_ACF\_EXT.1

#### TSS

The evaluator shall confirm that the TSS specifies the locations of kernel drivers/modules, security audit logs, shared libraries, system executables, and system configuration files. Every file does not need to be individually identified, but the system's conventions for storing and protecting such files must be specified.

There are no additional TSS evaluation activities for this component.

#### **Guidance**

There are no additional Guidance evaluation activities for this component.

There are no additional Guidance evaluation activities for this component.

#### **Tests**

The evaluator shall create an unprivileged user account. Using this account, the evaluator shall ensure that the following tests result in a negative outcome (i.e., the action results in the OS denying the evaluator permission to complete the action):

- Test FPT\_ACF\_EXT.1:1: The evaluator shall attempt to modify all kernel drivers and modules.
- Test FPT\_ACF\_EXT.1:2: The evaluator shall attempt to modify all security audit logs generated by the logging subsystem.
- Test FPT\_ACF\_EXT.1:3: The evaluator shall attempt to modify all shared libraries that are used throughout the system.
- Test FPT\_ACF\_EXT.1:4: The evaluator shall attempt to modify all system executables.
- Test FPT\_ACF\_EXT.1:5: The evaluator shall attempt to modify all system configuration files.
- Test FPT\_ACF\_EXT.1:6: The evaluator shall attempt to modify any additional components selected.

The evaluator shall create an unprivileged user account. Using this account, the evaluator shall ensure that the following tests result in a negative outcome (i.e., the action results in the OS denying the evaluator permission to complete the action):

- Test FPT\_ACF\_EXT.1:7: The evaluator shall attempt to read security audit logs generated by the auditing subsystem
- Test FPT\_ACF\_EXT.1:8: The evaluator shall attempt to read system-wide credential repositories
- Test FPT\_ACF\_EXT.1:9: The evaluator shall attempt to read any other object specified in the assignment

## FPT\_ASLR\_EXT.1 Address Space Layout Randomization

### FPT\_ASLR\_EXT.1.1

The T.S.F shall always randomize process address space memory locations with [selection: 8, [assignment: number greater than 8]] bits of entropy except for [assignment: list of explicit exceptions].

## Evaluation Activities ▼

### [FPT\\_ASLR\\_EXT.1](#)

#### **TSS**

The evaluator shall examine the TSS to verify that it identifies the number of entropy bits used for ASLR and what exceptions there are to this, if any.

#### **Guidance**

There are no additional Guidance evaluation activities for this component.

#### **Tests**

The evaluator shall select 3 executables included with the T.S.F. If the T.S.F includes a web browser it must be selected. If the T.S.F includes a mail client it must be selected. For each of these apps, the evaluator shall launch the same executables on two separate instances of the OS on identical hardware and compare all memory mapping locations. The evaluator shall ensure that no memory mappings are placed in the same location. If the rare chance occurs that two mappings are the same for a single executable and not the same for the other two, the evaluator shall repeat the test with that executable to verify that in the second test the mappings are different. This test can also be completed on the same hardware and rebooting between application launches.

## FPT\_FLS.1 Failure with Preservation of Secure State

### FPT\_FLS.1.1

The T.S.F shall preserve a secure state when the following types of failures occur: [DRBG self-test failure].

**Application Note:** The intent of this requirement is to ensure that cryptographic services requiring random bit generation cannot be performed if a failure of a self-test defined in FPT\_TST.1 occurs.

## Evaluation Activities ▼

### [FPT\\_FLS.1](#)

### ***TSS***

*The evaluator shall verify that the **TSS** describes how the **TOE** enters an error state in the event of a DRBG self-test failure.*

### ***Guidance***

*The evaluator shall verify that the guidance documentation describes the error state that results from a DRBG self-test failure and the actions that a user or administrator should take in response to attempt to resolve the error state.*

### ***Tests***

*There are no test activities for this component.*

## **FPT\_SBOP\_EXT.1 Stack Buffer Overflow Protection**

### **FPT\_SBOP\_EXT.1.1**

The **TSS** shall [**selection:** *employ stack-based buffer overflow protections, not store parameters or variables in the same data structures as control flow values*].

**Application Note:** Many OSES store control flow values (i.e. return addresses) in stack data structures that also contain parameters and variables. For these OSES, it is expected that most of the OS, to include the kernel, libraries, and application software from the OS vendor be compiled with stack-based buffer overflow protection enabled. OSES that store parameters and variables separately from control flow values do not need additional stack protections.

## **Evaluation Activities ▼**

### ***FPT\_SBOP\_EXT.1***

### ***TSS***

*The evaluator shall examine the **TSS** to verify that it describes how stack-based buffer overflow protection is implemented, or how the **TOE** is designed in such a way that these protections are not explicitly needed.*

### ***Guidance***

*There are no additional Guidance evaluation activities for this component.*

### ***Tests***

*For stack-based OSES, the evaluator shall determine that the **TSS** contains a description of stack-based buffer overflow protections used by the OS. These are referred to by a variety of terms. These include, but are not limited to, tagging, stack cookie, stack guard, and stack canaries. The **TSS** must include a rationale for any binaries that are not protected in this manner. The evaluator shall also preform the following test:*

*For OSES that store parameters/variables separately from control flow values, the evaluator shall verify that the **TSS** describes what data structures control values, parameters, and variables are stored. The evaluator shall also ensure that the **TSS** includes a description of the safeguards that ensure parameters and variables do not intermix with control flow values.*

## **FPT\_W^X\_EXT.1 Write XOR Execute Memory Pages**



#### FPT\_W^X\_EXT.1.1

The TSS shall prevent allocation of any memory region with both write and execute permissions except for [**assignment:** *list of exceptions*].

**Application Note:** Requesting a memory mapping with both write and execute permissions subverts the platform protection provided by DEP. If the OS provides no exceptions (such as for just-in-time compilation), then "no exceptions" should be indicated in the assignment. Full realization of this requirement requires hardware support, but this is commonly available.

### Evaluation Activities ▼

#### *FPT\_W^X\_EXT.1*

##### TSS

*The evaluator shall inspect the vendor-provided developer documentation and verify that no memory-mapping can be made with write and execute permissions except for the cases listed in the assignment.*

##### **Guidance**

*There are no additional Guidance evaluation activities for this component.*

##### **Tests**

*The evaluator shall also perform the following tests.*

- *Test FPT\_W^X\_EXT.1:1: The evaluator shall acquire or construct a test program which attempts to allocate memory that is both writable and executable. The evaluator shall run the program and confirm that it fails to allocate memory that is both writable and executable.*
- *Test FPT\_W^X\_EXT.1:2: The evaluator shall acquire or construct a test program which allocates memory that is executable and then subsequently requests additional write/modify permissions on that memory. The evaluator shall run the program and confirm that at no time during the lifetime of the process is the memory both writable and executable.*
- *Test FPT\_W^X\_EXT.1:3: The evaluator shall acquire or construct a test program which allocates memory that is writable and then subsequently requests additional execute permissions on that memory. The evaluator shall run the program and confirm that at no time during the lifetime of the process is the memory both writable and executable.*

## 5.2.7 TOE Access (FTA)

### FTA\_TSE.1 TOE Session Establishment

#### FTA\_TSE.1.1

The TSS shall be able to deny session establishment **of a wireless client session** based on [TOE *interface, time, day*, [**selection:** [**assignment:** *other attributes*], *no other attributes*]].

**Application Note:** The “TOE interface” can be specified in terms of the device in the TOE that the LiFi client is connecting to (e.g. specific LiFi APs). “Time” and “day” refer to time-of-day and day-of-week, respectively.

The assignment is to be used by the ST author to specify additional attributes on which denial of session establishment can be based.

### FTA\_TSE.1

#### TSS

The evaluator will examine the TSS to determine that all of the attributes on which a client session can be denied are specifically defined.

#### Guidance

The evaluator will examine the operational guidance to determine that it contains guidance for configuring each of the attributes identified in the TSS.

#### Tests

For each supported attribute, the evaluator will perform the following test:

- Test FTA\_TSE.1:1: The evaluator successfully establishes a client session with a wireless client. The evaluator then follows the operational guidance to configure the system so that the client's access is denied based on a specific value of the attribute. The evaluator will then attempt to establish a session in contravention to the attribute setting (for instance, the client is denied network access based upon the TOE interface that it is connecting to, or that the client is denied access based upon the time-of-day or day-of-week it is attempting connection on). The evaluator will observe that the access attempt fails.

## 5.2.8 Trusted Path/Channels (FTP)

### FTP\_ITC.1/8021X Inter-TSF Trusted Channel (802.1X)

#### FTP\_ITC.1.1/8021X

The TSF shall provide a communication channel **using IEEE 802.1X and [selection: IPsec, RADIUS over TLS]** between itself and **an 802.1X authentication server** that is logically distinct from other communication channels and provides assured identification of its end points and protection of the channel data from modification or disclosure.

**Application Note:** This requirement has been iterated from its definition in the NDcPP to mandate the communications protocols and environmental components that a LiFi AS must use for 802.1X. IPsec or RADIUS over TLS (commonly known as "RadSec") is required at least for communications with the 802.1X authentication server. The requirement implies that not only are communications protected when they are initially established, but also on resumption after an outage.

The IT entity of "802.1X authentication server" is distinct from "authentication server" as specified in FTP\_ITC.1 in the NDcPP because the latter may be used for administrator authentication rather than authorization of LiFi clients.

If IPsec is selected in FTP\_ITC.1.1, then FCS\_IPSEC\_EXT.1 from the NDcPP must be claimed. If RADIUS over TLS is selected in FTP\_ITC.1.1, then FCS\_RADSEC\_EXT.1 in this PP-Module must be claimed, as well as FCS\_TLSC\_EXT.1 from the Functional Package for TLS.

#### FTP\_ITC.1.2/8021X

The TSE shall permit [*the TSE*] to initiate communication via the trusted channel.

FTP\_ITC.1.3/8021X

The TSE shall initiate communication via the trusted channel for [802.1X authentication].

## Evaluation Activities ▼

### FTP\_ITC.1/8021X

*The evaluator will perform the following activities in addition to those required by the NDcPP:*

#### **TSS**

*The evaluator will examine the TSS to determine that, for all communications with authorized IT entities identified in the requirement, each communications mechanism is identified in terms of the allowed protocols for that IT entity. The evaluator will also confirm that all protocols listed in the TSS are specified and included in the requirements in the ST.*

#### **Guidance**

*The evaluator will confirm that the guidance documentation contains instructions for establishing the allowed protocols with each authorized IT entity and that it contains recovery instructions should a connection be unintentionally broken.*

#### **Tests**

*The evaluator will perform the following tests:*

- *Test FTP\_ITC.1/8021X:1: The evaluator will ensure that communications using each protocol with each authorized IT entity is tested during the course of the evaluation, setting up the connections as described in the guidance documentation and ensuring that communication is successful.*
- *Test FTP\_ITC.1/8021X:2: For each protocol that the TOE can initiate as defined in the requirement, the evaluator will follow the guidance documentation to ensure that the communication channel can be initiated from the TOE.*
- *Test FTP\_ITC.1/8021X:3: The evaluator will ensure, for each communication channel with an authorized IT entity, the channel data is not sent in plaintext.*
- *Test FTP\_ITC.1/8021X:4: The evaluator will, for each protocol associated with each authorized IT entity tested during test 1, physically interrupt an established connection. The evaluator will ensure that when physical connectivity is restored, communications are appropriately protected.*

## 5.3 TOE Security Functional Requirements Rationale

The following rationale provides justification for each SFR for the TOE, showing that the SFRs are suitable to address the specified threats:

**Table 4: SFR Rationale**

| Threat | Addressed by | Rationale |
|--------|--------------|-----------|
|--------|--------------|-----------|

|                      |                                              |                                                                                                                                                                                                                   |
|----------------------|----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| T.DATA_<br>INTEGRITY | FCS_CKM.1/WPA (implementation-dependent)     | Mitigates the threat by generating a secure key used to encrypt and protect wireless traffic using WPA.                                                                                                           |
|                      | FCS_CKM.2/DISTRIB (implementation-dependent) | Mitigates the threat by securely distributing 802.11 keys to clients so that they are not disclosed, maintaining the integrity of the data the key is used to protect.                                            |
|                      | FCS_CKM.2/GTK (implementation-dependent)     | Mitigates the threat by securely distributing group temporal keys to clients so that they are not disclosed, maintaining the integrity of the data the key is used to protect.                                    |
|                      | FCS_CKM.2/PMK (implementation-dependent)     | Mitigates the threat by securely receiving a key from an authentication server so that it is not disclosed, maintaining the integrity of the data the key is used to protect.                                     |
|                      | FCS_COP.1/LiFiDataEncryption                 | Mitigates the threat by defining implementation of secure cryptographic integrity algorithms.                                                                                                                     |
|                      | FTP_ITC.1/Client (implementation-dependent)  | Mitigates the threat by providing a secure channel for LiFi client traffic that protects the confidentiality and integrity of the data. <a href="#">update status of this if needed to resolve github comment</a> |
|                      | FTP_ITC.1/Gvlc (implementation-dependent)    | Mitigates the threat by providing a secure channel for LiFi client traffic that protects the confidentiality and integrity of the data.                                                                           |
| T.NETWORK_<br>ACCESS | FAU_GEN.1/LiFi                               | Mitigates the threat by generating audit data that will detect access to the network.                                                                                                                             |
|                      | FCS_RADSEC_EXT.1 (selection-based)           | Mitigates the threat by utilizing a secure RADIUS implementation to authenticate clients.                                                                                                                         |
|                      | FCS_RADSEC_EXT.2 (selection-based)           | Mitigates the threat by utilizing a secure TLS configuration for RADIUS over TLS.                                                                                                                                 |
|                      | FIA_PSK_EXT.1 (implementation-dependent)     | Mitigates the threat by defining the use of a PSK to authenticate clients.                                                                                                                                        |
|                      | FIA_UAU.6                                    | Mitigates the threat by re-authenticating users when specified criteria are met.                                                                                                                                  |
|                      | FMT_SMF.1/LiFi                               | Mitigates the threat by defining management functions that must be protected.                                                                                                                                     |
|                      | FMT_SMR_EXT.1                                | Mitigates the threat by preventing remote administration functions from being exercised from a wireless client.                                                                                                   |

|                      |                                              |                                                                                                                                            |
|----------------------|----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
|                      | FTA_TSE.1                                    | Mitigates the threat by denying sessions based on undesirable characteristics.                                                             |
|                      | FTP_ITC.1/8021X                              | Mitigates the threat by authenticating clients before allowing access to the controlled network.                                           |
| T.NETWORK_ATTACK     | FAU_GEN.1/LiFi                               | Mitigates the threat by generating audit data that will detect TSE failures.                                                               |
|                      | FPT_ACF_EXT.1                                | Mitigates the threat by limiting access that could be obtained on the system as a result of successful network attack.                     |
|                      | FPT_ASLR_EXT.1                               | Mitigates the threat by preventing network attacks that rely on predictable program memory layout.                                         |
|                      | FPT_SBOP_EXT.1                               | Mitigates the threat by preventing network attacks that rely on overwriting stack memory to execute arbitrary code.                        |
|                      | FPT_W^X_EXT.1                                | Mitigates the threat by preventing network attacks that rely on writing arbitrary executable code to memory and subsequently executing it. |
| T.NETWORK_DISCLOSURE | FCS_CKM.1/WPA (implementation-dependent)     | Mitigates the threat by utilizing a secure key generation function for WPA functionality.                                                  |
|                      | FCS_CKM.2/DISTRIB (implementation-dependent) | Mitigates the threat by securely distributing 802.11 keys to clients.                                                                      |
|                      | FCS_CKM.2/GTK (implementation-dependent)     | Mitigates the threat by securely distributing GTK keys to clients.                                                                         |
|                      | FCS_CKM.2/PMK (implementation-dependent)     | Mitigates the threat by securely receiving a key from an authentication server.                                                            |
|                      | FCS_COP.1/LiFiDataEncryption                 | Mitigates the threat by defining implementation of secure cryptographic confidentiality algorithms.                                        |
|                      | FCS_RADSEC_EXT.1 (selection-based)           | Mitigates the threat by utilizing a secure RADIUS implementation to authenticate clients.                                                  |
|                      | FCS_RADSEC_EXT.2 (selection-based)           | Mitigates the threat by utilizing a secure TLS configuration for RADIUS over TLS.                                                          |
|                      | FIA_UAU.6                                    | Mitigates the threat by re-authenticating users when specified criteria are met.                                                           |
|                      | FTA_TSE.1                                    | Mitigates the threat by denying sessions based on undesirable characteristics.                                                             |
|                      | FTP_ITC.1/8021X                              | Mitigates the threat by enforcing the use of authentication to access the network.                                                         |

|                 |                                              |                                                                                                                                                                                          |
|-----------------|----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                 | FTP_ITC.1/Client (implementation-dependent)  | Mitigates the threat by providing a secure channel for LiFi client traffic.                                                                                                              |
|                 | FTP_ITC.1/Gvlc (implementation-dependent)    | Mitigates the threat by providing a secure channel for LiFi client traffic. <a href="#">update status of this if needed to resolve github comment</a>                                    |
| T.REPLAY_ATTACK | FCS_CKM.1/WPA (implementation-dependent)     | Mitigates the threat by utilizing a secure key generation function for WPA functionality that is not subject to replay or guessing.                                                      |
|                 | FCS_CKM.2/DISTRIB (implementation-dependent) | Mitigates the threat by securely distributing 802.11 keys to clients so that they are not disclosed, maintaining confidentiality and preventing replay.                                  |
|                 | FCS_CKM.2/GTK (implementation-dependent)     | Mitigates the threat by securely distributing GTK keys to clients so that they are not disclosed, maintaining confidentiality and preventing replay.                                     |
|                 | FCS_CKM.2/PMK (implementation-dependent)     | Mitigates the threat by securely receiving a key from an authentication server so that it is not disclosed, maintaining confidentiality and preventing replay.                           |
|                 | FCS_COP.1/LiFiDataEncryption                 | Mitigates the threat by defining implementation of secure cryptographic integrity algorithms that prevent the disclosure of data that would be potentially suitable for replay attempts. |
|                 | FCS_RADSEC_EXT.1 (selection-based)           | Mitigates the threat by utilizing a secure RADIUS implementation to authenticate clients, which protects authentication data from replay attacks.                                        |
|                 | FCS_RADSEC_EXT.2 (selection-based)           | Mitigates the threat by utilizing a secure TLS configuration for RADIUS over TLS, which provides protection against replay and data modification.                                        |
|                 | FIA_UAU.6                                    | Mitigates the threat by re-authenticating users when specified criteria are met, which can include if a specified time has passed or other indicators of stale authentication data.      |
|                 | FTA_TSE.1                                    | Mitigates the threat by denying sessions based on undesirable characteristics, which can include a detection of replay or other indicators of stale authentication data.                 |
|                 | FTP_ITC.1/8021X                              | Mitigates the threat by authenticating clients before allowing access to the controlled network and preventing replay of previous authentication sessions.                               |

[FTP\\_ITC.1/Client](#) (implementation-dependent)

Mitigates the threat by providing a secure channel for LiFi client traffic that prevents the use of replayed data.

[FTP\\_ITC.1/Gvlc](#) (implementation-dependent)

Mitigates the threat by providing a secure channel for LiFi client traffic that prevents the use of replayed data.

# 6 Consistency Rationale

## 6.1 Protection Profile for Network Device

### 6.1.1 Consistency of TOE Type

When this PP-Module extends the NDcPP, the TOE type for the overall TOE is still a network device. This PP-Module just defines the TOE as a specific type of network device with functional capabilities distinct to that type.

### 6.1.2 Consistency of Security Problem Definition

Table 5: Consistency of Security Problem Definition (ND PP base)

| PP-Module Threat, Assumption, OSP | Consistency Rationale                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| T.DATA_INTEGRITY                  | This threat is a specific type of failure that may result from successful exploitation of the T.WEAK_CRYPTOGRAPHY threat defined by the Base-PP. It is an extension of the Base-PP threat for communications that are specific to this PP-Module.                                                                                                                                                                                                                                                                                               |
| T.NETWORK_ACCESS                  | This threat extends the security problem defined by the Base-PP to include the threat of a malicious entity in an untrusted network interacting with a protected entity in a trusted network. This is not addressed in the Base-PP because not all network devices are responsible for facilitating communications between separate networks.                                                                                                                                                                                                   |
| T.NETWORK_ATTACK                  | This threat extends the security problem defined by the Base-PP to define a specific manifestation of T.SECURITY_FUNCTIONALITY_FAILURE.                                                                                                                                                                                                                                                                                                                                                                                                         |
| T.NETWORK_DISCLOSURE              | This threat extends the security problem defined by the Base-PP to include the threat of a malicious entity in an untrusted network interacting with a protected entity in a trusted network. This is not addressed in the Base-PP because not all network devices are responsible for facilitating communications between separate networks. This threat is also consistent with the T.UNTRUSTED_COMMUNICATION_CHANNELS threat defined by the Base-PP because compromise of data in transit is one potential way this threat may be exploited. |
| T.REPLAY_ATTACK                   | This threat is a specific type of failure that may result from successful exploitation of the T.UNAUTHORIZED_ADMINISTRATOR_ACCESS and T.UNTRUSTED_COMMUNICATIONS_CHANNELS threats defined by the Base-PP. It is an extension of the Base-PP threat for communications that are specific to this PP-Module.                                                                                                                                                                                                                                      |
| A.MANAGED_CONFIG                  | This is consistent with A.TRUSTED_ADMINISTRATOR in the Base-PP by defining specific mechanisms by which the trusted administrator is defined.                                                                                                                                                                                                                                                                                                                                                                                                   |



|                                 |                                                                                                                                                                                                                                                                           |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>A.NETWORK_CONNECTIVITY</b>   | This is consistent with the <del>Base-PP</del> because a network device inherently requires network connectivity and the <del>Base-PP</del> similarly does not treat external entities as automatically trusted (hence the use of trusted channels to authenticate them). |
| <b>A.NON_SECURITY_FUNCTIONS</b> | This is consistent with the <del>Base-PP</del> because the notion of exact <del>PP</del> conformance accepts the case where non-TSF functionality exists within the physical boundary of the <del>TOE</del> if there are no <del>PP</del> requirements to evaluate it.    |
| <b>A.PROPER_USER</b>            | This is consistent with the expectations of A.TRUSTED_ADMINISTRATOR in the <del>Base-PP</del> by defining administrators as non-hostile but allowing for the possibility of unintentional error.                                                                          |
| <b>A.THIRD_PARTY_SOFTWARE</b>   | This is consistent with the <del>Base-PP</del> because the existence of a trusted update mechanism allows for the possibility that the <del>TOE</del> may have implementation flaws in need of fixing.                                                                    |

### 6.1.3 Consistency of OE Objectives

**Table 6: Consistency of OE Objectives (ND ~~PP~~ base)**

| <del>PP-Module</del> <b>OE Objective</b> | <b>Consistency Rationale</b>                                                                                                                                                                                                                                              |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>OE.MANAGED_CONFIG</b>                 | This is consistent with A.TRUSTED_ADMINISTRATOR in the <del>Base-PP</del> by defining specific mechanisms by which the trusted administrator is defined.                                                                                                                  |
| <b>OE.NETWORK_CONNECTIVITY</b>           | This is consistent with the <del>Base-PP</del> because a network device inherently requires network connectivity and the <del>Base-PP</del> similarly does not treat external entities as automatically trusted (hence the use of trusted channels to authenticate them). |
| <b>OE.NON_SECURITY_FUNCTIONS</b>         | This is consistent with the <del>Base-PP</del> because the notion of exact <del>PP</del> conformance accepts the case where non-TSF functionality exists within the physical boundary of the <del>TOE</del> if there are no <del>PP</del> requirements to evaluate it.    |
| <b>OE.PROPER_USER</b>                    | This is consistent with the expectations of A.TRUSTED_ADMINISTRATOR in the <del>Base-PP</del> by defining administrators as non-hostile but allowing for the possibility of unintentional error.                                                                          |
| <b>OE.THIRD_PARTY_SOFTWARE</b>           | This is consistent with the <del>Base-PP</del> because the existence of a trusted update mechanism allows for the possibility that the <del>TOE</del> may have implementation flaws in need of fixing.                                                                    |

### 6.1.4 Consistency of Requirements

This ~~PP-Module~~ identifies several ~~SFRs~~ from the ND ~~PP~~ that are needed to support LiFi Access System functionality. This is considered to be consistent because the functionality provided by the ND ~~PP~~ is being used for its intended purpose. The rationale for why this does not conflict with the claims defined by the ND ~~PP~~ are as follows:

**Table 7: Consistency of Requirements (ND PP base)**

| PP-Module Requirement                                                       | Consistency Rationale                                                                                                                                                |
|-----------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Modified SFRs</b>                                                        |                                                                                                                                                                      |
| This PP-Module does not modify any requirements when the ND PP is the base. |                                                                                                                                                                      |
| <b>Additional SFRs</b>                                                      |                                                                                                                                                                      |
| This PP-Module does not add any requirements when the ND PP is the base.    |                                                                                                                                                                      |
| <b>Mandatory SFRs</b>                                                       |                                                                                                                                                                      |
| FAU_GEN.1/LiFi                                                              | This SFR iterates the FAU_GEN.1 SFR defined in the Base-PP to define auditable events for the functionality that is specific to this PP-Module.                      |
| FCS_COP.1/LiFiDataEncryption                                                | This SFR defines cryptographic behavior for functions outside the scope of what the Base-PP originally defined.                                                      |
| FIA_8021X_EXT.1                                                             | This SFR defines support for 802.1X communications, which is a logical interface that extends the scope of what the Base-PP originally defined.                      |
| FIA_UAU.6                                                                   | This SFR defines support for re-authentication of wireless users, which are a type of subject beyond the scope of what the Base-PP originally defined.               |
| FMT_SMF.1/LiFi                                                              | This SFR defines additional management functionality that is specific to the Module's product type and would therefore not be expected to be present in the Base-PP. |
| FMT_SMR_EXT.1                                                               | This SFR specifies that remote administration occurs over a dedicated channel, which does not conflict with the Base-PP.                                             |
| FPT_ACF_EXT.1                                                               |                                                                                                                                                                      |
| FPT_ASLR_EXT.1                                                              |                                                                                                                                                                      |
| FPT_FLS.1                                                                   |                                                                                                                                                                      |
| FPT_SBOP_EXT.1                                                              |                                                                                                                                                                      |
| FPT_W^X_EXT.1                                                               |                                                                                                                                                                      |
| FTA_TSE.1                                                                   |                                                                                                                                                                      |
| FTP_ITC.1/8021X                                                             | This SFR iterates the FTP_ITC.1 SFR defined in the Base-PP to define trusted communication channels for the functionality that is specific to this PP-Module.        |
| <b>Optional SFRs</b>                                                        |                                                                                                                                                                      |
| This PP-Module does not define any Optional requirements.                   |                                                                                                                                                                      |
| <b>Objective SFRs</b>                                                       |                                                                                                                                                                      |
| This PP-Module does not define any Objective requirements.                  |                                                                                                                                                                      |

### Implementation-dependent SFRs

|                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">FCS_CKM.1/WPA</a>     | This SFR defines additional cryptographic functionality not defined in the <del>Base-PP</del> , but it implements this using the DRBG mechanism already defined in the <del>Base-PP</del> .                                                                                                                                                                                                                                               |
| <a href="#">FCS_CKM.2/GTK</a>     | This SFR defines additional cryptographic functionality not defined in the <del>Base-PP</del> that is used for functionality outside the original scope of the <del>Base-PP</del> .                                                                                                                                                                                                                                                       |
| <a href="#">FCS_CKM.2/PMK</a>     | This SFR defines additional cryptographic functionality not defined in the <del>Base-PP</del> that is used for functionality outside the original scope of the <del>Base-PP</del> .                                                                                                                                                                                                                                                       |
| <a href="#">FIA_PSK_EXT.1</a>     | This SFR defines parameters for pre-shared key generation. The <del>Base-PP</del> supports pre-shared keys as a potential authentication method for IPsec. This <del>PP-Module</del> does not prevent this from being used but does define restrictions on how pre-shared keys may be generated and what constitutes an acceptable key. This may also be used for RadSec, which is outside the original scope of the <del>Base-PP</del> . |
| <a href="#">FTP_ITC.1/Client</a>  | This SFR iterates the FTP_ITC.1 SFR defined in the <del>Base-PP</del> to define trusted communication channels for the functionality that is specific to this <del>PP-Module</del> .                                                                                                                                                                                                                                                      |
| <a href="#">FCS_CKM.2/DISTRIB</a> | This SFR defines an additional use for the cryptographic and self-protection mechanisms defined in the <del>Base-PP</del> .                                                                                                                                                                                                                                                                                                               |
| <a href="#">FTP_ITC.1/Gvlc</a>    | This SFR iterates the FTP_ITC.1 SFR defined in the <del>Base-PP</del> to define trusted communication channels for the functionality that is specific to this <del>PP-Module</del> .                                                                                                                                                                                                                                                      |

### Selection-based SFRs

|                                  |                                                                                                                                                                                                                                                                                                                                              |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">FCS_RADSEC_EXT.1</a> | This SFR defines the implementation of RadSec and the peer authentication method that it uses. This relies on the <del>TLS</del> requirements defined by the <del>Base-PP</del> and may also use the X.509v3 certificate validation methods specified in the <del>Base-PP</del> , depending on the selected peer authentication method.      |
| <a href="#">FCS_RADSEC_EXT.2</a> | This SFR defines the implementation of RadSec when pre-shared key authentication is used. This functionality is outside the original scope of the <del>Base-PP</del> , but it relies on the <del>TLS</del> client protocol implementation, cryptographic algorithms, and random bit generation functions defined by the <del>Base-PP</del> . |

# Appendix A - Optional SFRs

## A.1 Strictly Optional Requirements

This PP-Module does not define any Strictly Optional SFRs or SARs.

## A.2 Objective Requirements

This PP-Module does not define any Objective SFRs.

## A.3 Implementation-dependent Requirements

### A.3.1 Auditable Events for Implementation-Dependent SFRs

Table 8: Auditable Events for Implementation-dependent Requirements

| Requirement                       | Auditable Events                                                       | Additional Audit Record Contents                      |
|-----------------------------------|------------------------------------------------------------------------|-------------------------------------------------------|
| <a href="#">FCS_CKM.1/WPA</a>     | No events specified                                                    | N/A                                                   |
| <a href="#">FCS_CKM.2/DISTRIB</a> | No events specified                                                    | N/A                                                   |
| <a href="#">FCS_CKM.2/GTK</a>     | No events specified                                                    | N/A                                                   |
| <a href="#">FCS_CKM.2/PMK</a>     | No events specified                                                    | N/A                                                   |
| <a href="#">FIA_PSK_EXT.1</a>     | No events specified                                                    | N/A                                                   |
| <a href="#">FTP_ITC.1/Client</a>  | Failed attempts to establish a trusted channel (including IEEE 802.11) | Identification of the initiator and target of channel |
|                                   | Detection of modification of channel data                              | Identification of the initiator and target of channel |
| <a href="#">FTP_ITC.1/Gvlc</a>    | Failed attempts to establish a trusted channel                         | Identification of the initiator and target of channel |
|                                   | Detection of modification of channel data                              | Identification of the initiator and target of channel |

### A.3.2 SFRs for 802.11bb Implementations

**FCS\_CKM.1/WPA Cryptographic Key Generation (Symmetric Keys for WPA2 Connections)**

***This component must be included in the ST if the TQE implements any of the following features:***

- ***802.11bb Support***

#### FCS\_CKM.1.1/WPA

The TSE shall generate **symmetric** cryptographic keys in accordance with a specified cryptographic key generation algorithm [**selection:** *Cryptographic Key Generation Algorithm*] and specified cryptographic key sizes [**selection:** *Cryptographic Key Sizes*] that meet the following: [**selection:** *List of standards*]

The following table provides the allowable choices for completion of the selection operations of FCS\_CKM.1/WPA. At minimum, PRF-384 must be selected.

**Table 9: Allowable Choices for FCS\_CKM.1/WPA**

| Identifier | Cryptographic Key Generation Algorithm                                                              | Cryptographic Key Sizes | List of standards                    |
|------------|-----------------------------------------------------------------------------------------------------|-------------------------|--------------------------------------|
| PRF-384    | Pseudorandom Function using a random bit generator as specified in FCS_RBG.1 (from <u>Base-PP</u> ) | 384 bits                | IEEE 802.11-2020                     |
| PRF-512    | Pseudorandom Function using a random bit generator as specified in FCS_RBG.1 (from <u>Base-PP</u> ) | 512 bits                | IEEE 802.11-2020                     |
| PRF-704    | Pseudorandom Function using a random bit generator as specified in FCS_RBG.1 (from <u>Base-PP</u> ) | 704 bits                | IEEE 802.11-2020, IEEE 802.11ax-2021 |

**Application Note:** The cryptographic key derivation algorithm required by IEEE 802.11-2020 (Section 12.7.1.2) and verified in WPA2 certification is PRF-384, which uses the HMAC-SHA-1 function and outputs 384 bits. The use of GCMP is defined in IEEE 802.11ax-2021 (Section 12.5.5) and requires a Key Derivation Function (KDF) based on HMAC-SHA-256 (for 128-bit symmetric keys) or HMAC-SHA-384 (for 256-bit symmetric keys). This KDF outputs 704 bits.

This requirement applies only to the keys that are generated or derived for the communications between the AP and the client once the client has been authenticated. It refers to the derivation of the Group Temporal Key (GTK), through the Random Bit Generator (RBG) specified in this PP-Module, as well as the derivation of the Pairwise Transient Key (PTK) from the Pairwise Master Key (PMK), which is done using a random value generated by the RBG specified in this PP-Module, the HMAC function as specified in this PP-Module, as well as other information. This is specified in IEEE 802.11-2020, primarily in chapter 12. FCS\_RBG.1 is defined in the NDcPP.

#### Evaluation Activities ▼

The cryptographic primitives will be verified through evaluation activities specified elsewhere in this ~~PP-Module~~. The evaluator will verify that the ~~TSS~~ describes how the primitives defined and implemented by this ~~PP-Module~~ are used by the ~~TOE~~ in establishing and maintaining secure connectivity to the wireless clients. This description will include how the ~~GTK~~ and ~~PTK~~ are generated or derived. The ~~TSS~~ will also provide a description of the developer's methods of assuring that their implementation conforms to the cryptographic standards; this includes not only testing done by the developing organization, but also proof of third-party testing that is performed (e.g. WPA2 certification). The evaluator will ensure that the description of the testing methodology is of sufficient detail to determine the extent to which the details of the protocol specifics are tested.

### **Guidance**

There are no guidance evaluation activities for this component.

### **Tests**

The evaluator will perform the following test using a packet sniffing tool to collect frames between the ~~TOE~~ and a wireless client:

Step 1: The evaluator will identify the channel used by the ~~TOE~~ and configure the sniffer to sniff only on that channel (i.e., lock the sniffer on the selected channel). The sniffer should also be configured to filter on the ~~MAC~~ address of the ~~TOE~~ and client.

Step 2: The evaluator will configure the ~~TOE~~ to communicate with a LiFi client using IEEE 802.11-2020 and a 256-bit (64 hex values 0-f) pre-shared key, setting up the connections as described in the operational guidance. The pre-shared key is only used for testing.

Step 3: The evaluator will start the sniffing tool, initiate a connection between the ~~TOE~~ and LiFi client, and allow the ~~TOE~~ to authenticate, associate, and successfully complete the four-way handshake with the client.

Step 4: The evaluator will set a timer for one minute, at the end of which the evaluator will disconnect the client from the ~~TOE~~ and stop the sniffer.

Step 5: The evaluator will identify the four-way handshake frames (denoted EAPOL-key in Wireshark captures) and derive the ~~PTK~~ from the four-way handshake frames and pre-shared key as specified in IEEE 802.11-2020.

Step 6: The evaluator will select the first data frame from the captured packets that was sent between the client and ~~TOE~~ after the four-way handshake successfully completed and without the frame control value 0x4208 (the first two bytes are 08 42). The evaluator will use the ~~PTK~~ to decrypt the data portion of the packet as specified in IEEE 802.11-2020 and verify that the decrypted data contains ASCII-readable text.

Step 7: The evaluator will repeat Step 6 for the next two data frames between the ~~TOE~~ and client, and without frame control value 0x4208.

Additionally, the evaluator will test the PRF function using the test vectors from:

- Section 2.4 "The PRF Function – PRF (key, prefix, data, length)" of the IEEE 802.11-02/362r6 document "Proposed Test vectors for IEEE 802.11 TGi" dated September 10, 2002
- Annex J.3 "PRF reference implementation and test vectors" of IEEE 802.11-2020

***This component must be included in the ST if the TOE implements any of the following features:***

- ***802.11bb Support***

#### FCS\_CKM.2.1/GTK

The TSE shall distribute **Group Temporal Key (GTK)** in accordance with a specified cryptographic key distribution method: [**selection:** AES Key Wrap in an EAPOL-Key frame, AES Key Wrap with Padding in an EAPOL-Key frame] that meets the following: [NIST SP 800-38F, IEEE 802.11-2020 for the packet format and timing considerations] **and does not expose the cryptographic keys.**

**Application Note:** This requirement applies to the Group Temporal Key (GTK) that is generated by the TOE for use in broadcast and multicast messages to clients to which it is connected. 802.11-2020 specifies the format for the transfer as well as the fact that it must be wrapped by the AES Key Wrap method specified in NIST SP 800-38F.

#### Evaluation Activities ▼

##### FCS\_CKM.2/GTK

##### TSS

The evaluator will check the TSS to ensure that it describes how the GTK is wrapped prior to being distributed using the AES implementation specified in this PP-Module, and also how the GTKs are distributed when multiple clients connect to the TOE.

##### **Guidance**

There are no guidance evaluation activities for this component.

##### **Tests**

The evaluator will perform the following test using a packet sniffing tool to collect frames between a wireless client and the TOE (which may be performed in conjunction with the evaluation activity for FCS\_CKM.1/PMK).

To fully test the broadcast and multicast functionality, these steps will be performed as the evaluator connects multiple clients to the TOE. The evaluator will ensure that GTKs established are sent to the appropriate participating clients.

Step 1: The evaluator will identify the channel used by the TOE and configure the sniffer to sniff only on that channel (i.e., lock the sniffer on the selected channel). The sniffer should also be configured to filter on the MAC address of the TOE and client.

Step 2: The evaluator will configure the TOE to communicate with the client using IEEE 802.11-2020 and a 256-bit (64 hex values 0-f) pre-shared key, setting up the connections as described in the operational guidance. The pre-shared key is only used for testing.

Step 3: The evaluator will start the sniffing tool, initiate a connection between the TOE and client, and allow the client to authenticate, associate and successfully complete the four-way handshake with the TOE.

Step 4: The evaluator will set a timer for one minute, at the end of which the evaluator will disconnect the TOE from the client and stop the sniffer.

Step 5: The evaluator will identify the four-way handshake frames (denoted EAPOL-key in Wireshark captures) and derive the PTK and GTK from the four-way handshake frames and pre-shared key as specified in IEEE 802.11-2020.

Step 6: The evaluator will select the first data frame from the captured packets that was sent between the TOE and client after the four-way handshake successfully completed, and with the frame control value 0x4208 (the first two bytes are 08 42). The evaluator will use the GTK to decrypt the data portion of the selected packet as specified in IEEE 802.11-2020 and verify that the decrypted data contains ASCII-readable text.

Step 7: The evaluator will repeat Step 6 for the next two data frames with frame control value 0x4208.

The evaluator will also perform the following testing based on the supported GTK distribution methods:

AES Key Wrap (AES-KW Tests)

AES Key Wrap with Padding (AES-KWP Tests)

## FCS\_CKM.2/PMK Cryptographic Key Distribution (PMK)

*This component must be included in the ST if the TOE implements any of the following features:*

- **802.11bb Support**

### FCS\_CKM.2.1/PMK

The TSE shall **receive the 802.11 Pairwise Master Key (PMK)** in accordance with a specified cryptographic key distribution method: [from 802.1X Authorization Server] that meets the following: [IEEE 802.11-2020] **and does not expose the cryptographic keys.**

**Application Note:** This requirement applies to the Pairwise Master Key that is received from the RADIUS server by the TOE. The intent of this requirement is to ensure conformant TOEs implement 802.1X authentication prior to establishing secure communications with the client. The intent is that any LiFi AS product evaluated against this PP-Module will support both WPA2-Enterprise and WPA3-Enterprise at a minimum and certificate-based authentication mechanisms and therefore disallows implementations that support only pre-shared keys. Because communications with the RADIUS server are required to be performed over a protected connection, the transfer of the PMK will be protected.

## Evaluation Activities ▼

### FCS\_CKM.2/PMK

#### TSS

The evaluator will examine the TSS to determine that it describes how the PMK is transferred (that is, through what EAP attribute) to the TOE.

#### Guidance



*There are no guidance evaluation activities for this component.*

### Tests

*The evaluator will establish a session between the T.O.E and a RADIUS server according to the configuration guidance provided. The evaluator will then examine the traffic that passes between the RADIUS server and the T.O.E during a successful attempt to connect a wireless client to the T.O.E to determine that the P.M.K is not exposed.*

## FIA\_PSK\_EXT.1 Pre-Shared Key Composition

***This component must be included in the S.T if any of the following S.F.R.s are included:***

- [FCS\\_RADSEC\\_EXT.1](#)

### FIA\_PSK\_EXT.1.1

The T.S.F shall be able to use pre-shared keys for [**selection:** *RADIUS over TLS (RadSec), IPsec, WPA3-SAE, WPA3-SAE-PK, IEEE 802.11 WPA2-PSK, [assignment: other protocols that use pre-shared keys]*].

### FIA\_PSK\_EXT.1.2

The T.S.F shall be able to accept text-based pre-shared keys that:

- are 22 characters and [**selection:** *[assignment: other supported lengths]*, *no other lengths*] ;
- are composed of any combination of upper and lower case letters, numbers, and special characters (that include: “!”, “@”, “#”, “\$”, “%”, “^”, “&”, “\*”, “(”, and “)”).

### FIA\_PSK\_EXT.1.3

The T.S.F shall be able to [**selection:** *accept, generate using the random bit generator specified in FCS\_RBG.1*] bit-based pre-shared keys.

**Application Note:** This requirement must be included if IPsec or another protocol that uses pre-shared keys is claimed, and pre-shared key authentication is selected (e.g., "Pre-shared Keys" is selected in FCS\_IPSEC\_EXT.1.13 or "pre-shared keys" is selected in [FCS\\_RADSEC\\_EXT.1.2](#)). The intent of this requirement is that all protocols will support both text-based and bit-based pre-shared keys.

For the length of the text-based pre-shared keys, a common length (22 characters) is required to help promote interoperability. If other lengths are supported, they should be listed in the assignment; this assignment can also specify a range of values (e.g., "lengths from 5 to 55 characters") as well.

For [FIA\\_PSK\\_EXT.1.3](#), the S.T author specifies whether the T.S.F merely accepts bit-based pre-shared keys or is capable of generating them. If it generates them, the requirement specifies that they must be generated using the RBG provided by the T.O.E.

## Evaluation Activities ▼

## **TSS**

The evaluator will verify that the TSS describes

1. the protocols that can use pre-shared keys and that these are consistent with the selections made in [FIA\\_PSK\\_EXT.1.1](#).
2. the allowable values for pre-shared keys and that they are consistent with the selections made in [FIA\\_PSK\\_EXT.1.2](#).
3. the way bit-based pre-shared keys are procured and that it is consistent with the selections made in [FIA\\_PSK\\_EXT.1.3](#).

## **Guidance**

The evaluator will examine the operational guidance to determine that it provides guidance to administrators on the composition of strong text-based pre-shared keys, and (if the selection indicates keys of various lengths can be entered) that it provides information on the range of lengths supported. The guidance must specify the allowable characters for pre-shared keys, and that list must be a superset of the list contained in [FIA\\_PSK\\_EXT.1.2](#).

The evaluator will confirm the operational guidance contains instructions for either entering bit-based pre-shared keys for each protocol identified in the requirement or for generating a bit-based pre-shared key (or both).

## **Tests**

The evaluator will also perform the following tests for each protocol (or instantiation of a protocol, if performed by a different implementation on the TOE). Note that one or more of these tests can be performed with a single test case.

- Test FIA\_PSK\_EXT.1:1: The evaluator will compose a pre-shared key of 22 characters that contains a combination of the allowed characters in accordance with the operational guidance and demonstrates that a successful protocol negotiation can be performed with the key.
- Test FIA\_PSK\_EXT.1:2: [conditional]: If the TOE supports pre-shared keys of multiple lengths, the evaluator will repeat Test 1 using the minimum length; the maximum length; a length inside the allowable range; and invalid lengths beyond the supported range (both higher and lower). The minimum, maximum, and included length tests should be successful, and the invalid lengths must be rejected by the TOE.
- Test FIA\_PSK\_EXT.1:3: [conditional]: If the TOE does not generate bit-based pre-shared keys, the evaluator will obtain a bit-based pre-shared key of the appropriate length and enter it according to the instructions in the operational guidance. The evaluator will then demonstrate that a successful protocol negotiation can be performed with the key.
- Test FIA\_PSK\_EXT.1:4: [conditional]: If the TOE does generate bit-based pre-shared keys, the evaluator will generate a bit-based pre-shared key of the appropriate length and use it according to the instructions in the operational guidance. The evaluator will then demonstrate that a successful protocol negotiation can be performed with the key.

## **FTP\_ITC.1/Client Inter-TSF Trusted Channel (LiFi 802.11 Client Access)**

**This component must be included in the ST if the TOE implements any of the following features:**

- **[802.11bb Support](#)**

FTP\_ITC.1.1/Client

Do we need something similar for G.vlc? There was no equivalent to this in the Word doc requirements. Just checking as to whether anything is missing.

The T.SF shall provide a communication channel **using WPA3-Enterprise, WPA2-Enterprise, and [selection: WPA3-SAE, WPA3-SAE-PK, WPA2-PSK, no other mode] as defined by IEEE 802.11-2020** to provide a trusted channel between itself and **LiFi clients** that is logically distinct from other communication channels and provides assured identification of its end points and protection of the channel data from modification or disclosure.

**Application Note:** This requirement has been iterated from its definition in the NDcPP to mandate support for 802.11 specifically for LiFi client access.

FTP\_ITC.1.2/Client

The T.SF shall permit [*LiFi clients*] to initiate communication via the trusted channel.

FTP\_ITC.1.3/Client

The T.SF shall initiate communication via the trusted channel for [*no services*].

## Evaluation Activities ▼

### *FTP\_ITC.1/Client*

*This component is adequately evaluated when performing the evaluation activities for FTP\_ITC.1 in the , version base-PP. The evaluator shall repeat the tests from that SFR for each claimed LiFi communications channel.*

## A.3.3 SFRs for Distributed TOE Implementations

### FCS\_CKM.2/DISTRIB Cryptographic Key Distribution (802.11 Keys)

*This component must be included in the ST if the TOE implements any of the following features:*

- *Distributed TOE*

FCS\_CKM.2.1/DISTRIB

The T.SF shall distribute **IEEE 802.11** keys in accordance with a specified cryptographic key distribution method [**assignment:** *trusted channel protocol specified in FPT\_ITT.1 (from Base-PP)*] that meets the following: [**assignment:** *applicable standards as referenced by the distribution method specified in the Base-PP*].

**Application Note:** This SFR is required for use in distributed TOEs that support 802.11bb for distribution of keys to access nodes. G.Vlc TOEs will not claim this as they are used for point-to-point communications and do not have a distributed architecture.

If claimed, this requirement applies to any key necessary for successful IEEE 802.11 connections not covered by [FCS\\_CKM.2/GTK](#). In cases where a key must be distributed to other APs, this communication must be performed via a mechanism of commensurate cryptographic strength. Because communications with any

component of a distributed TOE are required to be performed over a trusted connection, the transfer of these keys will be protected.

## Evaluation Activities ▼

### FCS\_CKM.2/DISTRIB

#### TSS

*The evaluator will examine the TSS to determine that it describes which keys are distributed outside the TOE, where they are sent, and the purpose for this transfer.*

#### **Guidance**

*If this function is dependent on TOE configuration, the evaluator will confirm that the operational guidance contains instructions for how to configure that the keys are adequately protected.*

#### **Tests**

*This requirement will be tested in conjunction with the tests for the cryptographic primitives, the secure protocols, and FPT\_ITT.1 (Base\_PP).*

## A.3.4 SFRs for G.vlc Implementations

### FTP\_ITC.1/Gvlc Inter-TSF Trusted Channel (MACsec)

*This component must be included in the ST if the TOE implements any of the following features:*

- G.vlc Support

#### FTP\_ITC.1.1/Gvlc

The TSF shall provide a communication channel **for G.vlc using MACsec** to provide a trusted channel between itself and **a MACsec peer** that is logically distinct from other communication channels and provides assured identification of its end points and protection of the channel data from modification or disclosure.

**Application Note:** This requirement has been iterated from its definition in the NDcPP to mandate support for MACsec.

#### FTP\_ITC.1.2/Gvlc

The TSF shall permit [**selection: the TSF, a MACsec peer**] to initiate communication via the trusted channel.

#### FTP\_ITC.1.3/Gvlc

The TSF shall initiate communication via the trusted channel for [*communications with MACsec peers that require the use of MACsec*].

## Evaluation Activities ▼

### FTP\_ITC.1/Gvlc

*G.vlc is implemented using MACsec. To demonstrate the implementation of G.vlc, the evaluator shall apply the test activities for FCS\_MACSEC\_EXT.1, FCS\_MACSEC\_EXT.2, FCS\_MACSEC\_EXT.3, and FCS\_MACSEC\_EXT.4 as defined in the PP-Module for MACsec Ethernet Encryption.*

# Appendix B - Selection-based Requirements

## B.1 Auditable Events for Selection-based SFRs

Table 10: Auditable Events for Selection-based Requirements

| Requirement                      | Auditable Events    | Additional Audit Record Contents |
|----------------------------------|---------------------|----------------------------------|
| <a href="#">FCS_RADSEC_EXT.1</a> | No events specified | N/A                              |
| <a href="#">FCS_RADSEC_EXT.2</a> | No events specified | N/A                              |

## B.2 Cryptographic Support (FCS)

### FCS\_RADSEC\_EXT.1 RadSec

*The inclusion of this selection-based component depends upon selection in [FTP\\_ITC.1.1/8021X](#).*

#### FCS\_RADSEC\_EXT.1.1

The TSSF shall implement RADIUS over TLS as specified in RFC 6614 to communicate securely with a RADIUS server.

#### FCS\_RADSEC\_EXT.1.2

The TSSF shall perform peer authentication using [**selection:** X.509v3 certificates, pre-shared keys].

**Application Note:** This SFR is applicable if "RADIUS over TLS" is selected in FTP\_ITC.1.1.  
If X.509v3 certificates is selected in [FCS\\_RADSEC\\_EXT.1.2](#), then FCS\_TLSC\_EXT.1 from the Functional Package for TLS must be claimed and "mutual authentication" must be selected in FCS\_TLSC\_EXT.1.1. If pre-shared keys is selected in [FCS\\_RADSEC\\_EXT.1.2](#), then [FCS\\_RADSEC\\_EXT.2](#) and [FIA\\_PSK\\_EXT.1](#) in this PP-Module must be claimed.

### Evaluation Activities ▼

[FCS\\_RADSEC\\_EXT.1](#)  
**TSS**  
*The evaluator will verify that the TSS description includes the use of RADIUS over TLS, as described in RFC 6614.*  
*If X.509v3 certificates is selected, the evaluator will ensure that the TSS description includes the use of client-side certificates for TLS mutual authentication.*

### Guidance

The evaluator will verify that any configuration necessary to meet the requirement must be contained in the guidance.

### Tests

The evaluator will demonstrate the ability to successfully establish a RADIUS over TLS connection with a RADIUS server. This test will be performed with X.509v3 certificates if selected and performed with pre-shared keys if selected.

## FCS\_RADSEC\_EXT.2 RadSec using Pre-Shared Keys

*The inclusion of this selection-based component depends upon selection in [FCS\\_RADSEC\\_EXT.1.2](#).*

### FCS\_RADSEC\_EXT.2.1

The TSF shall implement TLS 1.2 and [selection: TLS 1.3, no other TLS versions] when acting as a RADIUS over TLS client that supports the following ciphersuites: [selection:

- TLS 1.2 ciphersuites: [selection:
  - TLS\_ECDHE\_PSK\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 8442
  - TLS\_DHE\_PSK\_WITH\_AES\_256\_GCM\_SHA384 as defined in RFC 5487

]

- TLS 1.3 ciphersuites:
  - TLS\_AES\_256\_GCM\_SHA384 as defined in RFC 8446

[selection:

- TLS\_AES\_128\_GCM\_SHA256 as defined in RFC 8446
- [assignment: other TLS 1.3 ciphersuites]

]

].

**Application Note:** The above ciphersuites are only for use when the TSF is acting as a RADIUS over TLS client, not for other uses of the TLS protocol. The ciphersuites to be tested in the evaluated configuration are limited by this requirement. The ST author should select the ciphersuites that are supported.

### FCS\_RADSEC\_EXT.2.2

The TSF shall be able to [selection: accept, generate using the random bit generator specified in FCS\_RBG.1] bit-based pre-shared keys.

## Evaluation Activities ▼

[FCS\\_RADSEC\\_EXT.2](#)  
TSS

The evaluator will check the description of the implementation of this protocol in the *TSS* to ensure that the ciphersuites supported are specified. The evaluator will check the *TSS* to ensure that the ciphersuites specified are identical to those listed for this component. The evaluator will also verify that the *TSS* contains a description of the denial of old SSL and *TLS* versions.

The evaluator will examine the *TSS* to ensure it describes the process by which the bit-based pre-shared keys are generated (if the *TOE* supports this functionality) and confirm that this process uses the *RBG* specified in *FCS\_RBG.1*.

### **Guidance**

The evaluator will verify that any configuration necessary to meet the requirement must be contained in the guidance.

The evaluator will also check the guidance documentation to ensure that it contains instructions on configuring the *TOE* so that *RADIUS* over *TLS* conforms to the description in the *TSS* (for instance, the set of ciphersuites advertised by the *TOE* may have to be restricted to meet the requirements).

The evaluator will confirm the operational guidance contains instructions for either entering bit-based pre-shared keys or generating a bit-based pre-shared key (or both).

### **Tests**

The testing for this requirement is addressed by the functional claims made in [Functional Package for Transport Layer Security \(TLS\), version 2.1](#) for this interface.



# Appendix C - Extended Component Definitions

This appendix contains the definitions for all extended requirements specified in the PP-Module.

## C.1 Extended Components Table

All extended components specified in the PP-Module are listed in this table:

Table 11: Extended Component Definitions

| Functional Class                        | Functional Components                                                                                                                                                         |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Cryptographic Support (FCS)             | FCS_RADSEC_EXT RadSec                                                                                                                                                         |
| Identification and Authentication (FIA) | FIA_8021X_EXT 802.1X Port Access Entity (Authenticator) Authentication                                                                                                        |
| Protection of the TSE (FPT)             | FPT_ACF_EXT Access Controls<br>FPT_ASLR_EXT Address Space Layout Randomization<br>FPT_SBOP_EXT Stack Buffer Overflow Protection<br>FPT_W^X_EXT Write XOR Execute Memory Pages |
| Security Management (FMT)               | FMT_SMR_EXT Security Management Restrictions                                                                                                                                  |

## C.2 Extended Component Definitions

### C.2.1 Cryptographic Support (FCS)

This PP-Module defines the following extended components as part of the FCS class originally defined by CC Part 2:

#### C.2.1.1 FCS\_RADSEC\_EXT RadSec

##### Family Behavior

Components in this family describe requirements for implementation of the RadSec (RADIUS over TLS) protocol.

##### Component Leveling



[FCS\\_RADSEC\\_EXT.1](#), RadSec, requires the TSE to implement RadSec using a specified peer authentication method.

[FCS\\_RADSEC\\_EXT.2](#), RadSec using Pre-Shared Keys, requires the TSF to implement RadSec using pre-shared key authentication in a manner that conforms to relevant [TLS](#) specifications.

#### **Management: FCS\_RADSEC\_EXT.1**

No specific management functions are identified.

#### **Audit: FCS\_RADSEC\_EXT.1**

There are no auditable events foreseen.

#### **FCS\_RADSEC\_EXT.1 RadSec**

Hierarchical to: No other components.

Dependencies to: [FCS\\_TLSC\\_EXT.1](#) [TLS](#) Client Protocol  
[FIA\\_PSK\\_EXT.1](#) Pre-Shared Key Composition  
[FIA\\_X509\\_EXT.1](#) X.509v3 Certificate Validation

##### **FCS\_RADSEC\_EXT.1.1**

The TSF shall implement [RADIUS](#) over [TLS](#) as specified in RFC 6614 to communicate securely with a [RADIUS](#) server.

##### **FCS\_RADSEC\_EXT.1.2**

The TSF shall perform peer authentication using [**assignment:** *some authentication method*].

#### **Management: FCS\_RADSEC\_EXT.2**

No specific management functions are identified.

#### **Audit: FCS\_RADSEC\_EXT.2**

There are no auditable events foreseen.

#### **FCS\_RADSEC\_EXT.2 RadSec using Pre-Shared Keys**

Hierarchical to: No other components.

Dependencies to: [FCS\\_CKM.1](#) Cryptographic Key Generation  
[FCS\\_COP.1](#) Cryptographic Operation  
[FCS\\_RADSEC\\_EXT.1](#) RadSec  
[FCS\\_RBG.1](#) Random Bit Generation

##### **FCS\_RADSEC\_EXT.2.1**

The TSF shall implement [**assignment:** *list of allowed [TLS](#) versions*] and reject all other [TLS](#) and SSL versions. The [TLS](#) implementation shall support the following ciphersuites for use when acting as a [RADIUS](#) over [TLS](#) client: [**assignment:** *list of supported ciphersuites*].

##### **FCS\_RADSEC\_EXT.2.2**

The TSF shall be able to [selection: accept, generate using the random bit generator specified in FCS\_RBG.1] bit-based pre-shared keys.

## C.2.2 Identification and Authentication (FIA)


This PP-Module defines the following extended components as part of the FIA class originally defined by CC Part 2:

### C.2.2.1 FIA\_8021X\_EXT 802.1X Port Access Entity (Authenticator) Authentication

#### Family Behavior

Components in this family describe requirements for implementation of 802.1X port-based network access control.

#### Component Leveling



[FIA\\_8021X\\_EXT.1](#), 802.1X Authentication, requires the TSF to securely implement IEEE 802.1X as an authenticator.

#### Management: FIA\_8021X\_EXT.1

No specific management functions are identified.

#### Audit: FIA\_8021X\_EXT.1

The following actions should be auditable if FAU\_GEN Security Audit Data Generation is included in the ST:

- Attempts to access the 802.1X controlled port prior to successful completion of the authentication exchange

#### FIA\_8021X\_EXT.1 802.1X Authentication

Hierarchical to: No other components.

Dependencies to: No dependencies

##### FIA\_8021X\_EXT.1.1

The TSF shall conform to IEEE Standard 802.1X for a Port Access Entity (PAE) in the “Authenticator” role.

##### FIA\_8021X\_EXT.1.2

The TSF shall support communications to a RADIUS authentication server conforming to RFCs 2865, 2866, and 3579.

##### FIA\_8021X\_EXT.1.3

The TSF shall ensure that no access to its 802.1X controlled port is given to the wireless client prior to successful completion of this authentication exchange.

## C.2.3 Protection of the TSF (FPT)


This PP-Module defines the following extended components as part of the FPT class originally defined by CC Part

### C.2.3.1 FPT\_ACF\_EXT Access Controls

#### Family Behavior

This family defines specific **T.O.E** components that are protected against unprivileged access. This is a new family defined for the FPT class.

#### Component Leveling



**FPT\_ACF\_EXT.1**, Access Controls, requires the **T.S.F** to prohibit unauthorized users from reading or modifying specific **T.S.F** data.

#### Management: FPT\_ACF\_EXT.1

There are no management functions foreseen.

#### Audit: FPT\_ACF\_EXT.1

The following actions should be auditable if FAU\_GEN Security audit data generation is included in the **P.P** or **S.T**:

- Unauthorized attempts to perform operations against protected data

#### FPT\_ACF\_EXT.1 Access Controls

Hierarchical to: No other components.

Dependencies to: No dependencies.

##### FPT\_ACF\_EXT.1.1

The **T.S.F** shall implement access controls which prohibit unprivileged users from modifying:

- Kernel and its drivers/modules
- Security audit logs
- Shared libraries
- System executables
- System configuration files
- [assignment: *other objects*]

.

##### FPT\_ACF\_EXT.1.2

The **T.S.F** shall implement access controls which prohibit unprivileged users from reading:

- Security audit logs
- System-wide credential repositories
- [assignment: *list of other objects*]


.

### C.2.3.2 FPT\_ASRLR\_EXT Address Space Layout Randomization

## Family Behavior

This family defines the ability of the **T.O.E** to implement address space layout randomization (**ASLR**). This is a new family defined for the **FPT** class.

## Component Leveling



**FPT\_AS LR\_EXT.1**, Address Space Layout Randomization, defines the ability of the **T.O.E** to use **ASLR** as well as the objects that **ASLR** is applied to.

### Management: **FPT\_AS LR\_EXT.1**

There are no management functions foreseen.

### Audit: **FPT\_AS LR\_EXT.1**

There are no auditable events foreseen.

## **FPT\_AS LR\_EXT.1 Address Space Layout Randomization**

Hierarchical to: No other components.

Dependencies to: No dependencies.

### **FPT\_AS LR\_EXT.1.1**


The **T.S.F** shall always randomize process address space memory locations with [**selection**: 8, [**assignment**: number greater than 8]] bits of entropy except for [**assignment**: list of explicit exceptions].

## C.2.3.3 **FPT\_SBOP\_EXT Stack Buffer Overflow Protection**

## Family Behavior

This family requires the **T.S.F** to be compiled using stack-based buffer overflow protections. This is a new family defined for the **FPT** class.

## Component Leveling



**FPT\_SBOP\_EXT.1**, Stack Buffer Overflow Protection, requires the **T.S.F** to be compiled using stack-based buffer overflow protections or to store data in such a manner that a stack-based buffer overflow cannot compromise the **T.S.F**.

### Management: **FPT\_SBOP\_EXT.1**

There are no management activities foreseen.

### Audit: **FPT\_SBOP\_EXT.1**

There are no auditable events foreseen.

## FPT\_SBOP\_EXT.1 Stack Buffer Overflow Protection

Hierarchical to: No other components.

Dependencies to: No dependencies.

### FPT\_SBOP\_EXT.1.1


The T<sub>TSF</sub> shall [**selection:** *employ stack-based buffer overflow protections, not store parameters or variables in the same data structures as control flow values*].

## C.2.3.4 FPT\_W^X\_EXT Write XOR Execute Memory Pages

### Family Behavior

This family defines the ability of the T<sub>TOE</sub> to implement data execution prevention (DEP) by preventing memory from being both writable and executable. This is a new family defined for the FPT class.

### Component Leveling



[FPT\\_W^X\\_EXT.1](#), Write XOR Execute Memory Pages, defines the ability of the T<sub>TOE</sub> to prevent memory from being simultaneously writable and executable unless otherwise specified.

### Management: FPT\_W^X\_EXT.1

There are no management functions foreseen.

### Audit: FPT\_W^X\_EXT.1

There are no auditable events foreseen.

## FPT\_W^X\_EXT.1 Write XOR Execute Memory Pages

Hierarchical to: No other components.

Dependencies to: No dependencies.

### FPT\_W^X\_EXT.1.1

The T<sub>TSF</sub> shall prevent allocation of any memory region with both write and execute permissions except for [**assignment:** *list of exceptions*].

## C.2.4 Security Management (FMT)


This PP-Module defines the following extended components as part of the FMT class originally defined by CC Part 2:

### C.2.4.1 FMT\_SMR\_EXT Security Management Restrictions

#### Family Behavior

Components in this family describe architectural restrictions on security administration that are not defined in CC Part 2.

## Component Leveling



[FMT\\_SMR\\_EXT.1](#), No Administration from Client, requires the TSF to reject remote administration from a wireless client by default.

### Management: FMT\_SMR\_EXT.1

No specific management functions are identified.

### Audit: FMT\_SMR\_EXT.1

There are no auditable events foreseen.

### FMT\_SMR\_EXT.1 No Administration from Client

Hierarchical to: No other components.

Dependencies to: FMT\_SMF.1 Specification of Management Functions

#### FMT\_SMR\_EXT.1.1

The TSF shall ensure that the ability to administer remotely the TOE from a wireless client shall be disabled by default.

# Appendix D - Acronyms

Table 12: Acronyms

| Acronym          | Meaning                                           |
|------------------|---------------------------------------------------|
| AES              | Advanced Encryption Standard                      |
| AP               | Access Point                                      |
| ASLR             | Address Space Layout Randomization                |
| Base-PP          | Base Protection Profile                           |
| CBC              | Cipher Block Chaining                             |
| CC               | Common Criteria                                   |
| CCM              | Counter Mode with CBC-Message Authentication Code |
| CCMP             | CCM mode Protocol                                 |
| CEM              | Common Evaluation Methodology                     |
| cPP              | Collaborative Protection Profile                  |
| CTR              | Counter (encryption mode)                         |
| EAP              | Extensible Authentication Protocol                |
| GCM              | Galois-Counter Mode                               |
| GTK              | Group Temporal Key                                |
| IPsec            | Internet Protocol Security                        |
| MAC              | Media Access Control                              |
| NDcPP            | Network Device collaborative Protection Profile   |
| OE               | Operational Environment                           |
| PAE              | Port Access Entity                                |
| PMK              | Pairwise Master Key                               |
| PP               | Protection Profile                                |
| PP-Configuration | Protection Profile Configuration                  |
| PP-Module        | Protection Profile Module                         |



|        |                                            |
|--------|--------------------------------------------|
| PTK    | Pairwise Transient Key                     |
| RADIUS | Remote Authentication Dial In User Service |
| RBG    | Random Bit Generator                       |
| SAR    | Security Assurance Requirement             |
| SFR    | Security Functional Requirement            |
| SSID   | Service Set Identifier                     |
| ST     | Security Target                            |
| TLS    | Transport Layer Security                   |
| TOE    | Target of Evaluation                       |
| TSE    | TOE Security Functionality                 |
| TSEI   | TSE Interface                              |
| TSS    | TOE Summary Specification                  |
| WPA    | Wi-Fi Protected Access                     |

# Appendix E - Bibliography

Table 13: Bibliography

| Identifier | Title                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [CC]       | Common Criteria for Information Technology Security Evaluation - <ul style="list-style-type: none"><li>• <a href="#">Part 1: Introduction and general model</a>, CCMB-2022-11-001, CC:2022, Revision 1, November 2022.</li><li>• <a href="#">Part 2: Security functional requirements</a>, CCMB-2022-11-002, CC:2022, Revision 1, November 2022.</li><li>• <a href="#">Part 3: Security assurance requirements</a>, CCMB-2022-11-003, CC:2022, Revision 1, November 2022.</li><li>• <a href="#">Part 4: Framework for the specification of evaluation methods and activities</a>, CCMB-2022-11-004, CC:2022, Revision 1, November 2022.</li><li>• <a href="#">Part 5: Pre-defined packages of security requirements</a>, CCMB-2022-11-005, CC:2022, Revision 1, November 2022.</li></ul> |
| [GEM]      | Common Methodology for Information Technology Security Evaluation - <ul style="list-style-type: none"><li>• <a href="#">Evaluation methodology</a>, CCMB-2022-11-006, CC:2022, Revision 1, November 2022.</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| [NDCPP]    | <a href="#">collaborative Protection Profile for Network Devices, Version 4.0, December 22, 2025</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |