

# PP-Module for VPN Gateways



Version: 2.0  
2026-01-21

National Information Assurance Partnership

# Revision History

---

Version	Date	Comment
1.0	2019-09-17	Initial publication
1.1	2020-06-18	Compatibility with CPP_ND_V2.2E, incorporation of NIAP Technical Decisions
1.2	2022-03-31	Format conversion, incorporation of NIAP Technical Decisions, TC feedback
1.3	2023-08-16	Incorporation of NIAP Technical Decisions, TC feedback
2.0	2026-01-21	Incorporation of NIAP Technical Decisions, Update to CC:2022

# Contents

---

1	Introduction	
1.1	Overview	
1.2	Terms	1.2.1 Common Criteria Terms
		1.2.2 Technical Terms
1.3	Compliant Targets of Evaluation	1.3.1 TOE Boundary
1.4	Use Cases	
1.5	Package Usage	
2	Conformance Claims	
3	Security Problem Definition	3.1 Threats
		3.2 Assumptions
		3.3 Organizational Security Policies
4	Security Objectives	4.1 Security Objectives for the Operational Environment
		4.2 Security Objectives Rationale
5	Security Requirements	5.1 Collaborative Protection Profile for Network Devices Security Functional Requirements Direction
		5.1.1 Modified SFRs
		5.1.1.1 Cryptographic Support (FCS)
		5.1.1.2 Security Management (FMT)
	5.2 TOE Security Functional Requirements	5.2.1 Auditable Events for Mandatory SFRs
		5.2.2 Security Audit (FAU)
		5.2.3 Cryptographic Support (FCS)
		5.2.4 Security Management (FMT)
		5.2.5 Packet Filtering (FPF)
		5.2.6 Protection of the TSF (FPT)
		5.2.7 Trusted Path/Channels (FTP)
	5.3 TOE Security Functional Requirements Rationale	
6	Consistency Rationale	

## 6.1 Collaborative Protection Profile for Network Devices

- 6.1.1 Consistency of TOE Type
- 6.1.2 Consistency of Security Problem Definition
- 6.1.3 Consistency of OE Objectives
- 6.1.4 Consistency of Requirements

## Appendix A - Optional SFRs

### A.1 Strictly Optional Requirements

- A.1.1 Auditable Events for Strictly Optional SFRs
- A.1.2 Packet Filtering (FPF)

### A.2 Objective Requirements

### A.3 Implementation-dependent Requirements

- A.3.1 Auditable Events for Implementation-Based SFRs
- A.3.2 TOE Access (FTA)

## Appendix B - Selection-based Requirements

### B.1 Auditable Events for Selection-based SFRs

### B.2 Cryptographic Support (FCS)

### B.3 Identification and Authentication (FIA)

## Appendix C - Extended Component Definitions

### C.1 Extended Components Table

### C.2 Extended Component Definitions

#### C.2.1 Cryptographic Support (FCS)

##### C.2.1.1 FCS\_EAP\_EXT EAP-TLS/TTLS

#### C.2.2 Identification and Authentication (FIA)

##### C.2.2.1 FIA\_HOTP\_EXT HMAC-Based One-Time Password Pre-Shared Keys

##### C.2.2.2 FIA\_PSK\_EXT Pre-Shared Key Composition

##### C.2.2.3 FIA\_TOTP\_EXT Time-Based One-Time Password Pre-Shared Keys

#### C.2.3 Packet Filtering (FPF)

##### C.2.3.1 FPF\_RUL\_EXT Packet Filtering Rules

##### C.2.3.2 FPF\_MFA\_EXT Multifactor Authentication Filtering

#### C.2.4 Protection of the TSF (FPT)

##### C.2.4.1 FPT\_TST\_EXT TSF Self-Test

#### C.2.5 TOE Access (FTA)

##### C.2.5.1 FTA\_VCM\_EXT VPN Client Management

## Appendix D - Implicitly Satisfied Requirements

## Appendix E - Entropy Documentation and Assessment

## Appendix F - Acronyms

## Appendix G - Bibliography

# 1 Introduction

## 1.1 Overview

---

The scope of this Protection Profile Module (PP-Module) is to describe the security functionality of a virtual private network (VPN) gateway in terms of [CC] and to define functional and assurance requirements for such products. This PP-Module is intended for use with the following Base-PP:

- Network Device collaborative Protection Profile Version 4.0

This Base-PP is valid because a VPN gateway is a device at the edge of a private network that terminates an IPsec tunnel, which provides device authentication, confidentiality, and integrity of information traversing a public or untrusted network. This is functionality that typically will be implemented by a network device.

A Target of Evaluation (TOE) that conforms to a PP-Configuration containing this PP-Module may be a ‘Distributed TOE’ as defined in the NDcPP; however, the VPN gateway functionality described in this PP-Module should be in a single TOE component. This PP-Module does not prohibit the TOE from implementing other security functionality in a distributed manner. For example, a TOE may have a centralized device that performs VPN gateway and other security functionality (such as intrusion prevention) with a number of distributed nodes that help in the enforcement of the secondary functionality.

## 1.2 Terms

---

The following sections list Common Criteria and technology terms used in this document.

### 1.2.1 Common Criteria Terms

Assurance	Grounds for confidence that a TOE meets the SFRs [CC].
Base Protection Profile (Base-PP)	Protection Profile used as a basis to build a PP-Configuration.
Collaborative Protection Profile (cPP)	A Protection Profile developed by international technical communities and approved by multiple schemes.
Common Criteria (CC)	Common Criteria for Information Technology Security Evaluation (International Standard ISO/IEC 15408).
Common Criteria Testing Laboratory	Within the context of the Common Criteria Evaluation and Validation Scheme (CCEVS), an IT security evaluation facility accredited by the National Voluntary Laboratory Accreditation Program (NVLAP) and approved by the NIAP Validation Body to conduct Common Criteria-based evaluations.
Common Evaluation Methodology (CEM)	Common Evaluation Methodology for Information Technology Security Evaluation.
Direct Rationale	A type of Protection Profile, PP-Module, or Security Target in which the security problem definition (SPD) elements are mapped directly to the SFRs and possibly to

the security objectives for the operational environment. There are no security objectives for the TOE.

Distributed TOE	A TOE composed of multiple components operating as a logical whole.
Functional Package (FP)	A document that collects SFRs for a particular protocol, technology, or functionality.
Operational Environment (OE)	Hardware and software that are outside the TOE boundary that support the TOE functionality and security policy.
Protection Profile (PP)	An implementation-independent set of security requirements for a category of products.
Protection Profile Configuration (PP-Configuration)	A comprehensive set of security requirements for a product type that consists of at least one Base-PP and at least one PP-Module.
Protection Profile Module (PP-Module)	An implementation-independent statement of security needs for a TOE type complementary to one or more Base-PPs.
Security Assurance Requirement (SAR)	A requirement to assure the security of the TOE.
Security Functional Requirement (SFR)	A requirement for security enforcement by the TOE.
Security Target (ST)	A set of implementation-dependent security requirements for a specific product.
Target of Evaluation (TOE)	The product under evaluation.
TOE Security Functionality (TSF)	The security functionality of the product under evaluation.
TOE Summary Specification (TSS)	A description of how a TOE satisfies the SFRs in an ST.

## 1.2.2 Technical Terms

Headend	A VPN use case where the VPN gateway is establishing VPN connectivity with endpoint VPN clients as opposed to other infrastructure devices (e.g., site-to-site).
Packet Filtering	The process by which an edge network device determines if traffic bound to or from its external network is passed to its destination or dropped.
VPN Gateway	A type of network device that resides at the edge of a private network and permits the establishment of VPN connectivity from computers residing in an external network.
Virtual Private Network (VPN)	A mechanism for overlaying a cryptographically secured network over distributed wide-area networks.

## 1.3 Compliant Targets of Evaluation

This ~~PP-Module~~ specifically addresses network gateway devices that terminate IPsec ~~VPN~~ tunnels. A compliant ~~VPN~~ gateway is a device composed of hardware and software that is connected to two or more distinct networks and has an infrastructure role in the overall enterprise network. In particular, a ~~VPN~~ gateway establishes a secure tunnel that provides an authenticated and encrypted path to one or more other sites and thereby decreases the risk of exposure of information transiting an untrusted network.

The baseline requirements of this ~~PP-Module~~ are those determined necessary for a multi-site ~~VPN~~ gateway device. A compliant ~~TOE~~ may also contain the ability to act as a headend for remote clients. Because this capability is optional, the remote client-based requirements have been included in Appendix A.

### **1.3.1 TOE Boundary**

The physical boundary for a ~~TOE~~ that conforms to this ~~PP-Module~~ is a hardware appliance that also provides generalized network device functionality, such as auditing, identification and authentication, and cryptographic services for network communications. The ~~TOE~~'s logical boundary includes all functionality required by the claimed ~~Base-PP~~ as well as the ~~VPN~~ functionality and related capabilities that are defined in this ~~PP-Module~~. Any functionality that is provided by the network device that is not relevant to the security requirements defined by this ~~PP-Module~~ or the ~~Base-PP~~ is considered to be outside the scope of the ~~TOE~~.

---

## **1.4 Use Cases**

This ~~PP-Module~~ defines two potential use cases for the ~~VPN~~ gateway ~~TOE~~, defined below. The first use case will always be applicable for a ~~TOE~~ that conforms to this ~~PP-Module~~. The second use case defines an optional deployment for the ~~TOE~~ that accompanies the first use case.

### **[USE CASE 1] Network Device**

The ~~VPN~~ gateway is part of the functionality that is provided by a general network device appliance, such as a router or switch, or a device that is dedicated solely to providing multi-site ~~VPN~~ gateway functionality.

### **[USE CASE 2] Remote Client Headend**

The ~~VPN~~ gateway provides the ability to act as a headend for remote clients.

---

## **1.5 Package Usage**

### **Functional Package for X.509, Version 1.0**

#### **Certificate Verification and Validation Required in FIA\_XCU\_EXT.1.1**

The ~~ST~~ author shall select the options to verify and assert identities in FIA\_XCU\_EXT.1.1.

#### **Limitations on Signature Algorithms in FIA\_X509\_EXT.1.1**

The ~~TOE~~ must utilize appropriate cryptographic algorithms that conform to CNSA standards. Thus, the ~~TOE~~ shall utilize no other algorithms outside of those specified in RFC 8603 for certificate or CRL signatures. Additionally, the ~~TOE~~ shall not use ECDSA with SHA-512 signatures for OCSP responses, and shall utilize no other algorithms for OCSP responses.

#### **Required Extension Processing in FIA\_X509\_EXT.1.2**

The ~~ST~~ author shall select the option to process the basicConstraints and extendedKeyUsage extensions in FIA\_X509\_EXT.1.2. If the ~~TOE~~ supports identifiers of types other than an identifier located in the ~~CN~~ (i.e., any identifiers specifically labeled as "~~CN~~", or the Distinguished Name), the ~~ST~~ author shall select the option to process the subjectAlternateName extension and the relevant options within the subjectAlternateName extension that correspond to the supported identifier types.

#### **CRL or OCSP-based Revocation Required for FIA\_X509\_EXT.1.3**

The TOE must support revocation that only involves CRL or OCSP. Accordingly, the ST author shall select only from options involving CRL or OCSP in FIA\_X509\_EXT.1.3 (e.g., the selection to treat all certificates older than a given short timeframe is not an acceptable substitute or alternative for supporting CRL or OCSP).

#### **Connections to CRL or OCSP Servers Required for FIA\_X509\_EXT.1.4**

Because the TOE is required to support CRL or OCSP, the TSF shall support an appropriate mechanism for obtaining revocation status information. In the case of CRL, the ST author shall claim that revocation status information is obtained via network connection to a CRL distribution point. In the case of OCSP, the ST author shall claim that revocation status information is obtained via network connection to an OCSP responder, via OCSP stapling, or via OCSP multi-stapling.

#### **Required Function Claims in FIA\_X509\_EXT.2.1**

The ST author shall ensure that the selections and assignments within FIA\_X509\_EXT.2.1 reflect the usage of X.509 for IPsec or IKE. Other selections and assignments may be made as appropriate for other TOE functionality.

# 2 Conformance Claims

## Conformance Statement

An ~~ST~~ must claim exact conformance to this ~~PP-Module~~.

The evaluation methods used for evaluating the ~~TQE~~ are a combination of the workunits defined in [CEM] as well as the Evaluation Activities for ensuring that individual ~~SFRs~~ and ~~SARs~~ have a sufficient level of supporting evidence in the Security Target and guidance documentation and have been sufficiently tested by the laboratory as part of completing ATE\_IND.1. Any functional packages this ~~PP~~ claims similarly contain their own Evaluation Activities that are used in this same manner.

## CC Conformance Claims

This ~~PP-Module~~ is conformant to Part 2 (extended) and Part 3 (conformant) of Common Criteria CC:2022, Revision 1.

## PP Claim

This ~~PP-Module~~ does not claim conformance to any Protection Profile.

The following ~~PPs~~ and ~~PP-Modules~~ are allowed to be specified in a ~~PP-Configuration~~ with this ~~PP-Module~~:

- collaborative Protection Profile Module for Stateful Traffic Filter Firewalls v2.0
- ~~PP-Module~~ for Intrusion Protection Systems, v2.0

## Package Claim

- This ~~PP-Module~~ is Functional Package for X.509, version 1.0 conformant.
- This ~~PP-Module~~ does not conform to any assurance packages.

The functional packages to which the ~~PP~~ conforms may include ~~SFRs~~ that are not mandatory to claim for the sake of conformance. An ~~ST~~ that claims one or more of these functional packages may include any non-mandatory ~~SFRs~~ that are appropriate to claim based on the capabilities of the ~~TSF~~ and on any triggers for their inclusion based inherently on the ~~SFR~~ selections made.

# 3 Security Problem Definition

The security problem is described in terms of the threats that the **TOE** is expected to address, assumptions about its operational environment (**OE**), and any organizational security policies that the **TOE** is expected to enforce.

## 3.1 Threats

---

The following threats defined in this **PP-Module** extend the threats defined by the **Base-PP**.

### T.DATA\_INTEGRITY

Devices on a protected network may be exposed to threats presented by devices located outside the protected network that may attempt to modify the data without authorization or determine the contents of secure communication. If known malicious external devices are able to communicate with devices on the protected network or if devices on the protected network can communicate with those external devices then the data contained in the communications may be susceptible to a loss of integrity or confidentiality.

### T.NETWORK\_ACCESS

Devices located outside the protected network may seek to exercise services located on the protected network that are intended to only be accessed from inside the protected network or only accessed by entities using an authenticated path into the protected network. Devices located outside the protected network may, likewise, offer services that are inappropriate for access from within the protected network.

From an ingress perspective, **VPN** gateways can be configured so that only those network servers intended for external consumption by entities operating on a trusted network (e.g., machines operating on a network where the peer **VPN** gateways are supporting the connection) are accessible and only via the intended ports. This serves to mitigate the potential for network entities outside a protected network to access network servers or services intended only for consumption or access inside a protected network.

From an egress perspective, **VPN** gateways can be configured so that only specific external services (e.g., based on destination port) can be accessed from within a protected network, or moreover are accessed via an encrypted channel. For example, access to external mail services can be blocked to enforce corporate policies against accessing uncontrolled email servers, or, that access to the mail server must be done over an encrypted link.

### T.NETWORK\_DISCLOSURE

Devices on a protected network may be exposed to threats presented by devices located outside the protected network, which may attempt to conduct unauthorized activities. If known malicious external devices are able to communicate with devices on the protected network, or if devices on the protected network can establish communications with those external devices (e.g., as a result of a phishing episode or by inadvertent responses to email messages), then those internal devices may be susceptible to the unauthorized disclosure of information.

From an infiltration perspective, **VPN** gateways serve not only to limit access to only specific destination network addresses and ports within a protected network, but whether network traffic will be encrypted or transmitted in plaintext. With these limits, general network port scanning can be prevented from reaching protected networks or machines, and access to information on a protected network can be limited to that obtainable from specifically configured ports on identified network nodes (e.g., web pages from a designated corporate web server). Additionally, access can be limited to only specific source addresses and ports so that specific networks or network nodes can be blocked from accessing a protected network thereby further limiting the potential disclosure of information.

From an exfiltration perspective, **VPN** gateways serve to limit how network nodes operating on a protected

network can connect to and communicate with other networks limiting how and where they can disseminate information. Specific external networks can be blocked altogether or egress could be limited to specific addresses or ports. Alternately, egress options available to network nodes on a protected network can be carefully managed in order to, for example, ensure that outgoing connections are encrypted to further mitigate inappropriate disclosure of data through packet sniffing.

## T.NETWORK\_MISUSE

Devices located outside the protected network, while permitted to access particular public services offered inside the protected network, may attempt to conduct inappropriate activities while communicating with those allowed public services. Certain services offered from within a protected network may also represent a risk when accessed from outside the protected network.

From an ingress perspective, it is generally assumed that entities operating on external networks are not bound by the use policies for a given protected network. Nonetheless, VPN gateways can log policy violations that might indicate violation of publicized usage statements for publicly available services.

From an egress perspective, VPN gateways can be configured to help enforce and monitor protected network use policies. As explained in the other threats, a VPN gateway can serve to limit dissemination of data, access to external servers, and even disruption of services – all of these could be related to the use policies of a protected network and as such are subject in some regards to enforcement. Additionally, VPN gateways can be configured to log network usages that cross between protected and external networks and as a result can serve to identify potential usage policy violations.

## T.REPLAY\_ATTACK

If an unauthorized individual successfully gains access to the system, the adversary may have the opportunity to conduct a “replay” attack. This method of attack allows the individual to capture packets traversing throughout the network and send the packets at a later time, possibly unknown by the intended receiver. Traffic is subject to replay if it meets the following conditions:

- Cleartext: an attacker with the ability to view unencrypted traffic can identify an appropriate segment of the communications to replay as well in order to cause the desired outcome
- No integrity: alongside cleartext traffic, an attacker can make arbitrary modifications to captured traffic and replay it to cause the desired outcome if the recipient has no means to detect these

## 3.2 Assumptions

---

These assumptions are made on the Operational Environment (OE) in order to be able to ensure that the security functionality specified in the PP-Module can be provided by the TOE. If the TOE is placed in an OE that does not meet these assumptions, the TOE may no longer be able to provide all of its security functionality.

This PP-Module defines assumptions that extend those defined in the supported Base-PP.

All assumptions for the OE of the Base-PP also apply to this PP-Module.

A.NO\_THRU\_TRAFFIC\_PROTECTION is still operative, but only for the interfaces in the TOE that are defined by the Base-PP and not the PP-Module.

## A.CONNECTIONS

It is assumed that the TOE is connected to distinct networks in a manner that ensures that the TOE's security policies will be enforced on all applicable network traffic flowing among the attached networks.

## 3.3 Organizational Security Policies

---

This PP defines no Organizational Security Policies beyond those defined in the claimed Base-PP(s).

# 4 Security Objectives

## 4.1 Security Objectives for the Operational Environment

---

This **PP-Module** defines environmental security objectives that extend those defined in the supported **Base-PP**. All objectives for the **OE** of the **Base-PP** also apply to this **PP-Module**. **OE.NO\_THRU\_TRAFFIC\_PROTECTION** is still operative, but only for the interfaces in the **TOE** that are defined by the **Base-PP** and not the **PP-Module**.

### OE.CONNECTIONS

The **TOE** is connected to distinct networks in a manner that ensures that the **TOE** security policies will be enforced on all applicable network traffic flowing among the attached networks.

## 4.2 Security Objectives Rationale

---

This section describes how the assumptions and organizational security policies map to operational environment security objectives.

**Table 1: Security Objectives Rationale**

Assumption or OSP	Security Objectives	Rationale
A.CONNECTIONS	OE.CONNECTIONS	The <b>OE</b> objective <b>OE.CONNECTIONS</b> is realized through <b>A.CONNECTIONS</b> .

# 5 Security Requirements

This chapter describes the security requirements which have to be fulfilled by the product under evaluation. Those requirements comprise functional components from Part 2 and assurance components from Part 3 of [CC]. The following conventions are used for the completion of operations:

- **Refinement** operation (denoted by **bold text** or ~~strikethrough text~~): Is used to add details to a requirement or to remove part of the requirement that is made irrelevant through the completion of another operation, and thus further restricts a requirement.
- **Selection** (denoted by *italicized text*): Is used to select one or more options provided by the [CC] in stating a requirement.
- **Assignment** operation (denoted by *italicized text*): Is used to assign a specific value to an unspecified parameter, such as the length of a password. Showing the value in square brackets indicates assignment.
- **Iteration** operation: Is indicated by appending the SFR name with a slash and unique identifier suggesting the purpose of the operation, e.g. "/EXAMPLE1."

## 5.1 Collaborative Protection Profile for Network Devices Security Functional Requirements Direction

---

In a ~~PP~~-Configuration that includes the NDcPP, the ~~VPN~~ gateway is expected to rely on some of the security functions implemented by the network device as a whole and evaluated against the ~~Base-PP~~. In this case, the following sections describe any modifications that the ~~ST~~ author must make to the SFRs defined in the ~~Base-PP~~ in addition to what is mandated by section 5.2.

### 5.1.1 Modified SFRs

The SFRs listed in this section are defined in the NDcPP and relevant to the secure operation of the TOE.

#### 5.1.1.1 Cryptographic Support (FCS)

##### FCS\_COP.1/AEAD: Cryptographic Operation - Authenticated Encryption with Associated Data

This SFR has been modified from its definition in the NDcPP to mandate selection of AES-GCM mode and 256-bit key sizes. Other selections may still be made if they are needed for other parts of the TSF.

The text of FCS\_COP.1.1/AEAD is replaced with:

**FCS\_COP.1.1/AEAD** The TSF shall perform [authenticated encryption with associated data] in accordance with a specified cryptographic algorithm [**selection: Cryptographic algorithm**] and cryptographic key sizes [**selection: Cryptographic key sizes**] that meet the following: [**selection: List of standards**].

The following table provides the allowable choices for completion of the selection operations of FCS\_COP.1.1/AEAD. In the last column, an X indicates it is mandatory for the ~~ST~~ author to include this row, and an O indicates that the row is optional and need not be included in the table if the TSF does not perform that function. Note that it is not necessary for the ~~ST~~ author to reproduce this final column in the ST.

##### Allowable choices for FCS\_COP.1/AEAD:

Identifier	Cryptographic algorithm	Cryptographic Key Sizes	List of standards	Mandatory or Optional
AES-CCM	AES in CCM mode with unpredictable, non-repeating nonce, minimum size of 64 bits	256 bits	[selection: ISO/IEC 18033-3:2010 (Subclause 5.2), FIPS PUB 197] [AES]  [selection: ISO/IEC 19772:2020 (Clause 7), NIST SP 800-38C] [CCM]	O
AES-GCM	AES in GCM mode with non-repeating IVs using [selection: deterministic, RBG-based], IV construction; the tag must be of length [selection: 96, 104, 112, 120, 128] bits.	256 bits	[selection: ISO/IEC 18033-3:2010 (Subclause 5.2), FIPS PUB 197] [AES]  [selection: ISO/IEC 19772:2020 (Clause 10), NIST SP 800-38D] [GCM]	X

## FCS\_COP.1/DataEncryption: Cryptographic Operation (AES Data Encryption/Decryption)

This SFR has been modified from its definition in the NDcPP to support this PP-Module's IPsec requirements by mandating support for GCM mode.

The text of the FCS\_COP.1.1/DataEncryption is replaced with:

**FCS\_COP.1.1/DataEncryption** The TSF shall perform encryption/decryption in accordance with a specified cryptographic algorithm AES operating in **GCM mode as defined in FCS\_COP.1/AEAD** and [selection:

- *CBC mode as defined in FCS\_COP.1/SKC*
- *CTR mode as defined in FCS\_COP.1/SKC*
- *XTS mode as defined in FCS\_COP.1/SKC*
- *CCM mode as defined in FCS\_COP.1/AEAD*
- ***no other modes***

].

**Application Note:** Other AES modes are selectable if the TSF uses them for another part of the TSF. A selection for 'no other modes' has been refined into the SFR because it is possible that a TOE may conform to the Base-PP by using AES-GCM exclusively for AES data encryption and decryption.

## FCS\_IPSEC\_EXT.1: IPsec Protocol

This ~~SER~~ has been modified from its definition in the NDcPP to support this module's IPsec requirements by mandating use of AES-GCM-256 and IKEv2 where applicable. Any element that is not mentioned in this section is unchanged from its definition in the ~~Base-PP~~.

**FCS\_IPSEC\_EXT.1.4:** This element has been modified to require the use of CNSA 1.0-compliant parameters.

The text of FCS\_IPSEC\_EXT.1.4 is replaced with:

**FCS\_IPSEC\_EXT.1.4** The ~~TSF~~ shall implement the IPsec protocol ESP as defined by RFC 4303 using the cryptographic algorithms **AES-GCM-256 (RFC 4106)** and [**no other algorithms**] together with a Secure Hash Algorithm (SHA)-based HMAC [**selection: HMAC-SHA-384, no HMAC algorithm**].

**Application Note:** SHA-based HMAC is not required since AES-GCM satisfies both confidentiality and integrity functions. IPsec may use a truncated version of the SHA-based HMAC functions contained in the selections. Where a truncated output is used, this is described in the ~~TSS~~.

**FCS\_IPSEC\_EXT.1.5:** This element has been modified from its definition in the NDcPP by choosing only the selection for IKEv2, which is selectable in the original definition of the element. It has also been modified to mandate the selection of RFC 4868 conformance due to the required support for SHA-384.

The text of FCS\_IPSEC\_EXT.1.5 is replaced with:

**FCS\_IPSEC\_EXT.1.5** The ~~TSF~~ shall implement the protocol: [

- *IKEv2 as defined in RFC 7296 [**selection: with no support for NAT traversal, with mandatory support for NAT traversal as specified in RFC 7296, Section 2.23**, and [**RFC 4868 for hash functions**]]*

]

**FCS\_IPSEC\_EXT.1.6:** This ~~SER~~ is modified from its definition in the ~~Base-PP~~ to remove support for non-CNSA parameters and algorithms. This includes mandating the use of IKEv2.

The text of FCS\_IPSEC\_EXT.1.6 is replaced with:

**FCS\_IPSEC\_EXT.1.6** The ~~TSF~~ shall ensure the encrypted payload in the [**IKEv2**] protocol uses the cryptographic algorithms [**AES-GCM-256 (specified in RFC 5282)**].

**Application Note:** This element is changed from its definition in the ~~Base-PP~~ to mandate support of 256-bit GCM. AES-GCM implementation for IPsec is specified in RFC 5282.

**FCS\_IPSEC\_EXT.1.7:** This element has been modified from its definition in the NDcPP by choosing only the selection for IKEv2, which is selectable in the original definition of the element.

The text of FCS\_IPSEC\_EXT.1.7 is replaced with:

**FCS\_IPSEC\_EXT.1.7** The ~~TSF~~ shall ensure that [

- *IKEv2 SA lifetimes can be configured by a Security Administrator based on [**selection: number of bytes**, **length of time**, where the time values can be configured between [**assignment: minimum configurable rekey time**] and [**assignment: maximum configurable rekey time**]]*

]

].

**FCS\_IPSEC\_EXT.1.8:** This element has been modified from its definition in the NDcPP by choosing only the selection for IKEv2, which is selectable in the original definition of the element.

The text of FCS\_IPSEC\_EXT.1.8 is replaced with:

**FCS\_IPSEC\_EXT.1.8** The TSF shall ensure that [

- *IKEv2 Child SA lifetimes can be configured by a Security Administrator based on [selection]:*
  - *number of bytes;*
  - *length of time, where the time values can be configured between [assignment: minimum configurable rekey time] and [assignment: maximum configurable rekey time]*

].

].

**FCS\_IPSEC\_EXT.1.10:** This element has been modified from its definition in the NDcPP by choosing only the selection for IKEv2, which is selectable in the original definition of the element.

The text of FCS\_IPSEC\_EXT.1.10 is replaced with:

**FCS\_IPSEC\_EXT.1.10** The shall generate nonces used in [IKEv2] protocol exchanges of length [selection]:

- *according to the security strength associated with the negotiated Diffie-Hellman group;*
- *at least 128 bits in size and at least half the output size of the negotiated pseudorandom function (PRF) hash*

].

**FCS\_IPSEC\_EXT.1.11:** This element has been modified from its definition in the NDcPP by mandating DH group 20, which is selectable in the original definition of the element. The selectable options have also been restricted to conform with CNSA 1.0 parameters.

The text of FCS\_IPSEC\_EXT.1.11 is replaced with:

**FCS\_IPSEC\_EXT.1.11** The TSF shall ensure that IKE protocols implement DH groups [

- **20 (384-bit Random ECP) and [selection: 21 (521-bit Random ECP, no other groups] according to RFC 5114**

] and [

- **[selection: 15 (3072-bit MODP), 16 (4096-bit MODP), 17 (6144-bit MODP), 18 (8192-bit MODP), no other groups] according to RFC 3526**

].

**Application Note:** This element has been modified from its definition in the NDcPP by mandating DH group 20, which is selectable in the original definition of the element. Any groups other than 20 that are allowed per the element may be selected by the ST author but they are not required for conformance to this PP-Module.

**FCS\_IPSEC\_EXT.1.12:** This element has been modified from its definition in the NDcPP by choosing only the selections for IKEv2, which are selectable in the original definition of the element.

The text of FCS\_IPSEC\_EXT.1.12 is replaced with:

**FCS\_IPSEC\_EXT.1.12** The TSF shall be able to ensure that the strength of the symmetric algorithm (in terms of the number of bits in the key) negotiated to protect the [**selection: IKEv2 IKE\_SA**] connection is greater than or equal to the strength of the symmetric algorithm (in terms of the number of bits in the key) negotiated to protect the [**selection: IKEv2 CHILD\_SA**] connection.

**Application Note:** Because this PP-Module only permits the use of 256-bit symmetric algorithms, this requirement will be satisfied by default.

**FCS\_IPSEC\_EXT.1.13:** This SFR is modified from its definition in the Base-PP by mandating the use of IKEv2 and its authentication methods.

The text of FCS\_IPSEC\_EXT.1.13 is replaced with:

**FCS\_IPSEC\_EXT.1.13** The TSF shall ensure that **IKEv2** performs peer authentication using [**selection: RSA, ECDSA**] that use X.509v3 certificates that conform to RFC 4945 and [**selection: Pre-shared Keys that conform to RFC 8784, Pre-shared Keys transmitted via EAP-TTLS, EAP-TLS, no other method**].

**Application Note:** At least one public-key-based Peer Authentication method is required in order to conform to this PP-Module; one or more of the public key schemes is chosen by the ST author to reflect what is implemented. The ST author also ensures that appropriate FCS requirements reflecting the algorithms used (and key generation capabilities, if provided) are listed to support those methods. Note that the TSS will elaborate on the way in which these algorithms are to be used.

If a selection with “EAP-TLS” or “EAP-TTLS” is chosen, the selection-based requirement [FCS\\_EAP\\_EXT.1](#) must be claimed. When an EAP method is used, verification occurs via an external authentication server. Though EAP-TTLS involves PSKs, [FIA\\_PSK\\_EXT.1](#) is not claimed because PSK requirements for EAP-TTLS are addressed instead via the Authentication Server PP.

If “pre-shared keys that conform to RFC 8784” is chosen, the selection-based requirement [FIA\\_PSK\\_EXT.1](#) must be claimed.

Multifactor support can be achieved via traffic filtering in accordance with [FPF\\_MFA\\_EXT.1](#).

It is acceptable for different use cases to leverage different selections. If this is the case, it must be identified.

**FCS\_IPSEC\_EXT.1.14:** This SFR is modified from its definition in the Base-PP to require DN to be supported for certificate reference identifiers.

The text of FCS\_IPSEC\_EXT.1.14 is replaced with:

**FCS\_IPSEC\_EXT.1.14** The TSF shall only establish a trusted channel if the presented identifier in the received certificate matches the configured reference identifier, where the presented and reference identifiers are of the following fields and types: **Distinguished Name (DN)**, [**selection: SAN: IP address, SAN: Fully Qualified Domain Name (FQDN), SAN: user FQDN, CN: IP address, CN: FQDN, CN: user FQDN, no other reference identifier types, [assignment: other supported reference identifier types]**].

**Application Note:** This PP-Module requires DN to be supported for certificate reference identifiers at minimum. Other selections may be made by the ST author but they are not required for conformance to

this PP-Module.

### 5.1.1.2 Security Management (FMT)

#### FMT\_MTD.1/CryptoKeys: Management of TSF Data

This SFR, defined in the NDcPP as selection-based, is mandated for inclusion in this PP-Module because the refinements to FMT\_SMF.1 mandate its inclusion. Note that it is also refined to refer specifically to keys and certificates used for VPN operation.

The text of FMT\_MTD.1.1/CryptoKeys is replaced with:

**FMT\_MTD.1.1/CryptoKeys** The TSF shall restrict the ability to [manage] the [cryptographic keys **and certificates used for VPN operation**] to [Security Administrators].

## 5.2 TOE Security Functional Requirements

The following section describes the SFRs that must be satisfied by any TOE that claims conformance to this PP-Module. These SFRs must be claimed regardless of which PP-Configuration is used to define the TOE.

### 5.2.1 Auditable Events for Mandatory SFRs

Table 2: Auditable Events for Mandatory Requirements

Requirement	Auditable Events	Additional Audit Record Contents
FAU_GEN.1/VPN	No events specified	N/A
FCS_CKM.1/IKE	No events specified	N/A
FMT_SMF.1/VPN	All administrative actions	No additional information.
FPF_RUL_EXT.1	Application of rules configured with the 'log' operation	<ul style="list-style-type: none"><li>• Source and destination addresses</li><li>• Source and destination ports</li><li>• Transport layer protocol</li></ul>
FPT_FLS.1/SelfTest	No events specified	N/A
FPT_TST_EXT.3	No events specified	N/A
FTP_ITC.1/VPN	Initiation of the trusted channel	No additional information.
	Termination of the trusted channel	No additional information.
	Failure of the trusted channel functions	Identification of the initiator and target of failed trusted channel establishment attempt

### 5.2.2 Security Audit (FAU)

#### FAU\_GEN.1/VPN Audit Data Generation (VPN Gateway)

## FAU\_GEN.1.1/VPN

The TSF shall be able to generate audit data of the following auditable events:

- a. Start-up and shutdown of the audit functions
- b. All auditable events for the [not specified] level of audit;
- c. [Indication that TSF self-test was completed]
- d. Failure of self-test
- e. *auditable events defined in the Auditable Events for Mandatory Requirements table*.

**Application Note:** The "Start-up and shutdown of the audit functions" event is identical to the event defined in the Base-PP's iteration of FAU\_GEN.1. The TOE is not required to have two separate events for this behavior if there is only a single audit stream that which all audit events use. If the TOE does maintain a separate logging facility for VPN gateway-related behavior, then this event must be addressed for it. Note that if the audit functions cannot be started and stopped separately from the TOE itself, then auditing the start-up and shutdown of the TOE is sufficient to address this.

## FAU\_GEN.1.2/VPN

The TSF shall record within the audit data at least the following information:

- a. Date and time of the event, type of event, subject identity (if applicable), and the outcome (success or failure) of the event;
- b. For each audit event type, based on the auditable event definitions of the functional components included in the PP, PP-Module, functional package or ST, [*additional information defined in the Auditable Events for Mandatory Requirements table for each auditable event, where applicable*].

**Application Note:** The ST author only needs to include the auditable events that correspond to the SFRs claimed in the ST. The TOE is not required to generate auditable events for selection-based or optional SFRs that it does not claim.

## Evaluation Activities

### FAU\_GEN.1/VPN

#### TSS

*The evaluator shall examine the TSS to verify that it describes the audit mechanisms that the TOE uses to generate audit records for VPN gateway behavior. If any audit mechanisms the TSF uses for this are not used to generate audit records for events defined by FAU\_GEN.1 in the Base-PP, the evaluator shall ensure that any VPN gateway-specific audit mechanisms also meet the relevant functional claims from the Base-PP.*

*For example, FAU\_STG\_EXT.1 requires all audit records to be transmitted to the QE over a trusted channel. This includes the audit records that are required by FAU\_GEN.1/VPN. Therefore, if the TOE has an audit mechanism that is only used for VPN gateway functionality, the evaluator shall ensure that the VPN gateway related audit records meet this requirement, even if the mechanism used to generate these audit records does not apply to any of the auditable events defined in the Base-PP.*

#### Guidance

*The evaluator shall examine the operational guidance to verify that it identifies all security-relevant auditable events claimed in the ST and includes sample records of each event type. If the TOE uses multiple audit mechanisms to generate different sets of records, the evaluator shall verify that the*

*operational guidance identifies the audit records that are associated with each of the mechanisms such that the source of each audit record type is clear.*

#### **Tests**

*The evaluator shall test the audit functionality by performing actions that trigger each of the claimed audit events and verifying that the audit records are accurate and that their format is consistent with what is specified in the operational guidance. The evaluator may generate these audit events as a consequence of performing other tests that would cause these events to be generated.*

### **5.2.3 Cryptographic Support (FCS)**

#### **FCS\_CKM.1/IKE Cryptographic Key Generation (for IKE Peer Authentication)**

##### **FCS\_CKM.1.1/IKE**

The **TSF** shall generate **asymmetric** cryptographic keys **used for IKE peer authentication** in accordance with a specified cryptographic key generation algorithm: *[selection: FIPS PUB 186-5, “Digital Signature Standard (DSS),” Appendix B.3 for RSA schemes, FIPS PUB 186-5, “Digital Signature Standard (DSS),” Appendix B.4 for ECDSA schemes, and implementing “NIST curves” P-384] and [selection:*

- *FFC Schemes using “safe-prime” groups that meet the following: NIST Special Publication 800-56A Revision 3, “Recommendation for Pair-Wise Key Establishment Schemes Using Discrete Logarithm Cryptography” and [selection: RFC 3526, RFC 7919]*
- *no other key generation algorithm*

*] and specified cryptographic key sizes [assignment: key size equivalent to, or greater than, a symmetric key strength of 256 bits] that meet the following: [no standard].*

**Application Note:** The keys that are required to be generated by the **TOE** through this requirement are intended to be used for the authentication of the **VPN** peers during the IKEv2 key exchange. FCS\_CKM.1 in the **Base\_PP** is intended to be used for mechanisms required by the **SFRs** in the **Base\_PP**. While it is required that the public key be associated with an identity in an X509v3 certificate, this association is not required to be performed by the **TOE**, and instead is expected to be performed by a **CA** in the **QE**.

As indicated in FCS\_IPSEC\_EXT.1, the **TOE** is required to implement RSA, ECDSA, or both for peer authentication.

The generated key strength of 2048-bit RSA keys need to be equivalent to, or greater than, a symmetric key strength of 112 bits. See NIST Special Publication 800-57, “Recommendation for Key Management” for information about equivalent key strengths.

#### **Evaluation Activities**

[\*\*FCS\\_CKM.1/IKE\*\*](#)  
**TSS**

The evaluator shall check to ensure that the *TSS* describes how the key-pairs are generated. In order to show that the *TSF* implementation complies with FIPS PUB 186-5, the evaluator shall ensure that the *TSS* contains the following information:

- The *TSS* shall list all sections of Appendix B to which the *TOE* complies
- For each applicable section listed in the *TSS*, for all statements that are not "shall" (that is, "shall not," "should," and "should not"), if the *TOE* implements such options it shall be described in the *TSS*. If the included functionality is indicated as "shall not" or "should not" in the standard, the *TSS* shall provide a rationale for why this will not adversely affect the security policy implemented by the *TOE*
- For each applicable section of Appendix B, any omission of functionality related to "shall" or "should" statements shall be described

Any *TOE*-specific extensions, processing that is not included in the Appendices, or alternative implementations allowed by the Appendices that may impact the security requirements the *TOE* is to enforce shall be described.

### **Guidance**

The evaluator shall check that the operational guidance describes how the key generation functionality is invoked, and describes the inputs and outputs associated with the process for each signature scheme supported. The evaluator shall also check that guidance is provided regarding the format and location of the output of the key generation process.

### **Tests**

#### **For FFC Schemes using “safe-prime” groups:**

Testing for FFC Schemes using safe-prime groups is done as part of testing in FCS\_CKM.2.

#### **For all other selections:**

The evaluator shall perform the corresponding tests for FCS\_CKM.1 specified in the NDcPP SD, based on the selections chosen for this *SFR*. If IKE key generation is implemented by a different algorithm than the NDcPP key generation function, the evaluator shall ensure this testing is performed using the correct implementation.

## **5.2.4 Security Management (FMT)**

### **FMT\_SMF.1/VPN Specification of Management Functions**

#### **FMT\_SMF.1.1/VPN**

The *TSF* shall be capable of performing the following management functions [

- Definition of packet filtering rules
- Association of packet filtering rules to network interfaces
- Ordering of packet filtering rules by priority

#### **[selection:**

- Configuration of remote VPN client session timeout
- Configuration of attributes used to deny establishment of remote VPN client sessions
- Generation of bit-based pre-shared key
- No other capabilities

]].

**Application Note:** This *SFR* defines additional management functions for the *TOE* beyond what is defined in the *Base-PP* as FMT\_SMF.1. The *TOE* may have all management functionality implemented in the same logical interface; it is not

necessary for “network device management” and “VPN gateway management” to be implemented in separate interfaces.

## Evaluation Activities ▾

### [\*\*FMT\\_SMF.1/VPN\*\*](#)

#### **TSS**

The evaluator shall examine the **TSS** to confirm that all management functions specified in [\*\*FMT\\_SMF.1/VPN\*\*](#) are provided by the **TOE**. As with **FMT\_SMF.1** in the **Base-PP**, the evaluator shall ensure that the **TSS** identifies what logical interfaces are used to perform these functions and that this includes a description of the local administrative interface.

#### **Guidance**

The evaluator shall examine the operational guidance to confirm that all management functions specified in [\*\*FMT\\_SMF.1/VPN\*\*](#) are provided by the **TOE**. As with **FMT\_SMF.1** in the **Base-PP**, the evaluator shall ensure that the operational guidance identifies what logical interfaces are used to perform these functions and that this includes a description of the local administrative interface.

#### **Tests**

The evaluator tests management functions as part of performing other test EAs. No separate testing for [\*\*FMT\\_SMF.1/VPN\*\*](#) is required unless one of the management functions in [\*\*FMT\\_SMF.1.1/VPN\*\*](#) has not already been exercised under any other **SFR**.

## 5.2.5 Packet Filtering (FPF)

### **FPF\_RUL\_EXT.1 Packet Filtering Rules**

#### **FPF\_RUL\_EXT.1.1**

The **TSF** shall perform packet filtering on network packets processed by the **TOE**.

#### **FPF\_RUL\_EXT.1.2**

The **TSF** shall allow the definition of packet filtering rules using the following network protocols and protocol fields: [

- *IPv4 (RFC 791)*
  - *source address*
  - *destination address*
  - *protocol*
- *IPv6 (RFC 8200)*
  - *source address*
  - *destination address*
  - *next header (protocol)*
- *TCP (RFC 793)*
  - *source port*
  - *destination port*
- *UDP (RFC 768)*
  - *source port*
  - *destination port*

].

**Application Note:** This element identifies the protocols and references the protocol definitions that serve to define to what extent the network traffic can be interpreted by the **TOE** when importing (receiving network traffic or ingress) and exporting (sending—or forming to be sent—network traffic or egress).

While the protocol formatting specified in the RFCs is still used, many RFCs define behaviors which are no longer considered safe to follow. For example, RFC 792 defined the “Redirect” Internet Control Message Protocol (**ICMP**) type, which is not considered safe to honor when it might come from an adversary; the “source quench” message, which is insecure because its source cannot be validated.

It also identifies the various attributes that are applicable when constructing rules to be enforced by this requirement – the applicable interface is a property of the **TOE** and the rest of the identified attributes are defined in the associated RFCs. Note that the Protocol is the IPv4 field (in IPv6 this field is called the “next header”) that identifies the applicable protocol, such as TCP, UDP, **ICMP**, etc. Also, ‘Interface’ identified above is the external port where the applicable network traffic was received or alternately will be sent.

#### FPF\_RUL\_EXT.1.3

The **TSF** shall allow the following operations to be associated with packet filtering rules: permit and drop with the capability to log the operation.

**Application Note:** This element defines the operations that can be associated with rules used to match network traffic.

#### FPF\_RUL\_EXT.1.4

The **TSF** shall allow the packet filtering rules to be assigned to each distinct network interface.

**Application Note:** This element identifies where rules can be assigned. Specifically, a conforming **TOE** must be able to assign filtering rules specific to each of its available and identifiable distinct network interfaces that handle layer 3 and 4 network traffic. Identifiable means the interface is unique and identifiable within the **TOE**, and does not necessarily require the interface to be visible from the network perspective (e.g., does not need to have an IP address assigned to it). A distinct network interface is one or more physical connections that share a common logical path into the **TOE**. For example, the **TOE** might have a small form-factor pluggable (**SFP**) port supporting **SFP** modules that expose a number of physical network ports, but since a common driver is used for all external ports they can be treated as a single distinct network interface.

Note that there could be a separate ruleset for each interface or alternately a shared ruleset that somehow associates rules with specific interfaces.

#### FPF\_RUL\_EXT.1.5

The **TSF** shall process the applicable packet filtering rules (as determined in accordance with [FPF\\_RUL\\_EXT.1.4](#)) in the following order: [Administrator-defined].

**Application Note:** This element requires that an administrator is able to define the order in which configured filtering rules are processed for matches.

#### FPF\_RUL\_EXT.1.6

The **TSF** shall drop traffic if a matching rule is not identified.

**Application Note:** This element requires that the behavior is always to deny network traffic when no rules apply.

## Evaluation Activities ▾

### [FPF\\_RUL\\_EXT.1.1](#)

#### **TSS**

The evaluator shall verify that the **TSS** provide a description of the **TOE**'s initialization and startup process, which clearly indicates where processing of network packets begins to take place, and provides a discussion that supports the assertion that packets cannot flow during this process.

The evaluator shall verify that the **TSS** also includes a narrative that identifies the components (e.g., active entity such as a process or task) involved in processing the network packets and describes the safeguards that would prevent packets flowing through the **TOE** without applying the ruleset in the event of a component failure. This could include the failure of a component, such as a process being terminated, or a failure within a component, such as memory buffers full and cannot process packets.

#### **Guidance**

The operational guidance associated with this requirement is assessed in the subsequent test EAs.

#### **Tests**

The evaluator shall perform the following tests:

- **Test FPF\_RUL\_EXT.1.1:1:** The evaluator shall attempt to get network traffic to flow through the **TOE** while the **TOE** is being initialized. A steady flow of network packets that would otherwise be denied by the ruleset should be sourced and directed to a host. The evaluator shall use a packet sniffer to verify none of the generated network traffic is permitted through the **TOE** during initialization.
- **Test FPF\_RUL\_EXT.1.1:2:** The evaluator shall attempt to get network traffic to flow through the **TOE** while the **TOE** is being initialized. A steady flow of network packets that would be permitted by the ruleset should be sourced and directed to a host. The evaluator shall use a packet sniffer to verify none of the generated network traffic is permitted through the **TOE** during initialization and is only permitted once initialization is complete.

Note: The remaining testing associated with application of the ruleset is addressed in the subsequent test EAs.

### [FPF\\_RUL\\_EXT.1.2](#)

There are no EAs specified for this element. Definition of packet filtering policy, association of operations with packet filtering rules, and association of these rules to network interfaces is described collectively under [FPF\\_RUL\\_EXT.1.4](#).

### [FPF\\_RUL\\_EXT.1.3](#)

There are no EAs specified for this element. Definition of packet filtering policy, association of operations with packet filtering rules, and association of these rules to network interfaces is described collectively under [FPF\\_RUL\\_EXT.1.4](#).

### [FPF\\_RUL\\_EXT.1.4](#)

#### **TSS**

The evaluator shall verify that the **TSS** describes a packet filtering policy that can use the following fields for each identified protocol, and that the RFCs identified for each protocol are supported:

- IPv4 (RFC 791)
  - source address
  - destination address

- protocol
- IPv6 (RFC 8200)
  - source address
  - destination address
  - next header (protocol)
- TCP (RFC 793)
  - source port
  - destination port
- UDP (RFC 768)
  - source port
  - destination port

The evaluator shall verify that the TSS describes how conformance with the identified RFCs has been determined by the TOE developer (e.g., third party interoperability testing, protocol compliance testing).

The evaluator shall verify that each rule can identify the following actions: permit, discard, and log. The evaluator shall verify that the TSS identifies all interface types subject to the packet filtering policy and explains how rules are associated with distinct network interfaces. Where interfaces can be grouped into a common interface type (e.g., where the same internal logical path is used, perhaps where a common device driver is used), they can be treated collectively as a distinct network interface.

### **Guidance**

The evaluator shall verify that the operational guidance identifies the following protocols as being supported and the following attributes as being configurable within packet filtering rules for the associated protocols:

- IPv4 (RFC 791)
  - destination address
  - protocol
- IPv6 (RFC 8200)
  - source address
  - destination address
  - next header (protocol)
- TCP (RFC 793)
  - source port
  - destination port
- UDP (RFC 768)
  - source port
  - destination port

The evaluator shall verify that the operational guidance indicates that each rule can identify the following actions: permit, discard, and log.

The evaluator shall verify that the operational guidance explains how rules are associated with distinct network interfaces.

The guidance may describe the other protocols contained within the ST (e.g., IPsec, IKE, potentially HTTPS, SSH, and TLS) that are processed by the TOE. The evaluator shall ensure that it is made clear what protocols were not considered as part of the TOE evaluation.

### **Tests**

*The evaluator shall perform the following tests:*

- *Test FPF\_RUL\_EXT.1.4:1: The evaluator shall use the instructions in the operational guidance to test that packet filter rules can be created that permit, discard, and log packets for each of the following attributes:*
  - *IPv4*
    - *Destination Address*
    - *Protocol*
  - *IPv6*
    - *Source address*
    - *Destination Address*
    - *Next Header (Protocol)*
  - *TCP*
    - *Source Port*
    - *Destination Port*
  - *UDP*
    - *Source Port*
    - *Destination Port*
- *Test FPF\_RUL\_EXT.1.4:2: The evaluator shall repeat Test 1 above for each distinct network interface type supported by the TOE to ensure that packet filtering rules can be defined for all supported types.*

*Note that these test activities should be performed in conjunction with those of FPF\_RUL\_EXT.1.6 where the effectiveness of the rules is tested; here the evaluator is just ensuring the guidance is sufficient and the TOE supports the administrator creating a ruleset based on the above attributes. The test activities for FPF\_RUL\_EXT.1.6 define the combinations of protocols and attributes required to be tested. If those combinations are configured manually, that will fulfill the objective of these test activities, but if those combinations are configured otherwise (e.g., using automation), these test activities may be necessary in order to ensure the guidance is correct and the full range of configurations can be achieved by a TOE administrator.*

### ***FPF\_RUL\_EXT.1.5***

#### ***TSS***

*The evaluator shall verify that the TSS describes the algorithm applied to incoming packets, including the processing of default rules, determination of whether a packet is part of an established session, and application of administrator defined and ordered ruleset.*

#### ***Guidance***

*The evaluator shall verify that the operational guidance describes how the order of packet filtering rules is determined and provides the necessary instructions so that an administrator can configure the order of rule processing.*

#### ***Tests***

*The evaluator shall perform the following tests:*

- *Test FPF\_RUL\_EXT.1.5:1: The evaluator shall devise two equal packet filtering rules with alternate operations – permit and discard. The rules should then be deployed in two distinct orders and in each case the evaluator shall ensure that the first rule is enforced in both cases by generating applicable packets and using packet capture and logs for confirmation.*
- *Test FPF\_RUL\_EXT.1.5:2: The evaluator shall repeat the procedure above, except that the two rules should be devised where one is a subset of the other (e.g., a specific address vs. a network segment). Again, the evaluator shall test both orders to ensure that the first is enforced regardless of the specificity of the rule.*

## FPF\_RUL\_EXT.1.6

### **TSS**

The evaluator shall verify that the **TSS** describes the process for applying packet filtering rules and also that the behavior (either by default, or as configured by the administrator) is to discard packets when there is no rule match. The evaluator shall verify the **TSS** describes when the IPv4 and IPv6 protocols supported by the **TOE** differ from the full list provided in the RFC Values for IPv4 and IPv6 table.

### **Guidance**

The evaluator shall verify that the operational guidance describes the behavior if no rules or special conditions apply to the network traffic. If the behavior is configurable, the evaluator shall verify that the operational guidance provides the appropriate instructions to configure the behavior to discard packets with no matching rules. The evaluator shall verify that the operational guidance describes the range of IPv4 and IPv6 protocols supported by the **TOE**.

### **Tests**

The evaluator shall perform the following tests:

- Test FPF\_RUL\_EXT.1.6:1: The evaluator shall configure the **TOE** to permit and log each supported IPv4 Transport Layer Protocol (see RFC Values for IPv4 and IPv6 table for full possible list) in conjunction with a specific source address and specific destination address, specific source address and wildcard destination address, wildcard source address and specific destination address, and wildcard source address and wildcard destination address. The evaluator shall generate packets matching each supported IPv4 Transport Layer Protocol and within the configured source and destination addresses in order to ensure that the supported protocols are permitted (i.e., by capturing the packets after passing through the **TOE**) and logged. Any protocols not supported by the **TOE** must be denied.
- Test FPF\_RUL\_EXT.1.6:2: The evaluator shall configure the **TOE** to permit all traffic except to discard and log each supported IPv4 Transport Layer Protocol (see RFC Values for IPv4 and IPv6 table for full possible list) in conjunction with a specific source address and specific destination address, specific source address and wildcard destination address, wildcard source address and specific destination address, and wildcard source address and wildcard destination address. The evaluator shall generate packets matching each defined IPv4 Transport Layer Protocol and within the configured source and destination addresses in order to ensure that the supported protocols are denied (i.e., by capturing no applicable packets passing through the **TOE**) and logged. Any protocols not supported by the **TOE** must also be denied but are not required to be logged.
- Test FPF\_RUL\_EXT.1.6:3: The evaluator shall configure the **TOE** to permit and log each supported IPv4 Transport Layer Protocol (see RFC Values for IPv4 and IPv6 table for full possible list) in conjunction with a specific source address and specific destination address, specific source address and wildcard destination address, wildcard source address and specific destination address, and wildcard source address and wildcard destination address. Additionally, the evaluator shall configure the **TOE** to discard and log each supported IPv4 Transport Layer Protocol (see RFC Values for IPv4 and IPv6 table for full possible list) in conjunction with different (than those permitted above) combinations of a specific source address and specific destination address, specific source address and wildcard destination address, wildcard source address and specific destination address, and wildcard source address and wildcard destination address. The evaluator shall generate packets matching each supported IPv4 Transport Layer Protocol and outside the scope of all source and destination addresses configured above in order to ensure that the supported protocols are denied (i.e., by capturing no applicable packets passing through the **TOE**) and logged. Any protocols not supported by the **TOE** must be denied.
- Test FPF\_RUL\_EXT.1.6:4: The evaluator shall configure the **TOE** to permit and log each supported IPv6 Transport Layer Protocol (see RFC Values for IPv4 and IPv6 table for full possible list) in conjunction with a specific source address and specific destination address, specific source address and wildcard destination address, wildcard source address and

*specific destination address, and wildcard source address and wildcard destination address. The evaluator shall generate packets matching each defined IPv6 Transport Layer Protocol and within the configured source and destination addresses in order to ensure that the supported protocols are permitted (i.e., by capturing the packets after passing through the TOE) and logged. Any protocols not supported by the TOE must be denied.*

- *Test FPF\_RUL\_EXT.1.6:5: The evaluator shall configure the TOE to permit all traffic except to discard and log each supported IPv6 Transport Layer Protocol (see RFC Values for IPv4 and IPv6 table for full possible list) in conjunction with a specific source address and specific destination address, specific source address and wildcard destination address, wildcard source address and specific destination address, and wildcard source address and wildcard destination address. The evaluator shall generate packets matching each defined IPv6 Transport Layer Protocol and within the configured source and destination addresses in order to ensure that the supported protocols are denied (i.e., by capturing no applicable packets passing through the TOE) and logged. Any protocols not supported by the TOE must also be denied but are not required to be logged.*
- *Test FPF\_RUL\_EXT.1.6:6: The evaluator shall configure the TOE to permit and log each supported IPv6 Transport Layer Protocol (see RFC Values for IPv4 and IPv6 table for full possible list) in conjunction with a specific source address and specific destination address, specific source address and wildcard destination address, wildcard source address and specific destination address, and wildcard source address and wildcard destination address. Additionally, the evaluator shall configure the TOE to discard and log each supported IPv6 Transport Layer Protocol (see RFC Values for IPv4 and IPv6 table for full possible list) in conjunction with different (than those permitted above) combinations of a specific source address and specific destination address, specific source address and wildcard destination address, wildcard source address and specific destination address, and wildcard source address and wildcard destination address. The evaluator shall generate packets matching each defined IPv6 Transport Layer Protocol and outside the scope of all source and destination addresses configured above in order to ensure that the supported protocols are dropped (i.e., by capturing no applicable packets passing through the TOE) and logged. Any protocols not supported by the TOE must be denied.*
- *Test FPF\_RUL\_EXT.1.6:7: The evaluator shall configure the TOE to permit and log protocol 6 (TCP) using a selected source port, a selected destination port, and a selected source and destination port combination. The evaluator shall generate packets matching the configured source and destination TCP ports in order to ensure that they are permitted (i.e., by capturing the packets after passing through the TOE) and logged.*
- *Test FPF\_RUL\_EXT.1.6:8: The evaluator shall configure the TOE to discard and log protocol 6 (TCP) using a selected source port, a selected destination port, and a selected source and destination port combination. The evaluator shall generate packets matching the configured source and destination TCP ports in order to ensure that they are denied (i.e., by capturing no applicable packets passing through the TOE) and logged.*
- *Test FPF\_RUL\_EXT.1.6:9: The evaluator shall configure the TOE to permit and log protocol 17 (UDP) using a selected source port, a selected destination port, and a selected source and destination port combination. The evaluator shall generate packets matching the configured source and destination UDP ports in order to ensure that they are permitted (i.e., by capturing the packets after passing through the TOE) and logged. Here the evaluator shall ensure that the UDP port 500 (IKE) is included in the set of tests.*
- *Test FPF\_RUL\_EXT.1.6:10: The evaluator shall configure the TOE to discard and log protocol 17 (UDP) using a selected source port, a selected destination port, and a selected source and destination port combination. The evaluator shall generate packets matching the configured source and destination UDP ports in order to ensure that they are denied (i.e., by capturing no applicable packets passing through the TOE) and logged. Again, the evaluator shall ensure that UDP port 500 is included in the set of tests.*

*The following table identifies the RFC defined values for the protocol fields for IPv4 and IPv6 to be used in configuring and otherwise testing packet filtering rule definition and enforcement:*

## **Protocol Defined Attributes**

IPv4	<ul style="list-style-type: none"><li>• <i>Transport Layer Protocol 1 - Internet Control Message</i></li><li>• <i>Transport Layer Protocol 2 - Internet Group Management</i></li><li>• <i>Transport Layer Protocol 3 - Gateway-to-Gateway</i></li><li>• <i>Transport Layer Protocol 4 - IP in IP (encapsulation)</i></li><li>• <i>Transport Layer Protocol 5 - Stream</i></li><li>• <i>Transport Layer Protocol 6 - Transmission Control</i></li><li>• <i>Transport Layer Protocol 7 - UCL</i></li><li>• <i>Transport Layer Protocol 8 - Exterior Gateway Protocol</i></li><li>• <i>Transport Layer Protocol 9 - Any private interior gateway</i></li><li>• <i>Transport Layer Protocol 10 - BBN RCC Monitoring</i></li><li>• <i>Transport Layer Protocol 11 - Network Voice Protocol</i></li><li>• <i>Transport Layer Protocol 12 - PUP</i></li><li>• <i>Transport Layer Protocol 13 - ARGUS</i></li><li>• <i>Transport Layer Protocol 14 - EMCON</i></li><li>• <i>Transport Layer Protocol 15 - Cross Net Debugger</i></li><li>• <i>Transport Layer Protocol 16 - Chaos</i></li><li>• <i>Transport Layer Protocol 17 - User Datagram</i></li><li>• <i>Transport Layer Protocol 18 - Multiplexing</i></li><li>• <i>Transport Layer Protocol 19 - DCN Measurement Subsystems</i></li><li>• <i>Transport Layer Protocol 20 - Host Monitoring</i></li><li>• <i>Transport Layer Protocol 21 - Packet Radio Measurement</i></li><li>• <i>Transport Layer Protocol 22 - XEROX NS IDP</i></li><li>• <i>Transport Layer Protocol 23 - Trunk-1</i></li><li>• <i>Transport Layer Protocol 24 - Trunk-2</i></li><li>• <i>Transport Layer Protocol 25 - Leaf-1</i></li><li>• <i>Transport Layer Protocol 26 - Leaf-2</i></li><li>• <i>Transport Layer Protocol 27 - Reliable Data Protocol</i></li><li>• <i>Transport Layer Protocol 28 - Internet Reliable Transaction</i></li><li>• <i>Transport Layer Protocol 29 - ISO Transport Protocol Class 4</i></li><li>• <i>Transport Layer Protocol 30 - Bulk Data Transfer Protocol</i></li><li>• <i>Transport Layer Protocol 31 - MFE Network Services Protocol</i></li><li>• <i>Transport Layer Protocol 32 - MERIT Internodal Protocol</i></li><li>• <i>Transport Layer Protocol 33 - Sequential Exchange Protocol</i></li><li>• <i>Transport Layer Protocol 34 - Third Party Connect Protocol</i></li><li>• <i>Transport Layer Protocol 35 - Inter-Domain Policy Routing Protocol</i></li><li>• <i>Transport Layer Protocol 36 - XTP</i></li><li>• <i>Transport Layer Protocol 37 - Datagram Delivery Protocol</i></li><li>• <i>Transport Layer Protocol 38 - IDPR Control Message Transport Protocol</i></li><li>• <i>Transport Layer Protocol 39 - TP++ Transport Protocol</i></li><li>• <i>Transport Layer Protocol 40 - IL Transport Protocol</i></li><li>• <i>Transport Layer Protocol 41 - Simple Internet Protocol</i></li><li>• <i>Transport Layer Protocol 42 - Source Demand Routing Protocol</i></li><li>• <i>Transport Layer Protocol 43 - SIP Source Route</i></li><li>• <i>Transport Layer Protocol 44 - SIP Fragment</i></li><li>• <i>Transport Layer Protocol 45 - Inter-Domain Routing Protocol</i></li><li>• <i>Transport Layer Protocol 46 - Reservation Protocol</i></li><li>• <i>Transport Layer Protocol 47 - General Routing Encapsulation</i></li><li>• <i>Transport Layer Protocol 48 - Mobile Host Routing Protocol</i></li><li>• <i>Transport Layer Protocol 49 - BNA</i></li><li>• <i>Transport Layer Protocol 50 - SIPP Encap Security Payload</i></li><li>• <i>Transport Layer Protocol 51 - SIPP Authentication Header</i></li></ul>
------	---

- Transport Layer Protocol 52 - Integrated Net Layer Security TUBA
- Transport Layer Protocol 53 - IP with Encryption
- Transport Layer Protocol 54 - NBMA Next Hop Resolution Protocol
- Transport Layer Protocol 61 - Any host internal protocol
- Transport Layer Protocol 62 - CFTP
- Transport Layer Protocol 63 - Any local network
- Transport Layer Protocol 64 - SATNET and Backroom EXPAK
- Transport Layer Protocol 65 - Kryptolan
- Transport Layer Protocol 66 - MIT Remote Virtual Disk Protocol
- Transport Layer Protocol 67 - Internet Pluribus Packet Core
- Transport Layer Protocol 68 - Any distributed file system
- Transport Layer Protocol 69 - SATNET Monitoring
- Transport Layer Protocol 70 - VISA Protocol
- Transport Layer Protocol 71 - Internet Packet Core Utility
- Transport Layer Protocol 72 - Computer Protocol Network Executive
- Transport Layer Protocol 73 - Computer Protocol Heart Beat
- Transport Layer Protocol 74 - Wang Span Network
- Transport Layer Protocol 75 - Packet Video Protocol
- Transport Layer Protocol 76 - Backroom SATNET Monitoring
- Transport Layer Protocol 77 - SUN ND PROTOCOL-Temporary
- Transport Layer Protocol 78 - WIDEBAND Monitoring
- Transport Layer Protocol 79 - WIDEBAND EXPAK
- Transport Layer Protocol 80 - ISO Internet Protocol
- Transport Layer Protocol 81 - VMTP
- Transport Layer Protocol 82 - SECURE-VMTP
- Transport Layer Protocol 83 - VINES
- Transport Layer Protocol 84 - TTP
- Transport Layer Protocol 85 - NSFNET-IGP
- Transport Layer Protocol 86 - Dissimilar Gateway Protocol
- Transport Layer Protocol 87 - TCF
- Transport Layer Protocol 88 - IGRP
- Transport Layer Protocol 89 - OSPFIGP
- Transport Layer Protocol 90 - Sprite RPC Protocol
- Transport Layer Protocol 91 - Locus Address Resolution Protocol
- Transport Layer Protocol 92 - Multicast Transport Protocol
- Transport Layer Protocol 93 - AX.25 Frames
- Transport Layer Protocol 94 - IP-within-IP Encapsulation Protocol
- Transport Layer Protocol 95 - Mobile Internetworking Control Protocol
- Transport Layer Protocol 96 - Semaphore Communications Security Protocol
- Transport Layer Protocol 97 - Ethernet-within-IP Encapsulation
- Transport Layer Protocol 98 - Encapsulation Header
- Transport Layer Protocol 99 - Any private encryption scheme
- Transport Layer Protocol 100 - GMTP

## IPv6

- Transport Layer Protocol 1 - Internet Control Message
- Transport Layer Protocol 2 - Internet Group Management
- Transport Layer Protocol 3 - Gateway-to-Gateway
- Transport Layer Protocol 4 - IPv4 encapsulation
- Transport Layer Protocol 5 - Stream
- Transport Layer Protocol 6 - Transmission Control
- Transport Layer Protocol 7 - CBT
- Transport Layer Protocol 8 - Exterior Gateway Protocol
- Transport Layer Protocol 9 - Any private interior gateway
- Transport Layer Protocol 10 - BBN RCC Monitoring

- *Transport Layer Protocol 11 - Network Voice Protocol*
- *Transport Layer Protocol 12 - PUP*
- *Transport Layer Protocol 13 - ARGUS*
- *Transport Layer Protocol 14 - EMCON*
- *Transport Layer Protocol 15 - Cross Net Debugger*
- *Transport Layer Protocol 16 - Chaos*
- *Transport Layer Protocol 17 - User Datagram*
- *Transport Layer Protocol 18 - Multiplexing*
- *Transport Layer Protocol 19 - DCN Measurement Subsystems*
- *Transport Layer Protocol 20 - Host Monitoring*
- *Transport Layer Protocol 21 - Packet Radio Measurement*
- *Transport Layer Protocol 22 - XEROX NS IDP*
- *Transport Layer Protocol 23 - Trunk-1*
- *Transport Layer Protocol 24 - Trunk-2*
- *Transport Layer Protocol 25 - Leaf-1*
- *Transport Layer Protocol 26 - Leaf-2*
- *Transport Layer Protocol 27 - Reliable Data Protocol*
- *Transport Layer Protocol 28 - Internet Reliable Transaction*
- *Transport Layer Protocol 29 - Transport Protocol Class 4*
- *Transport Layer Protocol 30 - Bulk Data Transfer Protocol*
- *Transport Layer Protocol 31 - MFE Network Services Protocol*
- *Transport Layer Protocol 32 - MERIT Internodal Protocol*
- *Transport Layer Protocol 33 - Datagram Congestion Control Protocol*
- *Transport Layer Protocol 34 - Third Party Connect Protocol*
- *Transport Layer Protocol 35 - Inter-Domain Policy Routing Protocol*
- *Transport Layer Protocol 36 - XTP*
- *Transport Layer Protocol 37 - Datagram Delivery Protocol*
- *Transport Layer Protocol 38 - IDPR Control Message Transport Protocol*
- *Transport Layer Protocol 39 - TP++ Transport Protocol*
- *Transport Layer Protocol 40 - IL Transport Protocol*
- *Transport Layer Protocol 41 - IPv6 encapsulation*
- *Transport Layer Protocol 42 - Source Demand Routing Protocol*
- *Transport Layer Protocol 43 - Intentionally blank*
- *Transport Layer Protocol 44 - Intentionally blank*
- *Transport Layer Protocol 45 - Inter-Domain Routing Protocol*
- *Transport Layer Protocol 46 - Reservation Protocol*
- *Transport Layer Protocol 47 - General Routing Encapsulation*
- *Transport Layer Protocol 48 - Dynamic Source Routing Protocol*
- *Transport Layer Protocol 49 - BNA*
- *Transport Layer Protocol 50 - Intentionally Blank*
- *Transport Layer Protocol 51 - Intentionally Blank*
- *Transport Layer Protocol 52 - Integrated Net Layer Security*
- *Transport Layer Protocol 53 - IP with Encryption*
- *Transport Layer Protocol 54 - NBMA Address Resolution Protocol*
- *Transport Layer Protocol 55 - Mobility*
- *Transport Layer Protocol 56 - Transport Layer Security Protocol using Kryptonet key management*
- *Transport Layer Protocol 57 - SKIP*
- *Transport Layer Protocol 58 - ICMP for IPv6*
- *Transport Layer Protocol 59 - No Next Header for IPv6*
- *Transport Layer Protocol 60 - Intentionally Blank*
- *Transport Layer Protocol 61 - Any host internal protocol*
- *Transport Layer Protocol 62 - CFTP*
- *Transport Layer Protocol 63 - Any local network*

- Transport Layer Protocol 64 - SATNET and Backroom EXPAK
- Transport Layer Protocol 65 - Kryptolan
- Transport Layer Protocol 66 - MIT Remote Virtual Disk Protocol
- Transport Layer Protocol 67 - Internet Pluribus Packet Core
- Transport Layer Protocol 68 - Any distributed file system
- Transport Layer Protocol 69 - SATNET Monitoring
- Transport Layer Protocol 70 - VISA Protocol
- Transport Layer Protocol 71 - Internet Packet Core Utility
- Transport Layer Protocol 72 - Computer Protocol Network Executive
- Transport Layer Protocol 73 - Computer Protocol Heart Beat
- Transport Layer Protocol 74 - Wang Span Network
- Transport Layer Protocol 75 - Packet Video Protocol
- Transport Layer Protocol 76 - Backroom SATNET Monitoring
- Transport Layer Protocol 77 - SUN ND PROTOCOL-Temporary
- Transport Layer Protocol 78 - WIDEBAND Monitoring
- Transport Layer Protocol 79 - WIDEBAND EXPAK
- Transport Layer Protocol 80 - ISO Internet Protocol
- Transport Layer Protocol 81 - VMTP
- Transport Layer Protocol 82 - SECURE-VMTP
- Transport Layer Protocol 83 - VINES
- Transport Layer Protocol 84 - TTP
- Transport Layer Protocol 85 - Internet Protocol Traffic Manager
- Transport Layer Protocol 86 - NSFNET-IGP
- Transport Layer Protocol 87 - Dissimilar Gateway Protocol
- Transport Layer Protocol 88 - TCF
- Transport Layer Protocol 89 - EIGRP
- Transport Layer Protocol 90 - OSPFIGP
- Transport Layer Protocol 91 - Sprite RPC Protocol
- Transport Layer Protocol 92 - Locus Address Resolution Protocol
- Transport Layer Protocol 93 - Multicast Transport Protocol
- Transport Layer Protocol 94 - AX.25 Frames
- Transport Layer Protocol 95 - IP-within-IP Encapsulation Protocol
- Transport Layer Protocol 96 - Mobile Internetworking Control Pro.
- Transport Layer Protocol 97 - Semaphore Communications Sec. Pro.
- Transport Layer Protocol 98 - Ethernet-within-IP Encapsulation
- Transport Layer Protocol 99 - Encapsulation Header
- Transport Layer Protocol 100 - GMTP
- Transport Layer Protocol 101 - Ipsilon Flow Management Protocol
- Transport Layer Protocol 102 - PNNI over IP
- Transport Layer Protocol 103 - Protocol Independent Multicast
- Transport Layer Protocol 104 - ARIS
- Transport Layer Protocol 105 - SCPS Transport Layer Protocol
- Transport Layer Protocol 106 - QNX
- Transport Layer Protocol 107 - Active Networks
- Transport Layer Protocol 108 - Payload Compression Protocol
- Transport Layer Protocol 109 - Sitara Networks Protocol
- Transport Layer Protocol 110 - Compaq Peer Protocol
- Transport Layer Protocol 111 - IPX in IP
- Transport Layer Protocol 112 - Virtual Router Redundancy Protocol
- Transport Layer Protocol 113 - PGM Reliable Transport Protocol
- Transport Layer Protocol 114 - Any 0-hop protocol
- Transport Layer Protocol 115 - Layer Two Tunneling Protocol
- Transport Layer Protocol 116 - D-II Data Exchange (DDX)
- Transport Layer Protocol 117 - Interactive Agent Transfer Protocol

- Transport Layer Protocol 118 - Schedule Transfer Protocol
- Transport Layer Protocol 119 - SpectraLink Radio Protocol
- Transport Layer Protocol 120 - UTI
- Transport Layer Protocol 121 - Simple Message Protocol
- Transport Layer Protocol 122 - SM
- Transport Layer Protocol 123 - Performance Transparency Protocol
- Transport Layer Protocol 124 - ISIS over IPv4
- Transport Layer Protocol 125 - FIRE
- Transport Layer Protocol 126 - Combat Radio Transport Protocol
- Transport Layer Protocol 127 - Combat Radio User Datagram
- Transport Layer Protocol 128 - SSCOPMCE
- Transport Layer Protocol 129 - IPLT
- Transport Layer Protocol 130 - Secure Packet Shield
- Transport Layer Protocol 131 - Private IP Encapsulation within IP
- Transport Layer Protocol 132 - Stream Control Transmission Protocol
- Transport Layer Protocol 133 - Fibre Channel
- Transport Layer Protocol 134 - RSVP-E2E-IGNORE
- Transport Layer Protocol 135 - Mobility Header
- Transport Layer Protocol 136 - UDPLite
- Transport Layer Protocol 137 - MPLS-in-IP
- Transport Layer Protocol 138 - MANET Protocols
- Transport Layer Protocol 139 - Host Identity Protocol
- Transport Layer Protocol 140 - Shim6 Protocol
- Transport Layer Protocol 141 - Wrapped Encapsulating Security Payload
- Transport Layer Protocol 142 - Robust Header Compression

**Table 3: RFC Values for IPv4 and IPv6**

## 5.2.6 Protection of the TSF (FPT)

### FPT\_FLS.1/SelfTest Failure with Preservation of Secure State (Self-Test Failures)

#### FPT\_FLS.1.1/SelfTest

The TSF shall ~~preserve a secure state~~ **shut down** when the following types of failures occur: [failure of the power-on self-tests, failure of integrity check of the TSF executable image, failure of noise source health tests].

**Application Note:** This SFR defines the expected TSF response to failures of the self-tests defined in the Base-PP.

#### Evaluation Activities

##### FPT\_FLS.1/SelfTest

##### TSS

The evaluator shall ensure the TSS describes how the TOE ensures a shutdown upon a self-test failure, a failed integrity check of the TSF executable image, or a failed health test of the noise source. If there are instances when a shutdown does not occur, (e.g., a failure is deemed non-security relevant), the evaluator shall ensure that those cases are identified and a rationale is provided that supports the classification and justifies why the TOE's ability to enforce its security policies is not affected in any such instance.

#### **Guidance**

The evaluator shall verify that the operational guidance provides information on the self-test failures that can cause the TOE to shut down and how to diagnose the specific failure that has occurred, including possible remediation steps if available.

#### **Tests**

There are no test EAs for this component.

### **FPT\_TST\_EXT.3 Self-Test with Defined Methods**

#### **FPT\_TST\_EXT.3.1**

The TSF shall run a suite of the following self-tests [*when loaded for execution*] to demonstrate the correct operation of the TSF: [*integrity verification of stored executable code*].

#### **FPT\_TST\_EXT.3.2**

The TSF shall execute the self-testing through [*a TSF-provided cryptographic service specified in FCS\_COP.1/SigGen (from NDcPP)*].

**Application Note:** This requirement expands upon the self-test requirements defined in the NDcPP by specifying the method by which one of the self-tests is to be performed. “Stored TSF executable code” refers to the entire software image of the device and not just the code related to the VPN gateway functionality defined by this PP-Module.

### **Evaluation Activities** ▾

#### **FPT\_TST\_EXT.3**

##### **TSS**

The evaluator shall verify that the TSS describes the method used to perform self-testing on the TSF executable code, and that this method is consistent with what is described in the SER.

#### **Guidance**

There are no guidance EAs for this component.

#### **Tests**

There are no test EAs for this component.

## **5.2.7 Trusted Path/Channels (FTP)**

### **FTP\_ITC.1/VPN Inter-TSF Trusted Channel (VPN Communications)**

#### **FTP\_ITC.1.1/VPN**

The TSF shall **be capable of using IPsec to** provide a communication channel between itself and **authorized IT entities supporting VPN communications** that is logically distinct from other communication channels and provides assured identification of its end points and protection of the channel data from **disclosure and detection of modification of the channel data**.

#### FTP\_ITC.1.2/VPN

The TSF shall permit [*the authorized IT entities*] to initiate communication via the trusted channel.

#### FTP\_ITC.1.3/VPN

The TSF shall initiate communication via the trusted channel for [**selection, choose one of:** *remote VPN gateways or peers, no functions*].

**Application Note:** The FTP\_ITC.1 requirement in the Base-PP relates to other trusted channel functions. This iteration is specific to IPsec VPN communications.

### Evaluation Activities ▾

#### FTP\_ITC.1/VPN

##### TSS

*The EAs specified for FTP\_ITC.1 in the Supporting Document for the Base-PP shall be applied for IPsec VPN communications.*

##### Guidance

*The EAs specified for FTP\_ITC.1 in the Supporting Document for the Base-PP shall be applied for IPsec VPN communications.*

##### Tests

*The EAs specified for FTP\_ITC.1 in the Supporting Document for the Base-PP shall be applied for IPsec VPN communications. Additional testing for IPsec is covered in FCS\_IPSEC\_EXT.1.*

## 5.3 TOE Security Functional Requirements Rationale

The following rationale provides justification for each SFR for the TOE, showing that the SFRs are suitable to address the specified threats:

**Table 4: SFR Rationale**

Threat	Addressed by	Rationale
T.DATA_INTEGRITY	FCS_COP.1/DataEncryption (refined from <u>Base-PP</u> )	Mitigates the threat by encrypting channel data using a specified algorithm.
	FCS_IPSEC_EXT.1 (refined from <u>Base-PP</u> )	Mitigates the threat by utilizing IPsec to verify message confidentiality and integrity.
	FPF_RUL_EXT.1	Mitigates the threat by filtering traffic from outside the protected network.
	FPT_FLS.1/SelfTest	Mitigates the threat by ceasing operations of the <u>TSF</u> if a test or security failure is detected, preventing a failure in secure functionality.
	FPT_TST_EXT.3	Mitigates the threat by executing self tests in a specified, repeatable manner.

	<a href="#">FTP_ITC.1/VPN</a>	Mitigates the threat by transmitting data over a secure <a href="#">VPN</a> connection protected from unauthorized disclosure.
	<a href="#">FTA_VCM_EXT.1</a> (optional)	Mitigates the threat by assigning a private, internal IP address to <a href="#">VPN</a> clients within the protection of the <a href="#">TSE</a> .
	<a href="#">FTA_SSL.3/VPN</a> (optional)	Mitigates the threat by terminating inactive <a href="#">VPN</a> sessions.
<a href="#">T.NETWORK_ACCESS</a>	<a href="#">FCS_IPSEC_EXT.1</a> (refined from <a href="#">Base_PP</a> )	Mitigates the threat by utilizing IPsec to create <a href="#">VPN</a> connections for authorized users to access the internal network.
	<a href="#">FIA_X509_EXT.1</a> (refined from <a href="#">Functional Package for X.509, version 1.0</a> )	Mitigates the threat by preventing connection to servers or clients with malformed or invalid X.509 certificates.
	<a href="#">FIA_X509_EXT.2</a> (refined from <a href="#">Functional Package for X.509, version 1.0</a> )	Mitigates the threat by authenticating a remote entity using X.509 certificates.
	<a href="#">FIA_X509_EXT.3</a> (refined from <a href="#">Functional Package for X.509, version 1.0</a> )	Mitigates the threat by utilizing a secure certificate request method to obtain a signed certificate.
	<a href="#">FCS_CKM.1/IKE</a>	Mitigates the threat by generating secure keys utilized for <a href="#">IKE</a> peer authentication.
	<a href="#">FPF_RUL_EXT.1</a>	Mitigates the threat by filtering traffic to disallow unauthorized access.
	<a href="#">FPF_MFA_EXT.1</a> (optional)	Mitigates the threat by providing for multi-factor authentication of <a href="#">VPN</a> clients.
	<a href="#">FTA_SSL.3/VPN</a> (optional)	Mitigates the threat by terminating inactive <a href="#">VPN</a> sessions to prevent potential unauthorized use.
	<a href="#">FTA_TSE.1</a> (optional)	Mitigates the threat by preventing connection of <a href="#">VPN</a> clients that meet undesirable criteria.
	<a href="#">FTA_VCM_EXT.1</a> (optional)	Mitigates the threat by assigning a private, internal IP address to <a href="#">VPN</a> clients within the protection of the <a href="#">TSE</a> .
	<a href="#">FCS_EAP_EXT.1</a> (selection-based)	Mitigates the threat by securely authenticating <a href="#">VPN</a> clients with a remote authentication server.
	<a href="#">FIA_HOTP_EXT.1</a> (selection-based)	Mitigates the threat by providing a second factor of authentication via hash-based one-time passwords.
	<a href="#">FIA_PSK_EXT.1</a> (selection-based)	Mitigates the threat by providing a second factor of authentication via a pre-shared key.

	<a href="#">FIA_PSK_EXT.2</a> (selection-based)	Mitigates the threat by securely and randomly generating a pre-shared key.
	<a href="#">FIA_PSK_EXT.3</a> (selection-based)	Mitigates the threat by securely deriving a pre-shared key from a password.
	<a href="#">FIA_TOTP_EXT.1</a> (selection-based)	Mitigates the threat by providing a second factor of authentication via time-based one-time passwords.
T.NETWORK_DISCLOSURE	<a href="#">FPF_RUL_EXT.1</a>	Mitigates the threat by filtering traffic to disallow unauthorized traffic flows.
	<a href="#">FPT_FLS.1/SelfTest</a>	Mitigates the threat by ceasing operations of the <b>TSF</b> if a test or security failure is detected, preventing a failure in traffic filtering.
	<a href="#">FPT_TST_EXT.3</a>	Mitigates the threat by executing self tests in a specified, repeatable manner.
	<a href="#">FTA_VCM_EXT.1</a> (optional)	Mitigates the threat by assigning a private, internal IP address to <b>VPN</b> clients within the protection of the <b>TSF</b> .
T.NETWORK_MISUSE	<a href="#">FAU_GEN.1/VPN</a>	Mitigates the threat by logging potential violations of policy.
	<a href="#">FCS_IPSEC_EXT.1</a>	Mitigates the threat by securing traffic originating from or traveling to an authorized user that resides outside the protected network, ensuring that an unauthorized attacker cannot inject their own actions into the protected network.
	<a href="#">FMT_MTD.1/CryptoKeys</a>	Mitigates the threat by implementing a management interface to manage the IPsec parameters so that unprivileged users do not have the ability to misuse its functions.
	<a href="#">FMT_SMF.1/VPN</a>	Mitigates the threat by implementing a management interface that allows for authorized usage of the <b>TQE</b> so that unprivileged users do not have the ability to misuse its functions.
	<a href="#">FPF_RUL_EXT.1</a>	Mitigates the threat by filtering traffic to or from disallowed services.
	<a href="#">FPT_FLS.1/SelfTest</a>	Mitigates the threat by ceasing operations of the <b>TSF</b> if a test or security failure is detected, preventing a failure in detection or prevention of network misuse.
	<a href="#">FPT_TST_EXT.3</a>	Mitigates the threat by executing self tests in a specified, repeatable manner.
	<a href="#">FTA_VCM_EXT.1</a> (optional)	Mitigates the threat by assigning a private, internal IP address to <b>VPN</b> clients within the protection of

the TSE.

T.REPLAY_ATTACK	FCS_COP.1/DataEncryption (refined from Base-PP)	Mitigates the threat by utilizing encryption algorithms to protect data from being sent in cleartext.
	FCS_IPSEC_EXT.1 (refined from Base-PP)	Mitigates the threat by utilizing the IPsec protocol to encapsulate and encrypt channel data.
	FPT_FLS.1/SelfTest	Mitigates the threat by ceasing operations of the TSE if a test or security failure is detected, preventing a failure in detection of replay attacks.
	FPT_TST_EXT.3	Mitigates the threat by executing self tests in a specified, repeatable manner.
	FTP_ITC.1/VPN	Mitigates the threat by ensuring the channel data (in this case, VPN data) is protected from unauthorized disclosure.
	FTA_TSE.1 (optional)	Mitigates the threat by preventing connection from a VPN client that meets undesirable criteria.

# 6 Consistency Rationale

## 6.1 Collaborative Protection Profile for Network Devices

### 6.1.1 Consistency of TOE Type

When this PP-Module is used to extend the NDcPP, the TOE type for the overall TOE is still a network device. The TOE boundary is simply extended to include VPN gateway functionality that is provided by the network device.

### 6.1.2 Consistency of Security Problem Definition

The threats, assumptions, and organizational security policies (OSPs) defined by this PP-Module (see sections 3.1 through 3.3) supplement those defined in the NDcPP as follows:

**Table 5: Consistency of Security Problem Definition (NDcPP base)**

PP-Module Threat, Assumption, OSP	Consistency Rationale
T.DATA_INTEGRITY	The threat of data integrity compromise is a specific example of the T.WEAK_CRYPTOGRAPHY threat defined in the Base-PP.
T.NETWORK_ACCESS	The threat of a malicious entity accessing protected network resources without authorization is a specific example of the T.UNTRUSTED_COMMUNICATION CHANNELS threat defined in the Base-PP.
T.NETWORK_DISCLOSURE	Exposure of network devices due to insufficient protection is a specific example of the T.UNTRUSTED_COMMUNICATION CHANNELS threat defined in the Base-PP.
T.NETWORK_MISUSE	Depending on the specific nature of the misuse of network resources, this threat is a specific manifestation of either the T.UNTRUSTED_COMMUNICATION CHANNELS or T.WEAK_AUTHENTICATION_ENDPOINTS threat defined in the Base-PP.
T.REPLAY_ATTACK	A replay attack is mentioned in the Base-PP as a specific type of attack based on the T.UNTRUSTED_COMMUNICATION CHANNELS threat.
A.CONNECTIONS	This assumption defines the TOE's placement in a network such that it is able to perform its required security functionality. The Base-PP does not define any assumptions about the TOE's architectural deployment so there is no conflict here.

### 6.1.3 Consistency of OE Objectives

**Table 6: Consistency of OE Objectives (NDcPP base)**

PP-Module OE Objective	Consistency Rationale
------------------------	-----------------------

<b>OE.CONNECTIONS</b>	This objective intends for the <b>TOE</b> to be connected to environmental networks in such a way that its primary functionality can be appropriately enforced. There is no inconsistency here with respect to the <b>Base-PP</b> because the <b>Base-PP</b> does not define any restrictions on how a network device is connected to its environment.
-----------------------	--

### 6.1.4 Consistency of Requirements

This **PP-Module** identifies several **SFRs** from the NDcPP that are needed to support **VPN** Gateway functionality. This is considered to be consistent because the functionality provided by the NDcPP is being used for its intended purpose. The **PP-Module** also identifies a number of modified **SFRs** from the NDcPP that are used entirely to provide functionality for **VPN** Gateways. The rationale for why this does not conflict with the claims defined by the NDcPP are as follows:

**Table 7: Consistency of Requirements (NDcPP base)**

<b>PP-Module Requirement</b>	<b>Consistency Rationale</b>
<b>Modified SFRs</b>	
FCS_COP.1/AEAD	This <b>PP-Module</b> mandates a specific selection to be made in this <b>SFR</b> , which does not conflict with the <b>Base-PP</b> because the required selection is an option originally defined in it.
FCS_COP.1/DataEncryption	This <b>PP-Module</b> restricts the <b>Base-PP SFR</b> to a subset of existing permissible functionality and does not introduce any new behavior.
FCS_IPSEC_EXT.1	This <b>PP-Module</b> restricts the <b>Base-PP SFR</b> to a subset of existing permissible functionality and does not introduce any new behavior.
FMT_MTD.1/CryptoKeys	This <b>PP-Module</b> applies the key management functionality already defined in the <b>Base-PP</b> specifically to functionality related to <b>VPN</b> gateways.
<b>Additional SFRs</b>	
This <b>PP-Module</b> does not add any requirements when the NDcPP is the base.	
<b>Mandatory SFRs</b>	
FAU_GEN.1/VPN	This <b>SFR</b> adds new auditable events for the <b>TOE</b> that relate to the functionality that is introduced by the <b>PP-Module</b> .
FCS_CKM.1/IKE	This <b>PP-Module</b> specifies a method of key generation that is not defined in the <b>Base-PP</b> . This is used for functionality defined in the <b>Base-PP (IKE)</b> that this <b>PP-Module</b> chooses to represent in greater detail.
FMT_SMF.1/VPN	This <b>SFR</b> defines management functions that are specific to the functionality required by this <b>PP-Module</b> and were therefore not already defined in the <b>Base-PP</b> iteration of it.
FPF_RUL_EXT.1	This <b>SFR</b> defines specific behavior for the processing of network traffic, specifically which communications channel is used based on certain attributes of the traffic. The <b>Base-PP</b> does not apply any constraints on how usage of a trusted channel is controlled so this does not contradict anything presented in the <b>Base-PP</b> .

FPT_FLS.1/SelfTest	The <u>Base-PP</u> already requires the <u>TOE</u> to specify the self-tests that are performed. This <u>PP-Module</u> simply goes one step further and requires the <u>TSF</u> to behave in a certain way upon failure of those self-tests.
FPT_TST_EXT.3	This <u>PP-Module</u> adds to the self-testing requirements from the <u>Base-PP</u> by mandating that a specific self-test be performed and that it be performed in a certain manner. This does not conflict with the <u>Base-PP</u> because the method used to perform the self-test is a cryptographic function already mandated by the <u>Base-PP</u> .
FTP_ITC.1/VPN	This <u>PP-Module</u> iterates a <u>Base-PP SFR</u> to refer to an interface that is unique to the <u>PP-Module</u> . This does not affect the ability of the <u>Base-PP</u> iteration of the <u>SFR</u> to be satisfied.
<b>Optional SFRs</b>	
FPF_MFA_EXT.1	This <u>SFR</u> relates specifically to the handling of traffic that is used for the establishment of IPsec connections.
<b>Objective SFRs</b>	
This <u>PP-Module</u> does not define any Objective requirements.	
<b>Implementation-dependent SFRs</b>	
FTA_SSL.3/VPN	This <u>SFR</u> refers to a specific condition under which a trusted channel is terminated by the <u>TSF</u> . The <u>Base-PP</u> supports termination of trusted channels and does not mandate this be done in any particular method.
FTA_TSE.1	This <u>SFR</u> refers to a specific condition under which a trusted channel is terminated by the <u>TSF</u> . The <u>Base-PP</u> supports termination of trusted channels and does not mandate this be done in any particular method.
FTA_VCM_EXT.1	This <u>SFR</u> refers to network addressing, which is outside the scope of the <u>Base-PP</u> and therefore not prohibited by it.
<b>Selection-based SFRs</b>	
FCS_EAP_EXT.1	This <u>SFR</u> defines the use of EAP-TLS/TTLS; the <u>Base-PP</u> already defines requirements for TLS so potential support for EAP-TLS is consistent with functionality that the <u>Base-PP</u> already expects the <u>TOE</u> may have.
FIA_HOTP_EXT.1	This <u>SFR</u> relates to use of pre-shared keys, which is behavior that only applies to the establishment of IPsec connections.
FIA_PSK_EXT.1	This <u>SFR</u> defines the use of pre-shared keys, which is behavior that only relates to the establishment of IPsec connections.
FIA_PSK_EXT.2	This <u>SFR</u> relates to use of pre-shared keys, which is behavior that only applies to the establishment of IPsec connections.
FIA_PSK_EXT.3	This <u>SFR</u> relates to use of pre-shared keys, which is behavior that only applies to the establishment of IPsec connections.

## [FIA\\_TOTP\\_EXT.1](#)

This ~~SFR~~ relates to use of pre-shared keys, which is behavior that only applies to the establishment of IPsec connections.

# Appendix A - Optional SFRs

## A.1 Strictly Optional Requirements

---

### A.1.1 Auditable Events for Strictly Optional SFRs

**Table 8: Auditable Events for Strictly Optional Requirements**

Requirement	Auditable Events	Additional Audit Record Contents
FPF_MFA_EXT.1	No events specified	N/A

### A.1.2 Packet Filtering (FPF)

The TOE may support multifactor authentication by blocking all other traffic after connection is established until secondary authentication is validated.

#### FPF\_MFA\_EXT.1 Multifactor Authentication Filtering

##### FPF\_MFA\_EXT.1.1

The TSF shall not forward packets to the internal network until the IKE tunnel has been established, except those necessary to verify additional authentication factors of the client.

##### FPF\_MFA\_EXT.1.2

The TSF shall [selection: verify, verify via an external authentication server] additional authentication factors of the client.

**Application Note:** If "verify" is selected, FIA\_PSK\_EXT.1 must be claimed.

#### Evaluation Activities ▾

##### FPF\_MFA\_EXT.1

###### TSS

*The evaluator shall examine the TSS to verify that it describes how authentication packets are identified and how all other traffic is blocked until secondary authentication is successful.*

*If the selection “verify” is included, the evaluator shall examine the TSS and verify it describes each authentication factor supported.*

*If the selection “verify via an external authentication server” is included, the evaluator shall examine the TSS and verify it describes how the factors are forwarded to the authentication server. The evaluator shall confirm other traffic is denied until verification is received by the authentication server.*

###### Guidance

*The evaluator shall examine the operational guidance to verify that it provides instructions to the administrator on how to configure the secondary authentication factors and any additional details*

necessary for filtering all other traffic.

If the selection “verify via an external authentication server” is included, the evaluator shall examine the operational guidance to verify that it provides instructions to the administrator on how to integrate the authentication server.

#### Tests

- Test FPF\_MFA\_EXT.1:1: For each accepted authentication factor, the evaluator shall configure the TOE in accordance with the operational guidance. The evaluator shall attempt to connect and verify other traffic is rejected per the filtering rules. The evaluator shall then provide the authentication factor and confirm it is accepted and that traffic is no longer blocked.

## A.2 Objective Requirements

This PP-Module does not define any Objective SFRs.

## A.3 Implementation-dependent Requirements

### A.3.1 Auditable Events for Implementation-Based SFRs

**Table 9: Auditable Events for Implementation-dependent Requirements**

Requirement	Auditable Events	Additional Audit Record Contents
FTA_SSL.3/VPN	No events specified	N/A
FTA_TSE.1	No events specified	N/A
FTA_VCM_EXT.1	No events specified	N/A

### A.3.2 TOE Access (FTA)

This section contains requirements that may be optionally selected by the ST author for a “headend” VPN gateway device. The requirements in the main body of this PP-Module are those determined necessary for a multi-site VPN gateway appliance. Another application of a VPN appliance is in an architecture that is intended to serve mobile users, by providing a secure means in which a remote client may access a trusted network. These devices provide the capability to manage remote VPN clients (e.g., assigning IP addresses, managing client sessions) that are not necessarily found in VPN gateways that are limited to providing a secure communication path between trusted networks. Rather than mandate that all VPN gateways provide this mobility aspect, the requirements below are specified as an option. What this means is that multi-site VPN gateways do not have to provide these capabilities, but those devices wishing to serve the mobility community should implement the optional requirements from this Appendix in addition to all mandatory and selection-based requirements that apply to them. This section contains requirements that may be optionally selected by the ST author for a “headend” VPN gateway device. The requirements in the main body of this PP-Module are those determined necessary for a multi-site VPN gateway appliance. Another application of a VPN appliance is in an architecture that is intended to serve mobile users, by providing a secure means in which a remote client may access a trusted network. These devices provide the capability to manage remote VPN clients (e.g., assigning IP addresses, managing client sessions) that are not necessarily found in VPN gateways that are limited to providing a secure communication path between trusted

networks. Rather than mandate that all **VPN** gateways provide this mobility aspect, the requirements below are specified as an option. What this means is that multi-site **VPN** gateways do not have to provide these capabilities, but those devices wishing to serve the mobility community should implement the optional requirements from this Appendix in addition to all mandatory and selection-based requirements that apply to them.

### **FTA\_SSL.3/VPN TSF-Initiated Termination (VPN Headend)**

#### **FTA\_SSL.3.1/VPN**

The **TSF** shall terminate **a remote VPN client** session after [*an Administrator-configurable time interval of session inactivity*].

**Application Note:** This requirement exists in the NDcPP; however, it is intended to address an interactive administrative session. Here, the requirement applies to a **VPN** client that has established an **SA**. After some configurable time period without any activity, the connection between the **VPN** headend and client is terminated.

### **Evaluation Activities** ▾

#### **FTA\_SSL.3/VPN**

##### **TSS**

*The evaluator shall examine the **TSS** to verify that it describes the ability of the **TSF** to terminate an inactive **VPN** client session.*

##### **Guidance**

*The evaluator shall examine the operational guidance to verify that it provides instructions to the administrator on how to configure the time limit for termination of an active **VPN** client session.*

##### **Tests**

*The evaluator shall perform the following tests:*

- *Test FTA\_SSL.3/VPN:1: The evaluator shall follow the steps provided in the operational guidance to set the inactivity timer for five minutes. The evaluator shall then connect a **VPN** client to the **TOE**, let it sit idle for four minutes and fifty seconds, and observe that the **VPN** client is still connected at this time by performing an action that would require **VPN** access. The evaluator shall then disconnect the client, reconnect it, wait five minutes and ten seconds, attempt the same action, and observe that it does not succeed. The evaluator shall then verify using audit log data that the **VPN** client session lasted for exactly five minutes.*
- *Test FTA\_SSL.3/VPN:2: The evaluator shall configure the inactivity timer to ten minutes and repeat Test 1, adjusting the waiting periods and expected audit log data accordingly.*

### **FTA\_TSE.1 TOE Session Establishment**

#### **FTA\_TSE.1.1**

The **TSF** shall be able to deny session establishment **of a remote VPN client session** based on [*location, time, day, [selection: no other attributes, [assignment: other attributes]]*].

**Application Note:** For this **PP-Module**, “location” is defined as the client’s IP address.

### **Evaluation Activities** ▾

## [FTA\\_TSE.1](#)

### **TSS**

The evaluator shall examine the **TSS** to verify that it describes the methods by which the **TSF** can deny the establishment of an otherwise valid remote **VPN** client session (e.g., client credential is valid, not expired, not revoked, etc.), including day, time, and IP address at a minimum.

### **Guidance**

The evaluator shall review the operational guidance to determine that it provides instructions for how to enable an access restriction that will deny **VPN** client session establishment for each attribute described in the **TSS**.

### **Tests**

The evaluator shall perform the following tests:

- **Test FTA\_TSE.1:1:** The evaluator shall successfully connect a remote **VPN** client to the **TOE** and then disconnect it, noting the IP address from which the client connected. The evaluator shall follow the steps described in the operational guidance to prohibit that IP address from connecting, attempt to reconnect using the same **VPN** client, and observe that it is not successful.
- **Test FTA\_TSE.1:2:** The evaluator shall successfully connect a remote **VPN** client to the **TOE** and then disconnect it. The evaluator shall follow the steps described in the operational guidance to prohibit the **VPN** client from connecting on a certain day (whether this is a day of the week or specific calendar date), attempt to reconnect using the same **VPN** client, and observe that it is not successful.
- **Test FTA\_TSE.1:3:** The evaluator shall successfully connect a remote **VPN** client to the **TOE** and then disconnect it. The evaluator shall follow the steps described in the operational guidance to prohibit the **VPN** client during a range of times that includes the time period during which the test occurs, attempt to reconnect using the same **VPN** client, and observe that it is not successful.
- **Test FTA\_TSE.1:4:** (conditional, the "other attributes" assignment has been selected and completed with one or more additional attributes) For any other attributes that are identified in [FTA\\_TSE.1](#), the evaluator shall conduct a test similar to the previous three tests to demonstrate the enforcement of each of these attributes. The evaluator shall demonstrate a successful remote client **VPN** connection, configure the **TSF** to deny that connection based on the attribute, and demonstrate that a subsequent connection attempt is unsuccessful.

## **FTA\_VCM\_EXT.1 VPN Client Management**

### **FTA\_VCM\_EXT.1.1**

The **TSF** shall assign a private IP address to a **VPN** client upon successful establishment of a security session.

**Application Note:** For this requirement, the private IP address is one that is internal to the trusted network for which the **TOE** is the headend.

### **Evaluation Activities**

#### [FTA\\_VCM\\_EXT.1](#)

##### **TSS**

*The evaluator shall check the TSS to verify that it asserts the ability of the TSE to assign a private IP address to a connected VPN client.*

**Guidance**

*There are no guidance EAs for this component.*

**Tests**

*The evaluator shall connect a remote VPN client to the TOE and record its IP address as well as the internal IP address of the TOE. The evaluator shall verify that the two IP addresses belong to the same network. The evaluator shall disconnect the remote VPN client and verify that the IP address of its underlying platform is no longer part of the private network identified in the previous step.*

# Appendix B - Selection-based Requirements

## B.1 Auditable Events for Selection-based SFRs

Table 10: Auditable Events for Selection-based Requirements

Requirement	Auditable Events	Additional Audit Record Contents
FCS_EAP_EXT.1	No events specified	N/A
FIA_HOTP_EXT.1	No events specified	N/A
FIA_PSK_EXT.1	No events specified	N/A
FIA_PSK_EXT.2	No events specified	N/A
FIA_PSK_EXT.3	No events specified	N/A
FIA_TOTP_EXT.1	No events specified	N/A

## B.2 Cryptographic Support (FCS)

### FCS\_EAP\_EXT.1 EAP-TLS/TTLS

*The inclusion of this selection-based component depends upon selection in FCS\_IPSEC\_EXT.1.*

#### FCS\_EAP\_EXT.1.1

The TSF shall support [**selection: EAP-TLS as specified in RFC 5216 and updated by RFC 8996, EAP-TTLS as specified in RFC 5281 and updated by RFC 8996**] over a protected channel per FTP\_ITC.1 **from the Base-PP** with an authentication server.

#### FCS\_EAP\_EXT.1.2

The TSF shall implement EAP-TLS or EAP-TTLS with the TSF as the EAP client, an authentication server as the EAP server, and the VPN peer as the supplicant.

#### FCS\_EAP\_EXT.1.3

The TSF shall use the MSK from the [**selection: EAP-TLS, EAP-TTLS**] response as the IKEv2 shared secret in the authentication payload.

**Application Note:** This SFR covers the EAP requirements for a client connection to an authentication server. In particular, authentication server functionality implemented in the same device, rather than in an external device, is covered under the Authentication Server PP-Module, and is out of scope for this PP-Module. The MSK derived from EAP is distinct from the PSK. The MSK is substituted in for the IKEv2 shared secret in the AUTH computations.

## Evaluation Activities ▾

### [FCS\\_EAP\\_EXT.1](#)

#### **TSS**

The evaluator shall verify that the TSS describes the use of EAP options for each of the selected peer authentication mechanisms, and that the TSF supports EAP messaging for mutually authenticated TLS between the peer and the authentication server.

#### **Guidance**

The evaluator shall verify that the guidance documents describe any configurable features of the EAP or TLS functionality, including instructions for configuration of the authenticators and registration processes for clients.

#### **Tests**

Testing for TLS functionality is in accordance with the TLS package. For each supported EAP method claimed in [FCS\\_EAP\\_EXT.1.1](#) and for each authentication method claimed in [FCS\\_EAP\\_EXT.1.3](#), the evaluator shall perform the following tests:

- Test FCS\_EAP\_EXT.1:1: The evaluator shall follow the operational guidance to configure the TSF to use the EAP method claimed. The evaluator shall follow the operational guidance to configure the TSF to use the authentication method claimed and, for EAP-TTLS, establish a trusted channel with an authentication server that requests the method, and register the peer as a TLS client with appropriate key material required for the authentication method.

The evaluator shall establish a VPN session using a test peer with a valid certificate and, for EAP-TTLS, configured to provide a correct value for the configured authenticator. The evaluator shall observe that the TSF sends EAP messages to the peer and authentication server to transfer the TLS handshake messages, and after the TSF receives the EAP-success message, that the VPN session between the peer and TSF is successfully established.

- Test FCS\_EAP\_EXT.1:2: The evaluator shall follow the operational guidance to configure the TSF to use a supported EAP method, establish a trusted channel with an authentication server that requests the method and register the peer as a TLS client with key material required for a supported authentication method. The evaluator shall cause the test client to respond to an IKEv2 exchange with EAP-request, but to compute the shared secret after a successful EAP exchange using the non-EAP method. The evaluator shall initiate a VPN session between the test client and the TSF and observe that the TSF aborts the session.

## B.3 Identification and Authentication (FIA)

The TOE may support pre-shared keys for use in the IPsec protocol, and may use pre-shared keys in other protocols as well. PSK in the context of this document refers to generated values, memorized values subject to conditioning, one-time passwords, and combinations as described in [FIA\\_PSK\\_EXT.1.2](#).

### **FIA\_HOTP\_EXT.1 HMAC-Based One-Time Password Pre-Shared Keys**

***The inclusion of this selection-based component depends upon selection in [FIA\\_PSK\\_EXT.1.2](#).***

The TSF shall support HMAC-Based One-Time Password (HOTP) authentication in accordance with RFC 4226 to authenticate the user before establishing VPN connection.

#### FIA\_HOTP\_EXT.1.2

The TSF shall generate an HOTP seed according to FCS\_RB.G.1 (from [NDcPP]) of [**selection**: 128, 256] bits.

#### FIA\_HOTP\_EXT.1.3

The TSF shall generate a new HOTP seed value for each client.

#### FIA\_HOTP\_EXT.1.4

The TSF shall use [**selection**: SHA-1, SHA-256, SHA-384, SHA-512] with key sizes [**assignment**: *key size (in bits) used in HMAC*] and message digest sizes [**selection**: 160, 256, 384, 512] to derive an HOTP hash from the HOTP seed and counter.

#### FIA\_HOTP\_EXT.1.5

The TSF shall truncate the HOTP hash per [FIA\\_HOTP\\_EXT.1.4](#) to create an HOTP of [**selection**:

- *administrator configurable character length of at least 6*
- *preset character length of [selection, choose one of: 6, 7, 8, 9, 10]*

].

#### FIA\_HOTP\_EXT.1.6

The TSF shall [**selection**:

- *throttle invalid requests to [selection: administrator configurable value, [assignment: value less than 10]] per minute*
- *lock the associated account after [selection: administrator configurable value, [assignment: value less than 10]] failed attempts until [selection: an administrator unlocks the account, a configurable time period]*

].

#### FIA\_HOTP\_EXT.1.7

The TSF shall not verify HOTP attempts outside of the counter look ahead window of [**selection**: *a configurable value, [assignment: a value less than or equal to 3]*] for resynchronization.

#### FIA\_HOTP\_EXT.1.8

The TSF shall increment the counter after each successful authentication.

**Application Note:** The selection [FIA\\_HOTP\\_EXT.1.4](#) must be consistent with the key size specified for the size of the keys used in conjunction with the keyed-hash message authentication.

In [FIA\\_HOTP\\_EXT.1.5](#) the ST author may either provide a configurable character length of at least 6 or a preset size between 6 and 10.

In [FIA\\_HOTP\\_EXT.1.6](#) the ST author may select throttle requests, account lockout, or both.

The HOTP seed and all derived values are considered secret keys for purposes of protection.

## Evaluation Activities

[FIA\\_HOTP\\_EXT.1](#)

## **TSS**

The evaluator shall verify the TSS describes how the HOTP is input into the client and how that value is sent to the server.

The evaluator shall confirm the TSS describes how the TOE complies with the RFC.

The evaluator shall confirm the TSS describes how the HOTP seed is generated and ensure it aligns with FCS\_RBG.1 (from [NDcPP](#)).

The evaluator shall confirm the TSS describes how the HOTP seed is protected and ensure it aligns with the storage requirements of the Base-PP.

The evaluator shall confirm the TSS describes how a new HOTP seed is assigned for each client and how each client is uniquely identified.

The evaluator shall confirm the TSS describes how the HOTP seed is conditioned into an HOTP hash and verify it matches the selection in [FIA\\_HOTP\\_EXT.1.4](#).

The evaluator shall confirm the TSS describes how the HOTP hash is truncated and verify it matches the selection in [FIA\\_HOTP\\_EXT.1.5](#).

The evaluator shall confirm the TSS describes how the TOE handles multiple incoming invalid requests and verify it provides an anti-hammer mechanism that matches the selections made in [FIA\\_HOTP\\_EXT.1.6](#).

The evaluator shall confirm the TSS describes how the TOE handles resynchronization and how it rejects attempts outside of the look-ahead window selected in [FIA\\_TOTP\\_EXT.1.7](#).

The evaluator shall confirm the TSS describes how the TOE counter is incremented after each successful authentication.

## **Guidance**

The evaluator shall verify the operational guidance contains any configuration necessary to enable HOTP.

The evaluator shall verify the operational guidance contains all configuration guidance for setting any administrative value that is configurable in the [FIA\\_HOTP\\_EXT.1](#) requirements.

## **Tests**

The evaluator shall configure the TOE to use a supported HOTP factor then:

- Test FIA\_HOTP\_EXT.1:1: Attempt to establish a connection using that factor. The evaluator shall verify the client prompts the user for the HOTP before initiating the connection. The evaluator shall verify the server validates the HOTP or receives confirmation from an authentication server before establishing the channel.
- Test FIA\_HOTP\_EXT.1:2: Attempt to establish a connection using a factor from a different client. The test passes if the client fails to connect.
- Test FIA\_HOTP\_EXT.1:3: Attempt multiple connections outside the limits set in [FIA\\_HOTP\\_EXT.1.6](#) and verify the remediation is triggered. The test passes if remediation is triggered as defined in the selections and assignments.
- Test FIA\_HOTP\_EXT.1:4: Attempt to use an HOTP that is outside of the value allowed for resynchronization. The test passes if the client fails to connect.
- Test FIA\_HOTP\_EXT.1:5: Attempt to connect with a valid HOTP, disconnect and attempt to authenticate again with the same HOTP value. The test passes if the client connects the first time and fails to connect the second time. If the HOTP generated is duplicated the test may be repeated.

## **FIA\_PSK\_EXT.1 Pre-Shared Key Composition**

***The inclusion of this selection-based component depends upon selection in [FPF\\_MFA\\_EXT.1.2](#).***

## FIA\_PSK\_EXT.1.1

The TSS shall be able to use pre-shared keys for IPsec and [selection: *IKEv2, multifactor authentication filtering*].

**Application Note:** If “IKEv2” is selected, then the corresponding IKEv2 selection must be made in FCS\_IPSEC\_EXT.1.13. If “multifactor authentication filtering” is selected, then “verify” should be selected in [FPF\\_MFA\\_EXT.1.2](#).

## FIA\_PSK\_EXT.1.2

The TSS shall be able to accept the following as pre-shared keys: [selection: *generated bit-based, password-based, HMAC-based one-time password, time-based one-time password, combination of a generated bit-based and HMAC-based one-time password, combination of a generated bit-based and time-based one-time password, combination of a password-based and HMAC-based one-time password, Combination of a password-based and time-based one-time password*] keys.

**Application Note:** This requirement is included if “pre-shared keys that conform to RFC 8784” is selected in FCS\_IPSEC\_EXT.1.13, or if “verify” is selected in [FPF\\_MFA\\_EXT.1.2](#). If these selections are made in both FCS\_IPSEC\_EXT.1.13 and [FPF\\_MFA\\_EXT.1.2](#), the TSS must satisfy the appropriate [FIA\\_PSK\\_EXT.1](#) selections for each.

If any selection including "generated bit-based" is chosen, then [FIA\\_PSK\\_EXT.2](#) must be included.

If “pre-shared keys that conform to RFC 8784” is selected in FCS\_IPSEC\_EXT.1.13, a generated, bit-based PSK must be used.

If any selection including Password-based keys is chosen, then [FIA\\_PSK\\_EXT.3](#) must be included.

If any selection including HMAC-based one-time password keys is chosen, then [FIA\\_HOTP\\_EXT.1](#) must be included.

If any selection including time-based one-time password is chosen, then [FIA\\_TOTP\\_EXT.1](#) must be included.

## Evaluation Activities ▾

### [FIA\\_PSK\\_EXT.1](#)

#### TSS

*The evaluator shall confirm that the TSS states which pre-shared key selections are supported for IKEv2 per FCS\_IPSEC\_EXT.1.13 and [FPF\\_MFA\\_EXT.1.1](#).*

#### **Guidance**

*The evaluator shall examine the operational guidance to determine that it provides guidance to administrators on how to configure all selected pre-shared key options if any configuration is required. The evaluator shall examine the operational guidance to determine that it provides guidance to administrators on how to configure the mandatory\_or\_not flag per RFC 8784.*

#### **Tests**

*The evaluator shall also perform the following tests for each protocol (or instantiation of a protocol, if performed by a different implementation on the TOE).*

- Test FIA\_PSK\_EXT.1:1: For each mechanism selected in [FIA\\_PSK\\_EXT.1.2](#) the evaluator shall attempt to establish a connection and confirm that the connection requires the selected factors in the PSK to establish the connection in alignment with table 1 from RFC 8784.

## FIA\_PSK\_EXT.2 Generated Pre-Shared Keys

*The inclusion of this selection-based component depends upon selection in [FIA\\_PSK\\_EXT.1.2](#).*

### FIA\_PSK\_EXT.2.1

The TSF shall be able to [selection]:

- accept externally generated pre-shared keys
- generate [selection: 128, 256] bit-based pre-shared keys via FCS\_RB.G.1 (from [\[NDcPP\]](#)).

]

**Application Note:** Generated PSKs are expected to be shared between components via an out of band mechanism.

This requirement is selection dependent on [FIA\\_PSK\\_EXT.1](#).

### Evaluation Activities ▾

#### [FIA\\_PSK\\_EXT.2](#)

##### [TSS](#)

If "generate" is selected, the evaluator shall confirm that this process uses the RBG specified in FCS\_RB.G.1 (from [\[NDcPP\]](#)) and the output matches the size selected in [FIA\\_PSK\\_EXT.2.1](#).

##### [Guidance](#)

The evaluator shall confirm the operational guidance contains instructions for entering generated pre-shared keys for each protocol identified in the [FIA\\_PSK\\_EXT.1.1](#).

##### [Tests](#)

- Test FIA\_PSK\_EXT.2:1: [conditional] If generate was selected the evaluator shall generate a pre-shared key and confirm the output matches the size selected in [FIA\\_PSK\\_EXT.2.1](#).

## FIA\_PSK\_EXT.3 Password-Based Pre-Shared Keys

*The inclusion of this selection-based component depends upon selection in [FIA\\_PSK\\_EXT.1.2](#).*

### FIA\_PSK\_EXT.3.1

The TSF shall support a PSK of up to [assignment: positive integer of 64 or more] characters.

### FIA\_PSK\_EXT.3.2

The TSE shall allow PSKs to be composed of any combination of upper case characters, lower case characters, numbers, and the following special characters: "!", "@", "#", "\$", "%", "^", "&", "\*", "(", and ")"., and [selection: *[assignment: other supported special characters], no other characters*]

#### FIA\_PSK\_EXT.3.3

The TSE shall perform Password-based Key Derivation Functions in accordance with a specified cryptographic algorithm HMAC-[SHA-384, with *[assignment: positive integer of 4096 or more]*] iterations, and output cryptographic key sizes [256] that meet the following: [NIST SP 800-132].

#### FIA\_PSK\_EXT.3.4

The TSE shall not accept PSKs less than [selection: *a value settable by the administrator, [assignment: minimum PSK length accepted by the TOE, must be >= 6]*] and greater than the maximum PSK length defined in [FIA\\_PSK\\_EXT.3.1](#).

#### FIA\_PSK\_EXT.3.5

The TSE shall generate all salts using an RBG that meets FCS\_RBG.1 (**from [NDcPP]**) and with entropy of [assignment: *value equal to or greater than 128*] bits.

#### FIA\_PSK\_EXT.3.6

The TSE shall require the PSK to be entered before every initiated connection.

#### FIA\_PSK\_EXT.3.7

The TSE shall [selection: *provide a password strength meter, check the password against a denylist, perform no action to assist the user in choosing a strong password*].

**Application Note:** For [FIA\\_PSK\\_EXT.3.1](#), the ST author assigns the maximum size of the PSK it supports; it must support at least 64 characters or a length defined by the platform.

For [FIA\\_PSK\\_EXT.3.2](#), the ST author assigns any other supported characters; if there are no other supported characters, they should select "no other characters."

For [FIA\\_PSK\\_EXT.3.3](#), the ST author selects the parameters based on the PBKDF used by the TSE.

For [FIA\\_PSK\\_EXT.3.4](#) If the minimum length is settable, then the ST author chooses "a value settable by the administrator." If the minimum length is not settable, the ST author fills in the assignment with the minimum length the PSK must be. This requirement is to ensure bounds work properly.

For [FIA\\_PSK\\_EXT.3.7](#), the ST author may select one, both, or neither of the functions in alignment with NIST SP 800-63b.

This requirement is selection dependent on [FIA\\_PSK\\_EXT.1](#).

### Evaluation Activities ▾

#### [FIA\\_PSK\\_EXT.3](#)

##### TSS

*The evaluator shall examine the TSS to ensure it describes the process by which the password-based pre-shared keys are used.*

*Support for length: The evaluator shall check to ensure that the TSS describes the allowable ranges for PSK lengths, and that at least 64 characters or a length defined by the platform may be specified by the user.*

*Support for character set: The evaluator shall check to ensure that the TSS describes the allowable character set and that it contains the characters listed in the SFR.*

*Support for PBKDF: The evaluator shall examine the TSS to ensure that the use of PBKDF2 is described and that the key sizes match that described by the ST author. The evaluator shall check that the TSS describes the method by which the PSK is first encoded and then fed to the hash algorithm. The settings for the algorithm (padding, blocking, etc.) shall be described, and the evaluator shall verify that these are supported by the selections in this component as well as the selections concerning the hash function itself.*

*For the NIST SP 800-132-based conditioning of the PSK, the required evaluation activities will be performed when doing the evaluation activities for the appropriate requirements (FCS\_COP.1/KeyedHash).*

*The evaluator shall confirm that the minimum length is described.*

*The ST author shall provide a description in the TSS regarding the salt generation. The evaluator shall confirm that the salt is generated using an RBG described in FCS\_RBG.1 (from [NDcPP]). [conditional] If password strength meter or password denylist is selected, the evaluator shall examine the TSS to ensure any password checking functionality provided by the TSF is described and contains details on how the function operates.*

### **Guidance**

*The evaluator shall confirm the operational guidance contains instructions for entering password-based pre-shared keys for each protocol identified in the requirement. The evaluator shall confirm that any management functions related to pre-shared keys that are performed by the TOE are specified in the operational guidance.*

*The guidance must specify the allowable characters for pre-shared keys, and that list must include, at minimum, the same items contained in FIA\_PSK\_EXT.3.2.*

*The evaluator shall confirm the operational guidance contains any necessary instructions for enabling and configuring password checking functionality.*

### **Tests**

*Support for Password/Passphrase characteristics: In addition to the analysis above, the evaluator shall also perform the following tests on a TOE configured according to the Operational Guidance:*

- Test FIA\_PSK\_EXT.3:1: *The evaluator shall compose a pre-shared key of at least 64 characters that contains a combination of the allowed characters in accordance with the FIA\_PSK\_EXT.3.2 and verify that a successful protocol negotiation can be performed with the key.*
- Test FIA\_PSK\_EXT.3:2: [conditional]: *If the TOE supports pre-shared keys of multiple lengths, the evaluator shall repeat Test 1 using the minimum length and invalid lengths that are below the minimum length, above the maximum length, null length, empty length, or zero length. The minimum test should be successful, and the invalid lengths must be rejected by the TOE.*
- Test FIA\_PSK\_EXT.3:3: [conditional]: *If the TOE initiates connections, initiate and establish a remote connection, disconnect from the connection, verify that the PSK is required when initiating the connection a second time.*
- Test FIA\_PSK\_EXT.3:4: [conditional]: *If the TOE supports a password meter, the evaluator shall enter a password and verify the password checker responds per the description in the TSS.*
- Test FIA\_PSK\_EXT.3:5: [conditional]: *If the TOE supports a password denylist, the evaluator shall enter a denylisted password and verify that the password is rejected or flagged as such.*

## **FIA\_TOTP\_EXT.1 Time-Based One-Time Password Pre-Shared Keys**

***The inclusion of this selection-based component depends upon selection in FIA\_PSK\_EXT.1.2.***

## FIA\_TOTP\_EXT.1.1

The TSF shall support Time-Based One-Time Password (TOTP) authentication in accordance with RFC 6238 to authenticate the user before establishing VPN connection.

## FIA\_TOTP\_EXT.1.2

The TSF shall generate a TOTP seed according to FCS\_RBG.1 (from [NDcPP]) of [selection: 128, 256] bits.

## FIA\_TOTP\_EXT.1.3

The TSF shall generate a new TOTP seed for each client.

## FIA\_TOTP\_EXT.1.4

The TSF shall use [selection: SHA-1, SHA-256, SHA-384, SHA-512] with key sizes [assignment: key size (in bits) used in HMAC] and message digest sizes [selection: 160, 256, 384, 512] to derive a TOTP hash from the TOTP seed and current time provided by NTP.

## FIA\_TOTP\_EXT.1.5

The TSF shall truncate the TOTP hash per FIA\_TOTP\_EXT.1.4 to create a TOTP of [selection:

- administrator configurable character length of at least 6
- preset character length of [selection, choose one of: 6, 7, 8, 9, 10]

].

## FIA\_TOTP\_EXT.1.6

The TSF shall [selection:

- throttle invalid requests to [selection: administrator configurable value, [assignment: value less than 10]] per minute
- lock the associated account after [selection: administrator configurable value, [assignment: value less than 10]] failed attempts until [selection: an administrator unlocks the account, a configurable time period]

].

## FIA\_TOTP\_EXT.1.7

The TSF shall set a time-step size of [selection: a configurable value, [assignment: a value less than or equal to 30]] seconds.

## FIA\_TOTP\_EXT.1.8

The TSF shall not validate a drift of more than [selection: a configurable value, [assignment: a value less than or equal to 3]] time-steps.

## FIA\_TOTP\_EXT.1.9

The TSF shall [selection: allow resynchronization by recording time drift within the limit of FIA\_TOTP\_EXT.1.8, not permit resynchronization].

**Application Note:** The selection FIA\_TOTP\_EXT.1.4 must be consistent with the key size specified for the size of the keys used in conjunction with the keyed-hash message authentication.

In FIA\_TOTP\_EXT.1.5 the ST author may either provide a configurable character length of at least 6 or a preset size between 6 and 10.

In FIA\_TOTP\_EXT.1.6 the ST author may select throttle requests, account lockout, or both.

The TOTP seed and all derived values are considered secret keys for purposes of protection.

## Evaluation Activities ▾

### [FIA\\_TOTP\\_EXT.1](#)

#### TSS

The evaluator shall verify the TSS describes how the TOTP is input into the client and how that value is sent to the server.

The evaluator shall confirm the TSS describes how the TOE complies with the RFC.

The evaluator shall confirm the TSS describes how the TOTP seed is generated and ensure it aligns with FCS\_RBG.1 (from [\[NDcPP\]](#)).

The evaluator shall confirm the TSS describes how the TOTP seed is protected and ensure it aligns with the storage requirements of the Base-PP.

The evaluator shall confirm the TSS describes how a new TOTP seed is assigned for each client and how each client is uniquely identified.

The evaluator shall confirm the TSS describes how the TOTP seed is conditioned into a TOTP hash and verify it matches the selection in [FIA\\_TOTP\\_EXT.1.4](#).

The evaluator shall confirm the TSS describes how the TOTP hash is truncated and verify it matches the selection in [FIA\\_TOTP\\_EXT.1.5](#).

The evaluator shall confirm the TSS describes how the TOE handles multiple incoming requests and verify it provides an anti-hammer mechanism that matches the selections made in

[FIA\\_TOTP\\_EXT.1.6](#).

The evaluator shall confirm the TSS describes how the TOE sets a time-step value and verify it matches the selections in the ST.

The evaluator shall confirm the TSS describes how the TOE handles drift and resynchronization and verify it matches the selections. The evaluator shall ensure the TSS describes how time is kept and whether drift is calculated and recorded. If drift is recorded, the evaluator shall ensure that the TSS describes how this is done.

#### **Guidance**

The evaluator shall verify the operational guidance contains any configuration necessary to enable TOTP.

The evaluator shall verify the operational guidance contains all configuration guidance for setting any administrative value that is configurable in the [FIA\\_TOTP\\_EXT.1](#) requirements.

#### **Tests**

The evaluator shall configure the TOE to use a supported TOTP factor then:

- Test [FIA\\_TOTP\\_EXT.1:1](#): Attempt to establish a connection using that factor. The evaluator shall verify the client prompts the user for the TOTP before initiating the connection. The evaluator shall verify the server validates the TOTP or receives confirmation from an authentication server before establishing the channel.
- Test [FIA\\_TOTP\\_EXT.1:2](#): Attempt to establish a connection using a factor from a different client. The test passes if the client fails to connect.
- Test [FIA\\_TOTP\\_EXT.1:3](#): Attempt multiple connections outside the limits set in [FIA\\_TOTP\\_EXT.1.6](#) and verify the remediation is triggered. The test passes if remediation is triggered as defined in the selections and assignments.
- Test [FIA\\_TOTP\\_EXT.1:4](#): Attempt to use a TOTP that is outside of the value allowed for resynchronization. The test passes if the client fails to connect.

Attempt to connect with a valid TOTP, disconnect and attempt to authenticate again with the same TOTP. The test passes if the client connects the first time and fails to connect the second time. If the TOTP generated is duplicated the test may be repeated.

# Appendix C - Extended Component Definitions

This appendix contains the definitions for all extended requirements specified in the [PP-Module](#).

## C.1 Extended Components Table

---

All extended components specified in the [PP-Module](#) are listed in this table:

**Table 11: Extended Component Definitions**

Functional Class	Functional Components
Cryptographic Support (FCS)	FCS_EAP_EXT EAP-TLS/TTLS
Identification and Authentication (FIA)	FIA_HOTP_EXT HMAC-Based One-Time Password Pre-Shared Keys FIA_PSK_EXT Pre-Shared Key Composition FIA_TOTP_EXT Time-Based One-Time Password Pre-Shared Keys
Packet Filtering (FPF)	FPF_MFA_EXT Multifactor Authentication Filtering FPF_RUL_EXT Packet Filtering Rules
Protection of the TSF (FPT)	FPT_TST_EXT TSF Self-Test
TOE Access (FTA)	FTA_VCM_EXT VPN Client Management

## C.2 Extended Component Definitions

---

### C.2.1 Cryptographic Support (FCS)

This [PP-Module](#) defines the following extended components as part of the FCS class originally defined by [CC Part 2](#):

#### C.2.1.1 FCS\_EAP\_EXT EAP-TLS/TTLS

##### Family Behavior

Components in this family describe the requirements for EAP-TLS/TTLS.

##### Component Leveling



[FCS\\_EAP\\_EXT.1](#), EAP-TLS/TTLS, defines the use of EAP-TLS/TTLS.

##### Management: FCS\_EAP\_EXT.1

No specific management functions are identified.

## **Audit: FCS\_EAP\_EXT.1**

There are no auditable events foreseen.

### **FCS\_EAP\_EXT.1 EAP-TLS/TTLS**

Hierarchical to: No other components.

Dependencies to: FCS\_IPSEC\_EXT.1 IPsec Protocol

#### **FCS\_EAP\_EXT.1.1**

The TSF shall support [**selection: EAP-TLS as specified in RFC 5216 and updated by RFC 8996, EAP-TTLS as specified in RFC 5281 and updated by RFC 8996**] over a protected channel per FTP\_ITC.1 with an authentication server.

#### **FCS\_EAP\_EXT.1.2**

The TSF shall implement EAP-TLS or EAP-TTLS with the TSF as the EAP client, an authentication server as the EAP server, and the VPN peer as the supplicant.

#### **FCS\_EAP\_EXT.1.3**

The TSF shall use the MSK from the [**selection: EAP-TLS, EAP-TTLS**] response as the IKEv2 shared secret in the authentication payload.

## **C.2.2 Identification and Authentication (FIA)**

This PP-Module defines the following extended components as part of the FIA class originally defined by CC Part 2:

### **C.2.2.1 FIA\_HOTP\_EXT HMAC-Based One-Time Password Pre-Shared Keys**

#### **Family Behavior**

Components in this family define requirements for the use of HMAC-Based One-Time password authentication, including generation methods and usage restrictions.

#### **Component Leveling**



[FIA\\_HOTP\\_EXT.1](#), HMAC-Based One-Time Password Pre-Shared Keys, defines the implementation of HOTP.

#### **Management: FIA\_HOTP\_EXT.1**

No specific management functions are identified.

#### **Audit: FIA\_HOTP\_EXT.1**

There are no auditable events foreseen.

### **FIA\_HOTP\_EXT.1 HMAC-Based One-Time Password Pre-Shared Keys**

Hierarchical to: No other components.

Dependencies to: FCS\_COP.1 Cryptographic Operation

### **FIA\_HOTP\_EXT.1.1**

The TSF shall support HMAC-Based One-Time Password (HOTP) authentication in accordance with RFC 4226 to authenticate the user before establishing VPN connection.

### **FIA\_HOTP\_EXT.1.2**

The TSF shall generate an HOTP seed according to FCS\_RBG.1 of [**selection**: 128, 256] bits.

### **FIA\_HOTP\_EXT.1.3**

The TSF shall generate a new HOTP seed value for each client.

### **FIA\_HOTP\_EXT.1.4**

The TSF shall use [**selection**: SHA-1, SHA-256, SHA-384, SHA-512] with key sizes [**assignment**: *key size (in bits) used in HMAC*] and message digest sizes [**selection**: 160, 256, 384, 512] to derive an HOTP hash from the HOTP seed and counter.

### **FIA\_HOTP\_EXT.1.5**

The TSF shall truncate the HOTP hash per [FIA\\_HOTP\\_EXT.1.4](#) to create an HOTP of [**selection**:

- *administrator configurable character length of at least 6*
- *preset character length of [selection, choose one of: 6, 7, 8, 9, 10]*

].

### **FIA\_HOTP\_EXT.1.6**

The TSF shall [**selection**:

- *throttle invalid requests to [selection: administrator configurable value, [assignment: value less than 10]] per minute*
- *lock the associated account after [selection: administrator configurable value, [assignment: value less than 10]] failed attempts until [selection: an administrator unlocks the account, a configurable time period]*

].

### **FIA\_HOTP\_EXT.1.7**

The TSF shall not verify HOTP attempts outside of the counter look ahead window of [**selection**: *a configurable value*, **assignment**: *a value less than or equal to 3*] for resynchronization.

### **FIA\_HOTP\_EXT.1.8**


The TSF shall increment the counter after each successful authentication.

## **C.2.2.2 FIA\_PSK\_EXT Pre-Shared Key Composition**

### **Family Behavior**

This family defines requirements for what the ~~TSF~~ defines or generates as an acceptably strong pre-shared key for authentication.

## Component Leveling



[\*\*FIA\\_PSK\\_EXT.1\*\*](#), Pre-Shared Key Composition, defines the use and composition of pre-shared keys used for IPsec.

[\*\*FIA\\_PSK\\_EXT.2\*\*](#), Generated Pre-Shared Keys, defines the use and composition of generated pre-shared keys used for IPsec.

[\*\*FIA\\_PSK\\_EXT.3\*\*](#), Password-Based Pre-Shared Keys, defines the use and composition of password-based pre-shared keys used for IPsec.

### Management: FIA\_PSK\_EXT.1

No specific management functions are identified.

### Audit: FIA\_PSK\_EXT.1

There are no auditable events foreseen.

### FIA\_PSK\_EXT.1 Pre-Shared Key Composition

Hierarchical to: No other components.

Dependencies to: FCS\_IPSEC\_EXT.1 IPsec Protocol

#### FIA\_PSK\_EXT.1.1

The ~~TSF~~ shall be able to use pre-shared keys for IPsec and [**selection**: *IKEv2, multifactor authentication filtering*].

#### FIA\_PSK\_EXT.1.2

The ~~TSF~~ shall be able to accept the following as pre-shared keys: [**selection**: *generated bit-based, password-based, HMAC-based one-time password, time-based one-time password, combination of a generated bit-based and HMAC-based one-time password, combination of a generated bit-based and time-based one-time password, combination of a password-based and HMAC-based one-time password, combination of a password-based and time-based one-time password*] keys.

### Management: FIA\_PSK\_EXT.2

No specific management functions are identified.

### Audit: FIA\_PSK\_EXT.2

The following actions should be auditable if FAU\_GEN Security Audit Data Generation is included in the PP/ST:

- Failure of the randomization process

## **FIA\_PSK\_EXT.2 Generated Pre-Shared Keys**

Hierarchical to: No other components.

Dependencies to: [FIA\\_PSK\\_EXT.1](#) Pre-Shared Key Composition

### **FIA\_PSK\_EXT.2.1**

The ~~TSF~~ shall be able to **[selection]**:

- *accept externally generated pre-shared keys*
- *generate [selection: 128, 256] bit-based pre-shared keys via FCS\_RBG.1.*

]

### **Management: FIA\_PSK\_EXT.3**

No specific management functions are identified.

### **Audit: FIA\_PSK\_EXT.3**

The following actions should be auditable if FAU\_GEN Security Audit Data Generation is included in the ~~PP/ST~~:

- Failure of the randomization process

## **FIA\_PSK\_EXT.3 Password-Based Pre-Shared Keys**

Hierarchical to: No other components.

Dependencies to: [FIA\\_PSK\\_EXT.1](#) Pre-Shared Key Composition

### **FIA\_PSK\_EXT.3.1**

The ~~TSF~~ shall support a PSK of up to **[assignment: positive integer of 64 or more]** characters.

### **FIA\_PSK\_EXT.3.2**

The ~~TSF~~ shall allow PSKs to be composed of any combination of upper case characters, lower case characters, numbers, and the following special characters: "!", "@", "#", "\$", "%", "^", "&", "\*", "(", and ")", and **[selection: [assignment: other supported special characters], no other characters]**

### **FIA\_PSK\_EXT.3.3**

The ~~TSF~~ shall perform Password-based Key Derivation Functions in accordance with a specified cryptographic algorithm **[assignment: cryptographic algorithm]** and output cryptographic key sizes **[assignment: output key sizes]** that meet the following: **[assignment: applicable standard]**.

### **FIA\_PSK\_EXT.3.4**

The ~~TSF~~ shall not accept PSKs less than **[selection: a value settable by the administrator, [assignment: minimum PSK length accepted by the TOE, must be >= 6]]** and greater than the maximum PSK length defined in [FIA\\_PSK\\_EXT.3.1](#).

### **FIA\_PSK\_EXT.3.5**

The TSF shall generate all salts using an RBG that meets FCS\_RBG.1 and with entropy of [**assignment: value equal to or greater than 128**] bits.

### **FIA\_PSK\_EXT.3.6**

The TSF shall require the PSK to be entered before every initiated connection.

### **FIA\_PSK\_EXT.3.7**


The TSF shall [**selection: provide a password strength meter, check the password against a denylist, perform no action to assist the user in choosing a strong password**].

## **C.2.2.3 FIA\_TOTP\_EXT Time-Based One-Time Password Pre-Shared Keys**

### **Family Behavior**

Components in this family define requirements for the use of Time-Based One-Time password authentication, including generation methods and usage restrictions.

### **Component Leveling**



[FIA\\_TOTP\\_EXT.1](#), Time-Based One-Time Password Pre-Shared Keys, defines the implementation of TOTP.

### **Management: FIA\_TOTP\_EXT.1**

No specific management functions are identified.

### **Audit: FIA\_TOTP\_EXT.1**

There are no auditable events foreseen.

## **FIA\_TOTP\_EXT.1 Time-Based One-Time Password Pre-Shared Keys**

Hierarchical to: No other components.

Dependencies to: FPT STM.1 Reliable Time Stamps

### **FIA\_TOTP\_EXT.1.1**

The TSF shall support Time-Based One-Time Password (TOTP) authentication in accordance with RFC 6238 to authenticate the user before establishing VPN connection.

### **FIA\_TOTP\_EXT.1.2**

The TSF shall generate a TOTP seed according to FCS\_RBG.1 of [**selection: 128, 256**] bits.

### **FIA\_TOTP\_EXT.1.3**

The TSF shall generate a new TOTP seed for each client.

### **FIA\_TOTP\_EXT.1.4**

The TSF shall use [**selection**: *SHA-1, SHA-256, SHA-384, SHA-512*] with key sizes [**assignment**: *key size (in bits) used in HMAC*] and message digest sizes [**selection**: *160, 256, 384, 512*] to derive a TOTP hash from the TOTP seed and current time provided by NTP.

### **FIA\_TOTP\_EXT.1.5**

The TSF shall truncate the TOTP hash per [FIA\\_TOTP\\_EXT.1.4](#) to create a TOTP of [**selection**:

- *administrator configurable character length of at least 6*
- *preset character length of [selection, choose one of: 6, 7, 8, 9, 10]*

].

### **FIA\_TOTP\_EXT.1.6**

The TSF shall [**selection**:

- *throttle invalid requests to [selection: administrator configurable value, [assignment: value less than 10]] per minute*
- *lock the associated account after [selection: administrator configurable value, [assignment: value less than 10]] failed attempts until [selection: an administrator unlocks the account, a configurable time period]*

].

### **FIA\_TOTP\_EXT.1.7**

The TSF shall set a time-step size of [**selection**: *a configurable value, [assignment: a value less than or equal to 30]*] seconds.

### **FIA\_TOTP\_EXT.1.8**

The TSF shall not validate a drift of more than [**selection**: *a configurable value, [assignment: a value less than or equal to 3]*] time-steps.

### **FIA\_TOTP\_EXT.1.9**

The TSF shall [**selection**: *allow resynchronization by recording time drift within the limit of FIA\_TOTP\_EXT.1.8, not permit resynchronization*].

## **C.2.3 Packet Filtering (FPF)**

This class contains families that describe packet filtering behavior. Packet filtering refers to the notion that network traffic that is transmitted through the TOE (i.e., the source and destination of the traffic is not the TOE but the TOE is on the routing path between these two entities) can be treated differently by the TSF based on attributes associated with the traffic. As this class is defined solely to contain an extended component defined for this PP-Module, it has two families, FPF\_MFA\_EXT and FPF\_RUL\_EXT.

### **C.2.3.1 FPF\_RUL\_EXT Packet Filtering Rules**

#### **Family Behavior**

This family defines the requirements for the rules that are used to perform packet filtering of network traffic.

#### **Component Leveling**

**FPF\_RUL\_EXT.1**, Packet Filtering Rules, requires the TSF to enforce a given set of packet filtering rules in an administrator-defined order against one or more TOE interfaces.

### **Management: FPF\_RUL\_EXT.1**

The following actions could be considered for the management functions in FMT:

- Ability to configure the TOE's packet filtering functionality (i.e., the operations to be performed on network traffic based on configured attributes, the interfaces that these are associated with, and the order in which they are applied).

### **Audit: FPF\_RUL\_EXT.1**

The following actions should be auditable if FAU\_GEN Security audit data generation is included in the PP/ST:

- Application of rules configured with the 'log' operation (including source and destination address, source and destination port, and transport layer protocol value).

## **FPF\_RUL\_EXT.1 Packet Filtering Rules**

Hierarchical to: No other components.

Dependencies to: No dependencies.

### **FPF\_RUL\_EXT.1.1**

The TSF shall perform packet filtering on network packets processed by the TOE.

### **FPF\_RUL\_EXT.1.2**

The TSF shall allow the definition of packet filtering rules using the following network protocols and protocol fields: [assignment: *supported network protocols and protocol fields*].

### **FPF\_RUL\_EXT.1.3**

The TSF shall allow the following operations to be associated with packet filtering rules: permit and drop with the capability to log the operation.

### **FPF\_RUL\_EXT.1.4**

The TSF shall allow the packet filtering rules to be assigned to each distinct network interface.

### **FPF\_RUL\_EXT.1.5**

The TSF shall process the applicable packet filtering rules (as determined in accordance with **FPF\_RUL\_EXT.1.4**) in the following order: [assignment: *rule processing order*].

### **FPF\_RUL\_EXT.1.6**


The TSF shall drop traffic if a matching rule is not identified.

## **C.2.3.2 FPF\_MFA\_EXT Multifactor Authentication Filtering**

### **Family Behavior**

Components in this family describe the requirements for multifactor authentication filtering when using the VPN client.

## Component Leveling



**FPF\_MFA\_EXT.1**, Multifactor Authentication Filtering, defines the use and composition of multifactor authentication filtering.

### Management: FPF\_MFA\_EXT.1

No specific management functions are identified.

### Audit: FPF\_MFA\_EXT.1

There are no auditable events foreseen.

## FPF\_MFA\_EXT.1 Multifactor Authentication Filtering

Hierarchical to: No other components.

Dependencies to: No dependencies.

### FPF\_MFA\_EXT.1.1

The TSF shall not forward packets to the internal network until the IKE tunnel has been established, except those necessary to verify additional authentication factors of the client.

### FPF\_MFA\_EXT.1.2

The TSF shall [selection: *verify, verify via an external authentication server*] additional authentication factors of the client.

## C.2.4 Protection of the TSF (FPT)

This PP-Module defines the following extended components as part of the FPT class originally defined by CC Part 2:

### C.2.4.1 FPT\_TST\_EXT TSF Self-Test

#### Family Behavior

This family is defined in the Base-PP. This PP-Module augments the extended family by adding one additional component, **FPT\_TST\_EXT.3**. This new component and its impact on the extended family's component leveling are shown below; reference the Base-PP for all other definitions for this family.

## Component Leveling



**FPT\_TST\_EXT.3**, Self-Test with Defined Methods, requires the TSF to specify the methods by which self-testing is performed in addition to identifying the self-tests that are executed and the circumstances in which this execution occurs.

## **Management: FPT\_TST\_EXT.3**

No specific management functions are identified.

## **Audit: FPT\_TST\_EXT.3**

There are no auditable events foreseen.

### **FPT\_TST\_EXT.3 Self-Test with Defined Methods**

Hierarchical to: No other components.

Dependencies to: No dependencies.

#### **FPT\_TST\_EXT.3.1**

The TSF shall run a suite of the following self-tests [**assignment**: *timing when self-testing is run*] to demonstrate the correct operation of the TSF: [**assignment**: *list of self-tests performed*].

#### **FPT\_TST\_EXT.3.2**

The TSF shall execute the self-testing through [**assignment**: *self-testing mechanism*].

## **C.2.5 TOE Access (FTA)**


This PP-Module defines the following extended components as part of the FTA class originally defined by CC Part 2:

### **C.2.5.1 FTA\_VCM\_EXT VPN Client Management**

#### **Family Behavior**

This family defines requirements for how the TSF interacts with VPN clients in its OE.

#### **Component Leveling**



FTA\_VCM\_EXT.1, VPN Client Management, requires the TSF to assign private (internal) IP addresses to VPN clients that successfully establish IPsec connections with it.

## **Management: FTA\_VCM\_EXT.1**

No specific management functions are identified.

## **Audit: FTA\_VCM\_EXT.1**

There are no auditable events foreseen.

### **FTA\_VCM\_EXT.1 VPN Client Management**

Hierarchical to: No other components.

Dependencies to: FCS\_IPSEC\_EXT.1 IPsec Protocol  
[FTP\_ITC.1 Inter-TSF Trusted Channel, or

**FTA\_VCM\_EXT.1.1**

The TSF shall assign a private IP address to a VPN client upon successful establishment of a security session.

# Appendix D - Implicitly Satisfied Requirements

This appendix lists requirements that should be considered satisfied by products successfully evaluated against this ~~PP-Module~~. These requirements are not featured explicitly as ~~SFRs~~ and should not be included in the ~~ST~~. They are not included as standalone ~~SFRs~~ because it would increase the time, cost, and complexity of evaluation. This approach is permitted by [CC] Part 1, 8.3 Dependencies between components.

This information benefits systems engineering activities which call for inclusion of particular security controls. Evaluation against the ~~PP-Module~~ provides evidence that these controls are present and have been evaluated.

All ~~SFR~~ dependencies in this ~~PP-Module~~ are addressed by appropriate ~~SFRs~~, either from elsewhere in the ~~PP-Module~~ or inherited from the ~~Base-PP~~.

# **Appendix E - Entropy Documentation and Assessment**

The TOE does not require any additional supplementary information to describe its entropy sources beyond the requirements outlined in the Base-PP. As with other Base-PP requirements, the only additional requirement is that the entropy documentation also applies to the specific VPN gateway capabilities of the TOE in addition to the functionality required by the claimed Base-PP.

# Appendix F - Acronyms

**Table 12: Acronyms**

Acronym	Meaning
Base-PP	Base Protection Profile
CA	Certificate Authority
CC	Common Criteria
CEM	Common Evaluation Methodology
CN	Common Name
cPP	Collaborative Protection Profile
DH	Diffie-Hellman
DN	Distinguished Name
FP	Functional Package
FQDN	Fully Qualified Domain Name
ICMP	Internet Control Message Protocol
IKE	Internet Key Exchange
MSK	Master Session Key
OE	Operational Environment
PBKDF	Password-Based Key Derivation Function
PP	Protection Profile
PP-Configuration	Protection Profile Configuration
PP-Module	Protection Profile Module
SA	Security Association
SAN	Subject Alternative Name
SAR	Security Assurance Requirement
SFP	Small Form-Factor Pluggable
SFR	Security Functional Requirement

<b>ST</b>	Security Target
<b>TOE</b>	Target of Evaluation
<b>TSF</b>	<b>TOE</b> Security Functionality
<b>TSEI</b>	<b>TSF</b> Interface
<b>TSS</b>	<b>TOE</b> Summary Specification
<b>VPN</b>	Virtual Private Network

# Appendix G - Bibliography

**Table 13: Bibliography**

Identifier	Title
[CC]	Common Criteria for Information Technology Security Evaluation - <ul style="list-style-type: none"><li>• <a href="#">Part 1: Introduction and general model</a>, CCMB-2022-11-001, CC:2022, Revision 1, November 2022.</li><li>• <a href="#">Part 2: Security functional requirements</a>, CCMB-2022-11-002, CC:2022, Revision 1, November 2022.</li><li>• <a href="#">Part 3: Security assurance requirements</a>, CCMB-2022-11-003, CC:2022, Revision 1, November 2022.</li><li>• <a href="#">Part 4: Framework for the specification of evaluation methods and activities</a>, CCMB-2022-11-004, CC:2022, Revision 1, November 2022.</li><li>• <a href="#">Part 5: Pre-defined packages of security requirements</a>, CCMB-2022-11-005, CC:2022, Revision 1, November 2022.</li></ul>
[CEM]	Common Methodology for Information Technology Security Evaluation - <ul style="list-style-type: none"><li>• <a href="#">Evaluation methodology</a>, CCMB-2022-11-006, CC:2022, Revision 1, November 2022.</li></ul>
[NDcPP]	<a href="#">collaborative Protection Profile for Network Devices, Version 4.0, December 22, 2025</a>