

PP-Module for VVoIP



Version: 2.0

2026-03-17

National Information Assurance Partnership

Revision History

Version	Date	Comment
1.0	2020-10-28	Initial publication
2.0	2026-03-17	CC:2022 updates, incorporation of TDs

Contents

- 1 Introduction
 - 1.1 Overview
 - 1.2 Terms
 - 1.2.1 Common Criteria Terms
 - 1.2.2 Technical Terms
 - 1.3 Compliant Targets of Evaluation
 - 1.3.1 TOE Boundary
 - 1.4 Use Cases
 - 1.5 Package Usage
 - 1.6 Implementation-Based Features
 - 1.6.1 Software Application with Logging
- 2 Conformance Claims
- 3 Security Problem Definition
 - 3.1 Threats
 - 3.2 Assumptions
 - 3.3 Organizational Security Policies
- 4 Security Objectives
 - 4.1 Security Objectives for the Operational Environment
 - 4.2 Security Objectives Rationale
- 5 Security Requirements
 - 5.1 Collaborative Protection Profile for Network Devices Security Functional Requirements Direction
 - 5.1.1 Modified SFRs
 - 5.1.1.1 Security Audit (FAU)
 - 5.1.1.2 Cryptographic Support (FCS)
 - 5.1.1.3 Protection of the TSF (FPT)
 - 5.1.1.4 Trusted Path (FTP)
 - 5.1.2 Additional SFRs
 - 5.2 Protection Profile for Application Software Security Functional Requirements Direction
 - 5.2.1 Modified SFRs
 - 5.2.1.1 Protection of the TSF (FPT)
 - 5.2.1.2 Trusted Path/Channel (FTP)
 - 5.2.2 Additional SFRs
 - 5.3 TOE Security Functional Requirements
 - 5.3.1 Auditable Events for Mandatory SFRs
 - 5.3.2 Communications (FCO)
 - 5.3.3 User Data Protection (FDP)
 - 5.3.4 Security Management (FMT)
 - 5.3.5 TOE Access (FTA)

5.3.6	Trusted Path/Channels (FTP)
5.4	TOE Security Functional Requirements Rationale
6	Consistency Rationale
6.1	Collaborative Protection Profile for Network Devices
6.1.1	Consistency of TOE Type
6.1.2	Consistency of Security Problem Definition
6.1.3	Consistency of OE Objectives
6.1.4	Consistency of Requirements
6.2	Protection Profile for Application Software
6.2.1	Consistency of TOE Type
6.2.2	Consistency of Security Problem Definition
6.2.3	Consistency of OE Objectives
6.2.4	Consistency of Requirements
Appendix A - Optional SFRs	
A.1	Strictly Optional Requirements
A.1.1	Security Audit(FAU)
A.2	Objective Requirements
A.3	Implementation-dependent Requirements
A.3.1	Security Audit (FAU)
Appendix B - Selection-based Requirements	
B.1	Security Audit (FAU)
B.2	Cryptographic Support (FCS)
B.3	User Data Protection (FDP)
B.4	Protection of the TSF (FPT)
Appendix C - Extended Component Definitions	
C.1	Extended Components Table
C.2	Extended Component Definitions
C.2.1	Communications (FCO)
C.2.1.1	FCO_VOC_EXT Fixed-Rate Vocoder
C.2.2	Cryptographic Support (FCS)
C.2.2.1	FCS_SRTP_EXT Secure Real-Time Transport Protocol
Appendix D - Implicitly Satisfied Requirements	
Appendix E - Entropy Documentation and Assessment	
Appendix F - Acronyms	
Appendix G - Bibliography	

1 Introduction

1.1 Overview

The scope of this PP-Module is to describe the security functionality of a Voice/Video over IP (VVoIP) endpoint in terms of [CC] and to define functional and assurance requirements for such products. This PP-Module is intended for use with the following Base-PPs:

- Protection Profile for Application Software, Version 2.0
- Network Device collaborative Protection Profile, Version 4.0

These Base-PPs are both valid because a VVoIP endpoint is a specific type of network device or software application that carries sensitive data over remote channels and uses protocols to do so that a typical network device or software application does not implement. Therefore, additional security requirements are necessary to ensure that sensitive communications are not subject to unauthorized disclosure to unintended recipients.

Note that the NDcPP defines an optional architecture for a “distributed TOE” that allows for security functionality to be spread across multiple distinct components. However, a TOE that conforms to the NDcPP and this PP-Module will not be a distributed TOE. All security functionality will be contained within a single physical device.

1.2 Terms

The following sections list Common Criteria and technology terms used in this document.

1.2.1 Common Criteria Terms

Assurance	Grounds for confidence that a TOE meets the SFRs [CC].
Base Protection Profile (Base-PP)	Protection Profile used as a basis to build a PP-Configuration.
Collaborative Protection Profile (cPP)	A Protection Profile developed by international technical communities and approved by multiple schemes.
Common Criteria (CC)	Common Criteria for Information Technology Security Evaluation (International Standard ISO/IEC 15408).
Common Criteria Testing Laboratory	Within the context of the Common Criteria Evaluation and Validation Scheme (CCEVS), an IT security evaluation facility accredited by the National Voluntary Laboratory Accreditation Program (NVLAP) and approved by the NIAP Validation Body to conduct Common Criteria-based evaluations.
Common Evaluation Methodology (CEM)	Common Evaluation Methodology for Information Technology Security Evaluation.

Direct Rationale	A type of Protection Profile, PP-Module, or Security Target in which the security problem definition (SPD) elements are mapped directly to the SFRs and possibly to the security objectives for the operational environment. There are no security objectives for the TOE.
Distributed TOE	A TOE composed of multiple components operating as a logical whole.
Functional Package (FP)	A document that collects SFRs for a particular protocol, technology, or functionality.
Operational Environment (OE)	Hardware and software that are outside the TOE boundary that support the TOE functionality and security policy.
Protection Profile (PP)	An implementation-independent set of security requirements for a category of products.
Protection Profile Configuration (PP-Configuration)	A comprehensive set of security requirements for a product type that consists of at least one Base-PP and at least one PP-Module.
Protection Profile Module (PP-Module)	An implementation-independent statement of security needs for a TOE type complementary to one or more Base-PPs.
Security Assurance Requirement (SAR)	A requirement to assure the security of the TOE.
Security Functional Requirement (SFR)	A requirement for security enforcement by the TOE.
Security Target (ST)	A set of implementation-dependent security requirements for a specific product.
Target of Evaluation (TOE)	The product under evaluation.
TOE Security Functionality (TSF)	The security functionality of the product under evaluation.
TOE Summary Specification (TSS)	A description of how a TOE satisfies the SFRs in an ST.

1.2.2 Technical Terms

Basic telephony functions	The basic functions a VVoIP phone must provide – pick up, dial tone, dial, talk.
Call control	The packets exchanged between devices to establish, maintain, and tear down a telephony call.
Client	A VVoIP endpoint.
Enterprise Session Controller (ESC)	A VVoIP call control server for VVoIP devices.
H.323	A communications protocol defined by ITU-T that is used for creating, modifying, and terminating multimedia sessions with multiple participants.

Peer-to-Peer (P2P)	A VVoIP architecture that forces each peer to be a server and client at the same time.
SDS-SRTP	A method of key negotiation for SRTP.
Secure Real-Time Transport Protocol (SRTP)	A protocol that is used to provide multimedia (voice/video) streaming services with added security of encryption, message authentication and integrity, and replay protection.
Sensitive Data	Call control/signal data, media data, and audit/management data that must be protected while in transit to prevent unauthorized disclosure.
Session Initiation Protocol (SIP)	A communications protocol defined by IETF that is used for creating, modifying, and terminating multimedia sessions with multiple participants.
Software/firmware update delivery channel	A trusted channel between a client and file server (which may be the same server as the call control server) for secure file download of software/firmware updates.
State	A configuration of a VVoIP endpoint based on how the user is currently using or not using the endpoint. Examples include: • Hook state: whether the endpoint is active (off-hook) or inactive (on-hook) • Mute state: the endpoint is active but is deliberately not transmitting data • Hold state: the endpoint is active but is deliberately not transmitting or receiving data
Streaming media	The voice/video exchanged between VVoIP endpoints.
VVoIP Call Control Server	A VVoIP infrastructure device that performs call control functions between a client and other VVoIP endpoints; this may be either a dedicated device such as an ESC or a VVoIP device itself when using P2P.

1.3 Compliant Targets of Evaluation

This PP-Module specifically addresses a dedicated network device or software application that facilitates the exchange of voice or video communication across an Internet Protocol (IP) network. The endpoint is a client (TOE) that communicates with a VVoIP call control server and may serve as its own call control server when using P2P. The VVoIP endpoint shall be able to secure file download from a file server to update VVoIP endpoint software and configuration, to establish secure communication for call control with the call control server, and to secure streaming media to other devices.

The combination of the NDcPP and this PP-Module is a network device that provides VVoIP endpoint functionality in addition to all of the security functionality expected of a network device as mandated by the NDcPP. The combination of the App PP and this PP-Module is a software application running on a general-purpose operating system that includes VVoIP endpoint capabilities in addition to all of the security functionality expected of a software application as mandated by the App PP.

This PP-Module describes the functional requirements and threats specific to the VVoIP endpoint. The most notable additions are requirements for the call control protocol (SIP, H.323) and streaming media protocol (SRTP, RTP). A conformant TOE is expected to be a standalone device or application; distributed TOE's are not permitted.

1.3.1 TOE Boundary

The TOE boundary includes the VVoIP-capable device or application (VVoIP endpoint). A VVoIP-capable device is a dedicated phone whereas a VVoIP endpoint application is just one of many applications that runs on a general-

purpose device such as a smartphone, tablet, or PC. Regardless of whether the TOE is a hardware appliance or a client application on an operating system, it will be deployed in the same environment. The figure below shows a typical VVoIP infrastructure from the perspective of the TOE. Many of the environmental components have direct connections between one another, but since these are not visible to the TOE, these connections have not been depicted.




Figure 1: Typical VVoIP Deployment

The TOE uses a VVoIP call control server, either by connecting to an ESC or acting as one itself when using P2P, in order to set up connections with other VVoIP endpoint devices or other telephony equipment such as a conference bridge. The call control server also may have the ability to deliver software/firmware updates to the TOE, but this can alternatively be performed by a file server. The TOE must be able to process Internet Protocol version 4 (IPv4) and/or IPv6 packets.

To be able to initiate communications in a client-server architecture, the TOE needs at minimum an IP address, network mask, gateway address, configuration server address, update server address (or may rely on platform for updates if it is a software application configured to do so), and call control server address. The address may be obtained by Dynamic Host Configuration Protocol (DHCP), manually entered on the VVoIP endpoint, or inherited from the device the TOE resides on (if it is a software application); addresses can belong to the same device if it performs multiple functions (such as an ESC which also performs updates). The TOE should allow basic telephony functions. Once the IP addresses are obtained, the TOE downloads any VVoIP application updates, downloads VVoIP endpoint configuration, and connects to the call control server as a VVoIP client. When a call is finished or the line is otherwise not in use, the TOE will ensure that streaming media communication paths/ports are closed while call control remains open.

To be able to initiate communications in P2P, the TOE needs at minimum an IP address, network mask, gateway address, and update server address (or may rely on platform for updates if it is a software application configured to do so). The address may be obtained by DHCP, manually entered on the VVoIP endpoint, or inherited from the device the TOE resides on (if it is a software application). The TOE should allow basic telephony functions. Once the IP addresses are obtained, the TOE downloads any VVoIP application updates. The endpoint configuration for P2P TOE of telephony functions is local. When the TOE initiates a call, the TOE connects to the other peer's call

control (which is active) and the TOE is a client. When the TOE receives a call, the other peer acts as a client and connects to the TOE's call control. When a call is finished or the line is otherwise not in use, the TOE will ensure that streaming media communication paths/ports are closed while call control remains open.

The TOE has three paths for three different functions that need to execute: streaming media path that contains voice, video, and session control (endpoint to endpoint); call control path to control the endpoint (endpoint to YVoIP call control server), and configuration/management path to configure and manage the TOE (software/firmware updates, configuration updates, audit).

1.4 Use Cases

This PP-Module defines four potential use cases for the YVoIP TOE, defined below. The first two use cases define the physical embodiment of the TOE, while the latter two define its role in a telecommunications deployment.

Regardless of the physical embodiment of the TOE, the expected functional capabilities are similar. However, when the TOE is deployed in a peer-to-peer architecture, it must perform auditing and call control functions that a client-server TOE does not need to perform because the Enterprise Session Controller provides those functions in that architecture. A client-server TOE may also perform its own auditing, but it is not required.

[USE CASE 1] Dedicated Appliance

The YVoIP endpoint is sold and packaged as a standalone network appliance that does not have a direct interface to the underlying platform operating system. In this use case, conformance to the NDcPP and this PP-Module is sufficient to ensure security. Note that the NDcPP defines optional functionality for “distributed TOEs” – for a TOE to conform to this PP-Module, it must be a single device and not a distributed TOE.

[USE CASE 2] Software Application

The YVoIP endpoint is sold and packaged as an application that is installed on a general-purpose computer or mobile device running a modifiable operating system (such as Windows or Linux). This computer may run end user applications above and beyond those used for YVoIP communications since it functions as a user workstation. In this case, the YVoIP endpoint application is expected to conform to both this PP-Module and the App PP.

[USE CASE 3] Client-Server Architecture

The YVoIP endpoint, whether hardware or software, is deployed in an environment where it interacts with an Enterprise Session Controller to facilitate call control functions.

[USE CASE 4] Peer-to-Peer Architecture

The YVoIP endpoint, whether hardware or software, is deployed in an environment where it interacts directly with other YVoIP endpoints without the use of an Enterprise Session Controller as an intermediary.

1.5 Package Usage

This section contains selections and assignments that are required when the listed Functional Packages are claimed by this PP-Module.

Package Usage guidance defined in the TOE's relevant Base-PP applies to the usage of the packages for this module, unless explicitly stated otherwise in this section.

Functional Package for X.509, Version 1.0

Certificate Verification and Assertion Required in FIA_XCU_EXT.1.1

Because this PP-Module mandates support for mutual authentication for media channels, the ST author shall select the options to both verify and assert certificate identities in FIA_XCU_EXT.1.1.

Limitations on Signature Algorithms in FIA_X509_EXT.1.1

The ~~TOE~~ must utilize appropriate cryptographic algorithms that conform to CNSA standards. Thus, the ~~TOE~~ shall utilize no other algorithms outside of those specified in RFC 8603 for certificate or CRL signatures. Additionally, the ~~TOE~~ shall not use ECDSA with SHA-512 signatures for OCSP responses, and shall utilize no other algorithms for OCSP responses.

Required Extension Processing for FIA_X509_EXT.1.2

The ~~ST~~ author shall select the options to process the basicConstraints and extendedKeyUsage extensions. Other extensions may be selected as appropriate without restriction.

CRL or OCSP-based Revocation Required for FIA_X509_EXT.1.3

The ~~TOE~~ must support revocation that only involves CRL or OCSP. Accordingly, the ~~TOE~~ shall select only from options involving CRL or OCSP in FIA_X509_EXT.1.3 (e.g., the selection to treat all certificates older than a given short timeframe is not an acceptable substitute or alternative for supporting CRL or OCSP).

Connections to CRL or OCSP Servers Required for FIA_X509_EXT.1.4

Because the ~~TOE~~ is required to support CRL or OCSP, the ~~TSF~~ shall support an appropriate mechanism for obtaining revocation status information. In the case of CRL, the ~~ST~~ author shall claim that revocation status information is obtained via network connection to a CRL distribution point. In the case of OCSP, the ~~ST~~ author shall claim that revocation status information is obtained via network connection to an OCSP responder, via OCSP stapling, or via OCSP multi-stapling.

Restrictions on Acceptable Key Usage Values for FIA_X509_EXT.1.5

The ~~TOE~~ will always support the use of extendedKeyUsage values to verify that X.509 certificates are used in accordance with their intended purpose. Accordingly, the ~~ST~~ author shall claim that the ~~TOE~~ supports the processing of extendedKeyUsage fields in the leaf certificate (as opposed to application of trust store context rules or passing the certification path or other supported context information to an external function) and shall select all values that are relevant to the claimed uses of X.509 in the ~~ST~~. In particular, since the ~~PP~~ does not define any functions that require the use of S/MIME, the ~~ST~~ author shall not select this as an extendedKeyUsage value to be validated.

Requirements on Functions for FIA_X509_EXT.2.1

The ~~ST~~ author shall additionally ensure that the selections and assignments in this requirement reflect the ~~TOE~~'s usage of X.509 certificate validation for TLS. Other assignments and selections may be made as applicable for other ~~TOE~~ functions.

Functional Package for Transport Layer Security (TLS), Version 2.1

DTLS or TLS Server and Client Functionality Required

The ~~ST~~ author shall select the option to utilize TLS as a client. The ~~ST~~ author shall additionally select the option to utilize DTLS as a client if support for DTLS is claimed in FTP_ITC.1.

DTLS or TLS Mutual Authentication Required

The ~~ST~~ shall select the option to support mutual authentication in FCS_TLSC_EXT.1 and FCS_TLSS_EXT.1, or FCS_DTLSC_EXT.1 and FCS_DTLSS_EXT.1, according with the protocol support claimed in FTP_ITC.1.

1.6 Implementation-Based Features

The following features of the ~~TOE~~ are implementation-based. A ~~TOE~~ is not required to implement these features to conform to this ~~PP-Module~~, but if the feature is implemented, it is expected that associated implementation-based requirements are claimed as part of the ~~TSF~~.

1.6.1 Software Application with Logging

The TOE is a software application and claims the App-PP as the Base-PP. The TOE additionally implements logging features (i.e. includes one or more of the following SFRs in the ST: [FAU_GEN.1/CSADMIN](#), [FAU_GEN.1/CSVVOIP](#), [FAU_GEN.1/P2PADMIN](#), [FAU_GEN.1/P2PVVOIP](#)).

If this feature is implemented by the TOE, the following requirements must be claimed in the ST:

- [FAU_STG.1](#)
- [FAU_STG.5](#)

2 Conformance Claims

Conformance Statement

An ST must claim exact conformance to this PP-Module.

The evaluation methods used for evaluating the TOE are a combination of the workunits defined in [\[CEM\]](#) as well as the Evaluation Activities for ensuring that individual SFRs and SARs have a sufficient level of supporting evidence in the Security Target and guidance documentation and have been sufficiently tested by the laboratory as part of completing ATE_IND.1. Any functional packages this PP claims similarly contain their own Evaluation Activities that are used in this same manner.

CC Conformance Claims

This PP-Module is conformant to Part 2 (extended) and Part 3 (extended) of Common Criteria CC:2022, Revision 1.

PP Claim

This PP-Module does not claim conformance to any Protection Profile.

The following PPs and PP-Modules are allowed to be specified in a PP-Configuration with this PP-Module:

- Network Device collaborative Protection Profile Version 4.0
- Protection Profile for Application Software Version 2.0

Package Claim

- This PP-Module is Functional Package for TLS, version 2.0 conformant.
- This PP-Module does not conform to any assurance packages.

The functional packages to which the PP conforms may include SFRs that are not mandatory to claim for the sake of conformance. An ST that claims one or more of these functional packages may include any non-mandatory SFRs that are appropriate to claim based on the capabilities of the TSE and on any triggers for their inclusion based inherently on the SFR selections made.

3 Security Problem Definition

The security problem is described in terms of the threats that the TOE is expected to address, assumptions about its operational environment, and any organizational security policies that the TOE is expected to enforce.

3.1 Threats

The following threats defined in this PP-Module extend the threats defined by the Base-PP.

T.MEDIA_DISCLOSURE

An attacker can use the encrypted variable rate vocoder frames to their advantage to decode transmitted data.
An attacker can also use improperly protected data to discern sensitive information.

T.UNDETECTED_TRANSMISSION

An attacker may cause the TOE to exfiltrate audio or video media over a remote channel while in a state where the user has a reasonable expectation that no media is being transmitted.

3.2 Assumptions

These assumptions are made on the Operational Environment (OE) in order to be able to ensure that the security functionality specified in the PP-Module can be provided by the TOE. If the TOE is placed in an OE that does not meet these assumptions, the TOE may no longer be able to provide all of its security functionality.

The following assumptions that are defined in this PP-Module extend the assumptions that are defined by the Base-PPs.

A.UPDATE_SOURCE

It is assumed that TOE software/firmware updates will be made available on either the call control server that the TOE connects to or a separate file server managed by the organization.

Note that because this PP-Module specifically disallows distributed TOEs, a conformant TOE will not claim A.COMPONENTS_RUNNING when NDcPP is the Base-PP.

3.3 Organizational Security Policies

This PP defines no Organizational Security Policies beyond those defined in the claimed Base-PP(s).

4 Security Objectives

4.1 Security Objectives for the Operational Environment

The following environmental security objectives that are defined in this PP-Module extend the objectives that are defined by the Base-PPs.

OE.UPDATE_SOURCE

The operational environment will have T.O.E software/firmware made available on either the call control server that the T.O.E connects to or a separate file server managed by the organization.

Note that because this PP-Module specifically disallows distributed T.O.Es, a conformant T.O.E will not claim OE.COMPONENTS_RUNNING when NDcPP is the Base-PP.

4.2 Security Objectives Rationale

This section describes how the assumptions and organizational security policies map to operational environment security objectives.

Table 1: Security Objectives Rationale

Assumption or OSP	Security Objectives	Rationale
A.UPDATE_SOURCE	OE.UPDATE_SOURCE	The objective satisfies the assumption by ensuring that T.O.E updates are made available in the intended location.

5 Security Requirements

This chapter describes the security requirements which have to be fulfilled by the product under evaluation. Those requirements comprise functional components from Part 2 and assurance components from Part 3 of [CC]. The following conventions are used for the completion of operations:

- **Refinement** operation (denoted by **bold text** or ~~striketrough text~~): Is used to add details to a requirement or to remove part of the requirement that is made irrelevant through the completion of another operation, and thus further restricts a requirement.
- **Selection** (denoted by *italicized text*): Is used to select one or more options provided by the [CC] in stating a requirement.
- **Assignment** operation (denoted by *italicized text*): Is used to assign a specific value to an unspecified parameter, such as the length of a password. Showing the value in square brackets indicates assignment.
- **Iteration** operation: Is indicated by appending the SFR name with a slash and unique identifier suggesting the purpose of the operation, e.g. "/EXAMPLE1."

5.1 Collaborative Protection Profile for Network Devices Security Functional Requirements Direction

In a ~~PP-Configuration~~ that includes the NDcPP, the ~~VVoIP~~ client is expected to rely on some of the security functions implemented by the network device as a whole and evaluated against the NDcPP. In this case, the following sections describe any modifications that the ~~ST~~ author must make to the ~~SFRs~~ defined in the NDcPP in addition to what is mandated by section 5.3.

5.1.1 Modified SFRs

The ~~SFRs~~ listed in this section are defined in the NDcPP and relevant to the secure operation of the ~~TOE~~.

5.1.1.1 Security Audit (FAU)

FAU_STG_EXT.1: Protected Audit Event Storage

This ~~SFR~~ is modified to prohibit the selection of distributed ~~TOE~~ options. Any element not specified in this section is unchanged from its definition in the ~~Base-PP~~.

The text of FAU_STG_EXT.1.2 is replaced with:

FAU_STG_EXT.1.2 The ~~TSE~~ shall be able to store generated audit data on the ~~TOE~~ itself. In addition,

- [*The ~~TOE~~ shall consist of a single standalone component that stores audit data locally*].

Application Note: This ~~PP-Module~~ modifies the existing FAU_STG_EXT.1 ~~SFR~~ in the NDcPP to prohibit the selection of any “distributed ~~TOE~~” behavior in FAU_STG_EXT.1.2. The ~~SFR~~ is otherwise unchanged.

5.1.1.2 Cryptographic Support (FCS)

FCS_NTP_EXT.1: NTP Protocol

This SFR is selection-based in the NDcPP and remains selection-based in this PP-Module. However, an additional trigger for this SFR's inclusion is added for the selection of "register the TOE to an ESC..." in FMT_SMF.1/VVoIP if the TOE is a hardware device. This is because any hardware-based VVoIP TOE that can be registered to an ESC is required to use the ESC as an NTP time source.

If the TOE is not registered to an ESC, it is not relevant to this PP-Module whether or not NTP is implemented, and in this case this SFR remains selection-based on FPT_STM_EXT.1.2, which is not modified by this PP-Module (i.e. a peer-to-peer TOE does not register to an ESC but may still receive time data from a separate NTP source).

5.1.1.3 Protection of the TSF (FPT)

FPT_TUD_EXT.1: Trusted Update

This PP-Module does not modify this SFR as it is defined in the NDcPP. However, note that this PP-Module expects that either the call control server or a separate file server managed by the organization to function as the source of TOE software/firmware updates. The evaluator shall ensure that the test environment is configured appropriately.

Evaluation Activities:

There is no change to the EAs specified for this SFR in the NDcPP Supporting Document. Note however that the following additional configuration steps are necessary in order for this testing to be performed:

- The evaluator shall deploy a call control server or dedicated file server in the TOE's operational environment
- The evaluator shall load valid and invalid candidate updates to the call control server or dedicated file server
- The evaluator shall configure the TOE to use the call control server or dedicated file server as its source for software/firmware updates

5.1.1.4 Trusted Path (FTP)

FTP_ITC.1: Inter-TSF Trusted Channel

This SFR is modified to mandate the inclusion of TLS. Any other protocols may additionally be claimed. Any element that is not included in this section is unchanged from its definition in the Base-PP.

The text of the requirement is replaced with:

FTP_ITC.1.1 The TSF shall be capable of using **TLS as defined in the Functional Package for TLS and [selection: IPsec, SSH as defined in the Functional Package for SSH, DTLS as defined in the Functional Package for TLS, HTTPS, no other protocols]** to provide a trusted communication channel between itself and authorized IT entities supporting the following capabilities: audit server, **streaming media channel, call control channel, software/firmware update delivery channel, [selection: authentication server, [assignment: other capabilities], no other capabilities]** that is logically distinct from other communication channels and provides assured identification of its end points and protection of the channel data from disclosure and detection of modification of the channel data.

Application Note: The NDcPP provides the ability for the ST author to specify the protocols used to establish trusted communications in FTP_ITC.1.1. This PP-Module mandates the inclusion of TLS because it is the underlying protocol used to secure communications with the ESC and other VVoIP endpoints. Additional protocols should be selected if they are used for securing other trusted channels. For example, the TSF may communicate with an ESC using TLS for call control functions but some other

protocol for remote transmission of audit data. This PP-Module also specifies additional uses for the trusted channel beyond what the NDcPP defines. The remainder of the SFR is unchanged from its definition in the Base-PP.

5.1.2 Additional SFRs

This PP-Module does not define any additional SFRs for any PP-Configuration where the NDcPP is claimed as the Base-PP.

5.2 Protection Profile for Application Software Security Functional Requirements Direction

In a PP-Configuration that includes the App PP, the VVoIP client is expected to rely on some of the security functions implemented by the software application as a whole and evaluated against the App PP. In this case, the following sections describe any modifications that the ST author must make to the SFRs defined in the App PP in addition to what is mandated by section 5.3.

5.2.1 Modified SFRs

The SFRs listed in this section are defined in the APP PP and relevant to the secure operation of the TOE.

5.2.1.1 Protection of the TSF (FPT)

FPT_TUD_EXT.1: Trusted Update

This PP-Module does not modify this SFR as it is defined in the App PP. However, note that this PP-Module expects that either the call control server or a separate file server managed by the organization to function as the source of TOE software/firmware updates. A vendor provided source should only be used if a call control server or separate file server cannot be configured.

Evaluation Activities:

There is no change to the EAs specified for this SFR in the App PP. Note however that the following additional configuration steps may be necessary when relying on a call control server or dedicated file server in order for this testing to be performed:

- The evaluator shall deploy a call control server or dedicated file server in the TOE's operational environment
- The evaluator shall load valid and invalid candidate updates to the call control server or dedicated file server
- The evaluator shall configure the TOE or its operational environment (whichever is selected to implement the security functions) to use the call control server or dedicated file server as its source for software/firmware updates.

5.2.1.2 Trusted Path/Channel (FTP)

FTP_DIT_EXT.1: Protection of Data in Transit

This SFR is modified from its definition in the Base-PP to mandate the inclusion of TLS as a method to protect data and to add support for the use of SRTP to protect data in transit.

The text of the requirement is replaced with:

FTP_DIT_EXT.1.1 The application shall [selection:

- not transmit any [selection, choose one of: data, sensitive data]
 - encrypt all transmitted [selection, choose one of: sensitive data, data] with **TLS as a server as defined in the Functional Package for Transport Layer Security (TLS), version 2.1 and also supports functionality for [selection: mutual authentication, none] and TLS as a client as defined in the Functional Package for Transport Layer Security (TLS), version 2.1 and [selection:**
 - **HTTPS as a client in accordance with FCS_HTTPS_EXT.1 and FCS_HTTPS_EXT.2**
 - **HTTPS as a server in accordance with FCS_HTTPS_EXT.1**
 - **HTTPS as a server with support for mutual authentication in accordance with FCS_HTTPS_EXT.1 and FCS_HTTPS_EXT.2**
 - **DTLS as a server defined in the Functional Package for Transport Layer Security (TLS), version 2.1 and also supports functionality for [selection: mutual authentication, none]**
 - **DTLS as a client defined in the Functional Package for Transport Layer Security (TLS), version 2.1**
 - **SSH as defined in the Functional Package for Secure Shell (SSH), version 2.0**
 - **IPsec as defined in the VPN Client PP-Module, version 3.0**
 - **Secure Real-Time Transport Protocol (SRTP)**
-] for [assignment: function(s)] using certificates as defined in the Functional Package for X.509
- invoke platform-provided functionality to encrypt all transmitted sensitive data with **TLS and [selection: HTTPS, DTLS, SSH, IPsec]** for [assignment: function(s)] using certificates as defined in the Functional Package for X.509
 - invoke platform-provided functionality to encrypt all transmitted data with **TLS and [selection: HTTPS, DTLS, SSH, IPsec]** for [assignment: function(s)] using certificates as defined in the Functional Package for X.509

] between itself and another trusted IT product.

Application Note: The App PP provides the ability for the ST author to specify the protocols used to establish trusted communications and the behavior that trusted communications are used to protect. This PP-Module mandates the inclusion of TLS because it is the underlying protocol used to secure communications with a VVoIP call control server and other VVoIP endpoints. Additional protocols may be selected if they are used for securing other channels. For example, the TSF may communicate with an ESC using TLS for call control functions but some other protocol for remote transmission of audit data.

Since the App PP does not define separate SFRs for trusted channel (TOE to trusted third party) and trusted path (administrator to TOE), FTP_DIT_EXT.1 is expected to cover both use cases. The proper protocols should be selected accordingly.

Sensitive data includes at minimum call control/signal data, media data, and audit/management data.

If “SRTP” is selected in FTP_DIT_EXT.1.1, the selection-based SFRs [FCS_COP.1/SRTP](#) and [FCS_SRTP_EXT.1](#) must be claimed.

5.2.2 Additional SFRs

This PP-Module does not define any additional SFRs for any PP-Configuration where the APP PP is claimed as the Base-PP.

5.3 TOE Security Functional Requirements

The following section describes the SFRs that must be satisfied by any TOE that claims conformance to this PP-Module. These SFRs must be claimed regardless of which PP-Configuration is used to define the TOE.

5.3.1 Auditable Events for Mandatory SFRs

Table 2: Auditable Events for Mandatory Requirements

Requirement	Auditable Events	Additional Audit Record Contents
FCO_VOC_EXT.1	No events specified	N/A
FDP_IFC.1	Call Detail Record (CDR) of VVoIP peer communications.	• Calling party • Called party • Start time of call • Call duration
FDP_IFF.1	No events specified	N/A
FMT_SMF.1/VVoIP	[selection: Registration of TOE to ESC., None]	[selection, choose one of: IP address or identifier for the ESC., No additional information]
FTA_SSL.3/MEDIA	Termination of a call due to inactivity.	Call party dropped time
FTP_ITC.1/CONTROL	Establishment of connection to VVoIP call control server	• Called party • Calling party • Established connection time
	Termination of connection to VVoIP call control server	• Called party • Calling party • Terminated connection time
FTP_ITC.1/MEDIA	Establishment of connection to VVoIP peer	• Called party • Calling party • Connection time to VVoIP peer
	Termination of connection to VVoIP peer	• Called party • Calling party • Disconnection time to VVoIP peer

5.3.2 Communications (FCO)

FCO_VOC_EXT.1 Fixed-Rate Vocoder

FCO_VOC_EXT.1.1

The TSF shall transmit voice media using a constant bit rate voice vocoder.

Application Note: A constant bit rate vocoder provides a constant output length that does not have the vulnerabilities that a variable bit rate vocoder contains when encrypted.

5.3.3 User Data Protection (FDP)

FDP_IFC.1 Subset Information Flow Control

FDP_IFC.1.1

The TSSF shall enforce the [*media transmission policy*] on [*voice/video media transmitted by the TOE*].

Application Note: There are states when on-hook voice and video must not stream from the TOE.

FDP_IFF.1 Simple Security Attributes

FDP_IFF.1.1

The TSSF shall enforce the [*media transmission policy*] based on the following types of subject and information security attributes: [*TOE hook state, VVoIP call connection status, and VVoIP call control server status*].

FDP_IFF.1.2

The TSSF shall permit an information flow between a controlled subject and controlled information via a controlled operation if the following rules hold: [

- The TOE is [**selection:** registered with a VVoIP call control server, acting as a VVoIP call control server when using P2P],
- A call has been established with a telephony device (VVoIP endpoint),
- The TOE is in the off-hook state,
- The TOE is not in the mute state,
- [**selection:** The TOE is not in the hold state, no other rules]

].

Application Note: If "acting as a VVoIP call control server when using P2P" is selected, the ST must include the selection-based SFRs [FAU_GEN.1/P2PADMIN](#), [FAU_GEN.1/P2PVVOIP](#), [FDP_IFC.1/CALLCONTROL](#), and [FDP_IFF.1/CALLCONTROL](#).

FDP_IFF.1.3

The TSSF shall enforce ~~the~~ [*no additional information flow control policy rules*].

FDP_IFF.1.4

The TSSF shall explicitly authorize an information flow based on the following rules: [*no additional rules*].

FDP_IFF.1.5

The TSSF shall explicitly deny an information flow based on the following rules: [*all TCP and UDP ports used by the TOE are closed when not in active use*].

5.3.4 Security Management (FMT)

FMT_SMF.1/VVoIP Specification of Management Functions (VVoIP Communications)

FMT_SMF.1.1/VVoIP

The TSSF shall be capable of performing the following management functions: [

- Ability to [**selection:**
 - register the TOE to an ESC [**selection:** manually, via DHCP server]
 - act as a VVoIP call control server when using P2P

];

[selection:

- Ability to configure audit behavior (e.g., changes to storage locations for audit; changes to behavior when local audit storage space is full);
- Ability to modify the behavior of the transmission of audit data to an external IT entity;
- Ability to configure the termination period for idle calls;
- Ability to specify the vocoder used;
- Ability to disable ~~SRTT~~ NULL algorithm;
- Ability to specify the ports to be used for ~~SRTT~~ communications;
- no other capabilities

]].

Application Note: This ~~SFR~~ defines additional management functions for the ~~TOE~~ beyond what is defined in each of the supported ~~Base-PPs~~ as FMT_SMF.1. The ~~TOE~~ may have all management functionality implemented in the same logical interface; it is not necessary for the ~~Base-PP~~ management functions and the ~~PP-Module's~~ management functions to be implemented separately.

The audit-related sections are duplicates of those in the NDcPP's definition of FMT_SMF.1. If the ~~VVoIP~~ audit functionality is configurable separately from the auditing for the device as a whole, the relevant selections should be made or omitted in each iteration as needed.

If "register the ~~TOE~~ to an ~~ESC...~~" is selected, regardless of ~~Base-PP~~ selection, the ~~ST~~ must include the selection-based ~~SFR~~ [FPT_STM_EXT.1/VVoIP](#).

If the ~~TOE~~ claims conformance to the NDcPP and "register the ~~TOE~~ to an ~~ESC...~~" is selected, the selection-based NDcPP ~~SFR~~ FCS_NTP_EXT.1 must additionally be claimed since connectivity to an ~~ESC~~ implies that the ~~TSF~~ will use it as an ~~NTP~~ server. In this case, the ~~TOE~~ does not need to implement two distinct time services for different purposes. The same time service defined by FPT_STM_EXT.1 may be used here as well. Note however, for this ~~PP-Module~~, the ~~TOE~~ must use ~~ESCs~~ to which it is registered as its ~~NTP~~ time sources.

If "act as a ~~VVoIP~~ call control server when using ~~P2P~~." is selected, the ~~ST~~ must include the selection-based ~~SFRs~~ [FAU_GEN.1/P2PADMIN](#), [FAU_GEN.1/P2PVVoIP](#), [FDP_IFC.1/CALLCONTROL](#), and [FDP_IFF.1/CALLCONTROL](#).

5.3.5 TOE Access (FTA)

FTA_SSL.3/MEDIA TSF-Initiated Termination (Media Channel)

FTA_SSL.3.1/MEDIA

The ~~TSF~~ shall terminate **voice/video transmission** after [*inactivity longer than* **[selection: [assignment: default number of seconds] seconds, an administrator-configurable interval**]].

Application Note: This ~~SFR~~ is intended to mitigate the potential unauthorized disclosure of media data in the case where connectivity with the peer is lost. The ~~ST~~ author should choose one or both selections if applicable. Note that if "an administrator-configurable interval" is selected, the ~~ST~~ author must select "configure the termination period for idle calls" in [FMT_SMF.1.1/VVoIP](#).

5.3.6 Trusted Path/Channels (FTP)

FTP_ITC.1/CONTROL Inter-TSF Trusted Channel (Signaling Channel)

FTP_ITC.1.1/CONTROL

The TSF shall **be capable of using [selection: *Session Initiation Protocol (SIP)*, *H.323*]** to provide a **trusted** communication channel between itself and a **VoIP call control server** that is logically distinct from other communication channels and provides assured identification of its end points and protection of the channel data from disclosure and detection of modification of the channel data.

Application Note: Both the SIP and H.323 protocols rely on TLS. This SFR defines the application layer protocol used to secure call control functions.

FTP_ITC.1.2/CONTROL

The TSF shall permit [*the TSF*, *the VoIP call control server*] to initiate communication via the trusted channel.

FTP_ITC.1.3/CONTROL

The TSF shall initiate communication via the trusted channel for [*establishment of call control*].

Application Note: The call control channel is secured with TLS as specified in FTP_DIT_EXT.1 from App PP or FTP_ITC.1 from NDcPP.

FTP_ITC.1/MEDIA Inter-TSF Trusted Channel (Media Channel)

FTP_ITC.1.1/MEDIA

The TSF shall **be capable of using [selection: *SRTP*, *H.235/H.323*]** to provide a trusted communication channel between itself and **another VoIP endpoint or other telephony device** that is logically distinct from other communication channels and provides assured identification of its end points and protection of the channel data from disclosure and detection of modification of the channel data.

Application Note: This SFR defines the application layer protocol used to secure voice/video transmissions once a call is established between another VoIP endpoint or other telephony device such as a call conference device.

If “SRTP” is selected, the selection-based SFRs [FCS_COP.1/SRTP](#) and [FCS_SRTP_EXT.1](#) must be claimed.

FTP_ITC.1.2/MEDIA

The TSF shall permit [*the TSF*, *another VoIP endpoint or other telephony device*] to initiate communication via the trusted channel.

FTP_ITC.1.3/MEDIA

The TSF shall initiate communication via the trusted channel for [*transmission of voice/video media*].

Application Note: The corresponding trusted media channel must be chosen to match the trusted control channel: SIP – SRTP, H.323 – H.235/H.323.

If “SRTP” is selected in FTP_ITC.1.1/Media, the selection-based SFRs [FCS_COP.1/SRTP](#) and [FCS_SRTP_EXT.1](#) must be claimed.

5.4 TOE Security Functional Requirements Rationale

The following rationale provides justification for each **SFR** for the **TOE**, showing that the **SFRs** are suitable to address the specified threats:

Table 3: SFR Rationale

Threat	Addressed by	Rationale
T.MEDIA_DISCLOSURE	FAU_STG_EXT.1 (modified from NDcPP)	Mitigates the threat by ensuring that audit data is securely stored locally and transmitted to an external entity.
	FAU_STG.1 (optional for software-only TOEs)	Mitigates the threat by ensuring that audit data is securely transmitted to an external entity.
	FAU_STG.5 (optional for software-only TOEs)	Mitigates the threat by defining behavior for response to log space overruns.
	FCO_VOC_EXT.1	Mitigates the threat by defining the use of a fixed-rate vocoder to prevent the exposure of encryption vulnerabilities that are present with variable-rate vocoders.
	FCS_COP.1/SRTP (selection-based)	Mitigates the threat by defining the implementation of encryption used for SDES-SRTP, if supported by the TOE .
	FCS_NTP_EXT.1 (modified from NDcPP)	Mitigates the threat by defining how accurate system time is maintained, which is used to support certain cryptographic functions.
	FCS_SRTP_EXT.1 (selection-based)	Mitigates the threat by defining the implementation of the SRTP protocol, if supported by the TOE .
	FDP_IFC.1/CALLCONTROL (selection-based)	Mitigates the threat by defining a policy for protection of call control information in cases where the TOE can act as a V.VoIP call control server in a peer-to-peer configuration.
	FDP_IFF.1/CALLCONTROL (selection-based)	Mitigates the threat by defining the implementation of the call control policy in cases where the TOE can act as a V.VoIP call control server in a peer-to-peer configuration.
	FPT_STM_EXT.1/VVoIP (selection-based)	Mitigates the threat by defining how the TSE obtains system time in certain cases, which is then used as an input to other functions that support this objective.
	FPT_TUD_EXT.1 (modified from NDcPP and App PP)	Mitigates the threat by ensuring the cryptographic functions or other TSE can be updated to remain secure.
	FTP_DIT_EXT.1 (modified from App PP)	Mitigates the threat by defining the trusted communications channel used for V.VoIP .

	FTP_ITC.1 (modified from NDcPP)	Mitigates the threat by defining the trusted communications channel used for .VVoIP.
	FTP_ITC.1/CONTROL	Mitigates the threat by defining the application-layer channel used for communications with a .VVoIP call control server.
	FTP_ITC.1/MEDIA	Mitigates the threat by defining the application-layer channel used for communications of media (voice and video) data.
T.UNDETECTED_TRANSMISSION	FAU_GEN.1/CSADMIN (optional)	Mitigates the threat by optionally allowing a client-server .TOE to provide an audit trail of administrative actions, which could diagnose misconfiguration of the .TOE that could lead to unattended transmissions.
	FAU_GEN.1/P2PADMIN (selection-based)	Mitigates the threat by requiring a peer-to-peer .TOE to provide an audit trail of administrative actions, which could diagnose misconfiguration of the .TOE that could lead to unattended transmissions.
	FDP_IFC.1	Mitigates the threat by defining the existence of a media transmission policy.
	FDP_IFF.1	Mitigates the threat by defining how the media transmission policy is enforced to determine when transmissions should occur.
	FMT_SMF.1/VVoIP	Mitigates the threat by requiring the .TSF to implement certain the management functions specific to .VVoIP functionality.
	FPT_STM_EXT.1/VVoIP (selection-based)	Mitigates the threat by requiring the .TSF to specify how it obtains system time in certain cases, which is then used as an input to other functions that support this objective.
	FTA_SSL.3/MEDIA	Mitigates the threat by requiring the .TSF to terminate idle sessions.

6 Consistency Rationale

6.1 Collaborative Protection Profile for Network Devices

6.1.1 Consistency of TOE Type

When this PP-Module is used to extend the NDcPP, the `TOE` type for the overall `TOE` is still a network device. The `TOE` boundary is simply extended to include `YVoIP` endpoint functionality that is provided by the network device.

6.1.2 Consistency of Security Problem Definition

The threats and assumptions defined by this PP-Module (see sections 3.1 and 3.2) supplement those defined in the NDcPP as follows:

Table 4: Consistency of Security Problem Definition (NDcPP base)

PP-Module Threat, Assumption, OSP	Consistency Rationale
<code>T.MEDIA_DISCLOSURE</code>	The NDcPP defines a threat for untrusted communications channels. The threat of media disclosure through vocoder frames is a type of side channel attack that is unique to the functions of a <code>YVoIP</code> endpoint. However, it is consistent with the overall threat of unintended disclosure of sensitive data.
<code>T.UNDETECTED_TRANSMISSION</code>	The NDcPP defines threats for insecure communications and undetected activity. Unauthorized and undetected use of a communications channel is consistent with these threats.
<code>A.UPDATE_SOURCE</code>	The NDcPP does not have any assumptions for the source of <code>TOE</code> updates, only that the updates have adequate integrity protections. There is no conflict with this Module assuming that <code>TOE</code> updates will be retrieved from a particular location.

6.1.3 Consistency of OE Objectives

The objectives for the `TOE`'s operational environment are consistent with the NDcPP based on the following rationale:

Table 5: Consistency of OE Objectives (NDcPP base)

PP-Module OE Objective	Consistency Rationale
<code>OE.UPDATE_SOURCE</code>	The NDcPP requires the <code>TOE</code> to be able to apply software/firmware updates but does not define any specific way that these updates need to be made available. This PP-Module defines an objective that allows for an assumption that <code>TOE</code> updates will be made available in a specific location. <code>A.UPDATE_SOURCE</code> is consistent with the <code>Base-PP</code> objectives for the same reason.

6.1.4 Consistency of Requirements

This PP-Module identifies several SFRs from the NDcPP that are needed to support VVoIP functionality. This is considered to be consistent because the functionality provided by the NDcPP is being used for its intended purpose. The rationale for why this does not conflict with the claims defined by the NDcPP are as follows:

Table 6: Consistency of Requirements (NDcPP base)

PP-Module Requirement	Consistency Rationale
Modified SFRs	
FAU_STG_EXT.1	This PP-Module modifies this SFR to prohibit the selection of any “distributed TOE” behavior in FAU_STG_EXT.1.2.
FCS_NTP_EXT.1	This PP-Module does not modify this SFR; it only modifies the circumstances that trigger its inclusion in the TOE’s logical boundary.
FPT_TUD_EXT.1	This PP-Module does not modify this SFR; it only specifies that the source of TOE software/firmware updates must be a specific type of server.
FTP_ITC.1	This PP-Module restricts the Base-PP SFR to a subset of existing permissible functionality and does not introduce any new behavior.
Additional SFRs	
This PP-Module does not add any requirements when the NDcPP is the base.	
Mandatory SFRs	
FCO_VOC_EXT.1	The use of a fixed-rate vocoder relates to application-layer communications that are not within the scope of the NDcPP.
FDP_IFC.1	This SFR defines a policy for when data will or will not be transmitted by the TSF. The NDcPP defines requirements for how data is transmitted but a policy governing when an external interface may be invoked is beyond its scope.
FDP_IFF.1	This SFR defines the rules for a policy for when data will or will not be transmitted by the TSF. The NDcPP defines requirements for how data is transmitted but a policy governing when an external interface may be invoked is beyond its scope.
FMT_SMF.1/VVoIP	This PP-Module defines a new iteration of FMT_SMF.1 to add additional management functions that relate specifically to VVoIP functionality. The addition of these functions does not prevent any of the original functions from being implemented. This iteration does include two duplicates of management functions specified in the Base-PP; this is consistent because it is possible that auditing is handled differently for the VVoIP functionality as it is for the rest of the TOE’s auditing. These functions are also selectable so it is not required that a conformant TOE implement this.
FTA_SSL.3/MEDIA	This SFR defines session termination behavior for the TOE’s media channel. This interface is specific to this PP-Module and is not within the scope of the NDcPP.
FTP_ITC.1/CONTROL	This SFR defines the trusted communications protocol used by the TOE’s signaling channel, which is specific to the VVoIP technology and does not

conflict with the functionality defined in the NDcPP.

FTP_ITC.1/MEDIA

This ~~SFR~~ defines the trusted communications protocol used by the ~~TOE~~'s media channel, which is specific to the ~~VVoIP~~ technology and does not conflict with the functionality defined in the NDcPP.

Optional ~~SFRs~~

FAU_GEN.1/CSADMIN

The NDcPP already defines an audit generation function. This ~~PP-Module~~ adds redundant audit events for administrative actions (with respect to those defined in the NDcPP) to be required for software-only ~~TOEs~~. A ~~TOE~~ that conforms to the NDcPP satisfies this ~~SFR~~ by default.

FAU_GEN.1/CSVVOIP

The NDcPP already defines an audit generation function. This ~~PP-Module~~ adds an iteration of FAU_GEN.1 for the auditable events that relate specifically to ~~VVoIP~~ endpoint behavior that may apply for client-server ~~TOEs~~.

Objective ~~SFRs~~

This ~~PP-Module~~ does not define any Objective requirements.

Implementation-dependent ~~SFRs~~

FAU_STG.1

This ~~SFR~~ is implementation-dependent and is explicitly not claimed when the NDcPP is the ~~Base-PP~~. Therefore there is no conflict between this ~~SFR~~ and the NDcPP.

FAU_STG.5

This ~~SFR~~ is implementation-dependent and is explicitly not claimed when the NDcPP is the ~~Base-PP~~. Therefore there is no conflict between this ~~SFR~~ and the NDcPP.

Selection-based ~~SFRs~~

FAU_GEN.1/P2PADMIN

The NDcPP already defines an audit generation function. This ~~PP-Module~~ adds redundant audit events for administrative actions (with respect to those defined in the NDcPP) to be required for software-only ~~TOEs~~. A ~~TOE~~ that conforms to the NDcPP satisfies this ~~SFR~~ by default.

FAU_GEN.1/P2PVVOIP

The NDcPP already defines an audit generation function. This ~~PP-Module~~ adds an iteration of FAU_GEN.1 for the auditable events that relate specifically to ~~VVoIP~~ endpoint behavior that must apply for peer-to-peer ~~TOEs~~.

FCS_COP.1/SRTP

This ~~SFR~~ defines the AES functionality used to support ~~SRTP~~. This does not conflict with the NDcPP because the ~~TOE~~ can still use FCS_COP.1/DataEncryption to make claims related to all other uses of AES.

FCS_SRTP_EXT.1

This ~~SFR~~ defines support for the ~~SRTP~~ protocol, which is specific to ~~VVoIP~~ technology. The ~~TSE~~'s implementation of this protocol does not prevent the enforcement of any NDcPP ~~SFRs~~.

FDP_IFC.1/CALLCONTROL

This ~~SFR~~ defines ~~VVoIP~~ call control policy. The ~~TSE~~'s implementation of this protocol does not prevent the enforcement of any NDcPP ~~SFRs~~.

FDP_IFF.1/CALLCONTROL

This ~~SFR~~ defines ~~VVoIP~~ call control policy. The ~~TSE~~'s implementation of this protocol does not prevent the enforcement of any NDcPP ~~SFRs~~.

FPT_STM_EXT.1/VVoIP	This SFR defines the TOE's reliance on ESCs to act as its NTP servers in deployments where the TOE is registered to them. It is duplicative of the FPT_STM_EXT.1 SFR defined in the Base-PP but is refined to identify the use of the ESC as a specific NTP server, which is a restriction not present in the Base-PP.
---------------------	--

6.2 Protection Profile for Application Software

6.2.1 Consistency of TOE Type

When this PP-Module is used to extend the App PP, the TOE type for the overall TOE is still a software application. The TOE boundary is simply extended to include the VVoIP endpoint functionality that is supported by the application.

6.2.2 Consistency of Security Problem Definition

The threats and assumptions defined by this PP-Module (see sections 3.1 and 3.2) supplement those defined in the App PP as follows:

Table 7: Consistency of Security Problem Definition (APP PP base)

PP-Module Threat, Assumption, OSP	Consistency Rationale
T.MEDIA_DISCLOSURE	The App PP defines a threat for network eavesdropping. The threat of media disclosure through vocoder frames is a type of side-channel attack that is unique to the functions of a VVoIP endpoint. However, it is consistent with the overall threat of unintended disclosure of sensitive data.
T.UNDETECTED_TRANSMISSION	The App PP defines threats for network attack and network eavesdropping. Unauthorized and undetected use of a communications channel is consistent with these threats.
A.UPDATE_SOURCE	The App PP does not have any assumptions for the source of TOE updates, only that the updates have adequate integrity protections. There is no conflict with this Module assuming that TOE updates will be retrieved from a particular location.

6.2.3 Consistency of OE Objectives

The objectives for the TOE's operational environment are consistent with the App-PP based on the following rationale:

Table 8: Consistency of OE Objectives (APP PP base)

PP-Module OE Objective	Consistency Rationale
OE.UPDATE_SOURCE	The App PP requires the TOE to be able to apply software/firmware updates but does not define any specific way that these updates need to be made available. This PP-Module defines an objective that allows for an assumption that TOE updates will be made available in a specific location. A.UPDATE_SOURCE is consistent with the Base-PP objectives for the same reason.

6.2.4 Consistency of Requirements

This PP-Module identifies several SFRs from the APP PP that are needed to support VVoIP functionality. This is considered to be consistent because the functionality provided by the APP PP is being used for its intended purpose. The PP-Module also identifies a number of modified SFRs from the APP PP that are used entirely to provide functionality for VVoIP. The rationale for why this does not conflict with the claims defined by the APP PP are as follows:

Table 9: Consistency of Requirements (APP PP base)

PP-Module Requirement	Consistency Rationale
Modified SFRs	
FPT_TUD_EXT.1	This PP-Module does not modify this SFR; it only specifies that the source of TOE software/firmware updates must be a specific type of server.
FTP_DIT_EXT.1	This PP-Module modifies the App PP SFR by mandating the use of trusted communications to secure transmitted data, mandating support for TLS, and permitting support for SRTP. The first two modifications are derived from selections that are already present in the App PP version of the SFR. The addition of SRTP does not prevent any of the other protocols from being used if supported.
Additional SFRs	
This PP-Module does not add any requirements when the APP PP is the base.	
Mandatory SFRs	
FCO_VOC_EXT.1	The use of a fixed-rate vocoder relates to application-layer communications that are not within the scope of the App PP.
FDP_IFC.1	This SFR defines a policy for when data will or will not be transmitted by the TSF. The App PP defines requirements for how data is transmitted but a policy governing when an external interface may be invoked is beyond its scope.
FDP_IFF.1	This SFR defines the rules for a policy for when data will or will not be transmitted by the TSF. The App PP defines requirements for how data is transmitted but a policy governing when an external interface may be invoked is beyond its scope.
FMT_SMF.1/VVoIP	This PP-Module defines a new iteration of FMT_SMF.1 to add additional management functions that relate specifically to VVoIP functionality. The addition of these functions does not prevent any of the original functions from being implemented. This iteration does include two duplicates of management functions specified in the Base-PP; this is consistent because it is possible that auditing is handled differently for the VVoIP functionality as it is for the rest of the TOE's auditing. These functions are also selectable so it is not required that a conformant TOE implement this.
FTA_SSL.3/MEDIA	This SFR defines session termination behavior for the TOE's media channel. This interface is specific to this PP-Module and is not within the scope of the App PP.
FTP_ITC.1/CONTROL	This SFR defines the trusted communications protocol used by the TOE's signaling channel, which is specific to the VVoIP technology and does not

conflict with the functionality defined in the App PP.

FTP_ITC.1/MEDIA

This SFR defines the trusted communications protocol used by the TOE's media channel, which is specific to the VVoIP technology and does not conflict with the functionality defined in the App PP.

Optional SFRs

FAU_GEN.1/CSADMIN

This PP-Module specifies an iteration of FAU_GEN.1 for the auditable events that relate specifically to the administration of the VVoIP endpoint. The App PP does not mandate that the TOE include an audit function but it is not prohibited by the PP.

FAU_GEN.1/CSVVOIP

This PP-Module specifies an iteration of FAU_GEN.1 for the auditable events that relate specifically to VVoIP endpoint behavior. The App PP does not mandate that the TOE include an audit function but it is not prohibited by the PP.

Objective SFRs

This PP-Module does not define any Objective requirements.

Implementation-dependent SFRs

FAU_STG.1

This SFR defines the ability of the TOE to protect, store, and transmit audit data to a remote server using a secure channel. The App PP does not define its own requirements for auditing but it does not prohibit audit functionality, so this PP-Module's inclusion of an audit function does not conflict with the PP.

FAU_STG.5

This SFR defines the ability of the TOE to handle log space overruns in a defined manner. The App PP does not define its own requirements for auditing but it does not prohibit audit functionality, so this PP-Module's inclusion of an audit function does not conflict with the PP.

Selection-based SFRs

FAU_GEN.1/P2PADMIN

This PP-Module specifies an iteration of FAU_GEN.1 for the auditable events that relate specifically to the administration of the VVoIP endpoint. The App PP does not mandate that the TOE include an audit function but it is not prohibited by the PP.

FAU_GEN.1/P2PVVOIP

This PP-Module specifies an iteration of FAU_GEN.1 for the auditable events that relate specifically to VVoIP endpoint behavior. The App PP does not mandate that the TOE include an audit function but it is not prohibited by the PP.

FCS_COP.1/SRTP

This SFR defines the AES functionality used to support SRTP. This does not conflict with the App PP because the TOE can still use FCS_COP.1/DataEncryption to make claims related to all other uses of AES.

FCS_SRTP_EXT.1

This SFR defines support for the SRTP protocol, which is specific to VVoIP technology. The TSF's implementation of this protocol does not prevent the enforcement of any App PP SFRs.

FDP_IFC.1/CALLCONTROL	This SFR defines VVoIP call control policy. The TSF's implementation of this protocol does not prevent the enforcement of any App PP SFRs.
FDP_IFF.1/CALLCONTROL	This SFR defines VVoIP call control policy. The TSF's implementation of this protocol does not prevent the enforcement of any App PP SFRs.
FPT_STM_EXT.1/VVoIP	This SFR defines the TOE's reliance on ESCs to act as its NTP servers in deployments where the TOE is registered to them. The App PP does not define a specific method for how a conformant TOE is expected to receive time data so there is no contradiction here.

Appendix A - Optional SFRs

A.1 Strictly Optional Requirements

A.1.1 Security Audit(FAU)

FAU_GEN.1/CSADMIN Audit Data Generation (Client-Server Admin Events)

FAU_GEN.1.1/CSADMIN

The [**selection:** ~~TSE, TOE platform~~] shall be able to generate audit data of the following auditable events:

- a. ~~Start-up and shutdown of the audit functions;~~
- b. ~~All auditable events for the [**selection,** choose one of: minimum, basic, detailed, not specified] level of audit;~~
- c. [All administrative actions comprising:
 - i. Administrative login and logout (name of user account shall be logged if individual user accounts are required for Administrators).
 - ii. Changes to ~~TSE~~ data related to configuration changes (in addition to the information that a change occurred it shall be logged what has been changed).
 - iii. Generating/import of, changing, or deleting of cryptographic keys (in addition to the action itself a unique key name or key reference shall be logged).
 - iv. Resetting passwords (name of related user account shall be logged).
 - v. [**selection:** [assignment: list of other uses of privileges], no other actions]].

Application Note: This SFR defines the same auditable events as [FAU_GEN.1/P2PADMIN](#) in Appendix B below. It is defined as a separate iteration because when the ~~TOE~~ is deployed in a client-server architecture, the Enterprise Session Controller is expected to be responsible for the relevant auditing, so this capability is optional when the ~~TOE~~ is not peer-to-peer.

If the ~~TOE~~ claims this SFR and conforms to the App PP, the implementation-dependent SFRs [FAU_STG.1](#) and [FAU_STG.5](#) must also be claimed. This does not need to be claimed when the ~~TOE~~ conforms to the NDcPP because that PP already defines FAU_STG.1 as a mandatory requirement.

FAU_GEN.1.2/CSADMIN

The ~~TSE~~ shall record within the audit data at least the following information:

- a. Date and time of the auditable event, type of event, subject identity (if applicable), and the outcome (success or failure) of the event;
- b. For each auditable event type, based on the auditable event definitions of the functional components included in the PP, PP::Module, functional package or ST, [no additional information].

FAU_GEN.1/CSVVOIP Audit Data Generation (Client-Server VVoIP Events)

FAU_GEN.1.1/CSVVOIP

The TSE shall be able to generate audit data of the following auditable events:

- a. ~~Start-up and shutdown of the audit functions;~~
- b. ~~All auditable events for the [selection, choose one of: minimum, basic, detailed, not specified] level of audit;~~
- c. *[auditable events defined in the Auditable Events for Mandatory SERs table (Table 2)].*

FAU_GEN.1.2/CSVVOIP

The TSE shall record within the audit data at least the following information:

- a. Date and time of the auditable event, type of event, subject identity (if applicable), and the outcome (success or failure) of the event;
- b. For each auditable event type, based on the auditable event definitions of the functional components included in the PP, PP.Module, functional package or ST, *[information specified in column three of the Auditable Events table in which the event was defined]*.

Application Note: This SER defines the same auditable events as FAU_GEN.1/PP-VVoIP in Appendix B below. It is defined as a separate iteration because when the TOE is deployed in a client-server architecture, the Enterprise Session Controller is expected to be responsible for the relevant auditing, so this capability is optional when the TOE is not peer-to-peer.

If the TOE claims this SER and conforms to the App PP, the implementation-dependent SERs [FAU_STG.1](#) and [FAU_STG.5](#) must also be claimed. This does not need to be claimed when the TOE conforms to the NDcPP because that PP already defines [FAU_STG.1](#) as a mandatory requirement.

A.2 Objective Requirements

This PP.Module does not define any Objective SERs.

A.3 Implementation-dependent Requirements

A.3.1 Security Audit (FAU)

FAU_STG.1 Audit data storage location

This component must be included in the ST if the TOE implements any of the following features:

- [Software Application with Logging](#)

FAU_STG.1.1

The TSE shall be able to store generated audit data on the [*selection: TOE itself, TOE platform*], transmit the generated audit data to [*selection: an Enterprise Session Controller that the TOE is registered to, an external IT entity*] using a trusted channel according to [FTP_DIT_EXT.1](#).]

Application Note: This ~~SFR~~ is modified from its definition in [CC] Part 2 to define storage for audit data. Specifically, it is required that this data be stored both on the ~~TOE~~ itself and that it be transmitted securely to an external entity. Note that this ~~SFR~~ is only applicable for software application ~~TOEs~~ that implement logging, because the NDcPP specifies log data storage requirements itself. This ~~SFR~~ should not be claimed when the NDcPP is the ~~Base-PP~~.

FAU_STG.5 Prevention of audit data loss

This component must be included in the ~~ST~~ if the ~~TOE~~ implements any of the following features:

- *Software Application with Logging*

FAU_STG.5.1

The ~~TSE~~ shall [**selection:** *ignore audited events, overwrite the oldest stored audit records, [assignment: other actions to be taken in case of audit storage failure and conditions for the actions]*] if the audit data storage is full.

Application Note: Note that this ~~SFR~~ is only applicable for software application ~~TOEs~~ that implement logging, because the NDcPP specifies log data storage requirements itself. This ~~SFR~~ should not be claimed when the NDcPP is the ~~Base-PP~~.

Appendix B - Selection-based Requirements

B.1 Security Audit (FAU)

FAU_GEN.1/P2PADMIN Audit Data Generation (Peer-to-Peer Admin Events)

The inclusion of this selection-based component depends upon selection in [FDP_IFF.1.2](#), [FMT_SMF.1.1/VVoIP](#).

FAU_GEN.1.1/P2PADMIN

The **[selection: ~~TSE~~, ~~TOE~~ platform]** shall be able to generate audit data of the following auditable events:

- a. ~~Start-up and shutdown of the audit functions;~~
- b. ~~All auditable events for the [selection, choose one of: minimum, basic, detailed, not specified] level of audit;~~
- c. *[All administrative actions comprising:*
 - i. *Administrative login and logout (name of user account shall be logged if individual user accounts are required for Administrators).*
 - ii. *Changes to ~~TSE~~ data related to configuration changes (in addition to the information that a change occurred it shall be logged what has been changed).*
 - iii. *Generating/import of, changing, or deleting of cryptographic keys (in addition to the action itself a unique key name or key reference shall be logged).*
 - iv. *Resetting passwords (name of related user account shall be logged).*
 - v. *[selection: [assignment: list of other uses of privileges], no other actions]**].*

FAU_GEN.1.2/P2PADMIN

The ~~TSE~~ shall record within the audit data at least the following information:

- a. Date and time of the auditable event, type of event, subject identity (if applicable), and the outcome (success or failure) of the event;
- b. For each auditable event type, based on the auditable event definitions of the functional components included in the ~~PP~~, ~~PP-Module~~, functional package or ~~ST~~, *[no additional information]*.

Application Note: If the ~~TOE~~ is a hardware device and claims this ~~SFR~~, this is inherently satisfied through FAU_GEN.1 as defined by the NDcPP. Any other relevant auditable events for the functionality described in the NDcPP is defined there (the App ~~PP~~ does not include any auditing requirements).

If the ~~TOE~~ claims this ~~SFR~~ and conforms to the App ~~PP~~, the implementation-dependent ~~SFRs~~ [FAU_STG.1](#) and [FAU_STG.5](#) must also be claimed. This does not need to be claimed when the ~~TOE~~ conforms to the NDcPP because that ~~PP~~ already defines FAU_STG.1 as a mandatory requirement.

FAU_GEN.1/P2PVVOIP Audit Data Generation (Peer-to-Peer VVoIP Events)

The inclusion of this selection-based component depends upon selection in FDP_IFF.1.2, FMT_SMF.1.1/VVoIP.

FAU_GEN.1.1/P2PVVOIP

The TSF shall be able to generate audit data of the following auditable events:

- a. ~~Start-up and shutdown of the audit functions;~~
- b. ~~All auditable events for the [selection, choose one of: minimum, basic, detailed, not specified] level of audit;~~
- c. *[auditable events defined in the Auditable Events for Mandatory SFRs table (Table 2)].*

FAU_GEN.1.2/P2PVVOIP

The TSF shall record within the audit data at least the following information:

- a. Date and time of the auditable event, type of event, subject identity (if applicable), and the outcome (success or failure) of the event;
- b. For each auditable event type, based on the auditable event definitions of the functional components included in the PP, PP.Module, functional package or ST, *[information specified in column three of the Auditable Events table in which the event was defined]*.

Application Note: If the TOE claims this SFR and conforms to the App PP, the implementation-dependent SFRs FAU_STG.1 and FAU_STG.5 must also be claimed. This does not need to be claimed when the TOE conforms to the NDcPP because that PP already defines FAU_STG.1 as a mandatory requirement.

B.2 Cryptographic Support (FCS)

FCS_COP.1/SRTP Cryptographic Operation (Encryption/Decryption for SRTP)

The inclusion of this selection-based component depends upon selection in FTP_DIT_EXT.1.1, FTP_ITC.1.1/MEDIA.

FCS_COP.1.1/SRTP

The TSF shall perform *[encryption/decryption to support SDES-SRTP]* in accordance with a specified cryptographic algorithm *[AES-GCM]* and cryptographic key sizes *[256-bit]* that meet the following: *[NIST SP 800-38D]*.

Application Note: The NDcPP and App PP each define their own iteration of FCS_COP.1 for AES encryption and decryption (FCS_COP.1/DataEncryption and FCS_COP.1/SKC, respectively). The encryption and decryption used specifically for SRTP has been broken out into a separate iteration for readability purposes; the same cryptographic library that implements the AES algorithms claimed in the Base-PP requirements can be used here. Note that GCM is a supported AES mode both in this iteration and in the Base-PPs.

FCS_SRTP_EXT.1 Secure Real-Time Transport Protocol

The inclusion of this selection-based component depends upon selection in [FTP_DIT_EXT.1.1](#), [FTP_ITC.1.1/MEDIA](#).

FCS_SRTP_EXT.1.1

The ~~TSE~~ shall implement the Secure Real-Time Transport Protocol (SRTP) that complies with RFC 3711, and use Security Descriptions for Media Streams (SDS) in compliance with RFC 4568 to provide key information for the ~~SRTP~~ connection.

FCS_SRTP_EXT.1.2

The ~~TSE~~ shall implement SDS-SRTP supporting the following cipher suites: [~~AEAD_AES_256_GCM~~, in accordance with RFC 7714].

Application Note: This requirement specifies that the ~~SRTP~~ session that will be used to carry the ~~VVoIP~~ traffic will be keyed according to an SDS dialogue using the identified cipher suite.

FCS_SRTP_EXT.1.3

The ~~TSE~~ shall ensure the ~~SRTP~~ NULL algorithm can be disabled.

FCS_SRTP_EXT.1.4

The ~~TSE~~ shall allow the ~~SRTP~~ ports to be used for ~~SRTP~~ communications to be specified by an Authorized Administrator.

Application Note: This requirement specifies that the ~~SRTP~~ session that will be used to carry the VoIP traffic will be keyed according to an SDS dialog using the identified cipher suite.

B.3 User Data Protection (FDP)

FDP_IFC.1/CALLCONTROL Subset Information Flow Control (for Call Control)

The inclusion of this selection-based component depends upon selection in [FDP_IFF.1.2](#), [FMT_SMF.1.1/VVoIP](#).

FDP_IFC.1.1/CALLCONTROL

The ~~TSE~~ shall enforce the [call control policy] on [call control information transmitted by the ~~TOE~~].

FDP_IFF.1/CALLCONTROL Subset Information Flow Control (for Call Control)

The inclusion of this selection-based component depends upon selection in [FDP_IFF.1.2](#), [FMT_SMF.1.1/VVoIP](#).

FDP_IFF.1.1/CALLCONTROL

The ~~TSE~~ shall enforce the [call control policy] based on the following types of subject and information security attributes: [**assignment:** method by which the ~~TSE~~ identifies each endpoint for a call] using the following call control protocols: [**selection:** ~~SIP~~, H.323].

Application Note: The ST author should complete the assignment with an endpoint identifier (i.e. how the TSF identifies the endpoints each endpoint for a call). For example, the endpoint could be identified by an IP address, a phone number, or a username.

FDP_IFF.1.2/CALLCONTROL

The TSF shall permit an information flow between a controlled subject and controlled information via a controlled operation if the following rules hold: [*when valid communication with the TOE is attempted, the TSF will establish a connection between itself and the peer*].

Application Note: The validity of a call is determined by the protocol and the identifier of the endpoint.

FDP_IFF.1.3/CALLCONTROL

The TSF shall enforce ~~the~~ [*no additional information flow control policy rules*].

FDP_IFF.1.4/CALLCONTROL

The TSF shall explicitly authorize an information flow based on the following rules: [**assignment:** *rules based on security attributes that explicitly authorize information flows*].

FDP_IFF.1.5/CALLCONTROL

The TSF shall explicitly deny an information flow based on the following rules: [**assignment:** *rules based on security attributes that explicitly deny information flows*].

B.4 Protection of the TSF (FPT)

FPT_STM_EXT.1/VVoIP Reliable Time Stamps (VVoIP Communications)

The inclusion of this selection-based component depends upon selection in [FMT_SMF.1.1/VVoIP](#).

FPT_STM_EXT.1.1/VVoIP

The TSF shall be able to provide reliable time stamps for its own use.

FPT_STM_EXT.1.2/VVoIP

The TSF shall [*synchronize time with [**selection:** an ESC, the TOE platform]*].

Application Note: The selection made for this requirement depends on the TOE type. If the TOE is a hardware device, "an ESC" must be selected. If the TOE is a software application, "the TOE platform" must be selected. If the TOE is a software VVoIP application, [FMT_SMF.1.1/VVoIP](#) is not required as the TOE relies upon the platform for time.

Appendix C - Extended Component Definitions

This appendix contains the definitions for all extended requirements specified in the PP-Module.

C.1 Extended Components Table

All extended components specified in the PP-Module are listed in this table:

Table 10: Extended Component Definitions

Functional Class	Functional Components
Communications (FCO)	FCO_VOC_EXT Fixed-Rate Vocoder
Cryptographic Support (FCS)	FCS_SRTP_EXT Secure Real-Time Transport Protocol

C.2 Extended Component Definitions

C.2.1 Communications (FCO)


This PP-Module defines the following extended components as part of the FCO class originally defined by CC Part 2:

C.2.1.1 FCO_VOC_EXT Fixed-Rate Vocoder

Family Behavior

Components in this family define the use of vocoders in audio transmission.

Component Leveling



[FCO_VOC_EXT.1](#), Fixed-Rate Vocoder, requires the TSF to use a constant bit rate vocoder as opposed to a variable one.

Management: FCO_VOC_EXT.1

The following actions could be considered for the management functions in FMT:

- Ability to specify the vocoder used

Audit: FCO_VOC_EXT.1

There are no auditable events foreseen.

FCO_VOC_EXT.1 Fixed-Rate Vocoder

Hierarchical to: No other components.

Dependencies to: No dependencies.

FCO_VOC_EXT.1.1

The TSE shall transmit voice media using a constant bit rate voice vocoder.

C.2.2 Cryptographic Support (FCS)


This PP-Module defines the following extended components as part of the FCS class originally defined by CC Part 2:

C.2.2.1 FCS_SRTP_EXT Secure Real-Time Transport Protocol

Family Behavior

Components in this family define the implementation of the Secure Real-Time Transport Protocol (SRTP).

Component Leveling



[FCS_SRTP_EXT.1](#), Secure Real-Time Transport Protocol, requires the TSE to implement SRTP and defines conditions on its use.

Management: FCS_SRTP_EXT.1

No specific management functions are identified.

Audit: FCS_SRTP_EXT.1

There are no auditable events foreseen.

FCS_SRTP_EXT.1 Secure Real-Time Transport Protocol

Hierarchical to: No other components.

Dependencies to: FCS_COP.1 Cryptographic Operation

FCS_SRTP_EXT.1.1

The TSE shall implement the Secure Real-Time Transport Protocol (SRTP) that complies with RFC 3711, and use Security Descriptions for Media Streams (SDS) in compliance with RFC 4568 to provide key information for the SRTP connection.

FCS_SRTP_EXT.1.2

The TSE shall implement SDS-SRTP supporting the following cipher suites: [**assignment:** *list of permitted SDS-SRTP cipher suites*].

FCS_SRTP_EXT.1.3

The TSE shall ensure the SRTP NULL algorithm can be disabled.

FCS_SRTP_EXT.1.4

The TSF shall allow the SRTP ports to be used for SRTP communications to be specified by an Authorized Administrator.

Appendix D - Implicitly Satisfied Requirements

This appendix lists requirements that should be considered satisfied by products successfully evaluated against this PP-Module. These requirements are not featured explicitly as SFRs and should not be included in the ST. They are not included as standalone SFRs because it would increase the time, cost, and complexity of evaluation. This approach is permitted by [CC] Part 1, 8.3 Dependencies between components.

This information benefits systems engineering activities which call for inclusion of particular security controls. Evaluation against the PP-Module provides evidence that these controls are present and have been evaluated.

This appendix lists requirements that should be considered satisfied by products successfully evaluated against this PP-Module. However, these requirements are not featured explicitly as SFRs and should not be included in the ST. They are not included as standalone SFRs because it would increase the time, cost, and complexity of evaluation. This approach is permitted by [CC] Part 1, 8.2 Dependencies between components.

This information benefits systems engineering activities which call for inclusion of particular security controls. Evaluation against the PP-Module provides evidence that these controls are present and have been evaluated.

Requirement	Rationale for Satisfaction
FAU_GEN.2 – User identity association	The iterations of FAU_GEN.1.2 explicitly requires that the OS record any user account associated with each event; therefore, it is duplicative to include a separate requirement to associate a user account with each event. If the TOE claims conformance to the NDcPP, the dependency is explicitly met through FAU_GEN.2.
FIA_UID.1 – Timing of Identification	For the purpose of logging and processing VVoIP telephony functions, the TOE is identified solely by underlying system or configuration characteristics (e.g., IP address, phone number) independent of the identity of the user interacting with the TOE. When the TOE is a software application, neither this PP-Module nor the Base-PP (App PP) define a separate identification and authentication mechanism for the software application to interact with its management interface. The software application assumes that accessing the OS platform itself is sufficient to grant access to the application. For accountability purposes, the user of the TOE is identified as the user that logged in to the OS platform and subsequently interacted with the TSF.
FMT_MSA.1 – Management of Security Attributes	This SFR defines the TOE security attributes that can be managed and what management role can administer them. Specifically, this is indirectly dependent on FDP_IFF.1. The PP-Module defines two iterations of FDP_IFF.1. Each of these iterations define explicit rules that determine when the TSF transmits call control and media data. The relevant attributes are either directly under the control of an ordinary user, such that no specific security authorization is needed, or they are entirely under the control of the TSF and cannot be influenced by the user regardless of privilege. An example of the first case is that in FDP_IFF.1.2, whether or not the TOE is in the off-hook state or the mute state is controllable by a user with physical access to the TOE and does not require the assumption of an administrative role. An example of the second case is in FDP_IFF.1.2/CallControl, where the TSF will determine if the other end of the connection is a valid VVoIP endpoint, which is something the user has no ability to configure or influence.

FMT_MSA.3 –
Static Attribute
Initialization

This SFR is a dependency on [FDP_IFF.1](#). The PP-Module defines two iterations of [FDP_IFF.1](#). Each of these iterations define explicit rules that determine when the TSE transmits call control and media data. FMT_MSA.3 has not been specified because the default state of the attributes used to determine if data flow is authorized is not relevant to enforcement of the rules.

For example, [FDP_IFF.1.2](#) states that the TSE will not transmit media data within a call if the TOE is in the mute state. Whether the call starts with the mute state active or inactive does not affect the enforcement of the rule, and requiring the ST to state this information does not affect the security of the TSE.

FMT_SMR.1 –
Security Roles

When the TOE is a software application, neither this PP-Module nor the Base-PP (App PP.) define security roles that are authorized to perform management functionality on the TSE. For user access, the TOE does not require separate authentication to the TSE because authentication to the OS platform on which the TOE is installed is sufficient user access control; a user logged in to the OS platform is assumed to be a valid user of the TOE.

If the TOE is registered to an ESC, the ESC may be able to issue management commands to the TOE. No separate ‘user role’ is needed to define this because the ESC is not a ‘user’ and so FMT_SMR.1.2 is not applicable in this context. The ESC’s authorization to manage the TSE is implicitly granted through the user registering the TOE to the ESC.

FPT_STM.1 –
Reliable time
stamps

The iterations of FAU_GEN.1.2 explicitly requires that the software application TSE associate timestamps with audit records; therefore it is duplicative to include a separate timestamp requirement. Additionally, the App PP has an assumption of relying upon a trustworthy computing platform with a reliable time clock for its execution, so the dependency is also met through the assumption.

Alternatively, if the TOE is registered to an ESC, the selection-based requirement [FPT_STM_EXT.1/VVoIP](#) must be claimed, which is sufficient to address the dependency as the TSE will receive time data from the operational environment that is assumed to be reliable.

If the TOE claims conformance to the NDcPP, the dependency is also explicitly met through FPT_STM_EXT.1, regardless of whether the TOE is deployed in a client-server configuration (with registration to an ESC) or peer-to-peer configuration (with no ESC involved).

Appendix E - Entropy Documentation and Assessment

The ~~TOE~~ does not require any additional supplementary information to describe its entropy sources beyond the requirements outlined in the ~~Base-PPs~~. As with other ~~Base-PP~~ requirements, the only additional requirement is that the entropy documentation also applies to the specific ~~VVoIP~~ capabilities of the ~~TOE~~ that require random data, in addition to any functionality required by the claimed ~~Base-PP~~.

Appendix F - Acronyms

Table 11: Acronyms

Acronym	Meaning
Base-PP	Base Protection Profile
CC	Common Criteria
CEM	Common Evaluation Methodology
cPP	Collaborative Protection Profile
DHCP	Dynamic Host Configuration Protocol
ESC	Enterprise Session Controller
FP	Functional Package
IETF	Internet Engineering Task Force
IP	Internet Protocol
ITU-T	International Telegraph Union – Telecommunication Standardization Sector
NTP	Network Time Protocol
OE	Operational Environment
P2P	Peer-to-Peer
PP	Protection Profile
PP-Configuration	Protection Profile Configuration
PP-Module	Protection Profile Module
SAR	Security Assurance Requirement
SFR	Security Functional Requirement
SIP	Session Initiation Protocol
SRTP	Secure Real-Time Transport Protocol
ST	Security Target
TCP	Transmission Control Protocol
TFTP	Trivial File Transfer Protocol

T OE	Target of Evaluation
T SF	T OE Security Functionality
T SFI	T SF Interface
T SS	T OE Summary Specification
U DP	User Datagram Protocol
V VoIP	Voice/Video over IP

Appendix G - Bibliography

Table 12: Bibliography

Identifier	Title
[CC]	Common Criteria for Information Technology Security Evaluation - • Part 1: Introduction and general model, CCMB-2022-11-001, CC:2022, Revision 1, November 2022. • Part 2: Security functional requirements, CCMB-2022-11-002, CC:2022, Revision 1, November 2022. • Part 3: Security assurance requirements, CCMB-2022-11-003, CC:2022, Revision 1, November 2022. • Part 4: Framework for the specification of evaluation methods and activities, CCMB-2022-11-004, CC:2022, Revision 1, November 2022. • Part 5: Pre-defined packages of security requirements, CCMB-2022-11-005, CC:2022, Revision 1, November 2022.
[GEM]	Common Methodology for Information Technology Security Evaluation - • Evaluation methodology, CCMB-2022-11-006, CC:2022, Revision 1, November 2022.
[AppPP]	Protection Profile for Application Software, Version 2.0, June 16, 2025
[NDcPP]	collaborative Protection Profile for Network Devices, Version 4.0, December 22, 2025