

# SCHEMATA

---

Mariano Montone ( [marianomontone@gmail.com](mailto:marianomontone@gmail.com) )

---



## Table of Contents

<b>1</b>	<b>Introduction .....</b>	<b>1</b>
<b>2</b>	<b>Installation .....</b>	<b>2</b>
<b>3</b>	<b>Usage .....</b>	<b>3</b>
<b>4</b>	<b>Schema types .....</b>	<b>4</b>
4.1	Type schemas .....	4
4.2	Object schema .....	4
4.3	List schema .....	4
4.4	Schema references .....	4
4.5	SATISFIES-SCHEMA type .....	5
4.6	SCHEMA-CLASS metaclass .....	5
<b>5</b>	<b>Reference .....</b>	<b>7</b>
5.1	SCHEMATA package .....	7
<b>6</b>	<b>Index .....</b>	<b>11</b>

# 1 Introduction

Generic purpose schema library for serialization and validation of data.

This library is used by CL-REST-SERVER for API serialization and validation.

It features:

- Validation using schemas.
- Serialization and unserialization using schemas.
- Integration with Common Lisp type system.
- A schema class metaclass.

## 2 Installation

With Quicklisp:

```
(ql:quickload "schemata")
```

### 3 Usage

Use [DEFINE-SCHEMA], page 7 for defining schemas.

Schema example:

```
(schemata:define-schema customer
  (object "customer"
    ((id string :external-name "id" :accessor
        customer-id :documentation "customer id")
      (number string :external-name "number" :required nil
        :accessor customer-nr :documentation
          "customer number")
      (name string :external-name "name" :accessor
        customer-name :documentation "customer name")
      (address-1 string :external-name "address1"
        :required nil :documentation
          "customer first address")
      (address-2 string :external-name "address2"
        :required nil :documentation
          "customer second address")
      (postal-code string :external-name "postalcode"
        :required nil :documentation
          "postal code")
      (postal-area string :external-name "postalarea"
        :required nil :documentation
          "postal area")
      (country string :external-name "country" :required nil
        :documentation "country code")
      (phone string :external-name "phone" :required nil
        :documentation "phone")
      (fax string :external-name "fax" :required nil
        :documentation "fax")
      (email string :external-name "email" :required nil
        :documentation "email"))
    (:documentation "customer data fetched")))
```

## 4 Schema types

### 4.1 Type schemas

Schemas can be built from Common Lisp types:

```
SCHEMATA> (defparameter *s* (schema string))
*S*
SCHEMATA> *s*
#<TYPE-SCHEMA STRING {1006FBBD13}>
SCHEMATA> (validate-with-schema *s* "22")
NIL
SCHEMATA> (validate-with-schema *s* 22 :error-p nil)
#<VALIDATION-ERROR "~s is not of type: ~a" {100152EB13}>
```

### 4.2 Object schema

Object schemas are built using the syntax: (object name attributes options). Attributes are specified as: (attribute-name attribute-type &rest options).

The `attribute-type` is parsed as a schema.

Possible attribute options are: ‘required’, ‘required-message’, ‘default’, ‘accessor’, ‘writer’, ‘reader’, ‘parser’, ‘validator’, ‘add-validator’, ‘formatter’, ‘external-name’, ‘serializer’, ‘unserializer’, ‘slot’.

Example:

```
SCHEMATA> (schema (object person
                    ((name string)
                     (age integer :required nil))))
#<OBJECT-SCHEMA {1001843543}>
```

### 4.3 List schema

Homogeneous list of schemas are specified via `list-of`.

Example:

```
SCHEMATA> (defparameter *s* (schema (list-of integer)))
*S*
SCHEMATA> (validate-with-schema *s* '(1 2 "foo"))
; Evaluation aborted on #<SCHEMATA:VALIDATION-ERROR "~s is not of type: ~a" {1006ECA323}>.
SCHEMATA> (validate-with-schema *s* '(1 2 3))
NIL
```

### 4.4 Schema references

Defined schemas can be referenced via either ‘(schema schema-name)’ or ‘(ref schema-name)’ (they are identical).

Example:

```
SCHEMATA> (define-schema person
```

```

      (object person
        ((name string))))
#<OBJECT-SCHEMA {1006F8A813}>
SCHEMATA> (defparameter *list-of-person* (schema (list-of (ref person))))
*LIST-OF-PERSON*
SCHEMATA> *list-of-person*
#<LIST-SCHEMA {1006F8C2A3}>
SCHEMATA> (parse-with-schema *list-of-person* '(((("name" . "Mariano")) ((("name" . "Peter"))
(((NAME . "Mariano")) ((NAME . "Peter"))))
SCHEMATA> (validate-with-schema *list-of-person* '(((("name" . 22)) ((("name" . "Peter")))))
; processing (DEFMETHOD SCHEMA-VALIDATE ...); Evaluation aborted on #<SB-PCL::NO-APPLICABLE
SCHEMATA> (validate-with-schema *list-of-person* '(((("name" . 22)) ((("name" . "Peter")))))
; Evaluation aborted on #<SCHEMATA:VALIDATION-ERROR "~s is not of type: ~a" {10082EB883}>..
SCHEMATA> (validate-with-schema *list-of-person* '(((("name" . "Mariano")) ((("name" . "Peter
NIL
SCHEMATA> (validate-with-schema *list-of-person* '(((("names" . "Mariano")) ((("name" . "Pete
; Evaluation aborted on #<SCHEMATA:VALIDATION-ERROR "Attributes not part of schema: ~a" {10

```

## 4.5 SATISFIES-SCHEMA type

Schemata integrates with the Lisp type system via the SATISFIES-SCHEMA type. Schemas can be thought as types over data. Defined schemas can be checked using TYPEP and CHECK-TYPE with the type '(satisfies-schema schema-name)'.

Example:

```

SCHEMATA> (define-schema string-schema string)
#<TYPE-SCHEMA STRING {10019DA8B3}>
SCHEMATA> (typep "foo" '(satisfies-schema string-schema))
T
SCHEMATA> (typep 22 '(satisfies-schema string-schema))
NIL
SCHEMATA> (let ((x "foo"))
  (check-type x (satisfies-schema string-schema))
  x)
"foo"

```

## 4.6 SCHEMA-CLASS metaclass

SCHEMA-CLASS classes get an schema attached.

Example:

```

SCHEMATA> (define-schema-class person ()
  ((name :type string :initarg :name)
   (age :type integer :required nil :initarg :age)))
#<SCHEMA-CLASS SCHEMATA::PERSON>

SCHEMATA> (validate-with-schema (find-class 'person) '(((("name" . "Mariano") ("age" . 22))))
NIL

```



```
SCHEMATA> (validate-with-schema (find-class 'person) '(("name" . "Mariano") ("age" . 'asdf))  
#<VALIDATION-ERROR 'ASDF is not of type: INTEGER {100109F833}>
```

```
SCHEMATA> (generic-serializer:with-serializer :json  
            (generic-serializer:serialize (make-instance 'person :name "Mariano" :age 44)))  
{"name":"Mariano","age":44}
```

## 5 Reference

### 5.1 SCHEMATA package

SCHEMATA [PACKAGE]

#### External definitions

##### Macros

SCHEMATA:SCHEMA (*schema-def*) [Macro]  
 Wrapper macro for schema definitions.

SCHEMATA:DEFINE-SCHEMA (*name schema*) [Macro]  
 Register SCHEMA under NAME. The schema can then be accessed via  
 FIND-SCHEMA.

##### Generic functions

SCHEMATA:PARSE-WITH-SCHEMA (*schema string-or-data*) [Generic-Function]  
 Parses the string to an association list using the schema

SCHEMATA:ATTRIBUTE-NAME (*sb-pcl::object*) [Generic-Function]

SCHEMATA:UNSERIALIZE-WITH-SCHEMA (*schema data format*) [Generic-Function]

SCHEMATA:SCHEMA-DOCUMENTATION (*sb-pcl::object*) [Generic-Function]

SCHEMATA:OBJECT-CLASS (*sb-pcl::object*) [Generic-Function]

SCHEMATA:ATTRIBUTE-PARSER (*sb-pcl::object*) [Generic-Function]

SCHEMATA:ATTRIBUTE-VALIDATOR (*sb-pcl::object*) [Generic-Function]

SCHEMATA:ATTRIBUTE-ADD-VALIDATOR (*sb-pcl::object*) [Generic-Function]

SCHEMATA:ATTRIBUTE-EXTERNAL-NAME (*sb-pcl::object*) [Generic-Function]

SCHEMATA:SCHEMA-TYPE (*sb-pcl::object*) [Generic-Function]

SCHEMATA:ATTRIBUTE-FORMATTER (*sb-pcl::object*) [Generic-Function]

SCHEMATA:OBJECT-NAME (*sb-pcl::object*) [Generic-Function]

SCHEMATA:OBJECT-ATTRIBUTES (*sb-pcl::object*) [Generic-Function]

SCHEMATA:ATTRIBUTE-ACCESSOR (*sb-pcl::object*) [Generic-Function]

SCHEMATA:ATTRIBUTE-TYPE (*sb-pcl::object*) [Generic-Function]

## Functions

**SCHEMATA:ATTRIBUTE-READER** (*attribute*) [Function]

**SCHEMATA:POPULATE-WITH-SCHEMA** (*schema object data &key exclude*) [Function]

Populate CLOS objects from data + schema. Attributes members of EXCLUDE parameter are not populated.

**SCHEMATA:SCHEMA-CLASS-SCHEMA** (*schema-class*) [Function]

Generate a schema using the schema class meta info

**SCHEMATA:SERIALIZE-WITH-SCHEMA** (*schema input &optional (serializer generic-serializer::\*serializer\*) (stream generic-serializer::\*serializer-output\*)*) [Function]

**SCHEMATA:SCHEMA-SPEC** (*schema*) [Function]

**SCHEMATA:ATTRIBUTE-TYPE-NAME** (*attribute*) [Function]

**SCHEMATA:VALIDATION-ERROR** (*message &rest args*) [Function]

**SCHEMATA:VALIDATE-WITH-SCHEMA** (*schema data &key (collect-errors \*collect-validation-errors\*) (error-p \*signal-validation-errors\*)*) [Function]

Validate input using schema. Useful for validating resource operations posted content (for :post and :put methods). Input can be a string or an association list.

Args: - schema (symbol or schema): The schema - data (alist): The data to validate. - format (keyword): The data format. - collect-errors (boolean): If true, collect all the validation errors. If false, return the first validation error found. Default: true. - error-p (boolean): If true, when validation errors are found, a validation error is signaled. If false, the validation errors are returned as the function result and no error is signaled.

**SCHEMATA:ATTRIBUTE-OPTIONAL-P** (*attribute*) [Function]

**SCHEMATA:ATTRIBUTE-WRITER** (*attribute*) [Function]

**SCHEMATA:FIND-OBJECT-ATTRIBUTE** (*object attribute-name &key (error-p t)*) [Function]

**SCHEMATA:FIND-SCHEMA** (*name &optional (errorp t)*) [Function]

Find a schema definition by name

**SCHEMATA:PATCH-WITH-SCHEMA** (*schema object data*) [Function]

Populate CLOS objects from data + schema. Only populates attributes available in DATA, validating them. Useful for PATCH rest api operations implementations. DATA should be an association list.

## Classes

**SCHEMATA:OBJECT-SCHEMA** [Class]

Class precedence list: `object-schema`, `schema`, `standard-object`, `t`

Slots:

- **name** — type: (or string symbol); initarg: :name; reader: schemata:object-name; writer: (setf schemata:object-name)  
The name of the object.
- **attributes** — type: list; initarg: :attributes; reader: schemata:object-attributes; writer: (setf schemata:object-attributes)
- **class** — type: (or null symbol); initarg: :class; reader: schemata:object-class; writer: (setf schemata:object-class)
- **ignore-unknown-attributes** — type: boolean; initarg: :ignore-unknown-attributes; reader: schemata::ignore-unknown-attributes; writer: (setf schemata::ignore-unknown-attributes)
- **serializer** — type: (or null trivial-types:function-designator); initarg: :serializer; reader: schemata::object-serializer; writer: (setf schemata::object-serializer)
- **unserializer** — type: (or null trivial-types:function-designator); initarg: :unserializer; reader: schemata::object-unserializer; writer: (setf schemata::object-unserializer)

**SCHEMATA:SCHEMA-REFERENCE-SCHEMA** [Class]

Class precedence list: schema-reference-schema, schema, standard-object, t

Slots:

- **name** — type: symbol; initarg: :schema-name; reader: schemata::schema-name; writer: (setf schemata::schema-name)

**SCHEMATA:SCHEMA** [Class]

Class precedence list: schema, standard-object, t

Slots:

- **documentation** — type: t; initarg: :documentation; reader: schemata:schema-documentation; writer: (setf schemata:schema-documentation)

**SCHEMATA:VALIDATION-ERROR** [Class]

Class precedence list: validation-error, error, serious-condition, condition, t

**SCHEMATA:ATTRIBUTE** [Class]

Class precedence list: attribute, schema, attribute-properties, standard-object, t

Slots:

- **name** — type: symbol; initarg: :name; reader: schemata:attribute-name; writer: (setf schemata:attribute-name)
- **type** — type: schemata:schema; initarg: :type; reader: schemata:attribute-type; writer: (setf schemata:attribute-type)
- **accessor** — type: (or null symbol); initarg: :accessor; reader: schemata:attribute-accessor; writer: (setf schemata:attribute-accessor)
- **writer** — type: (or null trivial-types:function-designator); initarg: :writer

- `reader` — type: (or null trivial-types:function-designator); initarg: `:reader`
- `slot` — type: (or null symbol); initarg: `:slot`; reader: `schemata::attribute-slot`; writer: `(setf schemata::attribute-slot)`

**SCHEMATA:TYPE-SCHEMA** [Class]

Class precedence list: `type-schema`, `schema`, `standard-object`, `t`

Slots:

- `type` — type: `t`; initarg: `:type`; reader: `schemata:schema-type`; writer: `(setf schemata:schema-type)`

**SCHEMATA:SCHEMA-OBJECT** [Class]

Class precedence list: `schema-object`, `standard-object`, `t`

**SCHEMATA:SCHEMA-CLASS** [Class]

Metaclass for schema objects

Class precedence list: `schema-class`, `standard-class`, `class`, `specializer`, `metaobject`, `standard-object`, `t`

Slots:

- `schema-name` — type: (or null string symbol); initarg: `:schema-name`; reader: `schemata::schema-name`; writer: `(setf schemata::schema-name)`

## 6 Index

(Index is nonexistent)

### \*

*BASE64-ENCODE*	4
SCHEMATA:ATTRIBUTE-ACCESSOR	7
SCHEMATA:ATTRIBUTE-ADD-VALIDATOR	7
SCHEMATA:ATTRIBUTE-EXTERNAL-NAME	7
SCHEMATA:ATTRIBUTE-FORMATTER	7
SCHEMATA:ATTRIBUTE-NAME	7
SCHEMATA:ATTRIBUTE-OPTIONAL-P	8
SCHEMATA:ATTRIBUTE-PARSER	7
SCHEMATA:ATTRIBUTE-READER	8
SCHEMATA:ATTRIBUTE-TYPE	7
SCHEMATA:ATTRIBUTE-TYPE-NAME	8
SCHEMATA:ATTRIBUTE-VALIDATOR	7
SCHEMATA:ATTRIBUTE-WRITER	8
SCHEMATA:DEFINE-SCHEMA	7
SCHEMATA:FIND-OBJECT-ATTRIBUTE	8
SCHEMATA:FIND-SCHEMA	8

### S

SCHEMATA:*BASE64-ENCODE*	4
SCHEMATA:OBJECT-ATTRIBUTES	7
SCHEMATA:OBJECT-CLASS	7
SCHEMATA:OBJECT-NAME	7
SCHEMATA:PARSE-WITH-SCHEMA	7
SCHEMATA:PATCH-WITH-SCHEMA	8
SCHEMATA:POPULATE-WITH-SCHEMA	8
SCHEMATA:SCHEMA	7
SCHEMATA:SCHEMA-CLASS-SCHEMA	8
SCHEMATA:SCHEMA-DOCUMENTATION	7
SCHEMATA:SCHEMA-SPEC	8
SCHEMATA:SCHEMA-TYPE	7
SCHEMATA:SERIALIZE-WITH-SCHEMA	8
SCHEMATA:UNSERIALIZE-WITH-SCHEMA	7
SCHEMATA:VALIDATE-WITH-SCHEMA	8
SCHEMATA:VALIDATION-ERROR	8