

- Input
- addChild()
 - getAttributeCount()
 - getChild()
 - getChildren()
 - getContent()
 - getName()
 - getNum()
 - getParent()
 - getString()
 - hasAttribute()
 - hasChildren()
 - listAttributes()
 - listChildren()
 - removeChild()
 - serialize()
 - setAttribute()
 - setContent()
 - setName()
 - httpDo()

Reference > getContent()

getContent()

Returns the element's content as a `String`.

The parameter, `defaultValue`, is optional. If a string is passed, as in `myXML.getContent(' ??? ')`, it will be returned if the element has no content.

Examples



```
let myXML;

// Load the XML and create a p5.XML object.
function preload() {
  myXML = loadXML('/assets/animals.xml');
}

function setup() {
  createCanvas(100, 100);

  background(200);

  // Get the first reptile child element.
  let reptile = myXML.getChild('reptile');

  // Get the reptile's content.
  let content = reptile.getContent();

  // Style the text.
  textAlign(CENTER, CENTER);
  textFont('Courier New');
  textSize(14);

  // Display the element's content.
  text(content, 5, 50, 90);

  describe(`The text "${content}" written in green on a gray background.`);
}
```



```
function setup() {
  createCanvas(100, 100);

  background(200);

  // Create a p5.XML object.
  let blankSpace = new p5.XML();

  // Get the element's content and use a default value.
  let content = blankSpace.getContent('Your name');

  // Style the text.
  textAlign(CENTER, CENTER);
  textFont('Courier New');
  textSize(14);

  // Display the element's content.
  text(content, 5, 50, 90);

  describe(`The text "${content}" written in green on a gray background.`);
}
```

Syntax

```
getContent([defaultValue])
```

Parameters

`defaultValue` String: value to return if the element has no content.

Returns

String: element's content as a string.

This page is generated from the comments in [src/io/p5.XML.js](#). Please feel free to edit it and submit a pull request!

Related References

addChild Adds a new child element and returns a reference to it.	getAttributeCount Returns the number of attributes the element has.	getChild Returns the first matching child element as a new p5.XML object.	getChildren Returns an array with the element's child elements as new p5.XML objects.
--	---	---	---

p5.js

Resources

Information

Socials

- Reference
- Tutorials
- Examples
- Contribute
- Community
- About
- Start Coding
- Donate

- Download
- Contact
- Copyright
- Privacy Policy
- Terms of Use

- GitHub ↗
- Instagram ↗
- X ↗
- YouTube ↗
- Discord ↗
- Forum ↗

