

get()

Retrieves a value from the TableRow's specified column. The column may be specified by either its ID or title.

Examples

```
// Given the CSV file "mammals.csv" in the project's "assets" folder:
//
// id,species,name
// 0,Capra hircus,Goat
// 1,Panthera pardus,Leopard
// 2,Equus zebra,Zebra

let table;

function preload() {
  //my table is comma separated value "csv"
  //and has a header specifying the columns labels
  table = loadTable('/assets/mammals.csv', 'csv', 'header');
}

function setup() {
  let names = [];
  let rows = table.getRows();
  for (let r = 0; r < rows.length; r++) {
    names.push(rows[r].get('name'));
  }

  print(names);

  describe('no image displayed');
}
```

Syntax

```
get(column)
```

Parameters

column String|Integer: columnName (string) or ID (number)

Returns

String|Number:

This page is generated from the comments in [src/io/p5.TableRow.js](#) . Please feel free to edit it and submit a pull request!

Related References

addColumn

Use addColumn() to add a new column to a Table object.

addRow

Use addRow() to add a new row of data to a p5.Table object.

clearRows

Removes all rows from a Table.

columns

An array containing the names of the columns in the table, if the "header" the table is loaded with the "header" parameter.

p5.js

Reference
Tutorials
Examples
Contribute
Community
About
Start Coding
Donate

Resources

Reference
Tutorials
Examples
Contribute
Community
About
Start Coding
Donate

Information

Download
Contact
Copyright
Privacy Policy
Terms of Use

Socials

GitHub ↗
Instagram ↗
X ↗
YouTube ↗
Discord ↗
Forum ↗

