

setString()

Stores a String value in the TableRow's specified column. The column may be specified by either its ID or title.

Examples

// Given the CSV file "mammals.csv" in the project's "assets" folder:
//
// id,species,name
// 0,Capra hircus,Goat
// 1,Panthera pardus,Leopard
// 2,Equus zebra,Zebra

let table;

function preload() {
 //my table is comma separated value "csv"
 //and has a header specifying the columns labels
 table = loadTable('/assets/mammals.csv', 'csv', 'header');
}

function setup() {
 let rows = table.getRows();
 for (let r = 0; r < rows.length; r++) {
 let name = rows[r].getString('name');
 rows[r].setString('name', 'A ' + name + ' named George');
 }

 print(table.getArray());

 describe('no image displayed');
}

Syntax

setString(column, value)

Parameters

column	String Integer: Column ID (Number) or Title (String)
value	String Number Boolean Object: The value to be stored as a String

This page is generated from the comments in [src/io/p5.TableRow.js](#) . Please feel free to edit it and submit a pull request!

Related References

<div>addColumn</div> <div>Use addColumn() to add a new column to a Table object.</div>	<div>addRow</div> <div>Use addRow() to add a new row of data to a p5.Table object.</div>	<div>clearRows</div> <div>Removes all rows from a Table.</div>	<div>columns</div> <div>An array containing the names of the columns in the table, if the "header" the table is loaded with the "header" parameter.</div>
--	--	--	---

