

textStyle()

Sets the style for system fonts when `text()` is called.

The parameter, `style`, can be either `NORMAL`, `ITALIC`, `BOLD`, or `BOLDITALIC`.

`textStyle()` may be overridden by CSS styling. This function doesn't affect fonts loaded with `loadFont()`.

Examples

Normal

Italic

Bold

Bold Italic

▶

■

```
function setup() {
  createCanvas(100, 100);

  background(200);

  // Style the text.
  textSize(12);
  textAlign(CENTER);

  // First row.
  textStyle(NORMAL);
  text('Normal', 50, 15);

  // Second row.
  textStyle(ITALIC);
  text('Italic', 50, 40);

  // Third row.
  textStyle(BOLD);
  text('Bold', 50, 65);

  // Fourth row.
  textStyle(BOLDITALIC);
  text('Bold Italic', 50, 90);

  describe('The words "Normal" displayed normally, "Italic" in italic, "Bold" in bold, and "Bold Italic" in bold italics.');
```

Syntax

textStyle(style)

textStyle()

Parameters

style	Constant: styling for text, either NORMAL, ITALIC, BOLD or BOLDITALIC.
-------	------------------------------------------------------------------------

This page is generated from the comments in [src/typography/attributes.js](#) . Please feel free to edit it and submit a pull request!

Related References

ellipseMode

Changes where ellipses, circles, and arcs are drawn.

noSmooth

Draws certain features with jagged (aliased) edges.

rectMode

Changes where rectangles and squares are drawn.

smooth

Draws certain features with smooth (antialiased) edges.

