

dragLeave()

Calls a function when a file is dragged off the element.

Calling `myElement.dragLeave(false)` disables the function.

Examples

▶
■

□
⟳

```
// Drag a file over, then off
// the canvas to test.

function setup() {
  // Create a canvas element and
  // assign it to cnv.
  let cnv = createCanvas(100, 100);

  background(200);

  // Call byeFile() when a
  // file is dragged over,
  // then off the canvas.
  cnv.dragLeave(byeFile);

  describe('A gray square. The text "bye, file" appears when a
  file is dragged over, then off the square.');
}

function byeFile() {
  text('bye, file', 50, 50);
}
```

Syntax

`dragLeave(fxn)`



Parameters

`fxn` Function|Boolean: function to call when the file is dragged off the element. `false` disables the function.

This page is generated from the comments in [src/core/p5.Element.js](#). Please feel free to edit it and submit a pull request!

Related References

addClass

Adds a class to the element.

attribute

Adds an attribute to the element.

center

Centers the element either vertically, horizontally, or both.

child

Attaches the element as a child of another element.

p5.js

Resources

[Reference](#)
[Tutorials](#)
[Examples](#)
[Contribute](#)
[Community](#)
[About](#)
[Start Coding](#)
[Donate](#)

Information

[Download](#)
[Contact](#)
[Copyright](#)
[Privacy Policy](#)
[Terms of Use](#)

Socials

[GitHub](#) ↗
[Instagram](#) ↗
[X](#) ↗
[YouTube](#) ↗
[Discord](#) ↗
[Forum](#) ↗

