p5*js

Reference
Tutorials
Examples
Contribute
Community
About

(</> Start Coding)

(♡ Donate)

Reference > sub()

sub()

Subtract the given number from the value currently stored at the given key. The difference then replaces the value previously stored in the Dictionary.

Examples

```
function setup() {
  let myDictionary = createNumberDict(2, 5);
  myDictionary.sub(2, 2);
  print(myDictionary.get(2)); // logs 3 to console.
}
```

Syntax

```
sub(Key, Number)
```

Parameters

Key   Number: for the value you wish to subtract from
Number   Number: to subtract from the value

This page is generated from the comments in src/data/p5.TypedDict.js . Please feel free to edit it and submit a pull request!

Related References

add
Add the given number to the value currently stored at the given key.

div
Divide the given number with the value currently stored at the given key.

maxKey
Return the highest key currently used in the Dictionary.

maxValue
Return the highest number currently stored in the Dictionary.

p5.js

Resources
Reference
Tutorials
Examples
Contribute
Community
About
Start Coding
Donate

Information
Download
Contact
Copyright
Privacy Policy
Terms of Use

Socials
GitHub ↗
Instagram ↗
X ↗
YouTube ↗
Discord ↗
Forum ↗

Donate Today! Support p5.js and the Processing Foundation.   ✕