

rotateZ()

Rotates the coordinate system about the z-axis in WebGL mode.

The parameter, `angle`, is the amount to rotate. For example, calling `rotateZ(1)` rotates the coordinate system about the z-axis by 1 radian. `rotateZ()` interprets angle values using the current `angleMode()`.

By default, transformations accumulate. For example, calling `rotateZ(1)` twice has the same effect as calling `rotateZ(2)` once. The `push()` and `pop()` functions can be used to isolate transformations within distinct drawing groups.

Note: Transformations are reset at the beginning of the draw loop. Calling `rotateZ(1)` inside the `draw()` function won't cause shapes to spin.

Examples



// Click and drag the mouse to view the scene from different angles.

```
function setup() {
  createCanvas(100, 100, WEBGL);

  describe('A white cube on a gray background.');
}

function draw() {
  background(200);

  // Enable orbiting with the mouse.
  orbitControl();

  // Rotate the coordinate system 1/8 turn.
  rotateZ(QUARTER_PI);

  // Draw a box.
  box();
}
```

// Click and drag the mouse to view the scene from different angles.

```
function setup() {
  createCanvas(100, 100, WEBGL);

  describe('A white cube on a gray background.');
}

function draw() {
  background(200);

  // Enable orbiting with the mouse.
  orbitControl();

  // Rotate the coordinate system 1/16 turn.
  rotateZ(QUARTER_PI / 2);

  // Rotate the coordinate system 1/16 turn.
  rotateZ(QUARTER_PI / 2);

  // Draw a box.
  box();
}
```

// Click and drag the mouse to view the scene from different angles.

```
function setup() {
  createCanvas(100, 100, WEBGL);

  // Use degrees.
  angleMode(DEGREES);

  describe('A white cube on a gray background.');
}

function draw() {
  background(200);

  // Enable orbiting with the mouse.
  orbitControl();

  // Rotate the coordinate system 1/8 turn.
  rotateZ(45);

  // Draw a box.
  box();
}
```

// Click and drag the mouse to view the scene from different angles.

```
function setup() {
  createCanvas(100, 100, WEBGL);

  describe('A white cube rotates slowly against a gray background.');
}

function draw() {
  background(200);


  // Enable orbiting with the mouse.
  orbitControl();

  // Rotate the coordinate system a little more each frame.
  let angle = frameCount * 0.01;
  rotateZ(angle);

  // Draw a box.
  box();
}
```

Syntax

```
rotateZ(angle)
```



Parameters

`angle` Number: angle of rotation in the current `angleMode()`.

This page is generated from the comments in [src/core/transform.js](#). Please feel free to edit it and submit a pull request!


Related References

[applyMatrix](#) Applies a transformation matrix to the coordinate system.

[resetMatrix](#) Clears all transformations applied to the coordinate system.

[rotate](#) Rotates the coordinate system.

[rotateX](#) Rotates the coordinate system about the x-axis in WebGL mode.



Resources

[Reference](#)

[Tutorials](#)

[Examples](#)

[Contribute](#)

[Community](#)

[About](#)

[Start Coding](#)

[Donate](#)

Information

[Download](#)

[Contact](#)

[Privacy Policy](#)

[Terms of Use](#)

Socials

[GitHub](#) ↗

[Instagram](#) ↗

[X](#) ↗

[YouTube](#) ↗

[Discord](#) ↗

[Forum](#) ↗

Donate Today! Support p5.js and the Processing Foundation.

